Prompty generativní inteligenci využité k tvorbě aplikace Větná Dráha

Při úpravách kódu byl využit inline copilot a inline Cursor, který je schopen měnit části kódu bez vyzvání / promptu.

ahoj, chcio vyvijet vzdelavaci aplikaci za skolu a chci ji distribuovat do app store a google play, musim neco platit?

ahoj, budu delat hru / ucici aplikaci pro zaky okolo 6. tridy zs na trenovani vetnych clenu... chci aby to melo vesmirne tema. jak by se takovato hra mohla jmenovat? dalsi zkus prosim (jméno větná dráha stejně tento prompt nevymyslel)

kočka mňouká u stolu, rozlož to na větné členy

je dobry napad pouzit v expu/nativu classy (myslim tim JS class, ne HTML atribut)?

jasn, ted kdyz se kouknes na ten kod na CSV download a parci s temy daty, mam pouzit classu nebo funkce?

jasne, kam bych tuto logiku mel umistit v expu?

super, napis to prosim v typescriptu

budu pouzivat hook, zjednodus mi jak funguje ten kod cos napsa

dobre, ale prijde mi zbytecny davat CSVURL jako parametr, zdrojova adresa bude vzdy stejna

je v expu neco jako .env? ze bych to dal tam?

ahoj, budu delat aplikaci na urcovani vetnych clenu, jake minihry bych mohl udelat (aby byly vhodne pro sestaky)?

ahoj, delam hru na vetne cleny pro sestaky zs s tematem vesmiru - hrac si muze upravovat raketu a pak s ni cestuje po planetach, na kterych jsou cviceni na vetne cleny. mame vic druhu cviceni, hadani vsech vetnych clenu, pouze přívlastky, podmět/přísudek, příslovečná určení, doplňek. premyslim jak spracovat "herni mapu". napada te neco? zaprave planety generujeme generatorem - tudiz to nemuze byt znama soustava (navic jich bude vice). a chceme aby se hrac dostaval na ruzne planety, ne ze jeden ty ulohy (PK,PO/PŘ,PÚ,D) je jen jedna planeta

me jde o to, aby mel hrac porad sanci na vyber, ktery typ cviceni bude hrat, nehlede na to jak moc prozkoumal uz vesmir. ale chci taky aby se obtiznost postupne zvetsovala ale aby to bylo jednoduche na vizualizaci na mobilu.

libi se mi prvni napad, ale neslo by to planety spis spojit do slunecnich soustav?

muzes mi navrhnout jak to bude vypada v aplkaci? potrebuju aby se hrac mohl jednoduse dostat ke cviceni (dobry UX)

prijde mi to prekomplikovany - hrac ma vicemene na vyber jen kterou ulohu hrat, je zbytecny mu davat na vyber mnoho planet. navic pokud chce hrat jen jeden typ ulohy tak by to meo jit

ahoj, muzes mi vyplnit json ve tomto formatu: { "vsechny_cleny": [], "hlavni_cleny": [], "privlastky:": [], "prislovecna_urceni": [], "doplnky": [] } se jmeny planet, kazda kategorie ma 25 planet, vsechny_cleny maji 50, posledni planeta je cerna dira

super, ale pouzij jen fiktivni jmena planet. Pojmenuj i tu cernou diru nejak jinak nez cerna dira

vygeneruj mi 50 nazvu pro fiktivni planety. chci aby zneli trochu vedecky, ale ne moc. kazda 10. planeta bude hvezda, zkus je pojmenovat nejak zajimave. je to do hry o vetvych clenech (cestina), muzes pojmenovat par planet trochu tematicky, zkus tam obcas treba pridat cislovku aby to znelo vic scieftificky

hi, i dont udestand much expo router and i need help i want a few tabs - index, exams, tutorial, arenaplanet also a few other page - exams/create, exams/join, exams/practice, profile, games/game1, games/game2... i want the tabs to show down and also to be able to go to the other pages, which should not be tabs

ahoj, jak muzu vytvorit apple developer ucet pro vzdelavaci instituci abych se mohl vyhnout platbe (fee waiver), kdyz mi není 18?

ahoj, prave jsem upgradnul expo sdk na 53 a prestalo to nejak fungovat s temito chybami: ERROR TypeError: 0, _reactUtils.componentWithRef is not a function (it is undefined), js engine: hermes WARN Route "./_layout.tsx" is missing the required default export. Ensure a React component is exported as default. WARN [Layout children]: No route named "exams" exists in nested children: ["arenagalaxies", "arenaplanet", "index", "profile", "tutorial", "(debug)/gameTests"] WARN [Layout children]: No route named "exams" exists in nested children: ["arenagalaxies", "arenaplanet", "index", "profile", "tutorial", "(debug)/gameTests"] ktere to predtim nehazelo, co mam delat?

Wheres the bun global bin folder location

Ahoj, vytvoril jsem expo build pomoci eas a potrebuji ho dostat na svuj iphone. nemam placeny dev ucet ani mac

ahoj, delam aplikaci v expo podobnou duolingu a kahoot chci abych mohl jednoduse nasdilet kod hry, idealne pomoci odkazu. jak mam zajistit ze se otevre moje aplikace?

ahoj, píšu dokumentaci k ročníkové práce a už jsem napsal takto úvod: Úvod Ve světě zábavy, počítačů, tabletů a mobilů bývá těžké zaujmout pozornost mladistvých a něco je naučit. Proto vytvoříme jedinečnou mobilní aplikaci pro výuku větných členů, která se snaží svým designem a gamifikací zaujmout žáky i učitele na základních školách. Cílem této práce je vytvořit mobilní aplikaci, která bude stažitelná z Apple App Store a spustitelná na mobilním telefonu iPhone a tabletu iPad. Pro vývoj aplikace byly vybrány frameworky React, React Native a Expo, postavené na programovacích jazycích JavaScript a TypeScript. Tak bude pak nutné vytvořit účet Apple Developer pro vzdělávací instituci, který umožní bezplatné nasazení aplikace na App Store. Dalším cílem je taká vytvoření REST API, z kterého bude aplikace získávat sady vět s označenými větnými členy, které se pak používají k vytváření cvičení. API také zajišťuje výměnu dat mezi žáky a učitelem. Učitel může vytvořit test, s kterým se vygeneruje herní kód, který pak lze nesdílet se studenty a vidět jejich úspěšnost v testech. API využívá JavaScript a TypeScript pro sdílení části logiky s aplikací, Express.js pro tvorbu samotného webového serveru, Prisma ORM pro práci s databází SQLite a další nástroje pro zpracování dat. napises mi jak by mohla byt prace dal rozlozena na kapitoly?

Zabyva se onlinecviceni.cz vetnymi cleny?

ahoj, delam v coolify (nixpacks) a chci deploynout bun+express+primsa+sqlite aplikaci. co musim nastavit?

17 | 18 | We suggest to move the contents of ${Y(l)} to ${Y(a)} to consolidate your env vars. 19 | ;throw new Error(u)}else if(t=="warn"){let u=Conflict for env var${s.length>1?"s":""} ${s.map(c=>W(c)).join(", ")} in ${Y(a)} and ${Y(l)} 20 | Env vars from ${Y(l)} overwrite the ones from ${Y(a)} 21 | ;console.warn(${ke("warn(prisma)")} ${u})}}}}function _s(e){if(hp(e)){Li(Environment variables loaded from ${e});let r=Fi.default.config({path:e,debug:process.env.DOTENV_CONFIG_DEBUG?!0:void 0});return{dotenvResult:Ds(r),message:Ie(Environment variables loaded from ${wr.default.relative(process.cwd(),e)}),path:e}}else Li(Environment variables not found at ${e});return null}function Ns(e,r){return e&&r&&wr.default.resolve(e)===wr.default.resolve(r)}function hp(e){return!!(e&&nn.default.existsSync(e))}function Mi(e,r){return Object.prototype.hasOwnProperty.call(e,r)}function xr(e,r){let t={};for(let n of Object.keys(e))t[n]=r(e[n],n);return t}function $i(e,r){if(e.length===0)return;let t=e[0];for(let n=1;n<e.length;n++)r(t,e[n])<0&&(t=e[n]);return t}function x(e,r){Object.defineProperty(e,"name",{value:r,configurable:!0})}var Fs=new Set,ot=(e,r,...t)=>{Fs.has(e)||(Fs.add(e),Ii(r,...t))};var T=class e extends Error{clientVersion;errorCode;retryable;constructor(r,t,n){super(r),this.name="PrismaClie PrismaClientInitializationError: Unable to require(/app/node_modules/.prisma/client/libquery_engine-debian-openssl-3.0.x.so.node). Prisma cannot find the required libssl system library in your system. Please install openssl-3.0.x and try again. Details: libssl.so.3: cannot open shared object file: No such file or directory clientVersion: "6.6.0", errorCode: undefined, retryable: undefined, at new PrismaClientInitializationError (/app/node_modules/@prisma/client/runtime/library.js:21:995) at <anonymous> (/app/node_modules/@prisma/client/runtime/library.js:111:10794)

napiš mi regex který najde toto: malé písmeno, "_" a velký písmeno

Ahoj, navrhnes mi rozdelelni pate kapitoly k teto rocnikove praci?

```
// Calculate difficulty of a row based on word types

function getRowDifficulty(row: ProcessedRow): number {

  const types = row.map((word) => word[1].toLowerCase());



  const weights: Record<string, number> = {

    "po": 0,

    "př": 1,

    "pt": 2.5,

    "pks": 2,

    "pkn": 2.5,

    "d": 3,

    "default": 2
```

```
  };

  const sum = types.reduce((acc, type) => acc + (weights[type] || weights["default"]), 0);
  const difficulty = sum / Math.log2(types.length || 1); // Avoid division by zero

  return difficulty;
} jaky by z toho byl matematicky vzorec?
```

Ahoj, můžeš mi v ní najít chyby a opravit je? <zkopírovaná práce>

Určuji veťné členy ve větě “Co je za den?”

ahoj, chci udělat to, že v expo aplikaci nasdílím qr kód na hru a někdo si ho může naskenovat a připojit se

odkaz: vetnecleny://exams/join?code=1234

jak to mám udělat, musím to nějak nakonfigurovat?

mě to na ios funguje když je aplikace zapnutá v pozadí, ale napíše mi to že stránka neexistuje (jako kdyby exams/join vůbec neexistovalo) když zapnutá není

já linking nepoužívám, volám jen:

```
  useEffect(() => {
    if (params.code && !contextCode) {
      setCode(params.code as string);
      handleJoinGame(params.code as string);
    }
  }, [params.code]);
```

v exams/join, je to problém?

Vis co by mohlo způsobovat tento crash v expo aplikaci na iOS?

Thread 11 name:

Thread 11 Crashed:

0 hermes 0x0000000103d1ed10 0x103cf4000 + 175376

1 hermes 0x0000000103d35fc8 hermes::vm::JSObject::findProperty(hermes::vm::Handle<hermes::vm::JSObject>, hermes::vm::Runtime&, hermes::vm::SymbolID, hermes::vm::PropertyFlags, hermes::vm::NamedPropertyDescriptor&) + 48 (JSObject.h:1996)

2 hermes 0x0000000103d35fc8 hermes::vm::JSObject::findProperty(hermes::vm::Handle<hermes::vm::JSObject>, hermes::vm::Runtime&, hermes::vm::SymbolID, hermes::vm::NamedPropertyDescriptor&) + 48 (JSObject.h:1986)

3 hermes 0x0000000103d35fc8 hermes::vm::JSObject::getOwnNamedDescriptor(hermes::vm::Handle<hermes::vm::JSObject>, hermes::vm::Runtime&, hermes::vm::SymbolID, hermes::vm::NamedPropertyDescriptor&) + 48 (JSObject.h:1858)

4 hermes 0x0000000103d35fc8 hermes::vm::(anonymous namespace)::getOwnComputedPrimitiveDescriptorImpl(hermes::vm::Handle<hermes::vm::JSObject>, hermes::vm::Runtime&, hermes::vm::Handle<hermes::vm::HermesValue>, hermes::vm::JSO... + 204 (JSObject.cpp:748)

5 hermes 0x0000000103d35fc8 hermes::vm::JSObject::getOwnComputedPrimitiveDescriptor(hermes::vm::Handle<hermes::vm::JSObject>, hermes::vm::Runtime&, hermes::vm::Handle<hermes::vm::HermesValue>, hermes::vm::JSObject::IgnoreProx... + 252 (JSObject.cpp:815)

6 hermes 0x0000000103d36868 hermes::vm::(anonymous namespace)::getOwnComputedPrimitiveDescriptorImpl(hermes::vm::Handle<hermes::vm::JSObject>, hermes::vm::Runtime&, hermes::vm::Handle<hermes::vm::HermesValue>, hermes::vm::JSO... + 148 (JSObject.cpp:787)

7 hermes 0x0000000103d36868 hermes::vm::JSObject::getComputedPrimitiveDescriptor(hermes::vm::Handle<hermes::vm::JSObject>, hermes::vm::Runtime&, hermes::vm::Handle<hermes::vm::HermesValue>, hermes::vm::MutableHandle<hermes::v... + 584 (JSObject.cpp:986)

8 hermes 0x0000000103d388c4 hermes::vm::JSObject::putComputedWithReceiver_RJS(hermes::vm::Handle<hermes::vm::JSObject>, hermes::vm::Runtime&, hermes::vm::Handle<hermes::vm::HermesValue>, hermes::vm::Handle<hermes::vm::HermesV... + 368 (JSObject.cpp:1593)

9 hermes 0x0000000103d2532c hermes::vm::JSObject::putComputed_RJS(hermes::vm::Handle<hermes::vm::JSObject>, hermes::vm::Runtime&, hermes::vm::Handle<hermes::vm::HermesValue>, hermes::vm::Handle<hermes::vm::HermesValue>, herme... + 28 (JSObject.h:1959)

10 hermes 0x0000000103d2532c hermes::vm::CallResult<hermes::vm::HermesValue, (hermes::vm::detail::CallResultSpecialize)2> hermes::vm::Interpreter::interpretFunction<false, false>(hermes::vm::Runtime&, hermes::vm::InterpreterSt... + 3088 (Interpreter.cpp:2542)

11 hermes 0x0000000103d246f4 0x103cf4000 + 198388 (Interpreter.cpp:811)

12 hermes 0x0000000103d171dc hermes::vm::JSFunction::_callImpl(hermes::vm::Handle<hermes::vm::Callable>, hermes::vm::Runtime&) + 40 (Callable.cpp:1110)

13 hermes 0x0000000103d15c44 hermes::vm::Callable::call(hermes::vm::Handle<hermes::vm::Callable>, hermes::vm::Runtime&) + 48 (Callable.h:253)

14 hermes 0x0000000103d15c44 hermes::vm::Callable::executeCall3(hermes::vm::Handle<hermes::vm::Callable>, hermes::vm::Runtime&, hermes::vm::Handle<hermes::vm::HermesValue>, hermes::vm::HermesValue, hermes::vm::HermesValue, her... + 180 (Callable.cpp:280)

15 hermes 0x0000000103d71e90 hermes::vm::arrayPrototypeMap(void*, hermes::vm::Runtime&, hermes::vm::NativeArgs) + 708 (Array.cpp:2950)

16 hermes 0x0000000103d170f4 hermes::vm::NativeFunction::_nativeCall(hermes::vm::NativeFunction*, hermes::vm::Runtime&) + 140 (Callable.h:507)

17 hermes 0x0000000103d236fc hermes::vm::Interpreter::handleCallSlowPath(hermes::vm::Runtime&, hermes::vm::PinnedHermesValue*) + 60 (Interpreter.cpp:274)

18 hermes 0x0000000103d25108 0x103cf4000 + 200968 (Interpreter.cpp:1614)

19 hermes 0x0000000103d246f4 0x103cf4000 + 198388 (Interpreter.cpp:811)

20 hermes 0x0000000103d171dc hermes::vm::JSFunction::_callImpl(hermes::vm::Handle<hermes::vm::Callable>, hermes::vm::Runtime&) + 40 (Callable.cpp:1110)

21 hermes 0x0000000103d15c44 hermes::vm::Callable::call(hermes::vm::Handle<hermes::vm::Callable>, hermes::vm::Runtime&) + 48 (Callable.h:253)

22 hermes 0x0000000103d15c44 hermes::vm::Callable::executeCall3(hermes::vm::Handle<hermes::vm::Callable>, hermes::vm::Runtime&, hermes::vm::Handle<hermes::vm::HermesValue>, hermes::vm::HermesValue, hermes::vm::HermesValue, her... + 180 (Callable.cpp:280)

23 hermes 0x0000000103d71e90 hermes::vm::arrayPrototypeMap(void*, hermes::vm::Runtime&, hermes::vm::NativeArgs) + 708 (Array.cpp:2950)

24 hermes 0x0000000103d170f4 hermes::vm::NativeFunction::_nativeCall(hermes::vm::NativeFunction*, hermes::vm::Runtime&) + 140 (Callable.h:507)

25 hermes 0x0000000103d236fc hermes::vm::Interpreter::handleCallSlowPath(hermes::vm::Runtime&, hermes::vm::PinnedHermesValue*) + 60 (Interpreter.cpp:274)

26 hermes 0x0000000103d25108 0x103cf4000 + 200968 (Interpreter.cpp:1614)

27 hermes 0x0000000103d246f4 0x103cf4000 + 198388 (Interpreter.cpp:811)

28 hermes 0x0000000103d171dc hermes::vm::JSFunction::_callImpl(hermes::vm::Handle<hermes::vm::Callable>, hermes::vm::Runtime&) + 40 (Callable.cpp:1110)

29 hermes 0x0000000103d15980 hermes::vm::Callable::call(hermes::vm::Handle<hermes::vm::Callable>, hermes::vm::Runtime&) + 48 (Callable.h:253)

30 hermes 0x0000000103d15980 hermes::vm::Callable::executeCall0(hermes::vm::Handle<hermes::vm::Callable>, hermes::vm::Runtime&, hermes::vm::Handle<hermes::vm::HermesValue>, bool) + 156 (Callable.cpp:211)

31 hermes 0x0000000103d564f8 hermes::vm::Runtime::drainJobs() + 240 (Runtime.cpp:1868)

32 hermes 0x0000000103cfb91c facebook::hermes::HermesRuntimeImpl::drainMicrotasks(int) + 36 (hermes.cpp:1619)

33 Vtndrha 0x0000000102d9e584 facebook::react::RuntimeScheduler_Modern::performMicrotaskCheckpoint(facebook::jsi::Runtime&) + 112 (RuntimeScheduler_Modern.cpp:423)

34 Vtndrha 0x0000000102d9e404 facebook::react::RuntimeScheduler_Modern::runEventLoopTick(facebook::jsi::Runtime&, facebook::react::Task&, std::__1::chrono::time_point<std::__1::chrono::steady_clock, std::__1::chrono::duration<l... + 168 (RuntimeScheduler_Modern.cpp:331)

35 Vtndrha 0x0000000102d9e0ec facebook::react::RuntimeScheduler_Modern::runEventLoop(facebook::jsi::Runtime&, bool) + 156 (RuntimeScheduler_Modern.cpp:271)

36 Vtndrha 0x0000000102d32738 std::__1::__function::__value_func<void (facebook::jsi::Runtime&)>::operator()[abi:ne190102](facebook::jsi::Runtime&) const + 24 (function.h:430)

37 Vtndrha 0x0000000102d32738 std::__1::function<void (facebook::jsi::Runtime&)>::operator()(facebook::jsi::Runtime&) const + 24 (function.h:989)

38 Vtndrha 0x0000000102d32738 _ZZZN8facebook5react13ReactInstanceC1ENSt3__110unique_ptrINS0_9JSRuntimeENS2_14default_deleteIS4_EEEENS2_10shared_ptrINS0_18MessageQueueThreadEEENS8_INS0_12TimerManagerEEENS2_8functionIFvRNS_3jsi7R... + 100 (ReactInstance.cpp:83)

39 Vtndrha 0x0000000102d32738 _ZNSt3__18__invokeB8ne190102IRZZN8facebook5react13ReactInstanceC1ENS_10unique_ptrINS2_9JSRuntimeENS_14default_deleteIS5_EEEENS_10shared_ptrINS2_18MessageQueueThreadEEENS9_INS2_12TimerManagerEEENS_8... + 100 (invoke.h:149)

40 Vtndrha 0x0000000102d32738 _ZNSt3__128__invoke_void_return_wrapperIvLb1EE6__callB8ne190102IJRZZN8facebook5react13ReactInstanceC1ENS_10unique_ptrINS4_9JSRuntimeENS_14default_deleteIS7_EEEENS_10shared_ptrINS4_18MessageQueueThr... + 100 (invoke.h:224)

41 Vtndrha 0x0000000102d32738 _ZNSt3__110__function12__alloc_funcIZZN8facebook5react13ReactInstanceC1ENS_10unique_ptrINS3_9JSRuntimeENS_14default_deleteIS6_EEEENS_10shared_ptrINS3_18MessageQueueThreadEEENSA_INS3_12TimerManagerE... + 100 (function.h:171)

42 Vtndrha 0x0000000102d32738 _ZNSt3__110__function6__funcIZZN8facebook5react13ReactInstanceC1ENS_10unique_ptrINS3_9JSRuntimeENS_14default_deleteIS6_EEEENS_10shared_ptrINS3_18MessageQueueThreadEEENSA_INS3_12TimerManagerEEENS_8f... + 140 (function.h:313)

43 Vtndrha 0x0000000102b61b94 std::__1::__function::__value_func<void ()>::operator()[abi:ne190102]() const + 20 (function.h:430)

44 Vtndrha 0x0000000102b61b94 std::__1::function<void ()>::operator()() const + 20 (function.h:989)

45 Vtndrha 0x0000000102b61b94 facebook::react::tryAndReturnError(std::__1::function<void ()> const&) + 32 (RCTCxxUtils.mm:73)

46 Vtndrha 0x0000000102b70148 facebook::react::RCTMessageThread::tryFunc(std::__1::function<void ()> const&) + 24 (RCTMessageThread.mm:68)

47 Vtndrha 0x0000000102b6ff54 std::__1::__function::__value_func<void ()>::operator()[abi:ne190102]() const + 20 (function.h:430)

48 Vtndrha 0x0000000102b6ff54 std::__1::function<void ()>::operator()() const + 20 (function.h:989)

49 Vtndrha 0x0000000102b6ff54 invocation function for block in facebook::react::RCTMessageThread::runAsync(std::__1::function<void ()>) + 44 (RCTMessageThread.mm:44)

50 CoreFoundation 0x00000001a1d759b0 0x1a1d09000 + 444848

51 CoreFoundation 0x00000001a1d18188 0x1a1d09000 + 61832

52 CoreFoundation 0x00000001a1d19688 0x1a1d09000 + 67208

53 CoreFoundation 0x00000001a1d1ac3c CFRunLoopRunSpecific + 572 (CFRunLoop.c:3434)

54 Vtndrha 0x0000000102d2e4b0 +[RCTJSThreadManager runRunLoop] + 212 (RCTJSThreadManager.mm:102)

55 Foundation 0x00000001a09f8804 __NSThread__start__ + 732 (NSThread.m:991)

56 libsystem_pthread.dylib 0x000000022c41b344 _pthread_start + 136 (pthread.c:931)

57 libsystem_pthread.dylib 0x000000022c418ab8 thread_start + 8

Ahoj, můžeš mi prosím napsat popisek do App Store k této aplikaci <minuly kontext>

make this screen pretty... also use the <PlayfullButton>

design duolingo styled "good-job" overlay, for my react native app using expo, make sure to create it as a standalone component with popup like behaviour, it should popup at the end of the round

Rework this component so it takes style as input instead of the selected prop and also implement all styles including correct (green) and incorrect (red)

import React from "react"; import { TouchableOpacity, StyleSheet, Text } from "react-native";

enum LargeGameButtonStyle { default, selected, correct, incorrect, }

export const LargeGameButton = ({ text, selected, onPress }: { text: string; selected: boolean; onPress: () => void, }) => {

if (!text || text.length === 0) console.warn("LargeGameButton received an empty text prop.");

return (<TouchableOpacity style={[styles.option, selected && styles.selectedOption]} onPress={onPress} activeOpacity={0.7} > <Text style={styles.optionText}>{text}</Text> </TouchableOpacity>); }

const styles = StyleSheet.create({ option: { width: '47%', height: 120, borderRadius: 10, borderWidth: 1, borderColor: '#444', justifyContent: 'center', alignItems: 'center', backgroundColor: '#101223', }, selectedOption: { borderColor: '#6266f1', backgroundColor: 'rgba(98, 102, 241, 0.1)', }, optionText: { color: '#fff', fontSize: 18, fontWeight: '500', textAlign: 'center', }, });

I need you to generate a detail page for authored game in react native with expo go and typescript. This is the card that will triger navigation to the detail page and the game will be passed as a whole object into the navigation parameters. I will also provide a type for the authored game, display all of the data that would make sence: interface AuthoredGame { id: string; code: number; difficulty: number; galaxy: number; questiontypes: number; version: string; seed: string; active: boolean; expirationTime: string; createdAt: string; questionCount: number; seeded: boolean; sessions: Array<{ id: string; playerId: string; score: number; correctAnswers: number; completed: boolean; startedAt: string; endedAt: string; player: { id: string; name: string; bodyColor: string; trailColor: string; selectedRocketIndex: number; clientVersion: string; levels: string; }; }>; }

I want to test few methods in my expo app, what is the best way to do unit tests

Now create test that tests generateGameData from game context

Tell me how test the funtion ideally without separating it from the file, but its not mandatory if there is not other way

Ok Imma refactor the function and move the core logic out of the tsx file, what folder should I put the new file under

Create test for GameDataGenerator file

add test to check if two generations with same seed result in the same data and one more test to check if two generations with different seed result in different data

Rework this into context: useQuestionGenerator.ts:178-211

Create page that takes sentence from the input (WordSelectionOption[]) and displays it in the middle of the page

the props should be passed when navigating to the page as input params

replace sentence with use state

now create a new route /exams/share.tsx

when a user creates the game in create.tsx (and the request is successfull), they should be redirected to this share.tsx, where the QRCode and game code will be shown (also a cancel button which will redirect back to the create and fetch a cancel-game endpoint)

please use expo-router instead of the navigation

the code should be available in the useMultiplayerGameContext ??

create a exams/join route that can players use to join a game via a PIN...
when they join, make sure to show all info about the game on the screen

rename pin to code

the joinGame should write info to the context

gameInfo doesnt exist - use stuff from the context

add a start button to the join

it works when it is /exams/, ../exams/ (but gives typeerror), but /exams/index says it doesnt exist (but doesnt give typerr) but now it gives a type error

want to have a some type of context that we can write all questions too...

basicaly when a player

1. plays the galaxy (storymode) exercises
2. plays an online (via joining) game/exams
3. plays a practice game/exams

i want to store some stuff

1. a seed for the questions
2. all the questions and answers (and the type for that question)
3. users answers to the questions
4. active question index

which should be accessible for other routes (mainly the /games ones)

i also want another context for an multiplayer game, which should have all the important data

1. gameCode for that game
2. config of that game (difficulty, galaxy, seed, questiontypes)
3. other players (name, id, bodyColor, trailColor, selectedRocketIndex)

please make some functions in the context for doing that stuff

please move all types to their respective files in /types

nice! now create a function for joining the online multiplayer game with a gamecode as an input...

maybe it would be nice to create hooks for working with the API. But basically, when the code changes, i want to call the /join-game with the gamecode and info about the clients "rocket" stored in the rocket context.

create an env which will have API_URL and API_BACKUP_URL (if the first one s unreachable)

i dont like the usejoingame
instead, i want it to move the joining logic into the MultiplayerGameContext...
the onlt thing i dont want to do in the context is the fetching, because its long.
so instead, replace the usejoingame hook with a useAPI, which should have some method, path and payload params. make it also do the backup request

ice! now can you create a function for actually creating a game

Make sure the question types is a number.

now make sure that the multiplayergame context is used in the /exams/create correctly

change the galaxy when creating the page to an index of the galaxy

rename all instances of "gameCode" to just "code"

ok but i also want to use it like in the multiplayergamecontext

nah! i already use it like this but i doesnt work

maybe make the useAPI better - i dont want no initial "data" and a callAPI method...

make it so i can just use the useAPI(...params here...) and it will return {isLoading, data: Promise} and i can somehow await the data

React Hook "useAPI" is called in function "joinGame" that is neither a React function component nor a custom React Hook function. React component names must start with an uppercase letter. React Hook names must start with the word "use".

file:MultiplayerGameContext.tsx

adjust the useAPI so it returns a post and get function
useAPI will be called on top of every file that uses it...

ok now the code in useAPI is duplicated

file:useAPI.ts

hy does the /exams/create and all the /games show in tabs?

can you please find out why does it show in the tabs?

make usre that the teachermode is also stored in asyncstorage

default difficulty is 50%, change the theme color to 2A3192

i want to make it so some pages (like creategame) are not tabs, but can be opened thru a button on osme page. how can i do that? cuz now i see it down in the tabs...

i want to make it so some pages (like creategame) are not tabs, but can be opened thru a button on osme page. how can i do that? cuz now i see it down in the tabs...

how can i add the feature that when the user swipes from left to right, it will go back to previous page

when i restart the app, the saved selected galaxy is loaded but not the active planet or active level in that galaxy

file:GalaxyContext.tsx

can you render out a <Rocket> next to the activePlanet in GalaxyView

useCSV.ts

_layout.tsx

arena2.tsx

arena.tsx

GalaxyView.tsx

Rocket.tsx

NamedRocket.tsx

tsconfig.json

rocket1.svg

rocket2.svg

infer types

add an toggle bellow the "Jméno" input for the teacher mode "Učitelský režim"... also add it into the context userocket context

the teacher tab overflow the safe area, add it (this app is in expo btw)

the game code and QR code will be visible after the user selects the difficulty, galaxy, optionaly question types and presses a button (Start Exam)

file:teacher.tsx

nice! i have some images / icon of the each galaxy, they are already used in the arenagalaxy's and arenaplanet's headers... can you fit them next to the galaxy names

file:teacher.tsx

the galaxiy selection doesnt fit on the screen... make it so it either fits/wraps or is horizontally scrollable, its on you which fits better

nice, please the difficulty could be a slider from 0 to 100

can the slider autosnap by fives?

add names for the difficulties (in czech)

the {difficulty}% text looks wierd in that place

Všechny should be the defailt galaxy, also dont make the text bold in that sleected button

how do I do expo build onto my android device

how do I build it locally

I have this layout that is being used on multiple pages, the code is in expo and typescript. I need to add animations in such way that when the page is navigated from page using this layout to another page using this layout, the progressbar animates only the progress, the children are moved in using swipe in motion and the rest stays stationary import { SafeAreaView } from "react-native-safe-area-context"; import RocketProgressBar from "../ui/games/ProgressBar"; import { FeedbackOverlay } from "../FeedbackOverlay"; import React, { ReactNode } from "react"; import { StyleSheet, TouchableOpacity, View } from 'react-native'; import { useGameContext } from "@/contexts/GameContext"; import { Text } from "react-native-svg"; import { useRouter } from "expo-router"; interface GameLayoutProps { children: ReactNode; resetGame: () => void } export const GameLayout: React.FC<GameLayoutProps> = ({ children, resetGame }) => { const { state, gameData } = useGameContext(); const navigation = useRouter(); return (<SafeAreaView style={styles.container}> <FeedbackOverlay state={state} resetGame={resetGame} /> <View style={[styles.headerWrapper]}> <View style={{ flexShrink: 1, flexGrow: 999 }}> <RocketProgressBar progress={1 - (gameData.questionsRemaining + 1) / gameData.totalQuestion}/> </View> <View style={{ flexShrink: 1, flexGrow: 1 }}> <TouchableOpacity style={[styles.button]} onPress={() => { navigation.push('tutorial' as never,) }} > <Text>?</Text> </TouchableOpacity> </View> </View> {children} </SafeAreaView>); } const styles = StyleSheet.create({ headerWrapper: { width: '100%', display: 'flex', flexDirection: 'row', alignItems: 'center', gap: 8, flexShrink: 1 }, container: { flex: 1, backgroundColor: '#000', paddingHorizontal: 20, paddingVertical: 24, gap: 32, justifyContent: 'space-between', alignItems: 'center', }, button: { backgroundColor: '#1E1E5F', // Dark blue color from the image paddingVertical: 12, paddingHorizontal: 24, borderRadius: 24, // Rounded corners alignItems: 'center', justifyContent: 'center', width: '100%', maxWidth: 300, // Maximum width color: 'white', fontWeight: 'bold', }, });

rewrite this into animated component: import React from 'react'; import { View, StyleSheet } from 'react-native'; import { LinearGradient } from 'expo-linear-gradient'; import { Rocket } from '@/components/Rocket'; interface RocketProgressBarProps { progress: number; // Value from 0 to 1 width?: number; height?: number; } const RocketProgressBar: React.FC<RocketProgressBarProps> = ({ progress = 0.33, height = 40, }) => { // Constrain progress between 0 and 1 const normalizedProgress = Math.min(Math.max(progress, 0), 1); return (<View style={[styles.container, { height }]}> <View style={[styles.backgroundBar, { height, borderRadius: height / 2 }]}> <LinearGradient colors={['#4c1d95', '#6d28d9', '#7c3aed']} start={{ x: 0, y: 0 }} end={{ x: 1, y: 0 }} style={[styles.progressBar, { width: ${normalizedProgress * 100}%, height, borderRadius: height / 2, },]} /> <View style={[styles.rocketContainer, { width: ${normalizedProgress * 100}%, height }]}> <View style={styles.rocket} /> <Rocket style={styles.rocket} /> </View> </View> </View>); }; const styles = StyleSheet.create({ container: { justifyContent: 'center', alignItems: 'center', width: '100%', }, backgroundBar: { backgroundColor: '#111827', // overflow: 'hidden', position: 'relative', width: '100%', }, progressBar: { position: 'absolute', left: 0, }, rocketContainer: { width: '100%', }, rocket: { position: 'absolute', right: '-50%', top: '-75%', transform: [{ rotate: '90deg' }], }, }); export default RocketProgressBar;