



Python Scripts

Scripts added to a folder, C:\Users\psobh\Documents\Path

This folder added to the computer's Path Variable

.py

 File Name	 Format	 Description
<u>words.py</u>	<u>words.py</u> V3-09.xml	replace words between <tree text=" and (cannot use for headings can run in the command line. use full file name with .py extension takes the file name as a command line argument. can use for renamed files. replace words in words.txt to any file. use file name with extension xml. example: <u>replace.py</u> V3-2.xml add numbers to words.txt do not keep empty lines in the beginning of words.txt
<u>wordsh.py</u>	wordsh.py V3-09.xml	For headings onlyreplaces words between <tree text=" and "can run in the command line. use full file name with .py extensiontakes the file name as a command line argumentcan use for renamed filesreplace words in words.txt to any fileuse file name with extension xmlexample: <u>replace2.py</u> V3.xmladd numbers to words.txtdo not keep empty lines in the beginning of words.txtdoesn't add a space after the replacement text (before ")
<u>times.py</u>	<u>times.py</u> V3-09.xml	replaces times in xml file from times.txt use hours:minutes:seconds format in times.txt do not keep empty lines in the beginning of times.txt replaces words between ', and '); create a temp file called times-temp.txt
<u>capital.py</u>	<u>capital.py</u> words.txt	capitalize all words. English and Cyrillic including special characters
<u>numbers.py</u>	<u>numbers.py</u> words.txt	simply add numbers to the beginning of each line. use for words.txt

 File Name	 Format	 Description
<u>min0.py</u>	<u>min0.py</u> V3-09.xml	replaces any numbers in (15min.) to (00min.)used to create new files to add duration.
<u>page0.py</u>	<u>page0.py</u> V3-09.xml	replaces any numbers in ,[space]Xp to ,[space]00pused to create new files to add page numbers.
<u>minpage0.py</u>	<u>minpage0.py</u> V3-09.xml	combined <u>min0.py</u> and <u>page0.py</u> used to create new files to add duration and page numbers.
<u>clines.py</u>	<u>clines.py</u> V3-09.xml	clears xml files and outputs only words to words.txt, I commented out first line remove. Sometimes it ads first two lines together. Edited version is clines1.py.
<u>clinesh.py</u>	<u>clinesh.py</u> V3-09.xml	clears header xml files and outputs only words to words.txt, I commented out first line remove. Sometimes it ads first two lines together. Edited version is clinesh1.py. This script removes page numbers
<u>numbers-old.py</u>	<u>numbers-old.py</u> V3-09.xml	Not Used , replaces numbers with roman numbers in these languages. use this to convert words.txt
<u>numbersn.py</u>	<u>numbersn.py</u> <file_path> <start_number>	Can start numbering with a given number. Leading zero also preserved. Used for Digha and Majjhima.
<u>bjt.py</u>	<u>bjt.py</u> vinaya.xml	Change BJT book numbers in header files. Add lines to words.txt first. Must be a bracket () in the xml file to replace. Can use in X.xml files also.
<u>brackets.py</u>	<u>brackets.py</u> vinaya.xml	Removes any BJT book entries and adds () brackets to all lines. Then use <u>bjt.py</u> to add book numbers.
<u>replace.py</u>	<u>replace.py</u> file.xml search_string replace_string	Used to replace header files links.
<u>share.py</u>		Only used ones to make dhamma talk lists

📁 File Name	≡ Format	≡ Description
<u>sharefile.py</u>		Only used ones to make dhamma talk lists
<u>xml-text-2words.py</u>		Extracts only the value inside <code>text="..."</code> Writes the cleaned output to words.txt
<u>words2summary.py</u>		For every line in the main input file, replace the content inside <code><summary> ... </summary></code> with the corresponding line from <code>word.txt</code> . Save the modified result to output2.txt
<u>words2button.py</u>		Read lines from <code>word.txt</code> . Replace the content inside the first <code><button ...> ... </button></code> in each line with the corresponding line from <code>word.txt</code> . Save the modified result to output.txt
<u>xml-loadYoutubebe2-2words.py</u>		Extracts only the variable inside <code>javascript:loadYoutube2('...');</code> from each line. Writes all extracted variables line by line to <code>words.txt</code> .
<u>words2-loadYoutubebe2-and-share.py</u>		For each line in the input file, replaces the text inside both: <code>loadYoutube2('...')</code> <code>sharePage('...')</code> with successive lines from <code>word.txt</code> .Writes the result to <code>output2.txt</code> .
<u>xml-loadYoutubebeStartStop-2words.py</u>		it extracts variables from both <code>javascript:loadYoutubeStartStop('...');</code> <code>javascript:loadYoutubeStart('...');</code> and then writes them line by line into <code>words.txt</code> .
<u>words2-loadYoutubebeStartStop-and-share.py</u>		If the function is <code>loadYoutubeStartStop('...')</code> or <code>sharePageStartStop('...')</code> → replace the <code>'...'</code> with successive lines from <code>words.txt</code> , except the last line.If the function is <code>loadYoutubeStart('...')</code> or <code>sharePageStart('...')</code> → replace the <code>'...'</code> with the last line of <code>words.txt</code> .Write the result into <code>output2.txt</code> .
<u>xml-lines-loadYoutube</u>		created to make input.txt with same number of lines. This only copies <code>loadYoutube2('...')</code> to words.txt file .

 File Name	 Format	 Description
<u>be2-2words.py</u>		
<u>xml-lines-loadYoutubeStartStop.py</u>		created to make input.txt with same number of lines. This only copies <code>loadYoutubeStartStop('...')</code> and <code>loadYoutubeStart('...')</code> to words.txt file.
<u>words-loadYoutubebe2-2input-lines.py</u>		This replaces the <code>loadYoutube2('...')</code> lines in words.txt with a string and output to input.txt
<u>words-loadYoutubebeStartStop-2input-lines.py</u>		This replaces the <code>loadYoutubeStartStop('...')</code> and <code>loadYoutubeStart('...')</code> lines in words.txt with a string and output to input.txt
<u>xml-headings-lines-2words.py</u>		created to make input.txt with same number of lines. This only copies <code>src="any variable"</code> to words.txt file.
<u>words-heading-2input-lines.py</u>		This replaces the <code>src="any variable"</code> lines in words.txt with a string and output to input.txt
<u>check_share.py</u>		If variable1 = variable2 ignore, if variable1 not= variable2 output the line number to words.txt in <code>loadYoutube2('variable1')</code> <code>sharePage('variable2')</code> . Used to check whether I updated the <code>sharePage()</code> variable in html lists.
<u>words2html-headings.py</u>		Adds words from words.txt to lines with headings in input.html and writes the output to output.html. Used to make <code></code> lines.
<u>words2html-</u>		Adds words from words.txt to normal lines with chetiya in input.html and writes the output to output.html. Used to make

 File Name	 Format	 Description
<u>lines.py</u>		lines.
<u>words2html-clear.py</u>		combined above 2 codes to add words to mixed lines.
<u>words2html.py</u>		Ignore </details> and continue replacing. useful for nested lists.
<u>join-all.py</u>		joins words in input.txt and input2.txt and outputs to wods.txt
<u>join.py</u>		avoids any lines containing the word "blank" in input2.txt. use this to combine page numbers, times to words. add transliterated words to input.txt and times to input2.txt
<u>times2.py</u>		edited <u>times.py</u> above. Stops after creating times-temp.txt. last line with one time (Start only).
<u>add-times.py</u>		add times from times-temp.txt to output.html and outputs to output2.html - last line must be javascript:loadYoutubeStart
<u>add-times2.py</u>		add times from times-temp.txt to output.html and outputs to output2.html - last line is also javascript:loadYoutubeStartStop
<u>copy-to-page.py</u>		Copy variables in javascript:loadYoutubeStartStop and javascript:loadYoutubeStart to sharePageSrartStop and sharePageSrart. replaces output2.html and creates output3.html