

# Hypergraphs and Information Fusion for Term Representation Enrichment. Applications to Named Entity Recognition and Word Sense Disambiguation

Ph.D. Thesis Defense

---

Pavel Soriano-Morales

Supervised by Sabine Loudcher and Julien Ah-Pine

February 7th, 2018



UNIVERSITÉ  
LUMIÈRE  
LYON 2



UNIVERSITÉ  
DE LYON


INSTITUT  
DES SCIENCES  
DE L'HOMME



# Introduction


## Why it is useful to us to understand text?

Google search results for "Who invented Python?". The search bar shows the query and a magnifying glass icon. Below the search bar, there are tabs for "All", "Images", "Shopping", "Videos", "News", "More", "Settings", and "Tools". The "All" tab is selected. Below the tabs, it says "About 520,000 results (0.63 seconds)". The main result is for "Guido van Rossum", with a small photo of him. The text below the photo says: "Python was conceived in the late 1980s, and its implementation began in December 1989 by **Guido van Rossum** at Centrum Wiskunde & Informatica (CWI) in the Netherlands as a successor to the ABC language (itself inspired by SETL) capable of exception handling and interfacing with the operating system Amoeba. **Van Rossum** is ..."




# How do we extract meaning from text?


We use **Natural Language Processing** (NLP), a field of computer science interested on making computers extract useful information from text



How do we represent text for the machine to understand?



What techniques do we use to discover meaning from text?



# Representing Text

- **Three common ways to represent text**

# Representing Text

- **Three common ways to represent text**
  - Lexical

# Representing Text

- **Three common ways to represent text**
  - Lexical
  - Syntactic

# Representing Text

- **Three common ways to represent text**
  - Lexical
  - Syntactic
    - Constituency Tree



# Representing Text

- **Three common ways to represent text**
  - Lexical
  - Syntactic
    - Constituency Tree
    - **Dependency Tree**

# Representing Text

- **Three common ways to represent text**
  - Lexical
  - Syntactic
    - Constituency Tree
    - Dependency Tree
- **Working Example**

# Representing Text

- **Three common ways to represent text**

- Lexical
- Syntactic
  - Constituency Tree
  - Dependency Tree

- **Working Example**


*The report contains copies of the minutes of these meetings*

- **Three common ways to represent text**

- Lexical
- Syntactic
  - Constituency Tree
  - Dependency Tree

- **Working Example**

*The report contains copies of the minutes of these meetings*




# Representing Text

- **Three common ways to represent text**

- Lexical
- Syntactic
  - Constituency Tree
  - Dependency Tree

- **Working Example**

*The report contains copies of the minutes of these meetings*




# Representing Text

- **Three common ways to represent text**

- Lexical
- Syntactic
  - Constituency Tree
  - Dependency Tree

- **Working Example**

*The report contains copies of the minutes of these meetings*



- **Text Representation Models**

- Words and features can be represented by means of graph-based models matrices
- Or directly with (sparse) matrices

- **Leveraging the Network Structure**


- We can find communities of similar words according to their meaning

- **Text Representation Models**

- Words and features can be represented by means of graph-based models matrices
- Or directly with (sparse) matrices

- **Leveraging the Network Structure**

- We can find communities of similar words according to their meaning





# Main Challenges and Contributions

1. What type of model can we employ to represent a corpus using heterogeneous features?

# Main Challenges and Contributions

1. What type of model can we employ to represent a corpus using heterogeneous features?
  - *Hypergraph linguistic model to hold different types of linguistic information*

# Main Challenges and Contributions

1. What type of model can we employ to represent a corpus using heterogeneous features?
  - *Hypergraph linguistic model to hold different types of linguistic information*
2. How can we combine these features while dealing with feature sparsity?

# Main Challenges and Contributions

1. What type of model can we employ to represent a corpus using heterogeneous features?
  - *Hypergraph linguistic model to hold different types of linguistic information*
2. How can we combine these features while dealing with feature sparsity?
  - *Multimedia fusion techniques to combine and densify representation spaces*

# Main Challenges and Contributions


1. What type of model can we employ to represent a corpus using heterogeneous features?
  - *Hypergraph linguistic model to hold different types of linguistic information*
2. How can we combine these features while dealing with feature sparsity?
  - *Multimedia fusion techniques to combine and densify representation spaces*
3. How can we find and employ communities existing within the language networks?

# Main Challenges and Contributions

1. What type of model can we employ to represent a corpus using heterogeneous features?
  - *Hypergraph linguistic model to hold different types of linguistic information*
2. How can we combine these features while dealing with feature sparsity?
  - *Multimedia fusion techniques to combine and densify representation spaces*
3. How can we find and employ communities existing within the language networks?
  - *An alternative network-based algorithm to discover semantically related words within a text*

# Introduction

## Work Overview



# **Contributions in Detail**

## **Hypergraph Linguistic Model**

---



# Introduction

Based on the distributional hypothesis, a word is defined by its surroundings, we can extract useful information from a text.

- **How do we represent textual data?**

Based on the distributional hypothesis, a word is defined by its surroundings, we can extract useful information from a text.

- **How do we represent textual data?**
  - Network Models [MTFo4]

Based on the distributional hypothesis, a word is defined by its surroundings, we can extract useful information from a text.

- **How do we represent textual data?**
  - Network Models [MTFo4]
  - Vector Space Models [MS+99]

Based on the distributional hypothesis, a word is defined by its surroundings, we can extract useful information from a text.

- **How do we represent textual data?**

- Network Models [MTFo4]
- Vector Space Models [MS+99]

- **We choose network models**

Based on the distributional hypothesis, a word is defined by its surroundings, we can extract useful information from a text.

- **How do we represent textual data?**
  - Network Models [MTFo4]
  - Vector Space Models [MS+99]
- **We choose network models**
  - Used in a large quantity of NLP tasks [MR11]

Based on the distributional hypothesis, a word is defined by its surroundings, we can extract useful information from a text.

- **How do we represent textual data?**
  - Network Models [MTFo4]
  - Vector Space Models [MS+99]
- **We choose network models**
  - Used in a large quantity of NLP tasks [MR11]
  - Graphs structures can give us a clearer view into the relations of words within a text [CMo9]

Based on the distributional hypothesis, a word is defined by its surroundings, we can extract useful information from a text.

- **How do we represent textual data?**

- Network Models [MTFo4]
- Vector Space Models [MS+99]

- **We choose network models**

- Used in a large quantity of NLP tasks [MR11]
- Graphs structures can give us a clearer view into the relations of words within a text [CM09]
- Ultimately graphs are transformed to a vectorial representation through the adjacency/incidence matrices


*The report contains copies of the minutes of these meetings*



*The report contains copies of the minutes of these meetings*

### Lexical Networks

Sentence Level




[KMo8]

*The report contains copies of the minutes of these meetings*

## Syntactic Networks


Dependency Tree



*The report contains copies of the minutes of these meetings*


### Syntactic Networks

#### Constituency Tree



*The report contains copies of the minutes of these meetings*

### Semantic Networks



## Limitations and Proposition

- **Limitations of existing representations**

# Limitations and Proposition

- **Limitations of existing representations**
  - Language networks generally employ a single type of textual information

# Limitations and Proposition

- **Limitations of existing representations**
  - Language networks generally employ a single type of textual information
  - The edges of the network may relate maximum two words at each time

# Limitations and Proposition

- **Limitations of existing representations**
  - Language networks generally employ a single type of textual information
  - The edges of the network may relate maximum two words at each time
- **Proposition**



# Limitations and Proposition

- **Limitations of existing representations**

- Language networks generally employ a single type of textual information
- The edges of the network may relate maximum two words at each time

- **Proposition**

- Represent together linguistic co-occurrences through a hypergraph model

# Limitations and Proposition

- **Limitations of existing representations**

- Language networks generally employ a single type of textual information
- The edges of the network may relate maximum two words at each time

- **Proposition**

- Represent together linguistic co-occurrences through a hypergraph model
  - Link together three different types of networks, using lexical and syntactic data

# Limitations and Proposition

- **Limitations of existing representations**

- Language networks generally employ a single type of textual information
- The edges of the network may relate maximum two words at each time


- **Proposition**

- Represent together linguistic co-occurrences through a hypergraph model
  - Link together three different types of networks, using lexical and syntactic data
  - Get a semantic overview at three different levels: short range (with dependency functions), medium range (phrase constituency membership), and long range (lexical co-occurrence)


# Hypergraph Linguistic Model

## Proposed Model


**Lexical Networks**  
Sentence Level



**Syntactic Networks**  
Constituency Tree




**Syntactic Networks**  
Dependency Tree




# Hypergraph Linguistic Model

## Proposed Model


**Lexical Networks**  
Sentence Level



**Syntactic Networks**  
Constituency Tree




**Syntactic Networks**  
Dependency Tree



## Hypergraph Model


■ Lexical




# Hypergraph Linguistic Model

## Proposed Model


**Lexical Networks**  
Sentence Level




**Syntactic Networks**  
Constituency Tree



**Syntactic Networks**  
Dependency Tree



## Hypergraph Model




- Lexical
- Constituency (NP<sub>2</sub>)


# Hypergraph Linguistic Model

## Proposed Model


**Lexical Networks**  
Sentence Level




**Syntactic Networks**  
Constituency Tree



**Syntactic Networks**  
Dependency Tree



## Hypergraph Model




- Lexical
- Constituency (NP<sub>2</sub>)
- Constituency (VP)


# Hypergraph Linguistic Model

## Proposed Model


**Lexical Networks**  
Sentence Level




**Syntactic Networks**  
Constituency Tree



**Syntactic Networks**  
Dependency Tree



## Hypergraph Model




- Lexical
- Constituency (NP<sub>2</sub>)
- Constituency (VP)
- Dependency (dobj:contains)




# Hypergraph Linguistic Model

## Proposed Model


**Lexical Networks**  
Sentence Level




**Syntactic Networks**  
Constituency Tree



**Syntactic Networks**  
Dependency Tree



## Hypergraph Model



- Lexical
- Constituency (NP<sub>2</sub>)
- Constituency (VP)
- Dependency (dobj:contains)
- Dependency (nmod:of)

# **Contributions in Detail**

**Combining Features and Dealing with  
Sparsity**

---

- **Definition**

- **Definition**

- Set of techniques used in multimedia analysis tasks to integrate multiple media [Atr+10; ABL10]

- **Definition**

- Set of techniques used in multimedia analysis tasks to integrate multiple media [Atr+10; ABL10]
- The goal is to obtain rich insights about the data being treated

- **Definition**

- Set of techniques used in multimedia analysis tasks to integrate multiple media [Atr+10; ABL10]
- The goal is to obtain rich insights about the data being treated
- We adapt these techniques to our use case: textual information

- **Definition**

- Set of techniques used in multimedia analysis tasks to integrate multiple media [Atr+10; ABL10]
- The goal is to obtain rich insights about the data being treated
- We adapt these techniques to our use case: textual information

- **Main fusion operators:**

- **Definition**

- Set of techniques used in multimedia analysis tasks to integrate multiple media [Atr+10; ABL10]
- The goal is to obtain rich insights about the data being treated
- We adapt these techniques to our use case: textual information

- **Main fusion operators:**

- Early Fusion  $E_{\alpha}(\cdot)$ ,



- **Definition**

- Set of techniques used in multimedia analysis tasks to integrate multiple media [Atr+10; ABL10]
- The goal is to obtain rich insights about the data being treated
- We adapt these techniques to our use case: textual information

- **Main fusion operators:**

- Early Fusion  $E_{\alpha}(\cdot)$ ,
- Late Fusion  $L_{\beta}(\cdot)$ ,

- **Definition**

- Set of techniques used in multimedia analysis tasks to integrate multiple media [Atr+10; ABL10]
- The goal is to obtain rich insights about the data being treated
- We adapt these techniques to our use case: textual information


- **Main fusion operators:**

- Early Fusion  $E_{\alpha}(\cdot)$ ,
- Late Fusion  $L_{\beta}(\cdot)$ ,
- Cross Fusion  $X_{\gamma}(\cdot), X_F(\cdot)$

## Early and Late Fusion


### EARLY FUSION

Matrices  $M^L$  and  $M^S$  have the same number of rows




### EARLY FUSION

Matrices  $M^L$  and  $M^S$  have the same number of rows




### LATE FUSION: SIMILARITY FUSION

Matrices  $S^L$  and  $S^S$  have the same size



## Cross Fusion



- We distinguish three levels of fusion operators
  - **First Degree**
    - $E(M^L, M^S), L(S^S, M^L)$
    - Cross Feature Fusion:  $X_F(S^S, M^L)$
    - Cross Similarity Fusion:  $X_S(S^S, S^L)$
  - **Second Degree**
    - Cross Feature Early Fusion:  $X_F(S^T, E(M^L, M^S))$
    - Late Cross Feature Fusion:  $L(M^T, X_F(S^T, M^T))$
  - **Higher Degree**
    - Triple Early Double Late Cross Feature Fusion:  
 $E(M_L, E(E(M_T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L))))$

### Hybrid Fusion

$$E(M_L, E(E(M^T, L(M^T, X_F(S^T, M^T)))), L(M^L, X_F(S^S, M^L))))$$

### Hybrid Fusion

The diagram shows a nested function expression  $E(M^L, E(E(M^T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L))))$  enclosed in a blue box. The expression is composed of several nested components, each highlighted with a different color: a green box for  $E(M^T, \dots)$ , a red box for  $L(M^T, X_F(S^T, M^T))$ , and a yellow box for  $L(M^L, X_F(S^S, M^L))$ . The entire expression is enclosed in a blue box, which is itself inside a larger blue box.

$$E(M^L, E(E(M^T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L))))$$



$$E(M_L, E(E(M^T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L))))$$

$$L(M^L, X_F(S^S, M^L))$$

$$\begin{aligned} \begin{matrix} w_1 & w_2 & w_3 \\ \begin{pmatrix} S^S \end{pmatrix} \end{matrix} \times \begin{matrix} f_{L1} & f_{L2} & f_{L3} \\ \begin{pmatrix} M^L \end{pmatrix} \end{matrix} &= \begin{matrix} f_{L1} & f_{L2} & f_{L3} \\ \begin{pmatrix} X_F(S^S, M^L) \end{pmatrix} \end{matrix} \\ \begin{matrix} f_{L1} & f_{L2} & f_{L3} \\ \begin{pmatrix} M^L \end{pmatrix} \end{matrix} + \begin{matrix} f_{L1} & f_{L2} & f_{L3} \\ \begin{pmatrix} X_F(S^S, M^L) \end{pmatrix} \end{matrix} &= \begin{matrix} f_{L1} & f_{L2} & f_{L3} \\ \begin{pmatrix} L(M^L, X_F(S^S, M^L)) \end{pmatrix} \end{matrix} \end{aligned}$$

$$E(M_L, E(E(M^T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L))))$$

$$L(M^T, X_F(S^T, M^T))$$

$$\begin{aligned} & \begin{matrix} w_1 & w_2 & w_3 \\ \left( \begin{array}{c} S^T \end{array} \right) \end{matrix} \times \begin{matrix} f_{T1} & f_{T2} & f_{T3} \\ \begin{matrix} w_1 \\ w_2 \\ w_3 \end{matrix} \left( \begin{array}{c} M^T \end{array} \right) \end{matrix} = \begin{matrix} f_{T1} & f_{T2} & f_{T3} \\ \begin{matrix} w_1 \\ w_2 \\ w_3 \end{matrix} \left( \begin{array}{c} X_F(S^T, M^T) \end{array} \right) \end{matrix} \\ & \begin{matrix} f_{T1} & f_{T2} & f_{T3} \\ \begin{matrix} w_1 \\ w_2 \\ w_3 \end{matrix} \left( \begin{array}{c} M^T \end{array} \right) \end{matrix} + \begin{matrix} f_{T1} & f_{T2} & f_{T3} \\ \begin{matrix} w_1 \\ w_2 \\ w_3 \end{matrix} \left( \begin{array}{c} X_F(S^T, M^T) \end{array} \right) \end{matrix} = \begin{matrix} f_{T1} & f_{T2} & f_{T3} \\ \begin{matrix} w_1 \\ w_2 \\ w_3 \end{matrix} \left( \begin{array}{c} L(M^T, X_F(S^T, M^T)) \end{array} \right) \end{matrix} \end{aligned}$$

# Combining Features and Dealing with Sparsity

## Hybrid Fusion

$$E(M_L, E(E(M^T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L))))$$

$$E(M^T, L(M^T, X_F(S^T, M^T)))$$

$$\begin{matrix} w_1 \\ w_2 \\ w_3 \end{matrix} \begin{pmatrix} f_{T1} f_{T2} f_{T3} \\ M^T \end{pmatrix} \parallel \begin{matrix} w_1 \\ w_2 \\ w_3 \end{matrix} \begin{pmatrix} f_{T1} f_{T2} f_{T3} \\ L(M^T, X_F(S^T, M^T)) \end{pmatrix} = \begin{matrix} w_1 \\ w_2 \\ w_3 \end{matrix} \begin{pmatrix} f_{T1} f_{T2} f_{T3} \\ L(M^T, X_F(S^T, M^T)) \end{pmatrix}$$

$$E(M_L, E(E(M^T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L))))$$

$$E(M_L, E(E(M^T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L))))$$

$$\begin{aligned} & \begin{matrix} f_{L1} & f_{L2} & f_{L3} \\ w_1 & w_2 & w_3 \end{matrix} \left( \begin{matrix} M^T \end{matrix} \right) \parallel \begin{matrix} f_{L1} & f_{L2} & f_{L3} \\ w_1 & w_2 & w_3 \end{matrix} \left( E(E(M^T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L)))) \right) = \\ & \begin{matrix} f_{L1} & f_{L2} & f_{L3} \\ w_1 & w_2 & w_3 \end{matrix} \left( E(M_L, E(E(M^T, L(M^T, X_F(S^T, M^T))), L(M^L, X_F(S^S, M^L)))) \right) \end{aligned}$$

# **Contributions in Detail**

## **Finding Communities in the Network**

---

- **Language networks tend to be scale-free**

- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network

- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network
- **Seminal approaches**



- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network
- **Seminal approaches**
  - Hyperlex [Vó4]

- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network
- **Seminal approaches**
  - Hyperlex [VÓ4]
  - University of York (UoY) [KM07]

- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network
- **Seminal approaches**
  - Hyperlex [VÓ4]
  - University of York (UoY) [KM07]
- **Limitations of existing approaches**

- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network
- **Seminal approaches**
  - Hyperlex [VÓ4]
  - University of York (UoY) [KM07]
- **Limitations of existing approaches**
  - Single typed networks


- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network
- **Seminal approaches**
  - Hyperlex [VÓ4]
  - University of York (UoY) [KM07]
- **Limitations of existing approaches**
  - Single typed networks
  - Large number of parameters

- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network
- **Seminal approaches**
  - Hyperlex [VÓ4]
  - University of York (UoY) [KM07]
- **Limitations of existing approaches**
  - Single typed networks
  - Large number of parameters
- **Proposition**

- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network
- **Seminal approaches**
  - Hyperlex [VÓ4]
  - University of York (UoY) [KMo7]
- **Limitations of existing approaches**
  - Single typed networks
  - Large number of parameters
- **Proposition**
  - Be able to exploit different types of linguistic information (lexical or syntactic co-occurrence)

- **Language networks tend to be scale-free**
  - There are certain nodes (hubs) that are very well connected forming communities within the network
- **Seminal approaches**
  - Hyperlex [VÓ4]
  - University of York (UoY) [KMo7]
- **Limitations of existing approaches**
  - Single typed networks
  - Large number of parameters
- **Proposition**
  - Be able to exploit different types of linguistic information (lexical or syntactic co-occurrence)
  - Keep the number of parameters low and allow for their automatic adjusting according to the network's nature





# **Applications to NLP**

## **Hypergraph Model Instantiation**

---

# Hypergraph Model Instantiation

- **Apply our proposed linguistic model to a real world corpus**

# Hypergraph Model Instantiation

- **Apply our proposed linguistic model to a real world corpus**
  - Use the English Wikipedia as input and generate a textual structure following the proposed network model

# Hypergraph Model Instantiation

- **Apply our proposed linguistic model to a real world corpus**
  - Use the English Wikipedia as input and generate a textual structure following the proposed network model
- **We provide two resources**

# Hypergraph Model Instantiation

- **Apply our proposed linguistic model to a real world corpus**
  - Use the English Wikipedia as input and generate a textual structure following the proposed network model
- **We provide two resources**
  - A syntactically annotated English Wikipedia corpus (SAEWD)

- **Apply our proposed linguistic model to a real world corpus**
  - Use the English Wikipedia as input and generate a textual structure following the proposed network model
- **We provide two resources**
  - A syntactically annotated English Wikipedia corpus (SAEWD)
  - An Wikipedia-based enriched hypergraph linguistic model


# Hypergraph Model Instantiation

- **Apply our proposed linguistic model to a real world corpus**
  - Use the English Wikipedia as input and generate a textual structure following the proposed network model
- **We provide two resources**
  - A syntactically annotated English Wikipedia corpus (SAEWD)
  - An Wikipedia-based enriched hypergraph linguistic model
- **Steps performed**



# Hypergraph Model Instantiation

- **Apply our proposed linguistic model to a real world corpus**
  - Use the English Wikipedia as input and generate a textual structure following the proposed network model
- **We provide two resources**
  - A syntactically annotated English Wikipedia corpus (SAEWD)
  - An Wikipedia-based enriched hypergraph linguistic model
- **Steps performed**



# Hypergraph Model Instantiation

## SAEWD: Parsed sample

FILENAME wiki\_00.parsed

token	lemma	POS	constituency	head	dependency
%%#PAGE Anarchism					
:	:	:	:	:	:
%%#SEN 25 9					
A	a	DT	NP_22,S_97	3	det
great	great	JJ	NP_22,S_97	3	amod
brigand	brigand	NN	NP_22,S_97	4	nsubj
becomes	become	VBZ	VP_44,S_97	0	root
a	a	DT	NP_18,NP_20,VP_44,S_97	6	det
ruler	ruler	NN	NP_18,NP_20,VP_44,S_97	4	xcomp
of	of	IN	PP_57,NP_20,VP_44,S_97	9	case
a	a	DT	NP_18,PP_57,NP_20,VP_44,S_97	9	det
Nation	nation	NN	NP_18,PP_57,NP_20,VP_44,S_97	6	nmod

# Hypergraph Model Instantiation

## Hypergraph Incidence Matrix

		CONSTITUENT			DEPENDENCY	SENTENCE
		NP <sub>1</sub> DT:NN	NP <sub>2</sub> NP:PP:PP	NP <sub>3</sub> NNS	nsubj contains      dobj contains	S <sub>1</sub>
NN	report	1			1	1
	copies		1	1	1	1
	minutes		1			1
	meetings		1			1
VB	contains					1

Hypergraph Model Instantiation

Wikipedia Feature Enriched Space

	Lexical Features (5.49%) $M^L$	Syntactic Features (4.97%) $M^S$	Early Fusion (5.23%) $E(M^L, M^S)$	$X_F$ Fusion (16.75%) $X_F(S^S, M^L)$	$X_F$ Fusion (13.45%) $X_F(S^L, M^S)$
priest	priests	monk	sailor	vassal	sailor
	nun	regent	regent	regent	fluent
	canton	aedile	nuclei	nun	dean
	sailor	seer	nun	sailor	nuclei
	burial	meek	relic	monk	chorus

# **Applications to NLP**

## **Solving Named Entity Recognition**

---

- **NER Objective**

- **NER Objective**

- The goal is to automatically discover mentions that belong to a well-defined semantic category.

- **NER Objective**

- The goal is to automatically discover mentions that belong to a well-defined semantic category.

- **Classic entities types**



- **NER Objective**

- The goal is to automatically discover mentions that belong to a well-defined semantic category.

- **Classic entities types**

- Location (LOC)

- **NER Objective**

- The goal is to automatically discover mentions that belong to a well-defined semantic category.

- **Classic entities types**

- Location (LOC)
- Organization (ORG)

- **NER Objective**

- The goal is to automatically discover mentions that belong to a well-defined semantic category.

- **Classic entities types**

- Location (LOC)
- Organization (ORG)
- Person (PER)

- **NER Objective**

- The goal is to automatically discover mentions that belong to a well-defined semantic category.

- **Classic entities types**

- Location (LOC)
- Organization (ORG)
- Person (PER)
- Miscellaneous (MISC)

- **NER Objective**

- The goal is to automatically discover mentions that belong to a well-defined semantic category.

- **Classic entities types**

- Location (LOC)
- Organization (ORG)
- Person (PER)
- Miscellaneous (MISC)
- **None (O)**

- **NER Objective**

- The goal is to automatically discover mentions that belong to a well-defined semantic category.

- **Classic entities types**

- Location (LOC)
- Organization (ORG)
- Person (PER)
- Miscellaneous (MISC)
- None (O)

- **Our goal**

- **NER Objective**

- The goal is to automatically discover mentions that belong to a well-defined semantic category.

- **Classic entities types**

- Location (LOC)
- Organization (ORG)
- Person (PER)
- Miscellaneous (MISC)
- None (O)

- **Our goal**

- We assess the effectiveness of the classic fusion methods and propose new hybrid combinations

## Representation Spaces

## Lexical Space (L)

Word	Features
Australian	word:Australian, word+1:scientist, word+2:discovers
scientist	word-1:Australian, word:scientist, word+1:discovers, word+2:star
discovers	word-2:Australian, word-1:scientist, . . . , word+2:telescope
star	word-2:scientist, word-1:discovers, word:star, . . . , word+2:telescope
with	word-2:discovers, word-1:star, word:with, word+1:telescope
telescope	word-2:star, word-1:with, word:telescope



### Syntactic Space (S)

Word	Contexts
Australian	scientist/NN/amod_inv
scientist	Australian/JJ/amod, discovers/VBZ/nsubj_inv
discovers	scientist/NN/nsubj, star/NN/dobj, telescope/NN/nmod:with
star	discovers/VBZ/dobj_inv
telescope	discovers/VBZ/nmod:with_inv

### Standard Features Space (T)

- Each word
- Whether it is capitalized
- Prefix and suffix (of each word their surroundings)
- Part of Speech tag

# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**

# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**
  - Normalize numbers

# Experimental Protocol

- **Preprocessing**
  - Normalize numbers
- **Test Corpora**

# Experimental Protocol

- **Preprocessing**
  - Normalize numbers
- **Test Corpora**
  - CoNLL-2003 (CONLL) [SMO3]: Train: 219,554 lines. Test: 50,350

# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**

- Normalize numbers

- **Test Corpora**

- CoNLL-2003 (CONLL) [SM03]: Train: 219,554 lines. Test: 50,350
- Wikiner (WNER) [NMCo9]: No Train/Test split. 3.5 million words.  
Evaluated in a 5-fold CV

# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**

- Normalize numbers

- **Test Corpora**

- CoNLL-2003 (CONLL) [SM03]: Train: 219,554 lines. Test: 50,350
- Wikiner (WNER) [NMCo9]: No Train/Test split. 3.5 million words. Evaluated in a 5-fold CV
- Wikigold (WGLD) [Bal+09]: No Train/Test split. 41,011 words. Evaluated in a 5-fold CV



# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**

- Normalize numbers

- **Test Corpora**

- CoNLL-2003 (CONLL) [SM03]: Train: 219,554 lines. Test: 50,350
- Wikiner (WNER) [NMCo9]: No Train/Test split. 3.5 million words.  
Evaluated in a 5-fold CV
- Wikigold (WGLD) [Bal+09]: No Train/Test split. 41,011 words.  
Evaluated in a 5-fold CV

- **Annotation Scheme**

# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**

- Normalize numbers

- **Test Corpora**

- CoNLL-2003 (CONLL) [SMo3]: Train: 219,554 lines. Test: 50,350
- Wikiner (WNER) [NMCo9]: No Train/Test split. 3.5 million words.  
Evaluated in a 5-fold CV
- Wikigold (WGLD) [Bal+09]: No Train/Test split. 41,011 words.  
Evaluated in a 5-fold CV

- **Annotation Scheme**

- **Beginning, Inside, Outside**

# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**

- Normalize numbers

- **Test Corpora**

- CoNLL-2003 (CONLL) [SMo3]: Train: 219,554 lines. Test: 50,350
- Wikiner (WNER) [NMCo9]: No Train/Test split. 3.5 million words. Evaluated in a 5-fold CV
- Wikigold (WGLD) [Bal+09]: No Train/Test split. 41,011 words. Evaluated in a 5-fold CV

- **Annotation Scheme**

- **Beginning, Inside, Outside**

- **Learning Algorithm**

# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**

- Normalize numbers

- **Test Corpora**

- CoNLL-2003 (CONLL) [SMo3]: Train: 219,554 lines. Test: 50,350
- Wikiner (WNER) [NMCo9]: No Train/Test split. 3.5 million words. Evaluated in a 5-fold CV
- Wikigold (WGLD) [Bal+09]: No Train/Test split. 41,011 words. Evaluated in a 5-fold CV

- **Annotation Scheme**

- **B**eginning, **I**nside, **O**utside

- **Learning Algorithm**

- Structured Perceptron [Colo2]

# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**

- Normalize numbers

- **Test Corpora**

- CoNLL-2003 (CONLL) [SMo3]: Train: 219,554 lines. Test: 50,350
- Wikiner (WNER) [NMCo9]: No Train/Test split. 3.5 million words. Evaluated in a 5-fold CV
- Wikigold (WGLD) [Bal+09]: No Train/Test split. 41,011 words. Evaluated in a 5-fold CV

- **Annotation Scheme**

- **B**eginning, **I**nside, **O**utside

- **Learning Algorithm**

- Structured Perceptron [Colo2]

- **Evaluation Metrics**

# Solving Named Entity Recognition

## Experimental Protocol

- **Preprocessing**

- Normalize numbers

- **Test Corpora**

- CoNLL-2003 (CONLL) [SM03]: Train: 219,554 lines. Test: 50,350
- Wikiner (WNER) [NMCo9]: No Train/Test split. 3.5 million words.  
Evaluated in a 5-fold CV
- Wikigold (WGLD) [Bal+09]: No Train/Test split. 41,011 words.  
Evaluated in a 5-fold CV

- **Annotation Scheme**

- **B**eginning, **I**nside, **O**utside

- **Learning Algorithm**

- Structured Perceptron [Colo2]

- **Evaluation Metrics**

- Precision, Recall, F-measure

# Solving Named Entity Recognition

## Evaluation

A    B		Early Fusion (EF)		
		CONLL	WNER	WGLD
M <sup>L</sup>	M <sup>S</sup>	72.01	70.59	59.38
M <sup>L</sup>	M <sup>T</sup>	78.13	79.78	61.96
M <sup>S</sup>	M <sup>T</sup>	77.70	78.10	60.93
M <sup>L</sup>	E(M <sup>S</sup> , M <sup>T</sup> )	<b>78.90</b>	<b>80.04</b>	<b>63.20</b>
		Late Fusion (LF)		
		CONLL	WNER	WGLD
S <sup>L</sup>	S <sup>S</sup>	<b>61.65</b>	58.79	44.29
S <sup>L</sup>	S <sup>T</sup>	55.64	<b>67.70</b>	48.00
S <sup>S</sup>	S <sup>T</sup>	50.21	58.41	<b>49.81</b>

# Solving Named Entity Recognition

## Evaluation

A	B	Early Fusion (EF)		
		CONLL	WNER	WGLD
$M^L$	$M^S$	72.01	70.59	59.38
$M^L$	$M^T$	78.13	79.78	61.96
$M^S$	$M^T$	77.70	78.10	60.93
$M^L$	$E(M^S, M^T)$	<b>78.90</b>	<b>80.04</b>	<b>63.20</b>
		Late Fusion (LF)		
		CONLL	WNER	WGLD
$S^L$	$S^S$	<b>61.65</b>	58.79	44.29
$S^L$	$S^T$	55.64	<b>67.70</b>	48.00
$S^S$	$S^T$	50.21	58.41	<b>49.81</b>

Cross Feature Fusion ( $X_F F$ )				
		CONLL	WNER	WGLD
$S^L$	$M^T$	49.90	<b>70.27</b>	<b>62.69</b>
$S^S$	$M^T$	47.27	51.38	48.53
$S^T$	$b_{X_F F}^*$	<b>52.89</b>	62.21	50.15
Cross Similarity Fusion ( $X_S F$ )				
		CONLL	WNER	WGLD
$S^L$	$S^T$	27.75	<b>59.12</b>	38.35
$S^S$	$b_{X_S F}^*$	36.87	40.92	39.62
$S^T$	$b_{X_S F}^*$	<b>41.89</b>	52.03	<b>39.92</b>

$$b_{X_F F}^* \in \{M^L, M^T\}$$

$$b_{X_S F}^* \in \{S^L, S^S\}$$



## Solving Named Entity Recognition Evaluation



# Solving Named Entity Recognition

## Evaluation



		Triple Early Double Late Cross Feature Fusion (EEELX <sub>F</sub> LX <sub>F</sub> )		
		CONLL	WNER	WGLD
$M^L$	$\hat{b}_{EEELX_F LX_F}$	65.01	78.02	62.34
$M^L_{\alpha=0.95}$	$\hat{b}_{EEELX_F LX_F}$	<b>79.67</b>	<b>81.79</b>	<b>67.05</b>
EF Baseline		78.90	80.04	63.20

### Analyzing the Best Fusion Operator

- **Understand how the evolution towards and enriched space helps the model take the correct decision**

# Analyzing the Best Fusion Operator

- **Understand how the evolution towards and enriched space helps the model take the correct decision**
  - Decompose the large fusion operator into 4 separate representations

### Analyzing the Best Fusion Operator

- **Understand how the evolution towards and enriched space helps the model take the correct decision**
  - Decompose the large fusion operator into 4 separate representations
  - Train a model with each individual operator (4 models:  $M_1$ ,  $M_2$ ,  $M_3$ ,  $M_4$ )

### Analyzing the Best Fusion Operator

- **Understand how the evolution towards and enriched space helps the model take the correct decision**
  - Decompose the large fusion operator into 4 separate representations
  - Train a model with each individual operator (4 models:  $M_1$ ,  $M_2$ ,  $M_3$ ,  $M_4$ )
  - Investigate how the features added at each step help the model predict the correct class

## Analyzing the Best Fusion Operator

- **Understand how the evolution towards and enriched space helps the model take the correct decision**
  - Decompose the large fusion operator into 4 separate representations
  - Train a model with each individual operator (4 models:  $M_1, M_2, M_3, M_4$ )
  - Investigate how the features added at each step help the model predict the correct class

The diagram illustrates the decomposition of a fusion operator into four components, labeled 1, 2, 3, and 4, using curly braces and circled numbers.


- Component 1:**  $M^L$
- Component 2:**  $M^T$
- Component 3:**  $L(M^T, X_F(S^S, M^T))$
- Component 4:**  $L(M^L, X_F(S^S, M^L))$

The full expression is  $E_{\alpha=0.95}(\underbrace{M^L}_{1}, \underbrace{M^T}_{2}, \underbrace{L(M^T, X_F(S^S, M^T))}_{3}, \underbrace{L(M^L, X_F(S^S, M^L))}_{4})$ .

# Solving Named Entity Recognition

## Analyzing the Best Fusion Operator

We focus on the word *Kory*, and its performance from model  $M_1$  to  $M_2$






# Solving Named Entity Recognition

## Analyzing the Best Fusion Operator

We focus on the word *Green*, and its performance from model  $M_3$  to  $M_4$



# **Applications to NLP**

## **Solving Word Sense Induction and Disambiguation**

---

- **WSI/WSD Objective**

- **WSI/WSD Objective**

- The goal is to determine a set of possible senses to a given word according to its possible contexts (WSI). Then, assigning a correct sense to a particular instance of said word

- **WSI/WSD Objective**

- The goal is to determine a set of possible senses to a given word according to its possible contexts (WSI). Then, assigning a correct sense to a particular instance of said word

- **Our goal**

- **WSI/WSD Objective**

- The goal is to determine a set of possible senses to a given word according to its possible contexts (WSI). Then, assigning a correct sense to a particular instance of said word

- **Our goal**

- Again, to assess the effectiveness of the fusion enriched spaces and to evaluate the pertinence of our community discovering algorithm

## Experimental Protocol

- **Preprocessing**

- Remove very frequent and very infrequent words

- **Test Corpora**

- Semeval 2007 [SM03]: Train: 219,554 lines. Test: 50,350

- **Clustering Algorithm**

- Spectral Clustering [SM00]
- Proposed Community Algorithm

- **Evaluation Metrics**

- Supervised Recall
- Unsupervised F-measure
- Proposed: H-measure

$$\text{H-measure} = \frac{1}{2} \left( 2 * \frac{\text{SR} * \text{UF}}{\text{SR} + \text{UF}} + \frac{\delta}{\delta + |\#\text{cl} - \delta|} \right)$$

$\delta$  is the average true number of senses of the words in a test corpus

# Solving Word Sense Induction and Disambiguation

## Spectral Clustering Evaluation

Cross Feature Cross Similarity Fusion ( $X_F X_S F$ )				
$X_F(X_S(S^L, S^S), M^L)$	78.40	80.40	76.10	3.11
$X_F(X_S(S^L, S^S), M^S)$	78.90	81.80	75.60	3.16
Early Cross Feature Fusion ( $EX_F F$ )				
$E(M^L, X_F(S^L, M^L))$	79.20	82.40	75.70	3.57
$E(M^S, X_F(S^L, M^L))$	78.30	80.50	75.80	1.95
Late Cross Feature Fusion ( $LX_F F$ )				
$L(M^S, X_F(S^L, M^S))$	78.60	81.10	75.80	4.22
$L(M^L, X_F(S^L, M^L))$	79.50	82.80	75.70	3.96
Early Late Cross Feature Fusion ( $ELX_F F$ )				
$E(M^L, L(M^S, X_F(S^L, M^S)))$	78.50	81.40	75.40	4.26
$E(M^L, L(M^L, X_F(S^L, M^L)))$	79.50	82.70	75.90	3.99
Baseline MFS	78.70	80.90	76.20	1.00

Figure 1: Supervised Recall



# Solving Word Sense Induction and Disambiguation

## Spectral Clustering Evaluation

Cross Feature Cross Similarity Fusion (X <sub>F</sub> X <sub>S</sub> F)				
X <sub>F</sub> (X <sub>S</sub> (S <sup>L</sup> , S <sup>S</sup> ), M <sup>L</sup> )	78.40	80.40	76.10	3.11
X <sub>F</sub> (X <sub>S</sub> (S <sup>L</sup> , S <sup>S</sup> ), M <sup>S</sup> )	78.90	81.80	75.60	3.16
Early Cross Feature Fusion (EX <sub>F</sub> F)				
E(M <sup>L</sup> , X <sub>F</sub> (S <sup>L</sup> , M <sup>L</sup> ))	79.20	82.40	75.70	3.57
E(M <sup>S</sup> , X <sub>F</sub> (S <sup>L</sup> , M <sup>L</sup> ))	78.30	80.50	75.80	1.95
Late Cross Feature Fusion (LX <sub>F</sub> F)				
L(M <sup>S</sup> , X <sub>F</sub> (S <sup>L</sup> , M <sup>S</sup> ))	78.60	81.10	75.80	4.22
L(M <sup>L</sup> , X <sub>F</sub> (S <sup>L</sup> , M <sup>L</sup> ))	<b>79.50</b>	<b>82.80</b>	75.70	3.96
Early Late Cross Feature Fusion (ELX <sub>F</sub> F)				
E(M <sup>L</sup> , L(M <sup>S</sup> , X <sub>F</sub> (S <sup>L</sup> , M <sup>S</sup> )))	78.50	81.40	75.40	4.26
E(M <sup>L</sup> , L(M <sup>L</sup> , X <sub>F</sub> (S <sup>L</sup> , M <sup>L</sup> )))	<b>79.50</b>	82.70	75.90	3.99
Baseline MFS	78.70	80.90	76.20	1.00


Figure 1: Supervised Recall

Early Fusion (EF)				
E(M <sup>L</sup> , M <sup>S</sup> )	74.00	76.66	71.11	4.46
Cross Feature Fusion (X <sub>F</sub> F)				
X <sub>F</sub> (S <sup>L</sup> , M <sup>L</sup> )	76.20	79.60	72.50	3.63
X <sub>F</sub> (S <sup>L</sup> , M <sup>S</sup> )	74.60	75.10	73.90	3.08
X <sub>F</sub> (S <sup>S</sup> , M <sup>L</sup> )	<b>78.90</b>	80.70	<b>76.90</b>	1.08
X <sub>F</sub> (S <sup>S</sup> , M <sup>S</sup> )	73.70	77.70	70.00	2.72
Cross Similarity Fusion (X <sub>S</sub> F)				
X <sub>S</sub> (S <sup>S</sup> , S <sup>L</sup> )	<b>78.90</b>	<b>80.80</b>	76.80	1.01
X <sub>S</sub> (S <sup>L</sup> , S <sup>S</sup> )	78.70	80.50	76.80	1.33

Figure 2: Unsupervised F-measure

# Solving Word Sense Induction and Disambiguation

## Spectral Clustering Evaluation



# Solving Word Sense Induction and Disambiguation

## Proposed Algorithm Evaluation

	Early Fusion (EF)			
$E(M^L, M^S)$	78.80	81.00	<b>76.40</b>	2.43
	Cross Feature Fusion ( $X_F$ F)			
$X_F(S^L, M^L)$	78.70	80.90	76.20	3.11
$X_F(S^L, M^S)$	78.50	81.10	75.60	1.92
$X_F(S^S, M^L)$	<b>79.10</b>	<b>81.60</b>	<b>76.40</b>	1.73
$X_F(S^S, M^S)$	78.60	80.90	76.00	1.81
	Cross Similarity Fusion ( $X_S$ F)			
$X_S(S^S, S^L)$	78.60	80.80	76.20	1.44
$X_S(S^L, S^S)$	78.70	80.90	76.20	1.10

**Figure 4:** Supervised Recall

# Solving Word Sense Induction and Disambiguation

## Proposed Algorithm Evaluation

Early Fusion (EF)				
$E(M^L, M^S)$	78.80	81.00	<b>76.40</b>	2.43
Cross Feature Fusion ( $X_F F$ )				
$X_F(S^L, M^L)$	78.70	80.90	76.20	3.11
$X_F(S^L, M^S)$	78.50	81.10	75.60	1.92
$X_F(S^S, M^L)$	<b>79.10</b>	<b>81.60</b>	<b>76.40</b>	1.73
$X_F(S^S, M^S)$	78.60	80.90	76.00	1.81
Cross Similarity Fusion ( $X_S F$ )				
$X_S(S^S, S^L)$	78.60	80.80	76.20	1.44
$X_S(S^L, S^S)$	78.70	80.90	76.20	1.10


**Figure 4:** Supervised Recall

Early Fusion (EF)				
$E(M^L, M^S)$	76.90	<b>80.20</b>	73.10	2.43
Cross Feature Fusion ( $X_F F$ )				
$X_F(S^L, M^L)$	71.00	68.10	74.20	3.11
$X_F(S^L, M^S)$	77.70	79.60	75.50	1.92
$X_F(S^S, M^L)$	75.20	75.50	74.90	1.73
$X_F(S^S, M^S)$	77.60	80.50	74.30	1.81
Cross Similarity Fusion ( $X_S F$ )				
$X_S(S^S, S^L)$	74.10	72.10	76.50	1.44
$X_S(S^L, S^S)$	<b>78.30</b>	79.70	<b>76.80</b>	1.10

**Figure 5:** Unsupervised F-measure

# Solving Word Sense Induction and Disambiguation

## Proposed Algorithm Evaluation



**Figure 6:** Proposed H-measure

# Conclusions

---

# Insights From our Contributions

- **Hypergraph Linguistic Model**

# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure



# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text

# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text
- **Combining Features and Dealing with Sparsity**

# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text
- **Combining Features and Dealing with Sparsity**
  - Using fusion operators

# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text
- **Combining Features and Dealing with Sparsity**
  - Using fusion operators
    - Intuitive way to leverage the different points of view of each heterogeneous feature while increasing the density of the representation

# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text
- **Combining Features and Dealing with Sparsity**
  - Using fusion operators
    - Intuitive way to leverage the different points of view of each heterogeneous feature while increasing the density of the representation
- **Applications to NLP**

# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text
- **Combining Features and Dealing with Sparsity**
  - Using fusion operators
    - Intuitive way to leverage the different points of view of each heterogeneous feature while increasing the density of the representation
- **Applications to NLP**
  - Solving NER and WSI/WSD with fusion enriched representations and our community-driven algorithm

# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text
- **Combining Features and Dealing with Sparsity**
  - Using fusion operators
    - Intuitive way to leverage the different points of view of each heterogeneous feature while increasing the density of the representation
- **Applications to NLP**
  - Solving NER and WSI/WSD with fusion enriched representations and our community-driven algorithm
    - Enriched features are indeed useful compared to using single independent features

# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text
- **Combining Features and Dealing with Sparsity**
  - Using fusion operators
    - Intuitive way to leverage the different points of view of each heterogeneous feature while increasing the density of the representation
- **Applications to NLP**
  - Solving NER and WSI/WSD with fusion enriched representations and our community-driven algorithm
    - Enriched features are indeed useful compared to using single independent features
    - A high degree combination of fusion operators are the ones that yield the improvements



- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text
- **Combining Features and Dealing with Sparsity**
  - Using fusion operators
    - Intuitive way to leverage the different points of view of each heterogeneous feature while increasing the density of the representation
- **Applications to NLP**
  - Solving NER and WSI/WSD with fusion enriched representations and our community-driven algorithm
    - Enriched features are indeed useful compared to using single independent features
    - A high degree combination of fusion operators are the ones that yield the improvements
    - The community finding algorithm improves over similar algorithms while being simpler and allows for heterogeneous features

# Insights From our Contributions

- **Hypergraph Linguistic Model**
  - Considering heterogeneous features to link words together at once using a hypergraph structure
    - Yields a multi-layered representation of text
- **Combining Features and Dealing with Sparsity**
  - Using fusion operators
    - Intuitive way to leverage the different points of view of each heterogeneous feature while increasing the density of the representation
- **Applications to NLP**
  - Solving NER and WSI/WSD with fusion enriched representations and our community-driven algorithm
    - Enriched features are indeed useful compared to using single independent features
    - A high degree combination of fusion operators are the ones that yield the improvements
    - The community finding algorithm improves over similar algorithms while being simpler and allows for heterogeneous features
    - The Wikipedia-based instantiation serves as a NLP system starting

- **Hypergraph Linguistic Model**

- **Hypergraph Linguistic Model**
  - Implementing a dataframe-like structure allowing for queries and exploration of large corpora using the proposed model

- **Hypergraph Linguistic Model**
  - Implementing a dataframe-like structure allowing for queries and exploration of large corpora using the proposed model
- **Combining Features and Dealing with Sparsity**

- **Hypergraph Linguistic Model**
  - Implementing a dataframe-like structure allowing for queries and exploration of large corpora using the proposed model
- **Combining Features and Dealing with Sparsity**
  - Finding a more principled way to determine what type of context with what type of fusion operation according to the task at hand

- **Hypergraph Linguistic Model**
  - Implementing a dataframe-like structure allowing for queries and exploration of large corpora using the proposed model
- **Combining Features and Dealing with Sparsity**
  - Finding a more principled way to determine what type of context with what type of fusion operation according to the task at hand
  - Exploring with other modal features

- **Hypergraph Linguistic Model**
  - Implementing a dataframe-like structure allowing for queries and exploration of large corpora using the proposed model
- **Combining Features and Dealing with Sparsity**
  - Finding a more principled way to determine what type of context with what type of fusion operation according to the task at hand
  - Exploring with other modal features
- **Applications to NLP**



- **Hypergraph Linguistic Model**
  - Implementing a dataframe-like structure allowing for queries and exploration of large corpora using the proposed model
- **Combining Features and Dealing with Sparsity**
  - Finding a more principled way to determine what type of context with what type of fusion operation according to the task at hand
  - Exploring with other modal features
- **Applications to NLP**
  - Using the large Wikipedia-based network as a background corpus to further enrich domain-specific corpora

- **Hypergraph Linguistic Model**
  - Implementing a dataframe-like structure allowing for queries and exploration of large corpora using the proposed model
- **Combining Features and Dealing with Sparsity**
  - Finding a more principled way to determine what type of context with what type of fusion operation according to the task at hand
  - Exploring with other modal features
- **Applications to NLP**
  - Using the large Wikipedia-based network as a background corpus to further enrich domain-specific corpora
  - Test more feature weighting schemes, validate findings on more datasets

# Publications Produced by Our Research

- Edmundo-Pavel Soriano-Morales, Julien Ah-Pine, Sabine Loudcher: **Fusion Techniques for Named Entity Recognition and Word Sense Induction and Disambiguation**. DS 2017
- Edmundo-Pavel Soriano-Morales, Julien Ah-Pine, Sabine Loudcher: **Using a Heterogeneous Linguistic Network for Word Sense Induction and Disambiguation**. CICLING 2016
- Edmundo-Pavel Soriano-Morales, Julien Ah-Pine, Sabine Loudcher: **Hypergraph Modelization of a Syntactically Annotated English Wikipedia Dump**. LREC 2016
- Adrien Guille, Edmundo-Pavel Soriano-Morales, Ciprian-Octavian Truica: **Topic modeling and hypergraph mining to analyze the EGC conference history**. EGC 2016
- Adrien Guille, Edmundo-Pavel Soriano-Morales: **TOM: A library for topic modeling and browsing**. EGC 2016:

- Julien Ah-Pine, Edmundo-Pavel Soriano-Morales: **A Study of Synthetic Oversampling for Twitter Imbalanced Sentiment Analysis**. DMNLP@PKDD/ECML 2016
- Sabine Loudcher, Wararat Jakawat, Edmundo-Pavel Soriano-Morales, Cécile Favre: **Combining OLAP and information networks for bibliographic data analysis: a survey**. Scientometrics 103(2)

Thank you for your attention

## References

---



Christopher D Manning, Hinrich Schütze, et al.  
*Foundations of statistical natural language processing*.  
Vol. 999. MIT Press, 1999.



Jianbo Shi and Jitendra Malik. “Normalized Cuts and Image Segmentation”. In: *IEEE Trans. Pattern Anal. Mach. Intell.* 22.8 (Aug. 2000), pp. 888–905. ISSN: 0162-8828. DOI: 10.1109/34.868688. URL: <http://dx.doi.org/10.1109/34.868688>.



Michael Collins. “Discriminative Training Methods for Hidden Markov Models: Theory and Experiments with Perceptron Algorithms”. In: *Proceedings of the ACL-02 Conference on Empirical Methods in Natural Language Processing - Volume 10*. EMNLP '02. Stroudsburg, PA, USA: Association for Computational Linguistics, 2002, pp. 1–8. DOI: 10.3115/1118693.1118694.



Erik F. Tjong Kim Sang and Fien De Meulder. “Introduction to the CoNLL-2003 Shared Task: Language-Independent Named Entity Recognition”. In: *CoNLL*. ACL, 2003, pp. 142–147.



Rada Mihalcea, Paul Tarau, and Elizabeth Figa. “PageRank on Semantic Networks, with Application to Word Sense Disambiguation”. In: *Proceedings of the 20th International Conference on Computational Linguistics*. COLING '04. Geneva, Switzerland: Association for Computational Linguistics, 2004. DOI: 10.3115/1220355.1220517.



Jean Véronis. “HyperLex: lexical cartography for information retrieval”. In: *Computer Speech & Language* 18.3 (2004), pp. 223 –252. ISSN: 0885-2308. DOI: 10.1016/j.cs1.2004.05.002.





Ioannis P. Klapaftis and Suresh Manandhar. “UOY: A Hypergraph Model for Word Sense Induction & Disambiguation”. In: *Proceedings of the 4th International Workshop on Semantic Evaluations*. SemEval '07. Prague, Czech Republic: Association for Computational Linguistics, 2007, pp. 414–417.



Ioannis P. Klapaftis and Suresh Manandhar. “Word Sense Induction Using Graphs of Collocations”. In: *Proceedings of the 2008 Conference on ECAI 2008: 18th European Conference on Artificial Intelligence*. Amsterdam, The Netherlands, The Netherlands: IOS Press, 2008, pp. 298–302. ISBN: 978-1-58603-891-5.



Dominic Balasuriya et al. “Named Entity Recognition in Wikipedia”. In: *Proceedings of the 2009 Workshop on The People’s Web Meets NLP: Collaboratively Constructed Semantic Resources*. People’s Web ’09. Suntec, Singapore: Association for Computational Linguistics, 2009, pp. 10–18. ISBN: 978-1-932432-55-8. URL: <http://dl.acm.org/citation.cfm?id=1699765.1699767>.



Monojit Choudhury and Animesh Mukherjee. “The Structure and Dynamics of Linguistic Networks”. English. In: *Dynamics On and Of Complex Networks*. Ed. by Niloy Ganguly, Andreas Deutsch, and Animesh Mukherjee. Modeling and Simulation in Science, Engineering and Technology. Birkhäuser Boston, 2009, pp. 145–166. ISBN: 978-0-8176-4750-6. DOI: 10.1007/978-0-8176-4751-3\_9.



Joel Nothman, Tara Murphy, and James R. Curran. “Analysing Wikipedia and Gold-standard Corpora for NER Training”. In: *Proceedings of the 12th Conference of the European Chapter of the Association for Computational Linguistics*. EACL '09. Athens, Greece: Association for Computational Linguistics, 2009, pp. 612–620.



Yong-Yeol Ahn, James P Bagrow, and Sune Lehmann. “Link communities reveal multiscale complexity in networks”. In: *Nature* 466.7307 (2010), pp. 761–764.



Pradeep K. Atrey et al. “Multimodal fusion for multimedia analysis: a survey”. In: *Multimedia Syst.* 16.6 (2010), pp. 345–379.



Rada F. Mihalcea and Dragomir R. Radev. *Graph-based Natural Language Processing and Information Retrieval*. 1st. New York, NY, USA: Cambridge University Press, 2011. ISBN: 0521896134, 9780521896139.