

Formalizing colimits in *Cat*

Mario Carneiro  

Chalmers University of Technology, Sweden

Emily Riehl¹  

Department of Mathematics, Johns Hopkins University, 3400 N Charles Street, Baltimore, MD, USA

Abstract

Certain results involving “higher structures” are not currently accessible to computer formalization because the prerequisite ∞ -category theory has not been formalized. To support future work on formalizing ∞ -category theory in Lean’s mathematics library, we formalize some fundamental constructions involving the 1-category of categories. Specifically, we construct the left adjoint to the nerve embedding of categories into simplicial sets, defining the homotopy category functor. We prove further that this adjunction is reflective, which allows us to conclude that *Cat* has colimits. To our knowledge this is the first formalized proof that the category of categories is cocomplete.

2012 ACM Subject Classification Theory of computation \rightarrow Logic and verification

Keywords and phrases category theory, infinity-category theory, nerve, simplicial set, colimit

Funding *Emily Riehl*: NSF DMS-1652600, AFOSR FA9550-21-1-0009, ARO W911NF-20-1-0082

Acknowledgements This project was first instantiated at the 2024 Prospects of Formal Mathematics Trimester Program at the Hausdorff Institute for Mathematics in Bonn. The authors are grateful to the organizers of that program for facilitating many new collaborations and to the HIM for its hospitality. They also wish to thank Joël Riou for the excellent suggestions he made during the Mathlib PR review process.

¹ Corresponding author

Contents

- 1 Introduction** 3
- 2 The formalization** 6
 - 2.1 The 2-coskeletality of the nerve 7
 - 2.2 The 2-truncated nerve adjunction 9
- 3 Challenges** 14
 - 3.1 Bundling categories 14
 - 3.2 Equality of functors 15
 - 3.3 Proving functoriality 16
 - 3.4 Proving naturality 17
 - 3.5 Proving nerves are 2-coskeletal 18
- 4 Related work** 19
- 5 Future work** 21

1 Introduction

One of the myriad ways in which “category theory eats itself” is that the categorically-defined notions of limits and colimit can be interpreted in the category \mathbf{Cat} itself, whose objects are categories² and functors between them. Any suitably-small diagram of categories and functors has a *limit* in \mathbf{Cat} which is constructed by forming the limit of the corresponding diagrams of objects and hom-sets.³ For example, the *product* of two categories C and D is the category whose objects are defined as the product $\text{ob } C \times \text{ob } D$ of the types of objects of C and D . Given objects $c, c' : \text{ob } C$ and $d, d' : \text{ob } D$, the hom-type from (c, d) to (c', d') in the product category is the product $\text{Hom}_C(c, c') \times \text{Hom}_D(d, d')$ of the hom-types in C and D . The generalization of this construction to arbitrary diagram shapes is formalized in Lean’s `mathlib` as `Cat.instHasLimits` by Kim Morrison.

It is also the case that any suitably-small diagram in \mathbf{Cat} has a colimit, but the construction is considerably more complicated. To illustrate, consider the terminal category $\mathbf{Fin}(1)$ (with one object and only its identity arrow) and the walking arrow $\mathbf{Fin}(2)$ (with two objects 0 and 1 and a single non-identity morphism $\ell : 0 \rightarrow 1$). The *coequalizer* of the parallel pair of functors $0, 1 : \mathbf{Fin}(1) \rightarrow \mathbf{Fin}(2)$ that pick out these two objects is the category \mathbf{BN} with a single object but with a morphism for each natural number, with composition defined by addition and the morphism 0 serving as the identity. The quotient functor $q : \mathbf{Fin}(2) \rightarrow \mathbf{BN}$ sends the morphism ℓ to the generating non-identity morphism 1.



Given the much greater complexity involved in the construction of colimits in \mathbf{Cat} , it is perhaps unsurprising that none of the libraries of formal mathematics that currently exist in Agda [7, 14, 17, 32, 33], HOL Light [12], Isabelle [22, 23, 24, 27], Lean [21], or Rocq [3, 11, 34] contain a proof that \mathbf{Cat} is cocomplete. In particular, we discovered that this result was missing from Lean’s `mathlib` while attempting to formalize a theorem that is relevant to *∞ -category theory*, the extension of ordinary category theory to settings where there are “higher homotopies” between maps.⁴ When this project commenced in Summer 2024, `mathlib` contained an important 1-categorical pre-requisite to *∞ -category theory*, namely the construction of the

² An important point that is often elided on paper but is necessary to treat precisely in formalization is that the category of categories `Cat.{v,u}` is parametrized by two implicit universe levels, one `u` for the type of objects and one `v` for the hom-types.

³ The definition of *limit* is reviewed in §3.5; *colimits* are dual, formed by reversing the arrows.

⁴ As noted recently by the authors of [16], “myriad recent results from algebraic K-theory [5], derived and spectral algebraic geometry [18, 19], the Langlands program [9], and symplectic geometry [26] are inaccessible to formalization” because `mathlib` contains relatively few results from *∞ -category theory*.

nerve of a 1-category, formalized by Joël Riou. The nerve of a category C , is a *simplicial set*, a family of types $(\text{nerve } C_n)_{n:\mathbb{N}}$ equipped with various maps between them.⁵ Explicitly, $\text{nerve } C_n$ is the type of functors $\text{Fin}(n+1) \rightarrow C$, where $\text{Fin}(n+1)$ is the ordinal category with $n+1$ objects depicted below:

$$0 \longrightarrow 1 \longrightarrow \dots \longrightarrow n-1 \longrightarrow n$$

```

/-- 'ComposableArrows C n' is the type of functors 'Fin (n + 1) => C'. -/
abbrev ComposableArrows (n : ℕ) := Fin (n + 1) => C

/-- The nerve of a category -/
def nerve (C : Type) [Category C] : SSet where
  obj Δ := ComposableArrows C (Δ.unop.len)
  map f x := x.whiskerLeft (SimplexCategory.toCat.map f.unop)

```

Up to equivalence, $\text{nerve } C_0$ is the type of objects of C , $\text{nerve } C_1$ is the type of arrows of C , $\text{nerve } C_2$ is the type of composable pairs of arrows, and so on. In the presence of the “higher homotopies” alluded to above, this data is used to index “homotopy coherent diagrams” of shape C , incarnating the 1-category C as an ∞ -category.

The nerve construction defines a functor $\text{nerve} : \text{Cat} \rightarrow \text{Set}^{\Delta^{\text{op}}}$ valued in the category of simplicial sets. Our objective was to define its left adjoint $\text{ho} : \text{Set}^{\Delta^{\text{op}}} \rightarrow \text{Cat}$, a functor which takes a simplicial set to its *homotopy category*. This functor is used to collapse an ∞ -category to its quotient 1-category and will also be used to define the 2-category of ∞ -categories described in §5. As noted for instance in [30, 6.5.iv], this adjunction exists for formal reasons as a special case of a result which has already been formalized in [mathlib](#). Bhavik Mehta and Joël Riou formalized the construction of a general family of “Yoneda adjunctions”.⁶

► **Theorem 1** ([Presheaf.yonedaAdjunction](#)). *Suppose $A : \mathcal{A} \rightarrow \mathcal{E}$ is any functor, where \mathcal{A} is small and \mathcal{E} is cocomplete. Then the left Kan extension of A along the Yoneda embedding $\mathfrak{y} : \mathcal{A} \rightarrow \text{Set}^{\mathcal{A}^{\text{op}}}$ is left adjoint to the restricted Yoneda functor:*

$$\begin{array}{ccc}
 & \text{lan } \mathfrak{y} \, A & \\
 \mathcal{E} & \xleftarrow{\quad \perp \quad} & \text{Set}^{\mathcal{A}^{\text{op}}} \\
 & \mathcal{E}(A-, -) &
 \end{array}$$

The nerve adjunction is an example of a Yoneda adjunction defined relative to the functor [SimplexCategory.toCat](#) : $\Delta \rightarrow \text{Cat}$ which sends $n : \mathbb{N}$ to the ordinal

⁵ More precisely, a *simplicial set* is a contravariant functor indexed by the [SimplexCategory](#) Δ ; objects are natural numbers $n : \mathbb{N}$ commonly denoted by $[n]$ and morphisms $[m] \rightarrow [n]$ are defined in [SimplexCategory.Hom](#) to be order-preserving functions $\text{Fin}(m+1) \rightarrow \text{Fin}(n+1)$. The category [SSet](#) of simplicial sets is the functor category $\text{Set}^{\Delta^{\text{op}}}$.

⁶ We’ve simplified the statement here for readability. The only hypothesis that is actually required is that the left Kan extension of the functor A along the Yoneda embedding $\mathfrak{y} : \mathcal{A} \rightarrow \text{Set}^{\mathcal{A}^{\text{op}}}$ exists. In practice, one proves that this left Kan extension exists by showing that \mathcal{A} is small and \mathcal{E} is cocomplete.

category $\text{Fin}(n + 1)$. However, we could not apply this result because `mathlib` did not contain a proof that `Cat` has all colimits, only a proof that `Cat` has limits, which are far easier to construct. Consulting the literature again [30, 4.5.16], we were reminded that colimits in `Cat` can be constructed as a corollary of the adjunction we were hoping to define: since the nerve functor is fully faithful, the adjunction exhibits `Cat` as a reflective subcategory of a cocomplete category. Thus our new formalization objective was to give a direct proof of the following pair of results:

► **Theorem 2** (`nerveAdjunction`). *The nerve functor admits a left adjoint defined by the functor that sends a simplicial set to its homotopy category:*

$$\begin{array}{ccc} & \text{ho} & \\ \text{Cat} & \xleftarrow{\quad} & \text{Set}^{\Delta^{\text{op}}} \\ & \text{nerve} & \end{array}$$

► **Theorem 3** (`nerveFunctor.fullyfaithful`). *The nerve functor is full and faithful.*

A functor is *reflective* if it is a fully faithful right adjoint.

```

/-- A functor is reflective, or a reflective inclusion, if it is
    fully faithful and right adjoint. -/
class Reflective (R : D ⇒ C) extends R.Full, R.Faithful where
  /-- a choice of a left adjoint to 'R' -/
  L : C ⇒ D
  /-- 'R' is a right adjoint -/
  adj : L ⊣ R

```

As formalized by Kim Morrison, Jack McKoen, and Bhavik Mehta, any reflective subcategory of a cocomplete category has colimits.

```

/-- If 'C' has colimits then any reflective subcategory has colimits. -/
theorem hasColimits_of_reflective (R : D ⇒ C) [Reflective R]
  [HasColimits C] : HasColimits D := ...

```

Thus, as an immediate corollary of Theorems 2 and 3:⁷

```

/-- The category of small categories has all small colimits as a reflective
    subcategory of the category of simplicial sets, which has all small
    colimits. -/
instance : HasColimits Cat.{u, u} := hasColimits_of_reflective nerveFunctor

```

► **Corollary 4** (`Cat.instHasColimits`). *Cat is cocomplete.*

Proof. The presheaf category $\text{Set}^{\Delta^{\text{op}}}$ is cocomplete, with colimits defined object-wise in `Set`. On account of the adjunction with a fully faithful right adjoint

⁷ Most of the Lean statements here have been simplified to avoid asides about universes, but in this theorem statement it is important that we only assert the existence of *small* colimits, which is indicated by the use of universe `u` in both objects and homs.

$\mathcal{Cat} \begin{array}{c} \xleftarrow{\text{ho}} \\ \perp \\ \xrightarrow{\text{nerve}} \end{array} \mathbf{Set}^{\Delta^{\text{op}}}$, the reflective subcategory \mathcal{Cat} inherits these colimits, defined by taking the nerves of the categories in the original diagram, forming the colimit in $\mathbf{Set}^{\Delta^{\text{op}}}$, and then applying the homotopy category functor to the colimit cone. ◀

Importantly for aim of contributing to a general-purpose library, the construction given in the proof of Corollary 4 results in a good description of colimits in \mathcal{Cat} . Applied to the first example, Corollary 4 tells us to first form the coequalizer in simplicial sets

$$\Delta^0 \begin{array}{c} \xrightarrow{0} \\ \xrightarrow{1} \end{array} \Delta^1 \dashrightarrow^q S^1$$

and then take the homotopy category. As described in Definition 11 below, the homotopy category of S^1 is the free category defined by the underlying reflexive quiver — which has a single object and a single non-identity endo-arrow — modulo relations witnessed by non-degenerate 2-simplices. As the simplicial set S^1 has no non-degenerate 2-simplices, $\text{ho}(S^1) \cong \mathbf{BN}$ is the free category on a single non-identity endo-arrow, which is the category \mathbf{BN} described above. The construction for other diagram shapes is similar.

Other methods for proving that \mathcal{Cat} is cocomplete are discussed in §4, on related work. These methods typically invoke the theorem that a colimit of a diagram of any shape can be expressed as a coequalizer between two coproducts [20, V.2.2], so that it suffices to give explicit constructions of coproducts and coequalizers in \mathcal{Cat} . This works, but it results in more convoluted expressions for concrete colimits; for our running example, it would calculate the colimit \mathbf{BN} as the coequalizer of a pair of functors between the coproducts

$$\mathbf{Fin}(1) \sqcup \mathbf{Fin}(1) \sqcup \mathbf{Fin}(2) \rightrightarrows \mathbf{Fin}(1) \sqcup \mathbf{Fin}(2) \dashrightarrow \mathbf{BN}$$

which is more complicated than it needs to be.

In §2, we describe our formalizations of Theorems 2 and 3. After a PR process that took five and a half months, this entire formalization is now a part of [mathlib](#). In §3, we describe some challenges we encountered along the way. In §4, we discuss alternate theoretical approaches to the construction of colimits in \mathcal{Cat} and related formalization projects. In §5, we discuss plans for future work that will expand and apply these results.

2 The formalization

The formalized proof of our first main result, Theorem 2, which defines the left adjoint to the nerve functor, takes one line:

```
def nerveAdjunction : hoFunctor ⊣ nerveFunctor :=
  Adjunction.ofNatIsoRight ((SSet.coskAdj 2).comp nerve₂Adj)
  Nerve.cosk₂Iso.symm
```


For any functor valued in simplicial sets, we can obtain its n -truncated version by postcomposing with the functor $\text{tr}_n : \text{Set}^{\Delta^{\text{op}}} \rightarrow \text{Set}^{\Delta^{\text{op}}}_{\leq n}$. In particular, the 2-truncated nerve nerve_2 is defined to be the composite functor:

$$\text{nerve}_2 : \text{Cat} \xrightarrow{\text{nerve}} \text{Set}^{\Delta^{\text{op}}} \xrightarrow{\text{tr}_2} \text{Set}^{\Delta^{\text{op}}}_{\leq 2}.$$

```

/-- The essential data of the nerve functor is contained in the
    2-truncation, which is recorded by the composite functor
    'nerveFunction2'. -/
def nerveFunction2 : Cat => SSet.Truncated 2 := nerveFunction >>> truncation
2

```

The canonical natural transformation $v : \text{nerve} \Rightarrow \text{cosk}_2 \text{nerve}_2$ is defined by left whiskering the unit $\eta : \text{id} \Rightarrow \text{cosk}_2 \text{tr}_2$ of the adjunction $\text{tr}_2 \dashv \text{cosk}_2$ with the nerve functor:

$$\begin{array}{ccc}
 \text{Cat} & \xrightarrow{\text{nerve}_2} & \text{Set}^{\Delta^{\text{op}}}_{\leq 2} \\
 & \searrow \text{nerve} & \uparrow v \\
 & & \text{Set}^{\Delta^{\text{op}}}
 \end{array}
 \quad \text{cosk}_2 \quad
 \begin{array}{ccc}
 \text{Cat} & \xrightarrow{\text{nerve}_2} & \text{Set}^{\Delta^{\text{op}}}_{\leq 2} \\
 & \searrow \text{nerve} & \uparrow \eta \\
 & & \text{Set}^{\Delta^{\text{op}}}
 \end{array}
 \quad \text{cosk}_2$$

The natural transformation v is the underlying map of the isomorphism `Nerve.cosk2Iso`.

```

/-- The natural isomorphism between 'nerveFunction' and 'nerveFunction2 >>>
    Truncated.cosk 2' whose components 'nerve C ≅ (Truncated.cosk 2).obj
    (nerveFunction2.obj C)' show that nerves of categories are
    2-coskeletal. -/
def cosk2Iso : nerveFunction ≅ nerveFunction2 >>> Truncated.cosk 2 :=
  NatIso.ofComponents (fun C => (nerve C).isoCoskOfIsCoskeletal 2)
  (fun _ => (coskAdj 2).unit.naturality _)

/-- The canonical isomorphism 'X ≅ (cosk n).obj X' defined when X is
    coskeletal and the n-coskeleton functor exists. -/
def isoCoskOfIsCoskeletal [X.IsCoskeletal n] : X ≅ (cosk n).obj X :=
  asIso ((coskAdj n).unit.app X)

```

A simplicial set X is *2-coskeletal* just when the unit component $\eta_X : X \rightarrow \text{cosk}_2 \text{tr}_2 X$ is an isomorphism. Thus, our first main subproblem, to prove that the natural transformation v is a natural isomorphism, is achieved by the following proposition:

► **Proposition 5** (`isCoskeletal`). *Nerves of categories are 2-coskeletal.*

```

instance (C : Type u) [Category C] : (nerve C).IsCoskeletal 2 := ...

```

We unpack the 2-coskeletality condition and describe the proof of Proposition 5 in §3.5.

2.2 The 2-truncated nerve adjunction

On account of the natural isomorphism $v: \text{nerve} \cong \text{cosk}_2 \text{nerve}_2$ provided by Proposition 5, it now suffices to construct a left adjoint $\text{ho}_2: \mathbf{Set}^{\Delta_{\leq 2}^{\text{op}}} \rightarrow \mathbf{Cat}$ to the functor nerve_2 . To do so, we unpack the data contained in a (2-truncated) simplicial set.

On paper there is a well-known presentation of the morphisms in the [SimplexCategory](#) Δ by generators and relations [10, §I.1] that is in the process of being formalized by Robin Carlier. At present, [mathlib](#) contains the generating *face maps* $\delta^i: [n] \rightarrow [n+1]$, corresponding to monomorphisms whose image omits $i \in \text{Fin}(n+2)$, as well as the generating *degeneracy maps* $\sigma^i: [n+1] \rightarrow [n]$, corresponding to epimorphisms for which $i \in \text{Fin}(n+1)$ has two elements in its preimage; [mathlib](#) also knows the composition relations these maps satisfy, but does not contain a proof that Δ is equivalent to the category [SimplexCategoryGenRel](#) with this presentation.

A 2-truncated simplicial set X is given by the data of three sets X_0, X_1, X_2 and maps between them indexed by the morphisms between the three objects $[0], [1], [2]: \Delta_{\leq 2} \subset \Delta$. The further 1-truncation of X is given by the data below-left defined by the contravariant actions of the morphisms in $\Delta_{\leq 1}$ displayed below-right:

$$X_0 \begin{array}{c} \xleftarrow{\delta_0} \\ \xleftarrow{\sigma_0} \rightarrow \\ \xleftarrow{\delta_1} \end{array} X_1 \qquad [0] \begin{array}{c} \xleftarrow{\delta^0} \\ \xleftarrow{\sigma^0} \rightarrow \\ \xleftarrow{\delta^1} \end{array} [1] \qquad (6)$$

The composition relations $\sigma^0 \circ \delta^0 = \text{id} = \sigma^0 \circ \delta^1$ in Δ induce dual relations $\delta_0 \circ \sigma_0 = \text{id} = \delta_1 \circ \sigma_0$. This is closely related to categorical data known as a *reflexive quiver*.

A *quiver* is defined in [mathlib](#) as a type equipped with a dependent type of arrows:

```
class Quiver (V : Type) where
  /-- The type of edges/arrows/morphisms between a given source and
       target. -/
  Hom : V → V → Type
```

Kim Morrison formalized the “free \dashv forgetful” adjunction between the category [Quiv](#), of quivers and *prefunctors* between them, and [Cat](#).

► **Proposition 7** ([Quiv.adj](#)). *The free category on a quiver is left adjoint to the*

forgetful functor: $\text{Cat} \begin{array}{c} \xleftarrow{F} \\ \perp \\ \xrightarrow{U} \end{array} \text{Quiv}.$

A similar result also holds for *reflexive quivers*, which extend quivers with specified “identity” endo-arrows for each term in the base type:

```
/-- A reflexive quiver extends a quiver with a specified arrow ‘id X : X
     → X’ for each ‘X’ in its type of objects. We denote these arrows by
     ‘id’ since categories can be understood as an extension of reflexive
     quivers. -/
class ReflQuiver (obj : Type) extends Quiver obj where
```

```

/-- The identity morphism on an object. -/
id : ∀ X : obj, Hom X X

```

We introduced reflexive quivers and *reflexive prefunctors* and defined the evident forgetful functors $U^r : \mathbf{Cat} \rightarrow \mathbf{rQuiv}$ from the category of categories to the category of reflexive quivers and $U^q : \mathbf{rQuiv} \rightarrow \mathbf{Quiv}$ from the category of reflexive quivers to the category of quivers. Definitionally, we have $U = U^q U^r : \mathbf{Cat} \rightarrow \mathbf{Quiv}$.

► **Definition 8** ([Cat.FreeRefl](#)). *The free category on a reflexive quiver Q is the quotient of the free category $F U^q Q$ on the underlying quiver of Q by the hom relation that identifies the specified reflexivity arrows in Q with the identity arrows in the category $F U^q Q$.*

```

/-- A reflexive quiver generates a free category, defined as as quotient
    of the free category on its underlying quiver (called the "path
    category") by the hom relation that uses the specified reflexivity
    arrows as the identity arrows. -/
def FreeRefl (V) [ReflQuiver V] :=
  Quotient (C := Cat.free.obj (Quiv.of V)) (FreeReflRel (V := V))

instance (V) [ReflQuiver V] : Category (FreeRefl V) :=
  inferInstanceAs (Category (Quotient _))

```

This defines a functor $F^r : \mathbf{rQuiv} \rightarrow \mathbf{Cat}$ and a natural transformation $q : F U^q \Rightarrow F^r$ whose components $q_Q : F U^q Q \rightarrow F^r Q$ are universal among functors with domain $F U^q Q$ that respect the hom relation, sending the specified reflexivity arrows of Q to identities.

We then formalized the following proof:

► **Proposition 9** ([ReflQuiv.adj](#)). *The free category on a reflexive quiver is left adjoint to the forgetful functor:*

$$\mathbf{Cat} \begin{array}{c} \xleftarrow{F^r} \\ \perp \\ \xrightarrow{U^r} \end{array} \mathbf{rQuiv}.$$

Proof. We construct the adjunction by defining the unit and counit and verifying the triangle identities. The component of the counit ϵ_C^r at a category C is defined by appealing to the universal property of the quotient functor $q_{U^r C}$ in the following diagram:

$$\begin{array}{ccc} F U^q U^r C & \xrightarrow{q_{U^r C}} & F^r U^r C \\ \parallel & & \downarrow \epsilon_C^r \\ F U C & \xrightarrow{\epsilon_C} & C \end{array}$$

Modulo the definitional equality $U^q U^r = U$, the counit component ϵ_C of the adjunction $F \dashv U$ sends the specified reflexivity arrows of $U^r C$, the identities of C , to identities. Thus this functor factors through the quotient functor $q_{U^r C}$ to define the counit component ϵ_C^r . Naturality of ϵ follows from the uniqueness of the universal property of the quotient functor.

The construction of the unit components at a reflexive quiver Q is more subtle. In the category $\mathcal{Q}\text{uiv}$ of quivers and prefunctors we have the following composite:

$$U^q Q \xrightarrow{\eta_{U^q Q}} U F U^q Q \xrightarrow{U^{qQ}} U F^r Q = U^q U^r F^r Q,$$

defining a prefunctor between the underlying quivers of the reflexive quivers Q and $U^r F^r Q$. In fact, this map preserves the specified reflexivity arrows, lifting to a reflexive prefunctor $\eta_Q^r: Q \rightarrow U^r F^r Q$ with defining equality:

$$\begin{array}{ccc} U^r Q & \xrightarrow{U^q \eta_Q^r} & U^q U^r F^r Q \\ \eta_{U^q Q} \downarrow & & \parallel \\ U F U^q Q & \xrightarrow{U^{qQ}} & U F^r Q. \end{array}$$

Naturality in this case actually holds by reflexivity.

The proofs of the triangle equalities require diagram chases. To verify commutativity of

$$U^r C \xrightarrow{\eta_{U^r C}^r} U^r F^r U^r C \xrightarrow{U^r \epsilon_C^r} U^r C,$$

we use the fact that the functor $U^q: \mathbf{r}\mathcal{Q}\text{uiv} \rightarrow \mathcal{Q}\text{uiv}$ is faithful and the fact that U^q of this composite is equal to the corresponding triangle identity composite for the adjunction $F \dashv U$. To verify commutativity of

$$F^r Q \xrightarrow{F^r \eta_Q^r} F^r U^r F^r Q \xrightarrow{\epsilon_{F^r Q}^r} F^r Q,$$

we use the universal property of the quotient functor to instead verify commutativity of

$$F U^q Q \xrightarrow{qQ} F^r Q \xrightarrow{F^r \eta_Q^r} F^r U^r F^r Q \xrightarrow{\epsilon_{F^r Q}^r} F^r Q,$$

\xrightarrow{qQ}

which follows from naturality of q , the defining equalities for ϵ^r and η^r , naturality of ϵ , and the corresponding triangle equality for $F \dashv U$. These steps occupy 7 lines of a 23 line proof due to the challenges described in §3.1. ◀

► **Example 10** ([instReflQuiverOneTruncation₂](#)). Returning to (6), a 2-truncated simplicial set X has an underlying reflexive quiver $U_1^2 X$ whose type of objects is X_0 and whose type of arrows from $x: X_0$ to $y: X_1$ is the type of 1-simplices $f: X_1$ so that $\delta_1 f = x$ and $\delta_0 f = y$.⁹

We can now define the 2-truncated homotopy category functor.

⁹ To explain the orientation, note that $\delta^1: [0] \rightarrow [1]$ picks out the source object of $\mathbf{Fin}(2)$ while $\delta^0: [0] \rightarrow [1]$ picks out the target object.

► **Definition 11** (`Truncated.HomotopyCategory`). The homotopy category $\text{ho}_2 X$ is the quotient of the free category $F^r U_1^2 X$ on the underlying reflexive quiver of a 2-truncated simplicial set X by a hom relation generated by the 2-simplices: for every 2-simplex $\sigma : X_2$, we identify the face $\delta_1 \sigma$ with the composite $\delta_0 \sigma \cdot \delta_2 \sigma$ in the category $F^r U_1^2 X$.

```

/-- The 2-simplices in a 2-truncated simplicial set 'V' generate a hom
    relation on the free category on the underlying reflexive quiver of
    'V'. -/
inductive HoRel2 {V : SSet.Truncated 2} :
  (X Y : Cat.FreeRefl (OneTruncation2 V)) → (f g : X → Y) → Prop
| mk (φ : V → [2]2) : HoRel2 _ _
  (Quot.mk _ (Quiver.Hom.toPath (ev02 φ)))
  (Quot.mk _ ((Quiver.Hom.toPath (ev01 φ)).comp
    (Quiver.Hom.toPath (ev12 φ))))

/-- The type underlying the homotopy category of a 2-truncated simplicial
    set V. -/
def SSet.Truncated.HomotopyCategory (V : SSet.Truncated 2) : Type u :=
  Quotient (HoRel2 (V := V))

instance (V : SSet.Truncated 2) : Category.{u} (V.HomotopyCategory) :=
  inferInstanceAs (Category (CategoryTheory.Quotient ...))

```

This defines a functor $\text{ho}_2 : \text{Set}^{\Delta^{\text{op}}_{\leq 2}} \rightarrow \text{Cat}$ and a natural transformation $q : F^r U_1^2 \Rightarrow \text{ho}_2$ whose components $q_X : F^r U_1^2 X \rightarrow \text{ho}_2 X$ are universal among functors with domain $F^r U_1^2 X$ that respect the hom relation, sending the image of the composite $\delta_0 \sigma \cdot \delta_2 \sigma$ of the arrows along the “spine” of a 2-simplex $\sigma : X_2$ to the image of the “diagonal” arrow $\delta_1 \sigma$.

The proof that ho_2 is left adjoint to nerve_2 proceeds similarly to the proof of Proposition 9, with one step made considerably more difficult. As before, the counit of $\text{ho}_2 \dashv \text{nerve}_2$ is defined using the universal property of the quotient functor q while the unit is defined by lifting a map from the category of reflexive quivers to the category of 2-truncated simplicial sets. This lifting is enabled by the following proposition:

► **Proposition 12** (`toNerve2.mk`, `toNerve2.ext`). Let $X : \text{Set}^{\Delta^{\text{op}}_{\leq 2}}$ and $C : \text{Cat}$.

- (i) Consider a reflexive prefunctor $F : U_1^2 X \rightarrow U_1^2 \text{nerve}_2 C \cong U^r C$ from the underlying reflexive quiver of X to the underlying reflexive quiver of C . If for each 2-simplex $\sigma : X_2$, $F(\delta_1 \sigma)$ equals the composite $F(\delta_0 \sigma) \cdot F(\delta_2 \sigma)$ in C , then F lifts to a map of 2-truncated simplicial sets.
- (ii) Any parallel pair of maps of 2-truncated simplicial sets $F, G : X \rightarrow \text{nerve}_2 C$ are equal if their underlying reflexive prefunctors agree.

We discuss the proof of these results in §3.4.

► **Proposition 13** ([nerve₂Adj](#)). *The 2-truncated homotopy category functor is left*

adjoint to the 2-truncated nerve: $\text{Cat} \begin{array}{c} \xleftarrow{\text{ho}_2} \\ \perp \\ \xrightarrow{\text{nerve}_2} \end{array} \text{Set}^{\Delta_{\leq 2}^{\text{op}}}.$

Proof. We construct the adjunction by defining the unit and counit and verifying the triangle identities. The component of the counit ϵ_C at a category C is defined by appealing to the universal property of the quotient functor $q_{\text{nerve}_2 C}$ in the following diagram:

$$\begin{array}{ccc} F^r U_1^2 \text{nerve}_2 C & \xrightarrow{q_{\text{nerve}_2 C}} & \text{ho}_2 \text{nerve}_2 C \\ F^r \phi_C \downarrow \cong & & \downarrow \epsilon_C \\ F^r U^r C & \xrightarrow{\epsilon_C^r} & C, \end{array}$$

Modulo a natural isomorphism $\phi: U_1^2 \text{nerve}_2 \cong U^r$ between the two constructions of the reflexive quiver underlying a category, the counit component ϵ_C^r of the adjunction $F^r \dashv U^r$ respects the defining hom relation. Naturality is again established using the uniqueness of the universal property of the quotient functor.

The unit components are constructed by applying Proposition 12(i) to the composition of reflexive prefunctors defined below, which thus satisfies the defining equation:

$$\begin{array}{ccc} U_1^2 X & \xrightarrow{U_1^2 \eta_X} & U_1^2 \text{nerve}_2 \text{ho}_2 X \\ \eta_{U_1^2 X}^r \downarrow & & \cong \downarrow \phi_{\text{ho}_2 X} \\ U^r F^r U_1^2 X & \xrightarrow{U^r q_X} & U^r \text{ho}_2 X. \end{array}$$

By Proposition 12(ii), naturality can be checked at the level of reflexive prefunctors, at which point it follows from naturality of η^r , q , and ϕ .

The proofs of the triangle equalities require diagram chases. To verify commutativity of

$$\text{nerve}_2 C \xrightarrow{\eta_{\text{nerve}_2 C}} \text{nerve}_2 \text{ho}_2 \text{nerve}_2 C \xrightarrow{\text{nerve}_2 \epsilon_C} \text{nerve}_2 C,$$

we use Proposition 12(ii) to instead verify commutativity of the underlying reflexive prefunctors. This diagram chase follows from the defining equalities for η and ϵ , naturality of ϕ and η^r , and the corresponding triangle equality for $F^r \dashv U^r$, modulo cancelling ϕ with its inverse. These steps occupy 8 lines of a 25 line proof due to the challenges described in §3.1.

To verify commutativity of

$$\text{ho}_2 X \xrightarrow{\text{ho}_2 \eta_X} \text{ho}_2 \text{nerve}_2 \text{ho}_2 X \xrightarrow{\epsilon_{\text{ho}_2 X}} \text{ho}_2 X,$$

we use the universal property of the quotient functor to instead verify commutativity of

$$F^r U_1^2 X \xrightarrow{q_X} \text{ho}_2 X \xrightarrow{\text{ho}_2 \eta_X} \text{ho}_2 \text{nerve}_2 \text{ho}_2 X \xrightarrow{\epsilon_{\text{ho}_2 X}} \text{ho}_2 X,$$

q_X

which follows from naturality of q , the defining equalities for η and ϵ , naturality of ϵ^r , and the corresponding triangle equality for $F^r \dashv U^r$, modulo cancelling ϕ with its inverse. These steps occupy 8 lines of a 24 line proof due to the challenges described in §3.1. ◀

As discussed, Propositions 13 and 5 imply Theorem 2, proving our first main theorem. To show that the adjunction $\text{ho} \dashv \text{nerve}$ is reflective and conclude that \mathbf{Cat} has colimits, we must show that the nerve functor is fully faithful. As the nerve is isomorphic to the composite of the functors cosk_2 and nerve_2 and cosk_2 is fully faithful (since $\Delta_{\leq 2} \hookrightarrow \Delta$ is the inclusion of a full subcategory), it suffices to show that the 2-truncated nerve is fully faithful.

► **Lemma 14** (`nerveFunctor2.faithful`). *The 2-truncated nerve functor is faithful.*

Proof. We have a natural isomorphism $\phi: U_1^2 \text{nerve}_2 \cong U^r$ and the functor U^r is faithful. Thus by `Faithful.of_comp_iso`, nerve_2 is faithful. ◀

```
instance nerveFunctor2.faithful : nerveFunctor2.Faithful :=
  Functor.Faithful.of_comp_iso
    (G := oneTruncation2) (H := ReflQuiv.forget)
    OneTruncation2.ofNerve2.natIso
```

With considerably more effort, discussed in §3.3, we can also show:

► **Lemma 15** (`nerveFunctor2.full`). *The 2-truncated nerve functor is full.*

These lemmas combine to prove Theorem 3, our second main theorem, and these results together give Corollary 4 that \mathbf{Cat} has colimits.

3 Challenges

Although the mathematics of Theorems 2 and 3 is well established in the literature, and we came to the project suitably armed with category theoretic and Lean formalization expertise, the project ended up being quite challenging, for both expected and unexpected reasons. Below, we will discuss some of the aspects of the formalization that posed the most difficulties, and what we did to resolve or work around the issues.

3.1 Bundling categories

In `mathlib`, many notions come in two flavors of presentation, referred to as the “bundled” and “(partially) unbundled” presentations.¹⁰ In the unbundled presentation, a category is given as a type variable C together with a typeclass instance argument `Category` C which provides the rest of the data for a category whose type

¹⁰There is also a “fully unbundled” presentation, but `mathlib` does not use it and we will not discuss it.

of objects is C . This allows for a form of formal synecdoche, where one need only explicitly mention the type of objects and the rest of the structure comes along for the ride. In bundled style a category is an element $C : \text{Cat}$, with suitable projections $\text{ob } C : \text{Type}$ and $\text{Hom} : \text{ob } C \rightarrow \text{ob } C \rightarrow \text{Type}$.

Generally, `mathlib` prefers the unbundled form, but the bundled form is necessary if we need to consider the category of categories, that is, `Category Cat`, and our main theorem is about `Cat` so we cannot avoid it completely. A similar situation occurs for functors, which appear unbundled as $C \Rightarrow D$ and also bundled as $\text{Hom}_{\text{Cat}}(C, D)$.¹¹ There is functor composition $F \ggg G$ and morphism composition $F \gg_{\text{Cat}} G$, and so on. Not only are many notions duplicated, but by applying lemmas coming from each context one can end up with a mixture of both notions in goals, and simplification would frequently get stuck in this situation. We eventually mitigated this issue by unbundling as early as possible, stating lemmas only in the unbundled form, and packaging them up only for the higher order statements about operations on `Cat`.

3.2 Equality of functors

Our main theorem fundamentally deals with the 1-categorical (rather than 2-categorical) structure of `Cat`. The very statement that `Cat` has small colimits involves equality of functors, as does the definition of the nerve — a simplicial *set* rather than a simplicially-indexed category-valued pseudofunctor.¹² There are advantages to working strictly (1-categorically) rather than weakly (2-categorically or bicategorically) when possible. In future work, described in §5, we plan to use our homotopy category functor to convert from simplicial to categorical enrichments. As we have formalized this as a strict functor between 1-categories we can tap into existing `mathlib` developments of change of base in enriched category theory.

Lean’s `mathlib` provides an extensionality theorem for functors, but note the warning:

```
/-- Proving equality between functors. This isn't an extensionality lemma,
    because usually you don't really want to do this. -/
theorem ext {F G : C => D} (h_obj : ∀ X, F.obj X = G.obj X) (h_map : ∀ X Y
  f,
  F.map f = eqToHom (h_obj X) >> G.map f >> eqToHom (h_obj Y).symm) : F =
  G
```

So we knew in advance there would be trouble coming and needed to structure our proofs in specific ways to take advantage of `eqToHom`.

¹¹ Note the former notion of functor is strictly speaking more general than the latter, in which the universe levels of the domain category must match those of the codomain.

¹² The nerve of C could be regarded as a pseudofunctor $\text{nerve } C : \Delta^{\text{op}} \rightarrow \text{Cat}$ valued in `Cat`, sending the object $[n] : \Delta$ to the category of functors $\text{Fin}(n+1) \rightarrow C$. But this type-valued mapping is strictly functorial, and indeed (due to the care taken in formalizing the definition of `ComposableArrows`) the `map_id` and `map_comp` fields of `nerve` are filled by `rfl`.

At the core of this warning is the following issue: When one has an equality of objects, or an equality of functors (which involves an equality of objects — the `h_obj` assumption above), this induces an equality of types, namely $\text{Hom}(A, B) = \text{Hom}(A, B')$ given $B = B'$. In dependent type theory, if one has $f : \text{Hom}(A, B)$ and an equality $h : B = B'$, the plain expression $f : \text{Hom}(A, B')$ does not typecheck (unless B and B' are *definitionally equal*). However, it is possible to use h to *cast* f to the correct type, producing a term $\text{cast } h \ f : \text{Hom}(A, B')$. This is also known as “rewriting” and it is a common technique in proofs (using the `rw` tactic), but it is hazardous when applied to “data” such as f , because $\text{cast } h \ f$ is not the same term as f and so mismatches can arise between expressions such as $\text{cast } h \ (f \circ g)$ and $(\text{cast } h \ f) \circ g$. It is possible to prove these are equal, but it generally requires a rather delicate “induction on equality” to prove, with a manually written induction motive. This situation is commonly referred to as “DTT hell.”

The `mathlib` statement of `Functor.ext` is employing a technique to avoid this issue, which is to make use of the category structure to help alleviate the pains associated with using the cast function directly, by first converting $h : B = B'$ into `eqToHom h` : $\text{Hom}(B, B')$, so that $(\text{eqToHom } h) \circ f : \text{Hom}(A, B')$. This presents the casting of f as a composition, which means that many more lemmas from category theory apply (such as associativity of composition), and `eqToHom` itself has many lemmas for how it factors over various operations.

For the most part, this technique did its job. Although we obtained many goals that involved these `eqToHom` morphisms, after formalizing appropriate lemmas, the simplifier was able to push them out of the way. For instance, we added a `Quiver.homOfEq` to perform an analogous casting for (reflexive) quivers (which lack composition) and proved various lemmas by induction on equality. This is the kind of complication that essentially never appears in informal category theory, due to its more extensional handling of morphism typing.

3.3 Proving functoriality

Another example of DTT hell arises in the proof of `nerveFunctor2.full`, that the 2-truncated nerve functor $\text{nerve}_2 : \text{Cat} \rightarrow \text{Set}^{\Delta_{\leq 2}^{\text{op}}}$ is full. Given a pair of categories C and D and a map $F : \text{nerve}_2 C \rightarrow \text{nerve}_2 D$ between their 2-truncated nerves, our task is to lift this to a functor between C and D . The underlying reflexive prefunctor is defined by the 1-truncation of F , but it remains to show that this reflexive prefunctor is *functorial*, preserving composition of morphisms in C in addition to identities.

The idea of the proof is note that the composable morphisms $k \circ h$ define a 2-simplex $\sigma_{k,h} : (\text{nerve}_2 C)_2$. The 2-simplex $F(\sigma_{k,h}) : (\text{nerve}_2 D)_2$ defines a functor $\text{Fin}(3) \rightarrow D$, which gives rise to a commutative triangle involving three arrows in D . Using the naturality of F with respect to the three morphisms $\delta^i : [1] \rightarrow [2]$, this may be converted into the desired equality $F(k \circ h) = Fk \circ Fh$. But these naturality equalities live in the type $(\text{nerve}_2 D)_1$ of functors $\text{Fin}(2) \rightarrow D$, which give

rise to *heterogeneous* equalities between the corresponding arrows in D . We were forced to first prove and then string together a sequence of heterogeneous equalities before finally concluding the desired equality between arrows belonging to the same hom-type. It then remained to show that the 2-truncated nerve carries this lifted functor to the original map F , which is proven using Proposition 12(ii).

3.4 Proving naturality

In Proposition 12(i), our aim is to define a map of 2-truncated simplicial sets $F : X \rightarrow \text{nerve}_2 C$ from a map between the underlying reflexive quivers. Such a map is a natural transformation with three components F_0, F_1 , and F_2 corresponding to the three objects $[0], [1], [2] : \Delta_{\leq 2}$, which can be constructed straightforwardly from the hypotheses. But complications arise in the proof of naturality, which amounts to establishing commutative squares of the form

$$\begin{array}{ccc} X_n & \xrightarrow{F_n} & (\text{nerve}_2 C)_n \\ \downarrow \cdot \alpha & & \downarrow \cdot \alpha \\ X_m & \xrightarrow{F_m} & (\text{nerve}_2 C)_m \end{array} \quad (16)$$

for each morphism $\alpha : [m] \rightarrow [n]$ in $\Delta_{\leq 2}$ (there are 31 such morphisms). One annoyance, discussed at the start of §2.2, is the fact that `mathlib` does not yet know that $\Delta_{\leq 2}$ is generated by the three degeneracy maps σ^i and the five face maps δ^i . Our initial formalization instead explicitly treated the nine cases presented by the choice of domain and codomain objects, with the cases involving a morphism with domain $[2]$ reducing to the cases involving domain $[0]$ or $[1]$ by the 2-coskeletality of the nerve. Once we fixed domain and codomain objects there were often further case splits involving the specific nature of the morphism $\alpha : [m] \rightarrow [n]$.

When we submitted this as a pull request to `mathlib`, the reviewer Joël Riou suggested we think of this result as the task of showing that the `MorphismProperty` on $\Delta_{\leq 2}$ of satisfying the naturality condition (16) is universally true. An easier task than showing that the simplex category can be presented by generators and relations is to show that the `naturalityProperty` of its arrows follows from the cases corresponding to faces and degeneracy maps, as Riou formalized for us in `Truncated.morphismProperty_eq_top`. This reduces the problem to the eight cases corresponding to generating morphisms $\alpha : [m] \rightarrow [n]$ in $\Delta_{\leq 2}$, each of which still involves establishing an equality between functors $\text{Fin}(m+1) \rightarrow C$.

The extensionality result of Proposition 12(ii) is simpler but still less innocuous than it appears. Two natural transformations F and G are equal just when their three components are equal, and as these are functions between types it suffices to show they define the same mapping on terms. However, this involves proving equalities in the types $(\text{nerve}_2 C)_0$, $(\text{nerve}_2 C)_1$, and $(\text{nerve}_2 C)_2$, which are types of functors, and thus these equalities involved a fair amount of pain. In the final case $F_2 = G_2$, naturality again provided us with equalities in the type $(\text{nerve}_2 C)_1$

of functors $\text{Fin}(2) \rightarrow C$ which gave rise to heterogeneous equalities between the mappings on arrows of the functors $\text{Fin}(3) \rightarrow C$ we were tasked with identifying.

3.5 Proving nerves are 2-coskeletal

By a folklore result involving Reedy category theory [29], a simplicial set X is *2-coskeletal*, meaning that the adjunction unit component $\eta_X : X \rightarrow \text{cosk}_2 \text{tr}_2 X$ is an isomorphism, just when every k -simplex boundary in X can be filled to a simplex, for all $k > 2$. This property would be easy to check in the case where X is the nerve of a category, but unfortunately this characterization of 2-coskeletal simplicial sets has not been formalized. Thus, we directly unpack the invertible unit component definition into a condition that we can actually check.

Recall the functor cosk_2 is defined by right Kan extension along the inclusion $\Delta_{\leq 2}^{\text{op}} \hookrightarrow \Delta^{\text{op}}$. Thus, the condition of a simplicial set X being 2-coskeletal asserts that the identity natural transformation defines a right Kan extension:

$$\begin{array}{ccc} & \Delta^{\text{op}} & \\ \nearrow & \Downarrow \text{id} & \searrow X \\ \Delta_{\leq 2}^{\text{op}} & \xrightarrow{\quad} \Delta^{\text{op}} & \xrightarrow{X} \mathbf{Set}. \end{array} \quad (17)$$

```

/-- A simplicial object 'X' is 'n'-coskeletal when it is the right Kan
    extension of its restriction along '(Truncated.inclusion n).op' via
    the identity natural transformation. -/
class IsCoskeletal (X : SimplicialObject C) (n : ℕ) : Prop where
  isRightKanExt : IsRightKanExtension X (1! ((Truncated.inclusion n).op >>>
    X))

theorem isCoskeletal_iff_isIso :
  X.IsCoskeletal n ↔ IsIso ((coskAdj n).unit.app X) := by
  rw [isCoskeletal_iff]
  exact isRightKanExtension_iff_isIso ((coskAdj n).unit.app X)
    ((coskAdj n).counit.app _) (1! _) ((coskAdj n).left_triangle_components
  X)

```

As the category \mathbf{Set} is complete, any such right Kan extension (17) is *pointwise*, meaning that X is 2-coskeletal if and only if for each $n : \mathbb{N}$, a canonical cone — with summit X_n over a diagram with objects X_j indexed by arrows $[j] \rightarrow [n]$ in Δ with $j \leq 2$ — is a limit cone, the definition of which we now recall:

```

/-- A cone 't' on 'F' is a limit cone if each cone on 'F' admits a unique
    cone morphism to 't'. -/
structure IsLimit (t : Cone F) where
  /- There is a morphism from any cone point to 't.pt' -/
  lift : ∀ s : Cone F, s.pt → t.pt
  /- The map makes the triangle with the two natural transformations
    commute -/
  fac : ∀ (s : Cone F) (j : J), lift s >> t.π.app j = s.π.app j

```

```

/-- It is the unique such map to do this -/
uniq : ∀ (s : Cone F) (m : s.pt → t.pt)
  ( _ : ∀ j : J, m ≫ t.π.app j = s.π.app j), m = lift s

```

Thus, for the simplicial set nerve C , we must:

- (i) Construct `lift`, a function valued in functors $\text{Fin}(n+1) \rightarrow C$.
- (ii) Prove `fac`, an equality between functions valued in functors $\text{Fin}(j+1) \rightarrow C$ for $j = 0, 1, 2$.
- (iii) Prove `uniq`, an equality between functions valued in functors $\text{Fin}(n+1) \rightarrow C$.

We submitted a proof along these lines in our initial `mathlib` pull request, involving repeated painful appeals to `Functor.ext`. During the PR review process, Joël Riou suggested a useful abstraction boundary, using the following characterization of simplicial sets defined by nerves of categories.

► **Proposition 18** (`Nerve.strictSegal`). *For a simplicial set X the following are equivalent:*

- (i) X is isomorphic to the nerve of a category.¹³
- (ii) X satisfies the `StrictSegal` condition: for all $n : \mathbb{N}$, the canonical map that carries an n -simplex of X to the path of edges defined by its `spine` is an equivalence.

As Proposition 18 explains, the only examples of strict Segal simplicial sets are nerves of categories. But it was cleaner to formalize the proof that a strict Segal simplicial set X is 2-coskeletal because the functions involved in `lift`, `fac`, and `uniq` are now valued in an abstract type X_n which is equivalent to the type of paths of edges of length n in X . Thus, we formalized:

```

/-- A strict Segal simplicial set is 2-coskeletal. -/
def isPointwiseRightKanExtensionAt (n : ℕ) :
  (rightExtensionInclusion X 2).IsPointwiseRightKanExtensionAt ⟨[n]⟩
  where
    lift s x := ...
    fac s j := ...
    uniq s m hm := ...

```

together with a proof `Nerve.strictSegal` of the implication (i) \Rightarrow (ii) in Proposition 18.

4 Related work

There are myriad libraries of formalized mathematics that contain a substantial amount of category theory [3, 7, 14, 17, 21, 22, 23, 24, 32, 33, 34]. Several papers on the subject [11, 28] recall Harrison’s assessment, based on the early efforts of [15],

¹³In fact, when this condition holds, X is isomorphic to the nerve of the homotopy category $\text{ho}(X)$.

that “category theory [is] notoriously hard to formalize in any kind of system” [13]. Others describe additional complexities involved in developing a category theory library that is compatible with intensional identity types or homotopy type theory [2, 14].

A common feature of category theory libraries is a broad array of sophisticated categorical definitions, constructions, and theorems. To give a simplified illustration related to the theory of colimits, one will commonly find the general definition of a colimit, specific examples of colimits such as coproducts and coequalizers, and a proof that a colimit of any diagram shape can be built out of coequalizers and suitably-sized coproducts. What is less common is to find formalizations of applications of this general theory to specific categories, e.g., a proof that a specific category has coproducts and coequalizers and thus has all suitably-sized colimits — with a common exception being the category of types and functions.

More extensive examples of applications of category theory to specific categories can be found in the [UniMath](#) library in Rocq [34], which grew out of the formalization project [2], as well as Lean’s [mathlib](#) [21], which grew out of an experimental library developed by Kim Morrison [25]. Both libraries contain the construction of limits in \mathcal{Cat} . More explicitly, [UniMath](#) contains a construction of equalizers between so-called “strict categories” (those whose objects and morphisms form *sets*, rather than higher types).¹⁴ By contrast, [mathlib](#) directly formalizes the construction of the limit of a diagram of any shape as the category whose objects and hom-sets are defined by limits of the induced diagrams.¹⁵ We do not know of any other formalizations of the nerve functor, the nerve adjunction, or colimits in \mathcal{Cat} .

Alternate pen-and-paper approaches to the construction of colimits in \mathcal{Cat} can be given. Since coproducts in \mathcal{Cat} are elementary to define — created by the forgetful functor to reflexive quivers — this reduces the problem to the construction of coequalizers. In [6, 5.1.7], coequalizers are constructed in reference to the adjunction of Proposition 7 lifted to the category of quivers with commutativity conditions. In [4], which Robert Maxton brought to our attention after our formalization was complete, coequalizers in \mathcal{Cat} are constructed as quotient functors defined with respect to what the authors call a *generalized congruence*, generalizing the composition-stable hom-wise equivalence relations called *congruences* that we use here. A final approach that we considered would be to observe that \mathcal{Cat} is the category of models of a finite limit theory, and thus is an essentially algebraic theory, and all such categories are locally presentable, and in particular cocomplete [1, §3.D]. The construction of colimits given in the proof of this result is rather unwieldy [1, 3.36]. As noted above, our approach follows [30, 4.5.16].

¹⁴ See: [UniMath/CategoryTheory/Limits/Examples/CategoryOfSetcategoriesLimits.v](#)

¹⁵ See: [Mathlib/CategoryTheory/Category/Cat/Limit.html](#)

5 Future work

We plan to make use of the homotopy category functor to formalize a proof of the converse implication (ii) \Rightarrow (i) in Proposition 18 by showing that a strict Segal simplicial set is canonically isomorphic, via the unit of our nerve adjunction, to the nerve of its homotopy category. At our suggestion, Nick Ward has formalized the n -truncated analog of strict Segal simplicial sets in a pull request that is currently under review. We also plan to streamline our construction of the unit of the nerve adjunction through an abstraction boundary of strict Segal 2-truncated simplicial sets, which will allow us to remove further uses of `Functor.ext`.

Finally, the homotopy category functor will play a role in the task of formalizing ∞ -category theory in Lean. Lean’s `mathlib` contains a popular “analytic” definition of ∞ -categories as quasi-categories: a `Quasicategory` is a simplicial set satisfying a particular horn filling condition. In a nearly completed masters thesis project, Jack McKoen is formalizing a proof that the full subcategory \mathcal{QCat} of $\mathbf{Set}^{\Delta^{op}}$ defined by the quasi-categories is cartesian closed, meaning it is enriched over itself. We have written a blueprint which gives a detailed outline of a proof that the homotopy category functor, now considered as a functor $ho: \mathcal{QCat} \rightarrow \mathbf{Cat}$, preserves products. Applying this functor hom-wise converts the quasi-category enriched category of quasi-categories to a categorically enriched category of quasi-categories, aka a 2-category of quasi-categories. Recent work of Riehl and Verity has shown that the core basic theory of ∞ -categories can be developed within this 2-category, whose objects are ∞ -categories, whose morphisms are ∞ -functors, and whose 2-cells are ∞ -natural transformations [31]. In particular, the existing `mathlib` formalization of adjunctions in a bicategory will specialize to provide the theory of adjunctions between ∞ -categories [8].

References

- 1 J. Adamek and J. Rosicky. *Locally Presentable and Accessible Categories*. London Mathematical Society Lecture Note Series. Cambridge University Press, 1994.
- 2 Benedikt Ahrens, Krzysztof Kapulkin, and Michael Shulman. Univalent categories and the rezk completion. In Maria del Mar González, Paul C. Yang, Nicola Gambino, and Joachim Kock, editors, *Extended Abstracts Fall 2013*, pages 75–76, Cham, 2015. Springer International Publishing.
- 3 Andrej Bauer, Jason Gross, Peter LeFanu Lumsdaine, Michael Shulman, Matthieu Sozeau, and Bas Spitters. The hott library: A formalization of homotopy type theory in coq. In *Proceedings of the 6th ACM SIGPLAN Conference on Certified Programs and Proofs*, CPP 2017, page 164–172, New York, NY, USA, 2017. Association for Computing Machinery. doi:10.1145/3018610.3018615.
- 4 Marek A. Bednarczyk, Andrzej M. Borzyszkowski, and Wiesław Pawłowski. Generalized congruences – Epimorphisms in Cat. *Theory and Applications of Categories*, 5(11):266–280, 1999.

- 5 A.J. Blumberg, D. Gepner, and G. Tabuada. A universal characterization of higher algebraic k -theory. *Geometry & Topology*, 2(17):733–838, 2013. doi:[10.2140/gt.2013.17.733](https://doi.org/10.2140/gt.2013.17.733).
- 6 Francis Borceux. *Handbook of Categorical Algebra 1: Basic Category Theory*. Encyclopedia of Mathematics and its Applications. Cambridge University Press, 1994.
- 7 Guillaume Brunerie, Kuen-Bang Hou (Favonia), Evan Cavallo, Tim Baumann, Eric Finster, Jesper Cockx, Christian Sattler, Chris Jeris, Michael Shulman, et al. Homotopy type theory in Agda. <https://github.com/HotT/HotT-Agda>, 2019.
- 8 Mario Carneiro, Emily Riehl, and Dominic Verity. The ∞ -cosmos project. <https://emilyriehl.github.io/infinity-cosmos/>, 2025.
- 9 L. Fargues and P. Scholze. Geometrization of the local Langlands correspondence. arXiv:2102.13459, 2024.
- 10 P.G. Goerss and J.F. Jardine. *Simplicial homotopy theory*. Birkhäuser Basel, 2009.
- 11 Jason Gross, Adam Chlipala, and David I. Spivak. Experience implementing a performant category-theory library in coq. In Gerwin Klein and Ruben Gamboa, editors, *Interactive Theorem Proving*, pages 275–291, Cham, 2014. Springer International Publishing.
- 12 John Harrison. Hol light: An overview. In *International Conference on Theorem Proving in Higher Order Logics*, pages 60–66. Springer, 2009. URL: https://doi.org/10.1007/978-3-642-03359-9_4.
- 13 John Harrison et al. *Formalized mathematics*. Citeseer, 1996.
- 14 Jason Z. S. Hu and Jacques Carette. Formalizing category theory in agda. In *Proceedings of the 10th ACM SIGPLAN International Conference on Certified Programs and Proofs*, CPP 2021, page 327–342, New York, NY, USA, 2021. Association for Computing Machinery. doi:[10.1145/3437992.3439922](https://doi.org/10.1145/3437992.3439922).
- 15 Gérard Huet and Amokrane Saïbi. Constructive category theory. In *Proof, Language, and Interaction: Essays in Honour of Robin Milner*. The MIT Press, 05 2000. arXiv:https://direct.mit.edu/book/chapter-pdf/2295865/9780262281676_caj.pdf, doi:[10.7551/mitpress/5641.003.0015](https://doi.org/10.7551/mitpress/5641.003.0015).
- 16 Nikolai Kudasov, Emily Riehl, and Jonathan Weinberger. Formalizing the ∞ -categorical yoneda lemma. In *Proceedings of the 13th ACM SIGPLAN International Conference on Certified Programs and Proofs*, CPP 2024, pages 274–290, New York, NY, USA, 2024. Association for Computing Machinery. doi:[10.1145/3636501.3636945](https://doi.org/10.1145/3636501.3636945).
- 17 Amélia Liao, Daniel Sölch, Jonathan Coates, Matthew McQuaid, Nathan van Doorn, Naïm Favier, Patrick Nicodemus, Reed Mullanix, favonia, uni, et al. 1Lab. <https://1lab.dev/>, 2025.
- 18 J. Lurie. *Derived algebraic geometry*. PhD thesis, Massachusetts Institute of Technology, 2004. URL: <http://hdl.handle.net/1721.1/30144>.
- 19 J. Lurie. Spectral Algebraic Geometry. www.math.ias.edu/~lurie/papers/SAG-rootfile.pdf, February 2018.
- 20 S. Mac Lane. *Categories for the Working Mathematician*. Graduate Texts in Mathematics. Springer-Verlag, second edition, 1998.
- 21 The mathlib Community. The lean mathematical library. In *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs*,

- CPP 2020, page 367–381, New York, NY, USA, 2020. Association for Computing Machinery. doi:10.1145/3372885.3373824.
- 22 Mihails Milehins. Category theory for ZFC in HOL I: Foundations: Design patterns, set theory, digraphs, semicategories. *Archive of Formal Proofs*, September 2021. https://isa-afp.org/entries/CZH_Foundations.html, Formal proof development.
 - 23 Mihails Milehins. Category theory for ZFC in HOL II: Elementary theory of 1-categories. *Archive of Formal Proofs*, September 2021. https://isa-afp.org/entries/CZH_Elementary_Categories.html, Formal proof development.
 - 24 Mihails Milehins. Category theory for ZFC in HOL III: Universal constructions. *Archive of Formal Proofs*, September 2021. https://isa-afp.org/entries/CZH_Universal_Constructions.html, Formal proof development.
 - 25 Kim Morrison. Lean category theory. <https://github.com/kim-em/lean-category-theory>, 2023.
 - 26 David Nadler and Hiro Lee Tanaka. A stable ∞ -category of lagrangian cobordisms. *Advances in Mathematics*, 366:107026, 2020. URL: <https://www.sciencedirect.com/science/article/pii/S0001870820300517>, doi:<https://doi.org/10.1016/j.aim.2020.107026>.
 - 27 Tobias Nipkow, Markus Wenzel, and Lawrence C Paulson. *Isabelle/HOL: a proof assistant for higher-order logic*. Springer, 2002. URL: <https://doi.org/10.1007/3-540-45949-9>.
 - 28 Greg O’Keefe. Towards a readable formalisation of category theory. *Electronic Notes in Theoretical Computer Science*, 91:212–228, 2004. Proceedings of Computing: The Australasian Theory Symposium (CATS) 2004. URL: <https://www.sciencedirect.com/science/article/pii/S1571066103000215>, doi:<https://doi.org/10.1016/j.entcs.2003.12.014>.
 - 29 C.L. Reedy. Homotopy theory of model categories. <https://math.mit.edu/~psh/reedy.pdf>.
 - 30 E. Riehl. *Category Theory in Context*. Aurora Modern Math Originals. Dover Publications, 2016.
 - 31 Emily Riehl and Dominic Verity. *Elements of ∞ -Category Theory*. Cambridge Studies in Advanced Mathematics. Cambridge University Press, 2022.
 - 32 Egbert Rijke, Elisabeth Bonnet, Jonathan Prieto-Cubides, Fredrik Bakke, et al. The agda-unimath library. <https://github.com/UniMath/agda-unimath/>, 2025.
 - 33 Andrea Vezzosi, Anders Mörtberg, and Andreas Abel. Cubical agda: A dependently typed programming language with univalence and higher inductive types. *Journal of Functional Programming*, 31:e8, 2021. doi:10.1017/S0956796821000034.
 - 34 Vladimir Voevodsky, Benedikt Ahrens, Daniel Grayson, et al. Unimath — a computer-checked library of univalent mathematics. Available at <http://unimath.org>. URL: <https://github.com/UniMath/UniMath>, doi:10.5281/zenodo.7848572.