

# LAB #1: DATA CLEANING

**SUNDAY, 9/20**


**NDL**

NITTANY DATA LABS

# ATTENDANCE - “DATA CLEANING”



# DATA SCIENCE PIPELINE



# WHY IS DATA CLEANING IMPORTANT?

- Converts raw data into organized, model-ready data
- Prevents errors and inconsistencies
- Lessens the chance of model bias
- Improves visibility of data during EDA


## Expectation:

"Analysis is the job."



## Reality:

Cleaning the data is the job.  
Analysis is whatever time is left after that.



# WHAT IS “DIRTY DATA”

- Contains gaps, nulls, or duplicates
- Multiple data types in an attribute
- Few outliers that heavily bias summary statistics
- Any data that will cause errors during modeling

| county          | year | county_ra | v001_raw | v001_num | v001_den | v001_cilov | v001_cihig | v001_race | v001_race |
|-----------------|------|-----------|----------|----------|----------|------------|------------|-----------|-----------|
| United States   | 2019 |           | 6900.63  | 3745538  | 9.08E+08 | 6890.349   | 6910.912   |           |           |
| Alabama         | 2019 |           | 9917.233 | 80440    | 13636816 | 9815.191   | 10019.27   |           |           |
| Autauga County  | 2019 | 1         | 8824.057 | 815      | 156132   | 7935.326   | 9712.788   | 10471.25  |           |
| Baldwin County  | 2019 | 1         | 7224.632 | 2827     | 576496   | 6794.128   | 7655.136   | 10042.47  | 3086.606  |
| Barbour County  | 2019 | 1         | 9586.165 | 451      | 72222    | 8200.118   | 10972.21   | 11332.56  |           |
| Bibb County     | 2019 | 1         | 11783.54 | 445      | 63653    | 10159.98   | 13407.11   | 14812.54  |           |
| Blount County   | 2019 | 1         | 10908.1  | 1050     | 161107   | 9895.583   | 11920.62   |           | 5619.645  |
| Bullock County  | 2019 | 1         | 12066.91 | 205      | 29266    | 9519.704   | 14614.12   | 14336.54  |           |
| Butler County   | 2019 | 1         | 14018.61 | 393      | 54804    | 11976.43   | 16060.78   | 15793.58  |           |
| Calhoun County  | 2019 | 1         | 12217.76 | 2333     | 321406   | 11484.59   | 12950.93   | 12955.02  |           |
| Chambers County | 2019 | 1         | 11273.17 | 691      | 93770    | 9948.759   | 12597.58   | 10774.82  |           |
| Cherokee County | 2019 | 1         | 11294.41 | 575      | 71014    | 9767.023   | 12821.8    | 16395.25  |           |
| Chilton County  | 2019 | 1         | 10831.92 | 850      | 123617   | 9733.842   | 11929.99   | 12000.44  |           |
| Choctaw County  | 2019 | 1         | 12047.19 | 273      | 35489    | 9740.13    | 14354.24   | 12215.47  |           |
| Clarke County   | 2019 | 1         | 9688.374 | 412      | 67037    | 8207.626   | 11169.12   | 12447.32  |           |
| Clay County     | 2019 | 1         | 9666.041 | 271      | 36916    | 7821.948   | 11510.13   | 12628.16  |           |
| Cleburne County | 2019 | 1         | 11985.56 | 334      | 41389    | 9955.606   | 14015.5    |           |           |
| Coffee County   | 2019 | 1         | 7933.13  | 743      | 143899   | 7085.258   | 8781.002   | 10333.51  | 6033.742  |
| Colbert County  | 2019 | 1         | 10332.48 | 1016     | 149595   | 9321.505   | 11343.46   | 11604.94  |           |
| Conecuh County  | 2019 | 1         | 10635.37 | 272      | 34170    | 8546.834   | 12723.9    | 11100.61  |           |

# UNDERSTANDING THE DATA

- Difficult to make corrections without understanding data structure
- Look at column names, data types, summary statistics

Summary Statistics

| Variable                | Obs.  | Mean             | Std. Dev. | Min   | Max    |
|-------------------------|-------|------------------|-----------|-------|--------|
| English                 | 1670  | .588             | .492      | 0     | 1      |
| Male                    | 1670  | 0.741            | .438      | 0     | 1      |
| Age                     | 1670  | 2.169<br>(25-35) | .833      | 1     | 4      |
| Final Grades            | 1410  | 11.649           | 2.858     | 3.288 | 19.971 |
| Complete<br>any assign. | 23918 | .138             | .345      | 0     | 1      |
| Completion              | 23918 | .0602            | .458      | 0     | 1      |

# NULL/DUPLICATE VALUES

- Can either drop nulls or replace with mean/median
- Depends on how many nulls and how much variance matters
- Search for duplicates and remove

```
In [7]: df_students.isnull().sum()
```

```
Out[7]: First      0  
Last      0  
Math      2  
Physics   3  
Computers  4  
dtype: int64
```

```
In [155]: #drop the records with age missing in inp0 and copy in inp1 dataframe.  
inp0['age'].dropna(inplace=True)
```

```
In [156]: inp0['age'].isnull().sum()
```

```
Out[156]: 0
```

```
In [157]: inp0.isnull().sum()
```

```
Out[157]: age      20  
salary      0  
balance      0  
marital      0  
targeted     0  
default      0
```

# FORMATTING STRINGS

- Raw data often has string matching issues
  - ex. “New York” vs. “new york” vs. “NY”
- Use functions to homogenize strings

```
In [1]: a = 'MuG'
        a.lower()

Out[1]: 'mug'
```

## Stemming


adjust

## Lemmatization

was → (to) be  
better → good  
meeting → meeting

# OUTLIERS

- Outliers can bias the mean which could negatively affect model output
- Criteria:
  - $< Q1 - (1.5 * IQR)$
  - $> Q3 - (1.5 * IQR)$



# FIXING STRUCTURE

- Sometimes the data is structured in an unusable way
- Splitting columns may be needed
  - ex. extracting month from date

```
current_date = date.today()
print("Year:", current_date.year)
print("Month:", current_date.month)
print("Day:", current_date.day)
```

Year: 2023  
Month: 2  
Day: 18

| Left Table |    |    |   | Right Table |    |   | Result Table |    |    |    |
|------------|----|----|---|-------------|----|---|--------------|----|----|----|
| A          | B  | C  |   | C           | D  |   | A            | B  | C  | D  |
| A2         | B2 | C2 | ↔ | C1          | D1 | = |              |    | C1 | D1 |
| A3         | B3 | C3 |   | C2          | D2 |   | A2           | B2 | C2 | D2 |
| A4         | B4 | C4 |   | C4          | D4 |   | A3           | B3 | C3 |    |
|            |    |    |   | C5          | D5 |   | A4           | B4 | C4 | D4 |
|            |    |    |   |             |    |   |              |    | C5 | D5 |

# WORDS OF ADVICE

- Make edits carefully, and document them
- Never alter the raw data itself; create a copy or new data frame
- Understanding the data and what you want to model is crucial to successful cleaning



**COLAB**



# CODE IT YOURSELF!

Click [this link](#) to download our Retail Stores Dataset.

```
sales_df_cleaned.shape
```

```
(11362, 11)
```

```
# Show null counts
null_counts = sales_df_cleaned.isnull().sum()
print(null_counts)
```

```
Transaction ID    0
Customer ID      0
Category         0
Item             0
Price Per Unit   0
Quantity         0
Total Spent      0
Payment Method   0
Location         0
Transaction Date  0
Discount Applied  0
dtype: int64
```

```
# Show data types of each column
sales_df_cleaned.dtypes
```

```
Transaction ID    object
Customer ID      object
Category         object
Item             object
Price Per Unit   float64
Quantity         float64
Total Spent      float64
Payment Method   object
Location         object
Transaction Date  datetime64[ns]
Discount Applied  object
```

```
# Show summary statistics for the numerical data
sales_df_cleaned.describe(include="number")
```

|              | Price Per Unit | Quantity     | Total Spent  |
|--------------|----------------|--------------|--------------|
| <b>count</b> | 11362.000000   | 11362.000000 | 11362.000000 |
| <b>mean</b>  | 23.356847      | 5.535029     | 129.642537   |
| <b>std</b>   | 10.736030      | 2.855166     | 94.662368    |
| <b>min</b>   | 5.000000       | 1.000000     | 5.000000     |
| <b>25%</b>   | 14.000000      | 3.000000     | 52.000000    |
| <b>50%</b>   | 23.000000      | 6.000000     | 108.500000   |
| <b>75%</b>   | 33.500000      | 8.000000     | 192.000000   |
| <b>max</b>   | 41.000000      | 10.000000    | 410.000000   |

# CODE IT YOURSELF!

```
# Impute 'Unknown' for missing discount  
sales_df['Discount Applied'] = sales_df['Discount Applied'].fillna('Unknown')
```

```
# Drop rows with 2 or more nulls  
sales_df_cleaned = sales_df.dropna(thresh=10)  
sales_df_cleaned.shape
```

```
(11362, 11)
```



**THANKS FOR COMING!**

**NEXT MEETING:  
9/27 - EXPLORATORY DATA ANALYSIS**