SOP-OPS-003 · Private houses everything, public lanes witness

SOP OPS-003 | Status draft | Changed 2026-11-02 | For Stewards and officers

Department: OPS · **ID:** 003 · **Status:** draft (approved when tagged) · **Owner:** repository steward; officers decide each allowlist line · **Last changed:** 2026-11-02

Purpose

Everything the organisation writes lives first in a **private** repository: the house. A **public lane** (a repository whose name ends `-public`) is a witness: it carries only the pages an officer listed, copied by a machine after a tripwire, and nobody edits it by hand. This procedure says how a page reaches a public lane, how the reading room is built from the same mechanism, and why its icons never go stale.


Scope

Every private repository with a public lane: procedures (`ops-standard-operating-procedures` → `-public`), the reading room (`reading-room` → `reading-room-public`), legal (`legal` → `legal-public`, narrow), monitoring outputs, and any lab desk that feeds a room. Site repositories with rehearsal and live lanes follow the same rule through their own build (SOP-OPS-001).

Roles

Role	Does
Officer	decides each allowlist line, by pull request; attests a file a machine could not read
Steward	provisions the deploy key, keeps the workflow, reads the sync's log
Helper	proposes allowlist lines in a pull request; never edits a public lane; never attests
The sync workflow	stages, runs the tripwires, commits to the lane

The mechanism



The rule, in one sentence

> ***A public lane never publishes a file a machine or a person has not read.***

Allowlist, not exclude list. A new file is private until a line names it, so forgetting to list something leaves it private: the safe failure. How the tripwire reads each kind of file, and what nothing opens, is the section after the files.

The files, in a repository that has a public lane

File	What it does
`PUBLIC-ALLOWLIST.txt`	one path per line (a file, or a folder copied whole); no globs, no `..`, no hidden paths. Empty means nothing is public
`PUBLIC-ALLOWLIST-ATTESTED.txt`	files a person opened and read, one per line, never a folder
`scripts/sync-allowlist.sh`	`stage` copies only the listed paths and runs tripwire 1; `apply` writes them into the lane's clone. Runs locally as a dry run
`scripts/scan-public-lane.sh`	tripwire 2: reads every staged file, refuses what it cannot read unless attested
`.github/workflows/sync-public.yml`	runs both on each push to `main` (and after the PDF render), commits to the lane through a **deploy key** held as a secret; inert, and green, until that secret exists

A dry run on your own machine, before an officer says yes to a line (`brew install poppler` once, for `pdftotext`):

```
TRIPWIRE_PUBLIC=1 sh scripts/sync-allowlist.sh stage PUBLIC-ALLOWLIST.txt /tmp/public-stage
```

You should see: the staged paths listed and no `tripwire:` line; `ls /tmp/public-stage` shows exactly the allowlist.

The tripwire: a public lane never publishes a file a machine or a person has not read

Every public lane (a `-public` twin, a public reading room, a public monitor) is filled by a sync that copies only the allowlisted paths. Before anything is pushed, a tripwire reads **every** staged file. The rule is one sentence:

> ***A public lane never publishes a file a machine or a person has not read.***

Before 2026-11-01 the check read only plain text, so a PDF, a picture or a Word file passed through unread. Now each kind of file is read its own way, or stopped.

How each file is read

	Kind of file	How the tripwire reads it	Stopped when
	Text (Markdown, HTML, SVG, scripts)	read directly	it carries a credential, a pointer into agent notes, or a sensitive shape (below)

	PDF	its words are pulled out with `pdftotext` and read the same way	the same, **or** it has no words at all, or some pages have none (a scan, an image-only page), or it will not open
	`.docx`, `.xlsx`, `.pptx`, OpenDocument	unzipped; the text inside is read	the same, **or** it carries an embedded picture or object
	Pictures and fonts	checked to be what their name says	they sit anywhere other than an `assets/` or `icons/` folder
	Anything else (archives, old `.doc`, unknown binaries)	cannot be read here	always, unless a person attests it

Sensitive shapes are the ones a public page should almost never carry: an employer or social-security number shape, a label for a tax identifier or a birth date, a street address or post-office box, the word for a giver of gifts, an account number longer than four digits beside its label, and the fleet's personal-matter words. The exact patterns live in the script, assembled from pieces so the script itself can travel; this page names them in plain words so it can travel too.

When a person reads it instead: attestation


A machine cannot read a scanned letter or a photograph. A person can. When the tripwire stops a file it prints the exact line to add, and an officer who has **opened the file and read every page** adds it to `PUBLIC-ALLOWLIST-ATTESTED.txt` by pull request:


```
pdf/OPS/SOP-OPS-001-how-a-change-travels.pdf | <officer> | 2026-11-01 | opened and read | sha256:
<fingerprint>
```


The fingerprint is optional and recommended: with it, the attestation ends the moment the file changes, and the next sync asks for a fresh reading. An attestation clears a sensitive shape, a picture outside `assets/`, and a PDF with no words. It never clears the three things below.

What nothing opens

1. **A credential or a pointer into agent notes** found in any readable text, attested or not. Remove it from the file.
2. **The legal lanes by path:** `entity/`, `tax/`, `filings/`, `counsel/`. A file under any of them is refused whatever the allowlist or an attestation says. The legal public lane carries only its README, its folder map and policy skeletons.
3. **Names that never travel:** agent-note folders, tool configuration (`CLAUDE.md`, `AGENTS.md`, `.claude/`, `.github/`), keys, wallets, environment files, symbolic links, and any file over 15 MB.


A file the allowlist names
Under entity/, tax/, filings/ or counsel/? A name that never travels?
no
yes
Can a machine read it? text, PDF words, office text
yes


A credential or an agent-note pointer?
yes
no
no: a scan, a picture, a binary
Refused. Nothing opens it
A sensitive shape?
yes
no
Attested: opened and read (and the fingerprint still matches)?




Running it yourself

```
brew install poppler                                  # once, on a Mac: gives pdftotext
sh scripts/scan-public-lane.selftest.sh               # proves it: a planted fake number in a PDF must be refused
TRIPWIRE_PUBLIC=1 sh scripts/sync-allowlist.sh stage PUBLIC-ALLOWLIST.txt /tmp/stage   # a dry run of the sync
sh scripts/scan-public-lane.sh /tmp/stage PUBLIC-ALLOWLIST-ATTESTED.txt                # or scan any folder
```

You should see: `every file read; clean`, or a list of refused files, each with its reason. The scanner never prints what it matched, only the kind of match and where, so a found secret does not land in a log. On GitHub the sync installs `pdftotext` (`poppler-utils`) and runs the self-test before every sync; without a PDF reader, no PDF travels.

Master copy: `my-template/scripts/scan-public-lane.sh` and its self-test. Every repository's copy is the master, byte for byte; the self-test in my-template checks the SOP template's copies.

The reading room, built the same way



- **The private room** gathers what members may read. Each source writes only into its own folder (`PREFIX`), so two sources never overwrite each other. Its README is the index; PDFs sit beside the markdown. Members read it through the **readers** team (SOP-IT-002, SOP-GOV-002).
- **The public room** receives only the allowlisted pages of the private room. Its own top-level files (its README, its Pages front end) are **reserved**: the sync never overwrites them. With `MANIFEST` set, each sync writes the list of what it carried, so the front end shows exactly what arrived.
- **The public room links to the private one.** A visitor who clicks it sees a 404; a member sees the room. Names may be public; contents stay private (`my-template/NAMES-POLICY.md`).

- **Decks:** welcome decks live in the organisation's public `.github/decks/` ; members-only decks live in the private room. The rooms link to the decks rather than copying them.

Icons that never go stale

Every page draws its icons from the repository's own `assets/icons/` with a relative path (`../assets/icons/route.svg`). Put `assets/icons` on the allowlist as one line, and every sync carries the whole folder from the house to the lane. A recoloured or added icon in the house reaches the lane on the next sync; nobody copies icons by hand, so the lane's icons cannot drift. (Pictures under `assets/` or `icons/` are the one kind of image tripwire 2 accepts without an attestation.)

PIR®'s public lanes, and where the tripwire stands (read 2026-11-01)

Every sync in `psychedelicsinrecovery` that writes to a public repository, found by listing each repository's workflows (not from memory), and what the PDF-reading tripwire found when it was run over what each lane publishes. **Enforced** means a refusal stops the sync. **Report** means the tripwire runs on every sync and names each file it would refuse as a warning, without stopping a lane that is already live; each report lane becomes enforced (`TRIPWIRE_ENFORCE: "1"` in its workflow) once an officer has dealt with the files named.

	Source → public lane	How it copies	Live?	Tripwire	What it found
	`ops-standard-operating-procedures` → `-public`	allowlist, deploy key	inert until `SOP_PUBLIC_DEPLOY_KEY`	**enforced**	clean: the universal procedures, their PDFs, `assets/icons`
	`reading-room` → `reading-room-public`	allowlist, deploy key; `public-site/` becomes the room's front page	inert until `READING_ROOM_PUBLIC_DEPLOY_KEY`	**enforced**	clean: 000 *Start here* and the procedure PDFs
	`board-of-directors` → `-public`	filter-repo (history travels)	live	**enforced**	clean, at the head and in every version in history
	`public-relations` → `-public`	filter-repo	live	**enforced**	clean, head and history
	`catalyst-desk` → `-public`	`site/` copied	live	**enforced**	clean
	`alex-desk` → `-public`	the built `site/dist`	live	**enforced**	clean (the published copy)
	`pr-desk`, `github-desk`, `techcom-desk`, `litcom-desk` → `-public`	`portal/` copied	live	report	one picture each, `social-card.jpg`, at the portal's root (outside `assets/`): an officer opens it and attests it
	`literature-committee` → `-public`	filter-repo	live	report	four Keynote decks (`publications/2026/*.key`) travel unread: no machine reads a Keynote file, and the `.key` name never travels. An officer exports each as a PDF and lists the PDFs instead

	`tech-committee` → `-public`	filter-repo	live	report	a few files for an officer to review (the list is kept with the steward, not here); two street-address shapes in the public website's crawl (meeting and convention venues) for an officer to attest
	`changelog-astro` → `-public`	the built Astro site, over a filtered history	live	report	128 generated share pictures under `og/` (outside `assets/`); street-address shapes in five pages and feeds (meeting places on the map, `rss.xml`, `search.json`, `latest.json`) for an officer to attest; anything else for review is listed with the steward, not here
	`.github-private` → `.github` (`CONTACTS.md` only)	`scripts/publish-public-contacts.py` writes a masked copy (personal emails as `***`, members-only sections left out)	live	**none yet**	not run: this lane was missed in the first listing and added on review (2026-11-01). It carries one markdown file, so the tripwire's text checks apply; the next step is the same tripwire step in `publish-public-contacts.yml`
	the lab desk `drasticstatic/pir` → `reading-room/from-the-lab/`	allowlist, deploy key	inert	not a public lane	private to private: the room's members read it, visitors never do

Each source carries its own copy of `scripts/scan-public-lane.sh` and its self-test, byte for byte the master in `my-template/scripts/`, and each sync runs the self-test before it scans.

Steps: publishing a page


1. Open a pull request that adds the page's path (and its PDF's path, and `assets/icons` if not already there) to `PUBLIC-ALLOWLIST.txt`. *You should see:* a one-line diff per path.
2. Run the dry run above, and paste its result into the pull request. *You should see:* no `tripwire:` line.
3. If the dry run refuses a file a machine cannot read, an officer opens it, reads every page, and adds an attestation line in the same pull request.
4. An officer merges (merge commit). *You should see:* the sync workflow run on `main`, green.
5. Open the lane. *You should see:* the page and its icons; nothing else new.

To withdraw a page: remove its line by pull request. The next sync removes it from the lane. (Git history in the lane keeps the old commit; if the page should never have been public, tell the steward, who decides whether the lane's history needs more.)

Rotating a deploy key

A deploy key lets one repository's sync write to one lane. **Rotate it** when someone who could have reached it leaves, when a machine or a secret may have been exposed, or when the steward's yearly habit comes round. The lane just waits while you do this: no site goes down and nothing is lost.

Source → lane	Secret on the source
psychedelicsinrecovery/ops-standard-operating-procedures → psychedelicsinrecovery/ops-standard-operating-procedures-public	SOP_PUBLIC_DEPLOY_KEY
psychedelicsinrecovery/reading-room → psychedelicsinrecovery/reading-room-public	READING_ROOM_PUBLIC_DEPLOY_KEY
psychedelicsinrecovery/legal → psychedelicsinrecovery/legal-public	LEGAL_PUBLIC_DEPLOY_KEY
a lab desk → psychedelicsinrecovery/reading-room	READING_ROOM_DEPLOY_KEY



The private half is never printed, opened or pasted. It goes from a temporary file straight into `gh secret set`, then the file is deleted. Only the steward's machine ever holds it, and only for these few minutes. A helper may prepare the commands; the steward runs them.

1. **Generate.** In a temporary folder that only you can read:

   ```
   umask 077; T="$(mktemp -d)"
   ssh-keygen -t ed25519 -N "" -C "<secret name>" -f "$T/key"
   ssh-keygen -lf "$T/key.pub"
   ```

   You should see: one line with a fingerprint starting `SHA256:`. Note it; the fingerprint is safe to write down.
2. **Add** the public half to the lane, with today's date in its title:

   ```
   gh repo deploy-key add "$T/key.pub" -R <lane> --allow-write --title "sync from <source>
   (<secret name>, YYYY-MM-DD)"
   ```

   You should see: a confirmation. The lane now has two keys, the old and the new.
3. **Set** the private half as the secret on the source, and on a second source if two share this key (see below):

   ```
   gh secret set <secret name> -R <source> < "$T/key"
   ```

   You should see: `Set Actions secret`.
4. **Remove** the old key from the lane, and delete the temporary files:

   ```
   gh repo deploy-key list -R <lane>
   gh repo deploy-key delete <id of the old key> -R <lane>
   rm -f "$T/key" "$T/key.pub"; rmdir "$T"
   ```

   You should see: the list showing both keys, then, listed again, only the new one. The old one goes before you test, because a key being rotated for a reason shouldn't stay open while you check.
5. **Verify.** Run the source's sync workflow (its file is in `.github/workflows/`), from its **Actions** tab or here, then watch it:

```
gh workflow run <sync workflow file> -R <source>
gh run list -R <source> --limit 3
```

You should see: the sync green, and the lane's newest commit holding only allowlisted paths. **A run with nothing new to carry makes no commit, and proves only that the key can read;** the next real change proves it can write, so look at the lane once more after that one.

Two sources, one lane. Each deploy key belongs to one repository, and GitHub refuses the same public half twice. When two sources feed one room, they either share one key, with the same private half set as a secret on both, or each has its own key on the lane. Before you delete the temporary files, set every secret that used the old key, or that source's next sync stops.

Afterwards, record the title, fingerprint and date in the steward's key record. Never the private half.

Symptom	Likely cause	What to do
`key is already in use` when adding	that public half is on another repository	generate a new pair; never reuse one
The sync fails with `Permission denied (publickey)`	the secret and the lane's key don't match, or `--allow-write` was left off	start again from step 1, and remove the key that didn't work
The sync is green but says it's inert	the secret's name doesn't match the workflow's	`gh secret list -R <source>`, and compare with the workflow

Verification

The lane's tree contains exactly the allowlisted paths plus its reserved files; the last sync run is green; `PUBLIC-ALLOWLIST-ATTESTED.txt` names an officer and a date for every non-text file in the lane outside `assets/` and `icons/`.

Troubleshooting

Symptom	Likely cause	What to do
The sync run is green but nothing changed	the deploy key secret is not provisioned yet (inert by design), or the allowlist is empty	the steward provisions the key; an officer adds a line
`tripwire:` refuses a PDF	it has no extractable text (a scan) or a sensitive shape	read it; attest it, or replace it with a text PDF; never attest a personal matter
The lane's icons are missing	`assets/icons` is not on the allowlist	add the line
Someone edited the lane by hand	the next sync overwrites what it owns	make the change in the house instead
The sync fails pushing to the lane	the strict ruleset on a lane	lanes take the deletion-only ruleset (`my-template/branch-protection/`)

Related

- SOP-OPS-001 *How a change travels* · SOP-OPS-002 *Pull requests and Promotes* · SOP-IT-002 *Reading room and helper access* · SOP-GOV-002 *GitHub collaboration*

- `my-template/NAMES-POLICY.md` (names may be public, contents stay private), `my-template/LUCID.md` (icons and diagrams)
- `my-template/workflow-templates/sync-public-allowlist.yml` (the same pattern for any repository)

Change log

Date	Change	By
2026-11-01	Drafted: the rule (a public lane never publishes a file a machine or a person has not read), the allowlist files, the reading room's mechanics, icons carried by the sync; the tripwire section included whole from `OPS/_fragments/tripwire.md` (the tripwire package's own text)	Alfred
2026-11-01	PIR®'s copy: PIR®'s thirteen public lanes and the tripwire's reading of each (six enforced, seven in report mode, with what an officer needs to do), found by listing every repository's workflows	Alfred
2026-11-01	Review: a fourteenth lane added, `.github-private → .github` (the masked `CONTACTS.md`), which the first listing missed; it has no tripwire yet	Alfred
2026-11-01	Review: the `tech-committee` and `changelog-astro` rows name only what an officer attests; the fuller review list is kept with the steward	Alfred
2026-11-02	*Rotating a deploy key*: generate, add, set the secret, remove the old, verify; the private half is never printed	Alfred

Part of the fleet's procedures. The master copies and the legend live in my-template.