BRIGHT LED ELECTRONICS CORP.

SINCE 1981

DATA SHEET

●DEVICE NUMBER：BL-B2134-1

SHEET / DATE	1	2	3								CONTENTS
2009.3.3	1.0	1.0	1.0								Original Released

佰鴻工業股份有限公司

BRIGHT LED ELECTRONICS CORP.

台北縣板橋市和平路 19 號 3 樓

3F., No. 19, Ho Ping Road, Pan Chiao City, Taipei, Taiwan, R. O. C.

Tel: 886-2-29591090

Fax: 886-2-29547006/29558809

www.brtled.com.

APPROVED	DRAWER
馬 2009.3.3 駿	危 2009.3.3 燕紅

Http://www.brtled.com


Features:

1. Chip material: GaP/GaP
2. Emitted color : Green
3. Lens Appearance : Green Diffused
4. Low power consumption.
5. High efficiency.
6. Versatile mounting on P.C. Board or panel.
7. Low current requirement.
8. 5mm diameter package
9. This product don't contained restriction substance, compliance ROHS standard.

Applications:

1. TV set
2. Monitor
3. Telephone
4. Computer
5. Circuit board

Package dimensions:



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ±0.25mm (0.01") unless otherwise specified.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.

Absolute maximum ratings(Ta=25℃)

Parameter	Symbol	Rating	Unit
Power Dissipation	Pd	80	mW
Forward Current	I_F	30	mA
Peak Forward Current*[1]	I_{FP}	150	mA
Reverse Voltage	V_R	5	V
Operating Temperature	Topr	-40℃~85℃	
Storage Temperature	Tstg	-40℃~100℃	
Soldering Temperature	Tsol	260℃max (for 5 seconds)	
Hand Soldering Temperature	Tsol	350℃max(for 3 seconds)	

*[1]Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width.

● Electrical and optical characteristics(Ta=25℃)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	I_F=20mA	-	2.2	2.6	V
Luminous Intensity	Iv	I_F=20mA	-	30	-	mcd
Reverse Current	I_R	V_R=5V	-	-	100	μA
Peak Wave Length	λp	I_F=20mA	-	568	-	nm
Dominant Wave Length	λd	I_F=20mA	560	-	576	nm
Spectral Line Half-width	Δλ	I_F=20mA	-	30	-	nm
Viewing Angle	$2\theta_{1/2}$	I_F=20mA	-	50	-	deg

● Typical electro-optical characteristics curves

Fig.1 Relative intensity vs. Wavelength




Fig.2 Forward current derating curve vs. Ambient temperature




Fig.3 Forward current vs. Forward voltage




Fig.4 Relative luminous intensity vs. Ambient temperature




Fig.5 Relative luminous intensity vs. Forward current





Fig.6 Radiation diagram



● DIP soldering (Wave Soldering)

Preheating : 120℃,within 120~180 sec.
Operation heating : 255℃±5℃ within 5 sec.260℃ (Max)
Gradual Cooling (Avoid quenching).

