
Transforming and summarising data

10/11/2026

Plotting using ggplot2

```
ggplot(data = mpg,
       mapping = aes(x = displ,
                     y = hwy,
                     colour = factor(cyl)))
  geom_point() +
  geom_smooth(method = "lm", se = FALSE) +
  labs(x = "Engine displacement (litres)",
       y = "Highway miles per gallon",
       colour = "Cylinders")
```

```
## `geom_smooth()` using formula = 'y ~ x'
```



Importing your data

Fear of Crime Dataset

Ellis & Renouf (2018) - the relationship between fear of crime and various personality measures.

Their data is openly available, stored as text in a *comma-separated-values* format (*.csv*).

Once again, we can use the import button or some code (with `read_csv()`) to load this data in and automatically format it into a *tibble*.

```
library(readr)
FearofCrime <- read_csv("data/FearofCrime.CSV")
```

Fear of Crime Dataset

Ellis & Renouf (2018) collected data online using Qualtrics.

The file contains one column for each question that the participants answered, for a total of 169(!) columns.

Each row is a single participant's answers, and their demographic information.

```
FearofCrime
```

```
## # A tibble: 301 × 169
##    ResponseID Respo…¹ Name  Exter…² Status Start…³ EndDate Finis…⁴ Conse…⁵   sex
##    <chr>      <chr>   <chr> <lgl>    <dbl> <chr>   <chr>     <dbl>   <dbl> <dbl>
##  1 R_ai4tgG1… Defaul… Anon… NA           0 19/10/… 19/10/…       1       1     2
##  2 R_d5OiATV… Defaul… Anon… NA           0 20/10/… 20/10/…       1       1     2
##  3 R_aaBVZUe… Defaul… Anon… NA           0 20/10/… 20/10/…       1       1     1
##  4 R_6nxInLK… Defaul… Anon… NA           0 20/10/… 20/10/…       1       1     1
##  5 R_6SCYbhO… Defaul… Anon… NA           0 20/10/… 20/10/…       1       1     2
##  6 R_5pCxWA6… Defaul… Anon… NA           0 20/10/… 20/10/…       1       1     1
##  7 R_d1nji6V… Defaul… Anon… NA           0 20/10/… 20/10/…       1       1     2
##  8 R_9v6ZgUh… Defaul… Anon… NA           0 20/10/… 20/10/…       1       1     1
##  9 R_5Bg7VjB… Defaul… Anon… NA           0 20/10/… 20/10/…       1       1     2
## 10 R_9Sv17lQ… Defaul… Anon… NA           0 20/10/… 20/10/…       1       1     2
## # … with 291 more rows, 159 more variables: age <dbl>, hexaco1 <dbl>,
## #   hexaco2 <dbl>, hexaco3 <dbl>, hexaco4 <dbl>, hexaco5 <dbl>, hexaco6 <dbl>,
```

Prison population

Last week, we looked at some data regarding the UK's prison population.


The data is contained in an Excel spreadsheet, downloaded from data.gov.uk.


```
library(readxl)
prison_pop <- read_excel("data/prison-population-data-tool-31-december-2017.xlsx",
                         sheet = "PT Data")
```


We use the `read_excel()` function to read Excel files.

Note how the file name and location come first, and then I specify a specific *sheet*.

Excel spreadsheets often have multiple sheets with different information.


RStudio
File Edit Code View Plots Session Build Debug Profile Tools Help
Go to file/function
Addins
Project: (None)
FearofCrime
Filter
Cols: « < 1 - 50 > »
hexaco9 hexaco10 hexaco11 hexaco12 hexaco13 hexaco14 hexaco15 hexaco16 hexaco17 hexaco18 hexaco19
5 4 2 4 4 4 2 5 5 2 3 4
2 4 2 3 4 5 1 4 3 2 3 2
4 3 4 2 5 4 1 3 1 4 3 2
4 3 1 1 4 5 2 5 1 1 5 1
2 2 1 2 2 2 2 2 5 3 3 2
4 2 5 2 4 4 2 2 2 2 2 1
4 4 1 3 4 5 2 3 2 4 2 2
4 4 1 2 4 4 2 3 4 4 4 1
2 4 2 2 4 5 2 2 2 4 4 1
4 4 2 4 4 2 3 5 3 3 2 3
2 4 4 4 4 5 2 4 4 4 2 2
4 4 2 2 4 4 4 4 3 2 3 2
4 4 3 2 4 5 2 4 4 4 2 3
2 4 5 3 5 2 2 2 1 1 4 2
4 2 2 2 4 4 2 3 2 2 2 4
5 4 2 2 4 2 1 4 2 4 5 4
Showing 1 to 16 of 301 entries, 169 total columns
Environment History Connections Tutorial
Import Dataset
From Text (base)...
From Text (readr)...
From Excel...
From SPSS...
From SAS...
From Stata...
301 obs. of 169 variables
Files Plots Packages Help Viewer Presentation
Install Update
Name Description Version
User Library
abind Combine Multidimensional Arrays 1.4-5
ade4 Analysis of Ecological Data: Exploratory and Euclidean Methods in Environmental Sciences 1.7-22
ADGofTest Anderson-Darling GoF test 0.3
afex Analysis of Factorial Experiments 1.1-1
aod Analysis of Overdispersed Data 1.3.2
apaTables Create American Psychological Association (APA) Style Tables 2.0.8
ape Analyses of Phylogenetics and Evolution 5.6-2
arm Data Analysis Using Regression and Multilevel/Hierarchical Models 1.11-2
AsioHeaders 'Asio' C++ Header Files 1.22.1-2
askpass Safe Password Entry for R, Git, and SSH 1.1
assertthat Easy Pre and Post Assertions 0.2.1
backports Reimplementations of Functions Introduced Since R-3.0.0 1.4.1
base64enc Tools for base64 encoding 0.1-3
BayesFactor Computation of Bayes Factors for Common Designs 0.9.12-4.2
bayesplot Plotting for Bayesian Models 1.8.0
bayestestR Understand and Describe Bayesian Models and Posterior Distributions 0.13.2
BBmisc Miscellaneous Helper Functions for B. Bischl 1.12
beeswarm The Bee Swarm Plot, an Alternative to Stripchart 0.4.0
benchmarkmeData Data Set for the 'benchmarkme' Package 1.0.4
bfw Bayesian Framework for Computational Modeling 0.4.2
BH Boost C++ Header Files 1.81.0-1
bigD Flexibly Format Dates and Times to a Given Locale 0.2.0
binom Binomial Confidence Intervals For Several Parameterizations 1.1-1
biotools Tools for Biometry and Applied Statistics in Agricultural Science 4.3
bit Classes and Methods for Fast Memory-Efficient Boolean Selections 4.0.5
bit64 A S3 Class for Vectors of 64bit Integers 4.0.5
Console Terminal Background Jobs
R 4.0.5 · ~/
Rows: 301 Columns: 169
-- Column specification --
Delimiter: ","
chr (5): ResponseID, ResponseSet, Name, StartDate, EndDate
dbl (163): Status, Finished, Consent Form / This study includes a range ...
lgl (1): ExternalDataReference
i Use `spec()` to retrieve the full column specification for this data.
i Specify the column types or set `show_col_types = FALSE` to quiet this message.
> View(FearofCrime)
>


RStudio
File Edit Code View Plots Session Build Debug Profile Tools Help
Import Excel Data
File/URL:
D:/Backup 2024 June Sandisk/Teaching/RM&S/2026-27/Blackboard/Data/prison-population-data-tool-31-december-2017.xlsx
Browse...
Data Preview:
Offender Management Statistics - Prison Population Data Tool
(character)
Quarterly Prison Population at 30 June 2015 - 31 De...
NA
User Guide
Previewing first 50 entries.
Import Options:
Name: prison_population_data_t
Sheet: Default
Range: A1:D10
First Row as Names
Open Data Viewer
Code Preview:
library(readxl)
prison_population_data_tool_31_december_2017 <- read_excel("D:/Backup 2024 June Sandisk/Teaching/RM&S/2026-27/Blackboard/Data/prison-population-data-tool-31-december-2017.xlsx")
Reading Excel files using readxl
Import
Cancel
Environment
History
Connections
Tutorial
bit
Classes and Methods for Fast Memory-Efficient Boolean Selections
4.0.5
bit64
A S3 Class for Vectors of 64bit Integers
4.0.5


RStudio
File Edit Code View Plots Session Build Debug Profile Tools Help
Import Excel Data
File/URL:
D:/Backup 2024 June Sandisk/Teaching/RM&S/2026-27/Blackboard/Data/prison-population-data-tool-31-december-2017.xlsx
Browse...
Data Preview:
View (character)
Date (character)
Establishment (character)
Sex (character)
Age / Custody / Nationality / Offence Group (character)
Population (double)
a Establishment*Sex*Age Group 2015-06 Altcourse Male Adults (21+) 922
a Establishment*Sex*Age Group 2015-06 Altcourse Male Juveniles and Young Adults (15-20) 169
a Establishment*Sex*Age Group 2015-06 Ashfield Male Adults (21+) 389
a Establishment*Sex*Age Group 2015-06 Askham Grange Female Adults (21+) NA
a Establishment*Sex*Age Group 2015-06 Askham Grange Female Juveniles and Young Adults (15-20) NA
a Establishment*Sex*Age Group 2015-06 Aylesbury Male Adults (21+) 113
a Establishment*Sex*Age Group 2015-06 Aylesbury Male Juveniles and Young Adults (15-20) 268
a Establishment*Sex*Age Group 2015-06 Bedford Male Adults (21+) 459
a Establishment*Sex*Age Group 2015-06 Bedford Male Juveniles and Young Adults (15-20) 30
a Establishment*Sex*Age Group 2015-06 Belmarsh Male Adults (21+) 794
a Establishment*Sex*Age Group 2015-06 Belmarsh Male Juveniles and Young Adults (15-20) 74
a Establishment*Sex*Age Group 2015-06 Birmingham Male Adults (21+) 1434
a Establishment*Sex*Age Group 2015-06 Brinsford Male Adults (21+) 33
a Establishment*Sex*Age Group 2015-06 Brinsford Male Juveniles and Young Adults (15-20) 349
a Establishment*Sex*Age Group 2015-06 Bristol Male Adults (21+) 553
a Establishment*Sex*Age Group 2015-06 Bristol Male Juveniles and Young Adults (15-20) 42
a Establishment*Sex*Age Group 2015-06 Brixton Male Adults (21+) 787
a Establishment*Sex*Age Group 2015-06 Bronzefield Female Adults (21+) 459
a Establishment*Sex*Age Group 2015-06 Bronzefield Female Juveniles and Young Adults (15-20) 24
a Establishment*Sex*Age Group 2015-06 Buckley Hall Male Adults (21+) 440
Previewing first 50 entries.
Import Options:
Name: prison_population_data_t
Sheet: PT Data
Range: A1:D10
Max Rows:
Skip: 0
NA:
First Row as Names
Open Data Viewer
Code Preview:
library(readxl)
prison_population_data_tool_31_december_2017 <- read_excel("D:/Backup 2024 June Sandisk/Teaching/RM&S/2026-27/Blackboard/Data/prison-population-data-tool-31-december-2017.xlsx",
Reading Excel files using readxl
Import
Cancel

Prison population

Once the data is imported, we have a `tibble`.

We can immediately see there are 6 columns with 22409 rows.

```
prison_pop
```

```
## # A tibble: 22,409 × 6
##    View                          Date    Establishment Sex    Age / Cu…¹ Popul…²
##    <chr>                         <chr>   <chr>         <chr>  <chr>        <dbl>
##  1 a Establishment*Sex*Age Group 2015-06 Altcourse     Male   Adults (2…     922
##  2 a Establishment*Sex*Age Group 2015-06 Altcourse     Male   Juveniles…     169
##  3 a Establishment*Sex*Age Group 2015-06 Ashfield      Male   Adults (2…     389
##  4 a Establishment*Sex*Age Group 2015-06 Askham Grange Female Adults (2…      NA
##  5 a Establishment*Sex*Age Group 2015-06 Askham Grange Female Juveniles…      NA
##  6 a Establishment*Sex*Age Group 2015-06 Aylesbury     Male   Adults (2…     113
##  7 a Establishment*Sex*Age Group 2015-06 Aylesbury     Male   Juveniles…     268
##  8 a Establishment*Sex*Age Group 2015-06 Bedford       Male   Adults (2…     459
##  9 a Establishment*Sex*Age Group 2015-06 Bedford       Male   Juveniles…      30
## 10 a Establishment*Sex*Age Group 2015-06 Belmarsh      Male   Adults (2…     794
## # … with 22,399 more rows, and abbreviated variable names
## #   ¹`Age / Custody / Nationality / Offence Group`, ²Population
```

We need to do more work to make this file useable...

dpylr and data transformation



Data transformation



With datasets like those we've loaded, there are often organisational issues.

For example, there could be many columns or rows we don't need, or the data would make more sense if it were sorted.

This is where `dplyr` comes in!

Function	Effect
select()	Include or exclude variables (columns)
arrange()	Change the order of observations (rows)
filter()	Include or exclude observations (rows)
mutate()	Create new variables (columns)
group_by()	Create groups of observations
summarise()	Aggregate or summarise groups of observations (rows)

Selecting columns

Selecting columns



Sometimes only some columns are of interest.

The Fear of Crime dataset has 169 columns. Only some of them are useful; here are the first ten.

```
names(FearofCrime)[1:10]
```

```
##  [1] "ResponseID"
##  [2] "ResponseSet"
##  [3] "Name"
##  [4] "ExternalDataReference"
##  [5] "Status"
##  [6] "StartDate"
##  [7] "EndDate"
##  [8] "Finished"
##  [9] "Consent Form / This study includes a range of questionnaires collecting / demographic and i
## [10] "sex"
```

Selecting columns



We pass the name of the data frame that we want to select from, and the names of each column we want to keep after that.

Suppose that, first of all, we were only interested in the age and sex of our participants.

```
select(FearofCrime, age, sex)
```

```
## # A tibble: 301 × 2
##      age   sex
##    <dbl> <dbl>
##  1    26     2
##  2    66     2
##  3    41     1
##  4    46     1
##  5    53     2
##  6    33     1
##  7    41     2
##  8    39     1
##  9    38     2
## 10    19     2
## # … with 291 more rows
```

Selecting columns



The HEXACO-PI-R is a personality questionnaire that aims to measure six factors - Honesty-Humility, Emotionality, Extraversion, Agreeableness, Conscientiousness, and Openness to Experience.

The Fear of Crime dataset has the participants answers to the 60 questions of the HEXACO-PI-R in 60 columns.

```
select(FearofCrime, hexaco1,
       hexaco2, hexaco3)
```

```
## # A tibble: 8 × 3
##   hexaco1 hexaco2 hexaco3
##     <dbl>   <dbl>   <dbl>
## 1       4       5       2
## 2       2       4       2
## 3       1       5       2
## 4       1       5       2
## 5       2       4       4
## 6       2       4       2
## 7       1       5       4
## 8       2       4       3
```

Selecting columns



Typing these out one by one would be ... *laborious*.

Fortunately, there are some shorthands.

The colon (:) operator can be used to say "everything between these columns (inclusive)".

```
select(FearofCrime, hexaco1:hexaco5)
```

```
## # A tibble: 301 × 5
##    hexaco1 hexaco2 hexaco3 hexaco4 hexaco5
##      <dbl>   <dbl>   <dbl>   <dbl>   <dbl>
##  1       4       5       2       4       1
##  2       2       4       2       4       4
##  3       1       5       2       3       2
##  4       1       5       2       4       1
##  5       2       4       4       5       5
##  6       2       4       2       2       2
##  7       1       5       4       4       4
##  8       2       4       3       2       2
##  9       1       2       4       2       5
## 10       4       4       2       3       2
## # … with 291 more rows
```

Selecting columns



Note that you can also tell `select()` to *remove* columns using the minus (-) sign.

```
select(FearofCrime, -ResponseSet, -Name, -Status, -ExternalDataReference)
```

```
## # A tibble: 301 × 165
##    Respons…¹ Start…² EndDate Finis…³ Conse…⁴   sex   age hexaco1 hexaco2 hexaco3
##    <chr>     <chr>   <chr>     <dbl>   <dbl> <dbl> <dbl>   <dbl>   <dbl>   <dbl>
##  1 R_ai4tgG… 19/10/… 19/10/…       1       1     2    26       4       5       2
##  2 R_d5OiAT… 20/10/… 20/10/…       1       1     2    66       2       4       2
##  3 R_aaBVZU… 20/10/… 20/10/…       1       1     1    41       1       5       2
##  4 R_6nxInL… 20/10/… 20/10/…       1       1     1    46       1       5       2
##  5 R_6SCYbh… 20/10/… 20/10/…       1       1     2    53       2       4       4
##  6 R_5pCxWA… 20/10/… 20/10/…       1       1     1    33       2       4       2
##  7 R_d1nji6… 20/10/… 20/10/…       1       1     2    41       1       5       4
##  8 R_9v6ZgU… 20/10/… 20/10/…       1       1     1    39       2       4       3
##  9 R_5Bg7Vj… 20/10/… 20/10/…       1       1     2    38       1       2       4
## 10 R_9Sv17l… 20/10/… 20/10/…       1       1     2    19       4       4       2
## # … with 291 more rows, 155 more variables: hexaco4 <dbl>, hexaco5 <dbl>,
## #   hexaco6 <dbl>, hexaco7 <dbl>, hexaco8 <dbl>, hexaco9 <dbl>, hexaco10 <dbl>,
## #   hexaco11 <dbl>, hexaco12 <dbl>, hexaco13 <dbl>, hexaco14 <dbl>,
## #   hexaco15 <dbl>, hexaco16 <dbl>, hexaco17 <dbl>, hexaco18 <dbl>,
## #   hexaco19 <dbl>, hexaco20 <dbl>, hexaco21 <dbl>, hexaco22 <dbl>,
## #   hexaco23 <dbl>, hexaco24 <dbl>, hexaco25 <dbl>, hexaco26 <dbl>,
```

Creating new columns

Creating new columns



Here is a version of the Fear of Crime data where participants' overall scores on the various personality measures have been calculated.

```
crime
```

```
## # A tibble: 301 × 15
##    Partici…¹ sex     age victi…²     H     E     X     A     C     O    SA    TA
##    <chr>     <chr> <dbl> <chr>   <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
##  1 R_01TjXg… male     55 yes       3.7   3     3.4   3.9   3.2   3.6  1.15  1.55
##  2 R_0dN5Ye… fema…    20 no        2.5   3.1   2.5   2.4   2.2   3.1  2.05  2.95
##  3 R_0DPiPY… male     57 yes       2.6   3.1   3.3   3.1   4.3   2.8  2     2.6
##  4 R_0f7bSs… male     19 no        3.5   1.8   3.3   3.4   2.1   2.7  1.55  2.1
##  5 R_0rov2R… fema…    20 no        3.3   3.4   3.9   3.2   2.8   3.9  1.3   1.8
##  6 R_0wioqG… fema…    20 no        2.6   2.6   3     2.6   2.9   3.4  2.55  1.5
##  7 R_0wRO8l… male     34 yes       3.2   2.5   3.2   2.8   4     3.2  1.85  1.75
##  8 R_116nEd… fema…    19 no        2.9   4     3.9   4.2   3.7   1.9  1.1   2
##  9 R_11ZmBd… fema…    19 yes       3.4   3.4   3.3   3.4   3.2   3.2  2.2   2.9
## 10 R_12i26Q… male     20 no        2.4   2.1   1.8   2.2   3.4   2.9  2.15  2.4
## # … with 291 more rows, 3 more variables: OHQ <dbl>, FoC <dbl>, Foc2 <dbl>, and
## #   abbreviated variable names ¹Participant, ²victim_crime
```

Creating new columns




```
crime_sub <- select(crime,
                    age, SA, TA, sex)
mutate(crime_sub, age_group = ifelse(age > 40,
                                     "Over 40",
                                     "40 or under"))
```

```
## # A tibble: 301 × 5
##      age    SA    TA sex    age_group
##    <dbl> <dbl> <dbl> <chr>  <chr>
##  1    55  1.15  1.55 male   Over 40
##  2    20  2.05  2.95 female 40 or under
##  3    57  2     2.6  male   Over 40
##  4    19  1.55  2.1  male   40 or under
##  5    20  1.3   1.8  female 40 or under
##  6    20  2.55  1.5  female 40 or under
##  7    34  1.85  1.75 male   40 or under
##  8    19  1.1   2    female 40 or under
##  9    19  2.2   2.9  female 40 or under
## 10    20  2.15  2.4  male   40 or under
## # … with 291 more rows
```

Arranging rows



Having calculated each person's *state anxiety* score, perhaps we'd now like to check who has the lowest and highest scores (note: this can be a good way to check for extreme values!).

```
arrange(crime_sub, SA)
```

```
## # A tibble: 301 × 4
##      age    SA    TA sex
##    <dbl> <dbl> <dbl> <chr>
##  1    20  1     1.05 male
##  2    53  1     1.55 female
##  3    49  1     1.65 male
##  4    19  1.05  1.5  female
##  5    19  1.1   2    female
##  6    19  1.1   1.4  male
##  7    29  1.1   1.5  female
##  8    19  1.1   1.3  female
##  9    20  1.1   1.8  female
## 10    21  1.1   2.1  male
## # … with 291 more rows
```

```
arrange(crime_sub, desc(SA))
```

```
## # A tibble: 301 × 4
##      age    SA    TA sex
##    <dbl> <dbl> <dbl> <chr>
##  1    19  3.85  3.85 female
##  2    20  3.6   3.6  female
##  3    20  3.6   3.55 female
##  4    18  3.4   4    female
##  5    19  3.4   3.35 female
##  6    20  3.35  2.8  female
##  7    20  3.3   3.5  male
##  8    19  3.2   2.95 male
##  9    19  3.1   3.1  female
## 10    20  3.1   3.15 female
## # … with 291 more rows
```

Grouping and summarizing

Summarising rows



A common task when analyzing data is to create summaries of statistical characteristics.

Here I calculate the *mean*, *standard deviation*, and *variance* of the State Anxiety variable.

Other possible summmary functions (other than `mean()`, `sd()`, or `var()`) include `max()`, `min()`, `IQR()`, or `median()`.

```
summarise(crime,
          mean = mean(SA),
          standard_dev = sd(SA),
          variance = var(SA))
```

```
## # A tibble: 1 × 3
##    mean standard_dev variance
##   <dbl>        <dbl>    <dbl>
## 1  1.92        0.554    0.307
```

Grouping observations



`group_by()` is used to organise data frames into groups according to categorical variables.

```
grouped_crime <- group_by(crime, sex, victim_crime)
grouped_crime
```

```
## # A tibble: 301 × 15
## # Groups:   sex, victim_crime [4]
##    Partici…¹ sex     age victi…²     H     E     X     A     C     O    SA    TA
##    <chr>     <chr> <dbl> <chr>   <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
##  1 R_01TjXg… male     55 yes       3.7   3     3.4   3.9   3.2   3.6  1.15  1.55
##  2 R_0dN5Ye… fema…    20 no        2.5   3.1   2.5   2.4   2.2   3.1  2.05  2.95
##  3 R_0DPiPY… male     57 yes       2.6   3.1   3.3   3.1   4.3   2.8  2     2.6
##  4 R_0f7bSs… male     19 no        3.5   1.8   3.3   3.4   2.1   2.7  1.55  2.1
##  5 R_0rov2R… fema…    20 no        3.3   3.4   3.9   3.2   2.8   3.9  1.3   1.8
##  6 R_0wioqG… fema…    20 no        2.6   2.6   3     2.6   2.9   3.4  2.55  1.5
##  7 R_0wRO8l… male     34 yes       3.2   2.5   3.2   2.8   4     3.2  1.85  1.75
##  8 R_116nEd… fema…    19 no        2.9   4     3.9   4.2   3.7   1.9  1.1   2
##  9 R_11ZmBd… fema…    19 yes       3.4   3.4   3.3   3.4   3.2   3.2  2.2   2.9
## 10 R_12i26Q… male     20 no        2.4   2.1   1.8   2.2   3.4   2.9  2.15  2.4
## # … with 291 more rows, 3 more variables: OHQ <dbl>, FoC <dbl>, Foc2 <dbl>, and
## #   abbreviated variable names ¹Participant, ²victim_crime
```

Summarising groups



Once data is *grouped*, the most common thing to do is to `summarise()` those groups.

```
summarise(grouped_crime,
          state_anxiety = mean(SA),
          sd_SA = sd(SA),
          var_SA = var(SA))
```

```
## `summarise()` has grouped output by 'sex'. You can override using the `.groups`
## argument.

## # A tibble: 4 × 5
## # Groups:   sex [2]
##   sex    victim_crime state_anxiety sd_SA var_SA
##   <chr>  <chr>                <dbl> <dbl>  <dbl>
## 1 female no                    1.90 0.518  0.268
## 2 female yes                   1.98 0.643  0.413
## 3 male   no                    2.02 0.553  0.306
## 4 male   yes                   1.74 0.472  0.223
```

Removing unwanted rows

Filtering rows



The `prison_pop` dataset has 22409 rows, but we don't need (or want) them all!

```
unique(prison_pop$View)
```

```
## [1] "a Establishment*Sex*Age Group"     "b Establishment*Sex*Custody type"
## [3] "c Establishment*Sex*Nationality"   "d Establishment*Sex*Offence group"
```


The data is actually *repeated* four times, but organised differently each time.

```
## # A tibble: 4 × 3
##   View                              total_pop num_entries
##   <chr>                                 <dbl>       <int>
## 1 a Establishment*Sex*Age Group        938760        2042
## 2 b Establishment*Sex*Custody type     939314        2740
## 3 c Establishment*Sex*Nationality      938841        3215
## 4 d Establishment*Sex*Offence group    936191       14412
```


Filtering rows

If we just started investigating the data without accounting for this, it would be misleading.

```
ggplot(prison_pop, aes(x = Population)) +
  geom_histogram(binwidth = 100)
```




```
ggplot(prison_pop, aes(x = Population)) +
  geom_histogram(binwidth = 100) + facet_wr
```



Filtering rows



We can use the `filter()` function to select only the rows we're interested in, using *logical conditions* and *relational operators*.

```
filter(prison_pop,
       View == "a Establishment*Sex*Age Group")
```

```
## # A tibble: 2,042 × 6
##    View                          Date    Establishment Sex    Age / Cu…¹ Popul…²
##    <chr>                         <chr>   <chr>         <chr>  <chr>        <dbl>
##  1 a Establishment*Sex*Age Group 2015-06 Altcourse     Male   Adults (2…     922
##  2 a Establishment*Sex*Age Group 2015-06 Altcourse     Male   Juveniles…     169
##  3 a Establishment*Sex*Age Group 2015-06 Ashfield      Male   Adults (2…     389
##  4 a Establishment*Sex*Age Group 2015-06 Askham Grange Female Adults (2…      NA
##  5 a Establishment*Sex*Age Group 2015-06 Askham Grange Female Juveniles…      NA
##  6 a Establishment*Sex*Age Group 2015-06 Aylesbury     Male   Adults (2…     113
##  7 a Establishment*Sex*Age Group 2015-06 Aylesbury     Male   Juveniles…     268
##  8 a Establishment*Sex*Age Group 2015-06 Bedford       Male   Adults (2…     459
##  9 a Establishment*Sex*Age Group 2015-06 Bedford       Male   Juveniles…      30
## 10 a Establishment*Sex*Age Group 2015-06 Belmarsh      Male   Adults (2…     794
## # … with 2,032 more rows, and abbreviated variable names
## #   ¹`Age / Custody / Nationality / Offence Group`, ²Population
```

Relational operators

Relational operators compare two (or more) things and return a **logical** value (i.e. TRUE/FALSE)

Operator	Meaning	Example
>	Greater than	5 > 4
>=	Greater than or equal to	4 >= 4
<	Less than	Population < 400
<=	Less than or equal to	Population <= 400
==	Exactly equal to	Sex == "Male"
!=	Not equal to	Establishment != "Ashfield"
%in%	Is contained in	Establishment %in% c("Bedford", "Oakwood")

Logical operators

Logical operators can be used to combine multiple relational operators or *negate* a relational operator.

Operator	Meaning	Example
&	AND	Population < 1000 & Sex == "Male"
|	OR	Population > 200 | Population < 500
!	NOT	!(Establishment %in% c("Bedford", "Oakwood"))

Filtering rows



We can have multiple *conditions* for selection with `filter()`.

Suppose we only wanted to include rows where Population is over 300 but under 600.

```
filter(prison_pop,
       View == "a Establishment*Sex*Age Group",
       Population > 300 & Population < 600)
```

```
## # A tibble: 487 × 6
##    View                          Date    Establishment Sex    Age / Cu…¹ Popul…²
##    <chr>                         <chr>   <chr>         <chr>  <chr>        <dbl>
##  1 a Establishment*Sex*Age Group 2015-06 Ashfield      Male   Adults (2…     389
##  2 a Establishment*Sex*Age Group 2015-06 Bedford       Male   Adults (2…     459
##  3 a Establishment*Sex*Age Group 2015-06 Brinsford     Male   Juveniles…     349
##  4 a Establishment*Sex*Age Group 2015-06 Bristol       Male   Adults (2…     553
##  5 a Establishment*Sex*Age Group 2015-06 Bronzefield   Female Adults (2…     459
##  6 a Establishment*Sex*Age Group 2015-06 Buckley Hall  Male   Adults (2…     440
##  7 a Establishment*Sex*Age Group 2015-06 Coldingley    Male   Adults (2…     515
##  8 a Establishment*Sex*Age Group 2015-06 Deerbolt      Male   Juveniles…     311
##  9 a Establishment*Sex*Age Group 2015-06 Eastwood Park Female Adults (2…     331
## 10 a Establishment*Sex*Age Group 2015-06 Erlestoke     Male   Adults (2…     514
## # … with 477 more rows, and abbreviated variable names
## #   ¹`Age / Custody / Nationality / Offence Group`, ²Population
```

Putting it all together

Pipes



Often you want to conduct several steps, one after the other.

You could do this using objects to store each intermediate step.

```
temp_pris <- filter(prison_pop,
                    View == "a Establishment*Sex*Age Group",
                    Date == "2015-06")
temp_pris <- group_by(temp_pris,
                      Sex,
                      `Age / Custody / Nationality / Offence Group`)
temp_pris <- summarise(temp_pris,
                       mean_pop = mean(Population, na.rm = TRUE),
                       median_pop = median(Population, na.rm = TRUE),
                       total_pop = sum(Population, na.rm = TRUE),
                       max_pop = max(Population, na.rm = TRUE))
```

```
## `summarise()` has grouped output by 'Sex'. You can override using the `.groups`
## argument.
```

Pipes



A simpler way is to use *pipes* (%>%)

pipes can be read as meaning "AND THEN"

```
prison_pop %>%
  filter(View == "a Establishment*Sex*Age Group",
         Date == "2015-06") %>%
  group_by(Sex, `Age / Custody / Nationality / Offence Group`) %>%
  summarise(mean_pop = mean(Population, na.rm = TRUE),
            median_pop = median(Population, na.rm = TRUE),
            total_pop = sum(Population, na.rm = TRUE),
            max_pop = max(Population, na.rm = TRUE))
```

```
## `summarise()` has grouped output by 'Sex'. You can override using the `.groups`
## argument.

## # A tibble: 4 × 6
## # Groups:   Sex [2]
##   Sex    Age / Custody / Nationality / Offence…¹ mean_…² media…³ total…⁴ max_pop
##   <chr>  <chr>                                     <dbl>   <dbl>   <dbl>   <dbl>
## 1 Female Adults (21+)                              356       333    3560     480
## 2 Female Juveniles and Young Adults (15-20)         18.6      19     167      35
## 3 Male   Adults (21+)                              717.      677   76730    1587
```

Reading materials

Revision

For revision of this week's concepts, see Chapter *Data transformation* in R for Data Science.

For practice, use the "Work with Data" RStudio cloud primer.

Next week

Discovering Statistics using R (Field et al.)

- Chapter 9, Comparing two means
- Chapter 5, Exploring assumptions (additional)