

Working with RestTemplate

=====

Methods associated with RestTemplate

xxxForEntity(,,,) => overloaded method

Instead of calling xxxForEntity as per the request methods we can use single exchange(,,) for all operations

Note:: @RequestMapping(value="" method = RequestMethod.POST/GET)
or
@GetMapping(value="") and @PostMapping(value="")

Syntax of exchange()

=====

```
public <T> ResponseEntity<T> exchange(  
    String url,  
    HttpMethod method,  
    HttpEntity<?> requestEntity,  
    Class<T> responseType,  
    Object... uriVariables)throws
```

RestClientException

url => The URL
method => HttpMethod(GET,POST,...)
requestEntity => headers+body
responseType => required response type
uriVariables => path variable values

Output:: ResponseEntity<T>

Note: This method is an alternative to getForEntity(), postForEntity(),.....
RestTemplate supports synchronous communication.
RestTemplate introduced in Spring3.X version
Internally RestTemplate uses java.net connection to send HttpRequest

WebClient

=====

It is introduced from Spring5.X
It supports for both Synchronous and Asynchronous request
To use WebClient, SpringBoot has provided a starter called "SpringWebFlux".
<dependency>
 <groupId>org.springframework.boot</groupId>
 <artifactId>spring-boot-starter-webflux</artifactId>
</dependency>

Code

=====

```
@Service("service")  
public class CurrencyService {  
  
    private static final String REST_END_POINT =  
  
        "http://localhost:8888/SpringRest-CurrencyConverter-Providerapp/api/  
currency/getCurrencyExchangeCost/from/USD/to/INR";
```

```

public void invokeRestApiSync(String from, String to) {
    // Sending Synchronous request
    WebClient webClient = WebClient.create();
    System.out.println("****Synchronous: Restcall started ****");
    CurrencyResponse response = webClient.
        get().
        uri(REST_END_POINT, from, to).
        accept(MediaType.APPLICATION_JSON).
        retrieve().
        bodyToMono(CurrencyResponse.class).
        block();

    System.out.println(response);
    System.out.println("****Synchronous: Restcall ended ****");
}

public void invokeRestApiASync(String from, String to) {

    // Sending Synchronous request
    WebClient webClient = WebClient.create();
    System.out.println("****ASynchronous: Restcall started ****");
    webClient.
        get().
        uri(REST_END_POINT, from, to).
        accept(MediaType.APPLICATION_JSON).
        retrieve().
        bodyToMono(CurrencyResponse.class).
        subscribe(CurrencyService::myResponse);

    System.out.println("****ASynchronous: Restcall ended ****");
}

public static void myResponse(CurrencyResponse response) {
    System.out.println(response);
    //use response object as per the needs[push to Apache-kafka]
}

}

```

refer:: SpringRest-CurrencyConverter-Providerapp and SpringRest-WebClient-GetRequest

Sending POST request

=====

@Service("service")

public class ERailClientApp {

private static final String REST_END_URL = "http://localhost:8888/SpringRest-TicketBooking-ProviderApp/api/ticket/register";

public void invokeRestApi() {

WebClient client = WebClient.create();

PassengerInfo body = new PassengerInfo();

body.setFirstName("nitin");

body.setLastName("manjunath");

body.setJourneyDate("22/06/2023");

```

        body.setFrom("bengaluru");
        body.setTo("pune");
        body.setTrainNumber("BNG-PUN-1234");

        Ticket response =
client.post().uri(REST_END_URL).accept(MediaType.APPLICATION_JSON)
        .body(BodyInserters.fromValue(body)).retrieve().bodyToMono(
Ticket.class).block();

        System.out.println(response);

    }
}
refer::SpringRest-TicketBooking-ProviderApp and SpringRest-
WebClient-PostRequest

```

Develop a REST API with HATEOAS

=====

1. SpringBoot has provided a starter file to work with HATEOS

```

eg: <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-hateoas</artifactId>
</dependency>

```

eg#1

@Data

@AllArgsConstructor

@NoArgsConstructor

```

public class Book extends RepresentationModel {

```

```

    private String isbn;
    private String name;
    private Double price;
    private String author;

```

```

}

```

RestController

=====

```

public class BookController {

```

```

    @GetMapping(value = "/getBook/{isbn}", produces = "application/json")
    public ResponseEntity<Book> getBook(@PathVariable("isbn") String isbn) {

```

```

        Book book = new Book(isbn, "Spring", 234.5, "RodJhonson");

```

```

        Link link =

```

```

WebMvcLinkBuilder.linkTo(WebMvcLinkBuilder.methodOn(BookController.class).getAllBooks())

```

```

        .withRel("allBooks");

```

```

        book.add(link);

```

```

        return new ResponseEntity<Book>(book, HttpStatus.OK);

```

```

    }

```

```

    @GetMapping(value = "/allBooks")

```

```

public List<Book> getAllBooks() {

    List<Book> bookList = new ArrayList<Book>();

    bookList.add(new Book("ISBN-111", "Spring", 350.5, "RodJhonson"));
    bookList.add(new Book("ISBN-222", "Hibernate", 350.5, "GavinKing"));
    bookList.add(new Book("ISBN-333", "Servlet", 350.5, "KeitySeirra"));

    return bookList;

}
}

```

Input: <http://localhost:9999/getBook/10>

Output:

```

{
  "isbn": "10",
  "name": "Spring",
  "price": 234.5,
  "author": "RodJhonson",
  "_links": {
    "allBooks": {
      "href": "http://localhost:9999/allBooks"
    }
  }
}

```

.