

"author": "RodJhonson",

"href": "http://localhost:4444/api/books'

ooks"

▼ "allBooks": {

▼ "_links": {

Generic w.r.t GET

public <T> T getForObject(String url, Class<T> responseType, Object... uriVariables)

Specific w.r.t GET

getForEntity(String, Class<T>, Map<String, ?>) <T>: ResponseEntity<T>

• a getForEntity(String, Class<T>, Object...) <T>: ResponseEntity<T>

getForEntity(URI, Class<T>) <T> : ResponseEntity<T>

getForObject(URI, Class<T>) <T>:T

● a getForObject(String, Class < T >, Map < String, ?>) < T > : T

provide path variable as key-value

the order

while passing key-value pair no need 2 maintain the order

the order

To provide path variables we use

provide path variable as key-value

maintain the order

while passing key-value pair no need 2

varargs, so we need to maintain

To provide path variables we use

varargs, so we need to maintain

Speicific w.r.t POST

postForEntity(URI, Object, Class<T>) <T> : ResponseEntity<T>

ullet postForEntity(String, Object, Class<T>, Object...) <T> : ResponseEntity<T>

• postForEntity(String, Object, Class<T>, Map<String, ?>) <T>: ResponseEntity<T>

templates

src/test/java

> 🛋 Libraries

Deployed Resources

application.properties

> 🕭 target/generated-sources/annotations

> # target/generated-test-sources/test-annotations