

Documentation

Explore our guides and examples to integrate [Originality.ai](#) into your workflows

1 First step

[Create](#) or [Login](#) to [Originality.ai](#) and subscribe to our [Enterprise](#) level plan

2 Create API Key

Create an api key for use here: <https://app.originality.ai/home/api-token-dashboard>

3 Prepare Requests

All requests must contain the following header

Key	
X-OAI-API-KEY	your-api-key

Important Information

Rate Limit

The rate limit for our api is 500 requests per minute. Your remaining limit for the current minute can be found by examining the response headers after a request has completed. In the event you have reached the upper limit, a 429 “too many requests” error will be returned by our system

you've exhausted your [originality.ai](https://app.originality.ai) credits while using the api, credits will be automatically purchased using your default payment method on file. This is to ensure smooth operating of your workflows. You can manage your top up settings anytime here: <https://app.originality.ai/home/account#topup>

Tips to avoid unwanted credit card charges

a) Reduce request concurrency

b) Adjust Auto top up settings (disable, +/- threshold)

c) Manually purchase credits - <https://app.originality.ai/home/credits/purchase>

Scan Features

This page outlines the scan features you can use to check your content

AI Checker

For the most accurate scoring provide plain text into the api when initiating a new scan

Models

Version	String for Scan Request
Lite - 1.0.0	"lite"
Turbo - 3.0.2	"turbo"

Lite - 1.0.2	"lite-102"
Academic 0.0.5	"academic"

Plagiarism Checker

Use our plagiarism features to protect your reputation & improve your content quality by accurately detecting plagiarism content. Our plagiarism feature uses advanced machine learning to accurately detect plagiarism. It is designed to detect complex forms of plagiarism such as patchwork, unintentional, mosaic plagiarism and more!

When enabling this feature on a new scan request, it will extend the length of time it takes to get a response from the API. Depending on the size of content submitted, it could take up to 60 seconds to process. If you are experiencing timeouts when running a plagiarism check you can split the content into multiple chunks and run them separately.

Readability Checker

Use our readability feature to help ensure that your writing isn't too complex for your readers. By giving you an approximate grade level / score, you can ensure that your content is easily understood by your target audience and they're getting the most value possible out of the information you're sharing

Grammar & Spelling Checker

Use our Grammar checker to check for any grammatical, spelling, and punctuation errors. Regardless of what you are writing, you have to make sure your piece is without any mistakes.

Fact Checker: Our Automated Fact-Checker verifies your content in real time, flagging potential inaccuracies and providing clear justifications with trusted source links. Designed for publishers, agencies, and writers, it

 DOCUMENTATION

access actionable recommendations that boost overall content quality.

Was this section helpful?  Yes |  No

Scan

Run a new scan on your content. Check for AI Detection, Plagiarism, Factual Claims, Readability, Grammar/Spelling and Content Optimization

Header Parameters

X-OAI-API-KEY string **REQUIRED**

Your API key

Body Parameters

[Expand all](#)

title string **REQUIRED**

a title to help you identify your scan

check_ai boolean **REQUIRED**

Check for AI

check_plagiarism boolean **REQUIRED**

Check for Plagiarism

check_facts boolean **REQUIRED**

Check for Factual Accuracy

check_readability boolean **REQUIRED**

 DOCUMENTATION

Check Grammar & Spelling

`check_contentOptimizer` `boolean` **REQUIRED**

Check Content Optimization

`optimizerQuery` `string` **REQUIRED**

Keyword or phrase you want your content to rank for

`optimizerCountry` `string` **REQUIRED**

"United States" - only the United States is supported at this time

`optimizerDevice` `string` **REQUIRED**

"desktop" or "mobile"

`optimizerPublishingDomain` `string` **REQUIRED**

optional - enter the url of the website where this content will be published. This helps our AI analyze keyword relevance, back links, and content performance which can improve ranking predictions

`storeScan` `boolean` **REQUIRED**

Set to false if you don't want your scan stored for access later. Warning - setting this to false will prevent you from viewing the results again

`excludedUrls` `array` Show child attributes`aiModelVersion` `string` **REQUIRED**

what AI model to use for AI detection. "lite", "turbo", "multilang"

`content` `string` **REQUIRED**

The PLAIN TEXT content you want to scan

Response Attributes

results object

+ Show child attributes

Base URL

Version 3:

<https://api.originality.ai/api/v3>

POST /scan

cURL ▾



```
1 curl --location 'http://example.io/scan' \  
2 --header 'X-OAI-API-KEY: your-api-key' \  
3 --data '{  
4   "title": "My API Scan",  
5   "check_ai": true,  
6   "check_plagiarism": true,  
7   "check_facts": true,  
8   "check_readability": true,  
9   "check_grammar": true,  
10  "check_contentOptimizer": true,  
11  "optimizerQuery": "Mobile Hotspot",  
12  "optimizerCountry": "United States",  
13  "optimizerDevice": "Desktop",  
14  "optimizerPublishingDomain": "https://www.cnet.com/home/internet/i-tried-using-my-mot  
15  "storeScan": true,  
16  "excludedUrls": [  
17    "https://example-1.com",  
18    "https://example-2.com"  
19  ],  
20  "aiModelVersion": "lite",  
21  "content": "I didn't realize how convenient it is to stay connected by using my phone  
22  }'
```

```
{
  "results": {
    "properties": {
      "privateID": 30137337,
      "id": "removed from response",
      "title": "My API Scan",
      "excludedUrls": [
        "https://example-1.com",
        "https://example-2.com"
      ],
      "publicLink": "removed from response",
      "content": "I didn't realize how convenient it is to stay connected by using",
      "formattedContent": "I didn't realize how convenient it is to stay connected",
    },
    "credits": {
      "used": 9
    },
    "ai": {
      "aiModel": "lite",
      "classification": {
        "AI": 1,
        "Original": 0
      }
    },
  },
}
```

Show more ▾

Was this section helpful?  Yes |  No

Batch Scan

Scan multiple pieces of content for AI Detection, Plagiarism, Factual Claims, Readability, Grammar/Spelling

Body Parameters

Expand all

batches array

+ Show child attributes

title string **REQUIRED**

check_ai boolean **REQUIRED**

check_plagiarism boolean **REQUIRED**

check_facts boolean **REQUIRED**

check_readability boolean **REQUIRED**

check_grammar boolean **REQUIRED**

Response

Expand all

200 Object

Response Attributes

scanID string

content string

ai object

DOCUMENTATION ▾

paraphrase object

+ Show child attributes

facts object

+ Show child attributes

readability object

+ Show child attributes


grammar object

+ Show child attributes

credits_used number

POST /scan/batch

cURL ▾



```
1 curl --location 'http://example.io/scan/batch' \  
2 --header 'X-OAI-API-KEY: your-api-key' \  
3 --data '{  
4   "batches": [  
5     "Ronald Reagan (1911–2004) was an American politician and actor who served as the 40  
6     "Ronald Reagan (1911–2004) was an American politician and actor who served as the 40  
7     "Ronald Reagan (1911–2004) was an American politician and actor who served as the 40  
8     "Ronald Reagan (1911–2004) was an American politician and actor who served as the 40  
9     "Ronald Reagan (1911–2004) was an American politician and actor who served as the 40  
10    "Ronald Reagan (1911–2004) was an American politician and actor who served as the 4  
11    "Ronald Reagan (1911–2004) was an American politician and actor who served as the 4  
12    "Ronald Reagan (1911–2004) was an American politician and actor who served as the 4  
13    "Ronald Reagan (1911–2004) was an American politician and actor who served as the 4  
14    "Ronald Reagan (1911–2004) was an American politician and actor who served as the 4  
15  ],  
16  "title": "test batch scan",
```

DOCUMENTATION ▾

```
21     check_grammar : false
22 }
```

Response



200

```
[
  {
    "scanID": "removed from result",
    "content": "Ronald Reagan (1911–2004) was an American politician and actor who",
    "ai": {
      "aiModel": "lite",
      "classification": {
        "AI": 0,
        "Original": 1
      },
      "confidence": {
        "AI": 0.0686,
        "Original": 0.9316
      },
      "blocks": [
        {
          "text": "Ronald Reagan (1911–2004) was an American politician and actor v",
          "result": {
            "fake": 0.0694836876201842,
            "real": 0.9305163123798158,
            "status": "success"
          }
        }
      ]
    }
  },
]
```

Show more ▾

Was this section helpful? Yes | No

 DOCUMENTATION

Run a new scan on a url. Check for AI Detection, Plagiarism, Factual Claims, Readability, Grammar/Spelling and Content Optimization

Header Parameters

X-OAI-API-KEY string

Body Parameters

url string

title string

excludedUrl string

check_ai boolean

check_plagiarism boolean

check_facts boolean

check_readability boolean

check_grammar boolean

check_contentOptimizer boolean

optimizerQuery string

optimizerCountry string

optimizerDevice string

aiModel string

Response

[Expand all](#)

200 Object

Response Attributes

properties object

+ Show child attributes

credits object

+ Show child attributes

ai object

+ Show child attributes

plagiarism object

+ Show child attributes

facts array

+ Show child attributes

readability object

DOCUMENTATION ▾

grammarSpelling object

+ Show child attributes

contentOptimizer object

+ Show child attributes


POST /scan/url

cURL ▾



```
1 curl --location 'http://example.io/scan/url' \  
2 --header 'X-OAI-API-KEY: your-api-key' \  
3 --data '{  
4   "url": "https://www.cnet.com/home/internet/i-tried-using-my-mobile-hotspot-at-home-hei  
5   "title": "test api v3 url scan",  
6   "excludedUrl": null,  
7   "check_ai": true,  
8   "check_plagiarism": true,  
9   "check_facts": true,  
10  "check_readability": true,  
11  "check_grammar": true,  
12  "check_contentOptimizer": true,  
13  "optimizerQuery": "Mobile Hotspot",  
14  "optimizerCountry": "United States",  
15  "optimizerDevice": "Desktop",  
16  "optimizerPublishingDomain": "https://www.cnet.com/home/internet/i-tried-using-my-mo  
17  "storeScan": true,  
18  "aiModel": "turbo"  
19  }'
```

Response



200

```
[  
  {  
    "properties": {  
      "privateID": 123456789,  
      "id": "removed from response",
```

 DOCUMENTATION ▾

```
"publicLink": "removed from response",
"content": "Our expert, award-winning staff selects the products we cover and
"formattedContent": "Our expert, award-winning staff selects the products we
},
"credits": {
  "used": 101,
  "base_credits": 8646,
  "subscription_credits": 1603
},
"ai": {
  "aiModel": "turbo",
  "classification": {
    "AI": 0,
    "human": 1
```

Show more ▾

Was this section helpful?  Yes |  No

Credit Balance

Use this endpoint to return the number of base & subscription credits remaining. You can purchase more within the application [here](#)

Header Parameters

X-OAI-API-KEY string

Response

 DOCUMENTATION

Response Attributes

credits number

subscriptionCredits number

GET /account/balance

cURL 



```
1 curl --location 'http://example.io/account/balance' \  
2 --header 'X-OAI-API-KEY: your-api-key' \  

```

Response



200

```
{  
  "credits": 8646,  
  "subscriptionCredits": 1745  
}
```

Was this section helpful?  Yes |  No

Scan Results

Use this endpoint to fetch the results of a single scan by id

Text/link results in the example below are formatted with symbols converted to character code. Results returned by the actual api are plain text

Path Parameters

id string

The ID of your scan

Response

[Expand all](#)

200 Object

Response Attributes

results object

— Hide child attributes

properties object

+ Show child attributes

credits object

+ Show child attributes

ai object

+ Show child attributes

plagiarism object

+ Show child attributes

DOCUMENTATION ▾

readability object

+ Show child attributes

grammarSpelling object

+ Show child attributes

contentOptimizer object

+ Show child attributes

Base URL

Version 3:

<https://api.originality.ai/api/v3>

GET /scan/{id}

cURL ▾



```
1 curl --location --globoff 'http://example.io/scan/{id}' \  
2 --header 'X-OAI-API-KEY: your-api-key' \
```

Response



200

```
{  
  "results": {  
    "properties": {  
      "privateID": 123456789,  
      "id": "removed from result",  
      "title": "My API Scan",  
      "excludedUrls": [  
        "https://example-1.com",
```

 DOCUMENTATION

```
"formattedContent": "I didn't realize how convenient it is to stay connected",
},
"credits": {
  "used": 9
},
"ai": {
  "aiModel": "lite",
  "classification": {
    "AI": 1,
    "Original": null
  }
}
```

[Show more](#) 

Was this section helpful?  Yes |  No