





# AI Adapter Fix Guide - Step by Step





## What I Fixed

### All Adapters Updated:





#### 1. OpenAI Adapter (ChatGPT)

-  Added proper error checking
-  Added default model fallback
-  Added max\_tokens config
-  Better response validation




#### 2. Anthropic Adapter (Claude)

-  Fixed system message handling
-  Added proper model default
-  Better error messages
-  Response validation




#### 3. Gemini Adapter (Google)

-  Fixed endpoint URL generation
-  Proper API key in query param
-  Better response parsing
-  Model name handling

#### 4. DeepSeek Adapter

-  Added max\_tokens config
-  Better error handling
-  Response validation

#### 5. aiProviders Service

-  Better error logging
-  Detailed console output
-  Proper error propagation

## How to Apply Fixes

### Step 1: Update Database (Important!)

The Gemini endpoint was wrong in the database. Fix it:

```
bash

# Connect to database
docker-compose exec postgres psql -U aiplatform -d aiplatform

# Run this SQL:
UPDATE ai_providers
SET api_endpoint = 'https://generativelanguage.googleapis.com/v1beta/models',
    config = '{"temperature": 0.7, "max_tokens": 1000}'
WHERE name = 'chatgpt';

UPDATE ai_providers
SET config = '{"temperature": 0.7, "max_tokens": 1000}'
WHERE name = 'deepseek';

# Check it worked:
SELECT name, api_endpoint, config FROM ai_providers;

# Exit:
\q
```

## Step 2: Update All Adapter Files

Copy the updated code for each adapter from the artifacts above:

- `backend/src/services/adapters/openai.js`
- `backend/src/services/adapters/anthropic.js`
- `backend/src/services/adapters/gemini.js`
- `backend/src/services/adapters/deepseek.js`
- `backend/src/services/aiProviders.js`

## Step 3: Restart Backend

```
bash

docker-compose restart backend

# Watch logs
docker-compose logs -f backend
```



## Testing Each Adapter

### Option A: Use the Test Script

```
bash
```

```
chmod +x test-adapter.sh  
./test-adapter.sh
```

This interactive script will:

1. Ask for your login credentials
2. Show available providers
3. Let you choose which to test
4. Create a test project and chat
5. Send a message and show the response
6. Clean up after testing

## Option B: Manual Testing via API

### 1. Login

```
bash
```

```
TOKEN=$(curl -s -X POST http://localhost/api/auth/login \  
-H "Content-Type: application/json" \  
-d '{"username":"admin","password":"admin123"}' \  
| grep -o '"token":"[^"]*" | cut -d'"' -f4)  
  
echo "Token: $TOKEN"
```

### 2. Add API Key (if not already added)

```
bash
```

```
# For ChatGPT (provider_id: 1)  
curl -X POST http://localhost/api/providers/keys \  
-H "Authorization: Bearer $TOKEN" \  
-H "Content-Type: application/json" \  
-d '{  
  "provider_id": 1,  
  "key_value": "sk-your-actual-openai-key-here"  
'
```

### 3. Create Test Project

bash

```
PROJECT_ID=$(curl -s -X POST http://localhost/api/projects \
  -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"name":"Test","description":"Testing adapters"}' \
  | grep -o '"id":[0-9]*' | cut -d':' -f2)

echo "Project ID: $PROJECT_ID"
```

#### 4. Create Chat

bash

```
CHAT_ID=$(curl -s -X POST http://localhost/api/chats/project/$PROJECT_ID \
  -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"title":"Test Chat","provider_id":1}' \
  | grep -o '"id":[0-9]*' | cut -d':' -f2)

echo "Chat ID: $CHAT_ID"
```

#### 5. Send Message

bash

```
curl -X POST http://localhost/api/chats/$CHAT_ID/messages \
  -H "Authorization: Bearer $TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"content":"Hello! Say OK if you can read this."}' \
  | jq .
```

**Expected response:**

```
json
```

```
{  
  "message": {  
    "id": 2,  
    "role": "assistant",  
    "content": "OK! I can read your message.",  
    "token_count": 15,  
    "created_at": "2024-12-09T..."  
  },  
  "chat_status": "active"  
}
```



## Debugging Tips

### Check Backend Logs

```
bash
```

```
# Follow logs in real-time
```

```
docker-compose logs -f backend
```

```
# You should see:
```

```
# - "Calling chatgpt API at https://..."
```

```
# - Request payload (JSON)
```

```
# - "chatgpt response received"
```

```
# - Or error details if it failed
```

### Common Issues & Fixes

#### Issue 1: "Invalid API key"

##### Symptoms:

```
json
```

```
{"error": "invalid_api_key"}
```

##### Fix:

- Check your API key is correct
- Check it has proper permissions
- For OpenAI: Key should start with `sk-`
- For Anthropic: Key should start with `sk-ant-`
- For Gemini: Get key from Google AI Studio

## Issue 2: "Invalid response format"

### Symptoms:

json

```
{"error": "api_error", "message": "Invalid response format from ..."} 
```

### Fix:

- This means the API returned unexpected data
- Check backend logs for the actual response
- The adapter might need adjusting for your specific API version

## Issue 3: "Rate limit exceeded"

### Symptoms:

json

```
{"error": "rate_limited"} 
```

**This is normal!** The system handles it:

- Chat status becomes "pending\_rate\_limit"
- Shows reset time to user
- Background job will reactivate after reset

## Issue 4: "No available API keys"

### Symptoms:

json

```
{"error": "no_available_keys"} 
```

### Fix:

```
bash
```

```
# Check if keys exist
```

```
curl http://localhost/api/providers \  
-H "Authorization: Bearer $TOKEN" | jq .
```

```
# Add a key
```

```
curl -X POST http://localhost/api/providers/keys \  
-H "Authorization: Bearer $TOKEN" \  
-H "Content-Type: application/json" \  
-d '{"provider_id": 1, "key_value": "your-key"}'
```



## Adapter-Specific Notes

### ChatGPT (OpenAI)

#### Models supported:

- `gpt-3.5-turbo` (default, cheapest)
- `gpt-4` (smarter, more expensive)
- `gpt-4-turbo`

**API Key format:** `sk-proj-...` or `sk-...`

**Get key:** <https://platform.openai.com/api-keys>

### Claude (Anthropic)

#### Models supported:

- `claude-3-5-sonnet-20241022` (default)
- `claude-3-opus-20240229`
- `claude-3-haiku-20240307`

**API Key format:** `sk-ant-...`

**Get key:** <https://console.anthropic.com/>

### Gemini (Google)

#### Models supported:

- `gemini-pro` (default)
- `gemini-pro-vision` (for images)

**API Key format:** 39-character string

**Get key:** <https://makersuite.google.com/app/apikey>

**Note:** Gemini uses API key in URL, not header

## DeepSeek

### Models supported:

- `deepseek-chat` (default)
- `deepseek-coder`

**API Key format:** Similar to OpenAI

**Get key:** <https://platform.deepseek.com/>

## Verification Checklist

After applying fixes:

- ☐ All adapter files updated
- ☐ Database config updated (SQL above)
- ☐ Backend restarted
- ☐ API key added for at least one provider
- ☐ Test script runs successfully OR
- ☐ Manual API test returns AI response
- ☐ Backend logs show successful API call
- ☐ No errors in browser console (if using web UI)

## Next Steps

Once adapters are working:

1. **Add more API keys** - Add keys for all providers you want to use
2. **Test all providers** - Run test script for each
3. **Monitor usage** - Check Admin panel for key usage
4. **Set up backups** - Run `./backup.sh` daily
5. **Update models** - Change model names in database if needed

## Still Having Issues?

If adapters still don't work after these fixes:

1. **Check backend logs:**



```
bash
```

```
docker-compose logs backend | grep -A 20 "Error"
```

## 2. Verify database config:

```
bash
```

```
docker-compose exec postgres psql -U aiplatform -d aiplatform \  
-c "SELECT name, api_endpoint, model_name, adapter_module FROM ai_providers;"
```

## 3. Test API key separately:

```
bash
```

```
# For OpenAI:  
curl https://api.openai.com/v1/chat/completions \  
-H "Authorization: Bearer sk-your-key" \  
-H "Content-Type: application/json" \  
-d '{"model": "gpt-3.5-turbo", "messages": [{"role": "user", "content": "test"}]}'
```

## 4. Check adapter file exists:

```
bash
```

```
ls -la backend/src/services/adapters/*.js
```

Let me know which adapter is still failing and I'll help debug further!