

Admin System & User Management Guide

Overview

The platform implements a secure admin-based user management system:

- **First user** automatically becomes admin
- **Subsequent users** can only be created by admins
- **Admin privileges** required for API key management
- **Token-based authentication** for all operations






Key Concepts

User Roles

Role	Can Do
Admin	Everything: create users, manage API keys, all regular features
Regular User	Use platform: create projects, chats, share with others

Admin Privileges

Admins have exclusive access to:

-  Create new user accounts
-  Add/remove AI provider API keys
-  View all API keys and usage
-  Enable/disable API keys
-  All regular user features

Initial Setup Flow

Step 1: Create First Admin User

The first user registration requires **NO authentication**:

```
bash
```

```
# Register first user (becomes admin automatically)
```

```
curl -X POST http://localhost/api/auth/register \
-H "Content-Type: application/json" \
-d '{
  "username": "admin",
  "password": "SecurePassword123!",
  "email": "admin@example.com"
}'
```

Response:

```
json
```

```
{
  "user_id": 1,
  "username": "admin",
  "email": "admin@example.com",
  "is_admin": true,
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..."
}
```

Important: Save the token! You'll need it for all admin operations.

Step 2: Add AI Provider Keys (Admin Only)

```
bash
```

```
# Use the admin token from registration
```

```
ADMIN_TOKEN="eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..."
```

```
# Add OpenAI key
```

```
curl -X POST http://localhost/api/providers/keys \
  -H "Authorization: Bearer $ADMIN_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "provider_id": 1,
    "key_value": "sk-your-openai-key-here"
  }'
```

```
# Add Anthropic key
```

```
curl -X POST http://localhost/api/providers/keys \
  -H "Authorization: Bearer $ADMIN_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "provider_id": 2,
    "key_value": "sk-ant-your-anthropic-key-here"
  }'
```

Step 3: Create Additional Users (Admin Only)

```
bash
```

```
# Create a regular user (requires admin token)
```

```
curl -X POST http://localhost/api/auth/register \
  -H "Authorization: Bearer $ADMIN_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "username": "john",
    "password": "UserPassword123!",
    "email": "john@example.com"
  }'
```

Response:

```
json
```

```
{
  "user_id": 2,
  "username": "john",
  "email": "john@example.com",
  "is_admin": false,
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..."
}
```



Authentication Flow

User Login

```
bash
```

```
# Login with username and password
```

```
curl -X POST http://localhost/api/auth/login \
  -H "Content-Type: application/json" \
  -d '{
    "username": "admin",
    "password": "SecurePassword123!"
  }'
```

Response includes:

- `user_id` - User's unique ID
- `username` - Username
- `is_admin` - Admin status (true/false)
- `token` - JWT token for API requests

Get Current User Info

```
bash
```

```
# Check your current user details
```

```
curl http://localhost/api/auth/me \
  -H "Authorization: Bearer $TOKEN"
```

Response:

json

```
{
  "id": 1,
  "username": "admin",
  "email": "admin@example.com",
  "is_admin": true,
  "created_at": "2024-12-05T10:30:00.000Z"
}
```

User Management

Creating Users

As Admin:

bash

```
curl -X POST http://localhost/api/auth/register \
-H "Authorization: Bearer $ADMIN_TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "username": "newuser",
  "password": "Password123!",
  "email": "user@example.com"
}'
```

Without Admin Token:

bash

```
curl -X POST http://localhost/api/auth/register \
-H "Content-Type: application/json" \
-d '{
  "username": "hacker",
  "password": "Password123!"
}'
```

Response (Error):

json

```
{
  "error": "unauthorized",
  "message": "Authentication required to create new users"
}
```

Checking Admin Status

```
bash

# Login returns is_admin flag
curl -X POST http://localhost/api/auth/login \
  -H "Content-Type: application/json" \
  -d '{"username":"admin","password":"SecurePassword123!"}' \
  | jq '.is_admin'

# Output: true
```

API Key Management (Admin Only)

List All Providers

```
bash

# Available to all authenticated users
curl http://localhost/api/providers \
  -H "Authorization: Bearer $TOKEN"
```

Response:

```
json

{
  "providers": [
    {
      "id": 1,
      "name": "chatgpt",
      "display_name": "ChatGPT",
      "is_active": true,
      "available_keys": 2
    },
    {
      "id": 2,
      "name": "claude",
      "display_name": "Claude",
      "is_active": true,
      "available_keys": 1
    }
  ]
}
```

Add API Key (Admin Only)

```
bash
```

```
curl -X POST http://localhost/api/providers/keys \  
-H "Authorization: Bearer $ADMIN_TOKEN" \  
-H "Content-Type: application/json" \  
-d '{  
  "provider_id": 1,  
  "key_value": "sk-proj-abc123..."  
}'
```

View All API Keys (Admin Only)

```
bash
```

```
curl http://localhost/api/providers/keys \  
-H "Authorization: Bearer $ADMIN_TOKEN"
```

Response:

```
json
```

```
{  
  "keys": [  
    {  
      "id": 1,  
      "provider_id": 1,  
      "provider_name": "ChatGPT",  
      "key_preview": "sk-proj-ab...",  
      "usage_count": 42,  
      "last_used_at": "2024-12-05T14:30:00.000Z",  
      "status": "active",  
      "rate_limit_reset_at": null,  
      "created_at": "2024-12-01T10:00:00.000Z"  
    }  
  ]  
}
```

Update API Key Status (Admin Only)

```
bash
```

```
# Disable a key
```

```
curl -X PUT http://localhost/api/providers/keys/1 \  
-H "Authorization: Bearer $ADMIN_TOKEN" \  
-H "Content-Type: application/json" \  
-d '{"status": "disabled"}'
```

```
# Re-enable a key
```

```
curl -X PUT http://localhost/api/providers/keys/1 \  
-H "Authorization: Bearer $ADMIN_TOKEN" \  
-H "Content-Type: application/json" \  
-d '{"status": "active"}'
```

Delete API Key (Admin Only)

```
bash
```

```
curl -X DELETE http://localhost/api/providers/keys/1 \  
-H "Authorization: Bearer $ADMIN_TOKEN"
```

Access Control Examples

Scenario 1: Regular User Tries to Add User

```
bash
```

```
# Login as regular user
```

```
REGULAR_TOKEN=$(curl -s -X POST http://localhost/api/auth/login \  
-H "Content-Type: application/json" \  
-d '{"username": "john", "password": "UserPassword123!"}' \  
| jq -r '.token')
```

```
# Try to create another user
```

```
curl -X POST http://localhost/api/auth/register \  
-H "Authorization: Bearer $REGULAR_TOKEN" \  
-H "Content-Type: application/json" \  
-d '{"username": "hacker", "password": "Pass123!"}'
```

Response (Error):


```
json

{
  "error": "forbidden",
  "message": "Only administrators can create new users"
}
```

Scenario 2: Regular User Tries to Add API Key

```
bash

curl -X POST http://localhost/api/providers/keys \
  -H "Authorization: Bearer $REGULAR_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"provider_id":1,"key_value":"sk-stolen-key"}'
```

Response (Error):

```
json

{
  "error": "forbidden",
  "message": "Administrator access required"
}
```

Scenario 3: No Token Provided

```
bash

curl -X POST http://localhost/api/auth/register \
  -H "Content-Type: application/json" \
  -d '{"username":"hacker","password":"Pass123!"}'
```

Response (Error):

```
json

{
  "error": "unauthorized",
  "message": "Authentication required to create new users"
}
```



Database Schema

Users Table

sql

```
CREATE TABLE users (  
  id SERIAL PRIMARY KEY,  
  username VARCHAR(50) UNIQUE NOT NULL,  
  password_hash VARCHAR(255) NOT NULL,  
  email VARCHAR(100),  
  is_admin BOOLEAN DEFAULT FALSE, -- New field  
  created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
  updated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

Checking Admin Users

sql




```
-- List all admin users  
SELECT id, username, email, created_at  
FROM users  
WHERE is_admin = true;  
  
-- Count total users and admins  
SELECT  
  COUNT(*) as total_users,  
  COUNT(*) FILTER (WHERE is_admin = true) as admin_users,  
  COUNT(*) FILTER (WHERE is_admin = false) as regular_users  
FROM users;
```



Security Best Practices

Password Requirements

The system enforces:

-  Minimum 6 characters (increase in production)
-  Bcrypt hashing with salt
-  No plain text storage

Recommended for production:

```
javascript
```

```
// Add to auth.js validation
```

```
if (!/(?=.*[a-z])(?=.*[A-Z])(?=.*\d)/.test(password)) {  
  throw new AppError(400, 'validation_error',  
    'Password must contain uppercase, lowercase, and numbers');  
}
```

Token Security

- ☒ JWT tokens expire after 7 days
- ☒ Tokens include user ID, username, and admin flag
- ☒ Tokens signed with secret key
- ☒ HTTPS required in production

Admin Account Protection

Recommendations:

1. **Strong password** for admin account
2. **Unique email** for admin
3. **Regular token rotation** (re-login periodically)
4. **Monitor admin actions** (add logging)
5. **Backup admin account** (create second admin)

Creating Backup Admin

```
bash
```

```
# As existing admin, create another admin
```

```
# (Requires manual database update after creation)
```

```
# 1. Create user normally
```

```
curl -X POST http://localhost/api/auth/register \  
-H "Authorization: Bearer $ADMIN_TOKEN" \  
-H "Content-Type: application/json" \  
-d '{"username":"backup_admin","password":"SecurePass123!"}'
```

```
# 2. Promote to admin (database command)
```

```
docker-compose exec postgres psql -U aiplatform -d aiplatform \  
-c "UPDATE users SET is_admin = true WHERE username = 'backup_admin';"
```



Testing Admin System

bash

#!/bin/bash

echo "Testing Admin System..."

1. Register first user (should become admin)

echo "1. Creating first admin user..."

```
ADMIN_RESPONSE=$(curl -s -X POST http://localhost/api/auth/register \
-H "Content-Type: application/json" \
-d '{"username":"testadmin","password":"Admin123!"}')
```

```
ADMIN_TOKEN=$(echo $ADMIN_RESPONSE | jq -r '.token')
```

```
IS_ADMIN=$(echo $ADMIN_RESPONSE | jq -r '.is_admin')
```

```
if [ "$IS_ADMIN" = "true" ]; then
```

```
    echo "✓ First user is admin"
```

```
else
```

```
    echo "✗ First user is NOT admin - FAIL"
```

```
    exit 1
```

```
fi
```

2. Try to create user without token (should fail)

echo "2. Trying to create user without admin token..."

```
RESPONSE=$(curl -s -X POST http://localhost/api/auth/register \
-H "Content-Type: application/json" \
-d '{"username":"hacker","password":"Pass123!"}')
```

```
if echo $RESPONSE | grep -q "unauthorized"; then
```

```
    echo "✓ Registration blocked without token"
```

```
else
```

```
    echo "✗ Registration allowed without token - FAIL"
```

```
    exit 1
```

```
fi
```

3. Create user with admin token (should succeed)

echo "3. Creating user with admin token..."

```
RESPONSE=$(curl -s -X POST http://localhost/api/auth/register \
-H "Authorization: Bearer $ADMIN_TOKEN" \
-H "Content-Type: application/json" \
-d '{"username":"testuser","password":"User123!"}')
```

```
USER_TOKEN=$(echo $RESPONSE | jq -r '.token')
```

```
if [ "$USER_TOKEN" != "null" ]; then
```

```
    echo "✓ User created successfully"
```

```
!
```

```
else
    echo "X User creation failed - FAIL"
    exit 1
fi

# 4. Try to create another user with regular user token (should fail)
echo "4. Trying to create user with regular user token..."
RESPONSE=$(curl -s -X POST http://localhost/api/auth/register \
-H "Authorization: Bearer $USER_TOKEN" \
-H "Content-Type: application/json" \
-d '{"username":"hacker2","password":"Pass123!"}')

if echo $RESPONSE | grep -q "forbidden"; then
    echo "✓ Regular user cannot create users"
else
    echo "X Regular user can create users - FAIL"
    exit 1
fi

# 5. Try to add API key with regular user (should fail)
echo "5. Trying to add API key with regular user..."
RESPONSE=$(curl -s -X POST http://localhost/api/providers/keys \
-H "Authorization: Bearer $USER_TOKEN" \
-H "Content-Type: application/json" \
-d '{"provider_id":1,"key_value":"fake-key"}')

if echo $RESPONSE | grep -q "forbidden"; then
    echo "✓ Regular user cannot add API keys"
else
    echo "X Regular user can add API keys - FAIL"
    exit 1
fi

# 6. Add API key with admin (should succeed)
echo "6. Adding API key with admin token..."
RESPONSE=$(curl -s -X POST http://localhost/api/providers/keys \
-H "Authorization: Bearer $ADMIN_TOKEN" \
-H "Content-Type: application/json" \
-d '{"provider_id":1,"key_value":"test-key-12345"}')

if echo $RESPONSE | grep -q "API key added successfully"; then
    echo "✓ Admin can add API keys"
else
    echo "X Admin cannot add API keys - FAIL"
    exit 1
fi
```

```
echo ""  
echo "✅ All admin system tests passed!"
```



Monitoring Admin Actions

View User Activity

```
sql  
  
-- Recent user registrations  
SELECT  
  id,  
  username,  
  is_admin,  
  created_at  
FROM users  
ORDER BY created_at DESC  
LIMIT 10;  
  
-- API key usage by provider  
SELECT  
  p.display_name,  
  COUNT(k.id) as total_keys,  
  COUNT(k.id) FILTER (WHERE k.status = 'active') as active_keys,  
  SUM(k.usage_count) as total_usage  
FROM ai_providers p  
LEFT JOIN api_keys k ON k.provider_id = p.id  
GROUP BY p.id, p.display_name;
```



Migration from Existing System

If you already have users without the `is_admin` field:

sql

-- Add is_admin column

```
ALTER TABLE users ADD COLUMN IF NOT EXISTS is_admin BOOLEAN DEFAULT FALSE;
```

-- Make first user admin

```
UPDATE users
```

```
SET is_admin = true
```

```
WHERE id = (SELECT MIN(id) FROM users);
```

-- Or make specific user admin

```
UPDATE users
```

```
SET is_admin = true
```

```
WHERE username = 'admin';
```



Summary

- ✓ **First user** = automatic admin
- ✓ **Admin required** for user creation
- ✓ **Admin required** for API key management
- ✓ **Token-based** authentication
- ✓ **Secure by default**

This ensures your platform is secure and only authorized admins can manage users and API keys!