

DSP For Scientists and Engineers Notes

Philip Tracton

April 21, 2017

Contents

1	The Breadth and Depth of DSP	4
2	Statistics, Probability and Noise	5
2.1	Signals and Graph Terminology	5
2.1.1	Definitions	5
2.1.2	Concepts	5
2.2	Mean and Standard Deviation	5
2.2.1	Mean	5
2.2.2	Standard Deviation and Variance	6
2.2.3	Running Statistics	7
2.3	Signal vs. Underlying Process	8
2.4	The Histogram, PMF and PDF	8
2.5	The Normal Distribution	8
2.6	Digital Noise Generation	8
2.7	Precision and Accuracy	8
3	ADC and DAC	9
3.1	Definitions	9
3.2	Concepts	9
4	Appendix A – Code Listing	10
4.1	DSP Source Code	10
4.2	DSP Test Code	12

Listings

<code>"../src/DSP.py"</code>	10
<code>"../src/DSP_Test.py"</code>	12

List of Tables

1 The Breadth and Depth of DSP

These are my personal notes from learning DSP using [The Scientists and Engineers Guide to Digital Signal Processing](#), Second Edition.

The first chapter goes over the history and where you can find use for DSP work. The book writes some psuedo-code in a "BASIC" like language. I will be attempting to move it over to Python. Matlab would be better but I don't have it.

2 Statistics, Probability and Noise

2.1 Signals and Graph Terminology

2.1.1 Definitions

- **Signal** is how one parameter is related to another parameter
- **Continuous Signal** is if BOTH parameters can assume a continuous range
- **Discrete Signal** is if BOTH parameters are quantized in some manner
- **Time Domain** is if the X axis (the independent variable) is time
- **Frequency Domain** is if the X axis (the independent variable) is frequency

2.1.2 Concepts

- The two parameters of a signal are not interchangeable
- The parameter on the Y axis is a function of the one on the X axis
- Mathematicians tend to do 1-N, everyone else does 0-(N-1)

2.2 Mean and Standard Deviation

2.2.1 Mean

- **Mean** μ is the average of the signal. Add all samples together and divide by N. In electronics this is the DC (direct current) value.

$$\mu = \frac{1}{N} \sum_{i=1}^{N-1} x_i$$

```
1  def Mean(self):
2      """
3          Calculate the mean of a list of values.
4          The self.samples list should be set when instantiating
5          this instance.
6          """
7      mean = 0
8      for x in self.samples:
9          mean = mean + x
10     mean = mean/len(self.samples)
11     return mean
```

2.2.2 Standard Deviation and Variance

- **Average Deviation** is not commonly used. Sums up all the deviations, from the mean, for each sample and divided by the number of samples. Use absolute values for deviation otherwise differences could cancel out.
- **Standard Deviation** averages the power. This is the AC portion of the signal.

$$\sigma = \sqrt{\frac{1}{N-1} \sum_{i=1}^{N-1} (x_i - \mu)^2}$$

```
1 def StandardDeviation(self):
2     """
3     Calculate the standard deviation of a list of values.
4     The self.samples list should be set when instantiating
5     this instance.
6     """
7     mean = self.Mean()
8     std = 0.0
9     for x in self.samples:
10         std = std + math.pow((x - mean), 2)
11     std = std / (len(self.samples) - 1)
12     std = math.sqrt(std)
13     return std
```

- **Variance** is commonly used in statistics. Notice variance and standard deviation both divide by N-1, not N!

$$\sigma^2 = \frac{1}{N-1} \sum_{i=1}^{N-1} (x_i - \mu)^2$$

```
1 def Variance(self):
2     """
3     Calculate the variance of a list of values.
4     The self.samples list should be set when instantiating
5     this instance.
6     """
7     return math.pow(self.StandardDeviation(), 2)
```

- **Root Mean Square (rms)** measures both the AC and DC components.

$$x_{rms} = \sqrt{\frac{1}{N} \sum_{i=0}^{N-1} (x_i)^2}$$

2.2.3 Running Statistics

- **Running Statistics** is often needed. In this situation we want to recompute mean and standard deviation of new signal added in without redoing all of the calculations

$$\sigma^2 = \frac{1}{N-1} \left(\sum_{i=0}^{N-1} (x_i)^2 - \frac{1}{N} \left(\sum_{i=0}^{N-1} x_i \right)^2 \right)$$

```
1
2 def RunningStatistics(self):
3     """
4     Calculate the mean, variance and std while running through a list of
5     values. The self.samples list should be set when instantiating
6     this instance.
7     """
8     mean = 0
9     variance = 0
10    std = 0
11    temp_sum = 0
12    sum_squares = 0
13    N = len(self.samples)
14    for x in self.samples:
15        temp_sum = temp_sum + x
16        sum_squares = sum_squares + math.pow(x, 2)
17        mean = temp_sum/N
18        variance = (sum_squares - (math.pow(temp_sum, 2)/N)) / (N - 1)
19        std = math.sqrt(variance)
20        print("RunningStatistics: Mean {} Variance {} STD {}".format(
21            mean, variance, std))
22    return mean, variance, std
```

- In some situations mean describes what is being measured and standard deviation measures noise
- **Signal to Noise Ration (SNR)** is a comparison of mean to standard deviation

$$SNR = \frac{\mu}{\sigma}$$

- **Coefficient of Variance (CV)** is the standard deviation divided by the mean and multiplied by 100%.

$$CV = \frac{\sigma}{\mu} * 100\%$$

- High SNR and Low CV is a good signal!

- 2.3 Signal vs. Underlying Process
- 2.4 The Histogram, PMF and PDF
- 2.5 The Normal Distribution
- 2.6 Digital Noise Generation
- 2.7 Precision and Accuracy

3 ADC and DAC

3.1 Definitions

3.2 Concepts

4 Appendix A – Code Listing

4.1 DSP Source Code

```
1  #!/usr/bin/env python3
2
3  import math
4
5
6  class DSP():
7      """
8      DSP Demonstration class that implements the code
9      from DSP For Scientists and Engineers, Second Edition
10     """
11
12     def __init__(self, samples=None):
13         """
14         """
15         self.samples = samples
16         return
17
18     def Mean(self):
19         """
20         Calculate the mean of a list of values.
21         The self.samples list should be set when instantiating
22         this instance.
23         """
24         mean = 0
25         for x in self.samples:
26             mean = mean + x
27         mean = mean/len(self.samples)
28         return mean
29
30     def StandardDeviation(self):
31         """
32         Calculate the standard deviation of a list of values.
33         The self.samples list should be set when instantiating
34         this instance.
35         """
36         mean = self.Mean()
37         std = 0.0
38         for x in self.samples:
39             std = std + math.pow((x - mean), 2)
40         std = std / (len(self.samples) - 1)
41         std = math.sqrt(std)
42         return std
43
44     def Variance(self):
45         """
46         Calculate the variance of a list of values.
47         The self.samples list should be set when instantiating
48         this instance.
49         """
50         return math.pow(self.StandardDeviation(), 2)
51
52     def RunningStatistics(self):
```

```

53     """
54     Calculate the mean, variance and std while running through a list of
55     values. The self.samples list should be set when instantiating
56     this instance.
57     """
58     mean = 0
59     variance = 0
60     std = 0
61     temp_sum = 0
62     sum_squares = 0
63     N = len(self.samples)
64     for x in self.samples:
65         temp_sum = temp_sum + x
66         sum_squares = sum_squares + math.pow(x, 2)
67         mean = temp_sum/N
68         variance = (sum_squares - (math.pow(temp_sum, 2)/N)) / (N - 1)
69         std = math.sqrt(variance)
70         print("RunningStatistics: Mean {} Variance {} STD {}".format(
71             mean, variance, std))
72     return mean, variance, std

```

4.2 DSP Test Code

```
1  #!/usr/bin/env python3
2
3  """
4  Check Results:
5  http://www.calculator.net/standard-deviation-calculator.html?numberinputs=0%2C+1%2C+2%2C+3%2C+
6  """
7
8
9  import DSP
10
11
12  if __name__ == "__main__":
13      samples = [x for x in range(100)]
14      dsp = DSP.DSP(samples)
15      print(samples)
16      print("Mean {} ".format(dsp.Mean()))
17      print("StandardDeviation {} ".format(dsp.StandardDeviation()))
18      print("Variance {} ".format(dsp.Variance()))
19      mean, variance, std = dsp.RunningStatistics()
```
