Sampling and overfitting

Formation IA biodiversité

Paul Tresson

May 16, 2025

UMR AMAP

Introduction

What do we want when modelling ?

- Understand things

What do we want when modelling ?

- Understand things
- **Predict things**

What do we want when modelling ?

"All models are wrong, but some are useful"

George E. P. Box

What do we want when modelling ?

- **Robustness**: Useful when mistakes
- **Generalization**: Useful applied elsewhere

Overfitting

What is overfitting



adapted from scikit-learn docs

Common tools and intuitions - Train/Test loss





Common tools and intuitions - Train/Test loss





Common tools and intuitions - Train/Test loss





Common tools and intuitions - Train/Test loss





Common tools and intuitions - Train/Test loss





Common tools and intuitions - Train/Test loss





Common tools and intuitions - Train/Test loss





Common tools and intuitions - Train/Test loss





Common tools and intuitions - Train/Test loss





Common tools and intuitions - Train/Test loss



Figure from Goodfellow et al., 2016

Common tools and intuitions - AIC/BIC

Akaike information criterion (AIC)

Bayesian information criterion (BIC)

Is the model parameter efficient ?

Common tools and intuitions - Biases



from scikit-learn docs

And in Machine(/Deep) Learning ??

How many parameters to have

Shrek learning botany starting from random noise ?

And in Machine(/Deep) Learning ??

$\approx 2.5B$?

Root Causes

Too many parameters

Root Causes

Too many parameters

Too little training data

Root Causes

Too many parameters

Too little training data

(bad) training data

Illustrated examples in Ecology

Contraints in ecology

Data from the real world is noisy,



Contraints in ecology

Data from the real world is noisy, unbalanced,



Contraints in ecology

Data from the real world is noisy, unbalanced, hard to collect,

Contraints in ecology

Data from the real world is noisy, unbalanced, hard to collect, hard to interpret.



Contraints in ecology

Data from the real world is noisy, unbalanced, hard to collect, hard to interpret.

Contraints in ecology

Data from the real world is noisy, unbalanced, hard to collect, hard to interpret.





Train set



A good fitted model



Test set



An overfitted model

Biases in the train set

Biases in the train set



Biases in the train set



Biases in the train set - autocorrelation

Biases in the train set - autocorrelation

Biases in the train set - autocorrelation





Biases in the train set - autocorrelation



Unbalanced data

Unbalanced data



Unbalanced data



Unbalanced data





Deal with unbalanced data

- Oversample ?

Deal with unbalanced data

- Oversample ?



Deal with unbalanced data

- Oversample ?



Deal with unbalanced data

- Oversample ?
- Undersample/saturate ?

Deal with unbalanced data

- Oversample ?
- Undersample/saturate ?



Deal with unbalanced data

- Oversample ?
- Undersample/saturate ?



Deal with unbalanced data

- Oversample ?
- Undersample/saturate ?
- Adapt loss ?



Deal with lack of data

- Data augmentation

Deal with lack of data

- Data augmentation

Deal with lack of data

- Data augmentation
- Pretrained model



Deal with lack of data

- Data augmentation
- Pretrained model
- **... collect more data**

Play with your model

- Dropout
- Pruning
- Ablation studies
- Ensembles



Figure from Goodfellow et al., 2016

Need to be very carefull on how to evaluate

How to sample and evaluate ?

Random split ?

“random split training validation 80/20”

Random split ?

"random split training validation 80/20"

> For the uncurated dataset, we randomly sample 142 million images

Oquab et al., 2023

Random split ?

"random split training validation 80/20"

> For the uncurated dataset, we randomly sample 142 million images

Oquab et al., 2023

Works for huge DL papers, maybe not for you

Cross-validation



Figure from scikit-learn docs

Cross-validation



Figure from scikit-learn docs

Cross-validation



Figure from scikit-learn docs

Case study : Spatial cross-validation

Case study : Spatial cross-validation



Case study : Spatial cross-validation



Case study : Spatial cross-validation





Case study : Spatial cross-validation



See. Ploton et al., 2020

Case study : Spatial cross-validation



See. Ploton et al., 2020

Case study : Spatial cross-validation



See. Wadoux et al., 2021

Case study : Aging models ?



See. Vela et al., 2022

Perspective : Foundation models ?



(a) (b) (c) (d)

See. Oquab et al., 2023

Perspective : Foundation models ?

A photograph of Anne Graham Lotz included in the training set of Stable Diffusion, a text-to-image model

An image generated by Stable Diffusion using the prompt "Anne Graham Lotz"

Perspective : Foundation models ?



See. Udandarao et al., 2024

Usefull ressources

- `scikit-learn` docs !

Thanks for you attention !

Let's practice !

References i

Goodfellow, Ian, Yoshua Bengio, Aaron Courville, and Yoshua Bengio (2016). ***Deep learning***. Vol. 1. 2. MIT press Cambridge.

Oquab, Maxime et al. (2023). **"Dinov2: Learning robust visual features without supervision".** In: *arXiv preprint arXiv:2304.07193*.

Ploton, Pierre et al. (2020). **"Spatial validation reveals poor predictive performance of large-scale ecological mapping models".** In: *Nature communications* 11.1, p. 4540.

Udandarao, Vishaal et al. (2024). **"No zero-shot without exponential data: Pretraining concept frequency determines multimodal model performance".** In: *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

References ii

Vela, Daniel et al. (2022). **"Temporal quality degradation in AI models".** In: *Scientific reports* 12.1, p. 11654.

Wadoux, Alexandre MJ-C, Gerard BM Heuvelink, Sytze De Bruin, and Dick J Brus (2021). **"Spatial cross-validation is not the right way to evaluate map accuracy".** In: *Ecological Modelling* 457, p. 109692.