

Embedded Javascript example

The fault is with how the javascript is “cleaned” when embedded.

Original text:

```
<html>

  <head>

    <meta http-equiv="Content-Type" content="text/html;
charset=utf-8" />

    <meta name="generator" content="Aspose.Words for .NET
5.2.1.0" />

    <title>Introduction to Normative and Meta-
Ethics</title>

  </head>

  <body>

    <p>Watch this video before doing workshop number 3.</p>

<script type="text/javascript"
src="media/mediaplayer/swfobject.js"><!-- --></script>

    <div id='preview'>There was a problem loading the video.</div>

    <script type="text/javascript">

      var s1 = new
SWFObject('media/mediaplayer/player.swf','ply','470','320','9','#f
fffff');

      s1.addParam('allowfullscreen','true');

      s1.addParam('allowscriptaccess','always');

      s1.addParam('wmode','opaque');

      s1.addParam('flashvars','file=../video/computerEthics1.flv');

      s1.write('preview');

    </script>

  </body>

</html>
```

Code after embedding:

Note the way the two script tags have been transformed into one, which breaks the code.

```

<div class="embedded-html">

<p id="hcc8c204fp1">Watch this video before doing workshop number
3.</p>

<script type="text/javascript"
src="media/mediaplayer/swfobject.js">
<div id="preview">There was a problem loading the video.</div>
  <script type="text/javascript">  var s1 = new
SWFObject('media/mediaplayer/player.swf','ply','470','320','9','#f
ffffff');  s1.addParam('allowfullscreen','true');
s1.addParam('allowscriptaccess','always');
s1.addParam('wmode','opaque');
s1.addParam('flashvars','file=../video/computerEthics1.flv');
s1.write('preview');
</script>
</div>

```

Example file embedded in this document

Note: The actual media files have not been added, this example is to show how the code is changed.

[javascript]