Chapter 3: Install/setup Paquete

3.1 Install Paquete

This page is meant for Developers' reference. This paquete installation is using Paquete 0.2.

3.1.1 Download Paquete

Either download Paquete Client for single javascript file download or

Check out from SVN for complete download, including demonstration.

svn co http://fascinator.usq.edu.au/svn/code/paquete/client/tags/0.2rc1

3.1.2 Setup Paquete

- 1. Copy the package files into a web folder.
- 2. Locate the host page, the main page of the package. For example default.html or index.html **Note**

See example at http://fascinator.usq.edu.au/svn/code/paquete/client/tags/0.1/demo>default.htm.

3. Host page should have similar structure in body content as follows:

p.2 Install/setup Paquete

```
</body>
```

Note

The structure can be changed and is reconfigurable.

4. Edit host page. In header section add the links to javascript files and initializing script.

```
<!-- Paquete setup -->
    <script type="text/javascript" src="../shared/jquery-</pre>
1.4.1.min.js"></script>
    <script type="text/javascript" src="../shared/json2.js"></script>
    <script type="text/javascript" src="../paquete.js"></script>
    <script type="text/javascript">
        jQuery(function(){
            var jQ = jQuery;
            var paquete = paqueteFactory(jQ);
            paquete.contentSelector = "div.body";
            paquete.titleSelector = "div.title";
            paquete.tocSelector = "div.page-toc";
            paquete.contentBaseUrl = "./";
            paquete.getManifestJson("manifest.json");
        });
    </script>
```

Note:

contentSelector, titleSelector and tocSelector define where to put contents, titles and TOCs respectively.