DESeq2 mini project

Pham Vo

2/27/2022

```
library(DESeq2)
```

```
## Loading required package: S4Vectors

## Loading required package: stats4

## Loading required package: BiocGenerics

##
## Attaching package: 'BiocGenerics'

## The following objects are masked from 'package:stats':
##
##     IQR, mad, sd, var, xtabs

## The following objects are masked from 'package:base':
##
##     anyDuplicated, append, as.data.frame, basename, cbind, colnames,
##     dirname, do.call, duplicated, eval, evalq, Filter, Find, get, grep,
##     grepl, intersect, is.unsorted, lapply, Map, mapply, match, mget,
##     order, paste, pmax, pmax.int, pmin, pmin.int, Position, rank,
##     rbind, Reduce, rownames, sapply, setdiff, sort, table, tapply,
##     union, unique, unsplit, which.max, which.min

##
## Attaching package: 'S4Vectors'

## The following objects are masked from 'package:base':
##
##     expand.grid, I, unname

## Loading required package: IRanges

## Loading required package: GenomicRanges

## Loading required package: GenomeInfoDb

## Loading required package: SummarizedExperiment
```

```
## Loading required package: MatrixGenerics

## Loading required package: matrixStats

##
## Attaching package: 'MatrixGenerics'

## The following objects are masked from 'package:matrixStats':
##
##     colAlls, colAnyNAs, colAnys, colAvgsPerRowSet, colCollapse,
##     colCounts, colCummaxs, colCummins, colCumprods, colCumsums,
##     colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,
##     colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,
##     colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,
##     colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,
##     colWeightedMeans, colWeightedMedians, colWeightedSds,
##     colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgsPerColSet,
##     rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,
##     rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,
##     rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,
##     rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,
##     rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,
##     rowWeightedMads, rowWeightedMeans, rowWeightedMedians,
##     rowWeightedSds, rowWeightedVars

## Loading required package: Biobase

## Welcome to Bioconductor
##
##     Vignettes contain introductory material; view with
##     'browseVignettes()'. To cite Bioconductor, see
##     'citation("Biobase")', and for packages 'citation("pkgname")'.

##
## Attaching package: 'Biobase'

## The following object is masked from 'package:MatrixGenerics':
##
##     rowMedians

## The following objects are masked from 'package:matrixStats':
##
##     anyMissing, rowMedians
```

```
metaFile <- "GSE37704_metadata.csv"
countFile <- "GSE37704_featurecounts.csv"

# Import metadata and take a peak
colData = read.csv(metaFile, row.names=1)
head(colData)
```

```
##               condition
## SRR493366 control_sirna
## SRR493367 control_sirna
## SRR493368 control_sirna
## SRR493369      hoxa1_kd
## SRR493370      hoxa1_kd
## SRR493371      hoxa1_kd
```

```
# Import countdata
countData = read.csv(countFile, row.names=1)
head(countData)
```

```
##                 length SRR493366 SRR493367 SRR493368 SRR493369 SRR493370
## ENSG00000186092    918         0         0         0         0         0
## ENSG00000279928    718         0         0         0         0         0
## ENSG00000279457   1982        23        28        29        29        28
## ENSG00000278566    939         0         0         0         0         0
## ENSG00000273547    939         0         0         0         0         0
## ENSG00000187634   3214       124       123       205       207       212
##                 SRR493371
## ENSG00000186092         0
## ENSG00000279928         0
## ENSG00000279457        46
## ENSG00000278566         0
## ENSG00000273547         0
## ENSG00000187634       258
```

```
# Note we need to remove the odd first $length col
countData <- as.matrix(countData[,-1])
head(countData)
```

```
##                 SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
## ENSG00000186092         0         0         0         0         0         0
## ENSG00000279928         0         0         0         0         0         0
## ENSG00000279457        23        28        29        29        28        46
## ENSG00000278566         0         0         0         0         0         0
## ENSG00000273547         0         0         0         0         0         0
## ENSG00000187634       124       123       205       207       212       258
```

```
# Filter count data where you have 0 read count across all samples.
countData = countData[rowSums(countData[])>0,]
head(countData)
```

```
##                 SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
## ENSG00000279457        23        28        29        29        28        46
## ENSG00000187634       124       123       205       207       212       258
## ENSG00000188976      1637      1831      2383      1226      1326      1504
## ENSG00000187961       120       153       180       236       255       357
## ENSG00000187583        24        48        65        44        48        64
## ENSG00000187642         4         9        16        14        16        16
```

Running DESeq2

```
library(DESeq2)
citation("DESeq2")
```

```
##
##   Love, M.I., Huber, W., Anders, S. Moderated estimation of fold change
##   and dispersion for RNA-seq data with DESeq2 Genome Biology 15(12):550
##   (2014)
##
## A BibTeX entry for LaTeX users is
##
##   @Article{,
##     title = {Moderated estimation of fold change and dispersion for RNA-seq data with DESeq2},
##     author = {Michael I. Love and Wolfgang Huber and Simon Anders},
##     year = {2014},
##     journal = {Genome Biology},
##     doi = {10.1186/s13059-014-0550-8},
##     volume = {15},
##     issue = {12},
##     pages = {550},
##   }
```

```
dds = DESeqDataSetFromMatrix(countData=countData,
                             colData=colData,
                             design=~condition)
```

```
## Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in
## design formula are characters, converting to factors
```

```
dds = DESeq(dds)
```

```
## estimating size factors

## estimating dispersions

## gene-wise dispersion estimates

## mean-dispersion relationship

## final dispersion estimates

## fitting model and testing
```

```
dds
```

```
## class: DESeqDataSet
## dim: 15975 6
## metadata(1): version
```

```
## assays(4): counts mu H cooks
## rownames(15975): ENSG00000279457 ENSG00000187634 ... ENSG00000276345
##   ENSG00000271254
## rowData names(22): baseMean baseVar ... deviance maxCooks
## colnames(6): SRR493366 SRR493367 ... SRR493370 SRR493371
## colData names(2): condition sizeFactor
```

```
res = results(dds, alpha=0.1)
summary(res)
```

```
##
## out of 15975 with nonzero total read count
## adjusted p-value < 0.1
## LFC > 0 (up)       : 4349, 27%
## LFC < 0 (down)     : 4396, 28%
## outliers [1]       : 0, 0%
## low counts [2]     : 1237, 7.7%
## (mean count < 0)
## [1] see 'cooksCutoff' argument of ?results
## [2] see 'independentFiltering' argument of ?results
```

Volcono plot

```
plot( res$log2FoldChange, -log(res$padj) )
```



```
# Make a color vector for all genes
mycols <- rep("gray", nrow(res) )

# Color red the genes with absolute fold change above 2
mycols[ abs(res$log2FoldChange) > 2 ] <- "red"

# Color blue those with adjusted p-value less than 0.01
#  and absolute fold change more than 2
inds <- (res$padj<0.01) & (abs(res$log2FoldChange) > 2 )
mycols[ inds ] <- "blue"

plot( res$log2FoldChange, -log(res$padj), col=mycols, xlab="Log2(FoldChange)", ylab="-Log(P-value)" )
```



Adding gene annotation

```
library("AnnotationDbi")
library("org.Hs.eg.db")
```

```
##
```

```
columns(org.Hs.eg.db)
```

```
##  [1] "ACCNUM"       "ALIAS"        "ENSEMBL"      "ENSEMBLPROT"  "ENSEMBLTRANS"
##  [6] "ENTREZID"     "ENZYME"       "EVIDENCE"     "EVIDENCEALL"  "GENENAME"
## [11] "GENETYPE"     "GO"           "GOALL"        "IPI"          "MAP"
## [16] "OMIM"         "ONTOLOGY"     "ONTOLOGYALL"  "PATH"         "PFAM"
## [21] "PMID"         "PROSITE"      "REFSEQ"       "SYMBOL"       "UCSCKG"
## [26] "UNIPROT"
```

```
res$symbol = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="SYMBOL",
                    multiVals="first")
```

```
## 'select()' returned 1:many mapping between keys and columns
```

```
res$entrez = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="ENTREZID",
                    multiVals="first")
```

```
## 'select()' returned 1:many mapping between keys and columns
```

```
res$name =   mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="GENENAME",
                    multiVals="first")
```

```
## 'select()' returned 1:many mapping between keys and columns
```

```
head(res, 10)
```

```
## log2 fold change (MLE): condition hoxa1 kd vs control sirna
## Wald test p-value: condition hoxa1 kd vs control sirna
## DataFrame with 10 rows and 9 columns
##                    baseMean log2FoldChange     lfcSE       stat      pvalue
##                   <numeric>      <numeric> <numeric>  <numeric>   <numeric>
## ENSG00000279457   29.913579      0.1792571 0.3248216   0.551863 5.81042e-01
## ENSG00000187634  183.229650      0.4264571 0.1402658   3.040350 2.36304e-03
## ENSG00000188976 1651.188076     -0.6927205 0.0548465 -12.630158 1.43990e-36
## ENSG00000187961  209.637938      0.7297556 0.1318599   5.534326 3.12428e-08
## ENSG00000187583   47.255123      0.0405765 0.2718928   0.149237 8.81366e-01
## ENSG00000187642   11.979750      0.5428105 0.5215598   1.040744 2.97994e-01
## ENSG00000188290  108.922128      2.0570638 0.1969053  10.446970 1.51282e-25
## ENSG00000187608  350.716868      0.2573837 0.1027266   2.505522 1.22271e-02
## ENSG00000188157 9128.439422      0.3899088 0.0467163   8.346304 7.04321e-17
## ENSG00000237330    0.158192      0.7859552 4.0804729   0.192614 8.47261e-01
##                       padj      symbol      entrez                   name
##                  <numeric> <character> <character>            <character>
## ENSG00000279457 6.86555e-01      WASH9P   102723897 WAS protein family h..
```

```
## ENSG00000187634 5.15718e-03      SAMD11      148398 sterile alpha motif ..
## ENSG00000188976 1.76549e-35       NOC2L       26155 NOC2 like nucleolar ..
## ENSG00000187961 1.13413e-07      KLHL17      339451 kelch like family me..
## ENSG00000187583 9.19031e-01     PLEKHN1       84069 pleckstrin homology ..
## ENSG00000187642 4.03379e-01       PERM1       84808 PPARGC1 and ESRR ind..
## ENSG00000188290 1.30538e-24        HES4       57801 hes family bHLH tran..
## ENSG00000187608 2.37452e-02       ISG15        9636 ISG15 ubiquitin like..
## ENSG00000188157 4.21963e-16        AGRN      375790                  agrin
## ENSG00000237330          NA      RNF223      401934 ring finger protein ..
```

```
# Reorder these results by adjusted p-value and save them to a CSV file in your current project directo

res = res[order(res$pvalue),]
write.csv(res[order(res$padj),], "deseq_results_1.csv")
```

Pathway Analysis

```
library(pathview)
```

```
## ##############################################################################
## Pathview is an open source software package distributed under GNU General
## Public License version 3 (GPLv3). Details of GPLv3 is available at
## http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to
## formally cite the original Pathview paper (not just mention it) in publications
## or products. For details, do citation("pathview") within R.
##
## The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG
## license agreement (details at http://www.kegg.jp/kegg/legal.html).
## ##############################################################################
```

```
library(gage)
```

```
##
```

```
library(gageData)

data(kegg.sets.hs)
data(sigmet.idx.hs)

# Focus on signaling and metabolic pathways only
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]

# Examine the first 3 pathways
head(kegg.sets.hs, 3)
```

```
## $`hsa00232 Caffeine metabolism`
## [1] "10"   "1544" "1548" "1549" "1553" "7498" "9"
##
## $`hsa00983 Drug metabolism - other enzymes`
```

```
##  [1] "10"     "1066"   "10720"  "10941"  "151531" "1548"   "1549"   "1551"
##  [9] "1553"   "1576"   "1577"   "1806"   "1807"   "1890"   "221223" "2990"
## [17] "3251"   "3614"   "3615"   "3704"   "51733"  "54490"  "54575"  "54576"
## [25] "54577"  "54578"  "54579"  "54600"  "54657"  "54658"  "54659"  "54963"
## [33] "574537" "64816"  "7083"   "7084"   "7172"   "7363"   "7364"   "7365"
## [41] "7366"   "7367"   "7371"   "7372"   "7378"   "7498"   "79799"  "83549"
## [49] "8824"   "8833"   "9"      "978"
##
## $`hsa00230 Purine metabolism`
##   [1] "100"    "10201"  "10606"  "10621"  "10622"  "10623"  "107"    "10714"
##   [9] "108"    "10846"  "109"    "111"    "11128"  "11164"  "112"    "113"
##  [17] "114"    "115"    "122481" "122622" "124583" "132"    "158"    "159"
##  [25] "1633"   "171568" "1716"   "196883" "203"    "204"    "205"    "221823"
##  [33] "2272"   "22978"  "23649"  "246721" "25885"  "2618"   "26289"  "270"
##  [41] "271"    "27115"  "272"    "2766"   "2977"   "2982"   "2983"   "2984"
##  [49] "2986"   "2987"   "29922"  "3000"   "30833"  "30834"  "318"    "3251"
##  [57] "353"    "3614"   "3615"   "3704"   "377841" "471"    "4830"   "4831"
##  [65] "4832"   "4833"   "4860"   "4881"   "4882"   "4907"   "50484"  "50940"
##  [73] "51082"  "51251"  "51292"  "5136"   "5137"   "5138"   "5139"   "5140"
##  [81] "5141"   "5142"   "5143"   "5144"   "5145"   "5146"   "5147"   "5148"
##  [89] "5149"   "5150"   "5151"   "5152"   "5153"   "5158"   "5167"   "5169"
##  [97] "51728"  "5198"   "5236"   "5313"   "5315"   "53343"  "54107"  "5422"
## [105] "5424"   "5425"   "5426"   "5427"   "5430"   "5431"   "5432"   "5433"
## [113] "5434"   "5435"   "5436"   "5437"   "5438"   "5439"   "5440"   "5441"
## [121] "5471"   "548644" "55276"  "5557"   "5558"   "55703"  "55811"  "55821"
## [129] "5631"   "5634"   "56655"  "56953"  "56985"  "57804"  "58497"  "6240"
## [137] "6241"   "64425"  "646625" "654364" "661"    "7498"   "8382"   "84172"
## [145] "84265"  "84284"  "84618"  "8622"   "8654"   "87178"  "8833"   "9060"
## [153] "9061"   "93034"  "953"    "9533"   "954"    "955"    "956"    "957"
## [161] "9583"   "9615"
```

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

```
##      1266     54855      1465     51232      2034      2317
## -2.422719  3.201955 -2.313738 -2.059631 -1.888019 -1.649792
```

```
# Get the results
keggres = gage(foldchanges, gsets=kegg.sets.hs)
```

```
attributes(keggres)
```

```
## $names
## [1] "greater" "less"    "stats"
```

```
# Look at the first few down (less) pathways
head(keggres$less)
```

```
##                                      p.geomean stat.mean        p.val
## hsa04110 Cell cycle                8.995727e-06 -4.378644 8.995727e-06
```

```
## hsa03030 DNA replication              9.424076e-05 -3.951803 9.424076e-05
## hsa03013 RNA transport                1.375901e-03 -3.028500 1.375901e-03
## hsa03440 Homologous recombination     3.066756e-03 -2.852899 3.066756e-03
## hsa04114 Oocyte meiosis               3.784520e-03 -2.698128 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 8.961413e-03 -2.405398 8.961413e-03
##                                             q.val set.size         exp1
## hsa04110 Cell cycle                   0.001448312      121 8.995727e-06
## hsa03030 DNA replication              0.007586381       36 9.424076e-05
## hsa03013 RNA transport                0.073840037      144 1.375901e-03
## hsa03440 Homologous recombination     0.121861535       28 3.066756e-03
## hsa04114 Oocyte meiosis               0.121861535      102 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 0.212222694       53 8.961413e-03
```

```
head(keggres$greater)
```

```
##                                     p.geomean stat.mean       p.val
## hsa04640 Hematopoietic cell lineage   0.002822776  2.833362 0.002822776
## hsa04630 Jak-STAT signaling pathway   0.005202070  2.585673 0.005202070
## hsa00140 Steroid hormone biosynthesis 0.007255099  2.526744 0.007255099
## hsa04142 Lysosome                     0.010107392  2.338364 0.010107392
## hsa04330 Notch signaling pathway      0.018747253  2.111725 0.018747253
## hsa04916 Melanogenesis                0.019399766  2.081927 0.019399766
##                                         q.val set.size        exp1
## hsa04640 Hematopoietic cell lineage   0.3893570       55 0.002822776
## hsa04630 Jak-STAT signaling pathway   0.3893570      109 0.005202070
## hsa00140 Steroid hormone biosynthesis 0.3893570       31 0.007255099
## hsa04142 Lysosome                     0.4068225      118 0.010107392
## hsa04330 Notch signaling pathway      0.4391731       46 0.018747253
## hsa04916 Melanogenesis                0.4391731       90 0.019399766
```

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory /Users/phamvo/Desktop/Bioinformatics/week 8/DESeq2 mini project
```

```
## Info: Writing image file hsa04110.pathview.png
```

```
## Focus on top 5 upregulated pathways here for demo purposes only
keggrespathways <- rownames(keggres$greater)[1:5]

# Extract the 8 character long IDs part of each string
keggresids = substr(keggrespathways, start=1, stop=8)
keggresids
```

```
## [1] "hsa04640" "hsa04630" "hsa00140" "hsa04142" "hsa04330"
```

```
pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory /Users/phamvo/Desktop/Bioinformatics/week 8/DESeq2 mini project

## Info: Writing image file hsa04640.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/phamvo/Desktop/Bioinformatics/week 8/DESeq2 mini project

## Info: Writing image file hsa04630.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/phamvo/Desktop/Bioinformatics/week 8/DESeq2 mini project

## Info: Writing image file hsa00140.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/phamvo/Desktop/Bioinformatics/week 8/DESeq2 mini project

## Info: Writing image file hsa04142.pathview.png

## Info: some node width is different from others, and hence adjusted!

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/phamvo/Desktop/Bioinformatics/week 8/DESeq2 mini project

## Info: Writing image file hsa04330.pathview.png
```

Reactome Analysis

Reactome is database consisting of biological molecules and their relation to pathways and processes

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
## [1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=FALSE)
```

Then, to perform pathway analysis online go to the Reactome website (https://reactome.org/PathwayBrowser/#TOOL=AT). Select "choose file" to upload your significant gene list. Then, select the parameters "Project to Humans", then click "Analyze".

GO online

To perform Gene Set GO Enrichment online go to the website http://www.geneontology.org/page/go-enrichment-analysis. Paste your significant gene list from section 4. Then, select "biological process" and "homo sapiens", and click submit.

```
sessionInfo()
```

```
## R version 4.1.2 (2021-11-01)
## Platform: x86_64-apple-darwin17.0 (64-bit)
## Running under: macOS Big Sur 10.16
##
## Matrix products: default
## BLAS:   /Library/Frameworks/R.framework/Versions/4.1/Resources/lib/libRblas.0.dylib
## LAPACK: /Library/Frameworks/R.framework/Versions/4.1/Resources/lib/libRlapack.dylib
##
## locale:
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
##
## attached base packages:
## [1] stats4    stats     graphics  grDevices utils     datasets  methods
## [8] base
##
## other attached packages:
##  [1] gageData_2.32.0             gage_2.44.0
##  [3] pathview_1.34.0             org.Hs.eg.db_3.14.0
##  [5] AnnotationDbi_1.56.2        DESeq2_1.34.0
##  [7] SummarizedExperiment_1.24.0 Biobase_2.54.0
##  [9] MatrixGenerics_1.6.0        matrixStats_0.61.0
## [11] GenomicRanges_1.46.1        GenomeInfoDb_1.30.1
## [13] IRanges_2.28.0              S4Vectors_0.32.3
## [15] BiocGenerics_0.40.0
##
## loaded via a namespace (and not attached):
##  [1] httr_1.4.2             bit64_4.0.5            splines_4.1.2
##  [4] highr_0.9              blob_1.2.2             GenomeInfoDbData_1.2.7
##  [7] yaml_2.3.5             pillar_1.7.0           RSQLite_2.2.10
## [10] lattice_0.20-45        glue_1.6.2             digest_0.6.29
## [13] RColorBrewer_1.1-2     XVector_0.34.0         colorspace_2.0-3
## [16] htmltools_0.5.2        Matrix_1.4-0           XML_3.99-0.9
## [19] pkgconfig_2.0.3        genefilter_1.76.0      zlibbioc_1.40.0
## [22] GO.db_3.14.0           purrr_0.3.4            xtable_1.8-4
## [25] scales_1.1.1           BiocParallel_1.28.3    tibble_3.1.6
## [28] annotate_1.72.0        KEGGREST_1.34.0        generics_0.1.2
## [31] ggplot2_3.3.5          ellipsis_0.3.2         cachem_1.0.6
## [34] cli_3.2.0              survival_3.2-13        magrittr_2.0.2
## [37] crayon_1.5.0           KEGGgraph_1.54.0       memoise_2.0.1
## [40] evaluate_0.15          fansi_1.0.2            graph_1.72.0
## [43] tools_4.1.2            lifecycle_1.0.1        stringr_1.4.0
## [46] munsell_0.5.0          locfit_1.5-9.4         DelayedArray_0.20.0
## [49] Biostrings_2.62.0      compiler_4.1.2         rlang_1.0.1
## [52] grid_4.1.2             RCurl_1.98-1.6         rstudioapi_0.13
## [55] bitops_1.0-7           rmarkdown_2.11         gtable_0.3.0
## [58] DBI_1.1.2              R6_2.5.1               knitr_1.37
## [61] dplyr_1.0.8            fastmap_1.1.0          bit_4.0.4
## [64] utf8_1.2.2             Rgraphviz_2.38.0       stringi_1.7.6
## [67] parallel_4.1.2         Rcpp_1.0.8             vctrs_0.3.8
## [70] geneplotter_1.72.0     png_0.1-7              tidyselect_1.1.2
## [73] xfun_0.29
```