
Project 2

Release 1.0

Jodok Vieli¹, Puck van Gerwen², Felix Hoppe³

May 26, 2021

¹SCIPER: 336284

²SCIPER: 283530


³SCIPER: 276062

1.0 Project2

Project2 is a minimal tensor library for deep learning using CPUs. Our current version can:

- Build networks combining fully connected layers, Tanh and ReLU
- Run forward and backward passes
- Optimize parameters with SGD and Adam optimizers for MSE

The deep learning functionality is in the `nn` module and the `Trainer` can be used to facilitate training models. The library has the following structure:



A short example of how to use `Trainer` can be found in section 1.1.1. A test file `test.py` uses the library to train a fully connected network with 3 hidden layers on a toy 2D dataset of 1000 randomly generated points where points inside a circle of radius $1/\sqrt{2\pi}$ are labelled 1, and all others labelled 0. Training for 100 epochs using SGD yields an error rate of 4.81% on average over 10 folds.

1.1 Python API

1.1.0 nn package

1.1.0.0 Submodules

1.1.0.1 nn.activation module

```

class nn.activation.Activation
  Bases: nn.module.Module
  Class to compute activation functions.
  backward(dy)
    Compute gradients of input.
    Parameters dy (torch.tensor) – Backpropagated gradient from the next layer.
    Returns Gradient
    Return type torch.tensor
  forward(x)
    Compute the activation.
    Parameters x (torch.tensor) – Input tensor.

class nn.activation.ReLU
  Bases: nn.activation.Activation
  forward(x)
    Compute ReLU(x)
    Parameters x (torch.tensor) – Input tensor.
    Returns Computed ReLU.
    Return type torch.tensor

class nn.activation.Tanh
  Bases: nn.activation.Activation
  forward(x)
    Compute tanh(x)
    Parameters x (torch.tensor) – Input tensor.
    Returns Computed tanh(x).
    Return type torch.tensor
  
```

1.1.0.2 nn.functional module

`functional.py` contains the concrete implementations of specific functionals.

```

nn.functional.d_mse(x, y)
  Compute the gradient of the mean squared error.
  Parameters
    • x (torch.tensor) – Input tensor.
    • y (torch.tensor) – Target tensor.
  Returns Gradient of mean squared error.
  Return type float
  
```

```

nn.functional.d_relu(x)
  Compute gradient of ReLU(x)
  Parameters x (torch.tensor) – Input tensor
  Returns Output tensor
  Return type torch.tensor

nn.functional.d_tanh(x)
  Compute gradient of tanh(x)
  Parameters x (torch.tensor) – Input tensor
  Returns Output tensor
  Return type torch.tensor

nn.functional.mse(x, y)
  Compute the mean squared error.
  Parameters
    • x (torch.tensor) – Input tensor.
    • y (torch.tensor) – Target tensor.
  Returns Mean squared error.
  Return type torch.tensor

nn.functional.relu(x)
  Compute ReLU(x)
  Parameters x (torch.tensor) – Input tensor
  Returns Output tensor
  Return type torch.tensor

nn.functional.tanh(x)
  Compute tanh(x).
  Parameters x (torch.tensor) – Input tensor
  Returns Output tensor
  Return type torch.tensor
  
```

1.1.0.3 nn.linear module

```

class nn.linear.Layer
  Bases: nn.module.Module
  Layer implements layers that can be used in a network architecture.
  param()
    Return the params of the Layer.
  update_param(*args, **kwargs)
    Update the params of the Layer based on the cached gradients

class nn.linear.Linear(dim_in, dim_out)
  Bases: nn.linear.Layer
  backward(dy)
    Compute gradients of input and parameters.
    Parameters dy (torch.tensor) – Backpropagated gradient from the next layer.
    Returns Gradient.
    Return type torch.tensor
  forward(x)
    Calculate output of Linear layer.
    Parameters x (torch.tensor) – Input tensor of size (batch_size, input_dim)
    Returns Output tensor of size (batch_size, output_dim)
    Return type torch.tensor
  param()
    Get parameters of the linear layer from the cache.
    Returns weight and bias of linear layer.
    Return type torch.tensor, torch.tensor
  
```

1.1.0.4 nn.loss module

```

class nn.loss.Loss
  Bases: nn.module.Module
  The Loss Module is used to implement a node in the network that computes the loss. For the computation of any function the respective functional from functional.py should be used.
  backward()
    Backward pass.
    Returns Backpropagated gradient from the next layer.
    Return type torch.tensor
  forward(x, y)
  
```

Compute the loss.

Parameters

- **x** (*torch.tensor*) – Input tensor.
- **y** (*torch.tensor*) – Target tensor.

class `nn.loss.MSELoss`
Bases: `nn.loss.Loss`

forward (*x, y*)
Compute the mean squared error.

Parameters

- **x** (*torch.tensor*) – Input tensor.
- **y** (*torch.tensor*) – Target tensor.

Returns Mean squared error.

Return type `torch.tensor`

1.1.0.5 nn.module module

class `nn.module.Module`
Bases: `object`

Base Module with core functionality

backward (**args, **kwargs*)
Compute backward pass

forward (**args, **kwargs*)
Compute forward pass

1.1.0.6 nn.sequential module

class `nn.sequential.Sequential` (*modules, loss_fn*)
Bases: `nn.module.Module`

Sequential allows multiple layers to be combined in a network architecture.

backward ()
Perform backward pass.

forward (*x*)
Perform forward pass.

Parameters **x** (*torch.tensor*) – Input tensor

Returns Output tensor

Return type `torch.tensor`

loss (*x, y*)
Compute loss between two tensors.

Parameters

- **x** (*torch.tensor*) – Input tensor
- **y** (*torch.tensor*) – Target tensor

Returns Loss

Return type `torch.tensor`

print ()
str: Print model architecture.

test_step (*x, y*)
Test step. Wrapper for `validation_step`.

Parameters

- **x** (*torch.tensor*) – Input tensor
- **y** (*torch.tensor*) – Target tensor

Returns Loss

Return type `torch.tensor`

training_step (*x, y*)
Training step.

Parameters

- **x** (*torch.tensor*) – Input tensor
- **y** (*torch.tensor*) – Target tensor

Returns Loss

Return type `torch.tensor`

update_params (*optim, lr*)

Update the parameters of the network iteratively according to the cached gradients at each module.

Parameters

- **optim** (*string*) – The optimizer to use. op-

tions are 'adam' or 'sgd'

- **lr** (*float*) – Learning rate

validation_step (*x, y*)
Validation step.

Parameters

- **x** (*torch.tensor*) – Input tensor
- **y** (*torch.tensor*) – Target tensor

Returns Loss

Return type `torch.tensor`

1.1.1 trainer module

class `trainer.Trainer` (*nb_epochs*)
Bases: `object`

fit (*model, x_train, y_train, x_val, y_val, batch_size=32, lr=0.01, optim='sgd', verbose=True, print_every=32*)
Train the model on the specified data and print the training and validation loss and accuracy.

Parameters

- **model** (*nn.Module*) – Model to train
- **x_train** (*torch.tensor*) – Training data
- **y_train** (*torch.tensor*) – Training labels
- **x_val** (*torch.tensor*) – Validation data
- **y_val** (*torch.tensor*) – Validation labels
- **batch_size** (*int*) – Batch sizes for training and validation
- **lr** (*float*) – Learning rate for optimization (Default is 0.01)
- **optim** (*str*) – Optimizer (options are 'sgd' or 'adam'. Default is 'sgd')
- **verbose** (*bool*) – Whether or not to output training information (Default is True)
- **print_every** (*str*) – How often to print progress (Default is every 32 steps)

Example

Use the trainer to fit a new nn model.

```
>>> from trainer import Trainer
>>> from torch import empty
>>> from nn.sequential import Sequential
>>> ... # Read data into x_train, y_train, x_test, y_
↪ test
>>> LinNet = Sequential((Linear(2, 1), MSELoss()))
>>> trainer = Trainer(nb_epochs=25)
>>> loss_train, loss_val = trainer.fit(LinNet, x_train,
↪ y_train, x_test, y_test, batch_size=32, lr=0.1,
↪ print_every=10, optim='sgd')
```

test (*model, x_test, y_test, batch_size=32, test_verbose=True*)
Test the model on the specified data.

Parameters

- **model** (*nn.Module*) – Model to train
- **x_test** (*torch.tensor*) – Test data
- **y_test** (*torch.tensor*) – Test labels
- **batch_size** (*int*) – Batch size for testing
- **test_verbose** (*bool*) – Whether the test result should be printed

Example

Use the trainer to test an existing nn model.

```
>>> from trainer import Trainer
>>> from torch import empty
>>> ... # Train model LinNet
>>> ... # Read data into x_train, y_train, x_test, y_
↪ test
>>> trainer = Trainer(nb_epochs=25)
>>> loss_test = t.test(LinNet, x_test, y_test, batch_
↪ size=32, test_verbose=True)
loss_test=0.17
```