

Sample Lex Programs

1) CODE :

```
%{
int nchar=0,nword=0,nline=0;
}%
%%

\n      { nline++; nchar++; }
[^\t\n]+ { nword++; nchar+=yyleng; }
.        { nchar++; }
%%

int yywrap(void)
{
    return 1;
}

int main()
{
    yyin = fopen("/uploads/sample.c","r");
    if(yyin == NULL)
    {
        printf("File not found\n");
        return 1;
    }
    yylex();

    printf("Number of characters = %d\n",nchar);
    printf("Number of words = %d\n",nword);
    printf("Number of lines = %d\n",nline);

    fclose(yyin);
    return 0;
}
```

sample.c :

```
int main()
{
printf("HELLO");
}
```

OUTPUT :

OPTIONS

LIBRARIES

FILES



Drag files here or [browse](#)

They upload straight away, to /uploads

UPLOADED FILES

 /uploads/sample.c

OUTPUT

GENERATED FILES

DEBUGGER

GUI

Number of characters = 34
Number of words = 5
Number of lines = 3

2) CODE :

```
%{
#include <stdio.h>
%}
%%
[A-Z]+\t\n ] { printf("%s", yytext); };
%%

int yywrap()
{
    return 1;
}

int main()
{
    printf("Enter the input string:\n");
    yylex();
    return 0;
}
```

OUTPUT :

The screenshot displays an online compiler interface. At the top, there are three tabs: 'OPTIONS', 'LIBRARIES', and 'FILES'. The 'FILES' tab is selected and underlined. Below the tabs, there is a large dashed box containing an upload icon (an arrow pointing up) and the text 'Drag files here or [browse](#)'. Below this, it says 'They upload straight away, to /uploads'. Underneath the upload area, there is a section titled 'UPLOADED FILES' which shows a single file icon and the path '/uploads/sample.c'. At the bottom of the interface, there are four tabs: 'OUTPUT', 'GENERATED FILES', 'DEBUGGER', and 'GUI'. The 'OUTPUT' tab is selected and underlined. The output area shows the text: 'Enter the input string:', 'HELLO world ABC test XYZ', and 'HELLO ABC XYZ' on separate lines, with a blue cursor at the end of the last line.