

HW1

Preparation

Please make sure you have read the slides for Lectures 2 & 3


Please make sure you have read Textbook Chapter 2

Please make sure you check page 20 of this PPT.

The notations in this slide deck differ slightly from the lecture slides! The goal is to make implementation easier.



Problem overview

Given




Problem overview

Given



Y: 3D height


Goal: Generate



Z: 3D depth


Convention

- In this homework, given a map (or a matrix), say I
 - $I[i, j]$ means the i -th horizontal index (left-right) and j -th vertical index (bottom-up)
 - $i \geq 0, j \geq 0$




Convention

- There are differences in coordinate systems between (i, j) and (x, y)
- We thus provide a function $x, y = \text{image_plane}(\text{args}, I)$
 - $x[i, j]$ is the 2D x location of pixel (i, j)
 - $y[i, j]$ is the 2D y location of pixel (i, j)



Recall (from lectures)



We want to know $X(x, y)$, $Y(x, y)$, and $Z(x, y)$ from the given image!



What we know:

$$x = X$$


$$y = \cos(\theta)Y - \sin(\theta)Z$$

We need some **cues** from images and the 3D world!


For implementation, locations are indexed by $[i, j]$



y: 2D vertical



Y: 3D height



Z: 3D depth


(i, j)

$$y = \cos(\theta)Y - \sin(\theta)Z$$




$$y[i, j] = \cos(\theta)Y[i, j] - \sin(\theta)Z[i, j]$$


Cue 1: edges (white pixels mean edges)




All edges



Contact edges



Vertical edges




Horizontal

You need to find edge locations!


Cue 2: Surfaces & Cue 3: properties from 3D to 2D

- Separate into **foregrounds (figures)/backgrounds**



- **Not always true**, but let's assume it is true
 - Vertical edges in 2D mean vertical in 3D
 - Non-vertical edges in 2D means horizontal in 3D

Recall (from lectures)



We want to know $X(x, y)$, $Y(x, y)$, and $Z(x, y)$ from the given image!



$$x = X$$

$$y = \cos(\theta)Y - \sin(\theta)Z$$



If we know $Y(x, y)$, we know $Z(x, y)$

Estimating $Y[l, j]$: cues from the background



$$\tilde{Y} = \begin{bmatrix} Y(1,1) \\ Y(1,2) \\ \dots \\ Y(1,N) \\ Y(2,1) \\ Y(2,2) \\ \dots \\ Y(2,N) \\ \dots \\ Y(M,N) \end{bmatrix}$$





$$[0, \dots, 0, \mathbf{1}, \dots, 0] \begin{bmatrix} Y(1,1) \\ Y(1,2) \\ \dots \\ Y(1,N) \\ Y(2,1) \\ Y(2,2) \\ \dots \\ Y(2,N) \\ \dots \\ Y(M,N) \end{bmatrix} = 0$$

One row for each
background pixel

Meaning: these
locations have
height 0

Estimating $Y[l, j]$: cues from contact edges



$$\tilde{Y} = \begin{bmatrix} Y(1,1) \\ Y(1,2) \\ \dots \\ Y(1,N) \\ Y(2,1) \\ Y(2,2) \\ \dots \\ Y(2,N) \\ \dots \\ Y(M,N) \end{bmatrix}$$





$$[0, \dots, 0, \mathbf{1}, \dots, 0] \begin{bmatrix} Y(1,1) \\ Y(1,2) \\ \dots \\ Y(1,N) \\ Y(2,1) \\ Y(2,2) \\ \dots \\ Y(2,N) \\ \dots \\ Y(M,N) \end{bmatrix} = 0$$

One row for each
contact edge pixel

Meaning: these
locations have
height 0

Estimating $Y[l, j]$: cues from vertical edges



$$Y[i, j] - Y[i, j - 1] = 1 / \cos(\theta)$$





$$[0, \dots, 0, -1, 1, \dots, 0]$$

$$\begin{bmatrix} Y(1,1) \\ Y(1,2) \\ \dots \\ Y(1,N) \\ Y(2,1) \\ Y(2,2) \\ \dots \\ Y(2,N) \\ \dots \\ Y(M,N) \end{bmatrix} = 1 / \cos(\theta)$$

One row for each
vertical edge pixel

Meaning: two
vertically consecutive
pixels have 3D height
difference $1 / \cos(\theta)$


Estimating $Y[l, j]$: cues from horizontal edges



Horizontal edges: Y won't change along the edge

$$-n_y[i, j](Y[i, j] - Y[i - 1, j]) + n_x[i, j](Y[i, j] - Y[i, j - 1]) = 0$$



In the code, we have computed n_y and n_x for you!



$$\begin{bmatrix} 0, \dots, -n_x, (-n_y + n_x), 0, \dots, 0, n_y, \dots, 0 \end{bmatrix} \begin{bmatrix} Y(1,1) \\ Y(1,2) \\ \dots \\ Y(1,N) \\ Y(2,1) \\ Y(2,2) \\ \dots \\ Y(2,N) \\ \dots \\ Y(M,N) \end{bmatrix} = 0$$

One row for each
horizontal edge pixel

Estimating $Y[i, j]$: cues from surfaces



Three rows for each surface pixel

Surfaces: flat, not curved

$$2Y[i, j] - Y[i + 1, j] - Y[i - 1, j] = 0$$

$$2Y[i, j] - Y[i, j + 1] - Y[i, j - 1] = 0$$

$$Y[i, j] - Y[i, j - 1] - Y[i - 1, j] + Y[i - 1, j - 1] = 0$$



$$[0, \dots, -1, 0, \dots, 2, 0, \dots, -1, 0, \dots] \tilde{Y} = 0$$

$$[0, \dots, -1, 0, \dots, 2, 0, \dots, -1, 0, \dots] \tilde{Y} = 0$$

$$[0, \dots, -1, 0, \dots, 1, \dots, 0, \dots, 1, 0, \dots, -1, 0, \dots] \tilde{Y} = 0$$

Put all the constraints together

$$\begin{bmatrix} - & \mathbf{a}_1 & - \\ - & \mathbf{a}_2 & - \\ & \dots & \end{bmatrix} \tilde{\mathbf{Y}} = \mathbf{b}$$



$$\mathbf{A} \tilde{\mathbf{Y}} = \mathbf{b}$$



$$\tilde{\mathbf{Y}} = (\mathbf{A}^T \mathbf{A})^{-1} \mathbf{A}^T \mathbf{b}$$

For example,

$$\mathbf{A} = \begin{bmatrix} \vdots \\ 0, \dots, -n_x, (-n_y + n_x), 0, \dots, 0, n_y, \dots, 0 \\ \vdots \\ 0, \dots, 0, -1, 1, \dots, 0 \\ \vdots \\ 0, \dots, -1, 0, \dots, 2, 0, \dots, -1, 0, \dots \\ \vdots \end{bmatrix}$$

$$\mathbf{b} = \begin{bmatrix} \vdots \\ 0 \\ \vdots \\ 1/\cos(\theta) \\ \vdots \\ 0 \\ \vdots \end{bmatrix}$$

Least square solution!

A is like 2300-by-1681

Estimating Z from Y and y


$$x = X$$

$$y = \cos(\theta)Y - \sin(\theta)Z$$



$$y[i, j] = \cos(\theta)Y[i, j] - \sin(\theta)Z[i, j]$$

Why linear system? Try this toy example



$$\tilde{Y} = \begin{bmatrix} Y(1,1) \\ Y(1,2) \\ Y(1,3) \\ Y(2,1) \\ Y(2,2) \\ Y(2,3) \\ Y(3,1) \\ Y(3,2) \\ Y(3,3) \end{bmatrix}$$

$$\begin{bmatrix} 1,0,0,0,0,0,0,0,0 \\ 0,1,0,0,0,0,0,0,0 \\ 0,0,1,0,0,0,0,0,0 \\ 0,0,0,1,0,0,0,0,0 \\ 0,0,0,0,0,1,0,0,0 \\ 0,0,0,0,0,0,1,0,0 \\ 0,0,0,0,0,0,0,1,0 \\ 0,0,0,0,0,0,0,0,1 \\ 0,0,0,-1,2,-1,0,0,0 \\ 0,-1,0,0,2,0,0,-1,0 \\ 1,-1,0,-1,1,0,0,0,0 \end{bmatrix} \begin{bmatrix} Y(1,1) \\ Y(1,2) \\ Y(1,3) \\ Y(2,1) \\ Y(2,2) \\ Y(2,3) \\ Y(3,1) \\ Y(3,2) \\ Y(3,3) \end{bmatrix} = \begin{bmatrix} 7 \\ 8 \\ 9 \\ 4 \\ 6 \\ 1 \\ 2 \\ 3 \\ 0 \\ 0 \\ 0 \end{bmatrix}$$

By solving it through $\tilde{Y} = (A^T A)^{-1} A^T b$,
 $Y(2,2) \approx 5$

Additional hints on Part 4

- See an example implementation for including rows corresponding to the background pixels below. I've also implemented the least square solution at the end. What you need to do is to fill in similar for loops for the vertical, horizontal, and contact edges, as well as the surface pixels.

```
#### Your job 4 starts here: generate Y ####
```

```
A = np.zeros((0, I.size))
```

```
b = np.zeros((0, 1))
```

```
for i in range(I.shape[0]):
```

```
    for j in range(I.shape[1]):
```

```
        if Map_background[i, j] == 1:
```

```
            temp = np.zeros((1, I.size))
```

```
            temp[0, i + j * I.shape[0]] = 1
```

```
            A = np.concatenate((A, temp), axis=0)
```

```
            b = np.concatenate((b, np.zeros((1, 1))), axis=0)
```

```
# You need to fill in similar for loops for contact edges, horizontal edges, vertical edges, and surface here
```

```
Y = np.matmul(np.linalg.inv(np.matmul(A.transpose(), A) + 0.0000001 * np.identity(A.shape[1])), np.matmul(A.transpose(), b))
```

```
Y = Y.reshape((I.shape[1], I.shape[0])).transpose()
```

```
#### Your job 4 ends here: generate Y ####
```