

Schema documentation for TigerData_StandardMetadataSchema_v1.2.xsd

september 16, 2026

Table of Contents

Namespace: ""	4
Schema(s)	4
Main schema TigerData_StandardMetadataSchema_v1.2.xsd	4
Element(s)	4
Element userType / netID	4
Element userType / PUID	4
Element userType / orcid	5
Element userType / fullName	5
Element userType / givenName	6
Element userType / familyName	6
Element userType / nameDate	7
Element userType / alternativeNameIdentifier	7
Element shortUserType / netID	8
Element shortUserType / PUID	8
Element shortUserType / orcid	9
Element storageQuantityType / size	9
Element storageQuantityType / unit	9
Element alternativeID	10
Element alternativeIDs	11
Element parentProject	12
Element dataSponsor	13
Element dataManager	15
Element dataUser	17
Element dataUsers	19
Element title	20
Element description	22
Element language	24
Element languages	25
Element fundingReference	26
Element fundingReference / funderName	28
Element fundingReference / funderID	29
Element fundingReference / awardNumber	30
Element fundingReference / awardTitle	31
Element fundingReferences	32
Element itemResourceType	33
Element projectResourceType	34
Element license	36
Element licenses	38
Element duaReference	39
Element duaReference / grantorName	40
Element duaReference / duaID	41
Element duaReference / duaTitle	42
Element duaReferences	43
Element startDate	44
Element endDate	45
Element retirementDate	46
Element publicationDate	46
Element otherDate	47
Element projectDates	48
Element itemDates	50
Element schemaVersion	51
Element provenanceSubfields / requestedBy	52
Element provenanceSubfields / requestDateTime	53
Element provenanceSubfields / approvedBy	53
Element provenanceSubfields / approvalDateTime	54
Element provenanceSubfields / deniedBy	55
Element provenanceSubfields / denialDateTime	56
Element provenanceSubfields / eventNote	56
Element provenanceSubfields / eventNote / noteBy	58
Element provenanceSubfields / eventNote / noteDateTime	59

Element provenanceSubfields / eventNote / eventType	60
Element provenanceSubfields / eventNote / message	61
Element projectDescription / researchDomains	62
Element projectDescription / researchDomains / researchDomain	63
Element projectDescription / departments	64
Element projectDescription / departments / department	65
Element projectDescription / projectDirectory	66
Element projectDescription / projectDirectory / projectDirectoryPath	68
Element projectDescription / projectDirectory / requestedValue	69
Element projectDescription / projectDirectory / approvedValue	70
Element storageAndAccess / storageCapacity	71
Element storageAndAccess / storageCapacity / storageCapacitySetting	73
Element storageAndAccess / storageCapacity / requestedValue	73
Element storageAndAccess / storageCapacity / approvedValue	74
Element storageAndAccess / projectVisibility	74
Element storageAndAccess / storagePerformance	76
Element storageAndAccess / storagePerformance / storagePerformanceSetting	77
Element storageAndAccess / storagePerformance / requestedValue	78
Element storageAndAccess / storagePerformance / approvedValue	79
Element storageAndAccess / numberOfFiles	80
Element storageAndAccess / securityLevel	81
Element storageAndAccess / securityLevel / securityLevelSetting	82
Element storageAndAccess / securityLevel / requestedValue	83
Element storageAndAccess / securityLevel / approvedValue	83
Element storageAndAccess / storageSystem	84
Element storageAndAccess / accessPoints	85
Element storageAndAccess / accessPoints / hpcEnable	89
Element storageAndAccess / accessPoints / hpcEnable / hpcEnableSetting	90
Element storageAndAccess / accessPoints / hpcEnable / requestedValue	90
Element storageAndAccess / accessPoints / hpcEnable / approvedValue	91
Element storageAndAccess / accessPoints / smbEnable	91
Element storageAndAccess / accessPoints / smbEnable / smbEnableSetting	93
Element storageAndAccess / accessPoints / smbEnable / requestedValue	93
Element storageAndAccess / accessPoints / smbEnable / approvedValue	93
Element storageAndAccess / accessPoints / globusEnable	94
Element storageAndAccess / accessPoints / globusEnable / globusEnableSetting	95
Element storageAndAccess / accessPoints / globusEnable / requestedValue	96
Element storageAndAccess / accessPoints / globusEnable / approvedValue	96
Element storageAndAccess / accessPoints / globusCollection	97
Element storageAndAccess / accessPoints / globusCollection / globusName	98
Element storageAndAccess / accessPoints / globusCollection / globusUUID	98
Element storageAndAccess / accessPoints / globusCollection / globusOwner	99
Element storageAndAccess / accessPoints / globusCollection / globusURL	100
Element additionalProjectInformation / projectPurpose	100
Element additionalProjectInformation / provisionalProject	101
Element additionalProjectInformation / funded	103
Element additionalProjectInformation / dataUseAgreement	104
Element supplementalMetadata / keywords	105
Element supplementalMetadata / keywords / keyword	106
Element supplementalMetadata / relations	108
Element supplementalMetadata / relations / relation	110
Element supplementalMetadata / extendedMetadataSchemas	112
Element supplementalMetadata / extendedMetadataSchemas / extendedMetadataSchema	113
Element projectFields / projectID	115
Element projectFields / projectProvenance	116
Element projectFields / projectProvenance / submission	118
Element projectFields / projectProvenance / revisions	120
Element projectFields / projectProvenance / revisions / revision	121
Element projectFields / projectProvenance / retirement	123
Element projectFields / projectProvenance / publication	125
Element projectFields / projectProvenance / status	127
Element itemFields / itemID	128
Element resource	130
Simple Type(s)	134
Simple Type doiType	134
Simple Type netIDType	134
Simple Type puidType	135
Simple Type textLimitType	135
Simple Type titleLimitType	135
Simple Type shortTextLimitType	136
Simple Type longTextLimitType	136
Simple Type pathSafeType	137

Simple Type uuidType	137
Simple Type byteUnitType	138
Simple Type dateOrRangeType	139
Simple Type shortAttributeType	139
Simple Type trackingLevelType	140
Simple Type departmentCodeType	140
Simple Type protocolType	140
Simple Type resourceTypeGeneralType	141
Simple Type licenseURIType	146
Simple Type licenseIDType	147
Simple Type relatedIDTypeType	149
Simple Type relationTypeType	153
Simple Type dateTypeType	157
Simple Type researchDomainNameType	159
Simple Type departmentType	160
Simple Type visibilityType	160
Simple Type storagePerformanceType	161
Simple Type fileEstimateType	162
Simple Type securityLevelType	163
Simple Type yesNoMaybeType	164
Simple Type storageSystemType	164
Simple Type projectPurposeType	165
Simple Type licenseType	166
Simple Type statusType	167
Simple Type mediafluxAssetIDType	169
Complex Type(s)	169
Complex Type projectIDValueType	169
Complex Type textType	170
Complex Type titleType	171
Complex Type shortTextType	172
Complex Type longTextType	173
Complex Type userType	173
Complex Type shortUserType	176
Complex Type pathType	177
Complex Type storageQuantityType	178
Attribute(s)	178
Attribute projectIDValueType / @projectIDType	178
Attribute @inherited	179
Attribute @discoverable	179
Attribute @trackingLevel	180
Attribute @resourceTypeGeneral	180
Attribute @approved	182
Attribute userType / alternativeNameIdentifier / @nameIdentifierSchema	182
Attribute userType / alternativeNameIdentifier / @schemaURI	182
Attribute userType / @userID	183
Attribute userType / @userIDType	183
Attribute shortUserType / @userID	183
Attribute shortUserType / @userIDType	184
Attribute pathType / @protocol	184
Attribute alternativeID / @alternativeIDType	184
Attribute dataUser / @readOnly	184
Attribute fundingReference / funderID / @funderIDType	185
Attribute fundingReference / funderID / @funderIDSchema	185
Attribute fundingReference / awardNumber / @awardURI	185
Attribute fundingReference / @federalFunder	185
Attribute license / @licenseURI	186
Attribute license / @licenseID	186
Attribute license / @licenseIDSchema	187
Attribute license / @licenseIDSchemaURI	187
Attribute duaReference / duaID / @duaURI	188
Attribute otherDate / @dateType	188
Attribute otherDate / @dateInformation	188
Attribute projectDescription / departments / department / @departmentCode	189
Attribute additionalProjectInformation / funded / @federallyFunded	189
Attribute supplementalMetadata / keywords / keyword / @subjectSchema	189
Attribute supplementalMetadata / keywords / keyword / @subjectSchemaURI	189
Attribute supplementalMetadata / keywords / keyword / @valueURI	190
Attribute supplementalMetadata / keywords / keyword / @classificationCode	190
Attribute supplementalMetadata / relations / relation / @relatedIDType	190
Attribute supplementalMetadata / relations / relation / @relationType	192
Attribute supplementalMetadata / relations / relation / @relatedMetadataSchema	193
Attribute supplementalMetadata / relations / relation / @relatedMetadataSchemaURI	193

Attribute supplementalMetadata / relations / relation / @relatedMetadataSchemaType	194
Attribute itemFields / itemID / @itemIDType	194
Attribute resource / @resourceClass	194
Attribute resource / @resourceID	195
Attribute resource / @resourceIDType	195
Element Group(s)	195
Element Group provenanceSubfields	195
Element Group projectRoles	198
Element Group projectDescription	199
Element Group storageAndAccess	201
Element Group additionalProjectInformation	206
Element Group supplementalMetadata	208
Element Group projectFields	211
Element Group itemFields	214
Namespace: "http://www.w3.org/XML/1998/namespace"	216
Schema(s)	216
Imported schema xml.xsd	216
Attribute(s)	218
Attribute @xml:lang	218
Attribute @xml:space	218
Attribute @xml:base	219
Attribute @xml:id	219
Attribute Group(s)	220
Attribute Group xml:specialAttrs	220

Namespace: ""

Schema(s)

Main schema TigerData_StandardMetadataSchema_v1.2.xsd

Namespace	No namespace
Properties	attribute form default: unqualified
	element form default: qualified

Element(s)

Element userType / netID

Namespace	No namespace
Annotations	The Princeton University NetID (also called the OIT NetID) is the name or user-id that identifies a person to a computer system or electronic service at Princeton.
Diagram	
Type	netIDType
Properties	content: simple
	minOccurs: 0
	maxOccurs: 1
Facets	pattern [a-z0-9-]{2,10}
Source	<pre><xs:element name="netID" type="netIDType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Princeton University NetID (also called the OIT NetID) is the name or user-id that identifies a person to a computer system or electronic service at Princeton.</xs:documentation> </xs:annotation> </xs:element></pre>

Element userType / PUID

Namespace	No namespace
-----------	--------------

Annotations	The Princeton University ID (aka Student ID, Employee ID, EMPLID, Princeton ID, or PUID) is a unique nine digit identifier assigned to an individual who has an official affiliation with the University.
Diagram	
Type	puidType
Properties	content: simple minOccurs: 0 maxOccurs: 1
Facets	pattern [0-9]{9}
Source	<pre><xs:element name="PUID" type="puidType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Princeton University ID (aka Student ID, Employee ID, EMPLID, Princeton ID, or PUID) is a unique nine digit identifier assigned to an individual who has an official affiliation with the University.</xs:documentation> </xs:annotation> </xs:element></pre>

Element userType / orcid

Namespace	No namespace
Annotations	The ORCID ID URL for the person in a given role, if available and if verified as valid against the ORCID API upon entry.
Diagram	
Type	xs:anyURI
Properties	content: simple minOccurs: 0 maxOccurs: 1
Source	<pre><xs:element name="orcid" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The ORCID ID URL for the person in a given role, if available and if verified as valid against the ORCID API upon entry.</xs:documentation> </xs:annotation> </xs:element></pre>

Element userType / fullName

Namespace	No namespace
Annotations	The full name of the person in a given role, verified in the format family-comma-given and matching the corresponding given and family name fields, if available.
Diagram	
Type	titleLimitType
Properties	content: simple minOccurs: 0

	maxOccurs:	1
Facets	minLength	1
	maxLength	200
Source	<pre><xs:element name="fullName" type="titleLimitType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The full name of the person in a given role, verified in the format family-comma-given and matching the corresponding given and family name fields, if available.</xs:documentation> </xs:annotation> </xs:element></pre>	

Element userType / givenName

Namespace	No namespace	
Annotations	The given name(s) of the person in a given role. If the person has multiple given names, then all should be included in this field, along with any suffixes.	
Diagram		
Type	titleLimitType	
Properties	content:	simple
	minOccurs:	0
	maxOccurs:	1
Facets	minLength	1
	maxLength	200
Source	<pre><xs:element name="givenName" type="titleLimitType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The given name(s) of the person in a given role. If the person has multiple given names, then all should be included in this field, along with any suffixes.</ xs:documentation> </xs:annotation> </xs:element></pre>	

Element userType / familyName

Namespace	No namespace	
Annotations	The family name(s) of the person in a given role. If the person has multiple family names, then all should be included in this field.	
Diagram		
Type	titleLimitType	
Properties	content:	simple
	minOccurs:	0
	maxOccurs:	1
Facets	minLength	1
	maxLength	200
Source	<pre><xs:element name="familyName" type="titleLimitType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The family name(s) of the person in a given role. If the person has multiple family names, then all should be included in this field.</xs:documentation> </xs:annotation> </xs:element></pre>	

Element userType / nameDate

Namespace	No namespace						
Annotations	The date at which the name metadata was recorded.						
Diagram							
Type	dateOrRangeType						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						
Facets	<table> <tr> <td>pattern</td><td> \ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1]) (\ \ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1])) ? </td></tr> </table>	pattern	\ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1]) (\ \ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1])) ?				
pattern	\ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1]) (\ \ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1])) ?						
Source	<pre><xs:element name="nameDate" type="dateOrRangeType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The date at which the name metadata was recorded.</xs:documentation> </xs:annotation> </xs:element></pre>						

Element userType / alternativeNameIdentifier

Namespace	No namespace																				
Annotations	Records alternative (non-ORCID) identifier(s) for the person in a given role.																				
Diagram																					
Type	extension of titleLimitType																				
Type hierarchy	- xs:string - titleLimitType																				
Properties	<table><tr><td>content:</td><td>complex</td></tr><tr><td>minOccurs:</td><td>0</td></tr><tr><td>maxOccurs:</td><td>3</td></tr></table>	content:	complex	minOccurs:	0	maxOccurs:	3														
content:	complex																				
minOccurs:	0																				
maxOccurs:	3																				
Attributes	<table><tr><th>QName</th><th>Type</th><th>Use</th><th></th></tr><tr><td>nameIdentifierSchema</td><td>shortAttributeType</td><td>required</td><td></td></tr><tr><td></td><td colspan="3">The name of the schema to which the name identifier belongs (required when an alternative name identifier is given).</td></tr><tr><td>schemaURI</td><td>xs:anyURI</td><td>required</td><td></td></tr><tr><td></td><td colspan="3">The URI of the schema to which the name identifier belongs (required when an alternative name identifier is given).</td></tr></table>	QName	Type	Use		nameIdentifierSchema	shortAttributeType	required			The name of the schema to which the name identifier belongs (required when an alternative name identifier is given).			schemaURI	xs:anyURI	required			The URI of the schema to which the name identifier belongs (required when an alternative name identifier is given).		
QName	Type	Use																			
nameIdentifierSchema	shortAttributeType	required																			
	The name of the schema to which the name identifier belongs (required when an alternative name identifier is given).																				
schemaURI	xs:anyURI	required																			
	The URI of the schema to which the name identifier belongs (required when an alternative name identifier is given).																				
Source	<pre><xs:element name="alternativeNameIdentifier" minOccurs="0" maxOccurs="3"> <xs:annotation></pre>																				

```

<xs:documentation xml:lang="en">Records alternative (non-ORCID) identifier(s) for the person in
a given role.</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:simpleContent>
    <xs:extension base="titleLimitType">
      <xs:attribute name="nameIdentifierSchema" type="shortAttributeType" use="required">
        <xs:documentation xml:lang="en">The name of the schema to which the name identifier
belongs (required when an alternative name identifier is given).</xs:documentation>
        </xs:annotation>
      </xs:attribute>
      <xs:attribute name="schemaURI" type="xs:anyURI" use="required">
        <xs:documentation xml:lang="en">The URI of the schema to which the name identifier
belongs (required when an alternative name identifier is given).</xs:documentation>
        </xs:annotation>
      </xs:attribute>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
</xs:element>

```

Element shortUserType / netID


Namespace	No namespace						
Annotations	The Princeton University NetID (also called the OIT NetID) is the name or user-id that identifies a person to a computer system or electronic service at Princeton.						
Diagram							
Type	netIDType						
Properties	<table> <tr><td>content:</td><td>simple</td></tr> <tr><td>minOccurs:</td><td>0</td></tr> <tr><td>maxOccurs:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						
Facets	<table> <tr><td>pattern</td><td>[a-z0-9-]{2,10}</td></tr> </table>	pattern	[a-z0-9-]{2,10}				
pattern	[a-z0-9-]{2,10}						
Source	<pre> <xs:element name="netID" type="netIDType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Princeton University NetID (also called the OIT NetID) is the name or user-id that identifies a person to a computer system or electronic service at Princeton.</xs:documentation> </xs:annotation> </xs:element> </pre>						

Element shortUserType / PUID


Namespace	No namespace						
Annotations	The Princeton University ID (aka Student ID, Employee ID, EMPLID, Princeton ID, or PUID) is a unique nine digit identifier assigned to an individual who has an official affiliation with the University.						
Diagram							
Type	puidType						
Properties	<table> <tr><td>content:</td><td>simple</td></tr> <tr><td>minOccurs:</td><td>0</td></tr> <tr><td>maxOccurs:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						
Facets	<table> <tr><td>pattern</td><td>[0-9]{9}</td></tr> </table>	pattern	[0-9]{9}				
pattern	[0-9]{9}						
Source	<pre> <xs:element name="PUID" type="puidType" minOccurs="0" maxOccurs="1"> </pre>						

```
<xs:annotation>
  <xs:documentation xml:lang="en">The Princeton University ID (aka Student ID, Employee ID,
EMPLID, Princeton ID, or PUID) is a unique nine digit identifier assigned to an individual who has
an official affiliation with the University.</xs:documentation>
</xs:annotation>
</xs:element>
```

Element shortUserType / orcid

Namespace	No namespace						
Annotations	The ORCID ID URL for the person in a given role, if available and if verified as valid against the ORCID API upon entry.						
Diagram							
Type	xs:anyURI						
Properties	<table> <tr><td>content:</td><td>simple</td></tr> <tr><td>minOccurs:</td><td>0</td></tr> <tr><td>maxOccurs:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						
Source	<pre><xs:element name="orcid" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The ORCID ID URL for the person in a given role, if available and if verified as valid against the ORCID API upon entry.</xs:documentation> </xs:annotation> </xs:element></pre>						

Element storageQuantityType / size

Namespace	No namespace						
Annotations	The numeric size of the storage quantity The practical limits for floating point values set by Mediaflux are the range [4.9E-324,1.7976931348623157E308]						
Diagram							
Type	restriction of xs:double						
Properties	<table> <tr><td>content:</td><td>simple</td></tr> <tr><td>minOccurs:</td><td>1</td></tr> <tr><td>maxOccurs:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	1	maxOccurs:	1
content:	simple						
minOccurs:	1						
maxOccurs:	1						
Facets	<table> <tr><td>maxInclusive</td><td>100000000000000</td></tr> <tr><td>minExclusive</td><td>0</td></tr> </table>	maxInclusive	100000000000000	minExclusive	0		
maxInclusive	100000000000000						
minExclusive	0						
Source	<pre><xs:element name="size" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The numeric size of the storage quantity</xs:documentation> <xs:documentation xml:lang="en">The practical limits for floating point values set by Mediaflux are the range [4.9E-324,1.7976931348623157E308]</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:double"> <xs:minExclusive value="0"/> <xs:maxInclusive value="100000000000000"/> </xs:restriction> </xs:simpleType> </xs:element></pre>						

Element storageQuantityType / unit

Namespace	No namespace
Annotations	The logical byte unit for the storage quantity (base-10)

Diagram	The logical byte unit for the storage quantity (base-10) Standard type that defines the controlled vocabulary for byte units in storageQuantityType All byte units are base-10,....		
Type	byteUnitType		
Properties	content:	simple	
	minOccurs:	1	
	maxOccurs:	1	
Facets	enumeration	B	Bytes (B)
	enumeration	KB	Kilobytes (KB)
	enumeration	MB	Megabytes (MB)
	enumeration	GB	Gigabytes (GB)
	enumeration	TB	Terabytes (TB)
	enumeration	PB	Petabytes (PB)
Source	<pre><xs:element name="unit" type="byteUnitType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The logical byte unit for the storage quantity (base-10)</ </xs:annotation> </xs:element></pre>		

Element alternativeID

Namespace	No namespace			
Annotations	An alternative identifier for the resource (not the standard TigerData projectID or itemID), given as a string May apply to either Projects or Items Modeled after the DataCite definition for RelatedIdentifier (v4.6+)			
Diagram				
Type	extension of titleLimitType			
Type hierarchy	- xs:string - titleLimitType			
Properties	content:	complex		
Used by	Element	alternativeIDs		
Attributes	QName	Type	Default	Use
	alternativeIDType	shortTextLimitType		required
		A simple description of the alternative ID type (e.g. "Local accession number")		
	inherited	xs:boolean	false	optional

	QName	Type	Default	Use	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
Source	<pre> <xs:element name="alternativeID"> <xs:annotation> <xs:documentation xml:lang="en">An alternative identifier for the resource (not the standard TigerData projectID or itemID), given as a string</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">Modeled after the DataCite definition for RelatedIdentifier (v4.6+)</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleLimitType"> <xs:attribute name="alternativeIDType" type="shortTextLimitType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">A simple description of the alternative ID type (e.g. "Local accession number")</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute ref="inherited" default="false"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>				

Element alternativeIDs

Namespace	No namespace				
Annotations	The container element for all alternative IDs for a resource May apply to either Projects or Items If this element is present, then it should contain at least one sub-element				
Diagram	The diagram illustrates the structure of the <code>alternativeIDs</code> element. It is a container element for <code>alternativeID</code> elements. The <code>alternativeIDs</code> element has two attributes: <code>discoverable</code> (Type: <code>xs:boolean</code>, Default: <code>true</code>) and <code>trackingLevel</code> (Type: <code>trackingLevelType</code>, Fixed: <code>ResourceRecord</code>). The <code>alternativeID</code> element is a simple content element that is an extension of <code>titleLimitType</code>. It has a cardinality of 1..10.				
Properties	content:	complex			
Used by	Element Groups	itemFields, projectFields			
Model	alternativeID{1,10}				
Children	alternativeID				
Instance	<pre><alternativeIDs discoverable="true" trackingLevel="ResourceRecord"> <alternativeID alternativeIDType="" inherited="false">{1,10}</alternativeID> </alternativeIDs></pre>				
Attributes	QName	Type	Fixed	Default	Use
	discoverable	xs:boolean		true	optional
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			

	QName	Type	Fixed	Default	Use	
	trackingLevel	trackingLevelType	ResourceRecord		optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="alternativeIDs"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all alternative IDs for a resource</ xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="alternativeID" minOccurs="1" maxOccurs="10"/> </xs:sequence> <xs:attribute ref="discoverable" default="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:complexType> </xs:element></pre>					

Element parentProject


Namespace	No namespace
Annotations	The ID of the project to which the resource belongs directly Applies to both Projects and Items Takes precedence over any IsChildOf relations to other projects
Diagram	The diagram illustrates the structure of the parentProject element. It is an extension of the projectIDValueType (extension base). The base type projectIDValueType has a base type doType and an attribute projectIDType of type xs:string, fixed to DOI. The parentProject element is an extension of projectIDValueType and has three attributes: inherited (type xs:boolean, default true), discoverable (type xs:boolean, fixed true), and trackingLevel (type trackingLevelType, fixed ResourceRecord). The parentProject element is described as "The ID of the project to which the resource belongs directly. Applies to both Projects and Items. Takes precedence over..."
Type	extension of projectIDValueType

Type hierarchy	- xs:string - doiType - projectIDValueType					
Properties	content:	complex				
Used by	Element Groups	itemFields, projectFields				
Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean	true		optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean		true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	projectIDType	xs:string	DOI		optional	
		Makes explicit that the project ID is always given as a DOI				
	trackingLevel	trackingLevelType	ResourceRecord		optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="parentProject"> <xs:annotation> <xs:documentation xml:lang="en">The ID of the project to which the resource belongs directly</ xs:documentation> <xs:documentation xml:lang="en">Applies to both Projects and Items</xs:documentation> <xs:documentation xml:lang="en">Takes precedence over any IsChildOf relations to other projects</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="projectIDValueType"> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>					

Element dataSponsor

Namespace	No namespace
Annotations	The person who takes primary responsibility for the project Does not apply to Items

Diagram




Type	extension of userType				
Type hierarchy	• userType				
Properties	content:	complex			
Used by	Element Group	projectRoles			
Model	netID{0,1} , PUID{0,1} , orcid{0,1} , fullName{0,1} , givenName{0,1} , familyName{0,1} , nameDate{0,1} , alternativeNameIdentifier{0,3}				
Children	PUID, alternativeNameIdentifier, familyName, fullName, givenName, nameDate, netID, orcid				
Instance	<dataSponsor discoverable="true" inherited="true" trackingLevel="ResourceRecord" userID="" userIDType="NetID"> <netID>{0,1}</netID> <PUID>{0,1}</PUID> <orcid>{0,1}</orcid> <fullName>{0,1}</fullName> <givenName>{0,1}</givenName> <familyName>{0,1}</familyName> <nameDate>{0,1}</nameDate> <alternativeNameIdentifier nameIdentifierSchema="" schemaURI="">{0,3}</alternativeNameIdentifier> </dataSponsor>				
Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	true	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	inherited	xs:boolean	true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
	trackingLevel	trackingLevelType	ResourceRecord	optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)			
	userID	netIDType		required	
		Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID			
	userIDType	xs:string	NetID	optional	
	Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute				
Source	<xs:element name="dataSponsor"> <xs:annotation> <xs:documentation xml:lang="en">The person who takes primary responsibility for the project</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="userType"> <xs:attribute ref="inherited" fixed="true"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element>				

Element dataManager

Namespace	No namespace
Annotations	The person who manages the day-to-day activities for the project Does not apply to Items

Diagram




Type	extension of userType					
Type hierarchy	• userType					
Properties	content: complex					
Used by	Element Group projectRoles					
Model	netID{0,1} , PUID{0,1} , orcid{0,1} , fullName{0,1} , givenName{0,1} , familyName{0,1} , nameDate{0,1} , alternativeNameIdentifier{0,3}					
Children	PUID, alternativeNameIdentifier, familyName, fullName, givenName, nameDate, netID, orcid					
Instance	<dataManager discoverable="true" inherited="true" trackingLevel="ResourceRecord" userID="" userIDType="NetID"> <netID>{0,1}</netID> <PUID>{0,1}</PUID> <orcid>{0,1}</orcid> <fullName>{0,1}</fullName> <givenName>{0,1}</givenName> <familyName>{0,1}</familyName> <nameDate>{0,1}</nameDate> <alternativeNameIdentifier nameIdentifierSchema="" schemaURI="">{0,3}</alternativeNameIdentifier> </dataManager>					
Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean		true	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean		true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	trackingLevel	trackingLevelType	ResourceRecord		optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
	userID	netIDType			required	
		Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID				
	userIDType	xs:string	NetID		optional	
	Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute					
Source	<xs:element name="dataManager"> <xs:annotation> <xs:documentation xml:lang="en">The person who manages the day-to-day activities for the project</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Items</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="userType"> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" default="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element>					

Element dataUser

Namespace	No namespace
Annotations	A person who has access privileges to the resource May apply to either Projects or Items

Diagram



Type	extension of userType					
Type hierarchy	• userType					
Properties	content:	complex				
Used by	Element	dataUsers				
Model	netID{0,1} , PUID{0,1} , orcid{0,1} , fullName{0,1} , givenName{0,1} , familyName{0,1} , nameDate{0,1} , alternativeNameIdentifier{0,3}					
Children	PUID, alternativeNameIdentifier, familyName, fullName, givenName, nameDate, netID, orcid					
Instance	<dataUser discoverable="false" inherited="true" readOnly="" userID="" userIDType="NetID"> <netID>{0,1}</netID> <PUID>{0,1}</PUID> <orcid>{0,1}</orcid> <fullName>{0,1}</fullName> <givenName>{0,1}</givenName> <familyName>{0,1}</familyName> <nameDate>{0,1}</nameDate> <alternativeNameIdentifier nameIdentifierSchema="" schemaURI="">{0,3}</alternativeNameIdentifier> </dataUser>					
Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean		false	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean		true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	readOnly	xs:boolean			required	
		Specifies whether the data user has read-only access to the resource (if false, then read-write access is granted)				
	userID	netIDType			required	
		Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID				
	userIDType	xs:string	NetID		optional	
	Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute					
Source	<xs:element name="dataUser"> <xs:annotation> <xs:documentation xml:lang="en">A person who has access privileges to the resource</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="userType"> <xs:attribute name="readOnly" type="xs:boolean" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Specifies whether the data user has read-only access to the resource (if false, then read-write access is granted)</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" default="false"/> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element>					

Element dataUsers


Namespace	No namespace
Annotations	The container element for all data users of a resource May apply to either Projects or Items

	If this element is present, then it should contain at least one sub-element				
Diagram	The diagram illustrates the structure of the <code>dataUsers</code> element. It is a container element for all data users of a resource. It contains a sequence of <code>dataUser</code> elements (1..100) and an optional <code>trackingLevel</code> attribute. The <code>trackingLevel</code> attribute has a fixed value of <code>ResourceRecord</code> and a type of <code>trackingLevelType</code>. The <code>dataUser</code> element has a type of <code>Extension of 'userType'</code>.				
Properties	content:	complex			
Used by	Element Groups	itemFields, projectRoles			
Model	<code>dataUser{1,100}</code>				
Children	<code>dataUser</code>				
Instance	<pre><dataUsers trackingLevel="ResourceRecord"> <dataUser discoverable="false" inherited="true" readOnly="" userID="" userIDType="NetID">{1,100}</dataUser> </dataUsers></pre>				
Attributes	QName	Type	Fixed	Use	
	trackingLevel	trackingLevelType	ResourceRecord	optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="dataUsers"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all data users of a resource</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="dataUser" minOccurs="1" maxOccurs="100"/> </xs:sequence> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:complexType> </xs:element></pre>				

Element title

Namespace	No namespace
Annotations	A plain-language title for the resource May apply to either Projects or Items Restricted to fewer characters than the typical free-text limitations

Diagram




Type	extension of titleType					
Type hierarchy	- xs:string - titleLimitType - titleType					
Properties	content:	complex				
Used by	Element Groups	itemFields, projectDescription				
Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean	true		optional	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems					
	inherited	xs:boolean	false		optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)					
	trackingLevel	trackingLevelType	ResourceRecord		optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)					
	xml:lang	union of(xs:language, restriction of xs:string)		en	optional	
	<div> <h3>lang (as an attribute name)</h3>					

QName	Type	Fixed	Default	Use
	<p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p> </div>			
Source	<pre> <xs:element name="title"> <xs:annotation> <xs:documentation xml:lang="en">A plain-language title for the resource</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">Restricted to fewer characters than the typical free-text limitations</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleType"> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>			

Element description

Namespace	No namespace
Annotations	A plain-language description of the resource and/or its contents
	May apply to either Projects or Items

Diagram



Type: extension of longTextType

Type hierarchy:

- xs:string
- longTextLimitType
- longTextType

Properties: content: complex

Used by: Element Groups: itemFields, projectDescription

Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean	true		optional	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems					
	inherited	xs:boolean	false		optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)					
	trackingLevel	trackingLevelType	ResourceRecord		optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)					
	xml:lang	union of(xs:language, restriction of xs:string)		en	optional	
	<div> <h3>lang (as an attribute name)</h3>					

QName	Type	Fixed	Default	Use	
	<p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p> </div>				
Source	<pre><xs:element name="description"> <xs:annotation> <xs:documentation xml:lang="en">A plain-language description of the resource and/or its contents</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="longTextType"> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>				

Element language

Namespace	No namespace				
Annotations	Language declaration for the contents of the resource May apply to either Projects or Items				
Diagram					
Type	extension of xs:language				
Properties	content:	complex			
Used by	Element	languages			
Attributes	QName	Type	Default	Use	
	inherited	xs:boolean	true	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
Source	<pre><xs:element name="language"> <xs:annotation> <xs:documentation xml:lang="en">Language declaration for the contents of the resource</xs:documentation></pre>				

```
<xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:simpleContent>
    <xs:extension base="xs:language">
      <xs:attribute ref="inherited" default="true"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
</xs:element>
```

Element languages

Namespace	No namespace																													
Annotations	The container element for all languages for a resource May apply to either Projects or Items If this element is present, then it should contain at least one sub-element																													
Diagram	The diagram illustrates the structure of the languages element. It is a container element for all languages for a resource, applicable to either Projects or Items. It contains two attributes: discoverable (Type: xs:boolean, Fixed: true) and trackingLevel (Type: trackingLevelType, Fixed: ResourceRecord). The discoverable attribute specifies whether a given field should be discoverable to search operations within TigerData systems. The trackingLevel attribute specifies the tracking level of a given field (ResourceRecord or InternalUseOnly). The languages element contains a sequence of language elements (1..10), which are extensions of 'xs:language'. The language element is a language declaration for the contents of the resource, applicable to either Projects or Items.																													
Properties	content:	complex																												
Used by	Element Groups	itemFields, projectDescription																												
Model	language{1,10}																													
Children	language																													
Instance	<pre><languages discoverable="true" trackingLevel="ResourceRecord"> <language inherited="true">{1,10}</language> </languages></pre>																													
Attributes	<table><thead><tr><th>QName</th><th>Type</th><th>Fixed</th><th>Use</th><th></th></tr></thead><tbody><tr><td>discoverable</td><td>xs:boolean</td><td>true</td><td>optional</td><td></td></tr><tr><td></td><td colspan="4">Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems</td></tr><tr><td>trackingLevel</td><td>trackingLevelType</td><td>ResourceRecord</td><td>optional</td><td></td></tr><tr><td></td><td colspan="4">Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)</td></tr></tbody></table>	QName	Type	Fixed	Use		discoverable	xs:boolean	true	optional			Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				trackingLevel	trackingLevelType	ResourceRecord	optional			Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)							
QName	Type	Fixed	Use																											
discoverable	xs:boolean	true	optional																											
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems																													
trackingLevel	trackingLevelType	ResourceRecord	optional																											
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)																													
Source	<pre><xs:element name="languages"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all languages for a resource</ </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="language" minOccurs="1" maxOccurs="10"/> </xs:sequence> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:complexType> </xs:element></pre>																													

Element fundingReference

Namespace	No namespace				
Annotations	Information about financial support for the resource (at minimum, a name for the funding provider) This is most often used to acknowledge grant funding for research projects, but it may also be used to specify any other funding sources for any type of resource May apply to either Projects or Items Derived from the DataCite definitions for FundingReference (v4.6+) https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/fundingreference/				
Diagram					
Properties	content:	complex			
Used by	Element	fundingReferences			
Model	funderName , funderID{0,1} , awardNumber{0,1} , awardTitle{0,1}				
Children	awardNumber, awardTitle, funderID, funderName				
Instance	<pre><fundingReference federalFunder="false" inherited="true"> <funderName xml:lang="en">{1,1}</funderName> <funderID funderIDSchema="https://ror.org/" funderIDType="ROR" xml:lang="en">{0,1}</funderID> <awardNumber awardURI="">{0,1}</awardNumber> <awardTitle xml:lang="en">{0,1}</awardTitle> </fundingReference></pre>				
Attributes	QName	Type	Default	Use	
	federalFunder	xs:boolean	false	optional	
		Whether the funder is part of the U.S. federal government (default false) If true, then the federallyFunded attribute for funded should also be true			
	inherited	xs:boolean	true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources			

	QName	Type	Default	Use	
		Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
Source		<pre> <xs:element name="fundingReference"> <xs:annotation> <xs:documentation xml:lang="en">Information about financial support for the resource (at minimum, a name for the funding provider)</xs:documentation> <xs:documentation xml:lang="en">This is most often used to acknowledge grant funding for research projects, but it may also be used to specify any other funding sources for any type of resource</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite definitions for FundingReference (v4.6+)</xs:documentation> <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/fundingReference/</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="funderName" type="titleType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the name of the funding provider</xs:documentation> </xs:annotation> <xs:documentation xml:lang="en">If the funding provider is part of the U.S. federal government, then the federalFunder attribute should be set to true</xs:documentation> </xs:element> <xs:element name="funderID" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the unique identifier for the funding provider, if applicable</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleType"> <xs:attribute name="funderIDType" default="ROR"> <xs:annotation> <xs:documentation xml:lang="en">Records the type of identifier used for funderID</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> <xs:restriction base="xs:string"> <xs:enumeration value="Crossref Funder ID" xml:lang="en"/> <xs:enumeration value="GRID" xml:lang="en"/> <xs:enumeration value="ISNI" xml:lang="en"/> <xs:enumeration value="ROR" xml:lang="en"/> <xs:enumeration value="Other" xml:lang="en"/> </xs:restriction> </xs:sequence> <xs:attribute name="funderIDSchema" type="xs:anyURI" default="https://ror.org"> <xs:annotation> <xs:documentation xml:lang="en">Records the schema that defines funderIDType</xs:documentation> </xs:annotation> </xs:attribute> </xs:complexType> </xs:element> <xs:element name="awardNumber" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the award number for the fundingReference, if applicable</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleLimitType"> <xs:attribute name="awardURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">Records the URI for the awardNumber</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> <xs:element name="awardTitle" type="titleType" minOccurs="0" maxOccurs="1"> <xs:annotation> </pre>			

```

<xs:documentation xml:lang="en">Records the title for the fundingReference, if
applicable</xs:documentation>
</xs:annotation>
</xs:element>
</xs:sequence>
<xs:attribute name="federalFunder" type="xs:boolean" default="false">
<xs:annotation>
<xs:documentation xml:lang="en">Whether the funder is part of the U.S. federal government
(default false)</xs:documentation>
<xs:documentation xml:lang="en">If true, then the federallyFunded attribute for funded
should also be true</xs:documentation>
</xs:annotation>
</xs:attribute>
<xs:attribute ref="inherited" default="true"/>
</xs:complexType>
</xs:element>

```

Element fundingReference / funderName

Namespace	No namespace				
Annotations	Records the name of the funding provider If the funding provider is part of the U.S. federal government, then the federalFunder attribute should be set to true				
Diagram					
Type	titleType				
Type hierarchy	- xs:string - titleLimitType - titleType				
Properties	content:	complex			
	minOccurs:	1			
	maxOccurs:	1			
Attributes	QName	Type	Default	Use	
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
	<div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p> </div>				

	QName	Type	Default	Use	
		</div>			
Source	<pre><xs:element name="funderName" type="titleType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the name of the funding provider</xs:documentation> <xs:documentation xml:lang="en">If the funding provider is part of the U.S. federal government, then the federalFunder attribute should be set to true</xs:documentation> </xs:annotation> </xs:element></pre>				

Element fundingReference / funderID

Namespace	No namespace				
Annotations	Records the unique identifier for the funding provider, if applicable				
Diagram	The diagram illustrates the structure of the <code>fundingReference</code> element. It is an extension of the <code>titleType</code> base type. The <code>titleType</code> box shows a <code>titleLimitType</code> extension and an <code>Attributes</code> box containing the <code>xml:lang</code> attribute (default 'en'). The <code>funderID</code> attribute is shown as an extension of <code>titleType</code>, with a description: 'Records the unique identifier for the funding provider, if applicable'. The <code>funderID</code> attribute is further detailed with a <code>funderIDType</code> attribute (restriction of <code>xs:string</code>, default 'ROR') and a <code>funderIDSchema</code> attribute (<code>xs:anyURI</code>, default 'https://ror.org/').				
Type	extension of titleType				
Type hierarchy	- xs:string - titleLimitType - titleType				
Properties	content:	complex			
	minOccurs:	0			
	maxOccurs:	1			
Attributes	QName	Type	Default	Use	
	funderIDSchema	xs:anyURI	https://ror.org/	optional	
	Records the schema that defines funderIDType				
	funderIDType	restriction of xs:string	ROR	optional	
	Records the type of identifier used for funderID				
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
	<pre><div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p></pre>				

QName	Type	Default	Use
	Notes Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility. See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txt and the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registry for further information. The union allows for the 'un-declaration' of xml:lang with the empty string.		
Source	<pre><xs:element name="funderID" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the unique identifier for the funding provider, if applicable</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleType"> <xs:attribute name="funderIDType" default="ROR"> <xs:annotation> <xs:documentation xml:lang="en">Records the type of identifier used for funderID</ xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Crossref Funder ID" xml:lang="en"/> <xs:enumeration value="GRID" xml:lang="en"/> <xs:enumeration value="ISNI" xml:lang="en"/> <xs:enumeration value="ROR" xml:lang="en"/> <xs:enumeration value="Other" xml:lang="en"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="funderIDSchema" type="xs:anyURI" default="https://ror.org/"> <xs:annotation> <xs:documentation xml:lang="en">Records the schema that defines funderIDType</ xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>		

Element fundingReference / awardNumber

Namespace	No namespace						
Annotations	Records the award number for the fundingReference, if applicable						
Diagram	<pre> classDiagram class titleLimitType { <<abstract>> } class awardNumber { <<extension of titleLimitType>> +awardURI xs:anyURI } titleLimitType < -- awardNumber </pre>						
Type	extension of titleLimitType						
Type hierarchy	- xs:string - titleLimitType						
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						

Attributes	QName	Type	Use	
	awardURI	xs:anyURI	optional	
		Records the URI for the awardNumber		
Source	<pre><xs:element name="awardNumber" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the award number for the fundingReference, if applicable</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleLimitType"> <xs:attribute name="awardURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">Records the URI for the awardNumber</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>			

Element fundingReference / awardTitle

Namespace	No namespace			
Annotations	Records the title for the fundingReference, if applicable			
Diagram	The diagram illustrates the structure of the awardTitle element. It is a complex type that inherits from the titleType base type. The titleType base type has a titleLimitType restriction. The awardTitle element is defined as a complex type that inherits from titleType. The diagram also shows the attributes of titleType, including xml:lang with a default value of en. A note indicates that titleType is the standard type used for title values.			
Type	titleType			
Type hierarchy	- xs:string - titleLimitType - titleType			
Properties	content:	complex		
	minOccurs:	0		
	maxOccurs:	1		
Attributes	QName	Type	Default	Use
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional
		<pre> <div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc- editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at </pre>		

	QName	Type	Default	Use
		http://www.iana.org/assignments/language-subtag-registry for further information. The union allows for the 'un-declaration' of xml:lang with the empty string.		
Source	<xs:element name="awardTitle" type="titleType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the title for the fundingReference, if applicable</xs:documentation> </xs:annotation> </xs:element>			

Element fundingReferences

Namespace	No namespace																							
Annotations	The container element for all funding references for a resource May apply to either Projects or Items If this element is present, then it should contain at least one sub-element																							
Diagram	The diagram illustrates the structure of the fundingReferences element. It is a container element that can be applied to either Projects or Items. It contains two attributes: discoverable (a boolean attribute, fixed to true) and trackingLevel (a trackingLevelType attribute, fixed to ResourceRecord). The fundingReferences element contains one or more fundingReference elements (multiplicity 1..10). The fundingReference element represents information about financial support for the resource, with a minimum requirement of a name for the funding provider.																							
Properties	content:	complex																						
Used by	Element Groups	additionalProjectInformation, itemFields																						
Model	fundingReference{1,10}																							
Children	fundingReference																							
Instance	<pre><fundingReferences discoverable="true" trackingLevel="ResourceRecord"> <fundingReference federalFunder="false" inherited="true">{1,10}</fundingReference> </fundingReferences></pre>																							
Attributes	<table><thead><tr><th>QName</th><th>Type</th><th>Fixed</th><th>Use</th></tr></thead><tbody><tr><td>discoverable</td><td>xs:boolean</td><td>true</td><td>optional</td></tr><tr><td colspan="4">Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems</td></tr><tr><td>trackingLevel</td><td>trackingLevelType</td><td>ResourceRecord</td><td>optional</td></tr><tr><td colspan="4">Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)</td></tr></tbody></table>	QName	Type	Fixed	Use	discoverable	xs:boolean	true	optional	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				trackingLevel	trackingLevelType	ResourceRecord	optional	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)						
QName	Type	Fixed	Use																					
discoverable	xs:boolean	true	optional																					
Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems																								
trackingLevel	trackingLevelType	ResourceRecord	optional																					
Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)																								
Source	<pre><xs:element name="fundingReferences"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all funding references for a resource</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="fundingReference" minOccurs="1" maxOccurs="10"/> </xs:sequence> </xs:complexType></pre>																							

```
<xs:attribute ref="discoverable" fixed="true"/>
<xs:attribute ref="trackingLevel" fixed="ResourceRecord"/>
</xs:complexType>
</xs:element>
```

Element itemResourceType


Namespace	No namespace					
Annotations	A short description of the type of item, used in conjunction with a standard value for the resourceTypeGeneral attribute Does not apply to Projects Modeled after the DataCite definition for ResourceType (v4.6+)					
Diagram	The diagram illustrates the structure of the <code>itemResourceType</code> element. It is an extension of <code>shortTextType</code>. The diagram shows the following components: shortTextType (extension base): Base Type <code>shortTextLimitType</code>. shortTextLimitType: Specification for the practical limit for text values within <code>shortTextType</code>. Attributes: xml:lang: Default <code>en</code>. Denotes an attribute whose value is a language code for the natural... itemResourceType: Type <code>Extension of 'shortTextType'</code>. Attributes: resourceTypeGeneral: Type <code>resourceTypeGeneralType</code>. Standard attribute to specify the general type for a resource, following the controlled vocabulary in... inherited: Type <code>xs:boolean</code>, Default <code>false</code>. Standard attribute to specify whether a given field's value should be inherited by any child resources. Inheritance is... discoverable: Type <code>xs:boolean</code>, Fixed <code>true</code>. Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems. trackingLevel: Type <code>trackingLevelType</code>, Fixed <code>ResourceRecord</code>. Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly).					
Type	extension of shortTextType					
Type hierarchy	- xs:string - shortTextLimitType - shortTextType					
Properties	content:	complex				
Used by	Element Group	itemFields				
Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean	true		optional	

QName	Type	Fixed	Default	Use	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
inherited	xs:boolean		false	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
resourceTypeGeneral	resourceTypeGeneralType			required	
	Standard attribute to specify the general type for a resource, following the controlled vocabulary in resourceTypeGeneralType Derived from the DataCite definition for resourceTypeGeneral (v4.6+)				
trackingLevel	trackingLevelType	ResourceRecord		optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
xml:lang	union of(xs:language, restriction of xs:string)		en	optional	
	lang (as an attribute name) denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification. Notes Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility. See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txt and the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registry for further information. The union allows for the 'un-declaration' of xml:lang with the empty string.				
Source	<pre> <xs:element name="itemResourceType"> <xs:annotation> <xs:documentation xml:lang="en">A short description of the type of item, used in conjunction with a standard value for the resourceTypeGeneral attribute</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Projects</xs:documentation> <xs:documentation xml:lang="en">Modeled after the DataCite definition for Resource Type (v4.6+)</ xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="shortTextType"> <xs:attribute ref="resourceTypeGeneral" use="required"/> <xs:attribute ref="inherited" default="false"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>				

Element projectResourceType

Namespace	No namespace
Annotations	The standard (fixed) resource type setting for TigerData projects Does not apply to Items Modeled after the DataCite definition for resourceType (v4.6+)

Diagram



Type extension of shortTextType

Type hierarchy

- xs:string
- shortTextLimitType
- shortTextType

Properties

content:	complex
fixed:	TigerData Project

Used by

Element Group	additionalProjectInformation
---------------	------------------------------


Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean	true		optional	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems					
	inherited	xs:boolean		false	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)					
	resourceTypeGeneral	resourceTypeGeneralType	Project		optional	

QName	Type	Fixed	Default	Use	
	Standard attribute to specify the general type for a resource, following the controlled vocabulary in resourceTypeGeneralType Derived from the DataCite definition for resourceTypeGeneral (v4.6+)				
trackingLevel	trackingLevelType	ResourceRecord		optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
xml:lang	union of(xs:language, restriction of xs:string)		en	optional	
	lang (as an attribute name) denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification. Notes Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility. See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txt and the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registry for further information. The union allows for the 'un-declaration' of xml:lang with the empty string.				
Source	<pre> <xs:element name="projectResourceType" fixed="TigerData Project"> <xs:annotation> <xs:documentation xml:lang="en">The standard (fixed) resource type setting for TigerData projects</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Items</xs:documentation> <xs:documentation xml:lang="en">Modeled after the DataCite definition for resourceType (v4.6+)</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="shortTextType"> <xs:attribute ref="resourceTypeGeneral" fixed="Project"/> <xs:attribute ref="inherited" default="false"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>				

Element license

Namespace	No namespace
Annotations	Specific rights granted for copying and reusing the resource May apply to either Projects or Items Modeled after the DataCite definitions for Rights (v4.6+)

Diagram



Type extension of licenseType

Type hierarchy

- xs:string
- licenseType

Properties content: complex

Used by Element licenses

Attributes	QName	Type	Fixed	Default	Use	
	inherited	xs:boolean		true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	licenseID	licenseIDType			required	
		Specifies the short, standardized version of the license name				
	licenseIDSchema	titleLimitType	SPDX		optional	
		Specifies the schema used for licenseID				
	licenseIDSchemaURI	xs:anyURI	https://spdx.org/licenses/		optional	
		Specifies the URI of the schema given by licenseIDSchema				
	licenseURI	licenseURIType			required	
		Specifies the URI of the license				

Source

```
<xs:element name="license">
  <xs:annotation>
    <xs:documentation xml:lang="en">Specific rights granted for copying and reusing the resource</xs:documentation>
    <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation>
    <xs:documentation xml:lang="en">Modeled after the DataCite definitions for Rights (v4.6+)</xs:documentation>
  </xs:annotation>
  <xs:complexType>
```

```

<xs:simpleContent>
  <xs:extension base="licenseType">
    <xs:attribute name="licenseURI" type="licenseURIType" use="required">
      <xs:annotation>
        <xs:documentation xml:lang="en">Specifies the URI of the license</xs:documentation>
      </xs:annotation>
    </xs:attribute>
    <xs:attribute name="licenseID" type="licenseIDType" use="required">
      <xs:annotation>
        <xs:documentation xml:lang="en">Specifies the short, standardized version of the license
name</xs:documentation>
      </xs:annotation>
    </xs:attribute>
    <xs:attribute name="licenseIDSchema" type="titleLimitType" fixed="SPDX">
      <xs:annotation>
        <xs:documentation xml:lang="en">Specifies the schema used for licenseID</
xs:documentation>
      </xs:annotation>
    </xs:attribute>
    <xs:attribute name="licenseIDSchemaURI" type="xs:anyURI" fixed="https://spdx.org/licenses/">
      <xs:annotation>
        <xs:documentation xml:lang="en">Specifies the URI of the schema given by
licenseIDSchema</xs:documentation>
      </xs:annotation>
    </xs:attribute>
    <xs:attribute ref="inherited" default="true"/>
  </xs:extension>
</xs:simpleContent>
</xs:complexType>
</xs:element>

```

Element licenses

Namespace	No namespace															
Annotations	The container element for all licenses for a resource May apply to either Projects or Items If this element is present, then it should contain at least one sub-element															
Diagram																
Properties	content:	complex														
Used by	Element Groups	additionalProjectInformation, itemFields														
Model	license{1,10}															
Children	license															
Instance	<pre><licenses discoverable="true" trackingLevel="ResourceRecord"> <license inherited="true" licenseID="" licenseIDSchema="SPDX" licenseIDSchemaURI="https:// spdx.org/licenses/" licenseURI="">{1,10}</license> </licenses></pre>															
Attributes	<table><tr><th>QName</th><th>Type</th><th>Fixed</th><th>Use</th><th></th></tr><tr><td>discoverable</td><td>xs:boolean</td><td>true</td><td>optional</td><td></td></tr></table>	QName	Type	Fixed	Use		discoverable	xs:boolean	true	optional		<table><tr><td></td><td>Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems</td></tr></table>				Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems
QName	Type	Fixed	Use													
discoverable	xs:boolean	true	optional													
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems															

	QName	Type	Fixed	Use	
	trackingLevel	trackingLevelType	ResourceRecord	optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)			
Source	<pre><xs:element name="licenses"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all licenses for a resource</ xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="license" minOccurs="1" maxOccurs="10"/> </xs:sequence> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:complexType> </xs:element></pre>				

Element duaReference

Namespace	No namespace				
Annotations	Information about a formal agreement governing data use pertaining to the resource (at minimum, a name for the agreement grantor) DUA is short for Data Use Agreement May apply to either Projects or Items				
Diagram					
Properties	content:	complex			
Used by	Element	duaReferences			
Model	grantorName , duaID{0,1} , duaTitle{0,1}				
Children	duaID, duaTitle, grantorName				
Instance	<pre><duaReference inherited="true"> <grantorName xml:lang="en">{1,1}</grantorName> <duaID duaURI="" xml:lang="en">{0,1}</duaID> <duaTitle xml:lang="en">{0,1}</duaTitle> </duaReference></pre>				
Attributes	QName	Type	Default	Use	
	inherited	xs:boolean	true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources			

	QName	Type	Default	Use
		Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)		
Source	<pre><xs:element name="duaReference"> <xs:annotation> <xs:documentation xml:lang="en">Information about a formal agreement governing data use pertaining to the resource (at minimum, a name for the agreement grantor)</xs:documentation> <xs:documentation xml:lang="en">DUA is short for Data Use Agreement</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="grantorName" type="titleType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the name of the DUA grantor</xs:documentation> </xs:annotation> </xs:element> <xs:element name="duaID" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the identifier for the DUA, if applicable (given as a string)</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleType"> <xs:attribute name="duaURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">Records the URI for the DUA</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> <xs:element name="duaTitle" type="titleType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the title for the DUA, if applicable</ xs:documentation> </xs:annotation> </xs:element> </xs:sequence> <xs:attribute ref="inherited" default="true"/> </xs:complexType> </xs:element></pre>			

Element duaReference / grantorName

Namespace	No namespace
Annotations	Records the name of the DUA grantor
Diagram	
Type	titleType
Type hierarchy	- xs:string - titleLimitType - titleType
Properties	content: complex

	minOccurs:	1			
	maxOccurs:	1			
Attributes	QName	Type	Default	Use	
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
		<div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p></div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p></div>			
Source	<xs:element name="grantorName" type="titleType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the name of the DUA grantor</xs:documentation> </xs:annotation> </xs:element>				

Element duaReference / duaID

Namespace	No namespace						
Annotations	Records the identifier for the DUA, if applicable (given as a string)						
Diagram	<pre> classDiagram class titleType { titleLimitType } class titleLimitType { titleType } class duaReference { titleLimitType duaURI } titleType < -- duaReference titleLimitType --> titleType duaReference --> titleLimitType duaReference --> duaURI </pre> The diagram illustrates the structure of the <code>duaReference</code> / <code>duaID</code> element. It is an extension of the <code>titleType</code> base type. The <code>titleType</code> base type has a <code>titleLimitType</code> attribute. The <code>duaReference</code> / <code>duaID</code> element has a <code>titleLimitType</code> attribute and a <code>duaURI</code> attribute. The <code>duaURI</code> attribute is of type <code>xs:anyURI</code> and is used to record the URI for the DUA.						
Type	extension of titleType						
Type hierarchy	- xs:string - titleLimitType - titleType						
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						

Attributes	QName	Type	Default	Use		
	duaURI	xs:anyURI		optional		
		Records the URI for the DUA				
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional		
	lang (as an attribute name) denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification. Notes Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility. See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txt and the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registry for further information. The union allows for the 'un-declaration' of xml:lang with the empty string.					
Source	<pre><xs:element name="duaID" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the identifier for the DUA, if applicable (given as a string)</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleType"> <xs:attribute name="duaURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">Records the URI for the DUA</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>					

Element duaReference / duaTitle

Namespace	No namespace
Annotations	Records the title for the DUA, if applicable
Diagram	<pre> classDiagram class titleType { Base Type } class titleLimitType { titleLimitType } class duaTitle { Type titleType } titleType -- > titleLimitType titleType -- > duaTitle duaTitle --> titleType </pre> Records the title for the DUA, if applicable Specification for the practical limit for text values within titleType Attributes xml:lang Default en denotes an attribute whose value is a language code for the natural... Standard type used for title values
Type	titleType
Type hierarchy	- xs:string - titleLimitType - titleType
Properties	content: complex

	minOccurs:	0			
	maxOccurs:	1			
Attributes	QName	Type	Default	Use	
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
		<div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p> </div>			
Source	<xs:element name="duaTitle" type="titleType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Records the title for the DUA, if applicable</xs:documentation> </xs:annotation> </xs:element>				

Element duaReferences

Namespace	No namespace
Annotations	The container element for all DUA references for a resource DUA is short for Data Use Agreement May apply to either Projects or Items If this element is present, then it should contain at least one sub-element
Diagram	
Properties	content: complex
Used by	Element Groups additionalProjectInformation, itemFields
Model	duaReference{1,10}
Children	duaReference
Instance	<pre><duaReferences discoverable="true" trackingLevel="ResourceRecord"> <duaReference inherited="true">{1,10}</duaReference> </duaReferences></pre>

Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	true	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	trackingLevel	trackingLevelType	ResourceRecord	optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)			
Source	<pre><xs:element name="duaReferences"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all DUA references for a resource</ xs:documentation> <xs:documentation xml:lang="en">DUA is short for Data Use Agreement</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="duaReference" minOccurs="1" maxOccurs="10"/> </xs:sequence> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:complexType> </xs:element></pre>				

Element startDate

Namespace	No namespace																				
Annotations	The date when the resource became, or will become, active (may be estimated with a range) The value should not be chronologically earlier than that of the approvalDateTime subfield under the submission field Unlike provenance records, this date field is discoverable and tracked in the resource record May apply to either Projects or Items																				
Diagram	The diagram illustrates the relationship between the startDate element and the dateOrRangeType base type. startDate is shown as an extension of dateOrRangeType. A callout for startDate states: "The date when the resource became, or will become, active (may be estimated with a range). The value should not be...". A callout for dateOrRangeType states: "Standard type used for values that may be either dates or date ranges. Applies a pattern aligned with...". An 'Attributes' section shows the inherited attribute with Type xs:boolean and Default true. A callout for inherited states: "Standard attribute to specify whether a given field's value should be inherited by any child resources. Inheritance is...".																				
Type	extension of dateOrRangeType																				
Type hierarchy	- xs:string - dateOrRangeType																				
Properties	content: complex																				
Used by	Elements itemDates, projectDates																				
Attributes	<table><tr><th>QName</th><th>Type</th><th>Default</th><th>Use</th><th></th></tr><tr><td>inherited</td><td>xs:boolean</td><td>true</td><td>optional</td><td></td></tr><tr><td></td><td colspan="4">Standard attribute to specify whether a given field's value should be inherited by any child resources</td></tr><tr><td></td><td colspan="4">Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)</td></tr></table>	QName	Type	Default	Use		inherited	xs:boolean	true	optional			Standard attribute to specify whether a given field's value should be inherited by any child resources					Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
QName	Type	Default	Use																		
inherited	xs:boolean	true	optional																		
	Standard attribute to specify whether a given field's value should be inherited by any child resources																				
	Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)																				
Source	<pre><xs:element name="startDate"> <xs:annotation> <xs:documentation xml:lang="en">The date when the resource became, or will become, active (may be estimated with a range)</xs:documentation> </xs:annotation></pre>																				

```

<xs:documentation xml:lang="en">The value should not be chronologically earlier than that of the
approvalDateTime subfield under the submission field</xs:documentation>
<xs:documentation xml:lang="en">Unlike provenance records, this date field is discoverable and
tracked in the resource record</xs:documentation>
<xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:simpleContent>
    <xs:extension base="dateOrRangeType">
      <xs:attribute ref="inherited" default="true"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
</xs:element>

```

Element endDate

Namespace	No namespace														
Annotations	The date when the resource became, or will become, inactive from a user perspective, i.e., no further changes are expected to be made (may be estimated with a range) The value should not be chronologically earlier than that of startDate, nor later than that of retirementDate Unlike provenance records, this date field is discoverable and tracked in the resource record May apply to either Projects or Items														
Diagram	<pre>classDiagram class endDate { Type: Extension of 'dateOrRangeType' } class dateOrRangeType { Standard type used for values that may be either dates or date ranges Applies a pattern aligned with... } class inherited { Type: xs:boolean Default: true } endDate -- > dateOrRangeType inherited -- endDate</pre>														
Type	extension of dateOrRangeType														
Type hierarchy	- xs:string - dateOrRangeType														
Properties	content:	complex													
Used by	Elements	itemDates, projectDates													
Attributes	<table><thead><tr><th>QName</th><th>Type</th><th>Default</th><th>Use</th><th></th></tr></thead><tbody><tr><td>inherited</td><td>xs:boolean</td><td>true</td><td>optional</td><td></td></tr></tbody></table>	QName	Type	Default	Use		inherited	xs:boolean	true	optional		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
QName	Type	Default	Use												
inherited	xs:boolean	true	optional												
Source	<pre><xs:element name="endDate"> <xs:annotation> <xs:documentation xml:lang="en">The date when the resource became, or will become, inactive from a user perspective, i.e., no further changes are expected to be made (may be estimated with a range)</xs:documentation> <xs:documentation xml:lang="en">The value should not be chronologically earlier than that of startDate, nor later than that of retirementDate</xs:documentation> <xs:documentation xml:lang="en">Unlike provenance records, this date field is discoverable and tracked in the resource record</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="dateOrRangeType"> <xs:attribute ref="inherited" default="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>														

```
</xs:complexType>
</xs:element>
```

Element retirementDate

Namespace	No namespace				
Annotations	The date when the resource became, or will become, no longer useful to the primary users (may be estimated with a range) The value should not be chronologically earlier than that of endDate, nor later than that of the approvalDateTime subfield under the retirement provenance field Unlike provenance records, this date field is discoverable and tracked in the resource record May apply to either Projects or Items				
Diagram					
Type	extension of dateOrRangeType				
Type hierarchy	- xs:string - dateOrRangeType				
Properties	content:	complex			
Used by	Elements	itemDates, projectDates			
Attributes	QName	Type	Fixed	Use	
	inherited	xs:boolean	true	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
Source	<pre><xs:element name="retirementDate"> <xs:annotation> <xs:documentation xml:lang="en">The date when the resource became, or will become, no longer useful to the primary users (may be estimated with a range)</xs:documentation> <xs:documentation xml:lang="en">The value should not be chronologically earlier than that of endDate, nor later than that of the approvalDateTime subfield under the retirement provenance field</xs:documentation> <xs:documentation xml:lang="en">Unlike provenance records, this date field is discoverable and tracked in the resource record</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="dateOrRangeType"> <xs:attribute ref="inherited" fixed="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>				

Element publicationDate

Namespace	No namespace				
Annotations	The date when the resource became, or will become, publicly available (may be estimated with a range) The value should not be chronologically earlier than that of startDate, nor later than that of the approvalDateTime subfield under the publication field				

	Unlike provenance records, this date field is discoverable and tracked in the resource record Does not apply to Items				
Diagram	The diagram illustrates the relationship between the <code>publicationDate</code> element and the <code>dateOrRangeType</code> base type. <code>publicationDate</code> is shown as an extension of <code>dateOrRangeType</code>. The <code>dateOrRangeType</code> is a standard type used for values that may be either dates or date ranges, applying a pattern aligned with... It has an attribute <code>inherited</code> of type <code>xs:boolean</code> fixed to <code>true</code>. The <code>inherited</code> attribute is a standard attribute to specify whether a given field's value should be inherited by any child resources. Inheritance is limited to the applicability of the field to the child resource (e.g., <code>researchDomain</code> may be inherited by a subproject but not an item).				
Type	extension of <code>dateOrRangeType</code>				
Type hierarchy	<code>xs:string</code> <code>dateOrRangeType</code>				
Properties	content: complex				
Used by	Element <code>projectDates</code>				
Attributes	QName	Type	Fixed	Use	
	inherited	<code>xs:boolean</code>	<code>true</code>	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., <code>researchDomain</code> may be inherited by a subproject but not an item)				
Source	<pre><xs:element name="publicationDate"> <xs:annotation> <xs:documentation xml:lang="en">The date when the resource became, or will become, publicly available (may be estimated with a range)</xs:documentation> <xs:documentation xml:lang="en">The value should not be chronologically earlier than that of startDate, nor later than that of the approvalDateTime subfield under the publication field</ xs:documentation> <xs:documentation xml:lang="en">Unlike provenance records, this date field is discoverable and tracked in the resource record</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Items</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="dateOrRangeType"> <xs:attribute ref="inherited" fixed="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>				

Element otherDate

Namespace	No namespace
Annotations	A date or date range relevant to the resource, not captured by any other date field Unlike provenance records, this date field is discoverable and tracked in the resource record May apply to either Projects or Items


Diagram	otherDate Type Extension of 'dateOrRangeType' A date or date range relevant to the resource, not captured by any other date field Unlike provenance records, this... dateOrRangeType Standard type used for values that may be either dates or date ranges Applies a pattern aligned with... Attributes dateType Type dateTypeType dateInformation Type shortTextLimitType More information about the value of otherDate (recommended if dateType is Other) inherited Type xs:boolean Default true Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is...																																		
Type	extension of dateOrRangeType																																		
Type hierarchy	- xs:string - dateOrRangeType																																		
Properties	content:	complex																																	
Used by	Elements	itemDates, projectDates																																	
Attributes	<table><thead><tr><th>QName</th><th>Type</th><th>Default</th><th>Use</th><th></th></tr></thead><tbody><tr><td>dateInformation</td><td>shortTextLimitType</td><td></td><td>optional</td><td></td></tr><tr><td></td><td colspan="4">More information about the value of otherDate (recommended if dateType is Other)</td></tr><tr><td>dateType</td><td>dateTypeType</td><td></td><td>required</td><td></td></tr><tr><td>inherited</td><td>xs:boolean</td><td>true</td><td>optional</td><td></td></tr><tr><td></td><td colspan="4">Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)</td></tr></tbody></table>	QName	Type	Default	Use		dateInformation	shortTextLimitType		optional			More information about the value of otherDate (recommended if dateType is Other)				dateType	dateTypeType		required		inherited	xs:boolean	true	optional			Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)							
QName	Type	Default	Use																																
dateInformation	shortTextLimitType		optional																																
	More information about the value of otherDate (recommended if dateType is Other)																																		
dateType	dateTypeType		required																																
inherited	xs:boolean	true	optional																																
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)																																		
Source	<pre><xs:element name="otherDate"> <xs:annotation> <xs:documentation xml:lang="en">A date or date range relevant to the resource, not captured by any other date field</xs:documentation> <xs:documentation xml:lang="en">Unlike provenance records, this date field is discoverable and tracked in the resource record</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="dateOrRangeType"> <xs:attribute name="dateType" type="dateTypeType" use="required"/> <xs:attribute name="dateInformation" type="shortTextLimitType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">More information about the value of otherDate (recommended if dateType is Other)</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute ref="inherited" default="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>																																		

Element projectDates

Namespace	No namespace
Annotations	The container element for all date elements that apply to a Project Unlike provenance records, these date fields are all discoverable and tracked in the resource record

If this element is present, then it should contain at least one sub-element

Diagram



Properties content: complex

Used by Element Group additionalProjectInformation

Model startDate{0,1} , endDate{0,1} , retirementDate{0,1} , publicationDate{0,1} , otherDate{0,10}

Children endDate, otherDate, publicationDate, retirementDate, startDate

Instance

```
<projectDates discoverable="true" trackingLevel="ResourceRecord">
  <startDate inherited="true">{0,1}</startDate>
  <endDate inherited="true">{0,1}</endDate>
  <retirementDate inherited="true">{0,1}</retirementDate>
  <publicationDate inherited="true">{0,1}</publicationDate>
  <otherDate dateInformation="" dataType="" inherited="true">{0,10}</otherDate>
</projectDates>
```

Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	true	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	trackingLevel	trackingLevelType	ResourceRecord	optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)			

Source

```
<xs:element name="projectDates">
  <xs:annotation>
    <xs:documentation xml:lang="en">The container element for all date elements that apply to a Project</xs:documentation>
    <xs:documentation xml:lang="en">Unlike provenance records, these date fields are all discoverable and tracked in the resource record</xs:documentation>
  </xs:annotation>
  <xs:complexType base="baseComplexType">
    <xs:sequence>
      <xs:element name="startDate" type="dateOrRangeType" minOccurs="0" maxOccurs="1"/>
      <xs:element name="endDate" type="dateOrRangeType" minOccurs="0" maxOccurs="1"/>
      <xs:element name="retirementDate" type="dateOrRangeType" minOccurs="0" maxOccurs="1"/>
      <xs:element name="publicationDate" type="dateOrRangeType" minOccurs="0" maxOccurs="1"/>
      <xs:element name="otherDate" type="dateOrRangeType" minOccurs="0" maxOccurs="10"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

<xs:documentation xml:lang="en">If this element is present, then it should contain at least one
sub-element</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element ref="startDate" minOccurs="0" maxOccurs="1"/>
    <xs:element ref="endDate" minOccurs="0" maxOccurs="1"/>
    <xs:element ref="retirementDate" minOccurs="0" maxOccurs="1"/>
    <xs:element ref="publicationDate" minOccurs="0" maxOccurs="1"/>
    <xs:element ref="otherDate" minOccurs="0" maxOccurs="10"/>
  </xs:sequence>
  <xs:attribute ref="discoverable" fixed="true"/>
  <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/>
</xs:complexType>
</xs:element>

```

Element itemDates

Namespace	No namespace
Annotations	The container element for all date elements that apply to an Item Unlike provenance records, these date fields are all discoverable and tracked in the resource record If this element is present, then it should contain at least one sub-element
Diagram	
Properties	content: complex
Used by	Element Group itemFields
Model	startDate{0,1} , endDate{0,1} , retirementDate{0,1} , otherDate{0,10}
Children	endDate, otherDate, retirementDate, startDate
Instance	<pre> <itemDates discoverable="true" trackingLevel="ResourceRecord"> <startDate inherited="true">{0,1}</startDate> <endDate inherited="true">{0,1}</endDate> <retirementDate inherited="true">{0,1}</retirementDate> <otherDate dateInformation="" dateType="" inherited="true">{0,10}</otherDate> </itemDates> </pre>

Attributes	QName	Type	Fixed	Use		
	discoverable	xs:boolean	true	optional		
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	trackingLevel	trackingLevelType	ResourceRecord	optional		
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="itemDates"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all date elements that apply to an Item</xs:documentation> <xs:documentation xml:lang="en">Unlike provenance records, these date fields are all discoverable and tracked in the resource record</xs:documentation> <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="startDate" minOccurs="0" maxOccurs="1"/> <xs:element ref="endDate" minOccurs="0" maxOccurs="1"/> <xs:element ref="retirementDate" minOccurs="0" maxOccurs="1"/> <xs:element ref="otherDate" minOccurs="0" maxOccurs="10"/> </xs:sequence> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:complexType> </xs:element></pre>					

Element schemaVersion

Namespace	No namespace					
Annotations	The version of the TigerData Standard Metadata Schema to which the resource adheres (required)					
Diagram	The diagram illustrates the structure of the <code>schemaVersion</code> element. It is an extension of the <code>shortTextLimitType</code> element. The <code>shortTextLimitType</code> element is defined with a description: "Specification for the practical limit for text values within <code>shortTextType</code>". The <code>schemaVersion</code> element is defined with a description: "The version of the TigerData Standard Metadata Schema to which the resource adheres (required)". The <code>schemaVersion</code> element has three attributes: <code>inherited</code> (Type: <code>xs:boolean</code>, Default: <code>true</code>), <code>discoverable</code> (Type: <code>xs:boolean</code>, Fixed: <code>true</code>), and <code>trackingLevel</code> (Type: <code>trackingLevelType</code>, Fixed: <code>InternalUseOnly</code>). Each attribute has a description: <code>inherited</code> is "Standard attribute to specify whether a given field's value should be inherited by any child resources. Inheritance is...", <code>discoverable</code> is "Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems", and <code>trackingLevel</code> is "Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)".					
Type	extension of <code>shortTextLimitType</code>					
Type hierarchy	• <code>xs:string</code> • <code>shortTextLimitType</code>					
Properties	content:	complex				
Used by	Element	resource				
Attributes	QName	Type	Fixed	Default	Use	
	discoverable	<code>xs:boolean</code>	<code>true</code>		optional	

QName	Type	Fixed	Default	Use	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
inherited	xs:boolean		true	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
trackingLevel	trackingLevelType	InternalUseOnly		optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre> <xs:element name="schemaVersion"> <xs:annotation> <xs:documentation xml:lang="en">The version of the TigerData Standard Metadata Schema to which the resource adheres (required)</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="shortTextLimitType"> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>				

Element provenanceSubfields / requestedBy

Namespace	No namespace
Annotations	The person who made the request May be an eligible Data Sponsor or Data Manager, a System Administrator, or a technical service account
Diagram	requestedBy Type: shortUserType The person who made the request May be an eligible Data Sponsor or Data Manager, a System Administrator, or a technical... Attributes userID Type: netIDType Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value... userIDType Type: xs:string Fixed: NetID Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute netID Type: netIDType The Princeton University NetID (also called the OIT NetID) is the name or user-id that identifies a person to a... PUID Type: puidType The Princeton University ID (aka Student ID, Employee ID, EMPLID, Princeton ID, or PUID) is a unique nine digit... orcid Type: xs:anyURI The ORCID ID URL for the person in a given role, if available and if verified as valid against the ORCID API upon entry. Standard type used for user fields Given the required attribute userID, all sub-elements are optional, so the element...

Type	shortUserType				
Properties	content:	complex			
	minOccurs:	1			
	maxOccurs:	1			
Model	netID{0,1} , PUID{0,1} , orcid{0,1}				
Children	PUID, netID, orcid				
Instance	<pre><requestedBy userID="" userIDType="NetID"> <netID>{0,1}</netID> <PUID>{0,1}</PUID> <orcid>{0,1}</orcid> </requestedBy></pre>				
Attributes	QName	Type	Fixed	Use	
	userID	netIDType		required	
		Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID			
	userIDType	xs:string	NetID	optional	
		Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute			
Source	<pre><xs:element name="requestedBy" type="shortUserType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The person who made the request</xs:documentation> <xs:documentation xml:lang="en">May be an eligible Data Sponsor or Data Manager, a System Administrator, or a technical service account</xs:documentation> </xs:annotation> </xs:element></pre>				


Element provenanceSubfields / requestDateTime

Namespace	No namespace		
Annotations	The date and time the request was made Include the time zone at the location of the host institution Princeton University is in the Eastern Time Zone (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)		
Diagram	The diagram illustrates the <code>requestDateTime</code> element. It is a simple type derived from the built-in primitive type <code>xs:dateTime</code>. Annotations describe the required time zone information and the specific location (Princeton University) for which the time is recorded.		
Type	xs:dateTime		
Properties	content:	simple	
	minOccurs:	1	
	maxOccurs:	1	
Source	<pre><xs:element name="requestDateTime" type="xs:dateTime" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The date and time the request was made</xs:documentation> <xs:documentation xml:lang="en">Include the time zone at the location of the host institution</xs:documentation> </xs:annotation> <xs:documentation xml:lang="en">Princeton University is in the Eastern Time Zone (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)</xs:documentation> </xs:element></pre>		

Element provenanceSubfields / approvedBy

Namespace	No namespace				
Annotations	The person who approved the request				
	Should be a System Administrator				

Diagram



Type	shortUserType				
Properties	content:	complex			
	minOccurs:	0			
	maxOccurs:	1			
Model	netID {0,1} , PUID {0,1} , orcid {0,1}				
Children	PUID, netID, orcid				
Instance	<pre><approvedBy userID="" userIDType="NetID"> <netID>{0,1}</netID> <PUID>{0,1}</PUID> <orcid>{0,1}</orcid> </approvedBy></pre>				
Attributes	QName	Type	Fixed	Use	
	userID	netIDType		required	
		Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID			
	userIDType	xs:string	NetID	optional	
		Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute			
Source	<pre><xs:element name="approvedBy" type="shortUserType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The person who approved the request</xs:documentation> <xs:documentation xml:lang="en">Should be a System Administrator</xs:documentation> </xs:annotation> </xs:element></pre>				

Element provenanceSubfields / approvalDateTime

Namespace	No namespace
Annotations	The date and time the request was approved

	Include the time zone at the location of the host institution Princeton University is in the Eastern Time Zone (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)						
Diagram							
Type	xs:dateTime						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						
Source	<pre><xs:element name="approvalDateTime" type="xs:dateTime" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The date and time the request was approved</xs:documentation> <xs:documentation xml:lang="en">Include the time zone at the location of the host institution</xs:documentation> <xs:documentation xml:lang="en">Princeton University is in the Eastern Time Zone (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)</xs:documentation> </xs:annotation> </xs:element></pre>						

Element provenanceSubfields / deniedBy

Namespace	No namespace
Annotations	The person who denied the request Should be a System Administrator
Diagram	
Type	shortUserType

Properties	content:	complex			
	minOccurs:	0			
	maxOccurs:	1			
Model	netID{0,1} , PUID{0,1} , orcid{0,1}				
Children	PUID, netID, orcid				
Instance	<pre><deniedBy userID="" userIDType="NetID"> <netID>{0,1}</netID> <PUID>{0,1}</PUID> <orcid>{0,1}</orcid> </deniedBy></pre>				
Attributes	QName	Type	Fixed	Use	
	userID	netIDType		required	
		Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID			
	userIDType	xs:string	NetID	optional	
		Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute			
Source	<pre><xs:element name="deniedBy" type="shortUserType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The person who denied the request</xs:documentation> <xs:documentation xml:lang="en">Should be a System Administrator</xs:documentation> </xs:annotation> </xs:element></pre>				


Element provenanceSubfields / denialDateTime

Namespace	No namespace						
Annotations	The date and time the request was denied Include the time zone at the location of the host institution Princeton University is in the Eastern Time Zone (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)						
Diagram	The diagram illustrates the relationship between the <code>denialDateTime</code> element and the <code>xs:dateTime</code> type. The <code>denialDateTime</code> element is shown with a blue border and a white background. It has a 'Type' attribute set to 'xs:dateTime'. A callout box points to the element, stating: 'The date and time the request was denied. Include the time zone at the location of the host institution. Princeton...'. Another callout box points to the <code>xs:dateTime</code> type, stating: 'Built-in primitive type. The dateTime datatype represents a specific instant of time.'						
Type	xs:dateTime						
Properties	<table><tr><td>content:</td><td>simple</td></tr><tr><td>minOccurs:</td><td>0</td></tr><tr><td>maxOccurs:</td><td>1</td></tr></table>	content:	simple	minOccurs:	0	maxOccurs:	1
content:	simple						
minOccurs:	0						
maxOccurs:	1						
Source	<pre><xs:element name="denialDateTime" type="xs:dateTime" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The date and time the request was denied</xs:documentation> <xs:documentation xml:lang="en">Include the time zone at the location of the host institution</xs:documentation> <xs:documentation xml:lang="en">Princeton University is in the Eastern Time Zone (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)</xs:documentation> </xs:annotation> </xs:element></pre>						

Element provenanceSubfields / eventNote

Namespace	No namespace				
Annotations	A supplementary record of noteworthy details for a given provenance event Intended to be retained in a running log of all noteworthy events				

Diagram



Properties

content:	complex
minOccurs:	0
maxOccurs:	5

Model

noteBy , noteDateTime , eventType , message

Children

eventType, message, noteBy, noteDateTime

Instance

```

<eventNote>
  <noteBy userID="" userIDType="NetID">{1,1}</noteBy>
  <noteDateTime>{1,1}</noteDateTime>
  <eventType>{1,1}</eventType>
  <message xml:lang="en">{1,1}</message>
</eventNote>
  
```

Source

```

<xs:element name="eventNote" minOccurs="0" maxOccurs="5">
  <xs:annotation>
    <xs:documentation xml:lang="en">A supplementary record of noteworthy details for a given
    provenance event</xs:documentation>
    <xs:documentation xml:lang="en">Intended to be retained in a running log of all noteworthy
    events</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="noteBy" type="shortUserType" minOccurs="1" maxOccurs="1">
        <xs:annotation>
          <xs:documentation xml:lang="en">The person making the note</xs:documentation>
          <xs:documentation xml:lang="en">Should be a System Administrator</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="noteDateTime" type="xs:dateTime" minOccurs="1" maxOccurs="1">
        <xs:annotation>
          <xs:documentation xml:lang="en">The date and time the note was made</xs:documentation>
          <xs:documentation xml:lang="en">Include the time zone at the location of the host
          institution</xs:documentation>
          <xs:documentation xml:lang="en">Princeton University is in the Eastern Time Zone
          (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="eventType" minOccurs="1" maxOccurs="1">
        <xs:annotation>
          <xs:documentation xml:lang="en">A general category label for the event note</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="message" type="textType" minOccurs="1" maxOccurs="1">
        <xs:annotation>
          <xs:documentation xml:lang="en">The plain-language message contents of the event note</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
  
```

```


        <xs:enumeration value="Quota" xml:lang="en">
          <xs:annotation>
            <xs:documentation xml:lang="en">Event note pertains to the project's quota settings
in Mediaflux</xs:documentation>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Tier" xml:lang="en">
          <xs:annotation>
            <xs:documentation xml:lang="en">Event note pertains to the project's storage tier</
xs:documentation>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Sponsor" xml:lang="en">
          <xs:annotation>
            <xs:documentation xml:lang="en">Event note records any changes to the project's Data
Sponsor</xs:documentation>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Revision" xml:lang="en">
          <xs:annotation>
            <xs:documentation xml:lang="en">Event note explains the return of the project
request to the submitter for revision</xs:documentation>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Denial" xml:lang="en">
          <xs:annotation>
            <xs:documentation xml:lang="en">Event note explains the denial of the project
request</xs:documentation>
          </xs:annotation>
        </xs:enumeration>
        <xs:enumeration value="Other" xml:lang="en">
          <xs:annotation>
            <xs:documentation xml:lang="en">The event note is not otherwise classified</
xs:documentation>
          </xs:annotation>
        </xs:enumeration>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
  <xs:element name="message" type="textType" minOccurs="1" maxOccurs="1">
    <xs:annotation>
      <xs:documentation xml:lang="en">The plain-language message contents of the event note</
xs:documentation>
    </xs:annotation>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

Element provenanceSubfields / eventNote / noteBy

Namespace	No namespace
Annotations	The person making the note Should be a System Administrator

Diagram



Type	shortUserType				
Properties	content:	complex			
	minOccurs:	1			
	maxOccurs:	1			
Model	netID{0,1} , PUID{0,1} , orcid{0,1}				
Children	PUID, netID, orcid				
Instance	<pre><noteBy userID="" userIDType="NetID"> <netID>{0,1}</netID> <PUID>{0,1}</PUID> <orcid>{0,1}</orcid> </noteBy></pre>				
Attributes	QName	Type	Fixed	Use	
	userID	netIDType		required	
		Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID			
	userIDType	xs:string	NetID	optional	
		Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute			
Source	<pre><xs:element name="noteBy" type="shortUserType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The person making the note</xs:documentation> <xs:documentation xml:lang="en">Should be a System Administrator</xs:documentation> </xs:annotation> </xs:element></pre>				

Element provenanceSubfields / eventNote / noteDateTime

Namespace	No namespace
Annotations	The date and time the note was made

	Include the time zone at the location of the host institution Princeton University is in the Eastern Time Zone (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)						
Diagram							
Type	xs:dateTime						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>minOccurs:</td><td>1</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	1	maxOccurs:	1
content:	simple						
minOccurs:	1						
maxOccurs:	1						
Source	<pre><xs:element name="noteDateTime" type="xs:dateTime" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The date and time the note was made</xs:documentation> <xs:documentation xml:lang="en">Include the time zone at the location of the host institution</xs:documentation> </xs:annotation> <xs:documentation xml:lang="en">Princeton University is in the Eastern Time Zone (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)</xs:documentation> </xs:element></pre>						

Element provenanceSubfields / eventNote / eventType

Namespace	No namespace		
Annotations	A general category label for the event note		
Diagram			
Type	restriction of xs:string		
Properties	content:	simple	
	minOccurs:	1	
	maxOccurs:	1	
Facets	enumeration	Collection	Event note records the assignment of or change to the project's Mediaflux collection ID
	enumeration	Directory	Event note pertains to the project's directory or mount point
	enumeration	Quota	Event note pertains to the project's quota settings in Mediaflux
	enumeration	Tier	Event note pertains to the project's storage tier
	enumeration	Sponsor	Event note records any changes to the project's Data Sponsor
	enumeration	Revision	Event note explains the return of the project request to the submitter for revision
	enumeration	Denial	Event note explains the denial of the project request
	enumeration	Other	The event note is not otherwise classified
Source	<pre><xs:element name="eventType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">A general category label for the event note</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Collection" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Event note records the assignment of or change to the project's Mediaflux collection ID</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Directory" xml:lang="en"></pre>		

```

<xs:annotation>
  <xs:documentation xml:lang="en">Event note pertains to the project's directory or mount
point</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="Quota" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Event note pertains to the project's quota settings in
Mediaflux</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Tier" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Event note pertains to the project's storage tier</
xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Sponsor" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Event note records any changes to the project's Data
Sponsor</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Revision" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Event note explains the return of the project request to
the submitter for revision</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Denial" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Event note explains the denial of the project request</
xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Other" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">The event note is not otherwise classified</
xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>

```

Element provenanceSubfields / eventNote / message

Namespace	No namespace				
Annotations	The plain-language message contents of the event note				
Diagram	The diagram illustrates the structure of the 'message' element. It is a 'message' of type 'textType'. 'textType' is a 'Base Type' that inherits from 'textLimitType'. 'textLimitType' has a note: 'Specification for the practical limit for text values within textType'. The 'Attributes' section shows 'xml:lang' with a 'Default' value of 'en'. A note explains: '<div> <h3>lang (as an attribute name)</h3> <p> denotes an attribute whose value is a language code for the natural...'. A footer note states: 'Standard type used for generic text values'.				
Type	textType				
Type hierarchy	- xs:string - textLimitType - textType				
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	1
content:	complex				
minOccurs:	1				

	maxOccurs:		1		
Attributes	QName	Type	Default	Use	
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
		<div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p> </div>			
Source	<xs:element name="message" type="textType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The plain-language message contents of the event note</ xs:documentation> </xs:annotation> </xs:element>				

Element projectDescription / researchDomains

Namespace	No namespace						
Annotations	The container element for all research domains for a project If projectPurpose is Research, then at least one researchDomain element should be given If this element is present, then it should contain at least one sub-element No duplicate domains; no more than 4 total						
Diagram	The diagram illustrates the structure of the researchDomains element. It is a container element for all research domains for a project. It has two attributes: discoverable (Type: xs:boolean, Fixed: true) and trackingLevel (Type: trackingLevelType, Fixed: ResourceRecord). The researchDomains element contains a sequence of researchDomain elements (Type: Extension of 'researchDomainNameType') with a cardinality of 1..4. A note indicates that the general field(s) of academic research related to the project are limited to the 4 domains.						
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	researchDomain{1,4}						
Children	researchDomain						
Instance	<pre><researchDomains discoverable="true" trackingLevel="ResourceRecord"> <researchDomain inherited="true">{1,4}</researchDomain> </researchDomains></pre>						

Attributes	QName	Type	Fixed	Use		
	discoverable	xs:boolean	true	optional		
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	trackingLevel	trackingLevelType	ResourceRecord	optional		
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="researchDomains" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all research domains for a project</ xs:documentation> <xs:documentation xml:lang="en">If projectPurpose is Research, then at least one researchDomain element should be given</xs:documentation> <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation> <xs:documentation xml:lang="en">No duplicate domains; no more than 4 total</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="researchDomain" minOccurs="1" maxOccurs="4"> <xs:annotation> <xs:documentation xml:lang="en">The general field(s) of academic research related to the project, if applicable</xs:documentation> <xs:documentation xml:lang="en">Options are limited to the 4 domains Princeton University uses to categorize departments</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="researchDomainNameType"> <xs:attribute ref="inherited" fixed="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </xs:sequence> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:complexType> </xs:element></pre>					

Element projectDescription / researchDomains / researchDomain

Namespace	No namespace				
Annotations	The general field(s) of academic research related to the project, if applicable Options are limited to the 4 domains Princeton University uses to categorize departments				
Diagram					
Type	extension of researchDomainNameType				
Type hierarchy	- xs:string - researchDomainNameType				
Properties	content:	complex			
	minOccurs:	1			
	maxOccurs:	4			
Attributes	QName	Type	Fixed	Use	
	inherited	xs:boolean	true	optional	

	QName	Type	Fixed	Use	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
Source	<pre><xs:element name="researchDomain" minOccurs="1" maxOccurs="4"> <xs:annotation> <xs:documentation xml:lang="en">The general field(s) of academic research related to the project, if applicable</xs:documentation> <xs:documentation xml:lang="en">Options are limited to the 4 domains Princeton University uses to categorize departments</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="researchDomainNameType"> <xs:attribute ref="inherited" fixed="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>				

Element projectDescription / departments

Namespace	No namespace				
Annotations	The container element for all departments for a project				
Diagram	The diagram illustrates the structure of the <code>departments</code> element. It is a container element for all departments for a project. It has two attributes: <code>discoverable</code> (Type: <code>xs:boolean</code>, Fixed: <code>true</code>) and <code>trackingLevel</code> (Type: <code>trackingLevelType</code>, Fixed: <code>ResourceRecord</code>). The <code>departments</code> element contains a sequence of <code>department</code> elements (1..10). The <code>department</code> element is an extension of <code>departmentType</code>.				
Properties	content:	complex			
	minOccurs:	1			
	maxOccurs:	1			
Model	<code>department{1,10}</code>				
Children	<code>department</code>				
Instance	<pre><departments discoverable="true" trackingLevel="ResourceRecord"> <department departmentCode="" inherited="true">{1,10}</department> </departments></pre>				
Attributes	QName	Type	Fixed	Use	
	<code>discoverable</code>	<code>xs:boolean</code>	<code>true</code>	optional	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	<code>trackingLevel</code>	<code>trackingLevelType</code>	<code>ResourceRecord</code>	optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="departments" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all departments for a project</ </xs:annotation> <xs:documentation> </xs:documentation> </xs:element></pre>				

```

<xs:complexType>
  <xs:sequence>
    <xs:element name="department" minOccurs="1" maxOccurs="10">
      <xs:annotation>
        <xs:documentation xml:lang="en">The primary Princeton University department(s) affiliated
with the project</xs:documentation>
        <xs:documentation xml:lang="en">Use the canonical name for each recorded department</
xs:documentation>
        <xs:documentation xml:lang="en">Princeton department names typically start with a 2- or 3-
character abbreviation, followed by a minus-dash, and then a short description</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="departmentType">
            <xs:attribute name="departmentCode" type="departmentCodeType" use="required">
              <xs:annotation>
                <xs:documentation xml:lang="en">Records the numerical code for the department
(required)</xs:documentation>
              </xs:annotation>
            </xs:attribute>
            <xs:attribute ref="inherited" default="true"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute ref="discoverable" fixed="true"/>
  <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/>
</xs:complexType>
</xs:element>

```

Element projectDescription / departments / department


Namespace	No namespace				
Annotations	The primary Princeton University department(s) affiliated with the project Use the canonical name for each recorded department Princeton department names typically start with a 2- or 3-character abbreviation, followed by a minus-dash, and then a short description				
Diagram					
Type	extension of departmentType				
Type hierarchy	- xs:string - departmentType				
Properties	content:	complex			
	minOccurs:	1			
	maxOccurs:	10			
Attributes	QName	Type	Default	Use	
	departmentCode	departmentCodeType		required	
		Records the numerical code for the department (required)			
	inherited	xs:boolean	true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources			

	QName	Type	Default	Use
		Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)		
Source	<pre><xs:element name="department" minOccurs="1" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">The primary Princeton University department(s) affiliated with the project</xs:documentation> <xs:documentation xml:lang="en">Use the canonical name for each recorded department</ xs:documentation> <xs:documentation xml:lang="en">Princeton department names typically start with a 2- or 3- character abbreviation, followed by a minus-dash, and then a short description</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="departmentType"> <xs:attribute name="departmentCode" type="departmentCodeType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Records the numerical code for the department (required)</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute ref="inherited" default="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>			

Element projectDescription / projectDirectory

Namespace	No namespace
Annotations	The locally unique name for the project's directory The typical value is expected to be in NFS protocol A parent folder is recommended to organize projects by groups (e.g., lab or principal investigator) If no user request was received and no value has yet been approved, then this field may be empty

Diagram



Properties	content: complex					
	minOccurs:	1				
	maxOccurs:	1				
Model	projectDirectoryPath{0,10} , requestedValue{0,1} , approvedValue{0,1}					
Children	approvedValue, projectDirectoryPath, requestedValue					
Instance	<pre><projectDirectory approved="false" discoverable="false" inherited="false" trackingLevel="InternalUseOnly"> <projectDirectoryPath protocol="NFS">{0,10}</projectDirectoryPath> <requestedValue protocol="NFS">{0,1}</requestedValue> <approvedValue protocol="NFS">{0,1}</approvedValue> </projectDirectory></pre>					
Attributes	QName	Type	Fixed	Default	Use	
	approved	xs:boolean		false	optional	
		Standard attribute to specify whether a given field has an approved value Applies to fields which have a request-approval framework, including projectDirectory, storageCapacity, and storagePerformance				
	discoverable	xs:boolean	false		optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean	false		optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources				

	QName	Type	Fixed	Default	Use	
		Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	trackingLevel	trackingLevelType	InternalUseOnly		optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="projectDirectory" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The locally unique name for the project's directory</ </xs:documentation> <xs:documentation xml:lang="en">The typical value is expected to be in NFS protocol</ </xs:documentation> <xs:documentation xml:lang="en">A parent folder is recommended to organize projects by groups (e.g., lab or principal investigator)</xs:documentation> <xs:documentation xml:lang="en">If no user request was received and no value has yet been approved, then this field may be empty</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="projectDirectoryPath" type="pathType" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">A current setting for projectDirectory (omitted until approved)</xs:documentation> <xs:documentation xml:lang="en">After approval, this value should be updated to match the approved value (in rare cases, the current setting may later deviate from the approved value)</ </xs:documentation> <xs:documentation xml:lang="en">Multiple elements are allowed to specify paths in alternative protocols, using the protocol attribute</xs:documentation> <xs:documentation xml:lang="en">Example NFS path: /tigerdata/parent-folder/project- folder</xs:documentation> <xs:documentation xml:lang="en">Example SMB path: \\tigerdata-smb\parent-folder\project- folder</xs:documentation> <xs:documentation xml:lang="en">Example S3 path: S3://princeton/tigerdata/parent-folder/ project-folder</xs:documentation> </xs:annotation> </xs:element> <xs:element name="requestedValue" type="pathType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for projectDirectory (omitted if no user request was received)</xs:documentation> </xs:annotation> </xs:element> <xs:element name="approvedValue" type="pathType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for projectDirectory (omitted if no sys admin has approved yet)</xs:documentation> <xs:documentation xml:lang="en">Once approved, the approved attribute should also be set to true</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> <xs:attribute ref="approved" default="false"/> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element></pre>					

Element projectDescription / projectDirectory / projectDirectoryPath

Namespace	No namespace
Annotations	A current setting for projectDirectory (omitted until approved) After approval, this value should be updated to match the approved value (in rare cases, the current setting may later deviate from the approved value) Multiple elements are allowed to specify paths in alternative protocols, using the protocol attribute Example NFS path: /tigerdata/parent-folder/project-folder Example SMB path: \\tigerdata-smb\parent-folder\project-folder Example S3 path: S3://princeton/tigerdata/parent-folder/project-folder

Diagram	projectDirectoryPath Type pathType A current setting for projectDirectory (omitted until approved) After approval, this value should be updated to match... pathType Base Type pathSafeType pathSafeType Standard type used within pathType to prevent invalid entries Restricts to alphanumeric characters, underscore, forward... Attributes protocol Type protocolType Default NFS The storage connection protocol that defines how the path is written Standard type used for file path values															
Type	pathType															
Type hierarchy	- xs:string - pathSafeType - pathType															
Properties	<table><tr><td>content:</td><td>complex</td></tr><tr><td>minOccurs:</td><td>0</td></tr><tr><td>maxOccurs:</td><td>10</td></tr></table>	content:	complex	minOccurs:	0	maxOccurs:	10									
content:	complex															
minOccurs:	0															
maxOccurs:	10															
Attributes	<table><tr><th>QName</th><th>Type</th><th>Default</th><th>Use</th><th></th></tr><tr><td>protocol</td><td>protocolType</td><td>NFS</td><td>optional</td><td></td></tr><tr><td colspan="5">The storage connection protocol that defines how the path is written</td></tr></table>	QName	Type	Default	Use		protocol	protocolType	NFS	optional		The storage connection protocol that defines how the path is written				
QName	Type	Default	Use													
protocol	protocolType	NFS	optional													
The storage connection protocol that defines how the path is written																
Source	<pre><xs:element name="projectDirectoryPath" type="pathType" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">A current setting for projectDirectory (omitted until approved)</xs:documentation> <xs:documentation xml:lang="en">After approval, this value should be updated to match the approved value (in rare cases, the current setting may later deviate from the approved value)</ xs:documentation> <xs:documentation xml:lang="en">Multiple elements are allowed to specify paths in alternative protocols, using the protocol attribute</xs:documentation> <xs:documentation xml:lang="en">Example NFS path: /tigerdata/parent-folder/project-folder</ xs:documentation> <xs:documentation xml:lang="en">Example SMB path: \\tigerdata-smb\parent-folder\project-folder</ xs:documentation> <xs:documentation xml:lang="en">Example S3 path: S3://princeton/tigerdata/parent-folder/project- folder</xs:documentation> </xs:annotation> </xs:element></pre>															

Element projectDescription / projectDirectory / requestedValue

Namespace	No namespace
Annotations	The requested value for projectDirectory (omitted if no user request was received)

Diagram	The diagram illustrates the structure of the <code>pathType</code> complex type. It is a base type that includes a <code>pathSafeType</code> attribute. The <code>pathSafeType</code> is a standard type used within <code>pathType</code> to prevent invalid entries, restricting to alphanumeric characters, underscore, forward slash, and backslash. The <code>pathType</code> also has an attribute <code>protocol</code> of type <code>protocolType</code>, with a default value of <code>NFS</code>. The <code>protocolType</code> is a standard type used for file path values, defining how the path is written. A note for the <code>requestedValue</code> attribute states: 'The requested value for projectDirectory (omitted if no user request was received)'.															
Type	pathType															
Type hierarchy	- xs:string - pathSafeType - pathType															
Properties	<table><tr><td>content:</td><td>complex</td></tr><tr><td>minOccurs:</td><td>0</td></tr><tr><td>maxOccurs:</td><td>1</td></tr></table>	content:	complex	minOccurs:	0	maxOccurs:	1									
content:	complex															
minOccurs:	0															
maxOccurs:	1															
Attributes	<table><tr><th>QName</th><th>Type</th><th>Default</th><th>Use</th><th></th></tr><tr><td>protocol</td><td>protocolType</td><td>NFS</td><td>optional</td><td></td></tr><tr><td colspan="5">The storage connection protocol that defines how the path is written</td></tr></table>	QName	Type	Default	Use		protocol	protocolType	NFS	optional		The storage connection protocol that defines how the path is written				
QName	Type	Default	Use													
protocol	protocolType	NFS	optional													
The storage connection protocol that defines how the path is written																
Source	<pre><xs:element name="requestedValue" type="pathType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for projectDirectory (omitted if no user request was received)</xs:documentation> </xs:annotation> </xs:element></pre>															

Element projectDescription / projectDirectory / approvedValue

Namespace	No namespace				
Annotations	The approved value for projectDirectory (omitted if no sys admin has approved yet) Once approved, the approved attribute should also be set to true				
Diagram					
Type	pathType				
Type hierarchy	- xs:string - pathSafeType - pathType				

Properties	content:	complex			
	minOccurs:	0			
	maxOccurs:	1			
Attributes	QName	Type	Default	Use	
	protocol	protocolType	NFS	optional	
	The storage connection protocol that defines how the path is written				
Source	<pre><xs:element name="approvedValue" type="pathType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for projectDirectory (omitted if no sys admin has approved yet)</xs:documentation> <xs:documentation xml:lang="en">Once approved, the approved attribute should also be set to true</xs:documentation> </xs:annotation> </xs:element></pre>				

Element storageAndAccess / storageCapacity

Namespace	No namespace
Annotations	The amount of storage allotted for the project (using logical byte units, base-10) If no user request was received and no value has yet been approved, then this field may be empty
Diagram	storageCapacity The amount of storage allotted for the project (using logical byte units, base-10) If no user request was received and... Attributes approved - Type: xs:boolean - Default: false - Standard attribute to specify whether a given field has an approved value - Applies to fields which have a... inherited - Type: xs:boolean - Fixed: false - Standard attribute to specify whether a given field's value should be inherited by any child resources - Inheritance is... discoverable - Type: xs:boolean - Fixed: false - Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems trackingLevel - Type: trackingLevelType - Fixed: InternalUseOnly - Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly) storageCapacitySetting - Type: storageQuantityType - The current setting for storageCapacity (omitted until approved) - After the implementation of the approval, this value... requestedValue - Type: storageQuantityType - The requested value for storageCapacity (omitted if no user request was received) - This field gets updated when a Data... approvedValue - Type: storageQuantityType - The approved value for storageCapacity (omitted if no sys admin has approved yet) - Once approved for initial project...
Properties	content: complex

	minOccurs: 1					
	maxOccurs: 1					
Model	storageCapacitySetting{0,1} , requestedValue{0,1} , approvedValue{0,1}					
Children	approvedValue, requestedValue, storageCapacitySetting					
Instance	<storageCapacity approved="false" discoverable="false" inherited="false" trackingLevel="InternalUseOnly"> <storageCapacitySetting>{0,1}</storageCapacitySetting> <requestedValue>{0,1}</requestedValue> <approvedValue>{0,1}</approvedValue> </storageCapacity>					
Attributes	QName	Type	Fixed	Default	Use	
	approved	xs:boolean		false	optional	
		Standard attribute to specify whether a given field has an approved value Applies to fields which have a request-approval framework, including projectDirectory, storageCapacity, and storagePerformance				
	discoverable	xs:boolean	false		optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean	false		optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	trackingLevel	trackingLevelType	InternalUseOnly		optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)					
Source	<xs:element name="storageCapacity" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The amount of storage allotted for the project (using logical byte units, base-10)</xs:documentation> <xs:documentation xml:lang="en">If no user request was received and no value has yet been approved, then this field may be empty</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="storageCapacitySetting" type="storageQuantityType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for storageCapacity (omitted until approved)</xs:documentation> <xs:documentation xml:lang="en">After the implementation of the approval, this value should be updated to match the approvedValue</xs:documentation> </xs:annotation> </xs:element> <xs:element name="requestedValue" type="storageQuantityType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for storageCapacity (omitted if no user request was received)</xs:documentation> <xs:documentation xml:lang="en">This field gets updated when a Data Sponsor or Data Manager requests a change in storage capacity on an active project</xs:documentation> <xs:documentation xml:lang="en">Depending on the amount requested, a System Administrator may ask the Data Sponsor for more justification for the request</xs:documentation> </xs:annotation> </xs:element> <xs:element name="approvedValue" type="storageQuantityType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for storageCapacity (omitted if no sys admin has approved yet)</xs:documentation> <xs:documentation xml:lang="en">Once approved for initial project setup, the approved attribute should also be set to true</xs:documentation> <xs:documentation xml:lang="en">If the Data Sponsor or Data Manager requests a change in storage capacity, then the approval of the new amount will change the approvedValue</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> <xs:attribute ref="approved" default="false"/> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType>					

</xs:element>

Element storageAndAccess / storageCapacity / storageCapacitySetting

Namespace	No namespace						
Annotations	The current setting for storageCapacity (omitted until approved) After the implementation of the approval, this value should be updated to match the approvedValue						
Diagram							
Type	storageQuantityType						
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	size , unit						
Children	size, unit						
Instance	<pre><storageCapacitySetting> <size>{1,1}</size> <unit>{1,1}</unit> </storageCapacitySetting></pre>						
Source	<pre><xs:element name="storageCapacitySetting" type="storageQuantityType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for storageCapacity (omitted until approved)</xs:documentation> <xs:documentation xml:lang="en">After the implementation of the approval, this value should be updated to match the approvedValue</xs:documentation> </xs:annotation> </xs:element></pre>						

Element storageAndAccess / storageCapacity / requestedValue

Namespace	No namespace		
Annotations	The requested value for storageCapacity (omitted if no user request was received) This field gets updated when a Data Sponsor or Data Manager requests a change in storage capacity on an active project Depending on the amount requested, a System Administrator may ask the Data Sponsor for more justification for the request		
Diagram			
Type	storageQuantityType		
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> </table>	content:	complex
content:	complex		

	minOccurs: 0 maxOccurs: 1
Model	size , unit
Children	size, unit
Instance	<pre><requestedValue> <size>{1,1}</size> <unit>{1,1}</unit> </requestedValue></pre>
Source	<pre><xs:element name="requestedValue" type="storageQuantityType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for storageCapacity (omitted if no user request was received)</xs:documentation> <xs:documentation xml:lang="en">This field gets updated when a Data Sponsor or Data Manager requests a change in storage capacity on an active project</xs:documentation> <xs:documentation xml:lang="en">Depending on the amount requested, a System Administrator may ask the Data Sponsor for more justification for the request</xs:documentation> </xs:annotation> </xs:element></pre>

Element storageAndAccess / storageCapacity / approvedValue

Namespace	No namespace
Annotations	The approved value for storageCapacity (omitted if no sys admin has approved yet) Once approved for initial project setup, the approved attribute should also be set to true If the Data Sponsor or Data Manager requests a change in storage capacity, then the approval of the new amount will change the approvedValue
Diagram	The diagram illustrates the structure of the <code>storageQuantityType</code> and its application in the <code>approvedValue</code> element. <code>storageQuantityType</code> is a complex type containing two elements: <code>size</code> (a restriction of <code>xs:double</code>) and <code>unit</code> (a <code>byteUnitType</code>). The <code>approvedValue</code> element is shown as an instance of <code>storageQuantityType</code>. Annotations provide context: <code>size</code> is the numeric size of the storage quantity, with practical limits set by Mediaflux; <code>unit</code> is the logical byte unit (base-10). A note indicates that <code>storageQuantityType</code> is the standard type used for storage quantity values.
Type	storageQuantityType
Properties	content: complex minOccurs: 0 maxOccurs: 1
Model	size , unit
Children	size, unit
Instance	<pre><approvedValue> <size>{1,1}</size> <unit>{1,1}</unit> </approvedValue></pre>
Source	<pre><xs:element name="approvedValue" type="storageQuantityType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for storageCapacity (omitted if no sys admin has approved yet)</xs:documentation> <xs:documentation xml:lang="en">Once approved for initial project setup, the approved attribute should also be set to true</xs:documentation> <xs:documentation xml:lang="en">If the Data Sponsor or Data Manager requests a change in storage capacity, then the approval of the new amount will change the approvedValue</xs:documentation> </xs:annotation> </xs:element></pre>

Element storageAndAccess / projectVisibility

Namespace	No namespace
Annotations	The level of openness to allow for the project record (Restricted by default)

Diagram	visibilityType Standard type to specify how open a resource's record should be to users Only those fields which have the attribute... projectVisibility <table><tr><td>Type</td><td>Extension of 'visibilityType'</td></tr><tr><td>Default</td><td>Restricted</td></tr></table> The level of openness to allow for the project record (Restricted by default) If securityLevel is set to 2 or higher,.... Attributes inherited <table><tr><td>Type</td><td>xs:boolean</td></tr><tr><td>Default</td><td>true</td></tr></table> Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is... discoverable <table><tr><td>Type</td><td>xs:boolean</td></tr><tr><td>Fixed</td><td>false</td></tr></table> Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems trackingLevel <table><tr><td>Type</td><td>trackingLevelType</td></tr><tr><td>Fixed</td><td>InternalUseOnly</td></tr></table> Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly) <tr><td>Type</td><td>extension of visibilityType</td></tr> <tr><td>Type hierarchy</td><td> - xs:string - visibilityType </td></tr> <tr><td>Properties</td><td><table><tr><td>content:</td><td>complex</td></tr><tr><td>minOccurs:</td><td>1</td></tr><tr><td>maxOccurs:</td><td>1</td></tr><tr><td>default:</td><td>Restricted</td></tr></table></td></tr> <tr><td>Attributes</td><td><table><tr><th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th><th></th></tr><tr><td>discoverable</td><td>xs:boolean</td><td>false</td><td></td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems</td></tr><tr><td>inherited</td><td>xs:boolean</td><td></td><td>true</td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)</td></tr><tr><td>trackingLevel</td><td>trackingLevelType</td><td>InternalUseOnly</td><td></td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)</td></tr></table></td></tr> <tr><td>Source</td><td><pre><xs:element name="projectVisibility" minOccurs="1" maxOccurs="1" default="Restricted"> <xs:annotation> <xs:documentation xml:lang="en">The level of openness to allow for the project record (Restricted by default)</xs:documentation> <xs:documentation xml:lang="en">If securityLevel is set to 2 or higher, then project visibility should be set to Restricted</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="visibilityType"> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre></td></tr>	Type	Extension of 'visibilityType'	Default	Restricted	Type	xs:boolean	Default	true	Type	xs:boolean	Fixed	false	Type	trackingLevelType	Fixed	InternalUseOnly	Type	extension of visibilityType	Type hierarchy	- xs:string - visibilityType	Properties	<table><tr><td>content:</td><td>complex</td></tr><tr><td>minOccurs:</td><td>1</td></tr><tr><td>maxOccurs:</td><td>1</td></tr><tr><td>default:</td><td>Restricted</td></tr></table>	content:	complex	minOccurs:	1	maxOccurs:	1	default:	Restricted	Attributes	<table><tr><th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th><th></th></tr><tr><td>discoverable</td><td>xs:boolean</td><td>false</td><td></td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems</td></tr><tr><td>inherited</td><td>xs:boolean</td><td></td><td>true</td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)</td></tr><tr><td>trackingLevel</td><td>trackingLevelType</td><td>InternalUseOnly</td><td></td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)</td></tr></table>	QName	Type	Fixed	Default	Use		discoverable	xs:boolean	false		optional			Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems					inherited	xs:boolean		true	optional			Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)					trackingLevel	trackingLevelType	InternalUseOnly		optional			Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)					Source	<pre><xs:element name="projectVisibility" minOccurs="1" maxOccurs="1" default="Restricted"> <xs:annotation> <xs:documentation xml:lang="en">The level of openness to allow for the project record (Restricted by default)</xs:documentation> <xs:documentation xml:lang="en">If securityLevel is set to 2 or higher, then project visibility should be set to Restricted</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="visibilityType"> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>
Type	Extension of 'visibilityType'																																																																												
Default	Restricted																																																																												
Type	xs:boolean																																																																												
Default	true																																																																												
Type	xs:boolean																																																																												
Fixed	false																																																																												
Type	trackingLevelType																																																																												
Fixed	InternalUseOnly																																																																												
Type	extension of visibilityType																																																																												
Type hierarchy	- xs:string - visibilityType																																																																												
Properties	<table><tr><td>content:</td><td>complex</td></tr><tr><td>minOccurs:</td><td>1</td></tr><tr><td>maxOccurs:</td><td>1</td></tr><tr><td>default:</td><td>Restricted</td></tr></table>	content:	complex	minOccurs:	1	maxOccurs:	1	default:	Restricted																																																																				
content:	complex																																																																												
minOccurs:	1																																																																												
maxOccurs:	1																																																																												
default:	Restricted																																																																												
Attributes	<table><tr><th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th><th></th></tr><tr><td>discoverable</td><td>xs:boolean</td><td>false</td><td></td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems</td></tr><tr><td>inherited</td><td>xs:boolean</td><td></td><td>true</td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)</td></tr><tr><td>trackingLevel</td><td>trackingLevelType</td><td>InternalUseOnly</td><td></td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)</td></tr></table>	QName	Type	Fixed	Default	Use		discoverable	xs:boolean	false		optional			Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems					inherited	xs:boolean		true	optional			Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)					trackingLevel	trackingLevelType	InternalUseOnly		optional			Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)																																						
QName	Type	Fixed	Default	Use																																																																									
discoverable	xs:boolean	false		optional																																																																									
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems																																																																												
inherited	xs:boolean		true	optional																																																																									
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)																																																																												
trackingLevel	trackingLevelType	InternalUseOnly		optional																																																																									
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)																																																																												
Source	<pre><xs:element name="projectVisibility" minOccurs="1" maxOccurs="1" default="Restricted"> <xs:annotation> <xs:documentation xml:lang="en">The level of openness to allow for the project record (Restricted by default)</xs:documentation> <xs:documentation xml:lang="en">If securityLevel is set to 2 or higher, then project visibility should be set to Restricted</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="visibilityType"> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>																																																																												

QName	Type	Fixed	Default	Use	
discoverable	xs:boolean	false		optional	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
inherited	xs:boolean		true	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
trackingLevel	trackingLevelType	InternalUseOnly		optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre> <xs:element name="storagePerformance" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The qualitative assignment for storage performance, i.e. storage tier</xs:documentation> <xs:documentation xml:lang="en">If no user request was received and no value has yet been approved, then this field may be empty</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="storagePerformanceSetting" type="storagePerformanceType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for storagePerformance (omitted until approved)</xs:documentation> <xs:documentation xml:lang="en">After the implementation of the approval, this value should be updated to match the approvedValue</xs:documentation> </xs:annotation> </xs:element> <xs:element name="requestedValue" type="storagePerformanceType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for storagePerformance (omitted if no user request was received)</xs:documentation> <xs:documentation xml:lang="en">This field gets updated when a Data Sponsor or Data Manager requests a change in storage performance on an active project</xs:documentation> <xs:documentation xml:lang="en">Depending on the level requested, a System Administrator may ask the Data Sponsor for more justification for the request</xs:documentation> </xs:annotation> </xs:element> <xs:element name="approvedValue" type="storagePerformanceType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for storagePerformance (omitted if no sys admin has approved yet)</xs:documentation> <xs:documentation xml:lang="en">Once approved, the approved attribute should also be set to true</xs:documentation> <xs:documentation xml:lang="en">If the Data Sponsor or Data Manager requests a change in storage performance, then the approval of the new level will change the approvedValue</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> <xs:attribute ref="approved" default="false"/> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element> </pre>				

Element storageAndAccess / storagePerformance / storagePerformanceSetting

Namespace	No namespace
Annotations	The current setting for storagePerformance (omitted until approved) After the implementation of the approval, this value should be updated to match the approvedValue
Diagram	<pre> classDiagram class storagePerformanceSetting { approved boolean = false inherited boolean = true discoverable boolean = false trackingLevel InternalUseOnly } class storagePerformanceType storagePerformanceSetting "1" -- "1" storagePerformanceType </pre> The current setting for storagePerformance (omitted until approved) After the implementation of the approval, this... Standard type that defines the controlled vocabulary for storage performance values
Type	storagePerformanceType

Properties	content:	simple	
	minOccurs:	0	
	maxOccurs:	1	
Facets	enumeration	Eco	The most economical storage tier available in TigerData (lowest cost and smallest carbon footprint) Appropriate for long-term/low-use data, i.e. cold storage The typical implementation is an object store system, e.g. IBM Cloud Object Storage
	enumeration	Standard	The middle storage tier for TigerData, expected as a default Appropriate for data that is accessed occasionally but infrequently edited, i.e. cool storage The typical implementation is a network attached storage system, e.g. Dell PowerScale
	enumeration	Premium	The most performant storage tier available in TigerData Reserved for actively edited data that needs to be close to high performance computing systems, i.e. warm storage The typical implementation is a cluster file system, e.g. IBM General Parallel File System A special request may be required for this tier
Source	<pre><xs:element name="storagePerformanceSetting" type="storagePerformanceType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for storagePerformance (omitted until approved)</xs:documentation> <xs:documentation xml:lang="en">After the implementation of the approval, this value should be updated to match the approvedValue</xs:documentation> </xs:annotation> </xs:element></pre>		

Element storageAndAccess / storagePerformance / requestedValue

Namespace	No namespace		
Annotations	The requested value for storagePerformance (omitted if no user request was received) This field gets updated when a Data Sponsor or Data Manager requests a change in storage performance on an active project Depending on the level requested, a System Administrator may ask the Data Sponsor for more justification for the request		
Diagram	<pre> classDiagram class requestedValue { Type storagePerformanceType } class storagePerformanceType { <<standard type>> } requestedValue --> storagePerformanceType </pre> The requested value for storagePerformance (omitted if no user request was received) This field gets updated when a... Standard type that defines the controlled vocabulary for storage performance values		
Type	storagePerformanceType		
Properties	content:	simple	
	minOccurs:	0	
	maxOccurs:	1	
Facets	enumeration	Eco	The most economical storage tier available in TigerData (lowest cost and smallest carbon footprint) Appropriate for long-term/low-use data, i.e. cold storage The typical implementation is an object store system, e.g. IBM Cloud Object Storage

	enumeration	Standard	The middle storage tier for TigerData, expected as a default Appropriate for data that is accessed occasionally but infrequently edited, i.e. cool storage The typical implementation is a network attached storage system, e.g. Dell PowerScale
	enumeration	Premium	The most performant storage tier available in TigerData Reserved for actively edited data that needs to be close to high performance computing systems, i.e. warm storage The typical implementation is a cluster file system, e.g. IBM General Parallel File System A special request may be required for this tier
Source	<pre><xs:element name="requestedValue" type="storagePerformanceType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for storagePerformance (omitted if no user request was received)</xs:documentation> <xs:documentation xml:lang="en">This field gets updated when a Data Sponsor or Data Manager requests a change in storage performance on an active project</xs:documentation> <xs:documentation xml:lang="en">Depending on the level requested, a System Administrator may ask the Data Sponsor for more justification for the request</xs:documentation> </xs:annotation> </xs:element></pre>		

Element storageAndAccess / storagePerformance / approvedValue

Namespace	No namespace		
Annotations	The approved value for storagePerformance (omitted if no sys admin has approved yet) Once approved, the approved attribute should also be set to true If the Data Sponsor or Data Manager requests a change in storage performance, then the approval of the new level will change the approvedValue		
Diagram			
Type	storagePerformanceType		
Properties	content:	simple	
	minOccurs:	0	
	maxOccurs:	1	
Facets	enumeration	Eco	The most economical storage tier available in TigerData (lowest cost and smallest carbon footprint) Appropriate for long-term/low-use data, i.e. cold storage The typical implementation is an object store system, e.g. IBM Cloud Object Storage
	enumeration	Standard	The middle storage tier for TigerData, expected as a default Appropriate for data that is accessed occasionally but infrequently edited, i.e. cool storage The typical implementation is a network attached storage system, e.g. Dell PowerScale
	enumeration	Premium	The most performant storage tier available in TigerData Reserved for actively edited data that needs to be close to high performance computing systems, i.e. warm storage

	The typical implementation is a cluster file system, e.g. IBM General Parallel File System A special request may be required for this tier
Source	<pre><xs:element name="approvedValue" type="storagePerformanceType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for storagePerformance (omitted if no sys admin has approved yet)</xs:documentation> <xs:documentation xml:lang="en">Once approved, the approved attribute should also be set to true</xs:documentation> <xs:documentation xml:lang="en">If the Data Sponsor or Data Manager requests a change in storage performance, then the approval of the new level will change the approvedValue</xs:documentation> </xs:annotation> </xs:element></pre>

Element storageAndAccess / numberOfFiles

Namespace	No namespace																																														
Annotations	The estimated number of files the project will incorporate (default is Less than 10,000)																																														
Diagram	fileEstimateType Standard type that defines the controlled vocabulary for the numberOfFiles field Attributes inherited Typexs:boolean Defaultfalse Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is... discoverable Typexs:boolean Fixedfalse Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems trackingLevel TypetrackingLevelType FixedInternalUseOnly Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly) numberOfFiles TypeExtension of 'fileEstimateType' DefaultLess than 10,000 The estimated number of files the project will incorporate (default is Less than 10,000)																																														
Type	extension of fileEstimateType																																														
Type hierarchy	- xs:string - fileEstimateType																																														
Properties	<table><tr><td>content:</td><td>complex</td></tr><tr><td>minOccurs:</td><td>1</td></tr><tr><td>maxOccurs:</td><td>1</td></tr><tr><td>default:</td><td>Less than 10,000</td></tr></table>					content:	complex	minOccurs:	1	maxOccurs:	1	default:	Less than 10,000																																		
content:	complex																																														
minOccurs:	1																																														
maxOccurs:	1																																														
default:	Less than 10,000																																														
Attributes	<table><tr><th>QName</th><th>Type</th><th>Fixed</th><th>Default</th><th>Use</th><th></th></tr><tr><td>discoverable</td><td>xs:boolean</td><td>false</td><td></td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems</td></tr><tr><td>inherited</td><td>xs:boolean</td><td></td><td>false</td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)</td></tr><tr><td>trackingLevel</td><td>trackingLevelType</td><td>InternalUseOnly</td><td></td><td>optional</td><td></td></tr><tr><td></td><td colspan="5">Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)</td></tr></table>					QName	Type	Fixed	Default	Use		discoverable	xs:boolean	false		optional			Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems					inherited	xs:boolean		false	optional			Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)					trackingLevel	trackingLevelType	InternalUseOnly		optional			Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
QName	Type	Fixed	Default	Use																																											
discoverable	xs:boolean	false		optional																																											
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems																																														
inherited	xs:boolean		false	optional																																											
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)																																														
trackingLevel	trackingLevelType	InternalUseOnly		optional																																											
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)																																														

Source	<pre> <xs:element name="numberOfFiles" minOccurs="1" maxOccurs="1" default="Less than 10,000"> <xs:annotation> <xs:documentation xml:lang="en">The estimated number of files the project will incorporate (default is Less than 10,000)</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="fileEstimateType"> <xs:attribute ref="inherited" default="false"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>
--------	--

Element storageAndAccess / securityLevel

Namespace	No namespace						
Annotations	The appropriate data security classification level for the project contents https://protectingourinfo.princeton.edu/classify If the security level is set to 2 or higher, then project visibility should be set to Restricted						
Diagram							
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	securityLevelSetting , requestedValue , approvedValue						

Children	approvedValue, requestedValue, securityLevelSetting					
Instance	<securityLevel approved="false" discoverable="false" inherited="true" trackingLevel="InternalUseOnly"> <securityLevelSetting>{1,1}</securityLevelSetting> <requestedValue>{1,1}</requestedValue> <approvedValue>{1,1}</approvedValue> </securityLevel>					
Attributes	QName	Type	Fixed	Default	Use	
	approved	xs:boolean		false	optional	
		Standard attribute to specify whether a given field has an approved value Applies to fields which have a request-approval framework, including projectDirectory, storageCapacity, and storagePerformance				
	discoverable	xs:boolean		false	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean	true		optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	trackingLevel	trackingLevelType	InternalUseOnly		optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<xs:element name="securityLevel" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The appropriate data security classification level for the project contents</xs:documentation> <xs:documentation>https://protectingourinfo.princeton.edu/classify</xs:documentation> <xs:documentation xml:lang="en">If the security level is set to 2 or higher, then project visibility should be set to Restricted</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="securityLevelSetting" type="securityLevelType" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for security level</xs:documentation> </xs:annotation> </xs:element> <xs:element name="requestedValue" type="securityLevelType" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for security level</xs:documentation> </xs:annotation> </xs:element> <xs:element name="approvedValue" type="securityLevelType" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for security level</xs:documentation> <xs:documentation xml:lang="en">If an approvedValue is given, then the approved attribute should also be set to true</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> <xs:attribute ref="approved" default="false"/> <xs:attribute ref="inherited" fixed="true"/> <xs:attribute ref="discoverable" default="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element>					

Element storageAndAccess / securityLevel / securityLevelSetting

Namespace	No namespace
Annotations	The current setting for security level
Diagram	<pre> classDiagram class securityLevelSetting { "The current setting for security level" } class securityLevelType { "Standard type that defines the controlled vocabulary for data security classification..." } securityLevelSetting -- > securityLevelType </pre>
Type	securityLevelType
Properties	content: simple

	maxOccurs:	1	
Facets	enumeration	Level 0 - Public	Intended to be freely shared or disclosed inside and outside of Princeton University
	enumeration	Level 1 - Internal	Intended to be used only by Princeton University staff, faculty or students, and not for public disclosure
	enumeration	Level 2 - Confidential	Requires careful handling and protection due to contractual, regulatory, proprietary, or privacy considerations Requires TigerData Secure
	enumeration	Level 3 - Restricted	Subject to restrictive data security regulations and/or privacy protections, e.g. HIPAA Requires TigerData Secure
Source	<pre><xs:element name="securityLevelSetting" type="securityLevelType" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for security level</xs:documentation> </xs:annotation> </xs:element></pre>		

Element storageAndAccess / securityLevel / requestedValue

Namespace	No namespace		
Annotations	The requested value for security level		
Diagram			
Type	securityLevelType		
Properties	content:	simple	
	maxOccurs:	1	
Facets	enumeration	Level 0 - Public	Intended to be freely shared or disclosed inside and outside of Princeton University
	enumeration	Level 1 - Internal	Intended to be used only by Princeton University staff, faculty or students, and not for public disclosure
	enumeration	Level 2 - Confidential	Requires careful handling and protection due to contractual, regulatory, proprietary, or privacy considerations Requires TigerData Secure
	enumeration	Level 3 - Restricted	Subject to restrictive data security regulations and/or privacy protections, e.g. HIPAA Requires TigerData Secure
Source	<pre><xs:element name="requestedValue" type="securityLevelType" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for security level</xs:documentation> </xs:annotation> </xs:element></pre>		

Element storageAndAccess / securityLevel / approvedValue

Namespace	No namespace		
Annotations	The approved value for security level		
	If an approvedValue is given, then the approved attribute should also be set to true		
Diagram			
Type	securityLevelType		
Properties	content:	simple	

	maxOccurs:	1	
Facets	enumeration	Level 0 - Public	Intended to be freely shared or disclosed inside and outside of Princeton University
	enumeration	Level 1 - Internal	Intended to be used only by Princeton University staff, faculty or students, and not for public disclosure
	enumeration	Level 2 - Confidential	Requires careful handling and protection due to contractual, regulatory, proprietary, or privacy considerations Requires TigerData Secure
	enumeration	Level 3 - Restricted	Subject to restrictive data security regulations and/or privacy protections, e.g. HIPAA Requires TigerData Secure
Source	<pre><xs:element name="approvedValue" type="securityLevelType" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for security level</xs:documentation> <xs:documentation xml:lang="en">If an approvedValue is given, then the approved attribute should also be set to true</xs:documentation> </xs:annotation> </xs:element></pre>		

Element storageAndAccess / storageSystem


Namespace	No namespace				
Annotations	The name of the storage system to which the path applies Used to differentiate standard TigerData projects (in-band) from out-of-band systems (e.g., '/' projects' or 'Della /scratch/gpfs')				
Diagram	The diagram illustrates the structure of the <code>storageSystem</code> element. It is an extension of <code>storageSystemType</code>. The diagram includes a table for <code>storageSystem</code> with columns <code>Type</code> and <code>Default</code>, showing it extends <code>storageSystemType</code> and has a default of <code>TigerData</code>. A callout explains that <code>storageSystem</code> is the name of the storage system to which the path applies. The main diagram shows the attributes of <code>storageSystemType</code>: <code>inherited</code> (boolean, false), <code>discoverable</code> (boolean, false), and <code>trackingLevel</code> (trackingLevelType, InternalUseOnly). Each attribute has a callout explaining its purpose.				
Type	extension of storageSystemType				
Type hierarchy	- xs:string - storageSystemType				
Properties	content:	complex			
	minOccurs:	0			
	maxOccurs:	1			
	default:	TigerData			
Attributes	QName	Type	Fixed	Default	Use
	discoverable	xs:boolean	false		optional

QName	Type	Fixed	Default	Use	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
inherited	xs:boolean		false	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
trackingLevel	trackingLevelType	InternalUseOnly		optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="storageSystem" minOccurs="0" maxOccurs="1" default="TigerData"> <xs:annotation> <xs:documentation xml:lang="en">The name of the storage system to which the path applies</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="storageSystemType"> <xs:attribute ref="inherited" default="false"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>				

Element storageAndAccess / accessPoints

Namespace	No namespace
Annotations	Records requests/approvals and settings for HPC systems, SMB shares, and Globus endpoints
	If this element is present, then it should contain all 3 sub-elements

Diagram



Properties	content:	complex			
	minOccurs:	0			
	maxOccurs:	1			
Model	hpcEnable , smbEnable , globusEnable , globusCollection{0,5}				
Children	globusCollection, globusEnable, hpcEnable, smbEnable				
Instance	<code><accessPoints discoverable="false" inherited="false" trackingLevel="InternalUseOnly"> <hpcEnable approved="false">{1,1}</hpcEnable> <smbEnable approved="false">{1,1}</smbEnable> <globusEnable approved="false">{1,1}</globusEnable> <globusCollection>{0,5}</globusCollection> </accessPoints></code>				
Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	false	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	inherited	xs:boolean	false	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
	trackingLevel	trackingLevelType	InternalUseOnly	optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)			
Source	<code><xs:element name="accessPoints" minOccurs="0" maxOccurs="1"></code>				

```

<xs:annotation>
  <xs:documentation xml:lang="en">Records requests/approvals and settings for HPC systems, SMB
  shares, and Globus endpoints</xs:documentation>
  <xs:documentation xml:lang="en">If this element is present, then it should contain all 3 sub-
  elements</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element name="hpcEnable" minOccurs="1" maxOccurs="1">
      <xs:annotation>
        <xs:documentation xml:lang="en">Whether a project is enabled for access on HPC systems
        (via NFS)</xs:documentation>
        <xs:documentation xml:lang="en">By default, projects do not get set up for access
        on HPC systems, but if both SMB and Globus are disabled, then HPC enabling may be necessary</
        xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:sequence>
          <xs:element name="hpcEnableSetting" type="xs:boolean" maxOccurs="1" default="false">
            <xs:annotation>
              <xs:documentation xml:lang="en">The current setting for hpcEnable (false by
              default)</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No">
            <xs:annotation>
              <xs:documentation xml:lang="en">The requested value for hpcEnable (No by default)</
              xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false">
            <xs:annotation>
              <xs:documentation xml:lang="en">The approved value for smbEnable (false by
              default)</xs:documentation>
              <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but
              the approved value must be true/false</xs:documentation>
              <xs:documentation xml:lang="en">If approvedValue is true, then hpcEnableSetting and
              the approved attribute should also be set to true</xs:documentation>
            </xs:annotation>
          </xs:element>
        </xs:sequence>
        <xs:attribute ref="approved" default="false"/>
      </xs:complexType>
    </xs:element>
    <xs:element name="smbEnable" minOccurs="1" maxOccurs="1">
      <xs:annotation>
        <xs:documentation xml:lang="en">Whether a project has an SMB share enabled</
        xs:documentation>
        <xs:documentation xml:lang="en">By default, projects do not get an SMB share, but if HPC
        access is disabled, then smbEnable is likely needed</xs:documentation>
        <xs:documentation xml:lang="en">If an SMB share is approved and set, then the SMB path
        should be included in projectDirectoryPath</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:sequence>
          <xs:element name="smbEnableSetting" type="xs:boolean" maxOccurs="1" default="false">
            <xs:annotation>
              <xs:documentation xml:lang="en">The current setting for smbEnable (false by
              default)</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No">
            <xs:annotation>
              <xs:documentation xml:lang="en">The requested value for smbEnable (No by default)</
              xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false">
            <xs:annotation>
              <xs:documentation xml:lang="en">The approved value for smbEnable (false by
              default)</xs:documentation>
              <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but
              the approved value must be true/false</xs:documentation>
              <xs:documentation xml:lang="en">If approvedValue is true, then smbEnableSetting and
              the approved attribute should also be set to true</xs:documentation>
            </xs:annotation>
          </xs:element>
        </xs:sequence>
        <xs:attribute ref="approved" default="false"/>
      </xs:complexType>
    </xs:element>
    <xs:element name="globusEnable" minOccurs="1" maxOccurs="1">
      <xs:annotation>

```

```

        <xs:documentation xml:lang="en">Whether a project has a Globus collection enabled</
xs:documentation>
        <xs:documentation xml:lang="en">By default, projects do not get a Globus collection</
xs:documentation>
        <xs:documentation xml:lang="en">If a Globus collection is approved and set, then the
details should be given in globusCollection</xs:documentation>
    </xs:annotation>
    <xs:complexType>
    <xs:sequence>
        <xs:element name="globusEnableSetting" type="xs:boolean" maxOccurs="1" default="false">
            <xs:annotation>
                <xs:documentation xml:lang="en">The current setting for globusEnable (false by
default)</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No">
            <xs:annotation>
                <xs:documentation xml:lang="en">The requested value for globusEnable (No by
default)</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false">
            <xs:annotation>
                <xs:documentation xml:lang="en">The approved value for globusEnable (false by
default)</xs:documentation>
                <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but
the approved value must be true/false</xs:documentation>
                <xs:documentation xml:lang="en">If approvedValue is true, then globusEnableSetting
and the approved attribute should also be set to true</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
    <xs:attribute ref="approved" default="false"/>
</xs:complexType>
</xs:element>
<xs:element name="globusCollection" minOccurs="0" maxOccurs="5">
    <xs:annotation>
        <xs:documentation xml:lang="en">Details for an enabled Globus collection for the project</
xs:documentation>
        <xs:documentation xml:lang="en">If globusEnableSetting is true, then at least one
globusCollection value set should be given</xs:documentation>
        <xs:documentation xml:lang="en">If no Globus collection is approved, then this field
should be omitted</xs:documentation>
    </xs:annotation>
    <xs:complexType>
    <xs:sequence>
        <xs:element name="globusName" type="titleLimitType" minOccurs="1" maxOccurs="1">
            <xs:annotation>
                <xs:documentation xml:lang="en">The Globus collection name (required)</
xs:documentation>
                <xs:documentation xml:lang="en">The naming convention is "Princeton TigerData -
parent-folder/project-folder"</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="globusUUID" type="uuidType" minOccurs="1" maxOccurs="1">
            <xs:annotation>
                <xs:documentation xml:lang="en">The Globus collection universally unique identifier
(required)</xs:documentation>
                <xs:documentation xml:lang="en">The value is expected to be 32 hexadecimal digits in
8-4-4-4-12 format</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="globusOwner" type="userType" minOccurs="1" maxOccurs="1">
            <xs:annotation>
                <xs:documentation xml:lang="en">The Globus collection owner, given as a TigerData
userType (required)</xs:documentation>
                <xs:documentation xml:lang="en">The owner is typically the project's Data Manager</
xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="globusURL" type="xs:anyURI" minOccurs="0" maxOccurs="1">
            <xs:annotation>
                <xs:documentation xml:lang="en">The Globus collection URL (optional)</
xs:documentation>
                <xs:documentation xml:lang="en">The expected format for a Globus collection URL is
https://app.globus.org/file-manager?origin_id=[uuid]</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
<xs:attribute ref="inherited" fixed="false"/>

```

```
<xs:attribute ref="discoverable" fixed="false"/>
<xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
</xs:complexType>
</xs:element>
```

Element storageAndAccess / accessPoints / hpcEnable

Namespace	No namespace														
Annotations	Whether a project is enabled for access on HPC systems (via NFS) By default, projects do not get set up for access on HPC systems, but if both SMB and Globus are disabled, then HPC enabling may be necessary														
Diagram	hpcEnable Whether a project is enabled for access on HPC systems (via NFS) By default, projects do not get set up for access on... Attributes approved Type: xs:boolean Default: false Standard attribute to specify whether a given field has an approved value Applies to fields which have a... hpcEnableSetting Type: xs:boolean Default: false The current setting for hpcEnable (false by default) requestedValue Type: yesNoMaybeType Default: No The requested value for hpcEnable (No by default) approvedValue Type: xs:boolean Default: false The approved value for smbEnable (false by default) The requested value takes yes/no/maybe values, but the approved...														
Properties	content:	complex													
	minOccurs:	1													
	maxOccurs:	1													
Model	hpcEnableSetting , requestedValue , approvedValue														
Children	approvedValue, hpcEnableSetting, requestedValue														
Instance	<pre><hpcEnable approved="false"> <hpcEnableSetting>{1,1}</hpcEnableSetting> <requestedValue>{1,1}</requestedValue> <approvedValue>{1,1}</approvedValue> </hpcEnable></pre>														
Attributes	<table><thead><tr><th>QName</th><th>Type</th><th>Default</th><th>Use</th><th></th></tr></thead><tbody><tr><td>approved</td><td>xs:boolean</td><td>false</td><td>optional</td><td></td></tr></tbody></table>	QName	Type	Default	Use		approved	xs:boolean	false	optional		Standard attribute to specify whether a given field has an approved value Applies to fields which have a request-approval framework, including projectDirectory, storageCapacity, and storagePerformance			
QName	Type	Default	Use												
approved	xs:boolean	false	optional												
Source	<pre><xs:element name="hpcEnable" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Whether a project is enabled for access on HPC systems (via NFS)</xs:documentation> <xs:documentation xml:lang="en">By default, projects do not get set up for access on HPC systems, but if both SMB and Globus are disabled, then HPC enabling may be necessary</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="hpcEnableSetting" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for hpcEnable (false by default)</xs:documentation> </xs:annotation> </xs:element> <xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for hpcEnable (No by default)</xs:documentation> </xs:annotation> </xs:element> <xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for smbEnable (false by default)</xs:documentation> <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but the approved...</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> <xs:attribute ref="approved" fixed="false"/> </xs:element></pre>														

```

</xs:element>
<xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No">
  <xs:annotation>
    <xs:documentation xml:lang="en">The requested value for hpcEnable (No by default)</
xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false">
  <xs:annotation>
    <xs:documentation xml:lang="en">The approved value for smbEnable (false by default)</
xs:documentation>
    <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but the
approved value must be true/false</xs:documentation>
    <xs:documentation xml:lang="en">If approvedValue is true, then hpcEnableSetting and the
approved attribute should also be set to true</xs:documentation>
  </xs:annotation>
</xs:element>
</xs:sequence>
<xs:attribute ref="approved" default="false"/>
</xs:complexType>
</xs:element>

```

Element storageAndAccess / accessPoints / hpcEnable / hpcEnableSetting

Namespace	No namespace						
Annotations	The current setting for hpcEnable (false by default)						
Diagram							
Type	xs:boolean						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> <tr> <td>default:</td><td>false</td></tr> </table>	content:	simple	maxOccurs:	1	default:	false
content:	simple						
maxOccurs:	1						
default:	false						
Source	<pre> <xs:element name="hpcEnableSetting" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for hpcEnable (false by default)</ xs:documentation> </xs:annotation> </xs:element> </pre>						

Element storageAndAccess / accessPoints / hpcEnable / requestedValue

Namespace	No namespace								
Annotations	The requested value for hpcEnable (No by default)								
Diagram	The diagram illustrates the structure of the <code>requestedValue</code> element. It consists of a table with the following content: <table border="1"><thead><tr><th colspan="2">requestedValue</th></tr></thead><tbody><tr><td>Type</td><td>yesNoMaybeType</td></tr><tr><td>Default</td><td>No</td></tr></tbody></table> Below the table, a callout box explains the <code>yesNoMaybeType</code> standard type: "Standard type that defines the controlled vocabulary for request fields that allow uncertainty".			requestedValue		Type	yesNoMaybeType	Default	No
requestedValue									
Type	yesNoMaybeType								
Default	No								
Type	yesNoMaybeType								
Properties	content:	simple							
	maxOccurs:	1							
	default:	No							
Facets	enumeration	No	The requester does not need the option (typically, the default)						
	enumeration	Yes	The requester needs the option						
	enumeration	Maybe	The requester is unsure whether they will need the option						

More conversation may be required to clarify
before approval

Source

```
<xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No">
  <xs:annotation>
    <xs:documentation xml:lang="en">The requested value for hpcEnable (No by default)</
  </xs:annotation>
</xs:element>
```


Element storageAndAccess / accessPoints / hpcEnable / approvedValue

Namespace	No namespace						
Annotations	The approved value for smbEnable (false by default) The requested value takes yes/no/maybe values, but the approved value must be true/false If approvedValue is true, then hpcEnableSetting and the approved attribute should also be set to true						
Diagram							
Type	xs:boolean						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> <tr> <td>default:</td><td>false</td></tr> </table>	content:	simple	maxOccurs:	1	default:	false
content:	simple						
maxOccurs:	1						
default:	false						
Source	<pre><xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for smbEnable (false by default)</ </xs:annotation> <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but the approved value must be true/false</xs:documentation> <xs:documentation xml:lang="en">If approvedValue is true, then hpcEnableSetting and the approved attribute should also be set to true</xs:documentation> </xs:annotation> </xs:element></pre>						

Element storageAndAccess / accessPoints / smbEnable

Namespace	No namespace
Annotations	Whether a project has an SMB share enabled By default, projects do not get an SMB share, but if HPC access is disabled, then smbEnable is likely needed If an SMB share is approved and set, then the SMB path should be included in projectDirectoryPath

Diagram



Properties	content:	complex
	minOccurs:	1
	maxOccurs:	1

Model smbEnableSetting , requestedValue , approvedValue

Children approvedValue, requestedValue, smbEnableSetting

Instance

```
<smbEnable approved="false">
  <smbEnableSetting>{1,1}</smbEnableSetting>
  <requestedValue>{1,1}</requestedValue>
  <approvedValue>{1,1}</approvedValue>
</smbEnable>
```

Attributes	QName	Type	Default	Use	
	approved	xs:boolean	false	optional	
		Standard attribute to specify whether a given field has an approved value Applies to fields which have a request-approval framework, including projectDirectory, storageCapacity, and storagePerformance			

Source

```
<xs:element name="smbEnable" minOccurs="1" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">Whether a project has an SMB share enabled</xs:documentation>
    <xs:documentation xml:lang="en">By default, projects do not get an SMB share, but if HPC access
is disabled, then smbEnable is likely needed</xs:documentation>
    <xs:documentation xml:lang="en">If an SMB share is approved and set, then the SMB path should be
included in projectDirectoryPath</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="smbEnableSetting" type="xs:boolean" maxOccurs="1" default="false">
        <xs:annotation>
          <xs:documentation xml:lang="en">The current setting for smbEnable (false by default)</
xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No">
        <xs:annotation>
          <xs:documentation xml:lang="en">The requested value for smbEnable (No by default)</
xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false">
        <xs:annotation>
          <xs:documentation xml:lang="en">The approved value for smbEnable (false by default)</
xs:documentation>
          <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but the
approved value must be true/false</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
<xs:documentation xml:lang="en">If approvedValue is true, then smbEnableSetting and the
approved attribute should also be set to true</xs:documentation>
</xs:annotation>
</xs:element>
</xs:sequence>
<xs:attribute ref="approved" default="false"/>
</xs:complexType>
</xs:element>
```

Element storageAndAccess / accessPoints / smbEnable / smbEnableSetting

Namespace	No namespace						
Annotations	The current setting for smbEnable (false by default)						
Diagram							
Type	xs:boolean						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> <tr> <td>default:</td><td>false</td></tr> </table>	content:	simple	maxOccurs:	1	default:	false
content:	simple						
maxOccurs:	1						
default:	false						
Source	<pre><xs:element name="smbEnableSetting" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for smbEnable (false by default)</ </xs:annotation> </xs:element></pre>						

Element storageAndAccess / accessPoints / smbEnable / requestedValue

Namespace	No namespace		
Annotations	The requested value for smbEnable (No by default)		
Diagram			
Type	yesNoMaybeType		
Properties	content:	simple	
	maxOccurs:	1	
	default:	No	
Facets	enumeration	No	The requester does not need the option (typically, the default) Usually, when approved, applied as a false setting
	enumeration	Yes	The requester needs the option Usually, when approved, applied as a true setting
	enumeration	Maybe	The requester is unsure whether they will need the option More conversation may be required to clarify before approval
Source	<pre><xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for smbEnable (No by default)</ </xs:annotation> </xs:element></pre>		

Element storageAndAccess / accessPoints / smbEnable / approvedValue

Namespace	No namespace
-----------	--------------

Annotations	The approved value for smbEnable (false by default) The requested value takes yes/no/maybe values, but the approved value must be true/false If approvedValue is true, then smbEnableSetting and the approved attribute should also be set to true						
Diagram							
Type	xs:boolean						
Properties	<table> <tr> <td>content:</td><td>simple</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> <tr> <td>default:</td><td>false</td></tr> </table>	content:	simple	maxOccurs:	1	default:	false
content:	simple						
maxOccurs:	1						
default:	false						
Source	<pre><xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for smbEnable (false by default)</xs:documentation> <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but the approved value must be true/false</xs:documentation> <xs:documentation xml:lang="en">If approvedValue is true, then smbEnableSetting and the approved attribute should also be set to true</xs:documentation> </xs:annotation> </xs:element></pre>						

Element storageAndAccess / accessPoints / globusEnable

Namespace	No namespace						
Annotations	Whether a project has a Globus collection enabled By default, projects do not get a Globus collection If a Globus collection is approved and set, then the details should be given in globusCollection						
Diagram							
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>1</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	1	maxOccurs:	1
content:	complex						
minOccurs:	1						
maxOccurs:	1						
Model	globusEnableSetting , requestedValue , approvedValue						

Children	approvedValue, globusEnableSetting, requestedValue				
Instance	<pre><globusEnable approved="false"> <globusEnableSetting>{1,1}</globusEnableSetting> <requestedValue>{1,1}</requestedValue> <approvedValue>{1,1}</approvedValue> </globusEnable></pre>				
Attributes	QName	Type	Default	Use	
	approved	xs:boolean	false	optional	
		Standard attribute to specify whether a given field has an approved value Applies to fields which have a request-approval framework, including projectDirectory, storageCapacity, and storagePerformance			
Source	<pre><xs:element name="globusEnable" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Whether a project has a Globus collection enabled</ </xs:documentation> <xs:documentation xml:lang="en">By default, projects do not get a Globus collection</ </xs:documentation> <xs:documentation xml:lang="en">If a Globus collection is approved and set, then the details should be given in globusCollection</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="globusEnableSetting" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for globusEnable (false by default)</ </xs:documentation> </xs:annotation> </xs:element> <xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for globusEnable (No by default)</ </xs:documentation> </xs:annotation> </xs:element> <xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for globusEnable (false by default)</ </xs:documentation> <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but the approved value must be true/false</xs:documentation> <xs:documentation xml:lang="en">If approvedValue is true, then globusEnableSetting and the approved attribute should also be set to true</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> <xs:attribute ref="approved" default="false"/> </xs:complexType> </xs:element></pre>				

Element storageAndAccess / accessPoints / globusEnable / globusEnableSetting

Namespace	No namespace		
Annotations	The current setting for globusEnable (false by default)		
Diagram	The diagram illustrates the <code>globusEnableSetting</code> element. It is a box with a title <code>globusEnableSetting</code> and two attributes: <code>Type</code> with value <code>xs:boolean</code> and <code>Default</code> with value <code>false</code>. A line connects the <code>xs:boolean</code> type to a separate box labeled <code>xs:boolean</code> with a note: "Built-in primitive type. It defines the boolean values true and false." Another note points to the <code>globusEnableSetting</code> box: "The current setting for globusEnable (false by default)".		
Type	xs:boolean		
Properties	content:	simple	
	maxOccurs:	1	
	default:	false	
Source	<pre><xs:element name="globusEnableSetting" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The current setting for globusEnable (false by default)</xs:documentation> </xs:annotation> </xs:element></pre>		

Element storageAndAccess / accessPoints / globusEnable / requestedValue

Namespace	No namespace		
Annotations	The requested value for globusEnable (No by default)		
Diagram			
Type	yesNoMaybeType		
Properties	content:	simple	
	maxOccurs:	1	
	default:	No	
Facets	enumeration	No	The requester does not need the option (typically, the default) Usually, when approved, applied as a false setting
	enumeration	Yes	The requester needs the option Usually, when approved, applied as a true setting
	enumeration	Maybe	The requester is unsure whether they will need the option More conversation may be required to clarify before approval
Source	<pre><xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No"> <xs:annotation> <xs:documentation xml:lang="en">The requested value for globusEnable (No by default)</xs:documentation> </xs:annotation> </xs:element></pre>		

Element storageAndAccess / accessPoints / globusEnable / approvedValue

Namespace	No namespace						
Annotations	The approved value for globusEnable (false by default) The requested value takes yes/no/maybe values, but the approved value must be true/false If approvedValue is true, then globusEnableSetting and the approved attribute should also be set to true						
Diagram	The approved value for globusEnable (false by default) The requested value takes yes/no/maybe values, but the approved... Built-in primitive type. It defines the boolean values true and false.						
Type	xs:boolean						
Properties	<table><tr><td>content:</td><td>simple</td></tr><tr><td>maxOccurs:</td><td>1</td></tr><tr><td>default:</td><td>false</td></tr></table>	content:	simple	maxOccurs:	1	default:	false
content:	simple						
maxOccurs:	1						
default:	false						
Source	<pre><xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false"> <xs:annotation> <xs:documentation xml:lang="en">The approved value for globusEnable (false by default)</ xs:documentation> <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values, but the approved value must be true/false</xs:documentation> <xs:documentation xml:lang="en">If approvedValue is true, then globusEnableSetting and the approved attribute should also be set to true</xs:documentation> </xs:annotation> </xs:element></pre>						

Element storageAndAccess / accessPoints / globusCollection

Namespace	No namespace						
Annotations	Details for an enabled Globus collection for the project If globusEnableSetting is true, then at least one globusCollection value set should be given If no Globus collection is approved, then this field should be omitted						
Diagram							
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>5</td></tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	5
content:	complex						
minOccurs:	0						
maxOccurs:	5						
Model	globusName , globusUUID , globusOwner , globusURL{0,1}						
Children	globusName, globusOwner, globusURL, globusUUID						
Instance	<pre> <globusCollection> <globusName>{1,1}</globusName> <globusUUID>{1,1}</globusUUID> <globusOwner userID="" userIDType="NetID">{1,1}</globusOwner> <globusURL>{0,1}</globusURL> </globusCollection> </pre>						
Source	<pre> <xs:element name="globusCollection" minOccurs="0" maxOccurs="5"> <xs:annotation> <xs:documentation xml:lang="en">Details for an enabled Globus collection for the project</xs:documentation> <xs:documentation xml:lang="en">If globusEnableSetting is true, then at least one globusCollection value set should be given</xs:documentation> <xs:documentation xml:lang="en">If no Globus collection is approved, then this field should be omitted</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="globusName" type="titleLimitType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Globus collection name (required)</xs:documentation> <xs:documentation xml:lang="en">The naming convention is "Princeton TigerData - parent-folder/project-folder"</xs:documentation> </xs:annotation> </xs:element> <xs:element name="globusUUID" type="uuidType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Globus collection universally unique identifier (required)</xs:documentation> <xs:documentation xml:lang="en">The value is expected to be 32 hexadecimal digits in 8-4-4-4-12 format</xs:documentation> </xs:annotation> </xs:element> <xs:element name="globusOwner" type="userType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Globus collection owner, given as a TigerData userType (required)</xs:documentation> </pre>						

```

<xs:documentation xml:lang="en">The owner is typically the project's Data Manager</xs:documentation>
</xs:annotation>
</xs:element>
<xs:element name="globusURL" type="xs:anyURI" minOccurs="0" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">The Globus collection URL (optional)</xs:documentation>
    <xs:documentation xml:lang="en">The expected format for a Globus collection URL is
https://app.globus.org/file-manager?origin_id=[uuid]</xs:documentation>
    </xs:annotation>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

Element storageAndAccess / accessPoints / globusCollection / globusName

Namespace	No namespace						
Annotations	The Globus collection name (required) The naming convention is "Princeton TigerData - parent-folder/project-folder"						
Diagram	<pre> graph LR globusName[Type titleLimitType] -- required --> titleLimitType[titleLimitType] titleLimitType --- note1["Specification for the practical limit for text values within titleType"] globusName --- note2["The Globus collection name (required) The naming convention is 'Princeton TigerData - parent-folder/project-folder'"] </pre>						
Type	titleLimitType						
Properties	<table> <tr><td>content:</td><td>simple</td></tr> <tr><td>minOccurs:</td><td>1</td></tr> <tr><td>maxOccurs:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	1	maxOccurs:	1
content:	simple						
minOccurs:	1						
maxOccurs:	1						
Facets	<table> <tr><td>minLength</td><td>1</td></tr> <tr><td>maxLength</td><td>200</td></tr> </table>	minLength	1	maxLength	200		
minLength	1						
maxLength	200						
Source	<pre> <xs:element name="globusName" type="titleLimitType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Globus collection name (required)</xs:documentation> <xs:documentation xml:lang="en">The naming convention is "Princeton TigerData - parent-folder/ project-folder"</xs:documentation> </xs:annotation> </xs:element> </pre>						

Element storageAndAccess / accessPoints / globusCollection / globusUUID

Namespace	No namespace						
Annotations	The Globus collection universally unique identifier (required) The value is expected to be 32 hexadecimal digits in 8-4-4-4-12 format						
Diagram	<pre> graph LR globusUUID[Type uuidType] -- required --> uuidType[uuidType] uuidType --- note1["Standard type used for values meant to be Universally Unique Identifiers (e.g., in globusUUID) Restricts to hexadecimal..."] globusUUID --- note2["The Globus collection universally unique identifier (required) The value is expected to be 32 hexadecimal digits in..."] </pre>						
Type	uuidType						
Properties	<table> <tr><td>content:</td><td>simple</td></tr> <tr><td>minOccurs:</td><td>1</td></tr> <tr><td>maxOccurs:</td><td>1</td></tr> </table>	content:	simple	minOccurs:	1	maxOccurs:	1
content:	simple						
minOccurs:	1						
maxOccurs:	1						
Facets	<table> <tr><td>pattern</td><td>[0-9a-f\-\-]{32,36}</td></tr> </table>	pattern	[0-9a-f\-\-]{32,36}				
pattern	[0-9a-f\-\-]{32,36}						
Source	<pre> <xs:element name="globusUUID" type="uuidType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Globus collection universally unique identifier (required)</xs:documentation> </xs:annotation> </xs:element> </pre>						

```
<xs:documentation xml:lang="en">The value is expected to be 32 hexadecimal digits in 8-4-4-4-12
format</xs:documentation>
</xs:annotation>
</xs:element>
```

Element storageAndAccess / accessPoints / globusCollection / globusOwner

Namespace	No namespace
Annotations	The Globus collection owner, given as a TigerData userType (required) The owner is typically the project's Data Manager
Diagram	The diagram illustrates the structure of the globusOwner element. It is a required element of type userType. The userType type is defined with the following components: Attributes: userID (Type: netIDType): Specifies the (locally) unique user ID. If a value is given for the sub-element netID, then it should match the value... userIDType (Type: xs:string): Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute. Sub-elements: netID (Type: netIDType): The Princeton University NetID (also called the OIT NetID) is the name or user-id that identifies a person to a... PUID (Type: puidType): The Princeton University ID (aka Student ID, Employee ID, EMPLID, Princeton ID, or PUID) is a unique nine digit... orcid (Type: xs:anyURI): The ORCID ID URL for the person in a given role, if available and if verified as valid against the ORCID API upon entry. fullName (Type: titleLimitType): The full name of the person in a given role, verified in the format family-comma-given and matching the corresponding... givenName (Type: titleLimitType): The given name(s) of the person in a given role. If the person has multiple given names, then all should be included in... familyName (Type: titleLimitType): The family name(s) of the person in a given role. If the person has multiple family names, then all should be included... nameDate (Type: dateOrRangeType): The date at which the name metadata was recorded. alternativeNameIdentifier (Type: Extension of 'titleLimitType'): Records alternative (non-ORCID) identifier(s) for the person in a given role. Standard type used for user fields Given the required attribute userID, all sub-elements are optional, so the element...
Type	userType

Properties	content: complex				
	minOccurs: 1				
	maxOccurs: 1				
Model	netID{0,1} , PUID{0,1} , orcid{0,1} , fullName{0,1} , givenName{0,1} , familyName{0,1} , nameDate{0,1} , alternativeNameIdentifier{0,3}				
Children	PUID, alternativeNameIdentifier, familyName, fullName, givenName, nameDate, netID, orcid				
Instance	<pre><globusOwner userID="" userIDType="NetID"> <netID>{0,1}</netID> <PUID>{0,1}</PUID> <orcid>{0,1}</orcid> <fullName>{0,1}</fullName> <givenName>{0,1}</givenName> <familyName>{0,1}</familyName> <nameDate>{0,1}</nameDate> <alternativeNameIdentifier nameIdentifierSchema="" schemaURI="">{0,3}</alternativeNameIdentifier> </globusOwner></pre>				
Attributes	QName	Type	Fixed	Use	
	userID	netIDType		required	
		Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID			
	userIDType	xs:string	NetID	optional	
		Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute			
Source	<pre><xs:element name="globusOwner" type="userType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Globus collection owner, given as a TigerData userType (required)</xs:documentation> <xs:documentation xml:lang="en">The owner is typically the project's Data Manager</ xs:documentation> </xs:annotation> </xs:element></pre>				


Element storageAndAccess / accessPoints / globusCollection / globusURL

Namespace	No namespace		
Annotations	The Globus collection URL (optional) The expected format for a Globus collection URL is https://app.globus.org/file-manager?origin_id=[uuid]		
Diagram	<pre>graph LR globusURL["globusURL Type xs:anyURI"] --- xsanyURI["xs:anyURI"] globusURL --- callout1["The Globus collection URL (optional) The expected format for a Globus collection URL is..."] xsanyURI --- callout2["Built-in primitive type. The anyURI datatype represents a Uniform Resource Identifier Reference (URI)."]</pre>		
Type	xs:anyURI		
Properties	content:	simple	
	minOccurs:	0	
	maxOccurs:	1	
Source	<pre><xs:element name="globusURL" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Globus collection URL (optional)</xs:documentation> <xs:documentation xml:lang="en">The expected format for a Globus collection URL is https://app.globus.org/file-manager?origin_id=[uuid]</xs:documentation> </xs:annotation> </xs:element></pre>		

Element additionalProjectInformation / projectPurpose

Namespace	No namespace				
Annotations	The high-level category for the purpose of the project				

Diagram



Type extension of projectPurposeType

Type hierarchy

- xs:string
- projectPurposeType

Properties

content:	complex
minOccurs:	1
maxOccurs:	1

Attributes	QName	Type	Fixed	Default	Use
	discoverable	xs:boolean	true		optional
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean		true	optional
	Standard attribute to specify whether a given field's value should be inherited by any child resources				
	Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	trackingLevel	trackingLevelType	InternalUseOnly		optional
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				

Source

```
<xs:element name="projectPurpose" minOccurs="1" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">The high-level category for the purpose of the project</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:simpleContent>
      <xs:extension base="projectPurposeType">
        <xs:attribute ref="inherited" default="true"/>
        <xs:attribute ref="discoverable" fixed="true"/>
        <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
</xs:element>
```

Element additionalProjectInformation / provisionalProject


Namespace	No namespace
Annotations	Whether the project is provisional, i.e., temporary, experimental, or intended for testing purposes only (default false)

If the value is true, then limitations may be placed on other fields, e.g. storageCapacity, storagePerformance, and endDate

If the value is false, then the project is considered standard and the provisional limitations are not imposed

Whether provisional or standard, the same fields are required for all projects

Diagram



Type extension of xs:boolean

Properties

content:	complex
minOccurs:	1
maxOccurs:	1
default:	false

Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	true	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	inherited	xs:boolean	true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources			
		Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
	trackingLevel	trackingLevelType	InternalUseOnly	optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)			

Source

```
<xs:element name="provisionalProject" minOccurs="1" maxOccurs="1" default="false">
  <xs:annotation>
    <xs:documentation xml:lang="en">Whether the project is provisional, i.e., temporary,
    experimental, or intended for testing purposes only (default false)</xs:documentation>
    <xs:documentation xml:lang="en">If the value is true, then limitations may be placed on other
    fields, e.g. storageCapacity, storagePerformance, and endDate</xs:documentation>
    <xs:documentation xml:lang="en">If the value is false, then the project is considered standard
    and the provisional limitations are not imposed</xs:documentation>
    <xs:documentation xml:lang="en">Whether provisional or standard, the same fields are required
    for all projects</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:simpleContent>
      <xs:extension base="xs:boolean">
        <xs:attribute ref="inherited" fixed="true"/>
        <xs:attribute ref="discoverable" fixed="true"/>
        <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
</xs:element>
```

```
</xs:simpleContent>
</xs:complexType>
</xs:element>
```

Element additionalProjectInformation / funded

Namespace	No namespace					
Annotations	Whether a resource is funded If the value is true, then at least one fundingReference field must be filled If any subproject or item contained in a project has a fundingReference, then this field should be set to true					
Diagram						
Type	extension of xs:boolean					
Properties	content:	complex				
	minOccurs:	0				
	maxOccurs:	1				
Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean	false		optional	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems					
	federallyFunded	xs:boolean		false	optional	
	Whether the resource is funded by the U.S. federal government (default false) If true, then at least one fundingReference must have the federalFunder attribute set to true					
	inherited	xs:boolean		true	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)					
	trackingLevel	trackingLevelType	InternalUseOnly		optional	

	QName	Type	Fixed	Default	Use	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="funded" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Whether a resource is funded</xs:documentation> <xs:documentation xml:lang="en">If the value is true, then at least one fundingReference field must be filled</xs:documentation> <xs:documentation xml:lang="en">If any subproject or item contained in a project has a fundingReference, then this field should be set to true</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:boolean"> <xs:attribute name="federallyFunded" type="xs:boolean" default="false"> <xs:annotation> <xs:documentation xml:lang="en">Whether the resource is funded by the U.S. federal government (default false)</xs:documentation> <xs:documentation xml:lang="en">If true, then at least one fundingReference must have the federalFunder attribute set to true</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>					

Element additionalProjectInformation / dataUseAgreement

Namespace	No namespace					
Annotations	Whether a data use agreement applies to the project If the value is true, then at least one duaReference field must be filled If any subproject or item contained in a project has a duaReference, then this field should be set to true					
Diagram						
Type	extension of xs:boolean					
Properties	content:	complex				
	minOccurs:	0				
	maxOccurs:	1				
Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean	false		optional	

QName	Type	Fixed	Default	Use	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
inherited	xs:boolean		true	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
trackingLevel	trackingLevelType	InternalUseOnly		optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre> <xs:element name="dataUseAgreement" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">Whether a data use agreement applies to the project</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:boolean"> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>				

Element supplementalMetadata / keywords


Namespace	No namespace						
Annotations	The container element for all keywords for a resource May apply to either Projects or Items If this element is present, then it should contain at least one sub-element						
Diagram							
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>0</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	0	maxOccurs:	1
content:	complex						
minOccurs:	0						
maxOccurs:	1						
Model	keyword{1,10}						
Children	keyword						
Instance	<pre> <keywords discoverable="true" trackingLevel="ResourceRecord"> <keyword classificationCode="" inherited="true" xml:lang="en" subjectSchema="" subjectSchemaURI="" valueURI="">{ </keyword> </pre>						

	</keywords>				
Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	true	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	trackingLevel	trackingLevelType	ResourceRecord	optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)			
Source	<pre><xs:element name="keywords" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all keywords for a resource</ </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="keyword" minOccurs="1" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">Tag for a subject heading, content type, or other keyword (given as a string)</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects and Items</xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite definitions for Subject (v4.6+)</xs:documentation> <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/ subject</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="shortTextType"> <xs:attribute name="subjectSchema" type="titleLimitType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The name of the subject schema or classification code or authority, if applicable</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="subjectSchemaURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the subject identifier schema, if applicable</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="valueURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the subject term, if applicable</ </xs:annotation> </xs:attribute> <xs:attribute name="classificationCode" type="shortAttributeType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The classification code used for the subject term in the subject schema, if applicable</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute ref="inherited" default="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </xs:sequence> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:complexType> </xs:element></pre>				

Element supplementalMetadata / keywords / keyword

Namespace	No namespace
Annotations	Tag for a subject heading, content type, or other keyword (given as a string) May apply to either Projects and Items Derived from the DataCite definitions for Subject (v4.6+) https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/subject/

Diagram



Type: extension of shortTextType

- Type hierarchy
- xs:string
 - shortTextLimitType
 - shortTextType

Properties

content:	complex
minOccurs:	1
maxOccurs:	10

Attributes	QName	Type	Default	Use	
	classificationCode	shortAttributeType		optional	
	The classification code used for the subject term in the subject schema, if applicable				
	inherited	xs:boolean	true	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	subjectSchema	titleLimitType		optional	

QName	Type	Default	Use	
	The name of the subject schema or classification code or authority, if applicable			
subjectSchemaURI	xs:anyURI		optional	
	The URI of the subject identifier schema, if applicable			
valueURI	xs:anyURI		optional	
	The URI of the subject term, if applicable			
xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
	lang (as an attribute name) denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification. Notes Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility. See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txt and the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registry for further information. The union allows for the 'un-declaration' of xml:lang with the empty string.			
Source	<pre> <xs:element name="keyword" minOccurs="1" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">Tag for a subject heading, content type, or other keyword (given as a string)</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects and Items</xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite definitions for Subject (v4.6+)</xs:documentation> <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/subject/</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="shortTextType"> <xs:attribute name="subjectSchema" type="titleLimitType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The name of the subject schema or classification code or authority, if applicable</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="subjectSchemaURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the subject identifier schema, if applicable</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="valueURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the subject term, if applicable</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="classificationCode" type="shortAttributeType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The classification code used for the subject term in the subject schema, if applicable</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute ref="inherited" default="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>			


Element supplementalMetadata / relations

Namespace	No namespace
Annotations	The container element for all relations for a resource

May apply to either Projects or Items

If this element is present, then it should contain at least one sub-element

Diagram



Properties

content:	complex
minOccurs:	0
maxOccurs:	1

Model

relation{1,100}

Children

relation

Instance

```
<relations discoverable="true" trackingLevel="ResourceRecord">
  <relation inherited="false" relatedIDType="DOI" relatedMetadataSchema="" relatedMetadataSchemaType="" relatedMetadataSchemaVersion="">
    relation
  </relation>
</relations>
```

Attributes

QName	Type	Fixed	Use	
discoverable	xs:boolean	true	optional	
Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
trackingLevel	trackingLevelType	ResourceRecord	optional	
Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				

Source

```
<xs:element name="relations" minOccurs="0" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">The container element for all relations for a resource</xs:documentation>
    <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation>
    <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="relation" minOccurs="1" maxOccurs="100">
        <xs:annotation>
          <xs:documentation xml:lang="en">Specifies a related TigerData project or item, a published paper, or any other digital object, given as a string</xs:documentation>
          <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation>
          <xs:documentation xml:lang="en">Derived from the DataCite definitions for RelatedIdentifier (v4.6+)</xs:documentation>
          <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/relatedidentifier/</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:simpleContent>
            <xs:extension base="titleLimitType">
              <xs:attribute name="relatedIDType" type="relatedIDTypeType" default="DOI"/>
              <xs:attribute name="relationType" type="relationTypeType" use="required"/>
              <xs:attribute name="relatedMetadataSchema" type="titleLimitType" use="optional"/>
            </xs:extension>
          </xs:simpleContent>
          <xs:documentation xml:lang="en">The name of the related metadata schema, if applicable</xs:documentation>
          <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor relation types</xs:documentation>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```


</xs:annotation>
</xs:attribute>
<xs:attribute name="relatedMetadataSchemaURI" type="xs:anyURI" use="optional">
  <xs:annotation>
    <xs:documentation xml:lang="en">The URI of the related metadata schema, if
applicable</xs:documentation>
    <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor
relation types</xs:documentation>
  </xs:annotation>
</xs:attribute>
<xs:attribute name="relatedMetadataSchemaType" type="shortAttributeType"
use="optional">
  <xs:annotation>
    <xs:documentation xml:lang="en">The type of the related metadata schema, if
applicable (e.g. XSD, DDT, Turtle)</xs:documentation>
    <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor
relation types</xs:documentation>
  </xs:annotation>
</xs:attribute>
<xs:attribute ref="resourceTypeGeneral" use="optional"/>
<xs:attribute ref="inherited" default="false"/>
</xs:extension>
</xs:simpleContent>
</xs:complexType>
</xs:element>
</xs:sequence>
<xs:attribute ref="discoverable" fixed="true"/>
<xs:attribute ref="trackingLevel" fixed="ResourceRecord"/>
</xs:complexType>
</xs:element>

```

Element supplementalMetadata / relations / relation

Namespace	No namespace
Annotations	Specifies a related TigerData project or item, a published paper, or any other digital object, given as a string May apply to either Projects or Items Derived from the DataCite definitions for RelatedIdentifier (v4.6+) https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/relatedidentifier/

Diagram




Type	extension of titleLimitType				
Type hierarchy	- xs:string - titleLimitType				
Properties	content:	complex			
	minOccurs:	1			
	maxOccurs:	100			
Attributes	QName	Type	Default	Use	
	inherited	xs:boolean	false	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
	relatedIDType	relatedIDTypeType	DOI	optional	
	relatedMetadataSchema	titleLimitType		optional	
		The name of the related metadata schema, if applicable Use only with HasMetadata and IsMetadataFor relation types			
	relatedMetadataSchemaType	shortAttributeType		optional	
		The type of the related metadata schema, if applicable (e.g. XSD, DDT, Turtle) Use only with HasMetadata and IsMetadataFor relation types			

	QName	Type	Default	Use	
	relatedMetadataSchemaURI	xs:anyURI		optional	
		The URI of the related metadata schema, if applicable Use only with HasMetadata and IsMetadataFor relation types			
	relationType	relationTypeType		required	
	resourceTypeGeneral	resourceTypeGeneralType		optional	
		Standard attribute to specify the general type for a resource, following the controlled vocabulary in resourceTypeGeneralType Derived from the DataCite definition for resourceTypeGeneral (v4.6+)			
Source	<pre><xs:element name="relation" minOccurs="1" maxOccurs="100"> <xs:annotation> <xs:documentation xml:lang="en">Specifies a related TigerData project or item, a published paper, or any other digital object, given as a string</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite definitions for RelatedIdentifier (v4.6+)</xs:documentation> <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/ relatedidentifier/</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleLimitType"> <xs:attribute name="relatedIDType" type="relatedIDTypeType" default="DOI"/> <xs:attribute name="relationType" type="relationTypeType" use="required"/> <xs:attribute name="relatedMetadataSchema" type="titleLimitType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The name of the related metadata schema, if applicable</ xs:documentation> <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor relation types</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="relatedMetadataSchemaURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the related metadata schema, if applicable</ xs:documentation> <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor relation types</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="relatedMetadataSchemaType" type="shortAttributeType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The type of the related metadata schema, if applicable (e.g. XSD, DDT, Turtle)</xs:documentation> <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor relation types</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute ref="resourceTypeGeneral" use="optional"/> <xs:attribute ref="inherited" default="false"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>				

Element supplementalMetadata / extendedMetadataSchemas

Namespace	No namespace
Annotations	The container element for all extended metadata schemas for a resource, if applicable May apply to either Projects or Items If this element is present, then it should contain at least one sub-element

Diagram



Properties

content:	complex
minOccurs:	0
maxOccurs:	1

Model

extendedMetadataSchema{1,10}

Children

extendedMetadataSchema

Instance

```
<extendedMetadataSchemas discoverable="false" trackingLevel="InternalUseOnly">
  <extendedMetadataSchema inherited="false" xml:lang="en">{1,10}</extendedMetadataSchema>
</extendedMetadataSchemas>
```

Attributes

QName	Type	Fixed	Use
discoverable	xs:boolean	false	optional
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems		
trackingLevel	trackingLevelType	InternalUseOnly	optional
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)		

Source

```
<xs:element name="extendedMetadataSchemas" minOccurs="0" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">The container element for all extended metadata schemas for a
    resource, if applicable</xs:documentation>
    <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation>
    <xs:documentation xml:lang="en">If this element is present, then it should contain at least one
    sub-element</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="extendedMetadataSchema" minOccurs="1" maxOccurs="10">
        <xs:annotation>
          <xs:documentation xml:lang="en">An indication of which TigerData supported metadata
          schemas should apply to a resource (given as a string)</xs:documentation>
          <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:simpleContent>
            <xs:extension base="titleType">
              <xs:attribute ref="inherited" default="false"/>
            </xs:extension>
          </xs:simpleContent>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
    <xs:attribute ref="discoverable" fixed="false"/>
    <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
  </xs:complexType>
</xs:element>
```

Element supplementalMetadata / extendedMetadataSchemas / extendedMetadataSchema

Namespace	No namespace
-----------	--------------

Annotations	An indication of which TigerData supported metadata schemas should apply to a resource (given as a string) May apply to either Projects or Items				
Diagram	The diagram illustrates the schema structure. At the top, 'titleType (extension base)' is shown with a 'Base Type' of 'titleLimitType'. Below it, 'titleLimitType' is defined with a 'Specification for the practical limit for text values within titleType'. It has an attribute 'xml:lang' with a default value of 'en'. A note explains that '<div> <h3>lang (as an attribute name)</h3> <p>' denotes an attribute whose value is a language code for the natural...'. Below this, 'extendedMetadataSchema' is shown as an 'Extension of titleType'. It has a note: 'An indication of which TigerData supported metadata schemas should apply to a resource (given as a string) May apply to...'. It also has an attribute 'inherited' of type 'xs:boolean' with a default value of 'false'. A note explains that this is a 'Standard attribute to specify whether a given field's value should be inherited by any child resources' and that 'Inheritance is...'. A final note states 'Standard type used for title values'.				
Type	extension of titleType				
Type hierarchy	- xs:string - titleLimitType - titleType				
Properties	content:	complex			
	minOccurs:	1			
	maxOccurs:	10			
Attributes	QName	Type	Default	Use	
	inherited	xs:boolean	false	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
		<pre> <div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p> </div> </pre>			

Source	<pre> <xs:element name="extendedMetadataSchema" minOccurs="1" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">An indication of which TigerData supported metadata schemas should apply to a resource (given as a string)</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleType"> <xs:attribute ref="inherited" default="false"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>
--------	--

Element projectFields / projectID

Namespace	No namespace						
Annotations	The universally unique identifier for the project (required)						
Diagram	The diagram illustrates the structure of the projectID element. It is an extension of projectIDValueType. projectIDValueType is a base type for doctype. projectIDValueType has an attribute projectIDType of type xs:string with a fixed value of DOI. projectID has attributes inherited (type xs:boolean, fixed false), discoverable (type xs:boolean, fixed true), and trackingLevel (type trackingLevelType, fixed ResourceRecord).						
Type	extension of projectIDValueType						
Type hierarchy	- xs:string - doctype - projectIDValueType						
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>1</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	1	maxOccurs:	1
content:	complex						
minOccurs:	1						
maxOccurs:	1						

Attributes	QName	Type	Fixed	Use		
	discoverable	xs:boolean	true	optional		
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean	false	optional		
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	projectIDType	xs:string	DOI	optional		
		Makes explicit that the project ID is always given as a DOI				
	trackingLevel	trackingLevelType	ResourceRecord	optional		
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)					
Source	<pre><xs:element name="projectID" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The universally unique identifier for the project (required)</ xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="projectIDValueType"> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>					

Element projectFields / projectProvenance

Namespace	No namespace						
Annotations	The container element for all TigerData project provenance fields (required)						
Diagram	<pre> classDiagram class projectProvenance { submission revisions retirement publication status } class submission { "A record of a project's initial submission (required)" } class revisions { "The container element for all revision records, if applicable" } class retirement { "A record of a project's retirement, if applicable" } class publication { "A record of a project's publication, if applicable" } class status { "The current status of the project (required)" Type Default } projectProvenance --> submission projectProvenance --> revisions projectProvenance --> retirement projectProvenance --> publication projectProvenance --> status status --> statusType : Extension of 'statusType' status --> AdminReview : Default </pre>						
Properties	<table> <tr> <td>content:</td><td>complex</td></tr> <tr> <td>minOccurs:</td><td>1</td></tr> <tr> <td>maxOccurs:</td><td>1</td></tr> </table>	content:	complex	minOccurs:	1	maxOccurs:	1
content:	complex						
minOccurs:	1						
maxOccurs:	1						
Model	submission , revisions{0,1} , retirement{0,1} , publication{0,1} , status						
Children	publication, retirement, revisions, status, submission						
Instance	<pre> <projectProvenance> <submission discoverable="false" inherited="false" trackingLevel="InternalUseOnly">{1,1}</submission> <revisions discoverable="false" trackingLevel="InternalUseOnly">{0,1}</revisions> <retirement discoverable="false" inherited="true" trackingLevel="InternalUseOnly">{0,1}</retirement> </pre>						


	<pre> <publication discoverable="false" inherited="true" trackingLevel="InternalUseOnly">{0,1}</publication> <status discoverable="true" inherited="false" trackingLevel="InternalUseOnly">{1,1}</status> </projectProvenance> </pre>
Source	<pre> <xs:element name="projectProvenance" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all TigerData project provenance fields (required)</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="submission" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">A record of a project's initial submission (required)</ xs:documentation> </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element> <xs:element name="revisions" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all revision records, if applicable</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="revision" minOccurs="1" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">A record of a major revision to an active project</ xs:documentation> </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" default="false"/> </xs:complexType> </xs:element> </xs:sequence> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element> <xs:element name="retirement" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">A record of a project's retirement, if applicable</ xs:documentation> </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" fixed="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element> <xs:element name="publication" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">A record of a project's publication, if applicable</ xs:documentation> </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" fixed="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element> <xs:element name="status" minOccurs="1" maxOccurs="1" default="AdminReview"> <xs:annotation> <xs:documentation xml:lang="en">The current status of the project (required)</ xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="statusType"> <xs:attribute ref="inherited" default="false"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
```

Element projectFields / projectProvenance / submission

Namespace	No namespace
Annotations	A record of a project's initial submission (required)

Diagram



Properties

content:	complex
minOccurs:	1
maxOccurs:	1

Model	requestedBy , requestDateTime , approvedBy{0,1} , approvalDateTime{0,1} , deniedBy{0,1} , denialDateTime{0,1} , eventNote{0,5}				
Children	approvalDateTime, approvedBy, denialDateTime, deniedBy, eventNote, requestDateTime, requestedBy				
Instance	<pre><submission discoverable="false" inherited="false" trackingLevel="InternalUseOnly"> <requestedBy userID="" userIDType="NetID">{1,1}</requestedBy> <requestDateTime>{1,1}</requestDateTime> <approvedBy userID="" userIDType="NetID">{0,1}</approvedBy> <approvalDateTime>{0,1}</approvalDateTime> <deniedBy userID="" userIDType="NetID">{0,1}</deniedBy> <denialDateTime>{0,1}</denialDateTime> <eventNote>{0,5}</eventNote> </submission></pre>				
Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	false	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	inherited	xs:boolean	false	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources			
		Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
	trackingLevel	trackingLevelType	InternalUseOnly	optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="submission" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">A record of a project's initial submission (required)</xs:documentation> </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element></pre>				

Element projectFields / projectProvenance / revisions


Namespace	No namespace		
Annotations	The container element for all revision records, if applicable		
Diagram	revisions (1..10) The container element for all revision records, if applicable Attributes discoverable (xs:boolean, Fixed: false) Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems trackingLevel (trackingLevelType, Fixed: InternalUseOnly) Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly) revision (1) A record of a major revision to an active project		
Properties	content:	complex	
	minOccurs:	0	
	maxOccurs:	1	
Model	revision{1,10}		
Children	revision		

Instance	<pre><revisions discoverable="false" trackingLevel="InternalUseOnly"> <revision inherited="false">{1,10}</revision> </revisions></pre>				
Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	false	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	trackingLevel	trackingLevelType	InternalUseOnly	optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)			
Source	<pre><xs:element name="revisions" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all revision records, if applicable</ xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="revision" minOccurs="1" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">A record of a major revision to an active project</ xs:documentation> </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" default="false"/> </xs:complexType> </xs:element> </xs:sequence> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element></pre>				

Element projectFields / projectProvenance / revisions / revision

Namespace	No namespace
Annotations	A record of a major revision to an active project

Diagram




Properties	content:	complex
	minOccurs:	1
	maxOccurs:	10
Model	requestedBy , requestDateTime , approvedBy{0,1} , approvalDateTime{0,1} , deniedBy{0,1} , denialDateTime{0,1} , event-Note{0,5}	
Children	approvalDateTime, approvedBy, denialDateTime, deniedBy, eventNote, requestDateTime, requestedBy	
Instance	<pre> <revision inherited="false"> <requestedBy userID="" userIDType="NetID">{1,1}</requestedBy> <requestDateTime>{1,1}</requestDateTime> <approvedBy userID="" userIDType="NetID">{0,1}</approvedBy> <approvalDateTime>{0,1}</approvalDateTime> <deniedBy userID="" userIDType="NetID">{0,1}</deniedBy> <denialDateTime>{0,1}</denialDateTime> <eventNote>{0,5}</eventNote> </revision> </pre>	

Attributes	QName	Type	Default	Use	
	inherited	xs:boolean	false	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
Source	<pre><xs:element name="revision" minOccurs="1" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">A record of a major revision to an active project</ </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" default="false"/> </xs:complexType> </xs:element></pre>				

Element projectFields / projectProvenance / retirement

Namespace	No namespace
Annotations	A record of a project's retirement, if applicable

Diagram



Properties


content:	complex
minOccurs:	0
maxOccurs:	1

Model	requestedBy , requestDateTime , approvedBy{0,1} , approvalDateTime{0,1} , deniedBy{0,1} , denialDateTime{0,1} , eventNote{0,5}				
Children	approvalDateTime, approvedBy, denialDateTime, deniedBy, eventNote, requestDateTime, requestedBy				
Instance	<pre><retirement discoverable="false" inherited="true" trackingLevel="InternalUseOnly"> <requestedBy userID="" userIDType="NetID">{1,1}</requestedBy> <requestDateTime>{1,1}</requestDateTime> <approvedBy userID="" userIDType="NetID">{0,1}</approvedBy> <approvalDateTime>{0,1}</approvalDateTime> <deniedBy userID="" userIDType="NetID">{0,1}</deniedBy> <denialDateTime>{0,1}</denialDateTime> <eventNote>{0,5}</eventNote> </retirement></pre>				
Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	false	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	inherited	xs:boolean	true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources			
		Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
	trackingLevel	trackingLevelType	InternalUseOnly	optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="retirement" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">A record of a project's retirement, if applicable</ </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" fixed="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element></pre>				

Element projectFields / projectProvenance / publication

Namespace	No namespace
Annotations	A record of a project's publication, if applicable

Diagram



Properties

content:	complex
minOccurs:	0
maxOccurs:	1

Model	requestedBy , requestDateTime , approvedBy{0,1} , approvalDateTime{0,1} , deniedBy{0,1} , denialDateTime{0,1} , eventNote{0,5}				
Children	approvalDateTime, approvedBy, denialDateTime, deniedBy, eventNote, requestDateTime, requestedBy				
Instance	<publication discoverable="false" inherited="true" trackingLevel="InternalUseOnly"> <requestedBy userID="" userIDType="NetID">{1,1}</requestedBy> <requestDateTime>{1,1}</requestDateTime> <approvedBy userID="" userIDType="NetID">{0,1}</approvedBy> <approvalDateTime>{0,1}</approvalDateTime> <deniedBy userID="" userIDType="NetID">{0,1}</deniedBy> <denialDateTime>{0,1}</denialDateTime> <eventNote>{0,5}</eventNote> </publication>				
Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	false	optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems			
	inherited	xs:boolean	true	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources			
		Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)			
	trackingLevel	trackingLevelType	InternalUseOnly	optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<xs:element name="publication" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">A record of a project's publication, if applicable</xs:documentation> </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" fixed="true"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element>				

Element projectFields / projectProvenance / status


Namespace	No namespace
Annotations	The current status of the project (required)
Diagram	The diagram illustrates the structure of the status element. It is an extension of the statusType standard type. The status element is required and has a default value of AdminReview. The statusType standard type defines the controlled vocabulary for the status field and applies only to Projects. It has three attributes: inherited: A boolean attribute with a default value of false. It specifies whether a given field's value should be inherited by any child resources. discoverable: A boolean attribute with a fixed value of true. It specifies whether a given field should be discoverable to search operations within TigerData systems. trackingLevel: A trackingLevelType attribute with a fixed value of InternalUseOnly. It specifies the tracking level of a given field (ResourceRecord or InternalUseOnly).

Type	extension of statusType					
Type hierarchy	- xs:string - statusType					
Properties	content:	complex				
	minOccurs:	1				
	maxOccurs:	1				
	default:	AdminReview				
Attributes	QName	Type	Fixed	Default	Use	
	discoverable	xs:boolean	true		optional	
		Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean		false	optional	
		Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	trackingLevel	trackingLevelType	InternalUseOnly		optional	
		Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				
Source	<pre><xs:element name="status" minOccurs="1" maxOccurs="1" default="AdminReview"> <xs:annotation> <xs:documentation xml:lang="en">The current status of the project (required)</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="statusType"> <xs:attribute ref="inherited" default="false"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>					

Element itemFields / itemID

Namespace	No namespace
Annotations	The unique identifier for the item (required)
	TigerData items use Mediaflux Asset IDs as their primary identifiers
	If an item also has any other IDs, they all should be included under alternativeIDs

Diagram



Type extension of mediafluxAssetIDType

Type hierarchy

- xs:integer
- mediafluxAssetIDType

Properties

content:	complex
minOccurs:	1
maxOccurs:	1

Attributes	QName	Type	Fixed	Use	
	discoverable	xs:boolean	false	optional	
	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems				
	inherited	xs:boolean	false	optional	
	Standard attribute to specify whether a given field's value should be inherited by any child resources				
	Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)				
	itemIDType	xs:string	MFAID	optional	
	Makes explicit that itemID is always given as a Mediaflux Asset ID				
	trackingLevel	trackingLevelType	InternalUseOnly	optional	
	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)				

Source


```
<xs:element name="itemID" minOccurs="1" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">The unique identifier for the item (required)</xs:documentation>
    <xs:documentation xml:lang="en">TigerData items use Mediaflux Asset IDs as their primary identifiers</xs:documentation>
    <xs:documentation xml:lang="en">If an item also has any other IDs, they all should be included under alternativeIDs</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:simpleContent>
      <xs:extension base="mediafluxAssetIDType">
        <xs:attribute name="itemIDType" type="xs:string" fixed="MFAID">
```

```
<xs:annotation>
  <xs:documentation xml:lang="en">Makes explicit that itemID is always given as a
Mediaflux Asset ID</xs:documentation>
</xs:annotation>
</xs:attribute>
<xs:attribute ref="inherited" fixed="false"/>
<xs:attribute ref="discoverable" fixed="false"/>
<xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
</xs:extension>
</xs:simpleContent>
</xs:complexType>
</xs:element>
```

Element resource

Namespace	No namespace
Annotations	Root element of any metadata record for TigerData resources (projects and items). If the resourceClass is Project, then the projectFields group must be used. If the resourceClass is Item, then the itemFields group must be used.

Diagram



Properties	content: complex
Model	((projectID , alternativeIDs{0,1} , parentProject{0,1} , dataSponsor , dataManager , dataUsers{0,1} , researchDomains{0,1} , departments , projectDirectory , title , description , languages{0,1} , storageCapacity , projectVisibility , storagePerformance , numberOfFiles , securityLevel{0,1} , storageSystem{0,1} , accessPoints{0,1} , projectPurpose , provisionalProject , funded{0,1} , fundingReferences{0,1} , projectDates{0,1} , projectResourceType , licenses{0,1} , dataUseAgreement{0,1} , duaReferences{0,1} , keywords{0,1} , relations{0,1} , extendedMetadataSchemas{0,1} , projectProvenance) (itemID , alternativeIDs{0,1} , parentProject , dataUsers{0,1} , title{0,1} , description{0,1} , itemResourceType{0,1} , keywords{0,1} , relations{0,1} , extendedMetadataSchemas{0,1} , languages{0,1} , licenses{0,1} , fundingReferences{0,1} , duaReferences{0,1} , itemDates{0,1})) , schemaVersion
Children	accessPoints, alternativeIDs, dataManager, dataSponsor, dataUseAgreement, dataUsers, departments, description, duaReferences, extendedMetadataSchemas, funded, fundingReferences, itemDates, itemID, itemResourceType, keywords, languages, licenses, numberOfFiles, parentProject, projectDates, projectDirectory, projectID, projectProvenance, projectPurpose, projectResourceType, projectVisibility, provisionalProject, relations, researchDomains, schemaVersion, securityLevel, storageCapacity, storagePerformance, storageSystem, title
Instance	<pre> <resource resourceClass="" resourceID="" resourceIDType=""> <projectID discoverable="true" inherited="false" projectIDType="DOI" trackingLevel="ResourceRecord">{1,1}</projectID> <alternativeIDs discoverable="true" trackingLevel="ResourceRecord">{0,1}</alternativeIDs> <parentProject discoverable="true" inherited="true" projectIDType="DOI" trackingLevel="ResourceRecord">{0,1}</parentProject> <dataSponsor discoverable="true" inherited="true" trackingLevel="ResourceRecord" userID="" userIDType="NetID">{1,1}</dataSponsor> <dataManager discoverable="true" inherited="true" trackingLevel="ResourceRecord" userID="" userIDType="NetID">{1,1}</dataManager> <dataUsers trackingLevel="ResourceRecord">{0,1}</dataUsers> <researchDomains discoverable="true" trackingLevel="ResourceRecord">{0,1}</researchDomains> <departments discoverable="true" trackingLevel="ResourceRecord">{1,1}</departments> <projectDirectory approved="false" discoverable="false" inherited="false" trackingLevel="InternalUseOnly">{1,1}</projectDirectory> <title discoverable="true" inherited="false" xml:lang="en" trackingLevel="ResourceRecord">{1,1}</title> <description discoverable="true" inherited="false" xml:lang="en" trackingLevel="ResourceRecord">{1,1}</description> <languages discoverable="true" trackingLevel="ResourceRecord">{0,1}</languages> <storageCapacity approved="false" discoverable="false" inherited="false" trackingLevel="InternalUseOnly">{1,1}</storageCapacity> <projectVisibility discoverable="false" inherited="true" trackingLevel="InternalUseOnly">{1,1}</projectVisibility> <storagePerformance approved="false" discoverable="false" inherited="true" trackingLevel="InternalUseOnly">{1,1}</storagePerformance> <numberOfFiles discoverable="false" inherited="false" trackingLevel="InternalUseOnly">{1,1}</numberOfFiles> <securityLevel approved="false" discoverable="false" inherited="true" trackingLevel="InternalUseOnly">{0,1}</securityLevel> <storageSystem discoverable="false" inherited="false" trackingLevel="InternalUseOnly">{0,1}</storageSystem> <accessPoints discoverable="false" inherited="false" trackingLevel="InternalUseOnly">{0,1}</accessPoints> <projectPurpose discoverable="true" inherited="true" trackingLevel="InternalUseOnly">{1,1}</projectPurpose> <provisionalProject discoverable="true" inherited="true" trackingLevel="InternalUseOnly">{1,1}</provisionalProject> <funded discoverable="false" federallyFunded="false" inherited="true" trackingLevel="InternalUseOnly">{0,1}</funded> <fundingReferences discoverable="true" trackingLevel="ResourceRecord">{0,1}</fundingReferences> <projectDates discoverable="true" trackingLevel="ResourceRecord">{0,1}</projectDates> <projectResourceType discoverable="true" inherited="false" xml:lang="en" resourceTypeGeneral="Project" trackingLevel="ResourceRecord">{0,1}</projectResourceType> <licenses discoverable="true" trackingLevel="ResourceRecord">{0,1}</licenses> <dataUseAgreement discoverable="false" inherited="true" trackingLevel="InternalUseOnly">{0,1}</dataUseAgreement> <duaReferences discoverable="true" trackingLevel="ResourceRecord">{0,1}</duaReferences> <keywords discoverable="true" trackingLevel="ResourceRecord">{0,1}</keywords> <relations discoverable="true" trackingLevel="ResourceRecord">{0,1}</relations> <extendedMetadataSchemas discoverable="false" trackingLevel="InternalUseOnly">{0,1}</extendedMetadataSchemas> <projectProvenance>{1,1}</projectProvenance> <itemID discoverable="false" inherited="false" itemIDType="MFAID" trackingLevel="InternalUseOnly">{1,1}</itemID> <alternativeIDs discoverable="true" trackingLevel="ResourceRecord">{0,1}</alternativeIDs> <parentProject discoverable="true" inherited="true" projectIDType="DOI" trackingLevel="ResourceRecord">{1,1}</parentProject> <dataUsers trackingLevel="ResourceRecord">{0,1}</dataUsers> <title discoverable="true" inherited="false" xml:lang="en" trackingLevel="ResourceRecord">{0,1}</title> <description discoverable="true" inherited="false" xml:lang="en" trackingLevel="ResourceRecord">{0,1}</description> </pre>

	<pre><itemResourceType discoverable="true" inherited="false" xml:lang="en" resourceTypeGeneral="" trackingLevel="ResourceRecord"> <keywords discoverable="true" trackingLevel="ResourceRecord">{0,1}</keywords> <relations discoverable="true" trackingLevel="ResourceRecord">{0,1}</relations> <extendedMetadataSchemas discoverable="false" trackingLevel="InternalUseOnly">{0,1}</extendedMetadataSchemas> <languages discoverable="true" trackingLevel="ResourceRecord">{0,1}</languages> <licenses discoverable="true" trackingLevel="ResourceRecord">{0,1}</licenses> <fundingReferences discoverable="true" trackingLevel="ResourceRecord">{0,1}</fundingReferences> <duaReferences discoverable="true" trackingLevel="ResourceRecord">{0,1}</duaReferences> <itemDates discoverable="true" trackingLevel="ResourceRecord">{0,1}</itemDates> <schemaVersion discoverable="true" inherited="true" trackingLevel="InternalUseOnly">{1,1}</schemaVersion> </resource></pre>																															
Attributes	<table><tr><th>QName</th><th>Type</th><th>Use</th><th></th></tr><tr><td>resourceClass</td><td>restriction of xs:string</td><td>required</td><td></td></tr><tr><td></td><td colspan="3">Specifies the class of a given resource: either Project or Item (required)</td></tr><tr><td>resourceID</td><td>titleLimitType</td><td>required</td><td></td></tr><tr><td></td><td colspan="3">The unique identifier for the resource within TigerData systems (required) If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)</td></tr><tr><td>resourceIDType</td><td>restriction of xs:string</td><td>required</td><td></td></tr><tr><td></td><td colspan="3">If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)</td></tr></table>	QName	Type	Use		resourceClass	restriction of xs:string	required			Specifies the class of a given resource: either Project or Item (required)			resourceID	titleLimitType	required			The unique identifier for the resource within TigerData systems (required) If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)			resourceIDType	restriction of xs:string	required			If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)					
QName	Type	Use																														
resourceClass	restriction of xs:string	required																														
	Specifies the class of a given resource: either Project or Item (required)																															
resourceID	titleLimitType	required																														
	The unique identifier for the resource within TigerData systems (required) If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)																															
resourceIDType	restriction of xs:string	required																														
	If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)																															
Source	<pre><xs:element name="resource"> <xs:annotation> <xs:documentation xml:lang="en">Root element of any metadata record for TigerData resources (projects and items).</xs:documentation> <xs:documentation xml:lang="en">If the resourceClass is Project, then the projectFields group must be used. If the resourceClass is Item, then the itemFields group must be used.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:choice minOccurs="1" maxOccurs="1"> <xs:group ref="projectFields"/> <xs:group ref="itemFields"/> </xs:choice> <xs:element ref="schemaVersion" maxOccurs="1" minOccurs="1"/> </xs:sequence> <xs:attribute name="resourceClass" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Specifies the class of a given resource: either Project or Item (required)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Project" xml:lang="en"/> <xs:enumeration value="Item" xml:lang="en"/> </xs:restriction> </xs:simpleType> </xs:attribute> <xs:attribute name="resourceID" type="titleLimitType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">The unique identifier for the resource within TigerData systems (required)</xs:documentation> <xs:documentation xml:lang="en">If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="resourceIDType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="DOI"/> <xs:enumeration value="MFAID"/> </xs:restriction> </xs:simpleType> </xs:attribute> </xs:complexType> </xs:element></pre>																															

Simple Type(s)

Simple Type doiType

Namespace	No namespace
Annotations	Standard type used for DOI values (just the prefix and suffix; not a full URL) DOI is short for Digital Object Identifier Applies a pattern aligned with ISO 26324:2022, allowing any suffix that doesn't have whitespace and doesn't end with unexpected punctuation https://www.iso.org/standard/81599.html
Diagram	Standard type used for DOI values (just the prefix and suffix; not a full URL) DOI is short for Digital Object... Built-in primitive type. The string datatype represents character strings in XML.
Type	restriction of xs:string
Facets	pattern <code>10\.d{4,9}\/[a-z0-9]{4}-[a-z0-9]{4}</code>
Used by	Complex Type projectIDValueType
Source	<pre><xs:simpleType name="doiType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for DOI values (just the prefix and suffix; not a full URL)</xs:documentation> <xs:documentation xml:lang="en">DOI is short for Digital Object Identifier</xs:documentation> <xs:documentation xml:lang="en">Applies a pattern aligned with ISO 26324:2022, allowing any suffix that doesn't have whitespace and doesn't end with unexpected punctuation</xs:documentation> <xs:documentation>https://www.iso.org/standard/81599.html</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:pattern value="10\.d{4,9}\/[a-z0-9]{4}-[a-z0-9]{4}" /> </xs:restriction> </xs:simpleType></pre>

Simple Type netIDType

Namespace	No namespace
Annotations	Standard type used for values meant to be a Princeton NetID Applies a simple pattern that is true for all Princeton NetIDs Validation of user accounts and permissions happens separate from metadata validation
Diagram	Standard type used for values meant to be a Princeton NetID Applies a simple pattern that is true for all Princeton... Built-in primitive type. The string datatype represents character strings in XML.
Type	restriction of xs:string
Facets	pattern <code>[a-z0-9-]{2,10}</code>
Used by	Elements shortUserType/netID, userType/netID Attributes shortUserType/@userID, userType/@userID
Source	<pre><xs:simpleType name="netIDType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for values meant to be a Princeton NetID</xs:documentation> <xs:documentation xml:lang="en">Applies a simple pattern that is true for all Princeton NetIDs</xs:documentation> <xs:documentation xml:lang="en">Validation of user accounts and permissions happens separate from metadata validation</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:pattern value="[a-z0-9-]{2,10}" /> </xs:restriction> </xs:simpleType></pre>

</xs:simpleType>

Simple Type puidType

Namespace	No namespace
Annotations	Standard type used for values meant to be a Princeton University ID (PUID) Applies a simple pattern that is true for all PUIDs Validation of user accounts and permissions happens separate from metadata validation
Diagram	
Type	restriction of xs:string
Facets	pattern [0-9]{9}
Used by	Elements shortUserType/PUID, userType/PUID
Source	<pre> <xs:simpleType name="puidType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for values meant to be a Princeton University ID (PUID)</xs:documentation> <xs:documentation xml:lang="en">Applies a simple pattern that is true for all PUIDs</xs:documentation> <xs:documentation xml:lang="en">Validation of user accounts and permissions happens separate from metadata validation</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:pattern value="[0-9]{9}" /> </xs:restriction> </xs:simpleType> </pre>

Simple Type textLimitType

Namespace	No namespace				
Annotations	Specification for the practical limit for text values within textType				
Diagram					
Type	restriction of xs:string				
Facets	<table> <tr> <td>minLength</td> <td>1</td> </tr> <tr> <td>maxLength</td> <td>1000</td> </tr> </table>	minLength	1	maxLength	1000
minLength	1				
maxLength	1000				
Used by	Complex Type textType				
Source	<pre> <xs:simpleType name="textLimitType"> <xs:annotation> <xs:documentation xml:lang="en">Specification for the practical limit for text values within textType</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:minLength value="1" /> <xs:maxLength value="1000" /> </xs:restriction> </xs:simpleType> </pre>				

Simple Type titleLimitType

Namespace	No namespace
Annotations	Specification for the practical limit for text values within titleType
Diagram	

Type	restriction of xs:string	
Facets	minLength	1
	maxLength	200
Used by	Complex Type	titleType
	Elements	alternativeID, fundingReference/awardNumber, storageAndAccess/accessPoints/globusCollection/globusName, supplementalMetadata/relations/relation, userType/alternativeNameIdentifier, userType/familyName, userType/fullName, userType/givenName
	Attributes	license/@licenseIDSchema, resource/@resourceID, supplementalMetadata/keywords/keyword/@subjectSchema, supplementalMetadata/relations/relation/@relatedMetadataSchema
Source	<pre><xs:simpleType name="titleLimitType"> <xs:annotation> <xs:documentation xml:lang="en">Specification for the practical limit for text values within titleType</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="200"/> </xs:restriction> </xs:simpleType></pre>	

Simple Type shortTextLimitType

Namespace	No namespace	
Annotations	Specification for the practical limit for text values within shortTextType	
Diagram		
Type	restriction of xs:string	
Facets	minLength	1
	maxLength	60
Used by	Complex Type	shortTextType
	Attributes	alternativeID/@alternativeIDType, otherDate/@dateInformation
	Element	schemaVersion
Source	<pre><xs:simpleType name="shortTextLimitType"> <xs:annotation> <xs:documentation xml:lang="en">Specification for the practical limit for text values within shortTextType</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="60"/> </xs:restriction> </xs:simpleType></pre>	

Simple Type longTextLimitType

Namespace	No namespace	
Annotations	Specification for the practical limit for text values within longTextType	
Diagram		
Type	restriction of xs:string	
Facets	minLength	1
	maxLength	2000
Used by	Complex Type	longTextType
Source	<pre><xs:simpleType name="longTextLimitType"> <xs:annotation></pre>	

```
<xs:documentation xml:lang="en">Specification for the practical limit for text values within
longTextType</xs:documentation>
</xs:annotation>
<xs:restriction base="xs:string">
  <xs:minLength value="1"/>
  <xs:maxLength value="2000"/>
</xs:restriction>
</xs:simpleType>
```

Simple Type pathSafeType

Namespace	No namespace
Annotations	Standard type used within pathType to prevent invalid entries Restricts to alphanumeric characters, underscore, forward and back slashes, colon, and minus-dash The typical value is expected to start "/tigerdata/" and follow with a parent folder of at least 3 characters and a project folder of at least 3 characters, with a slash in-between, hence the minimum of 18 characters The ordinary practical limit of 1000 characters for a text field is too high; Windows systems have a hard limit of 260 characters for the full path, so the directory needs to much less than that to avoid problems, hence the maximum of 128 characters
Diagram	<pre> graph LR pathSafeType -- restriction --> xsString[xs:string] subgraph pathSafeTypeBox [pathSafeType] direction TB A1[Standard type used within pathType to prevent invalid entries] A2[Restricts to alphanumeric characters, underscore, forward...] end subgraph xsStringBox [xs:string] direction TB B1[Built-in primitive type. The string datatype represents character strings in XML.] end </pre>
Type	restriction of xs:string
Facets	pattern [a-zA-Z0-9\\/:_\\-]{18,128}
Used by	Complex Type pathType
Source	<pre><xs:simpleType name="pathSafeType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used within pathType to prevent invalid entries</xs:documentation> <xs:documentation xml:lang="en">Restricts to alphanumeric characters, underscore, forward and back slashes, colon, and minus-dash</xs:documentation> <xs:documentation xml:lang="en">The typical value is expected to start "/tigerdata/" and follow with a parent folder of at least 3 characters and a project folder of at least 3 characters, with a slash in-between, hence the minimum of 18 characters</xs:documentation> <xs:documentation xml:lang="en">The ordinary practical limit of 1000 characters for a text field is too high; Windows systems have a hard limit of 260 characters for the full path, so the directory needs to much less than that to avoid problems, hence the maximum of 128 characters</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:pattern value="[a-zA-Z0-9\\/:_\\-]{18,128}"/> </xs:restriction> </xs:simpleType></pre>

Simple Type uuidType

Namespace	No namespace
Annotations	Standard type used for values meant to be Universally Unique Identifiers (e.g., in globusUUID) Restricts to hexadecimal characters and minus-dashes, with a length ranging from 32 to 36 The most common value is expected to be hexadecimal in 8-4-4-4-12 format, but this type specification is simplified for XML, and therefore more permissive
Diagram	<pre> graph LR uuidType -- restriction --> xsString[xs:string] subgraph uuidTypeBox [uuidType] direction TB A1[Standard type used for values meant to be Universally Unique Identifiers (e.g., in globusUUID)] A2[Restricts to hexadecimal...] end subgraph xsStringBox [xs:string] direction TB B1[Built-in primitive type. The string datatype represents character strings in XML.] end </pre>
Type	restriction of xs:string

Facets	pattern [0-9a-f\-\-]{32,36}
Used by	Element storageAndAccess/accessPoints/globusCollection/globusUUID
Source	<pre> <xs:simpleType name="uuidType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for values meant to be Universally Unique Identifiers (e.g., in globusUUID)</xs:documentation> <xs:documentation xml:lang="en">Restricts to hexadecimal characters and minus-dashes, with a length ranging from 32 to 36</xs:documentation> <xs:documentation xml:lang="en">The most common value is expected to be hexadecimal in 8-4-4-4-12 format, but this type specification is simplified for XML, and therefore more permissive</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:pattern value="[0-9a-f\-\-]{32,36}"/> </xs:restriction> </xs:simpleType> </pre>

Simple Type byteUnitType

Namespace	No namespace																		
Annotations	Standard type that defines the controlled vocabulary for byte units in storageQuantityType All byte units are base-10, not base-2																		
Diagram	<pre>graph LR byteUnitType[byteUnitType] --- xsString[xs:string] byteUnitType --- doc1[Standard type that defines the controlled vocabulary for byte units in storageQuantityType. All byte units are base-10, not base-2.] xsString --- doc2[Built-in primitive type. The string datatype represents character strings in XML.]</pre>																		
Type	restriction of xs:string																		
Facets	<table><tr><td>enumeration</td><td>B</td><td>Bytes (B)</td></tr><tr><td>enumeration</td><td>KB</td><td>Kilobytes (KB)</td></tr><tr><td>enumeration</td><td>MB</td><td>Megabytes (MB)</td></tr><tr><td>enumeration</td><td>GB</td><td>Gigabytes (GB)</td></tr><tr><td>enumeration</td><td>TB</td><td>Terabytes (TB)</td></tr><tr><td>enumeration</td><td>PB</td><td>Petabytes (PB)</td></tr></table>	enumeration	B	Bytes (B)	enumeration	KB	Kilobytes (KB)	enumeration	MB	Megabytes (MB)	enumeration	GB	Gigabytes (GB)	enumeration	TB	Terabytes (TB)	enumeration	PB	Petabytes (PB)
enumeration	B	Bytes (B)																	
enumeration	KB	Kilobytes (KB)																	
enumeration	MB	Megabytes (MB)																	
enumeration	GB	Gigabytes (GB)																	
enumeration	TB	Terabytes (TB)																	
enumeration	PB	Petabytes (PB)																	
Used by	Element storageQuantityType/unit																		
Source	<pre><xs:simpleType name="byteUnitType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for byte units in storageQuantityType</xs:documentation> <xs:documentation xml:lang="en">All byte units are base-10, not base-2</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="B" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Bytes (B)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="KB" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Kilobytes (KB)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="MB" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Megabytes (MB)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="GB" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Gigabytes (GB)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="TB" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Terabytes (TB)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="PB" xml:lang="en"></pre>																		

```
<xs:annotation>
  <xs:documentation xml:lang="en">Petabytes (PB)</xs:documentation>
</xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
```

Simple Type dateOrRangeType

Namespace	No namespace		
Annotations	Standard type used for values that may be either dates or date ranges Applies a pattern aligned with RKMS-ISO8601 https://www.ukoln.ac.uk/metadata/dcmi/collection-RKMS-ISO8601/		
Diagram			
Type	restriction of xs:string		
Facets	<table> <tr> <td>pattern</td> <td> \ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1]) (\ / \ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1])) ? </td> </tr> </table>	pattern	\ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1]) (\ / \ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1])) ?
pattern	\ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1]) (\ / \ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1])) ?		
Used by	<table> <tr> <td>Elements</td> <td>endDate, otherDate, publicationDate, retirementDate, startDate, userType/nameDate</td> </tr> </table>	Elements	endDate, otherDate, publicationDate, retirementDate, startDate, userType/nameDate
Elements	endDate, otherDate, publicationDate, retirementDate, startDate, userType/nameDate		
Source	<pre><xs:simpleType name="dateOrRangeType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for values that may be either dates or date ranges</xs:documentation> <xs:documentation xml:lang="en">Applies a pattern aligned with RKMS-ISO8601</xs:documentation> <xs:documentation>https://www.ukoln.ac.uk/metadata/dcmi/collection-RKMS-ISO8601/</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:pattern value="\ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1]) (\ / \ d { 4 } - (0 [1 - 9] 1 [0 - 2]) - (0 [1 - 9] [1 2] [0 - 9] 3 [0 1])) ?" /> </xs:restriction> </xs:simpleType></pre>		

Simple Type shortAttributeType

Namespace	No namespace				
Annotations	Standard type that limits strings as attribute values (as opposed to element values), but also allows empty strings				
Diagram					
Type	restriction of xs:string				
Facets	<table> <tr> <td>minLength</td> <td>0</td> </tr> <tr> <td>maxLength</td> <td>60</td> </tr> </table>	minLength	0	maxLength	60
minLength	0				
maxLength	60				
Used by	<table> <tr> <td>Attributes</td> <td>supplementalMetadata/keywords/keyword/@classificationCode, supplementalMetadata/relations/relation/@relatedMetadataSchemaType, userType/alternativeNameIdentifier/@nameIdentifierSchema</td> </tr> </table>	Attributes	supplementalMetadata/keywords/keyword/@classificationCode, supplementalMetadata/relations/relation/@relatedMetadataSchemaType, userType/alternativeNameIdentifier/@nameIdentifierSchema		
Attributes	supplementalMetadata/keywords/keyword/@classificationCode, supplementalMetadata/relations/relation/@relatedMetadataSchemaType, userType/alternativeNameIdentifier/@nameIdentifierSchema				
Source	<pre><xs:simpleType name="shortAttributeType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that limits strings as attribute values (as opposed to element values), but also allows empty strings</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:minLength value="0" /> <xs:maxLength value="60" /> </xs:restriction> </xs:simpleType></pre>				

Simple Type trackingLevelType


Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for the trackingLevel attribute		
Diagram			
Type	restriction of xs:string		
Facets	enumeration	ResourceRecord	The respective field should be included in any long-term or crosswalked records for the resource
	enumeration	InternalUseOnly	The respective field is intended for internal (Princeton) use only
Used by	Attribute	@trackingLevel	
Source	<pre> <xs:simpleType name="trackingLevelType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the trackingLevel attribute</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="ResourceRecord"> <xs:annotation> <xs:documentation xml:lang="en">The respective field should be included in any long-term or crosswalked records for the resource</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="InternalUseOnly"> <xs:annotation> <xs:documentation xml:lang="en">The respective field is intended for internal (Princeton) use only</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre>		

Simple Type departmentCodeType


Namespace	No namespace		
Annotations	Standard type that defines the allowable values for the departmentCode attribute in department Princeton departments always have a 5-digit numerical code		
Diagram			
Type	restriction of xs:string		
Facets	pattern	[0-9]{5}	
Used by	Attribute	projectDescription/departments/department/@departmentCode	
Source	<pre> <xs:simpleType name="departmentCodeType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the allowable values for the departmentCode attribute in department</xs:documentation> <xs:documentation xml:lang="en">Princeton departments always have a 5-digit numerical code</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:pattern value="[0-9]{5}" /> </xs:restriction> </xs:simpleType> </pre>		

Simple Type protocolType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for the protocol attribute in pathType		

Diagram			
Type	restriction of xs:string		
Facets	enumeration	NFS	Network File System (version not tracked)
	enumeration	SMB	Server Message Block (version not tracked) Used interchangeably with Common Internet File System (CIFS)
	enumeration	S3	Amazon Simple Storage Service (version not tracked)
Used by	Attribute	pathType/@protocol	
Source	<pre><xs:simpleType name="protocolType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the protocol attribute in pathType</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="NFS" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Network File System (version not tracked)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="SMB" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Server Message Block (version not tracked)</ xs:documentation> <xs:documentation xml:lang="en">Used interchangeably with Common Internet File System (CIFS)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="S3" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Amazon Simple Storage Service (version not tracked)</ xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType></pre>		

Simple Type resourceTypeGeneralType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for resourceTypeGeneral values Applies to both Projects and Items TigerData projects and subprojects should always use the standard type Project Derived from the DataCite controlled vocabulary for resourceTypeGeneral (v4.6+) https://datacite-metadata-schema.readthedocs.io/en/4.6/appendices/appendix-1/resourceTypeGeneral/ Appends custom options for TigerData items: README and DataDocumentation For labeling an item as a Data Management Plan (DMP), use the DataCite standard type OutputManagementPlan		
Diagram			
Type	restriction of xs:string		
Facets	enumeration	Audiovisual	A series of visual representations imparting an impression of motion when shown in succession. May or may not include sound.
	enumeration	Award	An umbrella term for resources provided to individual(s) or organization(s) in support of research, academic output, or training, such as a specific instance of funding,

		grant, investment, sponsorship, scholarship, recognition, or non-monetary materials.
enumeration	Book	A medium for recording information in the form of writing or images, typically composed of many pages bound together and protected by a cover.
enumeration	BookChapter	One of the main divisions of a book.
enumeration	Collection	An aggregation of resources, which may encompass collections of one resourceType as well as those of mixed types. A collection is described as a group; its parts may also be separately described.
enumeration	ComputationalNotebook	A virtual notebook environment used for literate programming.
enumeration	ConferencePaper	Article that is written with the goal of being accepted to a conference.
enumeration	ConferenceProceeding	Collection of academic papers published in the context of an academic conference.
enumeration	DataPaper	A factual and objective publication with a focused intent to identify and describe specific data, sets of data, or data collections to facilitate discoverability.
enumeration	Dataset	Data encoded in a defined structure.
enumeration	Dissertation	A written essay, treatise, or thesis, especially one written by a candidate for the degree of Doctor of Philosophy.
enumeration	Event	A non-persistent, time-based occurrence.
enumeration	Image	A visual representation other than text.
enumeration	Instrument	A device, tool or apparatus used to obtain, measure and/or analyze data.
enumeration	InteractiveResource	A resource requiring interaction from the user to be understood, executed, or experienced.
enumeration	Journal	A scholarly publication consisting of articles that is published regularly throughout the year.
enumeration	JournalArticle	A written composition on a topic of interest, which forms a separate part of a journal.
enumeration	Model	An abstract, conceptual, graphical, mathematical or visualization model that represents empirical objects, phenomena, or physical processes.
enumeration	OutputManagementPlan	A formal document that outlines how research outputs are to be handled both during a research project and after the project is completed. Use this resource type for items that serve as the Data Management Plan (DMP) for a TigerData project.
enumeration	PeerReview	Evaluation of scientific, academic, or professional work by others working in the same field.
enumeration	PhysicalObject	A physical object or substance.
enumeration	Preprint	A version of a scholarly or scientific paper that precedes formal peer review and publication in a peer-reviewed scholarly or scientific journal.
enumeration	Project	A planned endeavor or activity, frequently collaborative, intended to achieve a particular aim using allocated resources such as budget, time, and expertise. Use this resource type for all TigerData projects and subprojects.
enumeration	Report	A document that presents information in an organized format for a specific audience and purpose.
enumeration	Service	An organized system of apparatus, appliances, staff, etc., for supplying some function(s) required by end users.
enumeration	Software	A computer program other than a computational notebook, in either source code (text) or compiled form. Use this type for general software components supporting scholarly

		research. Use the "ComputationalNotebook" value for virtual notebooks.
enumeration	Sound	A resource primarily intended to be heard.
enumeration	Standard	Something established by authority, custom, or general consent as a model, example, or point of reference.
enumeration	StudyRegistration	A detailed, time-stamped description of a research plan, often openly shared in a registry or published in a journal before the study is conducted to lend accountability and transparency in the hypothesis generating and testing process.
enumeration	Text	A resource consisting primarily of words for reading that is not covered by any other textual resource type in this list.
enumeration	Workflow	A structured series of steps which can be executed to produce a final outcome, allowing users a means to specify and enact their work in a more reproducible manner.
enumeration	Other	A type of resource not otherwise described by defined types.
enumeration	README	A simple text file used to document important information about a containing resource. Use this resource type for all items serving as README files for TigerData projects.
enumeration	DataDocumentation	A resource used to document detailed information about data in a containing resource (e.g., a codebook or data dictionary). Use this resource type for items serving as supplemental documentation to the README for a TigerData project.
Used by	Attribute	@resourceTypeGeneral
Source	<pre> <xs:simpleType name="resourceTypeGeneralType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for resourceTypeGeneral values</xs:documentation> <xs:documentation xml:lang="en">Applies to both Projects and Items</xs:documentation> <xs:documentation xml:lang="en">TigerData projects and subprojects should always use the standard type Project</xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite controlled vocabulary for resourceTypeGeneral (v4.6+)</xs:documentation> <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/appendices/appendix-1/resourceTypeGeneral/</xs:documentation> <xs:documentation xml:lang="en">Appends custom options for TigerData items: README and DataDocumentation</xs:documentation> <xs:documentation xml:lang="en">For labeling an item as a Data Management Plan (DMP), use the DataCite standard type OutputManagementPlan</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Audiovisual" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">A series of visual representations imparting an impression of motion when shown in succession. May or may not include sound.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Award" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">An umbrella term for resources provided to individual(s) or organization(s) in support of research, academic output, or training, such as a specific instance of funding, grant, investment, sponsorship, scholarship, recognition, or non-monetary materials.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Book" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">A medium for recording information in the form of writing or images, typically composed of many pages bound together and protected by a cover.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="BookChapter" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">One of the main divisions of a book.</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre>	

```

<xs:enumeration value="Collection" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">An aggregation of resources, which may encompass collections
of one resourceType as well as those of mixed types. A collection is described as a group; its
parts may also be separately described.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="ComputationalNotebook" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A virtual notebook environment used for literate
programming.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="ConferencePaper" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Article that is written with the goal of being accepted to a
conference.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="ConferenceProceeding" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Collection of academic papers published in the context of an
academic conference.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="DataPaper" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A factual and objective publication with a focused
intent to identify and describe specific data, sets of data, or data collections to facilitate
discoverability.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="Dataset" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Data encoded in a defined structure.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="Dissertation" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A written essay, treatise, or thesis, especially one written
by a candidate for the degree of Doctor of Philosophy.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="Event" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A non-persistent, time-based occurrence.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="Image" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A visual representation other than text.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="Instrument" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A device, tool or apparatus used to obtain, measure and/or
analyze data.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="InteractiveResource" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A resource requiring interaction from the user to be
understood, executed, or experienced.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="Journal" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A scholarly publication consisting of articles that is
published regularly throughout the year.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="JournalArticle" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A written composition on a topic of interest, which forms a
separate part of a journal.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
<xs:enumeration value="Model" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">An abstract, conceptual, graphical, mathematical or
visualization model that represents empirical objects, phenomena, or physical processes.</
xs:documentation>
    </xs:annotation>
  </xs:enumeration>

```

```

</xs:enumeration>
<xs:enumeration value="OutputManagementPlan" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A formal document that outlines how research outputs are to
be handled both during a research project and after the project is completed.</xs:documentation>
    <xs:documentation xml:lang="en">Use this resource type for items that serve as the Data
Management Plan (DMP) for a TigerData project.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="PeerReview" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Evaluation of scientific, academic, or professional work by
others working in the same field.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="PhysicalObject" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A physical object or substance.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Preprint" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A version of a scholarly or scientific paper that
precedes formal peer review and publication in a peer-reviewed scholarly or scientific journal.</
xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Project" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A planned endeavor or activity, frequently collaborative,
intended to achieve a particular aim using allocated resources such as budget, time, and
expertise.</xs:documentation>
    <xs:documentation xml:lang="en">Use this resource type for all TigerData projects and
subprojects.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Report" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A document that presents information in an organized format
for a specific audience and purpose.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Service" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">An organized system of apparatus, appliances, staff, etc.,
for supplying some function(s) required by end users.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Software" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A computer program other than a computational notebook,
in either source code (text) or compiled form. Use this type for general software components
supporting scholarly research. Use the "ComputationalNotebook" value for virtual notebooks.</
xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Sound" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A resource primarily intended to be heard.</
xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Standard" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Something established by authority, custom, or general
consent as a model, example, or point of reference.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="StudyRegistration" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A detailed, time-stamped description of a research
plan, often openly shared in a registry or published in a journal before the study is conducted
to lend accountability and transparency in the hypothesis generating and testing process.</
xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Text" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A resource consisting primarily of words for reading that is
not covered by any other textual resource type in this list.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Workflow" xml:lang="en">

```

```

<xs:annotation>
  <xs:documentation xml:lang="en">A structured series of steps which can be executed
to produce a final outcome, allowing users a means to specify and enact their work in a more
reproducible manner.</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="Other" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A type of resource not otherwise described by defined
types.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="README" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A simple text file used to document important information
about a containing resource.</xs:documentation>
    <xs:documentation xml:lang="en">Use this resource type for all items serving as README files
for TigerData projects.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DataDocumentation" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A resource used to document detailed information about data
in a containing resource (e.g., a codebook or data dictionary).</xs:documentation>
    <xs:documentation xml:lang="en">Use this resource type for items serving as supplemental
documentation to the README for a TigerData project.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>

```

Simple Type LicenseURIType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for the licenseURI attribute All standard specifications for licenses are drawn from https://spdx.org/licenses/		
Diagram			
Type	restriction of xs:anyURI		
Facets	enumeration	https://creativecommons.org/publicdomain/zero/1.0/	Creative Commons Public Domain Dedication 1.0 Universal CC0 1.0
	enumeration	https://creativecommons.org/licenses/by/4.0/	Creative Commons Attribution 4.0 International CC BY 4.0
	enumeration	https://creativecommons.org/licenses/by-sa/4.0/	Creative Commons Attribution-Sharealike 4.0 International CC BY-SA 4.0
	enumeration	https://creativecommons.org/licenses/by-nc/4.0/	Creative Commons Attribution-Noncommercial 4.0 International CC BY-NC 4.0
	enumeration	https://creativecommons.org/licenses/by-nc-sa/4.0/	Creative Commons Attribution-Noncommercial-Sharealike 4.0 International CC BY-NC-SA 4.0
	enumeration	https://creativecommons.org/licenses/by-nd/4.0/	Creative Commons Attribution-Nonderivatives 4.0 International CC BY-ND 4.0
	enumeration	https://creativecommons.org/licenses/by-nc-nd/4.0/	Creative Commons Attribution-Noncommercial-Nonderivatives 4.0 International CC BY-NC-ND 4.0
	enumeration	https://opensource.org/license/MIT	The MIT License MIT
Used by	Attribute	license/@licenseURI	

Source	<pre> <xs:simpleType name="licenseURIType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the licenseURI attribute</xs:documentation> <xs:documentation xml:lang="en">All standard specifications for licenses are drawn from https:// spdx.org/licenses/</xs:documentation> </xs:annotation> <xs:restriction base="xs:anyURI"> <xs:enumeration value="https://creativecommons.org/publicdomain/zero/1.0/"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Public Domain Dedication 1.0 Universal</ xs:documentation> <xs:documentation xml:lang="en">CC0 1.0</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="https://creativecommons.org/licenses/by/4.0/"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution 4.0 International</ xs:documentation> <xs:documentation xml:lang="en">CC BY 4.0</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="https://creativecommons.org/licenses/by-sa/4.0/"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution-Sharealike 4.0 International</ xs:documentation> <xs:documentation xml:lang="en">CC BY-SA 4.0</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="https://creativecommons.org/licenses/by-nc/4.0/"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution-Noncommercial 4.0 International</xs:documentation> <xs:documentation xml:lang="en">CC BY-NC 4.0</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="https://creativecommons.org/licenses/by-nc-sa/4.0/"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution-Noncommercial-Sharealike 4.0 International</xs:documentation> <xs:documentation xml:lang="en">CC BY-NC-SA 4.0</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="https://creativecommons.org/licenses/by-nd/4.0/"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution-Noncommercial 4.0 International</xs:documentation> <xs:documentation xml:lang="en">CC BY-ND 4.0</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="https://creativecommons.org/licenses/by-nc-nd/4.0/"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution-Noncommercial-Noncommercial 4.0 International</xs:documentation> <xs:documentation xml:lang="en">CC BY-NC-ND 4.0</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="https://opensource.org/license/MIT"> <xs:annotation> <xs:documentation xml:lang="en">The MIT License</xs:documentation> <xs:documentation xml:lang="en">MIT</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre>
--------	---

Simple Type licenseIDType

Namespace	No namespace
Annotations	Standard type that defines the controlled vocabulary for the licenseID attribute All standard specifications for licenses are drawn from https://spdx.org/licenses/
Diagram	<pre> classDiagram class licenseIDType class xs_string["xs:string"] licenseIDType -- > xs_string </pre>
Type	restriction of xs:string

Facets	enumeration	CC0 1.0	Creative Commons Public Domain Dedication 1.0 Universal https://creativecommons.org/publicdomain/zero/1.0/
	enumeration	CC BY 4.0	Creative Commons Attribution 4.0 International https://creativecommons.org/licenses/by/4.0/
	enumeration	CC BY-SA 4.0	Creative Commons Attribution-Sharealike 4.0 International https://creativecommons.org/licenses/by-sa/4.0/
	enumeration	CC BY-NC 4.0	Creative Commons Attribution-Noncommercial 4.0 International https://creativecommons.org/licenses/by-nc/4.0/
	enumeration	CC BY-NC-SA 4.0	Creative Commons Attribution-Noncommercial-Sharealike 4.0 International https://creativecommons.org/licenses/by-nc-sa/4.0/
	enumeration	CC BY-ND 4.0	Creative Commons Attribution-NoDerivatives 4.0 International https://creativecommons.org/licenses/by-nd/4.0/
	enumeration	CC BY-NC-ND 4.0	Creative Commons Attribution-Noncommercial-NoDerivatives 4.0 International https://creativecommons.org/licenses/by-nc-nd/4.0/
	enumeration	MIT	The MIT License https://opensource.org/license/MIT
	enumeration		
Used by	Attribute	license/@licenseID	
Source	<pre> <xs:simpleType name="licenseIDType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the licenseID attribute</xs:documentation> <xs:documentation xml:lang="en">All standard specifications for licenses are drawn from https:// spdx.org/licenses/</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="CC0 1.0" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Public Domain Dedication 1.0 Universal</ xs:documentation> <xs:documentation>https://creativecommons.org/publicdomain/zero/1.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CC BY 4.0" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution 4.0 International</ xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CC BY-SA 4.0" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution-Sharealike 4.0 International</ xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by-sa/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CC BY-NC 4.0" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution-Noncommercial 4.0 International</xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by-nc/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CC BY-NC-SA 4.0" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Creative Commons Attribution-Noncommercial-Sharealike 4.0 International</xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by-nc-sa/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CC BY-ND 4.0" xml:lang="en"> </pre>		

```

<xs:annotation>
  <xs:documentation xml:lang="en">Creative Commons Attribution-Nonderivatives 4.0
International</xs:documentation>
  <xs:documentation>https://creativecommons.org/licenses/by-nd/4.0/</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="CC BY-NC-ND 4.0" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Creative Commons Attribution-Noncommercial-Nonderivatives 4.0
International</xs:documentation>
    <xs:documentation>https://creativecommons.org/licenses/by-nc-nd/4.0/</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="MIT" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">The MIT License</xs:documentation>
    <xs:documentation>https://opensource.org/license/MIT</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>

```

Simple Type relatedIDTypeType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for the relatedIDType attribute Applies to both Projects and Items Derived from the DataCite controlled vocabulary for relatedIdentifierType (v4.6+) https://datacite-metadataschema.readthedocs.io/en/4.6/appendices/appendix-1/relatedIdentifierType/ Appends a custom option for TigerData items: MFAID TigerData projects and subprojects should use DOI		
Diagram			
Type	restriction of xs:string		
Facets	enumeration	ARK	Archival Resource Key A URI designed to support long-term access to information objects.
	enumeration	arXiv	arXiv identifier arXiv.org is a repository of preprints of scientific papers in the fields of mathematics, physics, astronomy, computer science, quantitative biology, statistics, and quantitative finance.
	enumeration	bibcode	Astrophysics Data System bibliographic codes
	enumeration	CSTR	Common Science and Technology Resources Identifier CSTR is an identifier based on the Chinese National Standard GB/T 32843-2016 "Science and technology resource identification", providing a unique identification service for scientific data, papers, scientific institutions, researchers, scientific instruments, patents and other scientific and technological resources.
	enumeration	DOI	Digital Object Identifier A character string used to uniquely identify an object. A DOI name is divided into two parts, a prefix and a suffix, separated by a slash. Use this type to reference TigerData projects
	enumeration	EAN13	European Article Number (now renamed International Article Number, but retaining the original acronym)

		A 13-digit barcoding standard that is a superset of the original 12-digit Universal Product Code (UPC) system.
enumeration	EISSN	Electronic International Standard Serial Number ISSN used to identify periodicals in electronic form (eISSN or e-ISSN).
enumeration	Handle	This refers specifically to an ID in the Handle system operated by the Corporation for National Research Initiatives (CNRI).
enumeration	IGSN	International Generic Sample Number A code that uniquely identifies samples from our natural environment and related features-of-interest.
enumeration	ISBN	International Standard Book Number A unique numeric book identifier. There are 2 formats: a 10-digit ISBN format and a 13-digit ISBN.
enumeration	ISSN	International Standard Serial Number A unique 8-digit number used to identify a print or electronic periodical publication.
enumeration	ISTC	International Standard Text Code A unique "number" assigned to a textual work. An ISTC consists of 16 numbers and/or letters.
enumeration	LISSN	The linking ISSN or ISSN-L enables collocation or linking among different media versions of a continuing resource.
enumeration	LSID	Life Science Identifiers A unique identifier for data in the Life Science domain.
enumeration	PMID	PubMed identifier A unique number assigned to each PubMed record.
enumeration	PURL	Persistent Uniform Resource Locator A PURL has three parts: (1) a protocol, (2) a resolver address, and (3) a name.
enumeration	RRID	Research Resource Identifier A character string used to uniquely identify key inputs to an experiment including the so-called "key biological resources" as defined by the National Institutes of Health, and related tools such as core facilities and databases. An RRID name is divided into two parts, the authority and a local identifier, separated by an underscore.
enumeration	UPC	Universal Product Code A barcode symbology used for tracking trade items in stores. Its most common form, the UPC-A, consists of 12 numerical digits.
enumeration	URL	Uniform Resource Locator Also known as web address, a URL is a specific character string that constitutes a reference to a resource.
enumeration	URN	Uniform Resource Name A unique and persistent identifier of an electronic document.
enumeration	w3id	Permanent identifier for Web applications Mostly used to publish vocabularies and ontologies. The letters 'w3' stand for "World Wide Web".
enumeration	MFAID	A Mediaflux Asset ID number Include the domain and namespace to make the ID as persistent as possible

	Use this type to reference TigerData items
Used by	Attribute supplementalMetadata/relation/relation/@relatedIDType
Source	<pre> <xs:simpleType name="relatedIDTypeType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the relatedIDType attribute</xs:documentation> <xs:documentation xml:lang="en">Applies to both Projects and Items</xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite controlled vocabulary for relatedIdentifierType (v4.6+)</xs:documentation> <xs:documentation>https://datacite-metadataschema.readthedocs.io/en/4.6/appendices/appendix-1/ relatedIdentifierType</xs:documentation> <xs:documentation xml:lang="en">Appends a custom option for TigerData items: MFAID</ xs:documentation> <xs:documentation xml:lang="en">TigerData projects and subprojects should use DOI</ xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="ARK" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Archival Resource Key</xs:documentation> <xs:documentation xml:lang="en">A URI designed to support long-term access to information objects.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="arXiv" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">arXiv identifier</xs:documentation> <xs:documentation xml:lang="en">arXiv.org is a repository of preprints of scientific papers in the fields of mathematics, physics, astronomy, computer science, quantitative biology, statistics, and quantitative finance.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="bibcode" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Astrophysics Data System bibliographic codes</ xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CSTR" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Common Science and Technology Resources Identifier</ xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="DOI" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Digital Object Identifier</xs:documentation> <xs:documentation xml:lang="en">A character string used to uniquely identify an object. A DOI name is divided into two parts, a prefix and a suffix, separated by a slash.</xs:documentation> <xs:documentation xml:lang="en">Use this type to reference TigerData projects</ xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="EAN13" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">European Article Number (now renamed International Article Number, but retaining the original acronym)</xs:documentation> <xs:documentation xml:lang="en">A 13-digit barcoding standard that is a superset of the original 12-digit Universal Product Code (UPC) system.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="EISSN" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Electronic International Standard Serial Number</ xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Handle" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">This refers specifically to an ID in the Handle system operated by the Corporation for National Research Initiatives (CNRI).</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="IGSN" xml:lang="en"> <xs:annotation> </pre>

```

        <xs:documentation xml:lang="en">International Generic Sample Number</xs:documentation>
        <xs:documentation xml:lang="en">A code that uniquely identifies samples from our natural
environment and related features-of-interest.</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="ISBN" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">International Standard Book Number</xs:documentation>
        <xs:documentation xml:lang="en">A unique numeric book identifier. There are 2 formats: a 10-
digit ISBN format and a 13-digit ISBN.</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="ISSN" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">International Standard Serial Number</xs:documentation>
        <xs:documentation xml:lang="en">A unique 8-digit number used to identify a print or
electronic periodical publication.</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="ISTC" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">International Standard Text Code</xs:documentation>
        <xs:documentation xml:lang="en">A unique "number" assigned to a textual work. An ISTC
consists of 16 numbers and/or letters.</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="LISSN" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">The linking ISSN or ISSN-L enables collocation or linking
among different media versions of a continuing resource.</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="LSID" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">Life Science Identifiers</xs:documentation>
        <xs:documentation xml:lang="en">A unique identifier for data in the Life Science domain.</
xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="PMID" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">PubMed identifier</xs:documentation>
        <xs:documentation xml:lang="en">A unique number assigned to each PubMed record.</
xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="PURL" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">Persistent Uniform Resource Locator</xs:documentation>
        <xs:documentation xml:lang="en">A PURL has three parts: (1) a protocol, (2) a resolver
address, and (3) a name.</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="RRID" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">Research Resource Identifier</xs:documentation>
        <xs:documentation xml:lang="en">A character string used to uniquely identify key inputs
to an experiment including the so-called "key biological resources" as defined by the National
Institutes of Health, and related tools such as core facilities and databases. An RRID name
is divided into two parts, the authority and a local identifier, separated by an underscore.</
xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="UPC" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">Universal Product Code</xs:documentation>
        <xs:documentation xml:lang="en">A barcode symbology used for tracking trade items in stores.
Its most common form, the UPC-A, consists of 12 numerical digits.</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="URL" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">Uniform Resource Locator</xs:documentation>
        <xs:documentation xml:lang="en">Also known as web address, a URL is a specific character
string that constitutes a reference to a resource.</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="URN" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">Uniform Resource Name</xs:documentation>
        <xs:documentation xml:lang="en">A unique and persistent identifier of an electronic
document.</xs:documentation>
    </xs:annotation>
</xs:enumeration>

```

```

</xs:enumeration>
<xs:enumeration value="w3id" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Permanent identifier for Web applications</xs:documentation>
    <xs:documentation xml:lang="en">Mostly used to publish vocabularies and ontologies. The
letters 'w3' stand for "World Wide Web".</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="MFAID" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A Mediaflux Asset ID number</xs:documentation>
    <xs:documentation xml:lang="en">Include the domain and namespace to make the ID as
persistent as possible</xs:documentation>
    <xs:documentation xml:lang="en">Use this type to reference TigerData items</
xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>

```

Simple Type relationTypeType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for the relationType attribute Applies to both Projects and Items Derived from the DataCite controlled vocabulary for relationType (v4.6+) https://datacite-metadataschema.readthedocs.io/en/4.6/appendices/appendix-1/relationType/ The value is applied to object A to denote its relation to object B Appends custom options for TigerData: HasSubproject, IsSubprojectOf, HasItem, and IsItemOf Formal parent-child relationships between TigerData resources are called out in the parentProject field, and they can be further specified by relationType		
Diagram	Standard type that defines the controlled vocabulary for the relationType attribute Applies to both Projects and... Built-in primitive type. The string datatype represents character strings in XML.		
Type	restriction of xs:string		
Facets	enumeration	IsCitedBy	B includes A in a citation
	enumeration	Cites	A includes B in a citation
	enumeration	IsSupplementTo	A is a supplement to B
	enumeration	IsSupplementedBy	B is a supplement to A
	enumeration	IsContinuedBy	A is continued by the work B
	enumeration	Continues	A is a continuation of the work B
	enumeration	Describes	A describes B
	enumeration	IsDescribedBy	A is described by B
	enumeration	HasMetadata	A has additional metadata B
	enumeration	IsMetadataFor	Indicates additional metadata A for a resource B
	enumeration	HasVersion	A has a version B
	enumeration	IsVersionOf	A is a version of B
	enumeration	IsNewVersionOf	A is a new edition of B, where the new edition has been modified or updated
	enumeration	IsPreviousVersionOf	A is a previous edition of B
	enumeration	IsPartOf	A is a portion of B; may be used for elements of a series
			Do not use for formal parent-child relationships between TigerData projects, subprojects, or items
	enumeration	HasPart	A includes the part B
			Do not use for formal parent-child relationships between TigerData projects, subprojects, or items

	enumeration	IsPublishedIn	A is published inside B, but is independent of other things published inside of B
	enumeration	IsReferencedBy	A is used as a source of information by B
	enumeration	References	B is used as a source of information for A
	enumeration	IsDocumentedBy	B is documentation about/explaining A
	enumeration	Documents	A is documentation about/explaining B
	enumeration	IsCompiledBy	B is used to compile or create A
	enumeration	Compiles	B is the result of a compile or creation event using A
	enumeration	IsVariantFormOf	A is a variant or different form of B
	enumeration	IsOriginalFormOf	A is the original form of B
	enumeration	IsIdenticalTo	A is identical to B, for use when there is a need to register two separate instances of the same resource
	enumeration	IsReviewedBy	A is reviewed by B
	enumeration	Reviews	A is a review of B
	enumeration	IsDerivedFrom	B is a source upon which A is based
	enumeration	IsSourceOf	A is a source upon which B is based
	enumeration	IsRequiredBy	A is required by B
	enumeration	Requires	A requires B
	enumeration	Obsoletes	A replaces B
	enumeration	IsObsoletedBy	A is replaced by B
	enumeration	IsCollectedBy	A is collected by B
	enumeration	Collects	A collects B
	enumeration	IsTranslationOf	A is a translation of B
	enumeration	HasTranslation	A has a translation B
	enumeration	HasSubproject	A and B are both projects, and A includes B as a subproject Use only with formal relationships between TigerData projects and subprojects
	enumeration	IsSubprojectOf	A and B are both projects, and B includes A as a subproject Use only with formal relationships between TigerData projects and subprojects
	enumeration	HasItem	A is either a project or an item, B is an item, and A includes B Use only with formal relationships between TigerData projects and/or items
	enumeration	IsItemOf	A is an item, B is either a project or an item, and B includes A Use only with formal relationships between TigerData projects and/or items
Used by	Attribute	supplementalMetadata/relations/relation/@relationType	
Source	<pre><xs:simpleType name="relationTypeType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the relationType attribute</xs:documentation> <xs:documentation xml:lang="en">Applies to both Projects and Items</xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite controlled vocabulary for relationType (v4.6+)</xs:documentation> <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/appendices/appendix-1/ relationType/</xs:documentation> <xs:documentation xml:lang="en">The value is applied to object A to denote its relation to object B</xs:documentation> <xs:documentation xml:lang="en">Appends custom options for TigerData: HasSubproject, IsSubprojectOf, HasItem, and IsItemOf</xs:documentation> <xs:documentation xml:lang="en">Formal parent-child relationships between TigerData resources are called out in the parentProject field, and they can be further specified by relationType</ xs:documentation> </xs:annotation> <xs:restriction base="xs:string"></pre>		

```

<xs:enumeration value="IsCitedBy" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">B includes A in a citation</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Cites" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A includes B in a citation</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsSupplementTo" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is a supplement to B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsSupplementedBy" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">B is a supplement to A</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsContinuedBy" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is continued by the work B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Continues" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is a continuation of the work B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Describes" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A describes B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsDescribedBy" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is described by B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="HasMetadata" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A has additional metadata B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsMetadataFor" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">Indicates additional metadata A for a resource B</
xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="HasVersion" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A has a version B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsVersionOf" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is a version of B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsNewVersionOf" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is a new edition of B, where the new edition has been
modified or updated</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsPreviousVersionOf" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is a previous edition of B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsPartOf" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is a portion of B; may be used for elements of a series</
xs:documentation>
    <xs:documentation xml:lang="en">Do not use for formal parent-child relationships between
TigerData projects, subprojects, or items</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="HasPart" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A includes the part B</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```

```

        <xs:documentation xml:lang="en">Do not use for formal parent-child relationships between
        TigerData projects, subprojects, or items</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsPublishedIn" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is published inside B, but is independent of other things
        published inside of B</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsReferencedBy" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is used as a source of information by B</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="References" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">B is used as a source of information for A</
xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsDocumentedBy" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">B is documentation about/explaining A</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Documents" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is documentation about/explaining B</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsCompiledBy" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">B is used to compile or create A</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Compiles" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">B is the result of a compile or creation event using A</
xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsVariantFormOf" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is a variant or different form of B</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsOriginalFormOf" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is the original form of B</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsIdenticalTo" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is identical to B, for use when there is a need to
        register two separate instances of the same resource</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsReviewedBy" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is reviewed by B</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Reviews" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is a review of B</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsDerivedFrom" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">B is a source upon which A is based</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsSourceOf" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is a source upon which B is based</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsRequiredBy" xml:lang="en">
    <xs:annotation>
        <xs:documentation xml:lang="en">A is required by B</xs:documentation>
    </xs:annotation>
</xs:enumeration>

```

```

<xs:enumeration value="Requires" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A requires B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Obsoletes" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A replaces B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsObsoletedBy" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is replaced by B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsCollectedBy" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is collected by B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Collects" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A collects B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsTranslationOf" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is a translation of B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="HasTranslation" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A has a translation B</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="HasSubproject" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A and B are both projects, and A includes B as a
subproject</xs:documentation>
    <xs:documentation xml:lang="en">Use only with formal relationships between TigerData
projects and subprojects</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsSubprojectOf" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A and B are both projects, and B includes A as a
subproject</xs:documentation>
    <xs:documentation xml:lang="en">Use only with formal relationships between TigerData
projects and subprojects</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="HasItem" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is either a project or an item, B is an item, and A
includes B</xs:documentation>
    <xs:documentation xml:lang="en">Use only with formal relationships between TigerData
projects and/or items</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="IsItemOf" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">A is an item, B is either a project or an item, and B
includes A</xs:documentation>
    <xs:documentation xml:lang="en">Use only with formal relationships between TigerData
projects and/or items</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>

```

Simple Type dateTypeType

Namespace	No namespace
Annotations	Standard type that defines the controlled vocabulary for the dateType attribute Applies to both Projects and Items Derived from the DataCite controlled vocabulary for dateType (v4.6+) https://datacite-metadataschema.readthedocs.io/en/4.6/appendices/appendix-1/dateType/

Diagram	<pre>graph LR dateTypeType[dateTypeType] --- xsString[xs:string] dateTypeType --- callout1[Standard type that defines the controlled vocabulary for the dateType attribute. Applies to both Projects and...] xsString --- callout2[Built-in primitive type. The string datatype represents character strings in XML.]</pre>		
Type	restriction of xs:string		
Facets	enumeration	Accepted	The date that the publisher accepted the resource into their system.
	enumeration	Available	The date the resource is made publicly available. May be a range.
	enumeration	Copyrighted	The specific, documented date at which the resource receives a copyrighted status, if applicable.
	enumeration	Collected	The date or date range in which the resource content was collected.
	enumeration	Created	The date the resource itself was put together; this could refer to a timeframe in ancient history, a date range, or a single date for a final component, e.g., the finalised file with all the data.
	enumeration	Issued	The date that the resource is published or distributed, e.g., to a data centre.
	enumeration	Submitted	The date the creator submits the resource to the publisher. This could be different from Accepted if the publisher then applies a selection process.
	enumeration	Updated	The date of the last update to the resource, when the resource is being added to. May be a range.
	enumeration	Valid	The date or date range during which the dataset or resource is accurate.
	enumeration	Withdrawn	The date the resource is removed.
	enumeration	Other	Other date that does not fit into an existing category.
Used by	Attribute	otherDate/@dateType	
Source	<pre><xs:simpleType name="dateTypeType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the dateType attribute</xs:documentation> <xs:documentation xml:lang="en">Applies to both Projects and Items</xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite controlled vocabulary for dateType (v4.6+)</xs:documentation> <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/appendices/appendix-1/ dateType/</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Accepted" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The date that the publisher accepted the resource into their system.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Available" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The date the resource is made publicly available. May be a range.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Copyrighted" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The specific, documented date at which the resource receives a copyrighted status, if applicable.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Collected" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The date or date range in which the resource content was collected.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Created" xml:lang="en"> <xs:annotation></pre>		

```

        <xs:documentation xml:lang="en">The date the resource itself was put together; this could
        refer to a timeframe in ancient history, a date range, or a single date for a final component,
        e.g., the finalised file with all the data.</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Issued" xml:lang="en">
      <xs:annotation>
        <xs:documentation xml:lang="en">The date that the resource is published or distributed,
        e.g., to a data centre.</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Submitted" xml:lang="en">
      <xs:annotation>
        <xs:documentation xml:lang="en">The date the creator submits the resource to the publisher.
        This could be different from Accepted if the publisher then applies a selection process.</
        xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Updated" xml:lang="en">
      <xs:annotation>
        <xs:documentation xml:lang="en">The date of the last update to the resource, when the
        resource is being added to. May be a range.</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Valid" xml:lang="en">
      <xs:annotation>
        <xs:documentation xml:lang="en">The date or date range during which the dataset or resource
        is accurate.</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Withdrawn" xml:lang="en">
      <xs:annotation>
        <xs:documentation xml:lang="en">The date the resource is removed.</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Other" xml:lang="en">
      <xs:annotation>
        <xs:documentation xml:lang="en">Other date that does not fit into an existing category.</
        xs:documentation>
      </xs:annotation>
    </xs:enumeration>
  </xs:restriction>
</xs:simpleType>

```

Simple Type researchDomainNameType

Namespace	No namespace								
Annotations	Standard type that defines the controlled vocabulary for the researchDomain field Applies when projectPurpose is Research Options are limited to the 4 domains Princeton University uses to categorize academic departments								
Diagram	<pre> classDiagram class researchDomainNameType { <<simpleType>> } class xsString { <<primitive>> } researchDomainNameType -- > xsString </pre> Standard type that defines the controlled vocabulary for the researchDomain field Applies when projectPurpose is... Built-in primitive type. The string datatype represents character strings in XML.								
Type	restriction of xs:string								
Facets	<table border="1"> <tr> <td>enumeration</td><td>Natural Sciences</td></tr> <tr> <td>enumeration</td><td>Engineering</td></tr> <tr> <td>enumeration</td><td>Social Sciences</td></tr> <tr> <td>enumeration</td><td>Humanities</td></tr> </table>	enumeration	Natural Sciences	enumeration	Engineering	enumeration	Social Sciences	enumeration	Humanities
enumeration	Natural Sciences								
enumeration	Engineering								
enumeration	Social Sciences								
enumeration	Humanities								
Used by	<table border="1"> <tr> <td>Element</td><td>projectDescription/researchDomains/researchDomain</td></tr> </table>	Element	projectDescription/researchDomains/researchDomain						
Element	projectDescription/researchDomains/researchDomain								
Source	<pre> <xs:simpleType name="researchDomainNameType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the researchDomain field</xs:documentation> <xs:documentation xml:lang="en">Applies when projectPurpose is Research</xs:documentation> <xs:documentation xml:lang="en">Options are limited to the 4 domains Princeton University uses to categorize academic departments</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Natural Sciences" xml:lang="en"/> <xs:enumeration value="Engineering" xml:lang="en"/> </xs:restriction> </xs:simpleType> </pre>								

```
<xs:enumeration value="Social Sciences" xml:lang="en"/>
<xs:enumeration value="Humanities" xml:lang="en"/>
</xs:restriction>
</xs:simpleType>
```

Simple Type departmentType

Namespace	No namespace				
Annotations	Standard type that defines the allowable values for department Applies to all projects, regardless of projectPurpose Princeton department names typically start with a 2- or 3-character abbreviation, followed by a minus-dash, and then a short description; however, several exceptions exist The enforceable pattern is a string length from 6 to 38 (the real string max is 30, but we need to account for XML escape sequences for special characters)				
Diagram					
Type	restriction of xs:string				
Facets	<table> <tr> <td>minLength</td><td>6</td></tr> <tr> <td>maxLength</td><td>38</td></tr> </table>	minLength	6	maxLength	38
minLength	6				
maxLength	38				
Used by	<table> <tr> <td>Element</td><td>projectDescription/departments/department</td></tr> </table>	Element	projectDescription/departments/department		
Element	projectDescription/departments/department				
Source	<pre><xs:simpleType name="departmentType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the allowable values for department</xs:documentation> <xs:documentation xml:lang="en">Applies to all projects, regardless of projectPurpose</xs:documentation> <xs:documentation xml:lang="en">Princeton department names typically start with a 2- or 3-character abbreviation, followed by a minus-dash, and then a short description; however, several exceptions exist</xs:documentation> <xs:documentation xml:lang="en">The enforceable pattern is a string length from 6 to 38 (the real string max is 30, but we need to account for XML escape sequences for special characters)</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:minLength value="6"/> <xs:maxLength value="38"/> </xs:restriction> </xs:simpleType></pre>				

Simple Type visibilityType

Namespace	No namespace		
Annotations	Standard type to specify how open a resource's record should be to users Only those fields which have the attribute discoverable set to true can be made visible		
Diagram			
Type	restriction of xs:string		
Facets	enumeration	Restricted	Visibility is restricted to those assigned explicit roles on the resource
	enumeration	Limited	Visibility is limited to TigerData users
	enumeration	Open	Visibility is open to the general public
Used by	Element	storageAndAccess/projectVisibility	
Source	<pre><xs:simpleType name="visibilityType"> <xs:annotation></pre>		

```

<xs:documentation xml:lang="en">Standard type to specify how open a resource's record should be
to users</xs:documentation>
<xs:documentation xml:lang="en">Only those fields which have the attribute discoverable set to
true can be made visible</xs:documentation>
</xs:annotation>
<xs:restriction base="xs:string">
  <xs:enumeration value="Restricted" xml:lang="en">
    <xs:annotation>
      <xs:documentation xml:lang="en">Visibility is restricted to those assigned explicit roles on
the resource</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="Limited" xml:lang="en">
    <xs:annotation>
      <xs:documentation xml:lang="en">Visibility is limited to TigerData users</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="Open" xml:lang="en">
    <xs:annotation>
      <xs:documentation xml:lang="en">Visibility is open to the general public</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
</xs:restriction>
</xs:simpleType>

```

Simple Type storagePerformanceType


Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for storage performance values		
Diagram			
Type	restriction of xs:string		
Facets	enumeration	Eco	The most economical storage tier available in TigerData (lowest cost and smallest carbon footprint) Appropriate for long-term/low-use data, i.e. cold storage The typical implementation is an object store system, e.g. IBM Cloud Object Storage
	enumeration	Standard	The middle storage tier for TigerData, expected as a default Appropriate for data that is accessed occasionally but infrequently edited, i.e. cool storage The typical implementation is a network attached storage system, e.g. Dell PowerScale
	enumeration	Premium	The most performant storage tier available in TigerData Reserved for actively edited data that needs to be close to high performance computing systems, i.e. warm storage The typical implementation is a cluster file system, e.g. IBM General Parallel File System A special request may be required for this tier
Used by	Elements	storageAndAccess/storagePerformance/approvedValue, storageAndAccess/storagePerformance/requestedValue, storageAndAccess/storagePerformance/storagePerformanceSetting	
Source	<pre><xs:simpleType name="storagePerformanceType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for storage performance values</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Eco" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The most economical storage tier available in TigerData (lowest cost and smallest carbon footprint)</xs:documentation> </xs:annotation> <xs:documentation xml:lang="en">Appropriate for long-term/low-use data, i.e. cold storage</ xs:documentation> </xs:restriction> </xs:simpleType></pre>		

```

        <xs:documentation xml:lang="en">The typical implementation is an object store system, e.g.
        IBM Cloud Object Storage</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Standard" xml:lang="en">
      <xs:annotation>
        <xs:documentation xml:lang="en">The middle storage tier for TigerData, expected as a
        default</xs:documentation>
        <xs:documentation xml:lang="en">Appropriate for data that is accessed occasionally but
        infrequently edited, i.e. cool storage</xs:documentation>
        <xs:documentation xml:lang="en">The typical implementation is a network attached storage
        system, e.g. Dell PowerScale</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="Premium" xml:lang="en">
      <xs:annotation>
        <xs:documentation xml:lang="en">The most performant storage tier available in TigerData</
        xs:documentation>
        <xs:documentation xml:lang="en">Reserved for actively edited data that needs to be close to
        high performance computing systems, i.e. warm storage</xs:documentation>
        <xs:documentation xml:lang="en">The typical implementation is a cluster file system, e.g.
        IBM General Parallel File System</xs:documentation>
        <xs:documentation xml:lang="en">A special request may be required for this tier</
        xs:documentation>
      </xs:annotation>
    </xs:enumeration>
  </xs:restriction>
</xs:simpleType>

```

Simple Type fileEstimateType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for the numberOfFiles field		
Diagram	 <pre>graph LR fileEstimateType -- restriction --> xsString[xs:string]</pre> Standard type that defines the controlled vocabulary for the numberOfFiles field Built-in primitive type. The string datatype represents character strings in XML.		
Type	restriction of xs:string		
Facets	enumeration	Less than 10,000	The project is estimated to include less than 10,000 files at any one time
	enumeration	10k - 100k	The project is estimated to include between 10,000 and 100,000 files at any one time
	enumeration	100k - 1mil	The project is estimated to include between 100,000 and 1,000,000 files at any one time
	enumeration	More than 1 million	The project is estimated to include more than 1,000,000 files at any one time A special request may be required for this largest category
Used by	Element	storageAndAccess/numberOfFiles	
Source	<pre><xs:simpleType name="fileEstimateType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the numberOfFiles field</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Less than 10,000" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The project is estimated to include less than 10,000 files at any one time</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="10k - 100k" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The project is estimated to include between 10,000 and 100,000 files at any one time</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="100k - 1mil" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The project is estimated to include between 100,000 and 1,000,000 files at any one time</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType></pre>		

```
<xs:enumeration value="More than 1 million" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">The project is estimated to include more than 1,000,000
files at any one time</xs:documentation>
    <xs:documentation xml:lang="en">A special request may be required for this largest
category</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
```

Simple Type securityLevelType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for data security classification levels https://protectingourinfo.princeton.edu/classify Level 4 is beyond the scope of TigerData		
Diagram			
Type	restriction of xs:string		
Facets	enumeration	Level 0 - Public	Intended to be freely shared or disclosed inside and outside of Princeton University
	enumeration	Level 1 - Internal	Intended to be used only by Princeton University staff, faculty or students, and not for public disclosure
	enumeration	Level 2 - Confidential	Requires careful handling and protection due to contractual, regulatory, proprietary, or privacy considerations Requires TigerData Secure
	enumeration	Level 3 - Restricted	Subject to restrictive data security regulations and/or privacy protections, e.g. HIPAA Requires TigerData Secure
Used by	Elements	storageAndAccess/securityLevel/approvedValue, storageAndAccess/securityLevel/requestedValue, storageAndAccess/securityLevel/securityLevelSetting	
Source	<pre><xs:simpleType name="securityLevelType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for data security classification levels</xs:documentation> <xs:documentation>https://protectingourinfo.princeton.edu/classify</xs:documentation> <xs:documentation xml:lang="en">Level 4 is beyond the scope of TigerData</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Level 0 - Public" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Intended to be freely shared or disclosed inside and outside of Princeton University</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Level 1 - Internal" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Intended to be used only by Princeton University staff, faculty or students, and not for public disclosure</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Level 2 - Confidential" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Requires careful handling and protection due to contractual, regulatory, proprietary, or privacy considerations</xs:documentation> <xs:documentation xml:lang="en">Requires TigerData Secure</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Level 3 - Restricted" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Subject to restrictive data security regulations and/or privacy protections, e.g. HIPAA</xs:documentation> <xs:documentation xml:lang="en">Requires TigerData Secure</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType></pre>		

```
</xs:restriction>
</xs:simpleType>
```

Simple Type yesNoMaybeType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for request fields that allow uncertainty		
Diagram	yesNoMaybeType Standard type that defines the controlled vocabulary for request fields that allow uncertainty xs:string Built-in primitive type. The string datatype represents character strings in XML.		
Type	restriction of xs:string		
Facets	enumeration	No	The requester does not need the option (typically, the default) Usually, when approved, applied as a false setting
	enumeration	Yes	The requester needs the option Usually, when approved, applied as a true setting
	enumeration	Maybe	The requester is unsure whether they will need the option More conversation may be required to clarify before approval
Used by	Elements	storageAndAccess/accessPoints/globusEnable/requestedValue, storageAndAccess/accessPoints/hpcEnable/requestedValue, storageAndAccess/accessPoints/smbEnable/requestedValue	
Source	<pre><xs:simpleType name="yesNoMaybeType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for request fields that allow uncertainty</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="No" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The requester does not need the option (typically, the default)</xs:documentation> <xs:documentation xml:lang="en">Usually, when approved, applied as a false setting</ xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Yes" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The requester needs the option</xs:documentation> <xs:documentation xml:lang="en">Usually, when approved, applied as a true setting</ xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Maybe" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The requester is unsure whether they will need the option</ xs:documentation> <xs:documentation xml:lang="en">More conversation may be required to clarify before approval</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType></pre>		

Simple Type storageSystemType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for storageSystem		
Diagram			
Type	restriction of xs:string		

Facets	enumeration	TigerData	The storage system is TigerData (for all in-band projects)
	enumeration	/projects	The storage system is /projects (out-of-band)
	enumeration	Della /scratch/gpfs	The storage system is /scratch/gpfs on the Della cluster (out-of-band)
	enumeration	Tiger /scratch/gpfs	The storage system is /scratch/gpfs on the Tiger cluster (out-of-band)
	enumeration	Stellar /scratch/gpfs	The storage system is /scratch/gpfs on the Stellar cluster (out-of-band)
	enumeration	StellarAI /scratch/gpfs	The storage system is /scratch/gpfs on the StellarAI cluster (out-of-band)
Used by	Element	storageAndAccess/storageSystem	
Source	<pre><xs:simpleType name="storageSystemType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for storageSystem</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="TigerData" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The storage system is TigerData (for all in-band projects)</ xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="/projects" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The storage system is /projects (out-of-band)</ xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Della /scratch/gpfs" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The storage system is /scratch/gpfs on the Della cluster (out-of-band)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Tiger /scratch/gpfs" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The storage system is /scratch/gpfs on the Tiger cluster (out-of-band)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Stellar /scratch/gpfs" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The storage system is /scratch/gpfs on the Stellar cluster (out-of-band)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="StellarAI /scratch/gpfs" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The storage system is /scratch/gpfs on the StellarAI cluster (out-of-band)</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType></pre>		

Simple Type projectPurposeType

Namespace	No namespace	
Annotations	Standard type that defines the controlled vocabulary for the projectPurpose field	
Diagram	<pre> classDiagram class projectPurposeType class xs_string["xs:string"] projectPurposeType -- > xs_string </pre> Standard type that defines the controlled vocabulary for the projectPurpose field Built-in primitive type. The string datatype represents character strings in XML.	
Type	restriction of xs:string	
Facets	enumeration	Research The project is intended to contain mainly research data This includes projects for labs and research groups; it is not restricted to one specific research project

	enumeration	Administrative	The project is intended to contain mainly administrative data This includes library and other staff-managed archive use-cases
	enumeration	Teaching	The project is intended to contain mainly data related to teaching and learning activities
Used by	Element	additionalProjectInformation/projectPurpose	
Source	<pre><xs:simpleType name="projectPurposeType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the projectPurpose field</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Research" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The project is intended to contain mainly research data</ xs:documentation> <xs:documentation xml:lang="en">This includes projects for labs and research groups; it is not restricted to one specific research project</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Administrative" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The project is intended to contain mainly administrative data</xs:documentation> <xs:documentation xml:lang="en">This includes library and other staff-managed archive use- cases</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Teaching" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The project is intended to contain mainly data related to teaching and learning activities</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType></pre>		

Simple Type licenseType

Namespace	No namespace		
Annotations	Standard type that defines the controlled vocabulary for the license field All standard specifications for licenses are drawn from https://spdx.org/licenses/		
Diagram	<pre> graph LR licenseType[licenseType] --- xsString[xs:string] licenseType --> Note1[Standard type that defines the controlled vocabulary for the license field. All standard specifications for licenses are...] xsString --> Note2[Built-in primitive type. The string datatype represents character strings in XML.] </pre>		
Type	restriction of xs:string		
Facets	enumeration	Creative Commons Public Domain Dedication 1.0 Universal	CC0 1.0 https://creativecommons.org/publicdomain/zero/1.0/
	enumeration	Creative Commons Attribution 4.0 International	CC BY 4.0 https://creativecommons.org/licenses/by/4.0/
	enumeration	Creative Commons Attribution-Sharealike 4.0 International	CC BY-SA 4.0 https://creativecommons.org/licenses/by-sa/4.0/
	enumeration	Creative Commons Attribution-Noncommercial 4.0 International	CC BY-NC 4.0 https://creativecommons.org/licenses/by-nc/4.0/
	enumeration	Creative Commons Attribution-Noncommercial-Sharealike 4.0 International	CC BY-NC-SA 4.0 https://creativecommons.org/licenses/by-nc-sa/4.0/
	enumeration	Creative Commons Attribution-NoDerivatives 4.0 International	CC BY-ND 4.0 https://creativecommons.org/licenses/by-nd/4.0/

	enumeration	Creative Commons Attribution-Noncommercial-Noderivatives 4.0 International	CC BY-NC-ND 4.0 https://creativecommons.org/licenses/by-nc-nd/4.0/
	enumeration	The MIT License	MIT https://opensource.org/license/MIT
Used by	Element	license	
Source	<pre> <xs:simpleType name="licenseType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type that defines the controlled vocabulary for the license field</xs:documentation> <xs:documentation xml:lang="en">All standard specifications for licenses are drawn from https:// spdx.org/licenses/</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Creative Commons Public Domain Dedication 1.0 Universal" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">CC0 1.0</xs:documentation> <xs:documentation>https://creativecommons.org/publicdomain/zero/1.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Creative Commons Attribution 4.0 International" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">CC BY 4.0</xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Creative Commons Attribution-Sharealike 4.0 International" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">CC BY-SA 4.0</xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by-sa/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Creative Commons Attribution-Noncommercial 4.0 International" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">CC BY-NC 4.0</xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by-nc/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Creative Commons Attribution-Noncommercial-Sharealike 4.0 International" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">CC BY-NC-SA 4.0</xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by-nc-sa/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Creative Commons Attribution-Noderivatives 4.0 International" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">CC BY-ND 4.0</xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by-nd/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Creative Commons Attribution-Noncommercial-Noderivatives 4.0 International" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">CC BY-NC-ND 4.0</xs:documentation> <xs:documentation>https://creativecommons.org/licenses/by-nc-nd/4.0/</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="The MIT License" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">MIT</xs:documentation> <xs:documentation xml:lang="en">https://opensource.org/license/MIT</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre>		

Simple Type statusType

Namespace	No namespace
Annotations	Standard type that defines the controlled vocabulary for the status field Applies only to Projects


```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="Active" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">The project is live: approved and available to users</
xs:documentation>
    <xs:documentation xml:lang="en">Applies if the submission field has complete approvedBy and
approvalDateTime subfields, the frontend has confirmed the project's collection ID in Mediaflux,
and the project has been neither retired nor published</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Retired" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">The project has been retired due to lack of use or by
request of the Data Sponsor or the Data Manager</xs:documentation>
    <xs:documentation xml:lang="en">Applies if the the retirement field has complete approvedBy
and approvalDateTime subfields</xs:documentation>
    <xs:documentation xml:lang="en">If the retirementDate field is filled, then the change to
Retired status is expected to occur on or after the retirementDate</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="Published" xml:lang="en">
  <xs:annotation>
    <xs:documentation xml:lang="en">The project has been published</xs:documentation>
    <xs:documentation xml:lang="en">Applies if the the publication field has complete approvedBy
and approvalDateTime subfields</xs:documentation>
    <xs:documentation xml:lang="en">If the publicationDate field is filled, then the change to
Published status is expected to occur on or after the publicationDate</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>

```

Simple Type mediafluxAssetIDType

Namespace	No namespace				
Annotations	Standard type used for Mediaflux Asset ID (MFAID) values Per Mediaflux Concepts v 0.10 (2021), asset IDs must be in the range [1,9223372036854775807]				
Diagram					
Type	restriction of xs:integer				
Facets	<table> <tr> <td>maxInclusive</td><td>9223372036854775807</td></tr> <tr> <td>minInclusive</td><td>1</td></tr> </table>	maxInclusive	9223372036854775807	minInclusive	1
maxInclusive	9223372036854775807				
minInclusive	1				
Used by	Element itemFields/itemID				
Source	<pre> <xs:simpleType name="mediafluxAssetIDType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for Mediaflux Asset ID (MFAID) values</ xs:documentation> <xs:documentation xml:lang="en">Per Mediaflux Concepts v 0.10 (2021), asset IDs must be in the range [1,9223372036854775807]</xs:documentation> </xs:annotation> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="9223372036854775807"/> </xs:restriction> </xs:simpleType> </pre>				

Complex Type(s)

Complex Type projectIDValue

Namespace	No namespace
Annotations	Standard type for the values of projectID and parentProject fields Applies to both Projects (projectID and parentProject) and Items (parentProject)

Diagram					
Type	extension of doiType				
Type hierarchy	- xs:string - doiType - projectIDValueType				
Used by	Elements parentProject, projectFields/projectID				
Attributes	QName	Type	Fixed	Use	
	projectIDType	xs:string	DOI	optional	
	Makes explicit that the project ID is always given as a DOI				
Source	<pre> <xs:complexType name="projectIDValueType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type for the values of projectID and parentProject fields</xs:documentation> <xs:documentation xml:lang="en">Applies to both Projects (projectID and parentProject) and Items (parentProject)</xs:documentation> </xs:annotation> <xs:simpleContent> <xs:extension base="doiType"> <xs:attribute name="projectIDType" type="xs:string" fixed="DOI"> <xs:annotation> <xs:documentation xml:lang="en">Makes explicit that the project ID is always given as a DOI</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </pre>				

Complex Type textType

Namespace	No namespace
Annotations	Standard type used for generic text values
Diagram	
Type	extension of textLimitType
Type hierarchy	- xs:string - textLimitType - textType
Used by	Element provenanceSubfields/eventNote/message

Attributes	QName	Type	Default	Use	
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
		<div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p> </div>			
Source	<pre><xs:complexType name="textType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for generic text values</xs:documentation> </xs:annotation> <xs:simpleContent> <xs:extension base="textLimitType"> <xs:attribute ref="xml:lang" default="en"/> </xs:extension> </xs:simpleContent> </xs:complexType></pre>				

Complex Type titleType

Namespace	No namespace				
Annotations	Standard type used for title values				
Diagram					
Type	extension of titleLimitType				
Type hierarchy	- xs:string - titleLimitType - titleType				
Used by	Elements	duaReference/duaID, duaReference/duaTitle, duaReference/grantorName, fundingReference/awardTitle, fundingReference/funderID, fundingReference/funderName, supplementalMetadata/extendedMetadataSchemas/extendedMetadataSchema, title			
Attributes	QName	Type	Default	Use	
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
		lang (as an attribute name) denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification. Notes			

	QName	Type	Default	Use	
		<p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p>			
Source		<pre><xs:complexType name="titleType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for title values</xs:documentation> </xs:annotation> <xs:simpleContent> <xs:extension base="titleLimitType"> <xs:attribute ref="xml:lang" default="en"/> </xs:extension> </xs:simpleContent> </xs:complexType></pre>			

Complex Type shortTextType

Namespace	No namespace														
Annotations	Standard type used for short text values in elements (e.g., itemResourceType and keyword)														
Diagram	The diagram illustrates the structure of the <code>shortTextType</code>. It is a complex type that extends <code>shortTextLimitType</code>. The <code>shortTextType</code> has a base type <code>shortTextLimitType</code> and an attribute <code>xml:lang</code> with a default value of <code>en</code>. A note explains that <code>xml:lang</code> denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.														
Type	extension of shortTextLimitType														
Type hierarchy	• xs:string • shortTextLimitType • shortTextType														
Used by	Elements itemResourceType, projectResourceType, supplementalMetadata/keywords/keyword														
Attributes	<table><thead><tr><th>QName</th><th>Type</th><th>Default</th><th>Use</th><th></th></tr></thead><tbody><tr><td>xml:lang</td><td>union of(xs:language, restriction of xs:string)</td><td>en</td><td>optional</td><td></td></tr></tbody></table>	QName	Type	Default	Use		xml:lang	union of(xs:language, restriction of xs:string)	en	optional		<div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h4>Notes</h4> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registryfor further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p> </div>			
QName	Type	Default	Use												
xml:lang	union of(xs:language, restriction of xs:string)	en	optional												
Source	<xs:complexType name="shortTextType">														

```
<xs:annotation>
  <xs:documentation xml:lang="en">Standard type used for short text values in elements (e.g.,
itemResourceType and keyword)</xs:documentation>
</xs:annotation>
<xs:simpleContent>
  <xs:extension base="shortTextLimitType">
    <xs:attribute ref="xml:lang" default="en"/>
  </xs:extension>
</xs:simpleContent>
</xs:complexType>
```

Complex Type longTextType

Namespace	No namespace				
Annotations	Standard type used for long text values (e.g., description)				
Diagram					
Type	extension of longTextLimitType				
Type hierarchy	- xs:string - longTextLimitType - longTextType				
Used by	Element description				
Attributes	QName	Type	Default	Use	
	xml:lang	union of(xs:language, restriction of xs:string)	en	optional	
lang (as an attribute name) denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification. Notes Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility. See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txt and the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registry for further information. The union allows for the 'un-declaration' of xml:lang with the empty string.					
Source	<pre><xs:complexType name="longTextType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for long text values (e.g., description)</xs:documentation> </xs:annotation> <xs:simpleContent> <xs:extension base="longTextLimitType"> <xs:attribute ref="xml:lang" default="en"/> </xs:extension> </xs:simpleContent> </xs:complexType></pre>				

Complex Type userType

Namespace	No namespace
-----------	--------------

Annotations	Standard type used for user fields Given the required attribute <code>userID</code>, all sub-elements are optional, so the element for a given user field may be left empty If the sub-element <code>netID</code> is included, its value should match that of the <code>userID</code> attribute				
Diagram					
Used by	Elements	dataManager, dataSponsor, dataUser, storageAndAccess/accessPoints/globusCollection/globusOwner			
Model	netID{0,1} , PUID{0,1} , orcid{0,1} , fullName{0,1} , givenName{0,1} , familyName{0,1} , nameDate{0,1} , alternativeNameIdentifier{0,3}				
Children	PUID, alternativeNameIdentifier, familyName, fullName, givenName, nameDate, netID, orcid				
Attributes	QName	Type	Fixed	Use	
	userID	netIDType		required	
	Specifies the (locally) unique user ID				

	QName	Type	Fixed	Use	
		If a value is given for the sub-element netID, then it should match the value given for userID			
	userIDType	xs:string	NetID	optional	
		Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute			
Source	<pre><xs:complexType name="userType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for user fields</xs:documentation> <xs:documentation xml:lang="en">Given the required attribute userID, all sub-elements are optional, so the element for a given user field may be left empty</xs:documentation> <xs:documentation xml:lang="en">If the sub-element netID is included, its value should match that of the userID attribute</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="netID" type="netIDType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Princeton University NetID (also called the OIT NetID) is the name or user-id that identifies a person to a computer system or electronic service at Princeton.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="PUID" type="puidType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Princeton University ID (aka Student ID, Employee ID, EMPLID, Princeton ID, or PUID) is a unique nine digit identifier assigned to an individual who has an official affiliation with the University.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="orcid" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The ORCID ID URL for the person in a given role, if available and if verified as valid against the ORCID API upon entry.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="fullName" type="titleLimitType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The full name of the person in a given role, verified in the format family-comma-given and matching the corresponding given and family name fields, if available.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="givenName" type="titleLimitType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The given name(s) of the person in a given role. If the person has multiple given names, then all should be included in this field, along with any suffixes.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="familyName" type="titleLimitType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The family name(s) of the person in a given role. If the person has multiple family names, then all should be included in this field.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="nameDate" type="dateOrRangeType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The date at which the name metadata was recorded.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="alternativeNameIdentifier" minOccurs="0" maxOccurs="3"> <xs:annotation> <xs:documentation xml:lang="en">Records alternative (non-ORCID) identifier(s) for the person in a given role.</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="titleLimitType"> <xs:attribute name="nameIdentifierSchema" type="shortAttributeType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">The name of the schema to which the name identifier belongs (required when an alternative name identifier is given).</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="schemaURI" type="xs:anyURI" use="required"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the schema to which the name identifier belongs (required when an alternative name identifier is given).</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType></pre>				

```

        </xs:attribute>
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
</xs:element>
</xs:sequence>
<xs:attribute name="userID" type="netIDType" use="required">
  <xs:annotation>
    <xs:documentation xml:lang="en">Specifies the (locally) unique user ID</xs:documentation>
    <xs:documentation xml:lang="en">If a value is given for the sub-element netID, then it should
match the value given for userID</xs:documentation>
  </xs:annotation>
</xs:attribute>
<xs:attribute name="userIDType" type="xs:string" fixed="NetID">
  <xs:annotation>
    <xs:documentation xml:lang="en">Makes explicit that Princeton NetIDs are always used as the
identifier for the userID attribute</xs:documentation>
  </xs:annotation>
</xs:attribute>
</xs:complexType>

```

Complex Type shortUserType

Namespace	No namespace				
Annotations	Standard type used for user fields Given the required attribute userID, all sub-elements are optional, so the element for a given user field may be left empty If the sub-element netID is included, its value should match that of the userID attribute				
Diagram					
Used by	Elements	provenanceSubfields/approvedBy, provenanceSubfields/deniedBy, provenanceSubfields/event-Note/noteBy, provenanceSubfields/requestedBy			
Model	netID{0,1} , PUID{0,1} , orcid{0,1}				
Children	PUID, netID, orcid				
Attributes	QName	Type	Fixed	Use	
	userID	netIDType		required	
		Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID			
	userIDType	xs:string	NetID	optional	

	QName	Type	Fixed	Use
		Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute		
Source	<pre> <xs:complexType name="shortUserType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for user fields</xs:documentation> <xs:documentation xml:lang="en">Given the required attribute userID, all sub-elements are optional, so the element for a given user field may be left empty</xs:documentation> <xs:documentation xml:lang="en">If the sub-element netID is included, its value should match that of the userID attribute</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="netID" type="netIDType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Princeton University NetID (also called the OIT NetID) is the name or user-id that identifies a person to a computer system or electronic service at Princeton.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="PUID" type="puidType" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The Princeton University ID (aka Student ID, Employee ID, EMPLID, Princeton ID, or PUID) is a unique nine digit identifier assigned to an individual who has an official affiliation with the University.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="orcid" type="xs:anyURI" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The ORCID ID URL for the person in a given role, if available and if verified as valid against the ORCID API upon entry.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> <xs:attribute name="userID" type="netIDType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Specifies the (locally) unique user ID</xs:documentation> <xs:documentation xml:lang="en">If a value is given for the sub-element netID, then it should match the value given for userID</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="userIDType" type="xs:string" fixed="NetID"> <xs:annotation> <xs:documentation xml:lang="en">Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute</xs:documentation> </xs:annotation> </xs:attribute> </xs:complexType> </pre>			

Complex Type pathType

Namespace	No namespace
Annotations	Standard type used for file path values
Diagram	<pre> classDiagram class pathType { +pathSafeType +protocol : protocolType } class pathSafeType { } class protocolType { +Type : protocolType +Default : NFS } pathType -- > pathSafeType pathType --> protocolType : protocol </pre> The diagram illustrates the structure of the <code>pathType</code> complex type. It is an extension of the <code>pathSafeType</code> base type. The <code>pathType</code> has an attribute named <code>protocol</code> of type <code>protocolType</code>, with a default value of <code>NFS</code>. A note indicates that <code>protocolType</code> defines how the path is written.
Type	extension of pathSafeType
Type hierarchy	- xs:string - pathSafeType - pathType
Used by	Elements projectDescription/projectDirectory/approvedValue, projectDescription/projectDirectory/projectDirectoryPath, projectDescription/projectDirectory/requestedValue

Attributes	QName	Type	Default	Use	
	protocol	protocolType	NFS	optional	
		The storage connection protocol that defines how the path is written			
Source	<pre><xs:complexType name="pathType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for file path values</xs:documentation> </xs:annotation> <xs:simpleContent> <xs:extension base="pathSafeType"> <xs:attribute name="protocol" type="protocolType" default="NFS"> <xs:annotation> <xs:documentation xml:lang="en">The storage connection protocol that defines how the path is written</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType></pre>				

Complex Type storageQuantityType

Namespace	No namespace		
Annotations	Standard type used for storage quantity values		
Diagram			
Used by	Elements	storageAndAccess/storageCapacity/approvedValue, storageAndAccess/storageCapacity/requestedValue, storageAndAccess/storageCapacity/storageCapacitySetting	
Model	size , unit		
Children	size, unit		
Source	<pre><xs:complexType name="storageQuantityType"> <xs:annotation> <xs:documentation xml:lang="en">Standard type used for storage quantity values</ xs:documentation> </xs:annotation> <xs:sequence minOccurs="0" maxOccurs="1"> <xs:element name="size" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The numeric size of the storage quantity</xs:documentation> <xs:documentation xml:lang="en">The practical limits for floating point values set by Mediaflux are the range [4.9E-324,1.7976931348623157E308]</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:double"> <xs:minExclusive value="0"/> <xs:maxInclusive value="1000000000000000"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="unit" type="byteUnitType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The logical byte unit for the storage quantity (base-10)</ xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType></pre>		

Attribute(s)

Attribute projectIDValueType / @projectIDType

Namespace	No namespace
Annotations	Makes explicit that the project ID is always given as a DOI

Type	xs:string
Properties	fixed: DOI
Used by	Complex Type projectIDValueType
Source	<pre><xs:attribute name="projectIDType" type="xs:string" fixed="DOI"> <xs:annotation> <xs:documentation xml:lang="en">Makes explicit that the project ID is always given as a DOI</ </xs:annotation> </xs:attribute></pre>

Attribute @inherited

Namespace	No namespace
Annotations	Standard attribute to specify whether a given field's value should be inherited by any child resources Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)
Type	xs:boolean
Properties	content: simple
Used by	Elements additionalProjectInformation/dataUseAgreement, additionalProjectInformation/funded, additionalProjectInformation/projectPurpose, additionalProjectInformation/provisionalProject, alternativeID, dataManager, dataSponsor, dataUser, description, duaReference, endDate, fundingReference, itemFields/itemID, itemResourceType, language, license, otherDate, parentProject, projectDescription/departments/department, projectDescription/projectDirectory, projectDescription/researchDomains/researchDomain, projectFields/projectID, projectFields/projectProvenance/publication, projectFields/projectProvenance/retirement, projectFields/projectProvenance/revisions/revision, projectFields/projectProvenance/status, projectFields/projectProvenance/submission, projectResourceType, publicationDate, retirementDate, schemaVersion, startDate, storageAndAccess/accessPoints, storageAndAccess/numberOfFiles, storageAndAccess/projectVisibility, storageAndAccess/securityLevel, storageAndAccess/storageCapacity, storageAndAccess/storagePerformance, storageAndAccess/storageSystem, supplementalMetadata/extendedMetadataSchemas/extendedMetadataSchema, supplementalMetadata/keywords/keyword, supplementalMetadata/relations/relation, title
Source	<pre><xs:attribute name="inherited" type="xs:boolean"> <xs:annotation> <xs:documentation xml:lang="en">Standard attribute to specify whether a given field's value should be inherited by any child resources</xs:documentation> <xs:documentation xml:lang="en">Inheritance is limited to the applicability of the field to the child resource (e.g., researchDomain may be inherited by a subproject but not an item)</ </xs:annotation> </xs:attribute></pre>

Attribute @discoverable

Namespace	No namespace
Annotations	Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems
Type	xs:boolean
Properties	content: simple
Used by	Elements additionalProjectInformation/dataUseAgreement, additionalProjectInformation/funded, additionalProjectInformation/projectPurpose, additionalProjectInformation/provisionalProject, alternativeIDs, dataManager, dataSponsor, dataUser, description, duaReferences, fundingReferences, itemDates, itemFields/itemID, itemResourceType, languages, licenses, parentProject, projectDates, projectDescription/departments, projectDescription/projectDirectory, projectDescription/researchDomains, projectFields/projectID, projectFields/projectProvenance/publication, projectFields/projectProvenance/retirement, projectFields/projectProvenance/revisions, projectFields/projectProvenance/status, projectFields/projectProvenance/submission, projectResourceType, schemaVersion, storageAndAccess/accessPoints, storageAndAccess/numberOfFiles, storageAndAccess/projectVisibility, storageAndAccess/securityLevel, storageAndAccess/storageCapacity, storageAndAccess/storagePerformance, storageAndAccess/storageSystem, supplementalMetadata/extendedMetadataSchemas, supplementalMetadata/keywords, supplementalMetadata/relations, title
Source	<pre><xs:attribute name="discoverable" type="xs:boolean"> <xs:annotation> <xs:documentation xml:lang="en">Standard attribute to specify whether a given field should be discoverable to search operations within TigerData systems</xs:documentation> </xs:annotation> </xs:attribute></pre>

```
</xs:annotation>
</xs:attribute>
```

Attribute @trackingLevel

Namespace	No namespace		
Annotations	Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)		
Type	trackingLevelType		
Properties	content:	simple	
Facets	enumeration	ResourceRecord	The respective field should be included in any long-term or crosswalked records for the resource
	enumeration	InternalUseOnly	The respective field is intended for internal (Princeton) use only
Used by	Elements	additionalProjectInformation/dataUseAgreement, additionalProjectInformation/funded, additionalProjectInformation/projectPurpose, additionalProjectInformation/provisionalProject, alternativeIDs, dataManager, dataSponsor, dataUsers, description, duaReferences, fundingReferences, itemDates, itemFields/itemID, itemResourceType, languages, licenses, parentProject, projectDates, projectDescription/departments, projectDescription/projectDirectory, projectDescription/researchDomains, projectFields/projectID, projectFields/projectProvenance/publication, projectFields/projectProvenance/retirement, projectFields/projectProvenance/revisions, projectFields/projectProvenance/status, projectFields/projectProvenance/submission, projectResourceType, schemaVersion, storageAndAccess/accessPoints, storageAndAccess/numberOfFiles, storageAndAccess/projectVisibility, storageAndAccess/securityLevel, storageAndAccess/storageCapacity, storageAndAccess/storagePerformance, storageAndAccess/storageSystem, supplementalMetadata/extendedMetadataSchemas, supplementalMetadata/key-words, supplementalMetadata/relations, title	
Source	<pre><xs:attribute name="trackingLevel" type="trackingLevelType"> <xs:annotation> <xs:documentation xml:lang="en">Standard attribute to specify the tracking level of a given field (ResourceRecord or InternalUseOnly)</xs:documentation> </xs:annotation> </xs:attribute></pre>		

Attribute @resourceTypeGeneral

Namespace	No namespace		
Annotations	Standard attribute to specify the general type for a resource, following the controlled vocabulary in resourceTypeGeneralType		
	Derived from the DataCite definition for resourceTypeGeneral (v4.6+)		
Type	resourceTypeGeneralType		
Properties	content:	simple	
Facets	enumeration	Audiovisual	A series of visual representations imparting an impression of motion when shown in succession. May or may not include sound.
	enumeration	Award	An umbrella term for resources provided to individual(s) or organization(s) in support of research, academic output, or training, such as a specific instance of funding, grant, investment, sponsorship, scholarship, recognition, or non-monetary materials.
	enumeration	Book	A medium for recording information in the form of writing or images, typically composed of many pages bound together and protected by a cover.
	enumeration	BookChapter	One of the main divisions of a book.
	enumeration	Collection	An aggregation of resources, which may encompass collections of one resourceType as well as those of mixed types. A collection is described as a group; its parts may also be separately described.
	enumeration	ComputationalNotebook	A virtual notebook environment used for literate programming.
	enumeration	ConferencePaper	Article that is written with the goal of being accepted to a conference.
	enumeration	ConferenceProceeding	Collection of academic papers published in the context of an academic conference.

enumeration	DataPaper	A factual and objective publication with a focused intent to identify and describe specific data, sets of data, or data collections to facilitate discoverability.
enumeration	Dataset	Data encoded in a defined structure.
enumeration	Dissertation	A written essay, treatise, or thesis, especially one written by a candidate for the degree of Doctor of Philosophy.
enumeration	Event	A non-persistent, time-based occurrence.
enumeration	Image	A visual representation other than text.
enumeration	Instrument	A device, tool or apparatus used to obtain, measure and/or analyze data.
enumeration	InteractiveResource	A resource requiring interaction from the user to be understood, executed, or experienced.
enumeration	Journal	A scholarly publication consisting of articles that is published regularly throughout the year.
enumeration	JournalArticle	A written composition on a topic of interest, which forms a separate part of a journal.
enumeration	Model	An abstract, conceptual, graphical, mathematical or visualization model that represents empirical objects, phenomena, or physical processes.
enumeration	OutputManagementPlan	A formal document that outlines how research outputs are to be handled both during a research project and after the project is completed. Use this resource type for items that serve as the Data Management Plan (DMP) for a TigerData project.
enumeration	PeerReview	Evaluation of scientific, academic, or professional work by others working in the same field.
enumeration	PhysicalObject	A physical object or substance.
enumeration	Preprint	A version of a scholarly or scientific paper that precedes formal peer review and publication in a peer-reviewed scholarly or scientific journal.
enumeration	Project	A planned endeavor or activity, frequently collaborative, intended to achieve a particular aim using allocated resources such as budget, time, and expertise. Use this resource type for all TigerData projects and subprojects.
enumeration	Report	A document that presents information in an organized format for a specific audience and purpose.
enumeration	Service	An organized system of apparatus, appliances, staff, etc., for supplying some function(s) required by end users.
enumeration	Software	A computer program other than a computational notebook, in either source code (text) or compiled form. Use this type for general software components supporting scholarly research. Use the "ComputationalNotebook" value for virtual notebooks.
enumeration	Sound	A resource primarily intended to be heard.
enumeration	Standard	Something established by authority, custom, or general consent as a model, example, or point of reference.
enumeration	StudyRegistration	A detailed, time-stamped description of a research plan, often openly shared in a registry or published in a journal before the study is conducted to lend accountability and transparency in the hypothesis generating and testing process.
enumeration	Text	A resource consisting primarily of words for reading that is not covered by any other textual resource type in this list.
enumeration	Workflow	A structured series of steps which can be executed to produce a final outcome, allowing

		users a means to specify and enact their work in a more reproducible manner.	
	enumeration	Other	A type of resource not otherwise described by defined types.
	enumeration	README	A simple text file used to document important information about a containing resource. Use this resource type for all items serving as README files for TigerData projects.
	enumeration	DataDocumentation	A resource used to document detailed information about data in a containing resource (e.g., a codebook or data dictionary). Use this resource type for items serving as supplemental documentation to the README for a TigerData project.
Used by	Elements	itemResourceType, projectResourceType, supplementalMetadata/relations/relation	
Source	<pre><xs:attribute name="resourceTypeGeneral" type="resourceTypeGeneralType"> <xs:annotation> <xs:documentation xml:lang="en">Standard attribute to specify the general type for a resource, following the controlled vocabulary in resourceTypeGeneralType</xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite definition for resourceTypeGeneral (v4.6+)</xs:documentation> </xs:annotation> </xs:attribute></pre>		

Attribute @approved

Namespace	No namespace		
Annotations	Standard attribute to specify whether a given field has an approved value Applies to fields which have a request-approval framework, including projectDirectory, storageCapacity, and storagePerformance		
Type	xs:boolean		
Properties	content:	simple	
Used by	Elements	projectDescription/projectDirectory, storageAndAccess/accessPoints/globusEnable, storageAndAccess/accessPoints/hpcEnable, storageAndAccess/accessPoints/smbEnable, storageAndAccess/securityLevel, storageAndAccess/storageCapacity, storageAndAccess/storagePerformance	
Source	<pre><xs:attribute name="approved" type="xs:boolean"> <xs:annotation> <xs:documentation xml:lang="en">Standard attribute to specify whether a given field has an approved value</xs:documentation> <xs:documentation xml:lang="en">Applies to fields which have a request-approval framework, including projectDirectory, storageCapacity, and storagePerformance</xs:documentation> </xs:annotation> </xs:attribute></pre>		

Attribute userType / alternativeNameIdentifier / @nameIdentifierSchema

Namespace	No namespace		
Annotations	The name of the schema to which the name identifier belongs (required when an alternative name identifier is given).		
Type	shortAttributeType		
Properties	use:	required	
Facets	minLength	0	
	maxLength	60	
Used by	Element	userType/alternativeNameIdentifier	
Source	<pre><xs:attribute name="nameIdentifierSchema" type="shortAttributeType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">The name of the schema to which the name identifier belongs (required when an alternative name identifier is given).</xs:documentation> </xs:annotation> </xs:attribute></pre>		

Attribute userType / alternativeNameIdentifier / @schemaURI

Namespace	No namespace		
-----------	--------------	--	--

Annotations	The URI of the schema to which the name identifier belongs (required when an alternative name identifier is given).
Type	xs:anyURI
Properties	use: required
Used by	Element userType/alternativeNameIdentifier
Source	<pre><xs:attribute name="schemaURI" type="xs:anyURI" use="required"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the schema to which the name identifier belongs (required when an alternative name identifier is given).</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute userType / @userID

Namespace	No namespace
Annotations	Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID
Type	netIDType
Properties	use: required
Facets	pattern [a-z0-9-]{2,10}
Used by	Complex Type userType
Source	<pre><xs:attribute name="userID" type="netIDType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Specifies the (locally) unique user ID</xs:documentation> <xs:documentation xml:lang="en">If a value is given for the sub-element netID, then it should match the value given for userID</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute userType / @userIDType

Namespace	No namespace
Annotations	Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute
Type	xs:string
Properties	fixed: NetID
Used by	Complex Type userType
Source	<pre><xs:attribute name="userIDType" type="xs:string" fixed="NetID"> <xs:annotation> <xs:documentation xml:lang="en">Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute shortUserType / @userID

Namespace	No namespace
Annotations	Specifies the (locally) unique user ID If a value is given for the sub-element netID, then it should match the value given for userID
Type	netIDType
Properties	use: required
Facets	pattern [a-z0-9-]{2,10}
Used by	Complex Type shortUserType
Source	<pre><xs:attribute name="userID" type="netIDType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Specifies the (locally) unique user ID</xs:documentation> <xs:documentation xml:lang="en">If a value is given for the sub-element netID, then it should match the value given for userID</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute shortUserType / @userIDType

Namespace	No namespace
Annotations	Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute
Type	xs:string
Properties	fixed: NetID
Used by	Complex Type shortUserType
Source	<pre><xs:attribute name="userIDType" type="xs:string" fixed="NetID"> <xs:annotation> <xs:documentation xml:lang="en">Makes explicit that Princeton NetIDs are always used as the identifier for the userID attribute</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute pathType / @protocol

Namespace	No namespace		
Annotations	The storage connection protocol that defines how the path is written		
Type	protocolType		
Properties	default:	NFS	
Facets	enumeration	NFS	Network File System (version not tracked)
	enumeration	SMB	Server Message Block (version not tracked) Used interchangeably with Common Internet File System (CIFS)
	enumeration	S3	Amazon Simple Storage Service (version not tracked)
Used by	Complex Type	pathType	
Source	<pre><xs:attribute name="protocol" type="protocolType" default="NFS"> <xs:annotation> <xs:documentation xml:lang="en">The storage connection protocol that defines how the path is written</xs:documentation> </xs:annotation> </xs:attribute></pre>		

Attribute alternativeID / @alternativeIDType

Namespace	No namespace	
Annotations	A simple description of the alternative ID type (e.g. "Local accession number")	
Type	shortTextLimitType	
Properties	use:	required
Facets	minLength	1
	maxLength	60
Used by	Element	alternativeID
Source	<pre><xs:attribute name="alternativeIDType" type="shortTextLimitType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">A simple description of the alternative ID type (e.g. "Local accession number")</xs:documentation> </xs:annotation> </xs:attribute></pre>	

Attribute dataUser / @readOnly

Namespace	No namespace
Annotations	Specifies whether the data user has read-only access to the resource (if false, then read-write access is granted)
Type	xs:boolean
Properties	use: required
Used by	Element dataUser
Source	<pre><xs:attribute name="readOnly" type="xs:boolean" use="required"></pre>

```
<xs:annotation>
  <xs:documentation xml:lang="en">Specifies whether the data user has read-only access to the
  resource (if false, then read-write access is granted)</xs:documentation>
</xs:annotation>
</xs:attribute>
```

Attribute fundingReference / funderID / @funderIDType

Namespace	No namespace
Annotations	Records the type of identifier used for funderID
Type	restriction of xs:string
Properties	default: ROR
Facets	enumeration Crossref Funder ID
	enumeration GRID
	enumeration ISNI
	enumeration ROR
	enumeration Other
Used by	Element fundingReference/funderID
Source	<pre><xs:attribute name="funderIDType" default="ROR"> <xs:annotation> <xs:documentation xml:lang="en">Records the type of identifier used for funderID</ xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Crossref Funder ID" xml:lang="en"/> <xs:enumeration value="GRID" xml:lang="en"/> <xs:enumeration value="ISNI" xml:lang="en"/> <xs:enumeration value="ROR" xml:lang="en"/> <xs:enumeration value="Other" xml:lang="en"/> </xs:restriction> </xs:simpleType> </xs:attribute></pre>

Attribute fundingReference / funderID / @funderIDSchema

Namespace	No namespace
Annotations	Records the schema that defines funderIDType
Type	xs:anyURI
Properties	default: https://ror.org/
Used by	Element fundingReference/funderID
Source	<pre><xs:attribute name="funderIDSchema" type="xs:anyURI" default="https://ror.org/"> <xs:annotation> <xs:documentation xml:lang="en">Records the schema that defines funderIDType</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute fundingReference / awardNumber / @awardURI

Namespace	No namespace
Annotations	Records the URI for the awardNumber
Type	xs:anyURI
Properties	use: optional
Used by	Element fundingReference/awardNumber
Source	<pre><xs:attribute name="awardURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">Records the URI for the awardNumber</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute fundingReference / @federalFunder

Namespace	No namespace
-----------	--------------

Annotations	Whether the funder is part of the U.S. federal government (default false) If true, then the federallyFunded attribute for funded should also be true		
Type	xs:boolean		
Properties	default:	false	
Used by	Element	fundingReference	
Source	<pre><xs:attribute name="federalFunder" type="xs:boolean" default="false"> <xs:annotation> <xs:documentation xml:lang="en">Whether the funder is part of the U.S. federal government (default false)</xs:documentation> <xs:documentation xml:lang="en">If true, then the federallyFunded attribute for funded should also be true</xs:documentation> </xs:annotation> </xs:attribute></pre>		

Attribute license / @licenseURI

Namespace	No namespace		
Annotations	Specifies the URI of the license		
Type	licenseURIType		
Properties	use:	required	
Facets	enumeration	https://creativecommons-s.org/publicdomain/zero/1.0/	Creative Commons Public Domain Dedication 1.0 Universal CC0 1.0
	enumeration	https://creativecommons-s.org/licenses/by/4.0/	Creative Commons Attribution 4.0 International CC BY 4.0
	enumeration	https://creativecommons-s.org/licenses/by-sa/4.0/	Creative Commons Attribution-Sharealike 4.0 International CC BY-SA 4.0
	enumeration	https://creativecommons-s.org/licenses/by-nc/4.0/	Creative Commons Attribution-Noncommercial 4.0 International CC BY-NC 4.0
	enumeration	https://creativecommons-s.org/licenses/by-nc-sa/4.0/	Creative Commons Attribution-Noncommercial-Sharealike 4.0 International CC BY-NC-SA 4.0
	enumeration	https://creativecommons-s.org/licenses/by-nd/4.0/	Creative Commons Attribution-Noncommercial 4.0 International CC BY-ND 4.0
	enumeration	https://creativecommons-s.org/licenses/by-nc-nd/4.0/	Creative Commons Attribution-Noncommercial-Nonderivatives 4.0 International CC BY-NC-ND 4.0
	enumeration	https://open-source.org/license/MIT	The MIT License MIT
Used by	Element	license	
Source	<xs:attribute name="licenseURI" type="licenseURIType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Specifies the URI of the license</xs:documentation> </xs:annotation> </xs:attribute>		

Attribute license / @licenseID

Namespace	No namespace		
Annotations	Specifies the short, standardized version of the license name		
Type	licenseIDType		
Properties	use:	required	
Facets	enumeration	CC0 1.0	Creative Commons Public Domain Dedication 1.0 Universal

			https://creativecommons.org/publicdomain/zero/1.0/
	enumeration	CC BY 4.0	Creative Commons Attribution 4.0 International https://creativecommons.org/licenses/by/4.0/
	enumeration	CC BY-SA 4.0	Creative Commons Attribution-Sharealike 4.0 International https://creativecommons.org/licenses/by-sa/4.0/
	enumeration	CC BY-NC 4.0	Creative Commons Attribution-Noncommercial 4.0 International https://creativecommons.org/licenses/by-nc/4.0/
	enumeration	CC BY-NC-SA 4.0	Creative Commons Attribution-Noncommercial-Sharealike 4.0 International https://creativecommons.org/licenses/by-nc-sa/4.0/
	enumeration	CC BY-ND 4.0	Creative Commons Attribution-NoDerivatives 4.0 International https://creativecommons.org/licenses/by-nd/4.0/
	enumeration	CC BY-NC-ND 4.0	Creative Commons Attribution-Noncommercial-NoDerivatives 4.0 International https://creativecommons.org/licenses/by-nc-nd/4.0/
	enumeration	MIT	The MIT License https://opensource.org/license/MIT
Used by	Element	license	
Source	<pre><xs:attribute name="licenseID" type="licenseIDType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Specifies the short, standardized version of the license name</xs:documentation> </xs:annotation> </xs:attribute></pre>		

Attribute license / @licenseIDSchema

Namespace	No namespace
Annotations	Specifies the schema used for licenseID
Type	titleLimitType
Properties	fixed: SPDX
Facets	minLength 1 maxLength 200
Used by	Element license
Source	<pre><xs:attribute name="licenseIDSchema" type="titleLimitType" fixed="SPDX"> <xs:annotation> <xs:documentation xml:lang="en">Specifies the schema used for licenseID</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute license / @licenseIDSchemaURI

Namespace	No namespace
Annotations	Specifies the URI of the schema given by licenseIDSchema
Type	xs:anyURI
Properties	fixed: https://spdx.org/licenses/
Used by	Element license
Source	<pre><xs:attribute name="licenseIDSchemaURI" type="xs:anyURI" fixed="https://spdx.org/licenses/"> <xs:annotation> <xs:documentation xml:lang="en">Specifies the URI of the schema given by licenseIDSchema</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute duaReference / duaID / @duaURI

Namespace	No namespace
Annotations	Records the URI for the DUA
Type	xs:anyURI
Properties	use: optional
Used by	Element duaReference/duaID
Source	<pre><xs:attribute name="duaURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">Records the URI for the DUA</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute otherDate / @dateType

Namespace	No namespace		
Type	dateTypeType		
Properties	use:	required	
Facets	enumeration	Accepted	The date that the publisher accepted the resource into their system.
	enumeration	Available	The date the resource is made publicly available. May be a range.
	enumeration	Copyrighted	The specific, documented date at which the resource receives a copyrighted status, if applicable.
	enumeration	Collected	The date or date range in which the resource content was collected.
	enumeration	Created	The date the resource itself was put together; this could refer to a timeframe in ancient history, a date range, or a single date for a final component, e.g., the finalised file with all the data.
	enumeration	Issued	The date that the resource is published or distributed, e.g., to a data centre.
	enumeration	Submitted	The date the creator submits the resource to the publisher. This could be different from Accepted if the publisher then applies a selection process.
	enumeration	Updated	The date of the last update to the resource, when the resource is being added to. May be a range.
	enumeration	Valid	The date or date range during which the dataset or resource is accurate.
	enumeration	Withdrawn	The date the resource is removed.
	enumeration	Other	Other date that does not fit into an existing category.
Used by	Element	otherDate	
Source	<xs:attribute name="dateType" type="dateTypeType" use="required"/>		

Attribute otherDate / @dateInformation

Namespace	No namespace	
Annotations	More information about the value of otherDate (recommended if dateType is Other)	
Type	shortTextLimitType	
Properties	use:	optional
Facets	minLength	1
	maxLength	60
Used by	Element	otherDate
Source	<pre><xs:attribute name="dateInformation" type="shortTextLimitType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">More information about the value of otherDate (recommended if dateType is Other)</xs:documentation> </xs:annotation> </xs:attribute></pre>	

```
</xs:annotation>
</xs:attribute>
```

Attribute projectDescription / departments / department / @departmentCode

Namespace	No namespace
Annotations	Records the numerical code for the department (required)
Type	departmentCodeType
Properties	use: required
Facets	pattern [0-9]{5}
Used by	Element projectDescription/departments/department
Source	<pre><xs:attribute name="departmentCode" type="departmentCodeType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Records the numerical code for the department (required)</ </xs:annotation> </xs:attribute></pre>

Attribute additionalProjectInformation / funded / @federallyFunded

Namespace	No namespace
Annotations	Whether the resource is funded by the U.S. federal government (default false) If true, then at least one fundingReference must have the federalFunder attribute set to true
Type	xs:boolean
Properties	default: false
Used by	Element additionalProjectInformation/funded
Source	<pre><xs:attribute name="federallyFunded" type="xs:boolean" default="false"> <xs:annotation> <xs:documentation xml:lang="en">Whether the resource is funded by the U.S. federal government (default false)</xs:documentation> <xs:documentation xml:lang="en">If true, then at least one fundingReference must have the federalFunder attribute set to true</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute supplementalMetadata / keywords / keyword / @subjectSchema

Namespace	No namespace
Annotations	The name of the subject schema or classification code or authority, if applicable
Type	titleLimitType
Properties	use: optional
Facets	minLength 1 maxLength 200
Used by	Element supplementalMetadata/keywords/keyword
Source	<pre><xs:attribute name="subjectSchema" type="titleLimitType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The name of the subject schema or classification code or authority, if applicable</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute supplementalMetadata / keywords / keyword / @subjectSchemaURI

Namespace	No namespace
Annotations	The URI of the subject identifier schema, if applicable
Type	xs:anyURI
Properties	use: optional
Used by	Element supplementalMetadata/keywords/keyword
Source	<pre><xs:attribute name="subjectSchemaURI" type="xs:anyURI" use="optional"> <xs:annotation></pre>

```
<xs:documentation xml:lang="en">The URI of the subject identifier schema, if applicable</xs:documentation>
</xs:annotation>
</xs:attribute>
```

Attribute supplementalMetadata / keywords / keyword / @valueURI

Namespace	No namespace
Annotations	The URI of the subject term, if applicable
Type	xs:anyURI
Properties	use: optional
Used by	Element supplementalMetadata/keywords/keyword
Source	<pre><xs:attribute name="valueURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the subject term, if applicable</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute supplementalMetadata / keywords / keyword / @classificationCode

Namespace	No namespace				
Annotations	The classification code used for the subject term in the subject schema, if applicable				
Type	shortAttributeType				
Properties	use: optional				
Facets	<table> <tr> <td>minLength</td><td>0</td></tr> <tr> <td>maxLength</td><td>60</td></tr> </table>	minLength	0	maxLength	60
minLength	0				
maxLength	60				
Used by	Element supplementalMetadata/keywords/keyword				
Source	<pre><xs:attribute name="classificationCode" type="shortAttributeType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The classification code used for the subject term in the subject schema, if applicable</xs:documentation> </xs:annotation> </xs:attribute></pre>				

Attribute supplementalMetadata / relations / relation / @relatedIDType

Namespace	No namespace		
Type	relatedIDTypeType		
Properties	default:	DOI	
Facets	enumeration	ARK	Archival Resource Key A URI designed to support long-term access to information objects.
	enumeration	arXiv	arXiv identifier arXiv.org is a repository of preprints of scientific papers in the fields of mathematics, physics, astronomy, computer science, quantitative biology, statistics, and quantitative finance.
	enumeration	bibcode	Astrophysics Data System bibliographic codes
	enumeration	CSTR	Common Science and Technology Resources Identifier CSTR is an identifier based on the Chinese National Standard GB/T 32843-2016 "Science and technology resource identification", providing a unique identification service for scientific data, papers, scientific institutions, researchers, scientific instruments, patents and other scientific and technological resources.
	enumeration	DOI	Digital Object Identifier A character string used to uniquely identify an object. A DOI name is divided into two parts, a prefix and a suffix, separated by a slash.

		Use this type to reference TigerData projects
enumeration	EAN13	European Article Number (now renamed International Article Number, but retaining the original acronym) A 13-digit barcoding standard that is a superset of the original 12-digit Universal Product Code (UPC) system.
enumeration	EISSN	Electronic International Standard Serial Number ISSN used to identify periodicals in electronic form (eISSN or e-ISSN).
enumeration	Handle	This refers specifically to an ID in the Handle system operated by the Corporation for National Research Initiatives (CNRI).
enumeration	IGSN	International Generic Sample Number A code that uniquely identifies samples from our natural environment and related features-of-interest.
enumeration	ISBN	International Standard Book Number A unique numeric book identifier. There are 2 formats: a 10-digit ISBN format and a 13-digit ISBN.
enumeration	ISSN	International Standard Serial Number A unique 8-digit number used to identify a print or electronic periodical publication.
enumeration	ISTC	International Standard Text Code A unique "number" assigned to a textual work. An ISTC consists of 16 numbers and/or letters.
enumeration	LISSN	The linking ISSN or ISSN-L enables collocation or linking among different media versions of a continuing resource.
enumeration	LSID	Life Science Identifiers A unique identifier for data in the Life Science domain.
enumeration	PMID	PubMed identifier A unique number assigned to each PubMed record.
enumeration	PURL	Persistent Uniform Resource Locator A PURL has three parts: (1) a protocol, (2) a resolver address, and (3) a name.
enumeration	RRID	Research Resource Identifier A character string used to uniquely identify key inputs to an experiment including the so-called "key biological resources" as defined by the National Institutes of Health, and related tools such as core facilities and databases. An RRID name is divided into two parts, the authority and a local identifier, separated by an underscore.
enumeration	UPC	Universal Product Code A barcode symbology used for tracking trade items in stores. Its most common form, the UPC-A, consists of 12 numerical digits.
enumeration	URL	Uniform Resource Locator Also known as web address, a URL is a specific character string that constitutes a reference to a resource.
enumeration	URN	Uniform Resource Name A unique and persistent identifier of an electronic document.
enumeration	w3id	Permanent identifier for Web applications Mostly used to publish vocabularies and ontologies. The letters 'w3' stand for "World Wide Web".

	enumeration	MFAID	A Mediaflux Asset ID number Include the domain and namespace to make the ID as persistent as possible Use this type to reference TigerData items
Used by	Element	supplementalMetadata/rerelations/relation	
Source	<xs:attribute name="relatedIDType" type="relatedIDTypeType" default="DOI"/>		

Attribute supplementalMetadata / relations / relation / @relationType

Namespace	No namespace		
Type	relationTypeType		
Properties	use:	required	
Facets	enumeration	IsCitedBy	B includes A in a citation
	enumeration	Cites	A includes B in a citation
	enumeration	IsSupplementTo	A is a supplement to B
	enumeration	IsSupplementedBy	B is a supplement to A
	enumeration	IsContinuedBy	A is continued by the work B
	enumeration	Continues	A is a continuation of the work B
	enumeration	Describes	A describes B
	enumeration	IsDescribedBy	A is described by B
	enumeration	HasMetadata	A has additional metadata B
	enumeration	IsMetadataFor	Indicates additional metadata A for a resource B
	enumeration	HasVersion	A has a version B
	enumeration	IsVersionOf	A is a version of B
	enumeration	IsNewVersionOf	A is a new edition of B, where the new edition has been modified or updated
	enumeration	IsPreviousVersionOf	A is a previous edition of B
	enumeration	IsPartOf	A is a portion of B; may be used for elements of a series Do not use for formal parent-child relationships between TigerData projects, subprojects, or items
	enumeration	HasPart	A includes the part B Do not use for formal parent-child relationships between TigerData projects, subprojects, or items
	enumeration	IsPublishedIn	A is published inside B, but is independent of other things published inside of B
	enumeration	IsReferencedBy	A is used as a source of information by B
	enumeration	References	B is used as a source of information for A
	enumeration	IsDocumentedBy	B is documentation about/explaining A
	enumeration	Documents	A is documentation about/explaining B
	enumeration	IsCompiledBy	B is used to compile or create A
	enumeration	Compiles	B is the result of a compile or creation event using A
	enumeration	IsVariantFormOf	A is a variant or different form of B
	enumeration	IsOriginalFormOf	A is the original form of B
	enumeration	IsIdenticalTo	A is identical to B, for use when there is a need to register two separate instances of the same resource
	enumeration	IsReviewedBy	A is reviewed by B
	enumeration	Reviews	A is a review of B
	enumeration	IsDerivedFrom	B is a source upon which A is based
	enumeration	IsSourceOf	A is a source upon which B is based

	enumeration	IsRequiredBy	A is required by B
	enumeration	Requires	A requires B
	enumeration	Obsoletes	A replaces B
	enumeration	IsObsoletedBy	A is replaced by B
	enumeration	IsCollectedBy	A is collected by B
	enumeration	Collects	A collects B
	enumeration	IsTranslationOf	A is a translation of B
	enumeration	HasTranslation	A has a translation B
	enumeration	HasSubproject	A and B are both projects, and A includes B as a subproject Use only with formal relationships between TigerData projects and subprojects
	enumeration	IsSubprojectOf	A and B are both projects, and B includes A as a subproject Use only with formal relationships between TigerData projects and subprojects
	enumeration	HasItem	A is either a project or an item, B is an item, and A includes B Use only with formal relationships between TigerData projects and/or items
	enumeration	IsItemOf	A is an item, B is either a project or an item, and B includes A Use only with formal relationships between TigerData projects and/or items
Used by	Element	supplementalMetadata/relations/relation	
Source	<xs:attribute name="relationType" type="relationTypeType" use="required"/>		

Attribute supplementalMetadata / relations / relation / @relatedMetadataSchema

Namespace	No namespace		
Annotations	The name of the related metadata schema, if applicable Use only with HasMetadata and IsMetadataFor relation types		
Type	titleLimitType		
Properties	use:	optional	
Facets	minLength	1	
	maxLength	200	
Used by	Element	supplementalMetadata/relations/relation	
Source	<pre><xs:attribute name="relatedMetadataSchema" type="titleLimitType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The name of the related metadata schema, if applicable</ xs:documentation> <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor relation types</ xs:documentation> </xs:annotation> </xs:attribute></pre>		

Attribute supplementalMetadata / relations / relation / @relatedMetadataSchemaURI

Namespace	No namespace		
Annotations	The URI of the related metadata schema, if applicable Use only with HasMetadata and IsMetadataFor relation types		
Type	xs:anyURI		
Properties	use:	optional	
Used by	Element	supplementalMetadata/relations/relation	

Source	<pre><xs:attribute name="relatedMetadataSchemaURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the related metadata schema, if applicable</ <xs:documentation> <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor relation types</ <xs:documentation> </xs:annotation> </xs:attribute></pre>
--------	---

Attribute supplementalMetadata / relations / relation / @relatedMetadataSchemaType

Namespace	No namespace				
Annotations	The type of the related metadata schema, if applicable (e.g. XSD, DDT, Turtle) Use only with HasMetadata and IsMetadataFor relation types				
Type	shortAttributeType				
Properties	use: optional				
Facets	<table> <tr> <td>minLength</td><td>0</td></tr> <tr> <td>maxLength</td><td>60</td></tr> </table>	minLength	0	maxLength	60
minLength	0				
maxLength	60				
Used by	Element supplementalMetadata/relations/relation				
Source	<pre><xs:attribute name="relatedMetadataSchemaType" type="shortAttributeType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The type of the related metadata schema, if applicable (e.g. XSD, DDT, Turtle)</xs:documentation> <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor relation types</ <xs:documentation> </xs:annotation> </xs:attribute></pre>				

Attribute itemFields / itemID / @itemIDType

Namespace	No namespace
Annotations	Makes explicit that itemID is always given as a Mediaflux Asset ID
Type	xs:string
Properties	fixed: MFAID
Used by	Element itemFields/itemID
Source	<pre><xs:attribute name="itemIDType" type="xs:string" fixed="MFAID"> <xs:annotation> <xs:documentation xml:lang="en">Makes explicit that itemID is always given as a Mediaflux Asset ID</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute resource / @resourceClass

Namespace	No namespace				
Annotations	Specifies the class of a given resource: either Project or Item (required)				
Type	restriction of xs:string				
Properties	use: required				
Facets	<table> <tr> <td>enumeration</td><td>Project</td></tr> <tr> <td>enumeration</td><td>Item</td></tr> </table>	enumeration	Project	enumeration	Item
enumeration	Project				
enumeration	Item				
Used by	Element resource				
Source	<pre><xs:attribute name="resourceClass" use="required"> <xs:annotation> <xs:documentation xml:lang="en">Specifies the class of a given resource: either Project or Item (required)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"></pre>				

```
<xs:enumeration value="Project" xml:lang="en"/>
<xs:enumeration value="Item" xml:lang="en"/>
</xs:restriction>
</xs:simpleType>
</xs:attribute>
```

Attribute resource / @resourceID

Namespace	No namespace
Annotations	The unique identifier for the resource within TigerData systems (required) If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)
Type	titleLimitType
Properties	use: required
Facets	minLength 1
	maxLength 200
Used by	Element resource
Source	<pre><xs:attribute name="resourceID" type="titleLimitType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">The unique identifier for the resource within TigerData systems (required)</xs:documentation> <xs:documentation xml:lang="en">If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)</xs:documentation> </xs:annotation> </xs:attribute></pre>

Attribute resource / @resourceIDType


Namespace	No namespace
Annotations	If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)
Type	restriction of xs:string
Properties	use: required
Facets	enumeration DOI
	enumeration MFAID
Used by	Element resource
Source	<pre><xs:attribute name="resourceIDType" use="required"> <xs:annotation> <xs:documentation xml:lang="en">If the resourceClass is Project, then the resourceID should be a DOI; if Item, then the resourceID should be a Mediaflux AssetID (MFAID)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="DOI"/> <xs:enumeration value="MFAID"/> </xs:restriction> </xs:simpleType> </xs:attribute></pre>

Element Group(s)

Element Group provenanceSubfields

Namespace	No namespace
Annotations	The group of all standard subfields included in project provenance fields Does not apply to Items

Diagram



Used by Elements projectFields/projectProvenance/publication, projectFields/projectProvenance/retirement, projectFields/projectProvenance/revisions/revision, projectFields/projectProvenance/submission

Model requestedBy , requestDateTime , approvedBy {0,1} , approvalDateTime {0,1} , deniedBy {0,1} , denialDateTime {0,1} , eventNote {0,5}

Children approvalDateTime, approvedBy, denialDateTime, deniedBy, eventNote, requestDateTime, requestedBy

```

<xs:group name="provenanceSubfields">
  <xs:annotation>
    <xs:documentation xml:lang="en">The group of all standard subfields included in project
    provenance fields</xs:documentation>
    <xs:documentation xml:lang="en">Does not apply to Items</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="requestedBy" type="shortUserType" minOccurs="1" maxOccurs="1">
      <xs:annotation>
        <xs:documentation xml:lang="en">The person who made the request</xs:documentation>
        <xs:documentation xml:lang="en">May be an eligible Data Sponsor or Data Manager, a System
        Administrator, or a technical service account</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="requestDateTime" type="xs:dateTime" minOccurs="1" maxOccurs="1">
      <xs:annotation>
        <xs:documentation xml:lang="en">The date and time the request was made</xs:documentation>
        <xs:documentation xml:lang="en">Include the time zone at the location of the host
        institution</xs:documentation>
        <xs:documentation xml:lang="en">Princeton University is in the Eastern Time Zone (UTC-05:00
        during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="approvedBy" type="shortUserType" minOccurs="0" maxOccurs="1">
      <xs:annotation>
        <xs:documentation xml:lang="en">The person who approved the request</xs:documentation>
        <xs:documentation xml:lang="en">Should be a System Administrator</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="approvalDateTime" type="xs:dateTime" minOccurs="0" maxOccurs="1">

```

```

        <xs:annotation>
          <xs:documentation xml:lang="en">The date and time the request was approved</
xs:documentation>
          <xs:documentation xml:lang="en">Include the time zone at the location of the host
institution</xs:documentation>
          <xs:documentation xml:lang="en">Princeton University is in the Eastern Time Zone (UTC-05:00
during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="deniedBy" type="shortUserType" minOccurs="0" maxOccurs="1">
        <xs:annotation>
          <xs:documentation xml:lang="en">The person who denied the request</xs:documentation>
          <xs:documentation xml:lang="en">Should be a System Administrator</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="denialDateTime" type="xs:dateTime" minOccurs="0" maxOccurs="1">
        <xs:annotation>
          <xs:documentation xml:lang="en">The date and time the request was denied</xs:documentation>
          <xs:documentation xml:lang="en">Include the time zone at the location of the host
institution</xs:documentation>
          <xs:documentation xml:lang="en">Princeton University is in the Eastern Time Zone (UTC-05:00
during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="eventNote" minOccurs="0" maxOccurs="5">
        <xs:annotation>
          <xs:documentation xml:lang="en">A supplementary record of noteworthy details for a given
provenance event</xs:documentation>
          <xs:documentation xml:lang="en">Intended to be retained in a running log of all noteworthy
events</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="noteBy" type="shortUserType" minOccurs="1" maxOccurs="1">
              <xs:annotation>
                <xs:documentation xml:lang="en">The person making the note</xs:documentation>
                <xs:documentation xml:lang="en">Should be a System Administrator</xs:documentation>
              </xs:annotation>
            </xs:element>
            <xs:element name="noteDateTime" type="xs:dateTime" minOccurs="1" maxOccurs="1">
              <xs:annotation>
                <xs:documentation xml:lang="en">The date and time the note was made</xs:documentation>
                <xs:documentation xml:lang="en">Include the time zone at the location of the host
institution</xs:documentation>
                <xs:documentation xml:lang="en">Princeton University is in the Eastern Time
Zone (UTC-05:00 during Eastern Standard Time and UTC-04:00 during Eastern Daylight Time)</
xs:documentation>
              </xs:annotation>
            </xs:element>
            <xs:element name="eventType" minOccurs="1" maxOccurs="1">
              <xs:annotation>
                <xs:documentation xml:lang="en">A general category label for the event note</
xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:string">
                  <xs:enumeration value="Collection" xml:lang="en">
                    <xs:annotation>
                      <xs:documentation xml:lang="en">Event note records the assignment of or change
to the project's Mediaflux collection ID</xs:documentation>
                    </xs:annotation>
                  </xs:enumeration>
                  <xs:enumeration value="Directory" xml:lang="en">
                    <xs:annotation>
                      <xs:documentation xml:lang="en">Event note pertains to the project's directory
or mount point</xs:documentation>
                    </xs:annotation>
                  </xs:enumeration>
                  <xs:enumeration value="Quota" xml:lang="en">
                    <xs:annotation>
                      <xs:documentation xml:lang="en">Event note pertains to the project's quota
settings in Mediaflux</xs:documentation>
                    </xs:annotation>
                  </xs:enumeration>
                  <xs:enumeration value="Tier" xml:lang="en">
                    <xs:annotation>
                      <xs:documentation xml:lang="en">Event note pertains to the project's storage
tier</xs:documentation>
                    </xs:annotation>
                  </xs:enumeration>
                  <xs:enumeration value="Sponsor" xml:lang="en">
                    <xs:annotation>

```

	<pre> <xs:documentation xml:lang="en">Event note records any changes to the project's Data Sponsor</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Revision" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Event note explains the return of the project request to the submitter for revision</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Denial" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">Event note explains the denial of the project request</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Other" xml:lang="en"> <xs:annotation> <xs:documentation xml:lang="en">The event note is not otherwise classified</ xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="message" type="textType" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The plain-language message contents of the event note</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:group> </pre>
--	---

Element Group projectRoles

Namespace	No namespace
Annotations	A group of all elements included in TigerData project roles Requires 1 Data Sponsor and 1 Data Manager; Data Users are optional and repeatable Does not apply to Items
Diagram	
Used by	Element Group projectFields
Model	dataSponsor , dataManager , dataUsers {0,1}
Children	dataManager, dataSponsor, dataUsers
Source	<pre> <xs:group name="projectRoles"> <xs:annotation> <xs:documentation xml:lang="en">A group of all elements included in TigerData project roles</ xs:documentation> <xs:documentation xml:lang="en">Requires 1 Data Sponsor and 1 Data Manager; Data Users are optional and repeatable</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Items</xs:documentation> </xs:annotation> <xs:sequence> <xs:element ref="dataSponsor" minOccurs="1" maxOccurs="1"/> <xs:element ref="dataManager" minOccurs="1" maxOccurs="1"/> <xs:element ref="dataUsers" minOccurs="0" maxOccurs="1"/> </xs:sequence> </pre>

</xs:group>

Element Group projectDescription

Namespace	No namespace
Annotations	A group of all elements included in TigerData project descriptions Does not apply to Items
Diagram	
Used by	Element Group projectFields
Model	researchDomains{0,1} , departments , projectDirectory , title , description , languages{0,1}
Children	departments, description, languages, projectDirectory, researchDomains, title
Source	<pre> <xs:group name="projectDescription"> <xs:annotation> <xs:documentation xml:lang="en">A group of all elements included in TigerData project descriptions</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Items</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="researchDomains" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all research domains for a project</xs:documentation> <xs:documentation xml:lang="en">If projectPurpose is Research, then at least one researchDomain element should be given</xs:documentation> <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation> <xs:documentation xml:lang="en">No duplicate domains; no more than 4 total</ xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="researchDomain" minOccurs="1" maxOccurs="4"> <xs:annotation> <xs:documentation xml:lang="en">The general field(s) of academic research related to the project, if applicable</xs:documentation> <xs:documentation xml:lang="en">Options are limited to the 4 domains Princeton University uses to categorize departments</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="researchDomainNameType"> <xs:attribute ref="inherited" fixed="true"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:group> </pre>

```

        </xs:sequence>
        <xs:attribute ref="discoverable" fixed="true"/>
        <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/>
    </xs:complexType>
</xs:element>
<xs:element name="departments" minOccurs="1" maxOccurs="1">
    <xs:annotation>
        <xs:documentation xml:lang="en">The container element for all departments for a project</
xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="department" minOccurs="1" maxOccurs="10">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The primary Princeton University department(s)
affiliated with the project</xs:documentation>
                    <xs:documentation xml:lang="en">Use the canonical name for each recorded department</
xs:documentation>
                    <xs:documentation xml:lang="en">Princeton department names typically start with
a 2- or 3-character abbreviation, followed by a minus-dash, and then a short description</
xs:documentation>
                </xs:annotation>
                <xs:complexType>
                    <xs:simpleContent>
                        <xs:extension base="departmentType">
                            <xs:attribute name="departmentCode" type="departmentCodeType" use="required">
                                <xs:annotation>
                                    <xs:documentation xml:lang="en">Records the numerical code for the department
(required)</xs:documentation>
                                </xs:annotation>
                            </xs:attribute>
                            <xs:attribute ref="inherited" default="true"/>
                        </xs:extension>
                    </xs:simpleContent>
                </xs:complexType>
            </xs:element>
        </xs:sequence>
        <xs:attribute ref="discoverable" fixed="true"/>
        <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/>
    </xs:complexType>
</xs:element>
<xs:element name="projectDirectory" minOccurs="1" maxOccurs="1">
    <xs:annotation>
        <xs:documentation xml:lang="en">The locally unique name for the project's directory</
xs:documentation>
        <xs:documentation xml:lang="en">The typical value is expected to be in NFS protocol</
xs:documentation>
        <xs:documentation xml:lang="en">A parent folder is recommended to organize projects by
groups (e.g., lab or principal investigator)</xs:documentation>
        <xs:documentation xml:lang="en">If no user request was received and no value has yet been
approved, then this field may be empty</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="projectDirectoryPath" type="pathType" minOccurs="0" maxOccurs="10">
                <xs:annotation>
                    <xs:documentation xml:lang="en">A current setting for projectDirectory (omitted until
approved)</xs:documentation>
                    <xs:documentation xml:lang="en">After approval, this value should be updated to match
the approved value (in rare cases, the current setting may later deviate from the approved value)</
xs:documentation>
                    <xs:documentation xml:lang="en">Multiple elements are allowed to specify paths in
alternative protocols, using the protocol attribute</xs:documentation>
                    <xs:documentation xml:lang="en">Example NFS path: /tigerdata/parent-folder/project-
folder</xs:documentation>
                    <xs:documentation xml:lang="en">Example SMB path: \\tigerdata-smb\parent-folder
\project-folder</xs:documentation>
                    <xs:documentation xml:lang="en">Example S3 path: S3://princeton/tigerdata/parent-
folder/project-folder</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="requestedValue" type="pathType" minOccurs="0" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The requested value for projectDirectory (omitted if
no user request was received)</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="approvedValue" type="pathType" minOccurs="0" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The approved value for projectDirectory (omitted if no
sys admin has approved yet)</xs:documentation>
                    <xs:documentation xml:lang="en">Once approved, the approved attribute should also be
set to true</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

        </xs:annotation>
      </xs:element>
    </xs:sequence>
    <xs:attribute ref="approved" default="false"/>
    <xs:attribute ref="inherited" fixed="false"/>
    <xs:attribute ref="discoverable" fixed="false"/>
    <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
  </xs:complexType>
</xs:element>
<xs:element ref="title" minOccurs="1" maxOccurs="1"/>
<xs:element ref="description" minOccurs="1" maxOccurs="1"/>
<xs:element ref="languages" minOccurs="0" maxOccurs="1"/>
</xs:sequence>
</xs:group>

```

Element Group storageAndAccess

Namespace	No namespace												
Annotations	A group of all elements included in TigerData project storage and access needs Does not apply to Items												
Diagram	<pre> graph TD storageAndAccess[storageAndAccess] --- storageCapacity[storageCapacity] storageAndAccess --- projectVisibility[projectVisibility] storageAndAccess --- storagePerformance[storagePerformance] storageAndAccess --- numberOfFiles[numberOfFiles] storageAndAccess --- securityLevel[securityLevel] storageAndAccess --- storageSystem[storageSystem] storageAndAccess --- accessPoints[accessPoints] </pre> storageAndAccess A group of all elements included in TigerData project storage and access needs Does not apply to Items storageCapacity The amount of storage allotted for the project (using logical byte units, base-10) If no user request was received and... projectVisibility <table border="1"> <tr> <td>Type</td> <td>Extension of 'visibilityType'</td> </tr> <tr> <td>Default</td> <td>Restricted</td> </tr> </table> The level of openness to allow for the project record (Restricted by default) If securityLevel is set to 2 or higher,... storagePerformance The qualitative assignment for storage performance, i.e. storage tier If no user request was received and no value has... numberOfFiles <table border="1"> <tr> <td>Type</td> <td>Extension of 'fileEstimateType'</td> </tr> <tr> <td>Default</td> <td>Less than 10,000</td> </tr> </table> The estimated number of files the project will incorporate (default is Less than 10,000) securityLevel The appropriate data security classification level for the project... storageSystem <table border="1"> <tr> <td>Type</td> <td>Extension of 'storageSystemType'</td> </tr> <tr> <td>Default</td> <td>TigerData</td> </tr> </table> The name of the storage system to which the path applies Used to differentiate standard TigerData projects (in-band)... accessPoints Records requests/approvals and settings for HPC systems, SMB shares, and Globus endpoints If this element is present,...	Type	Extension of 'visibilityType'	Default	Restricted	Type	Extension of 'fileEstimateType'	Default	Less than 10,000	Type	Extension of 'storageSystemType'	Default	TigerData
Type	Extension of 'visibilityType'												
Default	Restricted												
Type	Extension of 'fileEstimateType'												
Default	Less than 10,000												
Type	Extension of 'storageSystemType'												
Default	TigerData												
Used by	Element Group projectFields												
Model	storageCapacity , projectVisibility , storagePerformance , numberOfFiles , securityLevel{0,1} , storageSystem{0,1} , access-Points{0,1}												
Children	accessPoints, numberOfFiles, projectVisibility, securityLevel, storageCapacity, storagePerformance, storageSystem												
Source	<pre> <xs:group name="storageAndAccess"> <xs:annotation> <xs:documentation xml:lang="en">A group of all elements included in TigerData project storage and access needs</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Items</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="storageCapacity" minOccurs="1" maxOccurs="1"> <xs:annotation> </pre>												

```

        <xs:documentation xml:lang="en">The amount of storage allotted for the project (using
logical byte units, base-10)</xs:documentation>
        <xs:documentation xml:lang="en">If no user request was received and no value has yet been
approved, then this field may be empty</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="storageCapacitySetting" type="storageQuantityType" minOccurs="0"
maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The current setting for storageCapacity (omitted until
approved)</xs:documentation>
                    <xs:documentation xml:lang="en">After the implementation of the approval, this value
should be updated to match the approvedValue</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="requestedValue" type="storageQuantityType" minOccurs="0" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The requested value for storageCapacity (omitted if no
user request was received)</xs:documentation>
                    <xs:documentation xml:lang="en">This field gets updated when a Data Sponsor or Data
Manager requests a change in storage capacity on an active project</xs:documentation>
                    <xs:documentation xml:lang="en">Depending on the amount requested, a System
Administrator may ask the Data Sponsor for more justification for the request</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="approvedValue" type="storageQuantityType" minOccurs="0" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The approved value for storageCapacity (omitted if no
sys admin has approved yet)</xs:documentation>
                    <xs:documentation xml:lang="en">Once approved for initial project setup, the approved
attribute should also be set to true</xs:documentation>
                    <xs:documentation xml:lang="en">If the Data Sponsor or Data Manager requests a
change in storage capacity, then the approval of the new amount will change the approvedValue</
xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
        <xs:attribute ref="approved" default="false"/>
        <xs:attribute ref="inherited" fixed="false"/>
        <xs:attribute ref="discoverable" fixed="false"/>
        <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
    </xs:complexType>
</xs:element>
<xs:element name="projectVisibility" minOccurs="1" maxOccurs="1" default="Restricted">
    <xs:annotation>
        <xs:documentation xml:lang="en">The level of openness to allow for the project record
(Restricted by default)</xs:documentation>
        <xs:documentation xml:lang="en">If securityLevel is set to 2 or higher, then project
visibility should be set to Restricted</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:simpleContent>
            <xs:extension base="visibilityType">
                <xs:attribute ref="inherited" default="true"/>
                <xs:attribute ref="discoverable" fixed="false"/>
                <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
            </xs:extension>
        </xs:simpleContent>
    </xs:complexType>
</xs:element>
<xs:element name="storagePerformance" minOccurs="1" maxOccurs="1">
    <xs:annotation>
        <xs:documentation xml:lang="en">The qualitative assignment for storage performance, i.e.
storage tier</xs:documentation>
        <xs:documentation xml:lang="en">If no user request was received and no value has yet been
approved, then this field may be empty</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="storagePerformanceSetting" type="storagePerformanceType" minOccurs="0"
maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The current setting for storagePerformance (omitted
until approved)</xs:documentation>
                    <xs:documentation xml:lang="en">After the implementation of the approval, this value
should be updated to match the approvedValue</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="requestedValue" type="storagePerformanceType" minOccurs="0"
maxOccurs="1">
                <xs:annotation>

```

```

        <xs:documentation xml:lang="en">The requested value for storagePerformance (omitted if
no user request was received)</xs:documentation>
        <xs:documentation xml:lang="en">This field gets updated when a Data Sponsor or Data
Manager requests a change in storage performance on an active project</xs:documentation>
        <xs:documentation xml:lang="en">Depending on the level requested, a System
Administrator may ask the Data Sponsor for more justification for the request</xs:documentation>
        </xs:annotation>
        </xs:element>
        <xs:element name="approvedValue" type="storagePerformanceType" minOccurs="0"
maxOccurs="1">
        <xs:annotation>
        <xs:documentation xml:lang="en">The approved value for storagePerformance (omitted if
no sys admin has approved yet)</xs:documentation>
        <xs:documentation xml:lang="en">Once approved, the approved attribute should also be
set to true</xs:documentation>
        <xs:documentation xml:lang="en">If the Data Sponsor or Data Manager requests a
change in storage performance, then the approval of the new level will change the approvedValue</
xs:documentation>
        </xs:annotation>
        </xs:element>
    </xs:sequence>
    <xs:attribute ref="approved" default="false"/>
    <xs:attribute ref="inherited" default="true"/>
    <xs:attribute ref="discoverable" fixed="false"/>
    <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
</xs:complexType>
</xs:element>
<xs:element name="numberOfFiles" minOccurs="1" maxOccurs="1" default="Less than 10,000">
<xs:annotation>
    <xs:documentation xml:lang="en">The estimated number of files the project will incorporate
(default is Less than 10,000)</xs:documentation>
</xs:annotation>
<xs:complexType>
    <xs:simpleContent>
        <xs:extension base="fileEstimateType">
            <xs:attribute ref="inherited" default="false"/>
            <xs:attribute ref="discoverable" fixed="false"/>
            <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
</xs:element>
<xs:element name="securityLevel" minOccurs="0" maxOccurs="1">
<xs:annotation>
    <xs:documentation xml:lang="en">The appropriate data security classification level for the
project contents</xs:documentation>
    <xs:documentation>https://protectingourinfo.princeton.edu/classify</xs:documentation>
    <xs:documentation xml:lang="en">If the security level is set to 2 or higher, then project
visibility should be set to Restricted</xs:documentation>
</xs:annotation>
<xs:complexType>
    <xs:sequence>
        <xs:element name="securityLevelSetting" type="securityLevelType" maxOccurs="1">
            <xs:annotation>
                <xs:documentation xml:lang="en">The current setting for security level</
xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="requestedValue" type="securityLevelType" maxOccurs="1">
            <xs:annotation>
                <xs:documentation xml:lang="en">The requested value for security level</
xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="approvedValue" type="securityLevelType" maxOccurs="1">
            <xs:annotation>
                <xs:documentation xml:lang="en">The approved value for security level</
xs:documentation>
            <xs:documentation xml:lang="en">If an approvedValue is given, then the approved
attribute should also be set to true</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
    <xs:attribute ref="approved" default="false"/>
    <xs:attribute ref="inherited" fixed="true"/>
    <xs:attribute ref="discoverable" default="false"/>
    <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
</xs:complexType>
</xs:element>
<xs:element name="storageSystem" minOccurs="0" maxOccurs="1" default="TigerData">
<xs:annotation>
    <xs:documentation xml:lang="en">The name of the storage system to which the path applies</
xs:documentation>

```

```

        <xs:documentation xml:lang="en">Used to differentiate standard TigerData projects (in-band)
        from out-of-band systems (e.g., '/projects' or 'Della /scratch/gpfs')</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:simpleContent>
            <xs:extension base="storageSystemType">
                <xs:attribute ref="inherited" default="false"/>
                <xs:attribute ref="discoverable" fixed="false"/>
                <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
            </xs:extension>
        </xs:simpleContent>
    </xs:complexType>
</xs:element>
<xs:element name="accessPoints" minOccurs="0" maxOccurs="1">
    <xs:annotation>
        <xs:documentation xml:lang="en">Records requests/approvals and settings for HPC systems, SMB
        shares, and Globus endpoints</xs:documentation>
        <xs:documentation xml:lang="en">If this element is present, then it should contain all 3
        sub-elements</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="hpcEnable" minOccurs="1" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">Whether a project is enabled for access on HPC systems
                    (via NFS)</xs:documentation>
                    <xs:documentation xml:lang="en">By default, projects do not get set up for access
                    on HPC systems, but if both SMB and Globus are disabled, then HPC enabling may be necessary</
                    xs:documentation>
                </xs:annotation>
                <xs:complexType>
                    <xs:sequence>
                        <xs:element name="hpcEnableSetting" type="xs:boolean" maxOccurs="1" default="false">
                            <xs:annotation>
                                <xs:documentation xml:lang="en">The current setting for hpcEnable (false by
                                default)</xs:documentation>
                            </xs:annotation>
                        </xs:element>
                        <xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No">
                            <xs:annotation>
                                <xs:documentation xml:lang="en">The requested value for hpcEnable (No by
                                default)</xs:documentation>
                            </xs:annotation>
                        </xs:element>
                        <xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false">
                            <xs:annotation>
                                <xs:documentation xml:lang="en">The approved value for smbEnable (false by
                                default)</xs:documentation>
                                <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values,
                                but the approved value must be true/false</xs:documentation>
                                <xs:documentation xml:lang="en">If approvedValue is true, then hpcEnableSetting
                                and the approved attribute should also be set to true</xs:documentation>
                            </xs:annotation>
                        </xs:element>
                    </xs:sequence>
                </xs:complexType>
                <xs:attribute ref="approved" default="false"/>
            </xs:element>
            <xs:element name="smbEnable" minOccurs="1" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">Whether a project has an SMB share enabled</
                    xs:documentation>
                    <xs:documentation xml:lang="en">By default, projects do not get an SMB share, but if
                    HPC access is disabled, then smbEnable is likely needed</xs:documentation>
                    <xs:documentation xml:lang="en">If an SMB share is approved and set, then the SMB path
                    should be included in projectDirectoryPath</xs:documentation>
                </xs:annotation>
                <xs:complexType>
                    <xs:sequence>
                        <xs:element name="smbEnableSetting" type="xs:boolean" maxOccurs="1" default="false">
                            <xs:annotation>
                                <xs:documentation xml:lang="en">The current setting for smbEnable (false by
                                default)</xs:documentation>
                            </xs:annotation>
                        </xs:element>
                        <xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No">
                            <xs:annotation>
                                <xs:documentation xml:lang="en">The requested value for smbEnable (No by
                                default)</xs:documentation>
                            </xs:annotation>
                        </xs:element>
                        <xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false">
                            <xs:annotation>

```

```

        <xs:documentation xml:lang="en">The approved value for smbEnable (false by
default)</xs:documentation>
        <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values,
but the approved value must be true/false</xs:documentation>
        <xs:documentation xml:lang="en">If approvedValue is true, then smbEnableSetting
and the approved attribute should also be set to true</xs:documentation>
        </xs:annotation>
    </xs:element>
</xs:sequence>
<xs:attribute ref="approved" default="false"/>
</xs:complexType>
</xs:element>
<xs:element name="globusEnable" minOccurs="1" maxOccurs="1">
    <xs:annotation>
        <xs:documentation xml:lang="en">Whether a project has a Globus collection enabled</
xs:documentation>
        <xs:documentation xml:lang="en">By default, projects do not get a Globus collection</
xs:documentation>
        <xs:documentation xml:lang="en">If a Globus collection is approved and set, then the
details should be given in globusCollection</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="globusEnableSetting" type="xs:boolean" maxOccurs="1"
default="false">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The current setting for globusEnable (false by
default)</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="requestedValue" type="yesNoMaybeType" maxOccurs="1" default="No">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The requested value for globusEnable (No by
default)</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="approvedValue" type="xs:boolean" maxOccurs="1" default="false">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The approved value for globusEnable (false by
default)</xs:documentation>
                    <xs:documentation xml:lang="en">The requested value takes yes/no/maybe values,
but the approved value must be true/false</xs:documentation>
                    <xs:documentation xml:lang="en">If approvedValue is true, then
globusEnableSetting and the approved attribute should also be set to true</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
        <xs:attribute ref="approved" default="false"/>
    </xs:complexType>
</xs:element>
<xs:element name="globusCollection" minOccurs="0" maxOccurs="5">
    <xs:annotation>
        <xs:documentation xml:lang="en">Details for an enabled Globus collection for the
project</xs:documentation>
        <xs:documentation xml:lang="en">If globusEnableSetting is true, then at least one
globusCollection value set should be given</xs:documentation>
        <xs:documentation xml:lang="en">If no Globus collection is approved, then this field
should be omitted</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="globusName" type="titleLimitType" minOccurs="1" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The Globus collection name (required)</
xs:documentation>
                    <xs:documentation xml:lang="en">The naming convention is "Princeton TigerData -
parent-folder/project-folder"</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="globusUUID" type="uuidType" minOccurs="1" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The Globus collection universally unique
identifier (required)</xs:documentation>
                    <xs:documentation xml:lang="en">The value is expected to be 32 hexadecimal
digits in 8-4-4-4-12 format</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="globusOwner" type="userType" minOccurs="1" maxOccurs="1">
                <xs:annotation>
                    <xs:documentation xml:lang="en">The Globus collection owner, given as a
TigerData userType (required)</xs:documentation>
                    <xs:documentation xml:lang="en">The owner is typically the project's Data
Manager</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```


```

        </xs:annotation>
      </xs:element>
      <xs:element name="globusURL" type="xs:anyURI" minOccurs="0" maxOccurs="1">
        <xs:annotation>
          <xs:documentation xml:lang="en">The Globus collection URL (optional)</
xs:documentation>
          <xs:documentation xml:lang="en">The expected format for a Globus collection URL
is https://app.globus.org/file-manager?origin_id=[uuid]</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>
<xs:attribute ref="inherited" fixed="false"/>
<xs:attribute ref="discoverable" fixed="false"/>
<xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:group>
```

Element Group additionalProjectInformation

Namespace	No namespace
Annotations	A group of all elements included in TigerData additional project information fields
	Does not apply to Items

Diagram



Used by	Element Group projectFields
Model	projectPurpose , provisionalProject , funded{0,1} , fundingReferences{0,1} , projectDates{0,1} , projectResourceType , licenses{0,1} , dataUseAgreement{0,1} , duaReferences{0,1}
Children	dataUseAgreement, duaReferences, funded, fundingReferences, licenses, projectDates, projectPurpose, projectResourceType, provisionalProject
Source	<pre> <xs:group name="additionalProjectInformation"> <xs:annotation> <xs:documentation xml:lang="en">A group of all elements included in TigerData additional project information fields</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Items</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="projectPurpose" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The high-level category for the purpose of the project</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="projectPurposeType"> <xs:attribute ref="inherited" default="true"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </xs:sequence> </xs:group> </pre>

```

        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element name="provisionalProject" minOccurs="1" maxOccurs="1" default="false">
      <xs:annotation>
        <xs:documentation xml:lang="en">Whether the project is provisional, i.e., temporary,
experimental, or intended for testing purposes only (default false)</xs:documentation>
        <xs:documentation xml:lang="en">If the value is true, then limitations may be placed on
other fields, e.g. storageCapacity, storagePerformance, and endDate</xs:documentation>
        <xs:documentation xml:lang="en">If the value is false, then the project is considered
standard and the provisional limitations are not imposed</xs:documentation>
        <xs:documentation xml:lang="en">Whether provisional or standard, the same fields are
required for all projects</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:boolean">
            <xs:attribute ref="inherited" fixed="true"/>
            <xs:attribute ref="discoverable" fixed="true"/>
            <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element name="funded" minOccurs="0" maxOccurs="1">
      <xs:annotation>
        <xs:documentation xml:lang="en">Whether a resource is funded</xs:documentation>
        <xs:documentation xml:lang="en">If the value is true, then at least one fundingReference
field must be filled</xs:documentation>
        <xs:documentation xml:lang="en">If any subproject or item contained in a project has a
fundingReference, then this field should be set to true</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:boolean">
            <xs:attribute name="federallyFunded" type="xs:boolean" default="false">
              <xs:annotation>
                <xs:documentation xml:lang="en">Whether the resource is funded by the U.S. federal
government (default false)</xs:documentation>
                <xs:documentation xml:lang="en">If true, then at least one fundingReference must
have the federalFunder attribute set to true</xs:documentation>
              </xs:annotation>
            </xs:attribute>
            <xs:attribute ref="inherited" default="true"/>
            <xs:attribute ref="discoverable" fixed="false"/>
            <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element ref="fundingReferences" minOccurs="0" maxOccurs="1"/>
    <xs:element ref="projectDates" minOccurs="0" maxOccurs="1"/>
    <xs:element ref="projectResourceType" minOccurs="1" maxOccurs="1"/>
    <xs:element ref="licenses" minOccurs="0" maxOccurs="1"/>
    <xs:element name="dataUseAgreement" minOccurs="0" maxOccurs="1">
      <xs:annotation>
        <xs:documentation xml:lang="en">Whether a data use agreement applies to the project</
xs:documentation>
        <xs:documentation xml:lang="en">If the value is true, then at least one duaReference field
must be filled</xs:documentation>
        <xs:documentation xml:lang="en">If any subproject or item contained in a project has a
duaReference, then this field should be set to true</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:boolean">
            <xs:attribute ref="inherited" default="true"/>
            <xs:attribute ref="discoverable" fixed="false"/>
            <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element ref="duaReferences" minOccurs="0" maxOccurs="1"/>
  </xs:sequence>
</xs:group>

```

Element Group supplementalMetadata

Namespace	No namespace
Annotations	A group of all elements included in TigerData supplemental metadata fields

	May apply to either Projects and Items
Diagram	<pre> graph LR subgraph supplementalMetadata [supplementalMetadata] keywords relations extendedMetadataSchemas end keywords --- desc_keywords["The container element for all keywords for a resource May apply to either Projects or Items If this element is present,..."] relations --- desc_relations["The container element for all relations for a resource May apply to either Projects or Items If this element is..."] extendedMetadataSchemas --- desc_extended["The container element for all extended metadata schemas for a resource, if applicable May apply to either Projects or..."] </pre>
Used by	Element Groups itemFields, projectFields
Model	keywords{0,1} , relations{0,1} , extendedMetadataSchemas{0,1}
Children	extendedMetadataSchemas, keywords, relations
Source	<pre> <xs:group name="supplementalMetadata"> <xs:annotation> <xs:documentation xml:lang="en">A group of all elements included in TigerData supplemental metadata fields</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects and Items</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="keywords" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all keywords for a resource</ xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation> <xs:documentation xml:lang="en">If this element is present, then it should contain at least one sub-element</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="keyword" minOccurs="1" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">Tag for a subject heading, content type, or other keyword (given as a string)</xs:documentation> <xs:documentation xml:lang="en">May apply to either Projects and Items</ xs:documentation> <xs:documentation xml:lang="en">Derived from the DataCite definitions for Subject (v4.6+)</xs:documentation> <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/ subject</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="shortTextType"> <xs:attribute name="subjectSchema" type="titleLimitType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The name of the subject schema or classification code or authority, if applicable</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="subjectSchemaURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the subject identifier schema, if applicable</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="valueURI" type="xs:anyURI" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The URI of the subject term, if applicable</ xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute name="classificationCode" type="shortAttributeType" use="optional"> <xs:annotation> <xs:documentation xml:lang="en">The classification code used for the subject term in the subject schema, if applicable</xs:documentation> </xs:annotation> </xs:attribute> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </pre>

```

        </xs:complexType>
      </xs:element>
    </xs:sequence>
    <xs:attribute ref="discoverable" fixed="true"/>
    <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/>
  </xs:complexType>
</xs:element>
<xs:element name="relations" minOccurs="0" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">The container element for all relations for a resource</
xs:documentation>
    <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation>
    <xs:documentation xml:lang="en">If this element is present, then it should contain at least
one sub-element</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="relation" minOccurs="1" maxOccurs="100">
        <xs:annotation>
          <xs:documentation xml:lang="en">Specifies a related TigerData project or item, a
published paper, or any other digital object, given as a string</xs:documentation>
          <xs:documentation xml:lang="en">May apply to either Projects or Items</
xs:documentation>
          <xs:documentation xml:lang="en">Derived from the DataCite definitions for
RelatedIdentifier (v4.6+)</xs:documentation>
          <xs:documentation>https://datacite-metadata-schema.readthedocs.io/en/4.6/properties/
relatedidentifier/</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:simpleContent>
            <xs:extension base="titleLimitType">
              <xs:attribute name="relatedIDType" type="relatedIDTypeType" default="DOI"/>
              <xs:attribute name="relationType" type="relationTypeType" use="required"/>
              <xs:attribute name="relatedMetadataSchema" type="titleLimitType" use="optional">
                <xs:annotation>
                  <xs:documentation xml:lang="en">The name of the related metadata schema, if
applicable</xs:documentation>
                  <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor
relation types</xs:documentation>
                </xs:annotation>
              </xs:attribute>
              <xs:attribute name="relatedMetadataSchemaURI" type="xs:anyURI" use="optional">
                <xs:annotation>
                  <xs:documentation xml:lang="en">The URI of the related metadata schema, if
applicable</xs:documentation>
                  <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor
relation types</xs:documentation>
                </xs:annotation>
              </xs:attribute>
              <xs:attribute name="relatedMetadataSchemaType" type="shortAttributeType"
use="optional">
                <xs:annotation>
                  <xs:documentation xml:lang="en">The type of the related metadata schema, if
applicable (e.g. XSD, DDT, Turtle)</xs:documentation>
                  <xs:documentation xml:lang="en">Use only with HasMetadata and IsMetadataFor
relation types</xs:documentation>
                </xs:annotation>
              </xs:attribute>
            </xs:extension>
          </xs:simpleContent>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
    <xs:attribute ref="discoverable" fixed="true"/>
    <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/>
  </xs:complexType>
</xs:element>
<xs:element name="extendedMetadataSchemas" minOccurs="0" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">The container element for all extended metadata schemas for
a resource, if applicable</xs:documentation>
    <xs:documentation xml:lang="en">May apply to either Projects or Items</xs:documentation>
    <xs:documentation xml:lang="en">If this element is present, then it should contain at least
one sub-element</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="extendedMetadataSchema" minOccurs="1" maxOccurs="10">
        <xs:annotation>
          <xs:documentation xml:lang="en">An indication of which TigerData supported metadata
schemas should apply to a resource (given as a string)</xs:documentation>

```


```

        <xs:documentation xml:lang="en">May apply to either Projects or Items</
xs:documentation>
        </xs:annotation>
        <xs:complexType>
            <xs:simpleContent>
                <xs:extension base="titleType">
                    <xs:attribute ref="inherited" default="false"/>
                </xs:extension>
            </xs:simpleContent>
        </xs:complexType>
    </xs:element>
</xs:sequence>
<xs:attribute ref="discoverable" fixed="false"/>
<xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:group>
```

Element Group projectFields

Namespace	No namespace
Annotations	A group of all elements/groups included in the TigerData standard metadata for projects
	Does not apply to Items

Diagram



Used by	Element resource
Model	projectID , alternativeIDs{0,1} , parentProject{0,1} , dataSponsor , dataManager , dataUsers{0,1} , researchDomains{0,1} , departments , projectDirectory , title , description , languages{0,1} , storageCapacity , projectVisibility , storagePerformance , numberOfFiles , securityLevel{0,1} , storageSystem{0,1} , accessPoints{0,1} , projectPurpose , provisionalProject , funded{0,1} , fundingReferences{0,1} , projectDates{0,1} , projectResourceType , licenses{0,1} , dataUseAgreement{0,1} , duaReferences{0,1} , keywords{0,1} , relations{0,1} , extendedMetadataSchemas{0,1} , projectProvenance
Children	accessPoints, alternativeIDs, dataManager, dataSponsor, dataUseAgreement, dataUsers, departments, description, duaReferences, extendedMetadataSchemas, funded, fundingReferences, keywords, languages, licenses, numberOfFiles, parentProject, projectDates, projectDirectory, projectID, projectProvenance, projectPurpose, projectResourceType, projectVisibility, provisionalProject, relations, researchDomains, securityLevel, storageCapacity, storagePerformance, storageSystem, title
Source	<pre> <xs:group name="projectFields"> <xs:annotation> <xs:documentation xml:lang="en">A group of all elements/groups included in the TigerData standard metadata for projects</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Items</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="projectID" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The universally unique identifier for the project (required)</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="projectIDValueType"> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="true"/> <xs:attribute ref="trackingLevel" fixed="ResourceRecord"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> <xs:element ref="alternativeIDs" minOccurs="0" maxOccurs="1"/> <xs:element ref="parentProject" minOccurs="0" maxOccurs="1"/> <xs:group ref="projectRoles"/> <xs:group ref="projectDescription"/> <xs:group ref="storageAndAccess"/> <xs:group ref="additionalProjectInformation"/> <xs:group ref="supplementalMetadata"/> <xs:element name="projectProvenance" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all TigerData project provenance fields (required)</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="submission" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">A record of a project's initial submission (required)</xs:documentation> </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element> <xs:element name="revisions" minOccurs="0" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The container element for all revision records, if applicable</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="revision" minOccurs="1" maxOccurs="10"> <xs:annotation> <xs:documentation xml:lang="en">A record of a major revision to an active project</xs:documentation> </xs:annotation> <xs:complexType> <xs:group ref="provenanceSubfields"/> <xs:attribute ref="inherited" default="false"/> </xs:complexType> </xs:element> </xs:sequence> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:group> </pre>

```


</xs:element>
<xs:element name="retirement" minOccurs="0" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">A record of a project's retirement, if applicable</
xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:group ref="provenanceSubfields"/>
    <xs:attribute ref="inherited" fixed="true"/>
    <xs:attribute ref="discoverable" fixed="false"/>
    <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
  </xs:complexType>
</xs:element>
<xs:element name="publication" minOccurs="0" maxOccurs="1">
  <xs:annotation>
    <xs:documentation xml:lang="en">A record of a project's publication, if applicable</
xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:group ref="provenanceSubfields"/>
    <xs:attribute ref="inherited" fixed="true"/>
    <xs:attribute ref="discoverable" fixed="false"/>
    <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
  </xs:complexType>
</xs:element>
<xs:element name="status" minOccurs="1" maxOccurs="1" default="AdminReview">
  <xs:annotation>
    <xs:documentation xml:lang="en">The current status of the project (required)</
xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:simpleContent>
      <xs:extension base="statusType">
        <xs:attribute ref="inherited" default="false"/>
        <xs:attribute ref="discoverable" fixed="true"/>
        <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/>
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:group>

```

Element Group itemFields

Namespace	No namespace
Annotations	A group of all elements/groups included in the TigerData standard metadata for items
	Does not apply to Projects

Diagram



Used by	Element resource
Model	itemID , alternativeIDs{0,1} , parentProject , dataUsers{0,1} , title{0,1} , description{0,1} , itemResourceType{0,1} , keywords{0,1} , relations{0,1} , extendedMetadataSchemas{0,1} , languages{0,1} , licenses{0,1} , fundingReferences{0,1} , duaReferences{0,1} , itemDates{0,1}
Children	alternativeIDs, dataUsers, description, duaReferences, extendedMetadataSchemas, fundingReferences, itemDates, itemID, itemResourceType, keywords, languages, licenses, parentProject, relations, title
Source	<pre> <xs:group name="itemFields"> <xs:annotation> <xs:documentation xml:lang="en">A group of all elements/groups included in the TigerData standard metadata for items</xs:documentation> <xs:documentation xml:lang="en">Does not apply to Projects</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="itemID" minOccurs="1" maxOccurs="1"> <xs:annotation> <xs:documentation xml:lang="en">The unique identifier for the item (required)</ xs:documentation> <xs:documentation xml:lang="en">TigerData items use Mediaflux Asset IDs as their primary identifiers</xs:documentation> <xs:documentation xml:lang="en">If an item also has any other IDs, they all should be included under alternativeIDs</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="mediafluxAssetIDType"> <xs:attribute name="itemIDType" type="xs:string" fixed="MFAID"> <xs:annotation> <xs:documentation xml:lang="en">Makes explicit that itemID is always given as a Mediaflux Asset ID</xs:documentation> </xs:annotation> </xs:attribute> <xs:attribute ref="inherited" fixed="false"/> <xs:attribute ref="discoverable" fixed="false"/> <xs:attribute ref="trackingLevel" fixed="InternalUseOnly"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> <xs:element ref="alternativeIDs" minOccurs="0" maxOccurs="1"/> <xs:element ref="parentProject" minOccurs="1" maxOccurs="1"/> <xs:element ref="dataUsers" minOccurs="0" maxOccurs="1"/> <xs:element ref="title" minOccurs="0" maxOccurs="1"/> <xs:element ref="description" minOccurs="0" maxOccurs="1"/> <xs:element ref="itemResourceType" minOccurs="0" maxOccurs="1"/> <xs:group ref="supplementalMetadata"/> <xs:element ref="languages" minOccurs="0" maxOccurs="1"/> <xs:element ref="licenses" minOccurs="0" maxOccurs="1"/> <xs:element ref="fundingReferences" minOccurs="0" maxOccurs="1"/> <xs:element ref="duaReferences" minOccurs="0" maxOccurs="1"/> <xs:element ref="itemDates" minOccurs="0" maxOccurs="1"/> </xs:sequence> </xs:group> </pre>

Namespace: "http://www.w3.org/XML/1998/namespace"

Schema(s)

Imported schema xml.xsd

Namespace	http://www.w3.org/XML/1998/namespace
Annotations	<pre> <div> <h1>About the XML namespace</h1> <div class="bodytext"> <p>This schema document describes the XML namespace, in a form suitable for import by other schema documents.</p> <p>See http://www.w3.org/XML/1998/ namespace.htmland http://www.w3.org/TR/REC-xmlfor information about this namespace.</p> <p>Note that local names in this namespace are intended to be defined only by the World Wide Web Consortium or its subgroups. The names currently defined in this namespace are listed below. They should not be used with conflicting semantics by any Working Group, specification, or document instance.</p> <p>See further below in this document for more information about how to refer to this schema document from your own XSD schema documents</ a>and about </pre>

```

    <a href="#nsversioning">the namespace-versioning policy governing this schema document</a>.</
p>
</div>
</div>
<div>
  <h3>Father (in any context at all)</h3>
  <div class="bodytext">
    <p>denotes Jon Bosak, the chair of the original XML Working Group. This name is reserved by the
    following decision of the W3C XML Plenary and XML Coordination groups:</p>
    <blockquote>
      <p>In appreciation for his vision, leadership and dedication the W3C XML Plenary on this 10th
      day of February, 2000, reserves for Jon Bosak in perpetuity the XML name "xml:Father".</p>
    </blockquote>
  </div>
</div>
</div>
<div xml:id="usage" id="usage">
  <h2>
    <a name="usage">About this schema document</a>
  </h2>
  <div class="bodytext">
    <p>This schema defines attributes and an attribute group suitable for use by schemas wishing to
    allow
      <code>xml:base</code>,
      <code>xml:lang</code>,
      <code>xml:space</code>or
      <code>xml:id</code>attributes on elements they define.</p>
    <p>To enable this, such a schema must import this schema for the XML namespace, e.g. as
    follows:</p>
    <pre><schema . . .> . . . <import namespace="http://www.w3.org/XML/1998/namespace"
    schemaLocation="http://www.w3.org/2001/xml.xsd"/></pre>
    <p>or</p>
    <pre><import namespace="http://www.w3.org/XML/1998/namespace" schemaLocation="http://
    www.w3.org/2009/01/xml.xsd"/></pre>
    <p>Subsequently, qualified reference to any of the attributes or the group defined below will
    have the desired effect, e.g.</p>
    <pre><type . . .> . . . <attributeGroup ref="xml:specialAttrs"/></pre>
    <p>will define a type which will schema-validate an instance element with any of those
    attributes.</p>
  </div>
</div>
</div>
<div id="nsversioning" xml:id="nsversioning">
  <h2>
    <a name="nsversioning">Versioning policy for this schema document</a>
  </h2>
  <div class="bodytext">
    <p>In keeping with the XML Schema WG's standard versioning policy, this schema document will
    persist at
      <a href="http://www.w3.org/2009/01/xml.xsd">http://www.w3.org/2009/01/xml.xsd</a>.</p>
    <p>At the date of issue it can also be found at
      <a href="http://www.w3.org/2001/xml.xsd">http://www.w3.org/2001/xml.xsd</a>.</p>
    <p>The schema document at that URI may however change in the future, in order to remain
    compatible with the latest version of XML Schema itself, or with the XML namespace itself. In other
    words, if the XML Schema or XML namespaces change, the version of this document at
      <a href="http://www.w3.org/2001/xml.xsd">http://www.w3.org/2001/xml.xsd</a>will change
    accordingly; the version at
      <a href="http://www.w3.org/2009/01/xml.xsd">http://www.w3.org/2009/01/xml.xsd</a>will not
    change.</p>
    <p>Previous dated (and unchanging) versions of this schema document are at:</p>
    <ul>
      <li>
        <a href="http://www.w3.org/2009/01/xml.xsd">http://www.w3.org/2009/01/xml.xsd</a>
      </li>
      <li>
        <a href="http://www.w3.org/2007/08/xml.xsd">http://www.w3.org/2007/08/xml.xsd</a>
      </li>
      <li>
        <a href="http://www.w3.org/2004/10/xml.xsd">http://www.w3.org/2004/10/xml.xsd</a>
      </li>
      <li>
        <a href="http://www.w3.org/2001/03/xml.xsd">http://www.w3.org/2001/03/xml.xsd</a>
      </li>
    </ul>
  </div>
</div>
</div>

```

Properties	attribute form default:	unqualified
	element form default:	unqualified

Attribute(s)

Attribute @xml:lang

Namespace	http://www.w3.org/XML/1998/namespace
Annotations	lang (as an attribute name) denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification. Notes Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility. See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txt and the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registry for further information. The union allows for the 'un-declaration' of xml:lang with the empty string.
Type	union of(xs:language, restriction of xs:string)
Properties	content: simple
Used by	Complex Types longTextType, shortTextType, textType, titleType Attribute Group xml:specialAttrs
Source	<pre> <xs:attribute name="lang"> <xs:annotation> <xs:documentation> <div> <h3>lang (as an attribute name)</h3> <p>denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> <div> <h3>Notes</h3> <p>Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> <p>See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txt and the IANA language subtag registry at http://www.iana.org/assignments/language-subtag-registry for further information.</p> <p>The union allows for the 'un-declaration' of xml:lang with the empty string.</p> </div> </xs:documentation> </xs:annotation> <xs:simpleType> <xs:union memberTypes="xs:language"> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="" /> </xs:restriction> </xs:simpleType> </xs:union> </xs:simpleType> </xs:attribute> </pre>

Attribute @xml:space

Namespace	http://www.w3.org/XML/1998/namespace
Annotations	space (as an attribute name) denotes an attribute whose value is a keyword indicating what whitespace processing discipline is intended for the content of the element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.
Type	restriction of xs:NCName
Properties	content: simple
Facets	enumeration default

	enumeration	preserve
Used by	Attribute Group	xml:specialAttrs
Source	<pre><xs:attribute name="space"> <xs:annotation> <xs:documentation> <div> <h3>space (as an attribute name)</h3> <p>denotes an attribute whose value is a keyword indicating what whitespace processing discipline is intended for the content of the element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> </div> </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:NCName"> <xs:enumeration value="default"/> <xs:enumeration value="preserve"/> </xs:restriction> </xs:simpleType> </xs:attribute></pre>	

Attribute @xml:base

Namespace	http://www.w3.org/XML/1998/namespace	
Annotations	<pre><div> <h3>base (as an attribute name)</h3> <p>denotes an attribute whose value provides a URI to be used as the base for interpreting any relative URIs in the scope of the element on which it appears; its value is inherited. This name is reserved by virtue of its definition in the XML Base specification.</p> <p>See http://www.w3.org/TR/xmlbase/for information about this attribute.</p> </div></pre>	
Type	xs:anyURI	
Properties	content:	simple
Used by	Attribute Group	xml:specialAttrs
Source	<pre><xs:attribute name="base" type="xs:anyURI"> <xs:annotation> <xs:documentation> <div> <h3>base (as an attribute name)</h3> <p>denotes an attribute whose value provides a URI to be used as the base for interpreting any relative URIs in the scope of the element on which it appears; its value is inherited. This name is reserved by virtue of its definition in the XML Base specification.</p> <p>See http://www.w3.org/TR/xmlbase/for information about this attribute.</p> </div> </xs:documentation> </xs:annotation> </xs:attribute></pre>	

Attribute @xml:id

Namespace	http://www.w3.org/XML/1998/namespace	
Annotations	<pre><div> <h3>id (as an attribute name)</h3> <p>denotes an attribute whose value should be interpreted as if declared to be of type ID. This name is reserved by virtue of its definition in the xml:id specification.</p> <p>See http://www.w3.org/TR/xml-id/for information about this attribute.</p> </div></pre>	
Type	xs:ID	
Properties	content:	simple
Used by	Attribute Group	xml:specialAttrs
Source	<pre><xs:attribute name="id" type="xs:ID"> <xs:annotation> <xs:documentation> <div></pre>	

```

<h3>id (as an attribute name)</h3>
<p>denotes an attribute whose value should be interpreted as if declared to be of type ID.
This name is reserved by virtue of its definition in the xml:id specification.</p>
<p>See
  <a href="http://www.w3.org/TR/xml-id/">http://www.w3.org/TR/xml-id/</a>for information
about this attribute.</p>
</div>
</xs:documentation>
</xs:annotation>
</xs:attribute>

```

Attribute Group(s)

Attribute Group xml: specialAttrs

Namespace	http://www.w3.org/XML/1998/namespace			
Diagram	<pre> graph LR specialAttrs --> xmlbase specialAttrs --> xmlid specialAttrs --> xmlspace specialAttrs --> xmllang </pre>			
Attributes	QName	Type	Use	
	xml:base	xs:anyURI	optional	
		base (as an attribute name)</h3> denotes an attribute whose value provides a URI to be used as the base for interpreting any relative URIs in the scope of the element on which it appears; its value is inherited. This name is reserved by virtue of its definition in the XML Base specification.</p> See http://www.w3.org/TR/xmlbase/for information about this attribute.</p>		
	xml:id	xs:ID	optional	
		id (as an attribute name)</h3> denotes an attribute whose value should be interpreted as if declared to be of type ID. This name is reserved by virtue of its definition in the xml:id specification.</p> See http://www.w3.org/TR/xml-id/for information about this attribute.</p>		
	xml:lang	union of(xs:language, restriction of xs:string)	optional	
		lang (as an attribute name)</h3> denotes an attribute whose value is a language code for the natural language of the content of any element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.</p> Notes</h4> Attempting to install the relevant ISO 2- and 3-letter codes as the enumerated possible values is probably never going to be a realistic possibility.</p> See BCP 47 at http://www.rfc-editor.org/rfc/bcp/bcp47.txtand the IANA language subtag registry at		

QName	Type	Use	
	http://www.iana.org/assignments/language-subtag-registry for further information.	The union allows for the 'un-declaration' of xml:lang with the empty string.	
xml:space	restriction of xs:NCName	optional	
	space (as an attribute name) denotes an attribute whose value is a keyword indicating what whitespace processing discipline is intended for the content of the element; its value is inherited. This name is reserved by virtue of its definition in the XML specification.		
Source	<pre> <xs:attributeGroup name="specialAttrs"> <xs:attribute ref="xml:base"/> <xs:attribute ref="xml:lang"/> <xs:attribute ref="xml:space"/> <xs:attribute ref="xml:id"/> </xs:attributeGroup> </pre>		