

InventiX — Frontend Build Record

Everything done after the screens were written: environment, packages, configuration and commands.

Project InventiX Team Team 4 Date 2 September 2026 Scope frontend/ only Status running on device

77

source files

7,711

lines of code

30

screens

16

dependencies

54

Expo SDK

1. What was verified

Check	How	Result
Types are sound	<code>npx tsc --noEmit</code>	Exits 0, no errors
Compiles to a shippable bundle	<code>npx expo export --platform ios</code>	Bundle produced from every module
Dev server serves the right SDK	<code>curl</code> the Metro manifest	sdkVersion 54.0.0
Phone can fetch the bundle	<code>curl</code> the launch bundle URL	HTTP 200
Renders on a real device	Expo Go on iPhone	Confirmed by the team

2. Environment

Component	Version / value
Operating system	Windows 10 Pro (19045)
Node.js	24.16.0
npm	11.13.0
Project folder	F:\Projects\InventiX\Project\frontend
Expo SDK	54.0.37
React Native	0.81.5
React	19.1.0
TypeScript	5.9.2
Packages in node_modules	410 top-level folders

Why SDK 54 and not the newest. npm reports Expo 57 as latest, but Expo Go from the App Store only runs one SDK at a time, and that is whatever `expoGoSdkVersion` reports — 54.0.0. Targeting anything newer produces "Project is incompatible with this version of Expo Go" on the phone no matter how current the app is. Upgrading past 54 means leaving Expo Go for a custom development build, which needs an Apple developer account for iOS.

3. Commands run in cmd

In order, all from the `frontend` folder. Three full installs were needed because the SDK version was wrong twice before Expo Go was asked what it actually supports.

#	Command	Purpose and outcome
1	<code>npm install</code>	First install on SDK 57 versions. 634 packages — wrong SDK .
2	<code>npx tsc --noEmit</code>	Typecheck. 18 errors, all fixed.
3	<code>npx expo export --platform ios</code>	Prove it bundles. Failed — <code>rn-get-polyfills</code> missing.
4	<code>npx expo install --fix</code>	Align versions. Failed — the CLI itself was incomplete.
5	<code>npx create-expo-app tmpl --template blank-typescript</code>	Read Expo's own correct versions from a fresh template.
6	<code>npm install</code>	Clean reinstall on corrected versions. 585 packages.
7	<code>npx expo export</code>	Retry. Failed — <code>babel-preset-expo</code> missing.
8	<code>npx expo export</code>	After removing a hand-written babel config. Bundle built .
9	<code>npx expo start</code>	Failed — a bad <code>--tunnel=false</code> flag triggered a tunnel prompt.
10	—	Phone reported the Expo Go SDK mismatch. Root cause finally visible.
11	<code>curl api.expo.dev/v2/versions/latest</code>	Ask Expo which SDK Expo Go runs. Answer: 54.0.0 .
12	<code>npm install</code>	Third clean install, this time on the SDK 54 base.
13	<code>npx expo install <13 packages></code>	Let Expo choose every version for SDK 54. Consistent tree .
14	<code>npx tsc --noEmit</code>	Typecheck. 11 route errors surfaced by typed routes, all fixed.
15	<code>npx expo export --platform ios</code>	Bundle built on SDK 54 .
16	<code>npx expo start</code> + <code>curl</code> the manifest	Confirm the SDK the phone will see. 54.0.0 .
17	<code>curl</code> the launch bundle	Fetch exactly what the phone downloads. HTTP 200 .
18	<code>taskkill /PID 9036 /F</code>	Clear an orphaned Metro process holding port 8081.

The lesson worth recording. Step 11 should have been step 1. "Latest on npm" and "what the installed Expo Go can run" are different questions, and only the second one matters while the team is testing through Expo Go.

4. Packages installed

Runtime dependencies (16)

Package	Version	Why it is here
expo	~54.0.37	The SDK itself.

expo-router	~6.0.24	File-based navigation — the folder tree is the route tree.
expo-constants	~18.0.14	Required by expo-router.
expo-linking	~8.0.12	Required by expo-router; deep links.
expo-status-bar	~3.0.9	Status bar styling over the yellow app bar.
expo-splash-screen	~31.0.13	Holds the splash while the session is restored.
expo-document-picker	~14.0.8	CSV / Excel picker for the sales upload (spec 6.6).
react	19.1.0	—
react-native	0.81.5	Pinned by SDK 54.
react-native-safe-area-context	~5.6.0	Notch and home-indicator insets.
react-native-screens	~4.16.0	Native navigation primitives.
react-native-svg	15.12.1	The three-segment stock donut (spec 6.2).
@expo/vector-icons	^15.0.3	Every icon in the app. Ships with Expo.
@react-native-async-storage/async-storage	2.2.0	Persists the Supabase session across app restarts.
@supabase/supabase-js	^2.113.0	Auth and realtime.
react-native-url-polyfill	^4.0.0	Supabase needs a WHATWG URL on React Native.

Development dependencies (3)

Package	Version	Why it is here
typescript	~5.9.2	Typecheck via <code>npm run typecheck</code> .
@types/react	~19.1.10	React type definitions.
babel-preset-expo	~54.0.10	Required by SDK 54's babel config.

Only two were choices. `react-native-svg` and `expo-document-picker`. A three-segment donut is roughly eighty lines of rotated-View trickery without SVG, and there is no file upload at all without the picker. Everything else is Expo's own baseline for SDK 54.

5. Configuration files created

None of these existed. The project's own `frontend/README.md` had already flagged them as missing, because Expo's generator refuses to run into a non-empty folder.

File	What it sets
<code>package.json</code>	Dependencies and scripts. The critical line is <code>"main": "expo-router/entry"</code> , which makes file-based routing the entry point.
<code>app.json</code>	App name, slug, <code>scheme: inventix</code> for deep links, bundle id <code>lk.inventix.app</code> , icon and splash paths, brand yellow <code>#FFD94D</code> as the splash and adaptive-icon background, and <code>typedRoutes: true</code> .
<code>tsconfig.json</code>	<code>strict: true</code> and an <code>@/*</code> alias pointing at <code>src/</code> .
<code>babel.config.js</code>	<code>babel-preset-expo</code> . Required by SDK 54.
<code>.gitignore</code>	Keeps <code>node_modules/</code> , <code>.expo/</code> and — critically — <code>.env</code> out of git.
<code>.env.example</code>	The two Supabase values, with a note that a <code>service_role</code> key must never go here.

Environment template

```
# Copy to .env and fill in. Expo only exposes variables prefixed EXPO_PUBLIC_.
# Both of these are safe in the app: the anon key is public by design and is
# constrained by row level security. Never put a service_role key here.
EXPO_PUBLIC_SUPABASE_URL=https://your-project.supabase.co
EXPO_PUBLIC_SUPABASE_ANON_KEY=your-anon-key
```

6. Assets generated

Cut from the logo in the Figma file. No upload was needed — the mark was extracted from the design, keyed off its white card, and rendered at each required size.

File	Size	Bytes	Used for
<code>icon.png</code>	1024 × 1024	218 KB	App icon
<code>adaptive-icon.png</code>	1024 × 1024	166 KB	Android adaptive foreground, on yellow
<code>splash-icon.png</code>	512 × 512	105 KB	Splash, transparent background
<code>favicon.png</code>	64 × 64	2.7 KB	Web

The icon is mildly soft because it was upscaled from the Figma page render — the logo exists there only as part of a larger board. Fine for development; a clean 1024 px export or the original vector is worth having before any store submission.

7. Code changed after it was written

Two rounds, both mechanical rather than design changes.

Round one — React Native type strictness (8 files)

- `StyleProp<ViewStyle>` on Button, Card and Input, so they accept style arrays from callers.
- `StyleSheet.absoluteFillObject` written out longhand — it is gone from the generated types.
- A null-guard captured before the cleanup closure in `useRealtime`.
- An explicit return type on `elevation()`, which `Platform.select` had widened to a union.

Round two — typed routes (10 files)

Every `router.push('/stocks/' + id)` became `router.push(`/stocks/${id}`)`. String concatenation defeats route type-checking. This one is an improvement rather than a repair: a mistyped route now fails at compile time instead of dead-ending at runtime.

8. Deviations worth recording

Deviation	Reason
System font, not Inter	<code>typography.ts</code> specifies Inter. Inter needs a font package plus an async load gate at startup, which would tangle with the session-restore splash. San Francisco on iOS and Roboto on Android both read as modern. Marked with a <code>ponytail:</code> comment and an upgrade path.
<code>src/hooks/useAsync.ts</code> added	Not in <code>02-file-structure.md</code> . Without it, five data hooks were five copies of the same fifteen lines of loading / error / refresh state.
Assets folder added	<code>frontend/assets/</code> is not in the file-structure document either, but Expo requires it for the icon and splash.

9. Running it

Both devices must be on the same Wi-Fi. The phone needs Expo Go from the App Store.

```
cd /d F:\Projects\InventiX\Project\frontend
npx expo start
```

Scan the QR code with the iPhone Camera app and tap the banner. On Android, scan from inside Expo Go instead. `Ctrl + C` stops the server.

If this happens	Do this
Windows Firewall prompt appears	Click Allow access , or the phone cannot reach the PC.
Stuck at "Downloading 100%"	Almost always a Wi-Fi mismatch between phone and PC.
Still will not connect	<code>npx expo start --tunnel</code> — routes over the internet, slower.
Port 8081 already in use	<code>npx expo start --port 8082</code> , or kill the stale Metro process.
"Incompatible with this version of Expo Go"	The SDK moved. Check <code>expoGoSdkVersion</code> before changing the Expo version.

10. Current state and what is next

The frontend is complete and runs on device: 30 screens, 47 supporting modules, 7,711 lines, no placeholder files remaining. With no backend connected the login screen offers a sample-data entry point for each role, so every screen is walkable today. That panel disappears on its own once the two Supabase values are set in `.env`.

Open items. Five decisions still need writing into `docs/04-decision-log.md` as D-006 to D-010: Reports without charts, language deferred, the numeric score on the supplier profile, the New-supplier badge threshold of three, and the authentication flow. After that, the backend.