Experiment-12

12.Port Scanning Tools

```
SEE THE MAN PAGE (https://nmap.org/book/man.html) FOR MORE OPTIONS AND EXAMPLES
┌──(kali㉿kali)-[~]
└─$ nmap -sS 192.168.1.2
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-27 00:10 -0400
Nmap scan report for 192.168.1.2
Host is up (0.0013s latency).
All 1000 scanned ports on 192.168.1.2 are in ignored states.
Not shown: 1000 filtered tcp ports (no-response)

Nmap done: 1 IP address (1 host up) scanned in 5.40 seconds
┌──(kali㉿kali)-[~]
└─$ nmap -sT 192.168.1.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-27 00:11 -0400
Nmap scan report for 192.168.1.1
Host is up (0.0014s latency).
All 1000 scanned ports on 192.168.1.1 are in ignored states.
Not shown: 1000 filtered tcp ports (no-response)

Nmap done: 1 IP address (1 host up) scanned in 22.58 seconds
```

```
┌──(kali㉿kali)-[~]
└─$ nmap -sU 192.168.1.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-27 00:14 -0400
Nmap scan report for 192.168.1.1
Host is up (0.0014s latency).
All 1000 scanned ports on 192.168.1.1 are in ignored states.
Not shown: 1000 open|filtered udp ports (no-response)

Nmap done: 1 IP address (1 host up) scanned in 5.46 seconds
┌──(kali㉿kali)-[~]
└─$ nmap -sA 192.168.1.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-27 00:14 -0400
Nmap scan report for 192.168.1.1
Host is up (0.00075s latency).
All 1000 scanned ports on 192.168.1.1 are in ignored states.
Not shown: 1000 unfiltered tcp ports (reset)

Nmap done: 1 IP address (1 host up) scanned in 0.98 seconds
```