LPG Generator Sets — Technical Datasheet

Prime power range 15–350 kVA · Genset at 50 Hz, 400/230 V, 1,500 rpm, 3-phase 4-wire

Standard on every set: in-line four-stroke gas engine with electronic ignition, water-cooled · Pulita brushless alternator with AVR · Smartgen controller · 50 Hz (60 Hz available) · special voltages available.

Model	Prime power kW / kVA	Standby power kW / kVA	Gas engine model	Cylinders	LPG use at 100% load (kg/h)	Open type L × W × H (mm)	Open weight (kg)	Soundproof type L × W × H (mm)	Soundproof wt. (kg)
15 kVA	12/15	13.2/16.5	PW1.8T-NG	4 in line	**3**	1800 × 700 × 1100	650	2200 × 1050 × 1400	950
20 kVA	16/20	17.6/22	PW2.2T-NG	4 in line	**4**	1850 × 800 × 1100	800	2200 × 1050 × 1450	980
25 kVA	20/25	22/27.5	PI2.7-NG	4 in line	**5**	1850 × 900 × 1150	900	2200 × 1050 × 1450	1,000
30 kVA	24/30	26.4/33	PI2.7T-NG	4 in line	**6**	1850 × 900 × 1150	900	2200 × 1050 × 1450	1,000
40 kVA	32/40	35.2/44	PC3.9TA-NG	4 in line	**8**	1850 × 900 × 1150	950	2400 × 1050 × 1450	1,050
50 kVA	40/50	44/55	PC3.9TA-NG	4 in line	**10**	1850 × 900 × 1150	980	2400 × 1050 × 1450	1,080
60 kVA	48/60	52.8/66	PC5.9-NG	6 in line	**12**	2250 × 1050 × 1300	1,000	2800 × 1050 × 1650	1,400
80 kVA	64/80	70.4/88	PC5.9TA-NG	6 in line	**16**	2250 × 1050 × 1300	1,100	2800 × 1050 × 1650	1,600
100 kVA	80/100	88/110	PC5.9TA-NG	6 in line	**20**	2250 × 1050 × 1300	1,140	2800 × 1050 × 1650	1,640
125 kVA	100/125	110/137	PC8.3TA-NG	6 in line	**25**	2400 × 1100 × 1400	1,800	3000 × 1250 × 1800	2,500
150 kVA	120/150	132/165	PC8.3TA-NG	6 in line	**28.8**	2400 × 1100 × 1400	1,860	3000 × 1250 × 1800	2,560
180 kVA	150/180	165/196	PC8.9TA-NG	6 in line	**36**	2800 × 1100 × 1550	1,890	3100 × 1180 × 1960	2,600
200 kVA	160/200	176/220	PW10TA-NG	6 in line	**38.4**	2850 × 1100 × 1550	1,950	3300 × 1250 × 2060	2,800
250 kVA	200/250	220/275	PW12TA-NG	6 in line	**48**	3100 × 1100 × 1780	2,400	3600 × 1450 × 2060	2,900
300 kVA	240/300	264/330	PW13TA-NG	6 in line	**57.6**	3100 × 1100 × 1780	2,500	3800 × 1550 × 2160	3,200
350 kVA	280/350	308/385	PC15TA-NG	6 in line	**67.2**	3100 × 1100 × 1780	2,580	3800 × 1550 × 2160	3,380

- LPG consumption is at 100% load. All LPG sets in this table also run on natural gas (CNG).
- Options: Stamford, Leroy Somer or Marathon alternators; Deepsea, DEIF or ComAp controllers; soundproof canopy, ATS, parallel & synchronisation control, CHP, CNG cascades and PRMS.
- Certified: ISO 9001, ISO 14001, ISO 45001, CE. SONCAP Product Certificate (Registered) PC(R) No. CSIC26NPR0141 covers the 300 kVA and 1,000 kVA generator sets. Data may vary with production requirements or improved technology.