Lab: Midterm Review

Hye-Chung Kum

Population Informatics Research Group

http://research.tamhsc.edu/pinformatics/

http://pinformatics.web.unc.edu/

Course URL:
http://pinformatics.tamhsc.edu/phpm672

Midterm: Responsible materials

- Readings from the Little SAS Book
  - All sections in chapter 1
  - All sections in chapter 2
  - All sections in chapter 3
  - Sections 4.1 to 4.10 in chapter 4
  - All sections in chapter 6
  - Note that some of the materials were not covered in class or assignment, but you are responsible for anything covered in the required reading from the book
- Other materials
  - All class notes upto 3/10 (slides on the class website).
  - None of the articles are part of the midterm (except to the extent covered in class on the notes)

Questions

- Quizzes
- Assignments
- Labs

SAS Basics

- program/log/output
- libname
- ;
- setting up work environment
  - How you will use the software
  - How you will organize your files

What is a **Variable**?

- A user defined name to represent a piece of memory for storing evaluated value(s). A variable consists of 5 items

Name:

How the user refers to variable. Understandable by both human and computer

Label:

meaningful human friendly descriptions of the variable

Data Type: number or string (character=string of length 1)

How to interpret variable for data representation

Size:

How much storage memory is needed to store data value

Can be inferred from data type

Value:

Actual value associated with variable

stored in memory

Storage location:

Usually hidden from user by the interpreter or compiler

How the computer refers to a variable

For Our Purposes: Columns

Many variables. A columns of variables

Variable naming rules

- Starts with a single letter or underscore followed by any number of letters, digits, or underscores.
- Digits `[0-9]`, Letters `[a-zA-Z]`, Underscore '_'
- No special characters
- Small or Large does not matter in SAS

Formats

- Create using proc format
- Use Case 1: Labeling values
  - Assign using format statement
  - Only used interpret the value (ie. printing, display)
- Use Case 2: Can be used to recode variables (know how different)
  - put(var, format)
  - new variable type? Value?

```
proc format;
   value gender
   1= 'Male'
   2= 'Female'
   other= 'Missing' ;
```

```
* In data step;
data outfn;
set infn;

csex $7.;
csex=put(sex, gender.);
```

Boolean expression evaluation

- X || (Y & X)

X	Y		X||Y&X

SAS

- keywords
  - data, set, merge, obs, where, if, do, end, keep, drop, rename, label, in
  - array
  - proc
    - sort, print, summary, transpose, freq
- functions
  - put ()
  - compress ()
  - lowcase () / upcase ()

Arrays

- Array n{*} n9-n23;
- Array a{*} $7. a11-a23;
- Name? n and a
- How many elements? N=15 a=13
- Type? N=number, a=string of length 7
- n15 index? 7

ever{1}	ever{2}	ever{3}	ever{4}
cigever	alcever	cocever	mjever

bever{1}	bever{2}	bever{3}	bever{4}
bcigever	balcever	bcocever	bmjever

```
* Brute Force:  Cut & Paste & Tweak
if cigever=1 then bcigever=1;
else if cigever=2 then bcigever=0;

if alcever=1 then balcever=1;
else if alcever=2 then balcever=0;

if cocever=1 then bcocever=1;
else if cocever=2 then bcocever=0;

if mjever=1 then bmjever=1;
else if mjever in (0,2) then bmjever=0;

* Using arrays is much more elegant and accurate;
array ever{4} cigever alcever cocever mjever;
array bever{4} bcigever balcever bcocever bmjever;
do i=1 to 4;
  if ever{i}=1 then bever{i}=1;
  else if ever{i} in (0,2) then bever{i}=0;
end;
```

loops

- How many times?
- Do while (cond)
  - correct expression

Table Operations: 1 table → 1 table (reshaping)

- Proc Transpose

1	2
a	d
b	e
c	f

→

1	a	b	c
2	d	e	f

- Proc Summary

A
B
C

→

D

Where D=function(A,B,C)
Examples of function are
Sum(A,B,C) Mean(A,B,C) Max(A,B,C) Min(A,B,C)

Table Operations: multiple table → 1 table

- set (Append)



- merge (link)



lab 3

- proc transpose by

Record Linkage
Inherent Nature of Real Data

- Data are expressed differently
  - nick names
- Data change over time
  - person's last name
- Data are not unique attributes
  - John Smith
- Missing Data
  - ssn are often missing
- Errors in Data
  - Rule of thumb : 5% error in administrative data

Record Linkage

- When merging data
  - Use numeric codes whenever possible
  - Remember to use uniform formatting
  - Use string functions to standardize variables
  - Check if the key provides unique rows
    - 1-to-1 or 1-to-N mapping
- Pay attention to what rows link and what do not
- Consider how many rows should link
  - Example: 20% expected 18% achieved
- Validate by printing
  - Links made
  - Links not made

Common log messages

- NOTE: Variable yea is uninitialized
- ERROR: Array subscript out of range at line 45 column 3
- NOTE: MERGE statement has more than one data set with repeats of BY values.
- ERROR: BY variables are not properly sorted on data set WORK.FN

Assignment 1

- Setup work environment
- Use the SAS software
- SAS programming basics
  - data step & proc step
  - Libname (where is the folder with the data?)
  - Writing code & Reading logs

Assignment 2

- Understand variables (names, types, labels)
- To write conditional logic codes
- Subset columns (variables) from a table
- Subset rows (observations) from a table
- Recode, rename variables and calculate new variables
- Label variables and values

Assignment 3

- use for loops (iterative loops)
- use while loops (conditional loops)
- SAS: use one dimensional arrays

Assignment 4

- **Concatenate multiple tables (more rows)**
  - **stack tables on top of each other to increase the number of rows**
  - using `set`
  - Be sure to understand the different behavior given different situations (i.e. what happens to shared variables? What happens to not shared variables?)
- **Link up multiple tables using a shared key (more columns)**
  - **align the rows using the shared key, and link multiple tables to increase the number of variables in the tables**
  - using `merge`
  - Be sure to understand the different behavior given different situations (i.e. what happens to shared vars? What happens to not shared vars?)
  - What is a 1-to-1 link
  - What is a 1-to-N link
  - What is a N-to-N link (you will not be doing this, but need to understand what this is. This must be done with proc sql in SAS)

Assignment 4 continued

- Combine multiple rows into one row
  - by group processing `proc summary`
- Reshape table to flip rows & columns
  - using `proc transpose`
  - Also transpose (flip rows & columns) by groups or row

Midterm format (20%)

- 25 questions (about 2*25=50 points)
  - On BB
  - multiple choice similar to quiz
  - Closed book
  - 1-2: 1hour
- 5 questions (50 points)
  - Open book / open notes / use SAS
  - Programming/debugging questions
  - submit by 5pm on BB

Open Response (3h)

- Write SAS code to (8*5=40pts)
  - Data Step 1
    - Q1.1 read in datasets X1..Xn and make new dataset Y
    - Q1.2 keep, rename, label variables v1-vn
    - Q1.3 code variable c1
    - Q1.4 use arrays and loops to recode variable c2
  - Proc Steps
    - Q2.5 convert dataset Y to dataset Z
    - Q2.6 Find and show descriptive (avg/max/median) (Must use SAS code)
  - Data Step 2
    - Q2.7 link in dataset L to dataset Y
    - Q2.8 Print observations meeting condition (Must use SAS code)
  - Typically few lines of code per question
  - Submit code/log/output
- Debug the following code (10pts)
  - Fix the program to run properly
  - Submit code/log/output
- Extra Credit (10pts)

```
******** Section 1: Frist Data Step *******;
code

* Q1.1;
code

* Q1.2;
code

******** Section 2: Proc Steps *******;
* Q2.7;
code

******** Section 3: Second Data Step *******;
```

This week

- Friday Lab
  - Cancelled since midterm went out