Chapter 1

Demo problem: Solution of a Poisson problem in an "elastic" domain

Detailed documentation to be written. Here's a plot of the result and the already fairly well documented driver code...




Figure 1.1 Adaptive solution of Poisson's equation in a fish-shaped domain for various `widths' of the domain. The update of the nodal positions in response to changes in the boundary shape is done by pseudo-elasticity.

```
//LIC// ====================================================================
//LIC// This file forms part of oomph-lib, the object-oriented,
//LIC// multi-physics finite-element library, available
//LIC// at http://www.oomph-lib.org.
//LIC//
//LIC// Copyright (C) 2006-2026 Matthias Heil and Andrew Hazel
//LIC//
//LIC// This library is free software; you can redistribute it and/or
//LIC// modify it under the terms of the GNU Lesser General Public
//LIC// License as published by the Free Software Foundation; either
//LIC// version 2.1 of the License, or (at your option) any later version.
//LIC//
//LIC// This library is distributed in the hope that it will be useful,
//LIC// but WITHOUT ANY WARRANTY; without even the implied warranty of
//LIC// MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the GNU
//LIC// Lesser General Public License for more details.
```

```
//LIC//
//LIC// You should have received a copy of the GNU Lesser General Public
//LIC// License along with this library; if not, write to the Free Software
//LIC// Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA
//LIC// 02110-1301  USA.
//LIC//
//LIC// The authors may be contacted at oomph-lib@maths.man.ac.uk.
//LIC//
//LIC//====================================================================
// Solve Poisson equation in deformable fish-shaped domain.
// Mesh deformation is driven by pseudo-elasticity approach.

// Generic oomph-lib headers
#include "generic.h"

// Poisson equations
#include "poisson.h"

// Solid mechanics
#include "solid.h"
// The fish mesh
#include "meshes/fish_mesh.h"

// Circle as generalised element:
#include "circle_as_generalised_element.h"

using namespace std;

using namespace oomph;

////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////



//====================================================================
/// Namespace for const source term in Poisson equation
//====================================================================
namespace ConstSourceForPoisson
{
 /// Strength of source function: default value 1.0
 double Strength=1.0;

/// Const source function
 void get_source(const Vector<double>& x, double& source)
 {
  source = -Strength;
 }
}

////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////

//============================================================================
/// Refineable fish mesh upgraded to become a solid mesh
//============================================================================
template<class ELEMENT>
class ElasticFishMesh : public virtual RefineableFishMesh<ELEMENT>,
                        public virtual SolidMesh
{

public:

 /// Constructor: Build underlying adaptive fish mesh and then
 /// set current Eulerian coordinates to be the Lagrangian ones.
 /// Pass pointer to geometric objects that specify the
 /// fish's back in the "current" and "undeformed" configurations,
 /// and pointer to timestepper (defaults to Static)
 // Note: FishMesh is virtual base and its constructor is automatically
 // called first! --> this is where we need to build the mesh;
 // the constructors of the derived meshes don't call the
 // base constructor again and simply add the extra functionality.
 ElasticFishMesh(GeomObject* back_pt, GeomObject* undeformed_back_pt,
                 TimeStepper* time_stepper_pt=&Mesh::Default_TimeStepper) :
  FishMesh<ELEMENT>(back_pt,time_stepper_pt),
  RefineableFishMesh<ELEMENT>(back_pt,time_stepper_pt)
  {
   // Mesh has been built, adaptivity etc has been set up -->
   // assign the Lagrangian coordinates so that the current
   // configuration becomes the stress-free initial configuration
   set_lagrangian_nodal_coordinates();

   // Build "undeformed" domain: This is a "deep" copy of the
   // Domain that we used to create set the Eulerian coordinates
   // in the initial mesh -- the original domain (accessible via
```

```
   // the private member data Domain_pt) will be used to update
   // the position of boundary nodes; the copy that we're
   // creating here will be used to determine the Lagrangian coordinates
   // of any newly created SolidNodes during mesh refinement
   double xi_nose = this->Domain_pt->xi_nose();
   double xi_tail = this->Domain_pt->xi_tail();
   Undeformed_domain_pt=new FishDomain(undeformed_back_pt,xi_nose,xi_tail);

   // Loop over all elements and set the undeformed macro element pointer
   unsigned n_element=this->nelement();
   for (unsigned e=0;e<n_element;e++)
    {
     // Get pointer to full element type
     ELEMENT* el_pt=dynamic_cast<ELEMENT*>(this->element_pt(e));

     // Set pointer to macro element so the curvlinear boundaries
     // of the undeformed mesh/domain get picked up during adaptive
     // mesh refinement
     el_pt->set_undeformed_macro_elem_pt(
      Undeformed_domain_pt->macro_element_pt(e));
    }

  }

 /// Destructor: Kill "undeformed" Domain
 virtual ~ElasticFishMesh()
  {
   delete Undeformed_domain_pt;
  }

private:

 /// Pointer to "undeformed" Domain -- used to determine the
 /// Lagrangian coordinates of any newly created SolidNodes during
 /// Mesh refinement
 Domain* Undeformed_domain_pt;

};



////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////



//==================================================================
/// Global variables
//==================================================================
namespace Global_Physical_Variables
{
 /// Pointer to constitutive law
 ConstitutiveLaw* Constitutive_law_pt;

 /// Poisson's ratio
 double Nu=0.3;

}


////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////
////////////////////////////////////////////////////////////////////////



//====================================================================
/// Solve Poisson equation on deforming fish-shaped domain.
/// Mesh update via pseudo-elasticity.
//====================================================================
template<class ELEMENT>
class DeformableFishPoissonProblem : public Problem
{

public:

 /// Constructor:
 DeformableFishPoissonProblem();

 /// Run simulation
 void run();

 /// Access function for the specific mesh
 ElasticFishMesh<ELEMENT>* mesh_pt()
```

```
  {return dynamic_cast<ElasticFishMesh<ELEMENT>*>(Problem::mesh_pt());}

 /// Doc the solution
 void doc_solution(DocInfo& doc_info);

 /// Update function (empty)
 void actions_after_newton_solve() {}

 /// Update before solve: We're dealing with a static problem so
 /// the nodal positions before the next solve merely serve as
 /// initial conditions. For meshes that are very strongly refined
 /// near the boundary, the update of the displacement boundary
 /// conditions (which only moves the SolidNodes *on* the boundary),
 /// can lead to strongly distorted meshes. This can cause the
 /// Newton method to fail --> the overall method is actually more robust
 /// if we use the nodal positions as determined by the Domain/MacroElement-
 /// based mesh update as initial guesses.
 void actions_before_newton_solve()
  {
   bool update_all_solid_nodes=true;
   mesh_pt()->node_update(update_all_solid_nodes);
  }

 /// Update after adapt: Pin all redundant solid pressure nodes (if required)
 void actions_after_adapt()
  {
   // Pin the redundant solid pressures (if any)
   PVDEquationsBase<2>::pin_redundant_nodal_solid_pressures(
    mesh_pt()->element_pt());
  }

private:


 /// Node at which the solution of the Poisson equation is documented
 Node* Doc_node_pt;

 /// Trace file
 ofstream Trace_file;

 // Geometric object/generalised element that represents the deformable
 // fish back
 ElasticallySupportedRingElement* Fish_back_pt;

};



//==========================================================================
/// Constructor:
//==========================================================================
template<class ELEMENT>
DeformableFishPoissonProblem<ELEMENT>::DeformableFishPoissonProblem()
{

 // Set coordinates and radius for the circle that will become the fish back
 double x_c=0.5;
 double y_c=0.0;
 double r_back=1.0;

 // Build geometric object/generalised element that will become the
 // deformable fish back
 Fish_back_pt=new ElasticallySupportedRingElement(x_c,y_c,r_back);

 // Build geometric object/generalised that specifies the fish back in the
 // undeformed configuration (basically a deep copy of the previous one)
 GeomObject* undeformed_fish_back_pt=new
  ElasticallySupportedRingElement(x_c,y_c,r_back);

 // Build fish mesh with geometric object that specifies the deformable
 // and undeformed fish back
 Problem::mesh_pt()=new ElasticFishMesh<ELEMENT>(Fish_back_pt,
                                                 undeformed_fish_back_pt);


 // Choose a node at which the solution is documented: Choose
 // the central node that is shared by all four elements in
 // the base mesh because it exists at all refinement levels.
 // How many nodes does element 0 have?
 unsigned nnod=mesh_pt()->finite_element_pt(0)->nnode();

 // The central node is the last node in element 0:
 Doc_node_pt=mesh_pt()->finite_element_pt(0)->node_pt(nnod-1);

 // Doc
 cout « std::endl «  "Control node is located at: "
```

```
     « Doc_node_pt->x(0) « " " « Doc_node_pt->x(1) « std::endl « std::endl;


// Set error estimator
Z2ErrorEstimator* error_estimator_pt=new Z2ErrorEstimator;
mesh_pt()->spatial_error_estimator_pt()=error_estimator_pt;
// Change/doc targets for mesh adaptation
if (CommandLineArgs::Argc>1)
 {
  mesh_pt()->max_permitted_error()=0.05;
  mesh_pt()->min_permitted_error()=0.005;
 }
mesh_pt()->doc_adaptivity_targets(cout);


// Specify BC/source fct for Poisson problem:
//-------------------------------------------

// Set the Poisson boundary conditions for this problem: All nodes are
// free by default -- just pin the ones that have Dirichlet conditions
// here.
unsigned num_bound = mesh_pt()->nboundary();
for(unsigned ibound=0;ibound<num_bound;ibound++)
 {
  unsigned num_nod=mesh_pt()->nboundary_node(ibound);
  for (unsigned inod=0;inod<num_nod;inod++)
   {
    mesh_pt()->boundary_node_pt(ibound,inod)->pin(0);
   }
 }

// Set homogeneous boundary conditions for the Poisson equation
// on all boundaries
for(unsigned ibound=0;ibound<num_bound;ibound++)
 {
  // Loop over the nodes on boundary
  unsigned num_nod=mesh_pt()->nboundary_node(ibound);
  for (unsigned inod=0;inod<num_nod;inod++)
   {
    mesh_pt()->boundary_node_pt(ibound,inod)->set_value(0,0.0);
   }
 }

/// Loop over elements and set pointers to source function
unsigned n_element = mesh_pt()->nelement();
for(unsigned i=0;i<n_element;i++)
 {
  // Upcast from FiniteElement to the present element
  ELEMENT *el_pt = dynamic_cast<ELEMENT*>(mesh_pt()->element_pt(i));

  //Set the source function pointer
  el_pt->source_fct_pt() = &ConstSourceForPoisson::get_source;
 }


// Specify BC/source fct etc for (pseudo-)Solid problem
//-----------------------------------------------------

// Pin all nodal positions
for(unsigned ibound=0;ibound<num_bound;ibound++)
 {
  unsigned num_nod=mesh_pt()->nboundary_node(ibound);
  for (unsigned inod=0;inod<num_nod;inod++)
   {
    for (unsigned i=0;i<2;i++)
     {
      mesh_pt()->boundary_node_pt(ibound,inod)->pin_position(i);
     }
   }
 }

//Loop over the elements in the mesh to set Solid parameters/function pointers
for(unsigned i=0;i<n_element;i++)
 {
  //Cast to a solid element
  ELEMENT *el_pt = dynamic_cast<ELEMENT*>(mesh_pt()->element_pt(i));

  // Set the constitutive law
  el_pt->constitutive_law_pt() =
   Global_Physical_Variables::Constitutive_law_pt;

 }

// Pin the redundant solid pressures (if any)
PVDEquationsBase<2>::pin_redundant_nodal_solid_pressures(
```

```
  mesh_pt()->element_pt());

 //Attach the boundary conditions to the mesh
 cout << assign_eqn_numbers() << std::endl;

 // Refine the problem uniformly (this automatically passes the
 // function pointers/parameters to the finer elements
 refine_uniformly();

 // The non-pinned positions of the newly SolidNodes will have been
 // determined by interpolation. Update all solid nodes based on
 // the Mesh's Domain/MacroElement representation.
 bool update_all_solid_nodes=true;
 mesh_pt()->node_update(update_all_solid_nodes);

 // Now set the Eulerian equal to the Lagrangian coordinates
 mesh_pt()->set_lagrangian_nodal_coordinates();
}


//======================================================================
/// Doc the solution
//======================================================================
template<class ELEMENT>
void DeformableFishPoissonProblem<ELEMENT>::doc_solution(DocInfo& doc_info)
{
 ofstream some_file;
 char filename[100];

 // Number of plot points
 unsigned npts = 5;

 // Call output function for all elements
 snprintf(filename, sizeof(filename), "%s/soln%i.dat",doc_info.directory().c_str(),
         doc_info.number());
 some_file.open(filename);
 mesh_pt()->output(some_file,npts);
 some_file.close();


 // Write vertical position of the fish back, and solution at
 // control node to trace file
 Trace_file
  << static_cast<Circle*>(mesh_pt()->fish_back_pt())->y_c()
  << " " << Doc_node_pt->value(0) << std::endl;

}

//======================================================================
/// Run the problem
//======================================================================
template<class ELEMENT>
void DeformableFishPoissonProblem<ELEMENT>::run()
{

 // Output
 DocInfo doc_info;

 // Set output directory
 doc_info.set_directory("RESLT");

 // Step number
 doc_info.number()=0;
 // Open trace file
 char filename[100];
 snprintf(filename, sizeof(filename), "%s/trace.dat",doc_info.directory().c_str());
 Trace_file.open(filename);

 Trace_file << "VARIABLES=\"y<sub>circle</sub>\",\"u<sub>control</sub>\""
            << std::endl;

  //Parameter incrementation
 unsigned nstep=5;
 for(unsigned i=0;i<nstep;i++)
  {
   //Solve the problem with Newton's method, allowing for up to 2
   //rounds of adaptation
   newton_solve(2);

   // Doc solution
   doc_solution(doc_info);
   doc_info.number()++;

   // Increment width of fish domain
   Fish_back_pt->y_c()+=0.03;
```

```
  }

}

//======================================================================
/// Driver for simple elastic problem.
/// If there are any command line arguments, we regard this as a
/// validation run and perform only a single step.
//======================================================================
int main(int argc, char* argv[])
{

 // Store command line arguments
 CommandLineArgs::setup(argc,argv);

 //Set physical parameters
 Global_Physical_Variables::Nu = 0.4;
 // Define a constitutive law (based on strain energy function)
  Global_Physical_Variables::Constitutive_law_pt =
   new GeneralisedHookean(&Global_Physical_Variables::Nu);


  // Set up the problem: Choose a hybrid element that combines the
  // 3x3 node refineable quad Poisson element with a displacement-based
  // solid-mechanics element (for the pseudo-elastic mesh update in response
  // to changes in the boundary shape)
  DeformableFishPoissonProblem<
   RefineablePseudoSolidNodeUpdateElement<RefineableQPoissonElement<2,3>,
   RefineableQPVDElement<2,3>  >
                              > problem;

  problem.run();


}
```

1.1 PDF file

A pdf version of this document is available. \