Comparing Mixed-Effect Models in R and SPSS

Occasionally we are asked to help students or faculty implement a mixed-effect model in SPSS. Our training and expertise is primarily in R, so it can be challenging to transfer and apply our knowledge to SPSS. In this article we document for posterity how to fit some basic mixed-effect models in R using the lme4 and nlme packages, and how to replicate the results in SPSS.

In this article we work with R 4.2.0, lme4 version 1.1-29, nlme version 3.1-157, and SPSS version 28.0.1.1.

To begin we fit a model in R using the `sleepstudy` dataset that comes with lme4. This dataset contains average reaction time per day (in milliseconds) to a psychomotor vigilance task (PVT) for subjects in a sleep deprivation study. Each subject was observed for 10 days. Of interest is how sleep-deprived subjects' reaction times change over time.

After we load the lme4 package, we load the `sleepstudy` dataset into our global environment using the `data()` function. Once loaded we export the data as a CSV file to our working directory using `write.csv()`, so we can import it into SPSS.


```
# install.packages("lme4")
library(lme4)
data("sleepstudy")
write.csv(sleepstudy, "sleepstudy.csv", row.names = FALSE)
```

Here's the exported CSV file if you would like to download it: sleepstudy.csv

Visualizing the data with ggplot2 reveals that a linear model would seem to be suitable, but one that takes into account the random variation between subjects. It appears the subjects exert a random effect on both the intercept and slope of the fitted lines. In other words it looks like we should fit a mixed-effect model.

```
library(ggplot2)
ggplot(sleepstudy) +
  aes(x = Days, y = Reaction) +
  geom_point() +
```

```
  geom_smooth(method = "lm", se = FALSE) +
  facet_wrap(~Subject)
```



To model `Reaction` as a function `Days` with the intercept and slope coefficients conditional on `Subject`, we fit the following model using `lmer()`.

```
m1 <- lmer(Reaction ~ Days + (Days | Subject), sleepstudy)
```

The `(Days | Subject)` syntax says we want to model a random effect for the intercept, a random effect for the Days coefficient, and the correlation between the random effects. Random effects are variances, so we can symbolize this with the following covariance matrix, where σ_1^2 is the intercept random effect, σ_2^2 is the Days random effects, and ρ_{12} is the correlation between the two variances:

$$\begin{bmatrix} \sigma_1^2 & \rho_{12} \\ \rho_{12} & \sigma_2^2 \end{bmatrix}$$

Usually a covariance matrix contains covariance on the off-diagonals, not correlation. But we present it this way to conform to how lme4 summarizes random effects. Plus, correlation is simply a unitless version of covariance.

The summary output of the lme4 model lists the estimated variances/standard deviations and correlation under “Random effects”. (The

`corr = FALSE` argument in the `summary()` function says to not show the correlation of *fixed effects*, which is not relevant to the current article.)

```
summary(m1, corr = FALSE)
```

```
Linear mixed model fit by REML ['lmerMod']
Formula: Reaction ~ Days + (Days | Subject)
   Data: sleepstudy

REML criterion at convergence: 1743.6

Scaled residuals:
    Min      1Q  Median      3Q     Max
-3.9536 -0.4634  0.0231  0.4634  5.1793

Random effects:
 Groups   Name        Variance Std.Dev. Corr
 Subject  (Intercept) 612.10   24.741
          Days         35.07    5.922   0.07
 Residual             654.94   25.592
Number of obs: 180, groups:  Subject, 18

Fixed effects:
            Estimate Std. Error t value
(Intercept)  251.405      6.825  36.838
Days          10.467      1.546   6.771
```

The estimated covariance matrix for the random effects (with correlation on the off-diagonal) is:

$$\begin{bmatrix} 612.10 & 0.07 \\ 0.07 & 35.07 \end{bmatrix}$$


Now let's replicate the same result in SPSS.

First we need to load the data. Go to File…Import Data…CSV Data, navigate to the location of the "sleepstudy.csv" file and click Open. In the Read CSV File dialog, make sure the "First line contains variables names" is checked and click OK.


Now we fit the model by going to Analyze…Mixed Models…Linear… This can be performed using SPSS syntax but we'll show how to use the dialogs, as

this seems to be how most people prefer to use SPSS (at least in our experience).


In the “Specify Subjects and Repeated” dialog, add `Subject` to the “Subjects:” field and click Continue. (This variable does not have to be named “Subject”; this is only a coincidence. Common names for grouping structures include “id”, “plot”, “subject_id”, and so on.)



In the next dialog, “Linear Mixed Models”, add “Reaction” to the “Dependent Variable:” field and “Days” to the “Covariate(s):” field. (If we had any categorical predictors we would put them in “Factor(s)” field.)




Next click the “Fixed…” button to specify our model. In this case we only have one predictor and an intercept, so we select `Days` under “Factors and Covariates:” and click the “Add” button. Make sure the “Include intercept” option is checked and click “Continue”. Everything else can stay the same.



Next click the “Random…” button to specify our random effects. The first thing we need to do in this dialog is select “Unstructured: Correlation Metric” from the “Covariance Type:” pulldown. This says to use the covariance matrix we specified above. “Unstructured” means estimate all three parameters: the two variances and the covariance/correlation. We are not imposing any

structure on our covariance matrix. “Correlation Metric” means return the correlation between the random effects instead of the covariance.


Then we specify which factors and covariates will have a random effect. Select `Days` and click “Add”. Make sure “Include intercept” is checked. Finally, under “Subject Groupings” we specify which grouping variables indicate random effects. In this case it’s `Subject`, so we select it, click the add arrow, and click “Continue”. Everything else can stay the same.



Next click the “Statistics…” button to select which statistics we want computed for our linear mixed-effect model. To keep output minimal, we select two choices:

- Parameter estimates for fixed effects
- Covariances of random effects

When done click “Continue”.



Finally we click OK to run the model. A partial listing of the output shows results equivalent to the lme4 output (within rounding error). SPSS also provides additional statistics that lme4 does not provide such as approximate p-values for the coefficient tests and standard errors for the random effects.

Estimates of Fixed Effects[a]

Parameter	Estimate	Std. Error	df	t	Sig.	95% Confidence Interval	
						Lower Bound	Upper Bound
Intercept	251.405	6.825	17.000	36.838	<.001	237.007	265.804
Days	10.467	1.546	17.000	6.771	<.001	7.206	13.729

a. Dependent Variable: Reaction.

Covariance Parameters

Estimates of Covariance Parameters[a]

Parameter		Estimate	Std. Error
Residual		654.941	77.186
Intercept + Days [subject = Subject]	Var(1)	612.090	288.783
	Var(2)	35.072	14.782
	Corr(2,1)	.066	.325

a. Dependent Variable: Reaction.

Random Effect Covariance Structure (G)[a]

	Intercept | Subject	Days | Subject
Intercept | Subject	612.090	9.604
Days | Subject	9.604	35.072

Unstructured Correlations

a. Dependent Variable: Reaction.

Notice in the “Estimates of Covariance Parameters” output the variances and correlation are labeled with numbers to indicate their position in the covariance matrix:

$$\begin{bmatrix} \text{Var}(1) & \text{Corr}(2,1) \\ \text{Corr}(2,1) & \text{Var}(2) \end{bmatrix}$$

This is identical to the previous covariance matrix we presented above, but with names instead of Greek symbols. SPSS also prints the covariance matrix in the next section “Random Effect Covariance Structure”, but with the estimated covariance instead of the correlation.

The estimated correlation between the random effects is quite small, about 0.07. Perhaps we could assume the correlation is 0 and fit a simpler model. This would mean imposing some structure on the covariance matrix for the random effects, as follows:

$$\begin{bmatrix} \text{Var}(1) & 0 \\ 0 & \text{Var}(2) \end{bmatrix}$$

To specify this using `lmer()`, we use *two pipes* instead of one when specifying the random effects:

```
# Notice the || in the random effects syntax
m2 <- lmer(Reaction ~ Days + (Days || Subject), sleepstudy)
summary(m2, corr = FALSE)
```

```
  Linear mixed model fit by REML ['lmerMod']
  Formula: Reaction ~ Days + ((1 | Subject) + (0 + Days | Subject))
     Data: sleepstudy

  REML criterion at convergence: 1743.7

  Scaled residuals:
      Min      1Q  Median      3Q     Max
  -3.9626 -0.4625  0.0204  0.4653  5.1860


  Random effects:
   Groups    Name        Variance Std.Dev.
   Subject   (Intercept) 627.57   25.051
   Subject.1 Days         35.86    5.988
   Residual              653.58   25.565
```

```
Number of obs: 180, groups:  Subject, 18

Fixed effects:
            Estimate Std. Error t value
(Intercept)  251.405      6.885  36.513
Days          10.467      1.560   6.712
```

Notice there is no estimated correlation in the “Random effects” section. That’s because we constrained it to be 0.

To replicate this model in SPSS, we follow all the same steps above except we select “Diagonal” in the “Covariance Type:” pulldown in the Random Effects dialog.



The SPSS output for the random effects is basically the same as the lme4 output with some mild discrepancies in the decimals. This is likely due to minor differences in the default settings of the optimization routines. Notice the Random Effect Covariance Structure shows a 0 on the off-diagonal.

Estimates of Fixed Effects[a]

Parameter	Estimate	Std. Error	df	t	Sig.	95% Confidence Interval	
						Lower Bound	Upper Bound
Intercept	251.405	6.885	18.159	36.513	<.001	236.949	265.862
Days	10.467	1.559	18.183	6.714	<.001	7.194	13.740

a. Dependent Variable: Reaction.

Covariance Parameters

Estimates of Covariance Parameters[a]

Parameter		Estimate	Std. Error
Residual		653.582	76.587
Intercept + Days [subject = Subject]	Var: Intercept	627.556	283.678
	Var: Days	35.828	14.513

a. Dependent Variable: Reaction.

Random Effect Covariance Structure (G)[a]

	Intercept | Subject	Days | Subject
Intercept | Subject	627.556	0
Days | Subject	0	35.828

Diagonal

a. Dependent Variable: Reaction.