

```
CREATE DATABASE Parks_and_Recreation;
```

```
USE Parks_and_Recreation;
```

```
CREATE TABLE employee_demographics (  
  employee_id INT NOT NULL,  
  first_name VARCHAR(50),  
  last_name VARCHAR(50),  
  age INT,  
  gender VARCHAR(10),  
  birth_date DATE,  
  PRIMARY KEY (employee_id)  
);
```

```
CREATE TABLE employee_salary (  
  employee_id INT NOT NULL,  
  first_name VARCHAR(50) NOT NULL,  
  last_name VARCHAR(50) NOT NULL,  
  occupation VARCHAR(50),  
  salary INT,  
  dept_id INT  
);
```

```
INSERT INTO employee_demographics (employee_id, first_name, last_name, age,  
gender, birth_date)
```

```
VALUES
```

```
(1, 'Leslie', 'Knobe', 44, 'Female', '1979-09-25'),  
(3, 'Tom', 'Haverford', 36, 'Male', '1987-03-04'),  
(4, 'April', 'Ludgate', 29, 'Female', '1994-03-27'),  
(5, 'Jerry', 'Gergich', 61, 'Male', '1962-08-28'),  
(6, 'Donna', 'Meagle', 46, 'Female', '1977-07-30'),  
(7, 'Ann', 'Perkins', 35, 'Female', '1988-12-01'),  
(8, 'Chris', 'Traeger', 43, 'Male', '1980-11-11'),  
(9, 'Ben', 'Wyatt', 38, 'Male', '1985-07-26'),  
(10, 'Andy', 'Dwyer', 34, 'Male', '1989-03-25'),  
(11, 'Mark', 'Brendanawicz', 40, 'Male', '1983-06-14'),  
(12, 'Craig', 'Middlebrooks', 37, 'Male', '1986-07-27');
```

```

INSERT INTO employee_salary (employee_id, first_name, last_name, occupation,
salary, dept_id)
VALUES
(1, 'Leslie', 'Knobe', 'Deputy Director of Parks and Recreation', 75000,1),
(2, 'Ron', 'Swanson', 'Director of Parks and Recreation', 70000,1),
(3, 'Tom', 'Haverford', 'Entrepreneur', 50000,1),
(4, 'April', 'Ludgate', 'Assistant to the Director of Parks and Recreation',
25000,1),
(5, 'Jerry', 'Gergich', 'Office Manager', 50000,1),
(6, 'Donna', 'Meagle', 'Office Manager', 60000,1),
(7, 'Ann', 'Perkins', 'Nurse', 55000,4),
(8, 'Chris', 'Traeger', 'City Manager', 90000,3),
(9, 'Ben', 'Wyatt', 'State Auditor', 70000,6),
(10, 'Andy', 'Dwyer', 'Shoe Shiner and Musician', 20000, NULL),
(11, 'Mark', 'Brendanawicz', 'City Planner', 57000, 3),
(12, 'Craig', 'Middlebrooks', 'Parks Director', 65000,1);

```

```

CREATE TABLE parks_departments (
department_id INT NOT NULL AUTO_INCREMENT,
department_name varchar(50) NOT NULL,
PRIMARY KEY (department_id)
);

```

```

INSERT INTO parks_departments (department_name)
VALUES
('Parks and Recreation'),
('Animal Control'),
('Public Works'),
('Healthcare'),
('Library'),
('Finance');

```

1. Database creation and selection

1. `DROP DATABASE IF EXISTS Parks_and_Recreation;`
 - Checks if a database named `Parks_and_Recreation` already exists.
 - If it exists, it deletes (drops) that entire database (all its tables and data) so you can start fresh.
2. `CREATE DATABASE Parks_and_Recreation;`
 - Creates a new empty database named `Parks_and_Recreation`.
3. `USE Parks_and_Recreation;`
 - Tells the SQL server that all subsequent commands should be executed in the `Parks_and_Recreation` database.

2. Creating the `employee_demographics` table

```
CREATE TABLE employee_demographics (  
  employee_id INT NOT NULL,  
  first_name VARCHAR(50),  
  last_name VARCHAR(50),  
  age INT,  
  gender VARCHAR(10),  
  birth_date DATE,  
  PRIMARY KEY (employee_id)  
);
```

4. `CREATE TABLE employee_demographics (...);`
 - Creates a new table to store basic demographic information about employees.
5. `employee_id INT NOT NULL,`
 - Defines a column `employee_id` as an integer that cannot be NULL (must always have a value).
 - This will uniquely identify each employee in this table.
6. `first_name VARCHAR(50),`
 - Stores the employee's first name as text up to 50 characters.

7. `last_name VARCHAR(50),`

- Stores the employee's last name as text up to 50 characters.

8. `age INT,`

- Stores the employee's age as an integer.

9. `gender VARCHAR(10),`

- Stores the employee's gender as text up to 10 characters (e.g., 'Male', 'Female').

10. `birth_date DATE,`

- Stores the employee's date of birth as a date type.

11. `PRIMARY KEY (employee_id)`

- Sets `employee_id` as the primary key, meaning each `employee_id` must be unique and non-NULL, and will be used to identify rows.

3. Creating the `employee_salary` table

```
CREATE TABLE employee_salary (  
  employee_id INT NOT NULL,  
  first_name VARCHAR(50) NOT NULL,  
  last_name VARCHAR(50) NOT NULL,  
  occupation VARCHAR(50),  
  salary INT,  
  dept_id INT  
);
```

12. `CREATE TABLE employee_salary (...);`

- Creates a table to store job-related and salary information for employees.

13. `employee_id INT NOT NULL,`

- Employee identifier, must have a value. This will typically match `employee_demographics.employee_id`.

14. `first_name VARCHAR(50) NOT NULL,`

- First name, required (cannot be NULL).

15. `last_name VARCHAR(50) NOT NULL,`

- Last name, required.

16. `occupation VARCHAR(50),`

- Job title or role (e.g., 'Director of Parks and Recreation').

17. `salary INT,`

- Salary value as an integer.

18. `dept_id INT`

- Department identifier as an integer. This is intended to match up with a department in the `parks_departments` table (but note you have not declared a foreign key here).

(No primary key defined here: in practice, you might make `employee_id` a primary or unique key, or use a separate auto-increment ID.)

4. Inserting data into `employee_demographics`

```
INSERT INTO employee_demographics (employee_id, first_name, last_name, age, gender,
birth_date)
VALUES
(1, 'Leslie', 'Knobe', 44, 'Female', '1979-09-25'),
...
(12, 'Craig', 'Middlebrooks', 37, 'Male', '1986-07-27');
```

19. `INSERT INTO employee_demographics (...columns...) VALUES ...;`

- Inserts multiple rows of demographic data into `employee_demographics` in a single statement.

20–30. Each tuple like `(1, 'Leslie', 'Knobe', 44, 'Female', '1979-09-25')`

- Inserts one row with the given values corresponding to the specified columns:
 - `employee_id`
 - `first_name`

- last_name
- age
- gender
- birth_date

For example:

- (1, 'Leslie', 'Knobe', 44, 'Female', '1979-09-25') adds Leslie Knobe with ID 1, age 44, female, born on 1979-09-25.
- (3, 'Tom', 'Haverford', 36, 'Male', '1987-03-04') adds Tom Haverford with ID 3, etc.
- This continues for April, Jerry, Donna, Ann, Chris, Ben, Andy, Mark, and Craig.

5. Inserting data into employee_salary

```
INSERT INTO employee_salary (employee_id, first_name, last_name, occupation, salary,
dept_id)
VALUES
(1, 'Leslie', 'Knobe', 'Deputy Director of Parks and Recreation', 75000,1),
...
(12, 'Craig', 'Middlebrooks', 'Parks Director', 65000,1);
```

31. INSERT INTO employee_salary (...columns...) VALUES ...;

- Inserts multiple rows of salary and job information into employee_salary.

32-42. Each tuple like (1, 'Leslie', 'Knobe', 'Deputy Director of Parks and Recreation', 75000,1)

- For each row, the values map to:
 - employee_id
 - first_name
 - last_name
 - occupation
 - salary

- dept_id

Examples:

- (1, 'Leslie', 'Knope', 'Deputy Director of Parks and Recreation', 75000,1)
 - Leslie has employee ID 1, works as Deputy Director, earns 75000, in department dept_id = 1.
- (2, 'Ron', 'Swanson', 'Director of Parks and Recreation', 70000,1)
 - Ron Swanson has ID 2, Director, salary 70000, department 1.
- (10, 'Andy', 'Dwyer', 'Shoe Shiner and Musician', 20000, NULL)
 - Andy has no department assigned (dept_id is NULL).
- This continues similarly for Tom, April, Jerry, Donna, Ann, Chris, Ben, Mark, and Craig.

6. Creating the parks_departments table

```
CREATE TABLE parks_departments (  
  department_id INT NOT NULL AUTO_INCREMENT,  
  department_name varchar(50) NOT NULL,  
  PRIMARY KEY (department_id)  
);
```

43. CREATE TABLE parks_departments (...);

- Creates a table to store department information.

44. department_id INT NOT NULL AUTO_INCREMENT,

- department_id is an integer that auto-increments (MySQL automatically assigns the next number for each new row).
- It cannot be NULL.

45. department_name varchar(50) NOT NULL,

- Stores the department's name as text up to 50 characters.
- It is required (cannot be NULL).

46. PRIMARY KEY (department_id)

- Makes `department_id` the primary key, uniquely identifying each department.

7. Inserting data into `parks_departments`

```
INSERT INTO parks_departments (department_name)
VALUES
('Parks and Recreation'),
('Animal Control'),
('Public Works'),
('Healthcare'),
('Library'),
('Finance');
```

47. `INSERT INTO parks_departments (department_name) VALUES ...;`

- Inserts multiple department names into the `parks_departments` table.

48–53. Each row like `('Parks and Recreation')`

- Inserts one department with the given `department_name`.
- Because `department_id` is `AUTO_INCREMENT`, MySQL automatically assigns IDs, e.g.:
 - 1 → 'Parks and Recreation'
 - 2 → 'Animal Control'
 - 3 → 'Public Works'
 - 4 → 'Healthcare'
 - 5 → 'Library'
 - 6 → 'Finance'

These IDs can conceptually match the `dept_id` values in `employee_salary` (though no explicit foreign key is declared).

