

## Questions for Freshers

Q1. Explain JDK, JRE and JVM?

JDK

JRE

JVM

It stands for Java Development Kit. It stands for Java Runtime Environment.

It stands for Java Virtual Machine.

It is the tool necessary to compile, JRE refers to a runtime environment in

run-time  
It is an abstract machine. It is a specification that provides a

document and package Java programs. which Java bytecode can be executed.

environment in which Java bytecode can be executed.

It contains JRE + development tools. It's an implementation of the JVM which physically exists. JVM follows three notations: Specification, Implementation, and Runtime Instance.

Q2. Explain public static void main(String args[]) in Java.

main() in Java is the entry point for any Java program. It is always written as public static void main(String[] args).

public: Public is an access modifier, which is used to specify who can access this method. Public means that this Method will be accessible by any Class.

static: It is a keyword in java which identifies it is class-based. main() is made static in Java so that it can be accessed without creating the instance of a Class.

In case, main is not made static then the compiler will throw an error as main() is called by the JVM before any objects are made and only static methods can be directly invoked via the class.

void: It is the return type of the method. Void defines the method which will not return any value.

main: It is the name of the method which is searched by JVM as a starting point for an application with a particular signature only. It is the method where the main execution occurs.

String args[]: It is the parameter passed to the main method.

Q3. Why Java is platform independent?

Java is called platform independent because of its byte codes which can run on any system irrespective of its underlying operating system.

Write once run anywhere.

Q4. Why Java is not 100% Object-oriented?

Java is not 100% Object-oriented because it makes use of eight primitive data types such as boolean, byte, char, int, float, double, long, short which are not objects.

Q5. What are wrapper classes in Java?

Wrapper classes convert the Java primitives into the reference types (objects).

Every primitive data type has a class dedicated to it. These are known as wrapper classes because they "wrap" the primitive data type into an object of that class.

Refer to the below image which displays different primitive type, wrapper class and constructor argument.

\* to make program purely object oriented like int into Integer and char to Character

Q6. What are constructors in Java?

In Java, constructor refers to a block of code which is used to initialize an object. It must have the same name as that of the class. Also, it has no return type and it is automatically called when an object is created.

There are two types of constructors:

**Default Constructor:** In Java, a default constructor is the one which does not take any inputs. In other words, default constructors are the no argument constructors which will be created by default in case you no other constructor is defined by the user. Its main purpose is to initialize the instance variables with the default values. Also, it is majorly used for object creation.

**Parameterized Constructor:** The parameterized constructor in Java, is the constructor which is capable of initializing the instance variables with the provided values. In other words, the constructors which take the arguments are called parameterized constructors.

Q7. What is singleton class in Java and how can we make a class singleton?

Singleton class is a class whose only one instance can be created at any given time, in one JVM. A class can be made singleton by making its constructor private.

Q8. What is the difference between Array list and vector in Java?

ArrayList

Vector

Array List is not synchronized.  
synchronized.

Vector is

Array List is fast as it's non-synchronized.  
slow as it is thread safe.

Vector is

If an element is inserted into the Array List,  
defaults to doubling size of its array.

Vector

it increases its Array size by 50%.

Array List does not define the increment size.  
defines the increment size.

Vector

Array List can only use Iterator for traversing an Array List.  
use both Enumeration and Iterator for traversing.

Vector can

Q9. What is the difference between equals() and == in Java?

Equals() method is defined in Object class in Java and used for checking equality of two objects defined by business logic.

"==" or equality operator in Java is a binary operator provided by Java programming language and used to compare primitives and objects.

public boolean equals(Object o) is the method provided by the Object class. The default implementation uses == operator to compare two objects.

For example: method can be overridden like String class. equals() method is used to compare the values of two objects.

Q10. When can you use the super keyword?

In Java, the super keyword is a reference variable that refers to an immediate parent class object.

When you create a subclass instance, you're also creating an instance of the parent class, which is referenced to by the super reference variable.

The uses of the Java super Keyword are-

To refer to an immediate parent class instance variable, use super.

The keyword super can be used to call the method of an immediate parent class.

Super() can be used to call the constructor of the immediate parent class.

Q11. What makes a HashSet different from a TreeSet?

HashSet

TreeSet

It is implemented through a hash table.

TreeSet implements SortedSet Interface that uses trees for storing data.

It permits the null object.

It does not allow the null object.

It is faster than TreeSet especially for search, insert, and delete operations.

It is slower than HashSet for these operations.

It does not maintain elements in an ordered way.

The elements are maintained in a sorted order.

It uses equals() method to compare two objects.

It uses compareTo() method for comparing two objects.

It does not permit a heterogeneous object.

It permits a heterogeneous object.

Q12. What are the differences between HashMap and Hashtable in Java?

HashMap

Hashtable

It is non synchronized. It cannot be shared between many threads without proper synchronization code.

It is synchronized. It is thread-safe and can be shared with many threads.

It permits one null key and multiple null values.

It does not permit any null key or value.

is a new class introduced in JDK 1.2.

It was present in earlier versions of java as well.

It is faster.

It is slower.

It is traversed through the iterator.

It is traversed through Enumerator and Iterator.

It uses fail fast iterator.

It uses an enumerator which is not fail fast.

It inherits AbstractMap class.

It inherits Dictionary class.

Q13. What is the importance of reflection in Java?

Reflection is a runtime API for inspecting and changing the behavior of methods, classes, and interfaces. Java Reflection is a powerful tool that can be really beneficial.

Java Reflection allows you to analyze classes, interfaces, fields, and methods during runtime without knowing what they are called at compile time. Reflection can also be used to create new objects, call methods, and get/set field values. External, user-defined classes can be used by creating instances of extensibility objects with their fully-qualified names. Debuggers can also use reflection to examine private members of classes.

Q14. How to not allow serialization of attributes of a class in Java?

The Non-Serialized attribute can be used to prevent member variables from being serialized.

You should also make an object that potentially contains security-sensitive data non-serializable if possible.

Apply the Non-Serialized attribute to certain fields that store sensitive data if the object must be serialized.

If you don't exclude these fields from serialization, the data they store will be visible to any programs with serialization permission.

Q15. Can you call a constructor of a class inside another constructor?

Yes, we can call a constructor of a class inside another constructor. This is also called as constructor chaining. Constructor chaining can be done in 2 ways-

Within the same class: For constructors in the same class, the this() keyword can be used.

From the base class: The super() keyword is used to call the constructor from the base class.

The constructor chaining follows the process of inheritance. The constructor of the sub class first calls the constructor of the super class.

Due to this, the creation of sub class's object starts with the initialization of the data members of the super class.

The constructor chaining works similarly with any number of classes. Every constructor keeps calling the chain till the top of the chain.

Q16. Contiguous memory locations are usually used for storing actual values in an array but not in ArrayList. Explain.

An array generally contains elements of the primitive data types such as int, float, etc. In such cases, the array directly stores these elements at contiguous memory

locations.

While an ArrayList does not contain primitive data types. An ArrayList contains the reference of the objects at different memory locations instead of the object itself. That is why the objects are not stored at contiguous memory locations.

Q17. How is the creation of a String using new() different from that of a literal? When we create a string using new(), a new object is created. Whereas, if we create a string using the string literal syntax, it may return an already existing object with the same name.

Q18. Why is synchronization necessary? Explain with the help of a relevant example.

Java allows multiple threads to execute. They may be accessing the same variable or object. Synchronization helps to execute threads one after another.

It is important as it helps to execute all concurrent threads while being in sync.

It prevents memory consistency errors due to access to shared memory.

An example of synchronization code is-

```
public synchronized void increment()
{
    a++;
}
```

As we have synchronized this function, this thread can only use the object after the previous thread has used it.

Q19. Explain the term “Double Brace Initialization” in Java?

Double Brace Initialization is a Java term that refers to the combination of two independent processes. There are two braces used in this.

The first brace creates an anonymous inner class. The second brace is an initialization block. When these both are used together, it is known as Double Brace Initialization.

The inner class has a reference to the enclosing outer class, generally using the ‘this’ pointer. It is used to do both creation and initialization in a single statement.

It is generally used to initialize collections. It reduces the code and also makes it more readable.

Q20. Why is it said that the length() method of String class doesn’t return accurate results?

The length() method of String class doesn’t return accurate results because it simply takes into account the number of characters within in the String.

In other words, code points outside of the BMP (Basic Multilingual Plane), that is, code points having a value of U+10000 or above, will be ignored.

The reason for this is historical. One of Java's original goals was to consider all text as Unicode; yet, Unicode did not define code points outside of the BMP at the time.

It was too late to modify char by the time Unicode specified such code points.

Q21. What are the differences between Heap and Stack Memory in Java?

The major difference between Heap and Stack memory are:

Features	Heap	Stack
Memory	Heap memory is used by all the parts of the application.	Stack memory is used only by one thread of execution.
Access	Objects stored in the heap are globally accessible.	Stack memory can't be accessed by other threads.
Memory Management	Memory management is based on the generation associated with each object.	Follows LIFO manner to free memory.
Lifetime	Heap memory lives from the start till the end of application execution.	Exists until the end of execution of the thread.
Usage	Whenever an object is created, it's always stored in the Heap space.	Stack memory only contains local primitive and reference variables to objects in heap space.

Q22. What is a package in Java? List down various advantages of packages.

Packages in Java, are the collection of related classes and interfaces which are bundled together. By using packages, developers can easily modularize the code and optimize its reuse.

Also, the code within the packages can be imported by other classes and reused.

Below I have listed down a few of its advantages:

Packages help in avoiding name clashes

They provide easier access control on the code

Packages can also contain hidden classes which are not visible to the outer classes and only used within the package

Creates a proper hierarchical structure which makes it easier to locate the related classes

Q23. Why pointers are not used in Java?

Java doesn't use pointers because they are unsafe and increases the complexity of the program. Since, Java is known for its simplicity of code, adding the concept of pointers will be contradicting.

Moreover, since JVM is responsible for implicit memory allocation, thus in order to avoid direct access to memory by the user, pointers are discouraged in Java.

Q24. What is JIT compiler in Java?

JIT stands for Just-In-Time compiler in Java. It is a program that helps in converting the Java bytecode into instructions that are sent directly to the

processor.

By default, the JIT compiler is enabled in Java and is activated whenever a Java method is invoked. The JIT compiler then compiles the bytecode of the invoked method

-into native machine code, compiling it “just in time” to execute. Once the method has been compiled, the JVM summons the compiled code of that method directly rather than interpreting it.

This is why it is often responsible for the performance optimization of Java applications at the run time.

Q25. What are access modifiers in Java?

In Java, access modifiers are special keywords which are used to restrict the access of a class, constructor, data member and method in another class. Java supports four types of access modifiers:

Default  
Private  
Protected  
Public

Modifier		Default	Private
Protected	Public		
Same class		YES	YES
YES	YES		
Same Package subclass		YES	NO
YES	YES		
Same Package non-subclass		YES	NO
YES	YES		
Different package subclass		NO	NO
YES	YES		
Different package non-subclass		NO	NO
NO	YES		

Q26. Define a Java Class.

A class in Java is a blueprint which includes all your data. A class contains fields (variables) and methods to describe the behavior of an object. Let’s have a look at the syntax of a class.

```
class Abc {  
member variables // class body  
methods }.
```

Q27. What is an object in Java and how is it created?

An object is a real-world entity that has a state and behavior. An object has three characteristics:

State  
Behavior  
Identity

An object is created using the ‘new’ keyword. For example:

```
ClassName obj = new ClassName();
```

Q28. What is Object Oriented Programming?

Object-oriented programming or popularly known as OOPs is a programming model or approach where the programs are organized around objects rather than logic and functions.

In other words, OOP mainly focuses on the objects that are required to be manipulated instead of logic. This approach is ideal for the programs large and complex codes -

- and needs to be actively updated or maintained.

Q29. What are the main concepts of OOPs in Java?

Object-Oriented Programming or OOPs is a programming style that is associated with concepts like:

**Inheritance:** Inheritance is a process where one class acquires the properties of another.

**Encapsulation:** Encapsulation in Java is a mechanism of wrapping up the data and code together as a single unit.

**Abstraction:** Abstraction is the methodology of hiding the implementation details from the user and only providing the functionality to the users.

**Polymorphism:** Polymorphism is the ability of a variable, function or object to take multiple forms.

Q30. What is the difference between a local variable and an instance variable?

In Java, a local variable is typically used inside a method, constructor, or a block and has only local scope. Thus, this variable can be used only within the scope of a block.

The best benefit of having a local variable is that other methods in the class won't be even aware of that variable.

Example

```
if(x > 100)
{
String test = "Edureka";
}
```

Whereas, an instance variable in Java, is a variable which is bounded to its object itself. These variables are declared within a class, but outside a method.

Every object of that class will create its own copy of the variable while using it. Thus, any changes made to the variable won't reflect in any other instances of that class and will be bound to that particular instance only.

```
class Test{
public String EmpName;
public int empAge;
}
```

Q31. Differentiate between the constructors and methods in Java?



## Methods

### Constructors

- |                                                                                                                   |              |
|-------------------------------------------------------------------------------------------------------------------|--------------|
| 1. Used to represent the behavior of an object<br>initialize the state of an object                               | 1. Used to   |
| 2. Must have a return type<br>have any return type                                                                | 2. Do not    |
| 3. Needs to be invoked explicitly<br>invoked implicitly                                                           | 3. Is        |
| 4. No default method is provided by the compiler<br>constructor is provided by the compiler if the class has none | 4. A default |
| 5. Method name may or may not be same as class name<br>Constructor name must always be the same as the class name | 5.           |

Q32. What is final keyword in Java?

final is a special keyword in Java that is used as a non-access modifier. A final variable can be used in different contexts such as:

#### final variable

When the final keyword is used with a variable then its value can't be changed once assigned. In case the no value has been assigned to the final variable then using only the class constructor a value can be assigned to it.

#### final method

When a method is declared final then it can't be overridden by the inheriting class.

#### final class

When a class is declared as final in Java, it can't be extended by any subclass class but it can extend other class.

Q33. What is the difference between break and continue statements?

#### break

#### continue

- |                                                                                                |  |
|------------------------------------------------------------------------------------------------|--|
| 1. Can be used in switch and loop (for, while, do while) statements                            |  |
| 1. Can be only used with loop statements                                                       |  |
| 2. It causes the switch or loop statements to terminate the moment it is executed              |  |
| 2. It doesn't terminate the loop but causes the loop to jump to the next iteration             |  |
| 3. It terminates the innermost enclosing loop or switch immediately                            |  |
| 3. A continue within a loop nested with a switch will cause the next loop iteration to execute |  |

Example break:

```
for (int i = 0; i < 5; i++)  
{  
    if (i == 3)  
    {  
        break;  
    }  
    System.out.println(i);  
}
```

Example continue:

```
for (int i = 0; i < 5; i++)
{
    if(i == 2)
    {
        continue;
    }
    System.out.println(i);
}
```

Q34. What is an infinite loop in Java? Explain with an example.

An infinite loop is an instruction sequence in Java that loops endlessly when a functional exit isn't met.

This type of loop can be the result of a programming error or may also be a deliberate action based on the application behavior.

An infinite loop will terminate automatically once the application exits.

For example:

```
public class InfiniteForLoopDemo
{
    public static void main(String[] arg) {
        for(;;)
        System.out.println("Welcome to Edureka!");
        // To terminate this program press ctrl + c in the console.
    }
}
```

Q35. What is the difference between this() and super() in Java?

In Java, super() and this(), both are special keywords that are used to call the constructor.

this()

super()

- |                                                                |    |
|----------------------------------------------------------------|----|
| 1. this() represents the current instance of a class           | 1. |
| super() represents the current instance of a parent/base class |    |
| 2. Used to call the default constructor of the same class      | 2. |
| Used to call the default constructor of the parent/base class  |    |
| 3. Used to access methods of the current class                 | 3. |
| Used to access methods of the base class                       |    |
| 4. Used for pointing the current class instance                | 4. |
| Used for pointing the superclass instance                      |    |
| 5. Must be the first line of a block                           | 5. |
| Must be the first line of a block                              |    |

Q36. What is Java String Pool?

Java String pool refers to a collection of Strings which are stored in heap memory.

In this, whenever a new object is created, String pool first checks whether the object is already present in the pool or not.

If it is present, then the same reference is returned to the variable else new object will be created in the String pool and the respective reference will be returned.

Q37. Differentiate between static and non-static methods in Java.

Static Method

Non-Static Method

- |                                                                                                   |    |
|---------------------------------------------------------------------------------------------------|----|
| 1. The static keyword must be used before the method name                                         | 1. |
| No need to use the static keyword before the method name                                          |    |
| 2. It is called using the class (className.methodName)                                            | 2. |
| It is can be called like any general method                                                       |    |
| 3. They can't access any non-static instance variables or methods                                 | 3. |
| It can access any static method and any static variable without creating an instance of the class |    |

Q38. Explain the term "Double Brace Initialisation" in Java?

Double Brace Initialization is a Java term that refers to the combination of two independent processes. There are two braces used in this. The first brace creates an anonymous inner class.

The second brace is an initialization block. When these both are used together, it is known as Double Brace Initialisation. The inner class has a reference to the enclosing outer class, generally using the 'this' pointer.

It is used to do both creation and initialization in a single statement. It is generally used to initialize collections. It reduces the code and also makes it more readable.

Q39. What is constructor chaining in Java?

In Java, constructor chaining is the process of calling one constructor from another with respect to the current object.

Constructor chaining is possible only through legacy where a subclass constructor is responsible for invoking the superclass' constructor first.

There could be any number of classes in the constructor chain. Constructor chaining can be achieved in two ways:

Within the same class using this()

From base class using super()

Q40. Difference between String, StringBuilder, and StringBuffer.

Factor	String
String Builder	
Storage Area	Constant String Pool
Area	Heap
Mutability	Immutable
Mutable	
Thread Safety	Yes
Yes	No
Performance	Fast
	More

efficient

Less efficient

Q41. What is a classloader in Java?

The Java ClassLoader is a subset of JVM (Java Virtual Machine) that is responsible for loading the class files. Whenever a Java program is executed it is first loaded by the classloader.

Java provides three built-in classloaders:

Bootstrap ClassLoader

Extension ClassLoader

System/Application ClassLoader

Q42. Why Java Strings are immutable in nature?

In Java, string objects are immutable in nature which simply means once the String object is created its state cannot be modified.

Whenever you try to update the value of that object instead of updating the values of that particular object, Java creates a new string object.

Java String objects are immutable as String objects are generally cached in the String pool. Since String literals are usually shared between multiple clients, -

- action from one client might affect the rest. It enhances security, caching, synchronization, and performance of the application.

Q43. What is the difference between an array and an array list?

Array

ArrayList

Cannot contain values of different data types  
values of different data types.

Can contain

Size must be defined at the time of declaration  
dynamically changed

Size can be

Need to specify the index in order to add data  
specify the index

No need to

Arrays are not type parameterized  
are type

Arraylists

Arrays can contain primitive data types as well as objects  
can contain only objects, no primitive data types are allowed

Arraylists

Q44. What is a Map in Java?

In Java, Map is an interface of Util package which maps unique keys to values.

The Map interface is not a subset of the main Collection interface and thus it behaves little different from the other collection types.

Below are a few of the characteristics of Map interface:

Map doesn't contain duplicate keys.

Each key can map at max one value.

Q45. What is collection class in Java? List down its methods and interfaces.

In Java, the collection is a framework that acts as an architecture for storing and manipulating a group of objects.

Using Collections you can perform various tasks like searching, sorting, insertion, manipulation, deletion, etc. Java collection framework includes the following:

Interfaces  
Classes  
Methods

## OOPS Java Interview Questions

Q1. What is Polymorphism?

Polymorphism is briefly described as “one interface, many implementations”. Polymorphism is a characteristic of being able to assign a different meaning or usage to something in different contexts – specifically, to allow an entity such as a variable, a function, or an object to have more than one form. There are two types of polymorphism:

Compile time polymorphism

Run time polymorphism

Compile time polymorphism is method overloading whereas Runtime time polymorphism is done using inheritance and interface.

Q2. What is runtime polymorphism or dynamic method dispatch?

In Java, runtime polymorphism or dynamic method dispatch is a process in which a call to an overridden method is resolved at runtime rather than at compile-time. In this process, an overridden method is called through the reference variable of a superclass. Let's take a look at the example below to understand it better.

```
class Car {  
void run()  
{  
System.out.println("car is running");  
}  
}  
class Audi extends Car {  
void run()  
{  
System.out.println("Audi is running safely with 100km");  
}  
public static void main(String args[])  
{  
Car b= new Audi();    //upcasting  
b.run();  
}  
}
```

Q3. What is abstraction in Java?

Abstraction refers to the quality of dealing with ideas rather than events. It basically deals with hiding the details and showing the essential things to the

user.

Thus you can say that abstraction in Java is the process of hiding the implementation details from the user and revealing only the functionality to them. Abstraction can be achieved in two ways:

Abstract Classes (0-100% of abstraction can be achieved)

Interfaces (100% of abstraction can be achieved)

Q4. What do you mean by an interface in Java?

An interface in Java is a blueprint of a class or you can say it is a collection of abstract methods and static constants.

In an interface, each method is public and abstract but it does not contain any constructor. Thus, interface basically is a group of related methods with empty bodies. Example:

```
public interface Animal {  
    public void eat();  
    public void sleep();  
    public void run();  
}
```

Q5. What is the difference between abstract classes and interfaces?

Abstract Class

Interfaces

An abstract class can provide complete, default code and/or just the details that have to be overridden  
just the signature

An interface cannot provide any code at all,

In the case of an abstract class, a class may extend only one abstract class

A Class may implement several interfaces

An abstract class can have non-abstract methods

All methods of an Interface are abstract

An abstract class can have instance variables

An Interface cannot have instance variables

An abstract class can have any visibility: public, private, protected

An Interface visibility must be public (or) none

If we add a new method to an abstract class then we have the option of providing

to track down  
default implementation and therefore all the existing code might work properly.

all the implementations of the interface and  
define implementation for the new method.

An abstract class can contain constructors

An Interface cannot contain constructors

Abstract classes are fast

Interfaces are slow as it requires extra indirection  
to find the corresponding method in the actual class

Q6. What is inheritance in Java?

Inheritance in Java is the concept where the properties of one class can be

inherited by the other. It helps to reuse the code and establish a relationship between different classes.

Inheritance is performed between two types of classes:

Parent class (Super or Base class)

Child class (Subclass or Derived class)

A class which inherits the properties is known as Child Class whereas a class whose properties are inherited is known as Parent class.

Q7. What are the different types of inheritance in Java?

Java supports four types of inheritance which are:

Single Inheritance: In single inheritance, one class inherits the properties of another i.e there will be only one parent as well as one child class.

Multilevel Inheritance: When a class is derived from a class which is also derived from another class, i.e. a class having more than one parent class but at different levels, such type of inheritance is called Multilevel Inheritance.

Hierarchical Inheritance: When a class has more than one child classes (subclasses) or in other words, more than one child classes have the same parent class, then such kind of inheritance is known as hierarchical.

Hybrid Inheritance: Hybrid inheritance is a combination of two or more types of inheritance.

Q8. What is method overloading and method overriding?

Method Overloading :

In Method Overloading, Methods of the same class shares the same name but each method must have a different number of parameters or parameters having different types and order.

Method Overloading is to “add” or “extend” more to the method’s behavior.

It is a compile-time polymorphism.

The methods must have a different signature.

It may or may not need inheritance in Method Overloading.

Let’s take a look at the example below to understand it better.

```
class Adder {
    Static int add(int a, int b)
    {
        return a+b;
    }
    Static double add( double a, double b)
    {
        return a+b;
    }
    public static void main(String args[])
    {
        System.out.println(Adder.add(11,11));
        System.out.println(Adder.add(12.3,12.6));
    }
}
```

### Method Overriding:

In Method Overriding, the subclass has the same method with the same name and exactly the same number and type of parameters and same return type as a superclass. Method Overriding is to “Change” existing behavior of the method.

It is a run time polymorphism.

The methods must have the same signature.

It always requires inheritance in Method Overriding.

Let’s take a look at the example below to understand it better.

```
class Car {
void run(){
System.out.println(&ldquo;car is running&rdquo;);
}
Class Audi extends Car{
void run()
{
System.out.println("Audi is running safely with 100km");
}
public static void main( String args[])
{
Car b=new Audi();
b.run();
}
}
```

Q9. Can you override a private or static method in Java?

You cannot override a private or static method in Java. If you create a similar method with the same return type and same method arguments in child class then it will hide the superclass method;

this is known as method hiding. Similarly, you cannot override a private method in subclass because it’s not accessible there.

What you can do is create another private method with the same name in the child class. Let’s take a look at the example below to understand it better.

```
class Base {
private static void display() {
System.out.println("Static or class method from Base");
}
public void print() {
System.out.println("Non-static or instance method from Base");
}
class Derived extends Base {
private static void display() {
System.out.println("Static or class method from Derived");
}
public void print() {
System.out.println("Non-static or instance method from Derived");
}
public class test {
public static void main(String args[])
{
```



```
Base obj= new Derived();
obj1.display();
obj1.print();
}
}
```

Q10. What is multiple inheritance? Is it supported by Java?

MultipleInheritance - Java Interview Questions - Edureka  
If a child class inherits the property from multiple classes is known as multiple inheritance.  
Java does not allow to extend multiple classes.

The problem with multiple inheritance is that if multiple parent classes have the same method name, then at runtime it becomes difficult for the compiler to decide which method to execute from the child class.

Therefore, Java doesn't support multiple inheritance. The problem is commonly referred to as Diamond Problem.

Q11. What is encapsulation in Java?

Encapsulation is a mechanism where you bind your data(variables) and code(methods) together as a single unit. Here,  
the data is hidden from the outer world and can be accessed only via current class methods. This helps in protecting the data from any unnecessary modification.  
We can achieve encapsulation in Java by:

Declaring the variables of a class as private.

Providing public setter and getter methods to modify and view the values of the variables.

Q12. What is an association?

Association is a relationship where all object have their own lifecycle and there is no owner.

Let's take the example of Teacher and Student. Multiple students can associate with a single teacher and a single student can associate with multiple teachers -  
-but there is no ownership between the objects and both have their own lifecycle.  
These relationships can be one to one, one to many, many to one and many to many.

Q13. What do you mean by aggregation?

An aggregation is a specialized form of Association where all object has their own lifecycle but there is ownership and child object can not belong to another parent object.

Let's take an example of Department and teacher. A single teacher can not belong to multiple departments, but if we delete the department teacher object will not destroy.

Q14. What is composition in Java?

Composition is again a specialized form of Aggregation and we can call this as a "death" relationship. It is a strong type of Aggregation.

Child object does not have their lifecycle and if parent object deletes all child object will also be deleted. Let's take again an example of a relationship between House and rooms.

House can contain multiple rooms there is no independent life of room and any room can not belongs to two different houses if we delete the house room will automatically delete.

Q15. What is a marker interface?

A Marker interface can be defined as the interface having no data member and member functions. In simpler terms, an empty interface is called the Marker interface. The most common examples of Marker interface in Java are Serializable, Cloneable etc. The marker interface can be declared as follows.

```
public interface Serializable{  
}
```

Q16. What is object cloning in Java?

Object cloning in Java is the process of creating an exact copy of an object. It basically means the ability to create an object with a similar state as the original object.

To achieve this, Java provides a method clone() to make use of this functionality. This method creates a new instance of the class of the current object and then initializes all its fields with the exact same contents of corresponding fields. To object clone(), the marker interface java.lang.Cloneable must be implemented to avoid any runtime exceptions. One thing you must note is Object clone() is a protected method, thus you need to override it.

Q17. What is a copy constructor in Java?

Copy constructor is a member function that is used to initialize an object using another object of the same class.

Though there is no need for copy constructor in Java since all objects are passed by reference. Moreover, Java does not even support automatic pass-by-value.

Q18. What is a constructor overloading in Java?

In Java, constructor overloading is a technique of adding any number of constructors to a class each having a different parameter list.

The compiler uses the number of parameters and their types in the list to differentiate the overloaded constructors.

```
class Demo  
{  
int i;  
public Demo(int a)  
{  
i=k;  
}  
public Demo(int a, int b)  
{  
//body  
}  
}
```

What is Coupling in Java?

Coupling is nothing but the dependency of one class on the other.

If one object in a code uses the other object in the program, it is called loose coupling in Java.

When two classes are highly dependent on each other, it is called tight coupling.

Serialization :-- to convert its state to a byte stream so that the byte stream can be reverted back into a copy of the object.

Serializable is a marker interface (has no data member and method). It is used to "mark" Java classes so that the objects of these classes may get a certain capability.

Marker interface has a no data member and method or empty interface is called marker interface

There are six ways to create an object in Java.

- 1: Create Object in Java Using new Keyword.
- 2: Create Object in Java Using newInstance() method.
- 3: Create Object in Java Using newInstance() method of Constructor Class.
- 4: Create Object in Java Using clone() Method.
- 5: Create Object in Java Using Deserialization Method.