

punt-kit Is the Kit Manager for the Punt Labs Org

One tool manages the org's standards, its tools, its workflows, and its compliance checks — for the operator and for the AI agents that do the work across roughly thirty repositories

`/punt:auto` turns recurring prompts into reviewed programs: playbooks that mix deterministic shell with LLM judgment, and — next — prompt state machines that drive the agent instead of the operator retyping the loop

Press Release

PUNT LABS — December 1, 2026 — punt-kit is the kit manager for the Punt Labs org. One tool now manages the four things the org runs on: its **standards** (author them, activate them in a repo, audit against them), its **tools** (install them, enable them, wire their guidance into a session), its **workflows** (the release engine and the playbooks), and its **compliance** checks (audit, PII scan). The customer is Punt Labs itself — one operator and the AI agents that do the work across roughly thirty repositories. External adoption is not the goal of this version and is explicitly deferred (see [FAQ 1](#), [FAQ 9](#)).

The new capability in this release is `/punt:auto` as a **self-prompting engine**: the recurring prompts the operator used to type by hand become playbooks — reviewed, versioned programs that generate the prompts and drive the agent themselves (see [FAQ 4](#)).

Problem

Punt Labs is one operator and a roster of AI agents working roughly thirty repositories. Two costs dominate, and both scale with the number of repos and sessions rather than with the amount of code.

The first is context. Every agent session starts cold, with no memory of what came before [1], and the org's conventions — how a release runs, what a README must contain, when a PR may merge — live in prose that each session has to find. A study of 253 CLAUDE.md files found these manifests are optimized for code execution rather than organizational convention: only 8.7% include security guidance [2]. Static context files also have no feedback loop, so nothing notices when a repo has drifted from the document that describes it [3]. Catching that drift in review is the expensive path: rote standards checking is estimated at roughly four hours per engineer per week [4].

The second is the operator typing the same prompt again. Watching a pull request to merge, sweeping the backlog, running a release — these are loops with named states and guarded transitions, and today the operator re-authors each one as a fresh cron prompt, once per PR. A hand-typed loop is unreviewable, unversioned, and evaporates when the session compacts. It is the same toil the standards corpus removed for conventions, still untouched for procedure (see [FAQ 4](#)).

Solution

Standards. The corpus is 29 normative prose documents in `standards/`, plus per-language coding rules in `lang-rules/` that agents auto-load when they touch a matching file. They are prose on purpose: the consumer is a language model and a human reviewer, and neither needs the rules ground into assertions first. What is machine-checkable is checked separately and deterministically

— `punt audit` is hand-written Python that verifies the org’s conventions in a repo (CI workflows, tool config, permissions, Makefile targets, README SHA pins, plugin version sync, branch-protection rulesets) and reports each finding with its rule. `punt init` scaffolds a new repo that already satisfies them.

Tools. Punt Labs ships around a dozen of its own tools, and a repo should be able to say which ones it uses. The `standards/tool-enable-disable.md` convention is how: each tool owns a `.punt-labs/<tool>/` subtree, an enabled marker records the choice, and the host `CLAUDE.md` carries exactly one `@import` line per enabled tool so its guidance composes into every session. `enable` and `disable` are the verbs; `disable` is non-destructive. This is the kit-manager direction — `punt-kit` installs, enables, and audits the kit (see [FAQ 2](#)).

Workflows. `punt release` is an 11-phase release engine — preflight, version bump, build, release PR, tag, CI wait, GitHub release, PyPI verification, post-release, cross-repo propagation, and a final verify pass. It is the most-used feature in the org and runs on every release.

Compliance. `punt audit` and `punt pii` are the deterministic checks: convention conformance and a scan for emails, home directory paths, and hostnames, with a `-staged` mode for pre-commit.

The engine underneath. `/punt:auto` runs playbooks: YAML programs whose steps are either deterministic shell or scoped LLM judgment, with postconditions and a per-step failure strategy. The executor is an LLM following `skills/auto/SKILL.md` — not a daemon — which is what lets a judgment step sit next to a shell step in one program. The release engine is the shipped proof: eleven deterministic phases with LLM diagnosis on failure. The drafted next step turns the DSL into a prompt state machine — named states, guarded transitions, poll ticks, and persisted run-state with crash/resume — so a loop is a reviewed file rather than a retyped prompt (see [FAQ 4](#)).

Customer Quote

“I run the releases, and every one of them goes through `/punt:auto release` — eleven phases, and when a phase fails the executor reads the error and tries a fix instead of handing me a stack trace. That is the part I no longer think about. The part I still think about is the watching: I hand-type the same PR poll prompt every time a PR opens, and I typed it twice in one session last week. Those prompts are a state machine I re-derive from memory each time. I want to run the file instead.”

— **Claude Agento**, COO/VP Engineering agent, Punt Labs

Getting Started

Install with `install.sh` (or `uv tool install punt-kit` if `uv` is already present). In a new repo, `punt init` scaffolds CI workflows, tool config, permissions, and a `CLAUDE.md` that references the standards. `punt audit` reports where an existing repo diverges. `/punt:auto list` shows the playbooks available, and `/punt:auto release` runs a release end to end. Nothing phones home; every command runs locally against the checkout in front of it.

Spokesperson Quote

“The first version of this document described a tool that read our markdown standards and extracted checkable assertions from them. We never built that, and after two years of using

the thing, I do not want it. The consumer of a standard is a model and a reviewer, and prose is the right format for both; the checks that can be deterministic are better written as code than derived from a paragraph. What punt-kit actually became is the manager for the org's kit — the standards, the tools, the workflows, the compliance checks — and the honest version of this document says so. The part I am investing in is `/punt:auto`. Every recurring prompt I type by hand is a program I have not written yet. Turning those into playbooks, and then into state machines with guards and resume, means the tool writes the prompt and the agent runs the loop. That is the leverage. Whether anyone outside Punt Labs wants this is a question for later, deliberately.”

— J. Freeman, Creator, Punt Labs

Call to Action

punt-kit is public at `github.com/punt-labs/punt-kit`, on PyPI as `punt-kit`, and on the punt-labs Claude Code plugin marketplace as `punt@punt-labs`, under the MIT license. It is public because the org's other tools install it, not because it is being marketed. For a Punt Labs repo that has not adopted it: run `punt audit`, fix what it reports, and put the standards reference in `CLAUDE.md`.

Frequently Asked Questions

External FAQs

These are the questions the product’s actual users ask — the operator and the org’s agents. “External” here means outward from the tool, not outward from Punt Labs.

Q1: What is punt-kit and who is it for?

punt-kit is the kit manager for the Punt Labs org. It manages four things: **standards** (author them, activate them in a repo, audit against them), **tools** (install them, enable them, compose their guidance into a session), **workflows** (the release engine and the playbooks), and **compliance** (the conformance audit and the PII scan). Its users are one operator and the AI agents that work roughly thirty repositories. Two surfaces exist and are shipped: the punt CLI and the punt@punt-labs Claude Code plugin. There is no MCP server and no REST API; earlier versions of this document promised both, and neither was built (see [FAQ 7](#)).

Q2: What does “kit manager” mean?

A repo declares which of the org’s tools it uses, and punt-kit manages that declaration. Per standards/tool-enable-disable.md: each tool owns a .punt-labs/<tool>/ subtree in the repo, an enabled marker records the choice, and the host CLAUDE.md carries exactly one @-import line per enabled tool — so the tool’s own user guide, not a block of managed text, is what lands in the session. enable and disable are the verbs, and disable is non-destructive: it removes the import and the marker and leaves the subtree dormant.

The convention is deployed, not theoretical. Committed enabled markers exist in nine repos for biff and three for ethos. What punt-kit does not yet have is the manager surface itself — punt install and punt enable — which is the Should Do investment ([Feature 8](#)).

Q3: How do the standards actually reach an agent?

Three mechanisms, none of which involve parsing prose into assertions:

- **Reference.** A repo’s CLAUDE.md links the standards it is bound by; the agent reads the document. 26 of the org’s 30 CLAUDE.md files reference punt-kit today.
- **Auto-load.** lang-rules/ holds per-language coding rules (Python, Go, C, Swift) that load automatically when an agent touches a matching file, scoped by paths: frontmatter.
- **Check.** punt audit is hand-written deterministic Python that verifies the conventions a machine can verify — CI workflows, tool config, permissions, Makefile targets, README SHA pins, plugin version sync, branch-protection rulesets — and reports each finding with its rule.

The corpus is prose because its consumers are a language model and a human reviewer. Grinding a standard into assertions would lose the rationale that makes an agent apply it correctly to a case the rule did not anticipate, and the deterministic subset is cheaper to write directly as code.

Q4: What is /punt:auto and why is it the centerpiece?

/punt:auto runs **playbooks**: YAML programs whose steps are either script (deterministic shell) or llm (scoped judgment), each with an optional postcondition and a failure strategy (retry, diagnose, abort). The executor is an LLM following skills/auto/SKILL.md, which is why a judgment step can sit next to a shell step in one program — a daemon could not run half

of these steps. Six playbooks ship today; the release playbook is the proof, running the 11-phase engine with LLM diagnosis on failure.

The investment is turning that DSL into a **prompt state machine**. The drafted design adds named states, guarded transitions (shell checks plus scoped LLM-judgment guards for the clauses that are irreducibly judgment), poll ticks that compile to a /loop registration, and run-state persisted per instance so a machine survives a crash and resumes where it stopped. A linear playbook stays valid — it is the degenerate one-state machine.

What that buys: the recurring prompts the operator types by hand become files. Watching a PR to merge is a machine with a watch state that routes to fixing or merging on guards; sweeping the backlog is a non-terminating machine; a mission round is a do-while with a review cycle. Written as prose in a cron prompt, the current state lives only in the model's working context and evaporates on compaction. Written as a playbook, it is a reviewed, versioned artifact — **the tool generates the prompt, and the agent runs the loop**.

On naming: candidate playbook names in this document — /punt:auto sprint, /punt:auto backlog-cleanup, /punt:auto pr-loop — are illustrative. The names are open and the operator wants to debate them; nothing in the design depends on which ones are chosen.

Q5: How do I get started?

Install via `install.sh`, or `uv tool install punt-kit` if `uv` is already present. In a new repo, `punt init` scaffolds CI workflows, tool config, permissions, and a `CLAUDE.md`; it detects the project type and is idempotent, so re-running updates without overwriting customizations. In an existing repo, `punt audit` reports what diverges. `/punt:auto list` shows the available playbooks.

Q6: What happens to my data?

`punt-kit` runs locally against the checkout in front of it. It reads repository files and, when `gh` is authenticated, queries the GitHub API for repo settings. It transmits nothing to Punt Labs and has no telemetry today. That is about to change in one specific way: the operator wants **feature usage logged**, because there is currently no way to answer “which commands does anyone actually run?” Any such logging is local-first and internal-only by default ([Feature 9](#)).

Q7: Why only two surfaces?

Because two is what got built. `standards/architecture.md` describes the engine-and-clients model — one engine, thin CLI, plugin, MCP, and REST clients — and that is a good standard for the org's tools. `punt-kit` itself implements the CLI and the plugin. The MCP server and the REST API were aspirational and are listed in Won't Do for this version ([Feature 19](#)). An MCP surface is a reasonable future direction once a second agent runtime needs `punt-kit`; nothing today does.

Q8: Can a repo use its own standards or playbooks?

Partly, and this is honest rather than aspirational. Playbooks resolve project-local first: `./playbooks/<name>.yaml` shadows the org-wide copy, so a repo overrides any playbook by name. The standards corpus is currently referenced from `punt-kit` rather than pointed at a per-repo directory — the engine and corpus are separable in principle but not yet parameterized in practice ([Feature 13](#)).

Q9: Should anyone outside Punt Labs use this?

Not a question this version answers. `punt-kit` is public — MIT, on PyPI, on the marketplace — because the org's other tools install it, and public distribution is the cheapest way to do that. Whether it fits a team that is not Punt Labs is deferred by operator direction until the internal product has found its footing (see [FAQ 10](#), [FAQ 13](#)).

Internal FAQs

Value & Customer

Q10: Who is the customer, and what happened to the market case?

The customer is Punt Labs: one operator and the org's AI agents, working roughly thirty repositories. That is the whole addressable population this version is designed for.

Market sizing is deferred, deliberately. Version 1.0 of this document sized the platform-engineering market and argued that 5–50 engineer teams were an underserved segment. Nothing was ever done to test it, and the decision threshold that version set — “if after 6 months fewer than 3 non-punt-labs organizations are using punt-kit actively, consider whether the tool should remain internal-only” — has now fired. Zero external organizations use it. Rather than keep an untested market thesis in the document, this version drops it: punt-kit is internal, and sizing waits until the internal product has found its footing (see [FAQ 9](#)).

Q11: What evidence do we have that this is worth building?

Internal usage is the evidence now. It is real, and it is narrow — one org, one operator. Stated plainly:

- **The release engine is exercised on every release.** `punt release` drives all eleven phases, including cross-repo propagation into sibling repos, and it is invoked through `/punt:auto release`. It is the most-used feature in the org.
- **The standards corpus is consumed fleet-wide.** 29 normative documents, referenced from 26 of the org's 30 `CLAUDE.md` files, plus per-language rules that load automatically on matching files.
- **The enable/disable convention has adopters.** `biff`, `ethos`, and `vox` implement it; committed enabled markers exist in nine repos for `biff` and three for `ethos` — the convention survived contact with three independent implementations.
- **The pain the DSL targets is observed, not hypothesized.** The operator hand-authored the same PR watch loop as a fresh cron prompt twice in a single session on 2026-07-27. That specific event is what motivated the state-machine design.

The context problem is externally corroborated, which is why the standards corpus exists at all: single-file agent manifests “do not scale beyond modest codebases” [5]; a study of 2,303 context files found security specified in only 14.5% [6]; agent sessions without context files consume 28.64% more runtime and 16.58% more tokens [7].

What is missing: any evidence from outside Punt Labs. There are no external users, no interviews, and no usage data — not even internal usage data, because nothing is logged yet ([Feature 9](#)). This gap is accepted for now, not closed.

Q12: What are the reference points in this space?

These are tools worth reading, not competitors to beat. punt-kit is not competing for adoption right now, so the useful question is which ideas to borrow and which scope to stay out of.

Tool	What It Does Well	What We Take From It
projen	Standards-as-code for project config across N repos [8]	The strongest prior art for cross-repo config. We stayed with prose plus deterministic checks rather than a TypeScript project model
Backstage	Developer portal with golden-path scaffolding [9]	A warning: it needs a dedicated team to run. Scope we deliberately stay out of (Feature 14)
Trunk	Metalinter orchestrating 100+ tools [10]	The linting layer, which punt-kit orchestrates rather than reimplements (Feature 16)
Copier	Template scaffolding with lifecycle updates [11]	Idempotent re-templating, which punt init approximates

The one thing none of them does is the thing this version is investing in: running the org's recurring *procedures* as programs that mix deterministic steps with model judgment. That is not a differentiation claim — it may simply be a problem only an org run by agents has.

Q13: What is the next step to validate the direction?

Internal, and concrete:

1. **Build the state-machine DSL** and convert exactly one hand-typed loop — the PR watch — into a playbook. One loop, not three: if the construct does not carry the loop we run most, it does not carry the others.
2. **Turn on usage logging**, so the metrics below can be measured at all rather than recalled.
3. **Watch for six weeks** whether the operator stops typing the loop by hand.

Decision threshold: if after that window the operator is still hand-authoring watch prompts — because the playbook is harder to invoke, or its guards are wrong often enough to distrust — then the DSL is not the leverage, and the investment stops at playbooks as they exist today.

Technical**Q14: What are the major technical risks?**

1. **The executor is an LLM, so machines are not fully deterministic.** A shell guard is a pure function of the world and routes identically every evaluation; a judgment guard is not, so the same PR state can route two ways on two ticks. Mitigation: script is the default guard type and llm is opt-in, confined to clauses that are irreducibly judgment (“are these findings addressed?”). The trade is explicit in the design and is a decision the operator ratifies, not a property that leaks in.
2. **Ticks are session-scoped.** A poll compiles to a /loop registration, which lives in the session that created it and dies with it, so a machine pauses when its session ends. Mitigation is a documented property rather than machinery: run-state is durable, and any -resume

invocation re-registers the tick. A paused machine loses no state and cannot act wrongly — it just does not advance.

3. **Idempotency is the playbook author's burden.** Crash/resume re-visits a state, so an action that already ran must be a no-op the second time. The design pushes this onto authors (guard the merge on the PR still being open, guard the branch delete on the branch still existing). Authors will get it wrong; the mitigation is that guards recompute from live state, so a wrong re-visit is usually an empty one.
4. **Claude Code API surface.** Plugins, skills, and `/loop` are the substrate the executor stands on, and they evolve. Mitigation: `punt-kit` ships a working plugin and tracks changes as ordinary maintenance; the CLI half (`init`, `audit`, `pii`, `release`) runs without any of it.

Q15: What dependencies exist on other teams or systems?

`punt release` depends on GitHub (via `gh`), PyPI, and on sibling repos being checked out locally for cross-repo propagation. Distribution depends on PyPI and the Claude Code plugin marketplace.

The deeper dependency is the playbook executor: it *is* Claude Code reading `skills/auto/SKILL.md`, not a program `punt-kit` ships. That is a deliberate design choice — half the steps in a real playbook are judgment or sub-agent calls that no daemon could run — but it means playbooks do not execute outside a Claude Code session. The deterministic CLI has no such dependency.

Q16: What is the development timeline?

Shipped, through v0.11.x (August 2026):

- Standards corpus — 29 documents plus `lang-rules/` for Python, Go, C, and Swift
- `punt init` (scaffold, idempotent, project-type detection), `punt audit`, `punt pii`, `punt doctor`, `punt status`
- `punt release` — the 11-phase engine, plus `-resume-from` for restarting at any phase
- `/punt: auto` playbook executor and six playbooks; the Claude Code plugin on the `punt-labs` marketplace

Invested next, in priority order:

1. **Prompt state-machine DSL** — states, guarded transitions, poll ticks, run-state with crash/resume; convert the PR watch loop as the first machine ([Feature 7](#)).
2. **`punt enable` and `punt install`** — the kit-manager surface: activate a standard in a repo, install and enable a tool, per `tool-enable-disable.md` ([Feature 8](#)).
3. **Usage logging** — which commands and playbooks actually get run ([Feature 9](#)).
4. **Audit revival keyed to enabled policy** — `punt audit` checks a fixed set of conventions today; the revival scopes it to what a repo has actually enabled, so a repo is measured against its own declared kit ([Feature 10](#)).

No dates. One operator, agent-executed work, and a queue that reorders on the operator's ruling — a dated plan would be fiction, and the last one was.

Business

Q17: Why spend time on an internal tool with no revenue?

punt-kit is free and open-source with no paid tiers and no revenue plan. The case for the time is internal leverage:

- **It is the substrate the other tools ship on.** biff, quarry, vox, and lux all document punt release as their release path. Time spent here is amortized across every repo that releases.
- **It is how conventions reach agents at all.** The corpus plus the @-import architecture is the delivery mechanism for everything the org has decided about how work is done.
- **The DSL investment targets the operator's own time.** Every recurring prompt replaced by a playbook is a task the operator stops re-deriving from memory.

The risk this leaves open is opportunity cost: hours on punt-kit are hours not spent on the products it serves. The DSL work is the sharpest form of that bet (see [FAQ 13](#)).

Q18: What are the key metrics for success?

Internal, and chosen so that a bad number means something is actually wrong:

1. **Repos with standards activated** — how many of the org's repos reference the corpus and pass `punt audit`. Today: 26 of 30 reference it; conformance is unmeasured.
2. **Releases run through the engine** — the share of releases that complete via `/punt:auto` release without the operator dropping to manual steps. Resume-from-phase counts as engine; a hand-run merge does not.
3. **Recurring prompts replaced by playbooks** — how many of the loops the operator used to type are now files that are actually invoked. This is the metric for the DSL investment.
4. **Playbook failure mode mix** — of playbook runs that fail, how many are recovered by diagnose versus escalated to the operator. Rising escalation means the executor is not carrying its half.

Caveat, stated up front: three of these four cannot be measured today. There is no usage logging, so "how many releases ran clean" is currently an act of recall. The metrics are honest only after [Feature 9](#) lands — which is why it is on the invested list rather than a nice-to-have.

Q19: Why now? What has changed?

Two shifts, one external and one internal.

The work moved to agents. Nearly all code in this org is now written by AI agents in Claude Code sessions, and the agent-context infrastructure that makes that governable — `CLAUDE.md`, @-imports, plugins, skills, hooks — did not exist eighteen months ago. Standards that live only in a senior engineer's head do not reach an agent; standards in a document that the session imports do.

The bottleneck moved from writing code to steering loops. With execution cheap, the scarce resource is the operator's attention on which loop is running, what state it is in, and whether it may advance. That is what makes `/punt:auto` the centerpiece of this version rather than an automation convenience: the loops are now the expensive part, and they are still being typed by hand.

Risk Assessment

Risk	Rating	Assessment
Value	Medium	The shipped halves have demonstrated value: the release engine runs every release, and the standards corpus is referenced by 26 of the org's 30 <code>CLAUDE.md</code> files. The risk has moved to the new investment. Whether a prompt state machine actually makes agent-run loops more reliable than a well-written prose prompt is unproven — the design argues it does, because the current state survives compaction and the guards are reviewable, but no machine has run yet. If a playbook's guards are wrong often enough that the operator distrusts it, the DSL buys nothing and the value is only what already ships (see FAQ 13).
Usability	Medium	The shipped CLI is easy: <code>punt init</code> , <code>punt audit</code> , <code>/punt:auto release</code> , no configuration. The new surface is not. Writing a state machine — states, ordered guards, idempotent visits — is a harder authoring task than typing the prompt it replaces, and the person who must do the authoring is the same operator whose time the feature is supposed to save. Authoring cost is paid once per loop and the benefit recurs, so the arithmetic works only for loops that genuinely recur. The mitigation is to ship one machine for the most-repeated loop and see whether it gets used, rather than shipping a library of them.
Feasibility	Medium	The deterministic half is proven: the CLI ships, the 11-phase release engine runs across sibling repos, 210 tests pass. The unproven half is the executor. It is a language model following a protocol document, so a judgment guard is not reproducible across evaluations, and correct crash/resume depends on playbook authors writing idempotent actions. Both are named in the design with mitigations (<code>script guards</code> by default; guards recompute from live state) rather than assumed away. Nothing depends on unproven third-party technology.
Viability	Low	As an internal tool, viability is not about revenue — there is none planned — but about whether the org can keep it. It costs one operator's attention, it pays for itself on every release it drives, and it has no hosting, service, or support obligations. The real exposures are opportunity cost (hours here are hours not on the products <code>punt-kit</code> serves) and concentration: it is load-bearing for every release in the org and has one maintainer.

Feature Appendix

Defines the scope boundary. Because most of Must Do already ships, this appendix does double duty: it records what the product is today, and it names what is deliberately not being built — including the things an earlier version of this document promised.

Must Do

What the product is. Items 1–6 ship today at v0.11.2; item 7 is the one investment this version treats as essential rather than optional — without it, `/punt:auto` stays a script runner and the self-prompting story in the press release is not true.

- F1. Standards corpus and activation** — 29 normative prose documents in `standards/`, plus `lang-rules/` per-language rules (Python, Go, C, Swift) that agents auto-load on matching files. A repo activates them by referencing them from `CLAUDE.md`
- F2. Deterministic conformance audit** — `punt audit` — hand-written checks of CI workflows, tool config, permissions, Makefile targets, README SHA pins, plugin version sync, and branch-protection rulesets, each finding reported with its rule
- F3. Release engine** — `punt release` — the 11-phase pipeline from preflight through cross-repo propagation and a final verify, with `-resume-from` to restart at any phase. The most-used feature in the org
- F4. Playbook executor** — `/punt:auto` — YAML programs mixing script (deterministic shell) and `llm` (scoped judgment) steps, with postconditions and per-step failure strategies. Cross-repo rollout lives here as `standards-rollout` and `permissions-rollout`, not as a dedicated command
- F5. Compliance scans** — `punt pii` — emails, home directory paths, and `.local` hostnames, with `-staged` for pre-commit
- F6. Two surfaces: CLI and plugin** — the `punt` CLI (`init`, `audit`, `pii`, `release`, `doctor`, `status`) and the `punt@punt-labs` Claude Code plugin that wraps them as slash commands
- F7. Prompt state-machine DSL** — extend the playbook DSL with named states, guarded transitions (shell checks plus scoped LLM-judgment guards), `poll` ticks, and per-instance run-state with `crash/resume` — turning a hand-typed recurring prompt into a reviewed file

Should Do

Real improvements, not launch-blocking. The cold features live here: they were built or drafted, went unused, and are kept because the kit-manager identity gives them a reason to exist that they did not have before.

- F8. Kit-manager surface** — `punt install` and `punt enable` — install an org tool, write its `.punt-labs/<tool>/` subtree and `enabled` marker, add the one `@import` line, and reverse all of it on `disable`, per `standards/tool-enable-disable.md`
- F9. Usage logging** — record which commands and playbooks actually run, locally and internal-only, so the metrics in [FAQ 18](#) are measured rather than recalled
- F10. Audit revival keyed to enabled policy** — scope `punt audit` to what a repo has actually enabled, so each repo is measured against its own declared kit instead of one fixed list of conventions
- F11. Reconcile on the new engine** — `/punt:reconcile` — LLM-driven reconciliation of a repo against changed standards, rebuilt as a playbook rather than a standalone prompt

- F12. Autopilot as a state machine** — the autonomous backlog loop reborn as a non-terminating machine with guarded transitions, replacing today's prose loop playbook
- F13. Custom standards directory** — parameterize the corpus location so a repo can point at its own rules. Separable in principle today, not parameterized in practice

Won't Do

Naming what we will not build. The first four exclusions were in version 1.0 of this document and held — nothing since has argued for reopening them. The last three are new, and each retires a claim the earlier version made.

- F14. GUI or web dashboard** — punt-kit is a terminal tool and a Claude Code plugin. A web interface would split focus and target a different user. Teams that want a portal should use Backstage
- F15. CI system replacement** — punt-kit generates and validates CI workflows. It does not replace GitHub Actions, GitLab CI, or any CI runner
- F16. Code parsing or linting** — punt-kit orchestrates linters (ruff, mypy, shellcheck) and validates their configuration. It does not parse source code. Teams that want a metalinter should use Trunk or MegaLinter
- F17. Package management** — validates distribution config and automates release pipelines; does not replace PyPI, npm, or uv
- F18. Standards parsed into checkable assertions** — version 1.0 of this document promised an engine that read markdown standards and extracted assertions from them. It was never built and is not wanted: prose is the right format for a model and a reviewer, and the deterministic subset is better written directly as code ([Feature 2](#))
- F19. MCP server and REST API** — promised as two of four surfaces, neither built. A future direction if a second agent runtime or a CI system ever needs to call punt-kit; nothing does today, and building either now would be building for a user that does not exist
- F20. External adoption machinery** — no marketing site, no onboarding path for non-Punt-Labs teams, no third-party standards packs, no `punt rollout` command aimed at other orgs' repos. Deferred by operator direction until the internal product has found its footing ([FAQ 9](#))

References

- [1] Anthropic. *Effective Context Engineering for AI Agents*. “Each new session begins with no memory of what came before”. 2025. URL: <https://www.anthropic.com/engineering/effective-context-engineering-for-ai-agents>.
- [2] Matteo Ciniselli et al. *On the Use of Agentic Coding Manifests: An Empirical Study of Claude Code*. 253 CLAUDE.md files from 242 repos; manifests optimized for code execution not org conventions; security in 8.7%. 2025. URL: <https://arxiv.org/abs/2509.14744>.
- [3] Anthropic. *Manage Claude’s Memory — Claude Code Docs*. CLAUDE.md loaded every session but is static with no feedback loop to detect drift. 2025. URL: <https://code.claude.com/docs/en/memory>.
- [4] DeepSource. *Engineering Manager’s Guide to Static Analysis*. Quantifies static analysis at 4 hours/week/engineer saved on code reviews. 2025. URL: <https://deepsource.com/blog/engineering-manager-guide-to-static-analysis>.
- [5] Jonah Katz et al. *Codified Context: Infrastructure for AI Agents in a Complex Codebase*. 283 sessions on a 108,000-line codebase; single-file manifests do not scale; three-component infrastructure for persistent agent context. 2026. URL: <https://arxiv.org/abs/2602.20478>.
- [6] Filipe Calegario et al. *Agent READMEs: An Empirical Study of Context Files for Agentic Coding*. 2,303 context files from 1,925 repos; security in only 14.5% of files; build commands dominate at 62.3%. 2025. URL: <https://arxiv.org/abs/2511.12884>.
- [7] Lucas Larson et al. *On the Impact of AGENTS.md Files on the Efficiency of AI Coding Agents*. 10 repos, 124 PRs; AGENTS.md presence reduces runtime 28.64% and token consumption 16.58%. 2026. URL: <https://arxiv.org/abs/2601.20404>.
- [8] projen contributors. *projen: Rapidly Build Modern Applications with Advanced Configuration Management*. Synthesized config files should never be manually edited; custom project types can update N repos; AWS-centric, TypeScript-first. 2024. URL: <https://github.com/projen/projen>.
- [9] Spotify Engineering. *Celebrating Five Years of Backstage*. 3,000+ organizations; adoption stalls at under 10% in most non-Spotify orgs; requires dedicated full-time team. 2025. URL: <https://engineering.atspotify.com/2025/4/celebrating-five-years-of-backstage>.
- [10] Trunk.io. *Trunk Code Quality: Automated Code Quality for Teams*. Metalinter running 100+ tools; CI-focused; does not scaffold, manage releases, or integrate with AI agents. 2024. URL: <https://trunk.io/code-quality>.
- [11] Copier contributors. *Comparisons — Copier Documentation*. Lifecycle management: updating existing projects when templates evolve; confirms propagation problem is real. 2024. URL: <https://copier.readthedocs.io/en/stable/comparisons/>.