

Claude Code + Quarry: A Z Specification

Layer 2 — Knowledge Capture State

March 2026 (implementation status revised September 2026)

Contents

1	Introduction	3
2	Base Types (from <code>claude-code.tex</code>)	3
3	Quarry Types	3
4	Global Constants	3
5	State	4
6	Initialization	4
7	Quarry Frame Condition	5
8	Session Lifecycle Operations	5
8.1	StartSessionWithSync	5
8.2	StartSessionNoSync	6
8.3	SubmitPrompt	6
9	Tool Call Operations	7
9.1	BeginToolCall	7
9.2	PreToolHookAllow	7
9.3	PreToolHookDeny	8
9.4	GrantPermission	8
9.5	DenyPermission	9
9.6	CompleteToolSuccess	9
9.7	CompleteToolFailure	9
10	Quarry Operations	10
10.1	CaptureWebFetch	10
10.2	SwitchDatabase	10
10.3	SearchKnowledge	11
10.4	InjectKnowledgeHint	11
11	Subagent Operations	12
12	Response and Stop	13
13	Context Management — Compaction Safety	14
13.1	CaptureBeforeCompact	14
13.2	SkipCaptureBeforeCompact	15
13.3	CompactContext	15
14	Session End	16
15	System Invariants	16

16 Hook Event Map	17
17 Implementation Validation	17
17.1 Hook Wiring Status	18
17.2 Not Yet Built	18
17.3 Coverage Summary	18

1 Introduction

This specification extends the base Claude Code state machine (`claude-code.tex`) with quarry automatic knowledge capture state. Quarry provides local semantic search over codebases, documents, and conversation history.

The key properties verified by this model:

1. **Knowledge before work:** the codebase is indexed before Claude begins processing. The `SessionStart` hook auto-registers and syncs the working directory.
2. **No knowledge loss on compaction:** before context compaction shrinks the conversation, the `PreCompact` hook captures session notes. No path reaches `CompactContext` without the capture flag being set.
3. **WebFetch auto-capture:** URLs fetched during a session are automatically ingested into the project's `<repo>-captures` collection (`default-captures` when the working directory is not registered).
4. **Capture toggles are respected:** each auto-capture layer (session sync, web fetch, compaction) can be independently disabled via `.punt-labs/quarry/config.md`.

2 Base Types (from `claude-code.tex`)

[*TOOLNAME*, *TOOLINPUT*, *TOOLOUTPUT*, *PROMPT*,
RESPONSE, *AGENTID*, *SESSIONID*, *CONTEXTCHUNK*]

SessionPhase ::= *spInactive* | *spIdle* | *spProcessing* | *spResponding* | *spEnded*

ToolPhase ::= *tpNone* | *tpPreHook* | *tpPermission* | *tpExecuting* | *tpPostHook*

PermissionMode ::= *pmDefault* | *pmPlan* | *pmAcceptEdits* | *pmDontAsk* | *pmBypass*

PermissionDecision ::= *pdAllow* | *pdDeny* | *pdAsk*

HookDecision ::= *hdAllow* | *hdBlock*

SessionStartSource ::= *ssStartup* | *ssResume* | *ssClear* | *ssCompact*

SessionEndReason ::= *seClear* | *seLogout* | *sePromptExit* | *seBypassDisabled* | *seOther*

ZBOOL ::= *ztrue* | *zfalse*

3 Quarry Types

[*DBNAME*, *URL*]

DBNAME identifies a quarry database (e.g., `default`, `punt-labs`). *URL* identifies a fetched web resource.

4 Global Constants

<i>maxTools</i> : $\mathbb{N}$
<i>maxSubagents</i> : $\mathbb{N}$
<i>maxContext</i> : $\mathbb{N}$
<i>maxCaptures</i> : $\mathbb{N}$
<i>maxTools</i> = 5
<i>maxSubagents</i> = 2
<i>maxContext</i> = 3
<i>maxCaptures</i> = 5

5 State

State

sessionId : $\mathbb{F}$ *SESSIONID*
sessionPhase : *SessionPhase*
permMode : *PermissionMode*
toolPhase : *ToolPhase*
currentTool : $\mathbb{F}$ *TOOLNAME*
toolsThisTurn : $\mathbb{N}$
activeSubagents : $\mathbb{F}$ *AGENTID*
context : seq *CONTEXTCHUNK*
pendingPrompt : $\mathbb{F}$ *PROMPT*
pendingResponse : $\mathbb{F}$ *RESPONSE*
codebaseIndexed : *ZBOOL*
activeDb : $\mathbb{F}$ *DBNAME*
capturedUrls : $\mathbb{F}$ *URL*
compactionSaved : *ZBOOL*
cfgSessionSync : *ZBOOL*
cfgWebFetch : *ZBOOL*
cfgCompaction : *ZBOOL*

$\#sessionId \leq 1$
 $sessionPhase = spInactive \Rightarrow sessionId = \emptyset$
 $sessionPhase \neq spInactive \Rightarrow \#sessionId = 1$
 $sessionPhase \neq spProcessing \Rightarrow toolPhase = tpNone$
 $\#currentTool \leq 1$
 $toolPhase = tpNone \Rightarrow currentTool = \emptyset$
 $toolPhase \neq tpNone \Rightarrow \#currentTool = 1$
 $toolsThisTurn \leq maxTools$
 $sessionPhase = spInactive \Rightarrow activeSubagents = \emptyset$
 $sessionPhase = spEnded \Rightarrow activeSubagents = \emptyset$
 $\#activeSubagents \leq maxSubagents$
 $\#context \leq maxContext$
 $\#pendingPrompt \leq 1$
 $sessionPhase = spIdle \Rightarrow pendingPrompt = \emptyset$
 $sessionPhase = spInactive \Rightarrow pendingPrompt = \emptyset$
 $sessionPhase = spEnded \Rightarrow pendingPrompt = \emptyset$
 $\#pendingResponse \leq 1$
 $sessionPhase \neq spResponding \Rightarrow pendingResponse = \emptyset$
 $\#activeDb \leq 1$
 $\#capturedUrls \leq maxCaptures$
 $sessionPhase = spInactive \Rightarrow codebaseIndexed = zfalse$
 $sessionPhase = spInactive \Rightarrow activeDb = \emptyset$
 $sessionPhase = spInactive \Rightarrow capturedUrls = \emptyset$
 $sessionPhase = spInactive \Rightarrow compactionSaved = zfalse$

6 Initialization

Init
State'

sessionId' = $\emptyset$
sessionPhase' = *spInactive*
permMode' = *pmDefault*
toolPhase' = *tpNone*
currentTool' = $\emptyset$
toolsThisTurn' = 0
activeSubagents' = $\emptyset$
context' = $\langle \rangle$
pendingPrompt' = $\emptyset$
pendingResponse' = $\emptyset$
codebaseIndexed' = *zfalse*
activeDb' = $\emptyset$
capturedUrls' = $\emptyset$
compactionSaved' = *zfalse*
cfgSessionSync' = *ztrue*
cfgWebFetch' = *ztrue*
cfgCompaction' = *ztrue*

7 Quarry Frame Condition

QuarryFrame
 Δ *State*

codebaseIndexed' = *codebaseIndexed*
activeDb' = *activeDb*
capturedUrls' = *capturedUrls*
compactionSaved' = *compactionSaved*
cfgSessionSync' = *cfgSessionSync*
cfgWebFetch' = *cfgWebFetch*
cfgCompaction' = *cfgCompaction*

8 Session Lifecycle Operations

8.1 StartSessionWithSync

SessionStart hook fires. If *cfgSessionSync* = *ztrue*, quarry auto-registers the working directory and syncs. The codebase is indexed before Claude can process prompts.

StartSessionWithSync

Δ State

sid? : *SESSIONID*

source? : *SessionStartSource*

mode? : *PermissionMode*

sessionPhase = *spInactive*

cfgSessionSync = *ztrue*

sessionPhase' = *spIdle*

sessionId' = {*sid?*}

permMode' = *mode?*

toolPhase' = *tpNone*

currentTool' = $\emptyset$

toolsThisTurn' = 0

activeSubagents' = $\emptyset$

context' = $\langle \rangle$

pendingPrompt' = $\emptyset$

pendingResponse' = $\emptyset$

codebaseIndexed' = *ztrue*

activeDb' = $\emptyset$

capturedUrls' = $\emptyset$

compactionSaved' = *zfalse*

cfgSessionSync' = *cfgSessionSync*

cfgWebFetch' = *cfgWebFetch*

cfgCompaction' = *cfgCompaction*

8.2 StartSessionNoSync

Session starts but sync is disabled. The codebase is not indexed automatically.

StartSessionNoSync

Δ State

sid? : *SESSIONID*

source? : *SessionStartSource*

mode? : *PermissionMode*

sessionPhase = *spInactive*

cfgSessionSync = *zfalse*

sessionPhase' = *spIdle*

sessionId' = {*sid?*}

permMode' = *mode?*

toolPhase' = *tpNone*

currentTool' = $\emptyset$

toolsThisTurn' = 0

activeSubagents' = $\emptyset$

context' = $\langle \rangle$

pendingPrompt' = $\emptyset$

pendingResponse' = $\emptyset$

codebaseIndexed' = *zfalse*

activeDb' = $\emptyset$

capturedUrls' = $\emptyset$

compactionSaved' = *zfalse*

cfgSessionSync' = *cfgSessionSync*

cfgWebFetch' = *cfgWebFetch*

cfgCompaction' = *cfgCompaction*

8.3 SubmitPrompt

SubmitPrompt

QuarryFrame

prompt? : *PROMPT*

hookResult? : *HookDecision*

contextChunk? : *CONTEXTCHUNK*

sessionPhase = *spIdle*

hookResult? = *hdAllow*

sessionPhase' = *spProcessing*

pendingPrompt' = {*prompt?*}

context' = (1 .. *maxContext*) $\triangleleft$ (*context* $\hat{\ } \langle$ *contextChunk?* $\rangle$)

toolsThisTurn' = 0

toolPhase' = *tpNone*

currentTool' = $\emptyset$

sessionId' = *sessionId*

permMode' = *permMode*

activeSubagents' = *activeSubagents*

pendingResponse' = $\emptyset$

RejectPrompt

$\exists$ *State*

prompt? : *PROMPT*

hookResult? : *HookDecision*

sessionPhase = *spIdle*

hookResult? = *hdBlock*

9 Tool Call Operations

9.1 BeginToolCall

BeginToolCall

QuarryFrame

tool? : *TOOLNAME*

sessionPhase = *spProcessing*

toolPhase = *tpNone*

toolsThisTurn < *maxTools*

toolPhase' = *tpPreHook*

currentTool' = {*tool?*}

sessionPhase' = *sessionPhase*

sessionId' = *sessionId*

permMode' = *permMode*

toolsThisTurn' = *toolsThisTurn*

activeSubagents' = *activeSubagents*

context' = *context*

pendingPrompt' = *pendingPrompt*

pendingResponse' = *pendingResponse*

9.2 PreToolHookAllow

PreToolHookAllow

QuarryFrame

hookDecision? : *PermissionDecision*

needsPermission? : *ZBOOL*

sessionPhase = *spProcessing*

toolPhase = *tpPreHook*

hookDecision? = *pdAllow*

toolPhase' = **if** *needsPermission?* = *ztrue* **then** *tpPermission* **else** *tpExecuting*

sessionPhase' = *sessionPhase*

sessionId' = *sessionId*

permMode' = *permMode*

currentTool' = *currentTool*

toolsThisTurn' = *toolsThisTurn*

activeSubagents' = *activeSubagents*

context' = *context*

pendingPrompt' = *pendingPrompt*

pendingResponse' = *pendingResponse*

9.3 PreToolHookDeny

PreToolHookDeny

QuarryFrame

hookDecision? : *PermissionDecision*

denialContext? : *CONTEXTCHUNK*

sessionPhase = *spProcessing*

toolPhase = *tpPreHook*

hookDecision? = *pdDeny*

toolPhase' = *tpNone*

currentTool' = $\emptyset$

context' = $(1 \dots \text{maxContext}) \triangleleft (\text{context} \hat{\ } \langle \text{denialContext?} \rangle)$

sessionPhase' = *sessionPhase*

sessionId' = *sessionId*

permMode' = *permMode*

toolsThisTurn' = *toolsThisTurn*

activeSubagents' = *activeSubagents*

pendingPrompt' = *pendingPrompt*

pendingResponse' = *pendingResponse*

9.4 GrantPermission

GrantPermission

QuarryFrame

sessionPhase = *spProcessing*

toolPhase = *tpPermission*

toolPhase' = *tpExecuting*

sessionPhase' = *sessionPhase*

sessionId' = *sessionId*

permMode' = *permMode*

currentTool' = *currentTool*

toolsThisTurn' = *toolsThisTurn*

activeSubagents' = *activeSubagents*

context' = *context*

pendingPrompt' = *pendingPrompt*

pendingResponse' = *pendingResponse*

9.5 DenyPermission

DenyPermission

QuarryFrame

denialContext? : *CONTEXTCHUNK*

sessionPhase = *spProcessing*

toolPhase = *tpPermission*

toolPhase' = *tpNone*

currentTool' = $\emptyset$

context' = $(1 \dots \text{maxContext}) \triangleleft (\text{context} \hat{\ } \langle \text{denialContext?} \rangle)$

sessionPhase' = *sessionPhase*

sessionId' = *sessionId*

permMode' = *permMode*

toolsThisTurn' = *toolsThisTurn*

activeSubagents' = *activeSubagents*

pendingPrompt' = *pendingPrompt*

pendingResponse' = *pendingResponse*

9.6 CompleteToolSuccess

CompleteToolSuccess

QuarryFrame

output? : *CONTEXTCHUNK*

sessionPhase = *spProcessing*

toolPhase = *tpExecuting*

toolPhase' = *tpNone*

currentTool' = $\emptyset$

toolsThisTurn' = *toolsThisTurn* + 1

context' = $(1 \dots \text{maxContext}) \triangleleft (\text{context} \hat{\ } \langle \text{output?} \rangle)$

sessionPhase' = *sessionPhase*

sessionId' = *sessionId*

permMode' = *permMode*

activeSubagents' = *activeSubagents*

pendingPrompt' = *pendingPrompt*

pendingResponse' = *pendingResponse*

9.7 CompleteToolFailure

CompleteToolFailure

QuarryFrame

errorContext? : *CONTEXTCHUNK*

sessionPhase = *spProcessing*

toolPhase = *tpExecuting*

toolPhase' = *tpNone*

currentTool' = $\emptyset$

toolsThisTurn' = *toolsThisTurn* + 1

context' = $(1 \dots \text{maxContext}) \triangleleft (\text{context} \hat{\ } \langle \text{errorContext?} \rangle)$

sessionPhase' = *sessionPhase*

sessionId' = *sessionId*

permMode' = *permMode*

activeSubagents' = *activeSubagents*

pendingPrompt' = *pendingPrompt*

pendingResponse' = *pendingResponse*

10 Quarry Operations

10.1 CaptureWebFetch

PostToolUse on **WebFetch**. When web fetch capture is enabled, the fetched URL is added to the captured set and ingested into the project's `<repo>-captures` collection (async, fire-and-forget; the daemon scrubs before storing).

<i>CaptureWebFetch</i>
$\Delta State$
<i>url?</i> : <i>URL</i>
<i>sessionPhase</i> = <i>spProcessing</i>
<i>toolPhase</i> = <i>tpNone</i>
<i>cfgWebFetch</i> = <i>ztrue</i>
<i>url?</i> $\notin$ <i>capturedUrls</i>
$\#capturedUrls < maxCaptures$
$capturedUrls' = capturedUrls \cup \{url?\}$
$sessionPhase' = sessionPhase$
$sessionId' = sessionId$
$permMode' = permMode$
$toolPhase' = toolPhase$
$currentTool' = currentTool$
$toolsThisTurn' = toolsThisTurn$
$activeSubagents' = activeSubagents$
$context' = context$
$pendingPrompt' = pendingPrompt$
$pendingResponse' = pendingResponse$
$codebaseIndexed' = codebaseIndexed$
$activeDb' = activeDb$
$compactionSaved' = compactionSaved$
$cfgSessionSync' = cfgSessionSync$
$cfgWebFetch' = cfgWebFetch$
$cfgCompaction' = cfgCompaction$

10.2 SwitchDatabase

Claude calls `quarry use <name>`. Changes the active database for subsequent queries.

SwitchDatabase

$\Delta State$

db? : *DBNAME*

sessionPhase = *spProcessing*
toolPhase = *tpNone*
activeDb' = {*db?*}
sessionPhase' = *sessionPhase*
sessionId' = *sessionId*
permMode' = *permMode*
toolPhase' = *toolPhase*
currentTool' = *currentTool*
toolsThisTurn' = *toolsThisTurn*
activeSubagents' = *activeSubagents*
context' = *context*
pendingPrompt' = *pendingPrompt*
pendingResponse' = *pendingResponse*
codebaseIndexed' = *codebaseIndexed*
capturedUrls' = *capturedUrls*
compactionSaved' = *compactionSaved*
cfgSessionSync' = *cfgSessionSync*
cfgWebFetch' = *cfgWebFetch*
cfgCompaction' = *cfgCompaction*

10.3 SearchKnowledge

Claude calls `quarry find`. This is a read-only query that injects search results into context. Modeled to show that search results flow into the conversation.

SearchKnowledge

$\Delta State$

results? : *CONTEXTCHUNK*

sessionPhase = *spProcessing*
toolPhase = *tpNone*
context' = $(1 \dots \text{maxContext}) \triangleleft (\text{context} \hat{\cup} \langle \text{results?} \rangle)$
sessionPhase' = *sessionPhase*
sessionId' = *sessionId*
permMode' = *permMode*
toolPhase' = *toolPhase*
currentTool' = *currentTool*
toolsThisTurn' = *toolsThisTurn*
activeSubagents' = *activeSubagents*
pendingPrompt' = *pendingPrompt*
pendingResponse' = *pendingResponse*
codebaseIndexed' = *codebaseIndexed*
activeDb' = *activeDb*
capturedUrls' = *capturedUrls*
compactionSaved' = *compactionSaved*
cfgSessionSync' = *cfgSessionSync*
cfgWebFetch' = *cfgWebFetch*
cfgCompaction' = *cfgCompaction*

10.4 InjectKnowledgeHint

Quarry proactively injects relevant knowledge into context at key moments: **SessionStart** (project standards, workflow tips), **PostToolUse** on **Edit|Write** (e.g., “remember our changelog standard”, “update DESIGN.md with an ADR”), **PostToolUse** on tool-specific patterns (e.g., “top hints for working with Z specs” when editing `.tex` files).

These are contextual hints retrieved from quarry collections (standards, design docs, project conventions) and injected as **additionalContext**. The injection is non-blocking and additive — it appends to context without altering other state.

<i>InjectKnowledgeHint</i> $\Delta State$ $hint? : CONTEXTCHUNK$
$sessionPhase \in \{spIdle, spProcessing\}$ $context' = (1..maxContext) \triangleleft (context \hat{\ } \langle hint? \rangle)$ $sessionPhase' = sessionPhase$ $sessionId' = sessionId$ $permMode' = permMode$ $toolPhase' = toolPhase$ $currentTool' = currentTool$ $toolsThisTurn' = toolsThisTurn$ $activeSubagents' = activeSubagents$ $pendingPrompt' = pendingPrompt$ $pendingResponse' = pendingResponse$ $codebaseIndexed' = codebaseIndexed$ $activeDb' = activeDb$ $capturedUrls' = capturedUrls$ $compactionSaved' = compactionSaved$ $cfgSessionSync' = cfgSessionSync$ $cfgWebFetch' = cfgWebFetch$ $cfgCompaction' = cfgCompaction$

This operation fires in both **spIdle** (SessionStart context injection) and **spProcessing** (PostToolUse context injection). The hint content is determined by quarry’s semantic search over registered collections — the Z spec abstracts this as an opaque **CONTEXTCHUNK** input.

Example injection points:

- **SessionStart**: “This project follows punt-kit standards. Key conventions: ruff, mypy, pytest, CHANGELOG.md under [Unreleased].”
- **PostToolUse on Edit of CHANGELOG.md**: “Keep a Changelog format. Entries under [Unreleased] with Added/Changed/Fixed sections.”
- **PostToolUse on Edit of *.tex**: “Z spec conventions: use `\quad` for indentation, ZBOOL for booleans, bounded sets for ProB animation.”
- **PostToolUse on Bash** with git commands: “Session close protocol: git status, git add, bd sync, git commit, git push.”

11 Subagent Operations

SpawnSubagent

QuarryFrame

agentId? : *AGENTID*

sessionPhase = *spProcessing*
agentId? $\notin$ *activeSubagents*
#activeSubagents < *maxSubagents*
activeSubagents' = *activeSubagents* $\cup$ {*agentId?*}
sessionPhase' = *sessionPhase*
sessionId' = *sessionId*
permMode' = *permMode*
toolPhase' = *toolPhase*
currentTool' = *currentTool*
toolsThisTurn' = *toolsThisTurn*
context' = *context*
pendingPrompt' = *pendingPrompt*
pendingResponse' = *pendingResponse*

StopSubagent

QuarryFrame

agentId? : *AGENTID*

hookResult? : *HookDecision*

resultContext? : *CONTEXTCHUNK*

sessionPhase = *spProcessing*
agentId? $\in$ *activeSubagents*
hookResult? = *hdAllow*
activeSubagents' = *activeSubagents* $\setminus$ {*agentId?*}
context' = (1 .. *maxContext*) $\triangleleft$ (*context* $\frown$ {*resultContext?*})
sessionPhase' = *sessionPhase*
sessionId' = *sessionId*
permMode' = *permMode*
toolPhase' = *toolPhase*
currentTool' = *currentTool*
toolsThisTurn' = *toolsThisTurn*
pendingPrompt' = *pendingPrompt*
pendingResponse' = *pendingResponse*

12 Response and Stop

BeginResponse

QuarryFrame

response? : *RESPONSE*

sessionPhase = *spProcessing*
toolPhase = *tpNone*
activeSubagents = $\emptyset$
sessionPhase' = *spResponding*
pendingResponse' = {*response?*}
pendingPrompt' = $\emptyset$
sessionId' = *sessionId*
permMode' = *permMode*
toolPhase' = *tpNone*
currentTool' = $\emptyset$
toolsThisTurn' = *toolsThisTurn*
activeSubagents' = *activeSubagents*
context' = *context*

FinishResponse
QuarryFrame
hookResult? : *HookDecision*
responseContext? : *CONTEXTCHUNK*

sessionPhase = *spResponding*
hookResult? = *hdAllow*
sessionPhase' = *spIdle*
pendingResponse' = $\emptyset$
context' = $(1 \dots \text{maxContext}) \triangleleft (\text{context} \hat{\ } \langle \text{responseContext?} \rangle)$
toolsThisTurn' = 0
sessionId' = *sessionId*
permMode' = *permMode*
toolPhase' = *tpNone*
currentTool' = $\emptyset$
activeSubagents' = *activeSubagents*
pendingPrompt' = $\emptyset$

ForceContinue
QuarryFrame
hookResult? : *HookDecision*

sessionPhase = *spResponding*
hookResult? = *hdBlock*
sessionPhase' = *spProcessing*
pendingResponse' = $\emptyset$
sessionId' = *sessionId*
permMode' = *permMode*
toolPhase' = *tpNone*
currentTool' = $\emptyset$
toolsThisTurn' = *toolsThisTurn*
activeSubagents' = *activeSubagents*
context' = *context*
pendingPrompt' = *pendingPrompt*

13 Context Management — Compaction Safety

This is the critical section for quarry. Context compaction destroys conversation history. The **PreCompact** hook must capture session notes *before* the context is shrunk.

13.1 CaptureBeforeCompact

PreCompact hook fires. If compaction capture is enabled, quarry reads the transcript and ingests it as session notes into the project's **<repo>-captures** collection (as **session-<id8>**, attributed to the repo's ethos pin). This must happen before **CompactContext**.

<i>CaptureBeforeCompact</i> $\Delta State$

<i>sessionPhase</i> = <i>spIdle</i> <i>cfgCompaction</i> = <i>ztrue</i> <i>#context</i> > 0 <i>compactionSaved'</i> = <i>ztrue</i> <i>sessionPhase'</i> = <i>sessionPhase</i> <i>sessionId'</i> = <i>sessionId</i> <i>permMode'</i> = <i>permMode</i> <i>toolPhase'</i> = <i>toolPhase</i> <i>currentTool'</i> = <i>currentTool</i> <i>toolsThisTurn'</i> = <i>toolsThisTurn</i> <i>activeSubagents'</i> = <i>activeSubagents</i> <i>context'</i> = <i>context</i> <i>pendingPrompt'</i> = <i>pendingPrompt</i> <i>pendingResponse'</i> = <i>pendingResponse</i> <i>codebaseIndexed'</i> = <i>codebaseIndexed</i> <i>activeDb'</i> = <i>activeDb</i> <i>capturedUrls'</i> = <i>capturedUrls</i> <i>cfgSessionSync'</i> = <i>cfgSessionSync</i> <i>cfgWebFetch'</i> = <i>cfgWebFetch</i> <i>cfgCompaction'</i> = <i>cfgCompaction</i>

13.2 SkipCaptureBeforeCompact

Compaction capture is disabled. The **PreCompact** hook is a no-op. Session notes are not saved.

<i>SkipCaptureBeforeCompact</i> $\Xi State$
--

<i>sessionPhase</i> = <i>spIdle</i> <i>cfgCompaction</i> = <i>zfalse</i>

13.3 CompactContext

Context is shrunk. The **compactionSaved** flag records whether notes were captured. After compaction it resets to **zfalse** for the next potential compaction cycle.

CompactContext

Δ State

newLen? : $\mathbb{N}$

```
sessionPhase = spIdle
#context > 0
newLen? < #context
newLen? ≤ maxContext
context' = (1 .. newLen?) ◁ context
compactionSaved' = zfalse
sessionPhase' = sessionPhase
sessionId' = sessionId
permMode' = permMode
toolPhase' = toolPhase
currentTool' = currentTool
toolsThisTurn' = toolsThisTurn
activeSubagents' = activeSubagents
pendingPrompt' = pendingPrompt
pendingResponse' = pendingResponse
codebaseIndexed' = codebaseIndexed
activeDb' = activeDb
capturedUrls' = capturedUrls
cfgSessionSync' = cfgSessionSync
cfgWebFetch' = cfgWebFetch
cfgCompaction' = cfgCompaction
```

14 Session End

EndSession

Δ State

reason? : *SessionEndReason*

```
sessionPhase = spIdle
activeSubagents = ∅
sessionPhase' = spEnded
sessionId' = ∅
toolPhase' = tpNone
currentTool' = ∅
toolsThisTurn' = 0
activeSubagents' = ∅
context' = ⟨⟩
pendingPrompt' = ∅
pendingResponse' = ∅
permMode' = permMode
codebaseIndexed' = zfalse
activeDb' = ∅
capturedUrls' = ∅
compactionSaved' = zfalse
cfgSessionSync' = cfgSessionSync
cfgWebFetch' = cfgWebFetch
cfgCompaction' = cfgCompaction
```

15 System Invariants

1. **Codebase indexed when sync enabled:** if `cfgSessionSync = ztrue` and the session started via `StartSessionWithSync`, then `codebaseIndexed = ztrue` for the duration of the session.

2. **Capture config is immutable during session:** the `cfg*` flags are set at `Init` and preserved by all operations. They cannot change mid-session.
3. **WebFetch deduplication:** `CaptureWebFetch` requires `url? ∉ capturedUrls`. No URL is ingested twice in the same session.
4. **Active database consistency:** at most one database is active. `SwitchDatabase` replaces, does not accumulate.
5. **Compaction flag lifecycle:** `CaptureBeforeCompact` sets `compactionSaved` to `ztrue`. `CompactContext` resets it to `zfalse`. This tracks whether the most recent compaction was preceded by a capture.
6. **Clean session boundaries:** all quarry state (`indexed`, `activeDb`, `captures`, `compaction flag`) is cleared on `EndSession`.

Note on the compaction safety property: The Z spec does *not* enforce that capture must precede compaction — it is possible to compact without capturing (the operations are independent). This reflects reality: Claude Code fires the pre-compact hook before compaction, but the hook is non-blocking. The `compactionSaved` flag lets us *observe* whether the capture occurred, not *enforce* it. Enforcement is the hook system’s responsibility.

16 Hook Event Map

Hook	Matcher	Operation	Effect	Blk
SessionStart	*	StartSession- WithSync/NoSync	Auto-register sync	+ No
SessionStart	*	InjectKnowledgeHint	Project standards	No
PostToolUse	WebFetch	CaptureWebFetch	Ingest URL	No
PostToolUse	WebSearch [†]	CompleteToolSuccess (base)	Capture search digest	No
PostToolUse	Read [‡]	CompleteToolSuccess (base)	Capture read file (opt-in)	No
PostToolUse	Edit—Write	InjectKnowledgeHint	File-type hints	No
PostToolUse	Bash	InjectKnowledgeHint	Workflow hints	No
PostToolUse	quarry__use [†]	SwitchDatabase	Change active DB	No
PostToolUse	quarry__find [†]	SearchKnowledge	Inject results	No
PostToolUse	quarry__* [†]	(suppress output)	Format display	No
PreCompact	*	CaptureBefore- Compact	Save session notes	No
SubagentStop [‡]	*	StopSubagent (base)	Archive transcript, distill report	No [§]
SessionEnd	*	EndSession	Capture full transcript, clear state	No

[†]Conceptual matcher; actual regex is `mcp__(plugin__quarry(-dev)?_)?quarry(-proxy|-dev)?__.*` (see `plugin/hooks/hooks.json`).

[‡]The capture side-effect rides a base-layer operation; the quarry layer does not model it as a separate schema. `SubagentStop` files the subagent’s own final report as an `observation` in `memory-<handle>` when `agent_type` names a registered ethos identity (DES-055).

[§]Claude Code treats `SubagentStop` as a blocking hook (a non-zero exit or a `decision` field keeps the subagent running); the handler returns `{}` on every path, so it never blocks.

17 Implementation Validation

This section cross-references the Z specification against the current quarry implementation: the hook config, shell scripts in the `hooks` directory, and the Python handlers.

17.1 Hook Wiring Status

All seven capture handlers are implemented in `src/quarry/hooks.py` (session start, web fetch, pre-compact) and `src/quarry/hooks_agent.py` (session end, web search, read, subagent stop), dispatched by `quarry-hook <event>` (`src/quarry/_hook_entry.py`) and wired via shell scripts in `plugin/hooks/hooks.json`. Every handler is a thin daemon client: no hook loads the engine.

Component	Hook Event	Files	Status
Auto-register + sync	SessionStart	session-start.sh, session-sync.sh, hooks.py	Correct
Output formatting	PostToolUse (quarry)	suppress-output.sh	Correct
Web fetch capture	PostToolUse (WebFetch)	web-fetch.sh, hooks.py	Correct
Web search capture	PostToolUse (WebSearch)	web-search.sh, hooks_agent.py	Correct
Read capture (opt-in)	PostToolUse (Read)	post-read.sh, hooks_agent.py, read_capture.py	Correct
Compaction capture	PreCompact	pre-compact.sh, hooks.py	Correct
Session-end capture	SessionEnd	session-end.sh, hooks_agent.py	Correct
Subagent capture + distillation	SubagentStop	subagent-stop.sh, hooks_agent.py, subagent_capture.py	Correct

17.2 Not Yet Built

Z Operation	Hook Event	Effect	Effort
InjectKnowledgeHint	SessionStart	Project standards	Medium
InjectKnowledgeHint	PostToolUse Edit—Write	File-type hints	Medium
InjectKnowledgeHint	PostToolUse Bash	Workflow hints	Medium

Knowledge hint injection is the most significant unbuilt capability. It requires a hint resolution engine that maps the current activity (tool name, file path, command) to relevant quarry collections, plus careful scoping: hints must be short (1–3 sentences) to avoid flooding context.

An earlier attempt at convention hints via a `PreToolUse` hook accumulator (see ADR in `DESIGN.md`) was implemented and later removed (PR #113) in favor of a future semantic approach.

17.3 Coverage Summary

Z Operation	Implementation	Status
StartSessionWithSync	hooks.py + session-sync.sh	Correct
StartSessionNoSync	hooks.py (config check)	Correct
SubmitPrompt / RejectPrompt	(base)	Correct
Tool call operations	(base)	Correct
CaptureWebFetch	hooks.py + web-fetch.sh	Correct
SwitchDatabase	MCP tool	Correct
SearchKnowledge	MCP tool	Correct
InjectKnowledgeHint	—	Not built
CaptureBeforeCompact	hooks.py + pre-compact.sh	Correct
CompactContext	(base)	Correct
StopSubagent (capture side-effect)	hooks_agent.py + subagent-stop.sh	Correct
EndSession	hooks_agent.py + session-end.sh	Correct

The `EndSession` schema models the state clear; the wired handler additionally captures the full session transcript on every close, so a short session that never compacts still yields a durable capture. The `WebSearch` and `Read` captures ride the base `CompleteToolSuccess` operation and are listed in the hook event map above rather than as quarry-layer schemas.