

# REST API


Asst.Prof.Dr.Nuengwong Tuaycharoen

# Outline


1. REST API
2. API Development
3. API Security
4. OpenAPI with Swagger

# REST API

# The Client-Server Architecture



# The Architecture



# HTTP Request Methods

GET	Retrieve Resource
POST	Submit Resource
PUT/PATCH	Update Resource
DELETE	Delete/Destroy Resource

# RESTFUL API Standards

GET	/resources	Get resources
GET	/resources/1	Get resource with ID of 1
POST	/resources	Add a resource
PUT	/resources/1	Update resource with ID of 1
DELETE	/resources/1	Delete resource with ID of 1


# HTTP response status codes

<https://developer.mozilla.org/en-US/docs/Web/HTTP/Status>

- Informational responses (100–199)
- Successful responses (200–299)
  - 200 Success
  - 201 Created
  - 204 No Content
- Redirects (300–399)
  - 304 Not Modified
- Client errors (400–499)
  - 400 Bad Request
  - 401 Unauthorized
  - 404 Not Found
- Server errors (500–599)
  - 500 Internal Server Error



https://rapidapi.com/





# API Development

## Environment Setup [35 min]

1. Node.js [[nodejs.org](https://nodejs.org)]
2. VS Code [[code.visualstudio.com/download](https://code.visualstudio.com/download)]



[HOME](#) | [ABOUT](#) | [DOWNLOADS](#) | [DOCS](#) | [GET INVOLVED](#) | [SECURITY](#) | [CERTIFICATION](#) | [NEWS](#)



Node.js® is a JavaScript runtime built on [Chrome's V8 JavaScript engine](#).

#BlackLivesMatter

New security releases to be made available April 6, 2021

Download for Windows (x64)

14.16.0 LTS

Recommended For Most Users

15.13.0 Current

Latest Features

[Other Downloads](#) | [Changelog](#) | [API Docs](#)   [Other Downloads](#) | [Changelog](#) | [API Docs](#)

Or have a look at the [Long Term Support \(LTS\) schedule](#).



© OpenJS Foundation. All Rights Reserved. Portions of this site originally © Joyent.

Node.js is a trademark of Joyent, Inc. and is used with its permission. Please review the [Trademark List and Trademark Guidelines of the OpenJS Foundation](#).  
[Node.js Project Licensing Information](#).

[Report Node.js Issue](#) | [Report website issue](#) | [Get Help](#)



Thank you jscissr for being a Node.js contributor 9 contributions

Version 1.55 is now available! Read about the new features and fixes from March.

# Download Visual Studio Code

Free and built on open source. Integrated Git, debugging and extensions.



Windows

Windows 7, 8, 10

User Installer 64 bit 32 bit ARM  
System Installer 64 bit 32 bit ARM  
.zip 64 bit 32 bit ARM



.deb

Debian, Ubuntu

.rpm

Red Hat, Fedora, SUSE

.deb 64 bit ARM ARM 64  
.rpm 64 bit ARM ARM 64  
.tar.gz 64 bit ARM ARM 64


Snap Store



Mac

macOS 10.10+

.zip Universal Intel Chip Apple Silicon



# Install VS Code Extensions

1. Bracket Pair Colorizer
2. DotENV
3. ExpressSnippet
4. JavaScript (ES6) code snippets
5. Prettier - Code formatter
6. REST Client



FileEditSelectionViewGoRunTerminalHelp

Extension: REST Client - CU - Visual Studio Code

JS server2\_10.jsJS server.jsExtension: REST Client XJS server2\_8.jspackage-lock.json

REST cli

REST Client0.24.5

REST Client for Visual St...

Huachao Mao

51.8.0

Provides integration wit...

Salesforce

Install

Azure CLI Tools0.5.0

Tools for developing an...

Microsoft

Install

Simple REST C...1.4.2

Easy to examine your A...

Tino

Install

Generator for ...0.1.2

Generate a Java MicroPr...

MicroProfile Com...

Install

SP REST Client0.1.4

SharePoint REST Client f...

Sergei Sergeev

Install

httpYac - Rest ...2.4.0

Quickly and easily send ...

Andreas Weber

Install

reStructuredT...148.0.0

reStructuredText langua...

LeXtudio Inc.

Install

Bember REST ...0.21.1

Fork of "REST Client" for...

bemberas

Install

AWS CLI Confi...0.3.0

Quickly access the AWS ...

REST Clienthumao.rest-client

Huachao Mao

1,514,536

★★★★★

Repository

License

v0.24.5

REST Client for Visual Studio Code

Disable

Uninstall

This extension is enabled globally.

Details

Feature Contributions

Changelog

REST Client

Node CI

passing

chat

on github

VS Marketplace

v0.24.5

downloads

10309144

installs

1514451

rating

average: 4.95/5 (259 ratings)

REST Client allows you to send HTTP request and view the response in Visual Studio Code directly.

Main Features

Send/Cancel/Rerun HTTP request

in editor and view response in a separate pane with syntax highlight

Send GraphQL query

and author **GraphQL variables** in editor

PROBLEMS

OUTPUT

TERMINAL

DEBUG CONSOLE

1: powershell

[nodemon] 2.0.7

[nodemon] to restart at any time, enter `rs`

[nodemon] watching path(s): \*.\*

[nodemon] watching extensions: js,mjs,json

[nodemon] starting `node server.js`

Server running on port: 5000

Terminate batch job (Y/N)? y

PS C:\CU>

000

17

# Download the sample project

- [https://drive.google.com/file/d/1cwlyVacJFeCyvIwZVUZP61VEpUOte\\_Pd/view?usp=sharing](https://drive.google.com/file/d/1cwlyVacJFeCyvIwZVUZP61VEpUOte_Pd/view?usp=sharing)
- Unzip the file (i.e. C:\CU\)
- In VS Code, open the folder
- Run these commands in your VS Code terminal

1. `npm init`
2. `npm install -D nodemon`
3. `npm install express dotenv mongoose`
4. `npm start`

# route.rest: Route Structure

## GET/POST/PUT/DELETE

GET http://localhost:5000/subscribers

GET http://localhost:5000/subscribers/:id

POST http://localhost:5000/subscribers

DELETE http://localhost:5000/subscribers/:id

PATCH http://localhost:5000/subscribers/:id

# Package.json

```
{  
  "name": "firstapiproject",  
  "version": "1.0.0",  
  "main": "server.js",  
  "scripts": {  
    "devStart": "nodemon server.js",  
    "start": "nodemon server.js"  
  },  
  "author": "ohm",  
  "license": "ISC",  
  "dependencies": {  
    "express": "^4.18.1",  
    "mongoose": "^6.5.4"  
  },  
  "devDependencies": {  
    "dotenv": "^8.6.0",  
    "nodemon": "^1.19.4"  
  },  
  "description": ""  
}
```

# server.js

```
require('dotenv').config({path: './config.env'});
const express = require('express')
const app = express()
const mongoose = require('mongoose')
mongoose.set('strictQuery', true); // suppress deprecation warning
mongoose.connect(process.env.DATABASE_URL)

const db = mongoose.connection
db.on('error', (error) => console.error(error))
db.once('open', () => console.log('Connected to Database'))

app.use(express.json())

const subscribersRouter = require('./routes/subscribers')
app.use('/subscribers', subscribersRouter)

app.listen(process.env.PORT, () => console.log('Server Started'))
```

## config.env

```
NODE_ENV=development
```

```
PORT=5000
```

```
DATABASE_URL=mongodb+srv://ohm123:ohm123@traversymedia.o0h  
i2.mongodb.net/firstAPIproj?retryWrites=true&w=majority
```

## models/subscriber.js

```
const mongoose = require('mongoose')

const subscriberSchema = new mongoose.Schema({
  name: {
    type: String,
    required: true
  },
  subscribedToChannel: {
    type: String,
    required: true
  },
  subscribeDate: {
    type: Date,
    required: true,
    default: Date.now
  }
})

module.exports = mongoose.model('Subscriber', subscriberSchema)
```

## routes/subscribers.js (1/6)

```
const express = require('express')
const router = express.Router()
const Subscriber = require('../models/subscriber')

// Getting all
router.get('/', async (req, res) => {
  try {
    const subscribers = await Subscriber.find()
    res.json(subscribers)
  } catch (err) {
    res.status(500).json({ message: err.message })
  }
})
```



## routes/subscribers.js (2/6)

```
// Getting One
router.get('/:id', getSubscriber, (req, res) => {
  res.json(res.subscriber)
})
```

## routes/subscribers.js (3/6)

```
// Creating one
router.post('/', async (req, res) => {
  const subscriber = new Subscriber({
    name: req.body.name,
    subscribedToChannel: req.body.subscribedToChannel
  })
  try {
    const newSubscriber = await subscriber.save()
    res.status(201).json(newSubscriber)
  } catch (err) {
    res.status(400).json({ message: err.message })
  }
})
```

## routes/subscribers.js (4/6)

```
async function getSubscriber(req, res, next) {  
  let subscriber  
  try {  
    subscriber = await Subscriber.findById(req.params.id)  
    if (subscriber == null) {  
      return res.status(404).json({ message: 'Cannot find subscriber' })  
    }  
  } catch (err) {  
    return res.status(500).json({ message: err.message })  
  }  
  
  res.subscriber = subscriber  
  next()  
}  
  
module.exports = router
```

## routes/subscribers.js (5/6)

```
// Deleting One
router.delete('/:id', getSubscriber, async (req, res) => {
  try {
    await res.subscriber.remove()
    res.json({ message: 'Deleted Subscriber' })
  } catch (err) {
    res.status(500).json({ message: err.message })
  }
})
```

## routes/subscribers.js (6/6)

```
// Updating One
router.patch('/:id', getSubscriber, async (req, res) => {
  if (req.body.name !== null) {
    res.subscriber.name = req.body.name
  }
  if (req.body.subscribedToChannel !== null) {
    res.subscriber.subscribedToChannel = req.body.subscribedToChannel
  }
  try {
    const updatedSubscriber = await res.subscriber.save()
    res.json(updatedSubscriber)
  } catch (err) {
    res.status(400).json({ message: err.message })
  }
})
```

## route.rest : Call the API

```
GET http://localhost:5000/subscribers
```

```
###
```

```
GET http://localhost:5000/subscribers/609bd8671452242d88d36e36
```

```
###
```

```
POST http://localhost:5000/subscribers  
Content-Type: application/json
```

```
{  
  "name": "Ken Nakarin",  
  "subscribedToChannel": "THE STANDARD"  
}
```

```
###
```

```
DELETE http://localhost:5000/subscribers/609bd8671452242d88d36e36
```

```
###
```

```
PATCH http://localhost:5000/subscribers/609bd8671452242d88d36e36  
Content-Type: application/json
```

```
{  
  "name": "Jane Dawn",  
  "subscribedToChannel": "THE STANDARD"  
}
```

# API Security

# 1. Logout To Clear Token Cookie

```
//@desc      Log user out / clear cookie
//@route     GET /api/v1/auth/logout
//@access    Private


exports.logout=asyncHandler(async(req,res,next)=>{
  res.cookie('token','none',{
    expires: new Date(Date.now()+ 10*1000),
    httpOnly:true
  });

  res.status(200).json({
    success:true,
    data:{}
  });
});
```



## 2. Prevent NoSQL Injection & Sanitize Data

> npm i express-mongo-sanitize



```
//server.js
```

```
const  
mongoSanitize=require('expr  
ess-mongo-sanitize');
```

```
...
```

```
//Sanitize data
```

```
app.use(mongoSanitize());
```

POST

`{{URL}}/api/v1/auth/login`

Params

Authorization

Headers (11)

Body ●

Pre-request Script

Tests ●

Settings

☐ none☐ form-data☐ x-www-form-urlencoded☒ raw☐ binary☐ GraphQL

JSON



```
1 {  
2   "email": {"$gt": ""},  
3   "password": "123456"  
4 }
```

Body

Cookies (1)

Headers (16)

Test Results



Status: 404 Not Found

Pretty

Raw

Preview

Visualize

JSON



```
1 {  
2   "success": false,  
3   "error": "Resource Format ID not found with id of [object Object]"  
4 }
```

# 3. Security Headers

> npm i helmet

DevCamper API / Bootcamps / Get All Bootcamps

GET {{URL}}/api/v1/bootcamps

Params Authorization Headers (8) Body Pre-request Script Tests Settings

Query Params

KEY	VALUE	DESCRIPTION
X-Permitted-Cross-Domain-Policies	none	
Referrer-Policy	no-referrer	
X-XSS-Protection	0	
Content-Type	application/json; charset=utf-8	
Content-Length	8291	
ETag	W/"2063-05jG8xhtqRz9xEj+yAPHW3XYh+o"	
Date	Fri, 07 May 2021 08:51:10 GMT	
Connection	keep-alive	
Keep-Alive	timeout=5	

Status: 200 OK Time: 903 ms Size: 8.87 KB

```
//server.js

const helmet=require('helmet');

...

//Set security headers

app.use(helmet());
```

POST {{URL}}/api/v1/auth/register

# XSS : Cross-site Scripting

Params Headers (1) Body Pre-request Script Tests Settings

none form-data x-www-form-urlencoded raw binary GraphQL

```
1 {
2   "name": "Jane Doe",
3   "email": "jane@gmail.com",
4   "password": "123456",
5   "role": "publisher"
6 }
```

Environments

Mock Servers

Monitors

History

PUT Update Bootcamp  
DEL Delete Bootcamp  
GET Get Bootcamps by Distance  
PUT Upload photo  
Courses  
Authentication  
POST Register user  
POST Login  
GET Logout  
GET Get Me  
POST Forgot Password  
PUT Reset password  
PUT Update user's details  
PUT Update password  
Users

Search Postman

Create new Bootcamp

{{URL}}/api/v1/bootcamps

Send

Body Headers (12) Pre-request Script Tests Settings

Cookies

Beautify

```
1 {
2   "name": "ModernTech Bootcamp 2<script>alert(1)</script>",
3   "description": "Is coding your passion? Codemasters will give you the skills and the tools to become the best developer possible. We specialize in front end and full stack web development",
4   "website": "https://devcentral.com",
5   "phone": "(444) 444-4444",
6   "email": "enroll@devcentral.com",
7   "address": "45 Upper College Rd Kingston RI 02881",
8 }
```

Body Cookies (1) Headers (16) Test Results

Status: 201 Created Time: 1929 ms Size: 1.75 KB

Save Response

Pretty

Raw

Preview

Visualize

JSON

```
26 "jobGaurantee": false,
27 "acceptGi": true,
28 "_id": "6096010c5d4e320e00070000",
29 "name": "ModernTech Bootcamp 2<script>alert(1)</script>",
30 "description": "Is coding your passion? Codemasters will give you the skills and the tools to become the best developer possible. We specialize in front end and full stack web development",
31 "website": "https://devcentral.com",
32 "phone": "(444) 444-4444",
```

## 4. XSS Protection

>npm i xss-clean

The screenshot shows a REST client interface for a 'DevCamper API' endpoint. The request is a POST to 'api/v1/bootcamps' with a JSON body. The body contains a 'name' field with a malicious payload: 'ModernTech BC<script>alert(1)</script>'. This payload is highlighted with a red box. The response is a 201 status with a JSON body containing a 'name' field with the same malicious payload, also highlighted with a red box. The interface includes tabs for Params, Authorization, Headers, Body, Pre-request Script, Tests, and Settings. The Body tab is selected, and the response is shown in JSON format.

```
POST {{URL}}/api/v1/bootcamps

{
  "name": "ModernTech BC<script>alert(1)</script>",
  "description": "Is coding your passion? Codemasters will give you the best developer possible. We specialize in front end and full stack development.",
  "website": "https://devcentral.com",
  "phone": "(444) 444-4444",
  "email": "enroll@devcentral.com",
  "address": "45 Upper College Rd Kingston RI 02881"
}
```

```
{
  "jobGaurantee": false,
  "acceptGi": true,
  "id": "609503406b767eb6106b9eb4",
  "name": "ModernTech BC<script>alert(1)&lt;/script>",
  "description": "Is coding your passion? Codemasters will give you the best developer possible. We specialize in front end and full stack development.",
  "website": "https://devcentral.com",
  "phone": "(444) 444-4444",
}
```

server.js

```
const xss=require('xss-clean');
```

```
//Prevent XSS attacks
```


```
app.use(xss());
```

## 5. Rate Limiting & HPP

HPP: prevent HTTP parameter pollution attack

<http://www.aaa.com/search?p=cat&p=dog&p=pig&...>

> npm i express-rate-limit hpp




The screenshot shows a web browser's developer tools interface. The top bar indicates a GET request to `{{URL}}/api/v1/bootcamps`. The 'Params' tab is selected, showing 'Query Params'. Below this, a table with 'KEY' and 'VALUE' columns is visible. The 'Body' tab is also selected, showing a response with status 429 and the message 'Too many requests, please try again later.' The 'Headers' tab shows 20 headers, and the 'Test Results' tab is also visible.

server.js

```
const rateLimit=require('express-  
rate-limit');  
const hpp=require('hpp');  
...  
//Rate Limiting  
const limiter=rateLimit({  
  windowsMs:10*60*1000,//10 mins  
  max: 100  
});  
app.use(limiter);
```

## 6. CORS: Cross-Origin Resource Sharing

> npm i cors



`http://www.A.com`

`Access-Control-Allow-Origin: http://www.A.com`

`server.js`

```
const cors=require('cors');
```

```
...
```

```
//Enable CORS
```

```
app.use(cors());
```

<https://expressjs.com/en/resources/middleware/cors.html>

# Creating OpenAPI Document with Swagger




# OpenAPI

- A **standard, language-agnostic** interface to **REST APIs** which allows both **humans** and **computers** to **discover** and **understand** the capabilities of the service **without access** to source code documentation or through network traffic inspection.

# OpenAPI Specification

- Allow machines/tools to integrate with API
  - Allow humans to implement API code
  - Allow humans to read and generate API documentation and test case
- 
- OpenAPI = Specification
  - Swagger = tools

# OpenAPI Initiative: <https://www.openapis.org/>



- Info
- Tags
- Servers
- Search
- DELETE /pet/{petId}
- POST /pet/{petId}/uploadImage
- store ^
- GET /store/inventory
- POST /store/order
- GET /store/order/{orderId}
- DELETE /store/order/{orderId}
- user ^
- POST /user
- POST /user/createWithArray

```
148         - 'read:pets'
149         deprecated: true
150       '/pet/{petId}':
151         get:
152           tags:
153             - pet
154           summary: Find pet by ID
155           description: Returns a single pet
156           operationId: getPetById
157           parameters:
158             - name: petId
159               in: path
160               description: ID of pet to return
161               required: true
162               schema:
163                 type: integer
164                 format: int64
165           responses:
166             '200':
167               description: successful operation
168               content:
169                 application/json:
170                   schema:
171                     $ref: '#/components/schemas/Pet'
172                 application/xml:
173                   schema:
```

Read Only

Last Saved: 4:51:50 pm - May 12, 2021

VALID

- GET /pet/findByTags Finds Pets by tags
- GET /pet/{petId} Find pet by ID
- POST /pet/{petId} Updates a pet in the store with form data
- DELETE /pet/{petId} Deletes a pet
- POST /pet/{petId}/uploadImage uploads an image
- store Access to Petstore orders
- GET /store/inventory Returns pet inventories by status
- POST /store/order Place an order for a pet

# How to create OpenAPI document with swagger

■ > npm install --save swagger-jsdoc@6.0.0

■ > npm install --save swagger-ui-express

Ref: <https://www.npmjs.com/package/swagger-jsdoc>

■ Add swagger comment in your server.js and route files

Ref: <https://swagger.io/docs/specification/about/>

# server.js

```
const express =require('express');
const swaggerJsDoc = require('swagger-jsdoc');
const swaggerUI = require('swagger-ui-express');
```



```
const app = express();
```

```
const swaggerOptions={
  swaggerDefinition:{
    info: {
      title: 'Library API',
      version: '1.0.0'
    }
  },
  apis:['server.js'],
};
```

```
const swaggerDocs=swaggerJsDoc(swaggerOptions);
app.use('/api-docs', swaggerUI.serve, swaggerUI.setup(swaggerDocs));
```

```
/**
 * @swagger
 * /books:
 *   get:
 *     description: Get all books
 *     responses:
 *       200:
 *         description: Success
 *
 */

app.get('/books', (req, res)=>{
  ...
});
```



# Sample code

■ <https://drive.google.com/file/d/1cNbdCAiUTLNnfZqaqSbf-2ZDtHC9UmED/view?usp=sharing>


- 1. Unzip & open the folder with VS Code  
1. npm init
2. npm install -D nodemon
3. npm install **express** **dotenv** **mongoose**
4. npm install --save swagger-jsdoc@6.0.0
5. npm install --save swagger-ui-express
6. npm start
7. Go to: <http://localhost:5000/api-docs/>



# The (Simple) Client

# How to create the API Client

- > npm i unirest
- > npm i express-handlebars@6.0.6
- Create files:
  - client.js
  - views/main.hbs
  - views/layouts/main.hbs



## Subscribers

Name	Channel
Johny Walker	THE STANDARD
Singha Boonrod	BEER
Jane Sunny	THE STANDARD
Hen Ieken	BEER
San Migel	BEER
Ken Nakarin	THE STANDARD
Sake ADO	THE STANDARD
Rum Rasin	THE ALCOHOL
Bin II Wine	THE ALCOHOL
Sam Adams	BEER
Chang Chang	BEER
Jane Dawn	THE STANDARD
John Doe	CH7
John Doe	CH7
John Doe	CH7

## client.js (1/2)

```
const exphbs=require('express-handlebars')
const express = require('express')
const unirest = require('unirest')
const app = express()

//Handlebars
app.engine('.hbs',exphbs.engine({defaultLayout:'main',extname:'.hbs'}));
app.set('view engine','.hbs')

const PORT=3000;

app.get('/sub',async function(req,res){
  var Request = unirest.get('http://localhost:5000/subscribers').then((response) => {
    //console.log(response.body)
    var datafromserver = response.body
    res.render('main',{datafromserver})
  });
})

app.listen(PORT, () => console.log('Client Started'))
```

## views/main.hbs


```
<h1>Subscribers</h1>
<table border=1>
  <tr>
    <th>Name</th>
    <th>Channel</th>
  </tr>
  {{#each datafromserver}}
  <tr>
    <td>{{name}}</td>
    <td>{{subscribedToChannel}}</td>
  </tr>
  {{/each}}
</table>

</div>
```

## views/layouts/main.hbs

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="UTF-8">
    <meta name="viewport" content
    ="width=device-width, initial-
    scale=1.0">
    <title>Subscribers</title>
  </head>
  <body>
    {{{body}}}
  </body>
</html>
```

# The Results



## Subscribers

Name	Channel
Johny Walker	THE STANDARD
Singha Boonrod	BEER
Jane Sunny	THE STANDARD
Hen Ieken	BEER
San Migel	BEER
Ken Nakarin	THE STANDARD
Sake ADO	THE STANDARD

WEB APP  
SERVER

```
localhost:5000/subscribers
localhost:5000/subscribers
[{"_id":"609d1a45dccbee08808aa9f1","name":"Johny Walker","subscribedToChannel":"THE STANDARD","subscribeDate":"2021-05-13T12:23:33.965Z","__v":0}, {"_id":"609d1a5fdccbee08808aa9f2","name":"Singha Boonrod","subscribedToChannel":"BEER","subscribeDate":"2021-05-13T12:23:59.783Z","__v":0}, {"_id":"609d1a6cdccbee08808aa9f3","name":"Jane Sunny","subscribedToChannel":"THE STANDARD","subscribeDate":"2021-05-13T12:24:12.115Z","__v":0}, {"_id":"609d1a7cdccbee08808aa9f4","name":"Hen Ieken","subscribedToChannel":"BEER","subscribeDate":"2021-05-13T12:24:28.396Z","__v":0}, {"_id":"609d1a89dccbee08808aa9f5","name":"San Migel","subscribedToChannel":"BEER","subscribeDate":"2021-05-13T12:24:41.812Z","__v":0}, {"_id":"609d1a9edccbee08808aa9f6","name":"Ken Nakarin","subscribedToChannel":"THE STANDARD","subscribeDate":"2021-05-13T12:25:02.105Z","__v":0}, {"_id":"609d211cdccbee08808aa9f7","name":"Sake ADO","subscribedToChannel":"THE STANDARD","subscribeDate":"2021-05-13T12:52:44.818Z","__v":0}, {"_id":"609d21a27c574028bdcf29d33","name":"Rum Rasin","subscribedToChannel":"THE ALCOHOL","subscribeDate":"2021-05-13T12:54:58.496Z","__v":0}, {"_id":"609d21dc950916ddc23bd6","name":"San II Wine","subscribedToChannel":"THE ALCOHOL","subscribeDate":"2021-05-13T12:55:56.832Z","__v":0}, {"_id":"609d2240f6b78a49b88e9531","name":"Sam Adams","subscribedToChannel":"BEER","subscribeDate":"2021-05-13T12:57:36.801Z","__v":0}, {"_id":"609d226afdb81171e01dfac1","name":"Chang Chang","subscribedToChannel":"BEER","subscribeDate":"2021-05-13T12:58:18.513Z","__v":0}, {"_id":"60ac83de7e070f1d3c7ca418","name":"Jane Sunny","subscribedToChannel":"THE STANDARD","subscribeDate":"2021-05-13T12:58:18.513Z","__v":0}]]
```

# REST API's Assignment

1. Re-create a REST API from the sample code for a restaurant's member system.
2. Create your own database. It can be on mongodb.com. (Please do not use my MongoDB database.)
3. The data for a member includes name, address, telephone number, e-mail address, and member start date.
4. The REST API must be able to perform all CRUD operations with related methods (GET/POST/PUT/DELETE).
5. Record your demonstration of all methods with a route.rest file. The video clip should be less than 5 minutes in mp4 format.
6. Submit your Video clip to MCV.