

"Authenticate first, then authorize -- every request, every time."

MODULE 28

Spring Security Fundamentals

Learn core security concepts and implement robust authentication and authorization using Spring Security.





MODULE 28 OVERVIEW

Learn core security concepts and implement robust authentication and authorization using Spring Security.

Authenticate first, then authorize -- every request, every time. This module covers the security threat landscape, Spring Security's filter chain, JWT authentication, and role-based access control, then locks down the Northstar CRM API.

DURATION & LAB



5 Hours Theory

Authentication vs. authorization, the web security threat landscape, Spring Security architecture, JWT, and RBAC.



2 Hours Lab

Northstar CRM JWT and Roles: issue tokens on login and enforce AGENT/ADMIN access.



Scenario

Customer APIs cannot stay open on the network -- unauthenticated callers must be rejected automatically.

MODULE ARC



Understand Authn vs. Authz

Verifying identity is not the same as deciding what an identity is allowed to do.



Master the Filter Chain

SecurityFilterChain, JWT issuance and validation, and role-based endpoint matchers.



Build the Lab

Add login, JwtAuthenticationFilter, and AGENT/ADMIN matchers; prove the 401/403/200 matrix with MockMvc.

KEY TAKEAWAY Total time: 5 hours theory + 2 hours hands-on lab. You can now build secure, role-based Spring Boot applications that authenticate users and enforce access control at every endpoint.

Spring Security Overview

Comprehensive and Extensible Security for Spring Applications



Key Capabilities



Authentication

Verify the identity of users using a variety of mechanisms (username/password, JWT, OAuth2, SAML, LDAP, etc.)



Authorization

Control access to resources based on roles, permissions, or attributes.



Protection


Protects against common web attacks (CSRF, XSS, Clickjacking, Session Fixation, etc.).



Extensibility

Highly customizable to fit diverse application security requirements.

Spring Security Architecture



Security Benefits



Comprehensive

Covers authentication, authorization, protection, session management, and more.



Highly Customizable

Extensible architecture to meet unique business and security requirements.



Standards Based

Supports industry standards (OAuth2, OpenID Connect, SAML, JWT, etc.).



Production Ready

Widely used in enterprise applications with a strong security track record.



Seamless Integrations



Social Login
(Google, GitHub, etc.)



Spring Security provides a robust, flexible, and configurable security framework to build secure Spring applications with confidence.



WHY APPLICATION SECURITY MATTERS

Modern applications store and process sensitive data, handle critical business transactions, and are exposed to the internet.

Security is no longer optional -- it is essential.

THE IMPACT OF POOR SECURITY

Impact	What Happens
Data Breaches	Exposure of sensitive customer, financial, and business data.
Financial Loss	Direct losses, fraud, legal fees, and regulatory penalties.
Reputation Damage	Loss of customer trust and long-term brand impact.
Compliance Violations	Failure to meet security standards and industry regulations.
Service Disruption	Attacks can cause downtime and disrupt business operations.

KEY REASONS SECURITY MATTERS

- Protects Sensitive Data** — safeguards personal, financial, and business information from unauthorized access.
- Ensures Business Continuity** — prevents attacks that can disrupt services and impact availability.
- Builds Customer Trust** — secure applications show customers their data is safe.
- Meets Regulatory Requirements** — helps comply with standards like GDPR, PCI-DSS, HIPAA.
- Supports Secure Innovation** — security by design enables confident delivery of new features.

KEY TAKEAWAY Strong application security protects your users, your data, and your business -- today and in the future.



MODULE LEARNING OBJECTIVES

By the end of this module, you will be able to build secure, role-based Spring Boot applications with confidence.

Explain the Fundamentals — of application security and the difference between authentication and authorization.

Identify Common Threats — security threats and web application vulnerabilities and how they impact applications.

Describe the Architecture — Spring Security architecture and how the security filter chain processes requests.

Implement Authentication — using Spring Security and configure secure login and password encoding.

Implement Authorization — using role-based access control (RBAC) and secure application endpoints.

Understand JWT — JSON Web Token structure, and implement JWT-based authentication and token validation.

Apply Best Practices — and avoid common security mistakes in enterprise applications.

KEY TAKEAWAY Building confidence in secure Spring applications, protecting data and endpoints, and adhering to enterprise security standards.

AUTHENTICATION vs AUTHORIZATION

Two different but connected concepts that work together to secure your application.

	Authentication	Authorization
Question	"Who are you?"	"What are you allowed to do?"
Goal	Verify the identity of the user.	Determine what the user is allowed to access or do.
Examples	Login with username/password, MFA, social login, API key/token.	RBAC, permissions (READ/WRITE/DELETE), securing endpoints, feature access.
Outcome	User is authenticated -- the system knows who you are.	User is authorized -- the system knows what you can do.

HOW THEY WORK TOGETHER



KEY TAKEAWAY Authentication verifies who the user is. Authorization determines what the user can do. Both are essential for building secure and reliable applications.

Authentication vs Authorization



Two essential but different security concepts



AUTHENTICATION (AuthN)

Verifies who you are



Purpose: Confirms the identity of a user or system.



How it works:



1. User provides credentials (username/password, OTP, token, etc.)

2. System validates credentials

3. User is authenticated (identity is verified)



Examples:

- Login with username & password
- Multi-factor authentication (MFA)
- Biometric authentication

VS



AUTHORIZATION (AuthZ)

Determines what you can do



Purpose: Determines what an authenticated user is allowed to access or do.



How it works:



1. Authenticated user makes a request for a resource

2. System checks user's roles/permissions

3. Access is granted or denied



Examples:

- Access to /admin panel
- Submit / delete / update operation
- Access based on roles (ADMIN, USER, MANAGER)



In Simple Terms:



Authentication answers:
"Who are you?"



Authorization answers:
"What are you allowed to do?"



Both are essential for secure applications.

TRY IT YOURSELF -- EXERCISE 1: AUTHENTICATION VS AUTHORIZATION

Reinforces: separating 401 (not authenticated) from 403 (authenticated but forbidden) with real Northstar agent/admin examples.

STEP	WHAT TO DO
Goal	Explain 401 vs 403 with Northstar agent/admin examples -- in notes/authn-authz.md.
Define	Write authentication and authorization in one sentence each -- who you are vs. what you can do.
Reference row	Fill a 401/403/200 example matching: 401 = not authenticated, 403 = authenticated but forbidden, 200 = allowed.
Lab users	Record agent1 (AGENT) and admin1 (ADMIN) -- the two roles used throughout Lab 28.
Correlation != auth	lab-request-001 is operational metadata for tracing a request -- never treat it as a credential.
Reference	exercises/exercise-01-authn-vs-authz.md

Reference Matrix (fill this in)

Status	Meaning	CRM Example
401	Not authenticated	No/invalid Bearer token
403	Authenticated, forbidden	agent1 hits /api/admin/**
200	Allowed	agent1 GET CUS-1001

KEY TAKEAWAY TRY IT NOW Complete Exercise 1 before continuing -- define authn vs. authz, fill the 401/403/200 example, and record agent1/admin1 -- see exercises/exercise-01-authn-vs-authz.md.

SECURITY THREAT LANDSCAPE

Modern applications face a constantly evolving set of threats. Understanding the landscape is the first step to building secure, resilient applications.

COMMON THREAT CATEGORIES



1. Malicious Actors

Hackers, insiders, and cybercriminals targeting apps for financial gain or disruption.



2. Vulnerabilities

Flaws in code, frameworks, or dependencies exploitable for unauthorized access.



3. Social Eng.

Tricking users into revealing sensitive information (phishing, pretexting).



4. Data Exposure

Unauthorized access, leakage, or theft of data due to weak controls.



5. Service Disrupt.

Attacks aimed at making apps unavailable (denial-of-service).



6. Third-Party Risk

Risks from third-party APIs, libraries, and integrations with their own weaknesses.

POTENTIAL BUSINESS IMPACT

Financial Loss

Reputation Damage

Regulatory Penalties

Operational Disruption

Competitive Disadvantage

Security is not just an IT concern -- it's a business imperative. The threat landscape is dynamic; proactive awareness, secure coding, and defense-in-depth are essential.

KEY TAKEAWAY The threat landscape is dynamic and ever-changing. Proactive security awareness, secure coding, and defense-in-depth are essential.

Security Threat Landscape

A constantly evolving environment with increasing risks

The threat landscape continues to expand in complexity and scale. Organizations face more adversaries, more attack surfaces, and greater potential impact.



Key Insight

No organization is immune. Security must be proactive, layered, and continuously adaptive.

BY THE NUMBERS (2024)

	2,200+	Cyberattacks occur every day
	\$4.88M	Average cost of a data breach
	277 Days	Average time to identify a breach
	74%	YoY increase in ransomware attacks

MAJOR THREAT CATEGORIES



MALWARE

Malicious software designed to disrupt, damage, or gain unauthorized access.

Examples: Viruses, Worms, Trojans, Ransomware



PHISHING & SOCIAL ENGINEERING

Tricking users into revealing sensitive information or performing actions.

Examples: Spear phishing, Smishing, Vishing



CLOUD THREATS

Misconfigurations, insecure APIs, and weak access controls in cloud environments.

Examples: Data exposure, Shadow IT, Account hijacking



APPLICATION THREATS

Vulnerabilities in applications exploited to access or manipulate data and systems.

Examples: SQL Injection, XSS, Broken Authentication



INSIDER THREATS

Malicious or negligent insiders can cause data leaks, fraud, or system damage.

Examples: Privilege abuse, Data exfiltration



NETWORK THREATS

Attacks targeting network infrastructure to intercept, disrupt, or gain access.

Examples: DDoS, Man-in-the-Middle, Rogue APs



RANSOMWARE

Encrypts data and demands payment to restore access.

Examples: Data locking, Double extortion

COMMON ATTACK VECTORS



Email

Phishing emails, malicious attachments, unsafe links



Web

Malicious websites, drive-by downloads, malvertising



Removable Media

Infected USB drives and external devices



Credentials

Weak passwords, credential stuffing, brute force



Cloud Services

Misconfigurations, exposed storage, weak IAM

THREAT LANDSCAPE TRENDS



THREAT ACTOR MOTIVATIONS



Financial Gain

Profit through theft, fraud, or ransomware.



Espionage

Steal sensitive data for competitive or political advantage.



Hacktivism

Disrupt or expose organizations to promote a cause.



Disruption / Sabotage

Cause operational downtime or damage critical infrastructure.

BUSINESS IMPACT



Financial Loss

Direct losses, fines, legal costs, and recovery expenses.



Operational Disruption

Downtime, productivity loss, and service interruptions.



Reputational Damage

Loss of customer trust and brand value.



Compliance & Legal Risk

Regulatory penalties and lawsuits.

BEST PRACTICES TO STAY PROTECTED



Defense in Depth

Use multiple layers of security controls.



User Awareness

Train employees and promote security culture.



Continuous Monitoring

Detect and respond to threats in real-time.



Regular Assessments

Perform vulnerability scans and penetration tests.



Backup & Recovery

Maintain secure backups and test recovery plans.



Stay Updated

Keep systems, applications, and patches up to date.



The Bottom Line:

The threat landscape will continue to evolve. A proactive, risk-based, and people-centric security strategy is the key to resilience.

COMMON WEB SECURITY RISKS (1 OF 2)

Web applications are frequent targets for attackers. Understanding common risks helps us build secure and resilient applications.

Risk	Description	Example
1. Injection Attacks	Attackers inject malicious code via user input to manipulate queries or execute unauthorized commands.	SQL Injection, NoSQL Injection, Command Injection
2. Cross-Site Scripting (XSS)	Malicious scripts execute in the user's browser to steal cookies, session tokens, or deface pages.	Stored XSS, Reflected XSS, DOM-based XSS
3. Broken Authentication	Weak login mechanisms allow attackers to gain unauthorized access to accounts or data.	Weak passwords, session hijacking, credential stuffing
4. Broken Access Control	Improper restrictions allow users to access resources or perform actions outside their permissions.	IDOR (Insecure Direct Object Reference), privilege escalation

WHY THIS MATTERS FOR SPRING SECURITY

Spring Security directly addresses risks 3 and 4 (authentication and access control) -- risks 1, 2, and beyond require secure coding practices on top of the framework.

KEY TAKEAWAY No application is 100% secure, but awareness and best practices significantly reduce risk.

Common Web Security Risks

Understand the threats. Build secure applications.

Web applications are constantly targeted by attackers looking to exploit vulnerabilities. Awareness is the first step to prevention.



Key Insight

Most attacks exploit known vulnerabilities, weak configurations, or insecure code. Secure by design, defend in depth.

BY THE NUMBERS

	43%	Web attacks target small businesses
	94%	Applications have security vulnerabilities
	60 Days	Average time to patch a vulnerability
	\$4.88M	Average cost of a web application breach

TOP 10 COMMON WEB SECURITY RISKS (OWASP TOP 10 2021)

1 Broken Access Control



Restrictions on what authenticated users can do are not properly enforced.

Example: Regular user accessing admin functions.

2 Cryptographic Failures



Sensitive data is not properly protected in transit or at rest.

Example: Storing passwords in plain text.

3 Injection



Untrusted data is sent to an interpreter as part of a command or query.

Example: SQL Injection, NoSQL Injection.

4 Insecure Design



Security is missing or inadequate in the application design.

Example: Missing threat model or weak controls in design.

5 Security Misconfiguration



Security settings are not configured, hardened, or are left as defaults.

Example: Directory listing enabled, default accounts.

6 Vulnerable & Outdated Components



Using components with known vulnerabilities.

Example: Outdated libraries, frameworks, or plugins.

7 Identification & Authentication Failures



Weak authentication or session management allows attackers to impersonate users.

Example: Weak passwords, no MFA, session fixation.

8 Software & Data Integrity Failures



Code and data can be modified without detection.

Example: Unsigned updates, insecure CI/CD pipeline.

9 Security Logging & Monitoring Failures



Insufficient logging and monitoring prevents detection of attacks.

Example: Missing logs, no alerting, blind spots.

10 Server-Side Request Forgery (SSRF)



Attacker tricks the server into making requests to internal systems.

Example: Accessing internal APIs or cloud metadata.

COMMON ATTACK OUTCOMES



Data Breach



Account Takeover



Website Defacement



Financial Loss



Reputational Damage

BEST PRACTICES TO REDUCE RISKS

- ✓ Validate and sanitize all user input.
- ✓ Enforce strong authentication and authorization.
- ✓ Use HTTPS and encrypt sensitive data.
- ✓ Keep all components and libraries up to date.
- ✓ Apply least privilege and secure configurations.
- ✓ Implement logging, monitoring, and alerting.
- ✓ Perform regular security testing and code reviews.

WHO IS AT RISK?



Businesses of all sizes



Web application users



Cloud and SaaS platforms



E-commerce websites



Government and public services



THE BOTTOM LINE

Web security is everyone's responsibility—developers, operations, and business leaders. Secure applications protect data, users, and your organization's future.



Remember:

Attackers only need one vulnerability. You need strong controls everywhere.

COMMON WEB SECURITY RISKS (2 OF 2)

Risks 5-7, and the best practices that address all seven.

Risk	Description	Example
5. Security Misconfiguration	Unsafe default settings, open services, or verbose error messages expose sensitive information.	Default credentials, unnecessary services, verbose errors
6. Sensitive Data Exposure	Failure to protect sensitive data can lead to leakage of personal, financial, or business information.	Unencrypted data, weak encryption, data in logs
7. Cross-Site Request Forgery (CSRF)	Attackers trick authenticated users into performing unwanted actions on a web application.	Transfer funds, change email, update settings

BEST PRACTICES ACROSS ALL SEVEN RISKS

Validate & Sanitize Input

Strong Authn & Session Mgmt

Least Privilege Access

Keep Dependencies Updated

Monitor, Log, Respond

KEY TAKEAWAY No application is 100% secure, but awareness and best practices significantly reduce risk.

SPRING SECURITY OVERVIEW (1 OF 2)

Spring Security is the de-facto security framework for Spring-based applications, providing authentication, authorization, and protection against common attacks.

A powerful and highly customizable authentication and access-control framework, focused on providing both authentication and authorization to Java applications.

WHY SPRING SECURITY?

Industry Standard — widely adopted in enterprise applications.

Deep Spring Integration — works seamlessly with Spring Boot, Spring MVC, and Spring Cloud.

Comprehensive Security — covers authentication, authorization, CSRF protection, session management, and more.

Flexible & Powerful — easy to configure, yet highly customizable.

KEY FEATURES



Authentication

Supports multiple authentication mechanisms.



Authorization

Fine-grained access control using roles and permissions.



Protection

Built-in protection against common web threats.



Integration

Seamless integration with the Spring ecosystem.



Extensibility


Highly configurable and extensible architecture.

KEY TAKEAWAY Spring Security provides a robust, flexible, and extensible foundation for securing modern Java applications.

SPRING SECURITY OVERVIEW (2 OF 2)

How a request flows through Spring Security's modules on its way to your protected resource.

SPRING SECURITY MODULES (REQUEST FLOW)



AUTHENTICATION PROVIDERS

- UserDetailsService (in-memory, JDBC, JPA)
- DAO authentication provider
- LDAP
- OAuth2 / JWT

ACCESS DECISION MANAGERS

- Role-Based Access
- Voters
- Policies
- Permissions


KEY TAKEAWAY Spring Security provides a robust, flexible, and extensible foundation for securing modern Java applications.

SECURITY FILTER CHAIN (1 OF 2)

Spring Security uses a filter chain to intercept and process every incoming HTTP request.

A Security Filter Chain is an ordered list of filters that securitize requests and responses before they reach your application. Each filter has a specific responsibility and passes the request to the next filter.

DEFAULT FILTER CHAIN FLOW



KEY POINTS

- Every request goes through the filter chain, in a predefined order.
- Filters perform tasks like authentication, authorization, CSRF protection, session management.
- If a filter handles the request, the chain stops there; if not, the request continues to the next filter.

KEY TAKEAWAY The Security Filter Chain is the backbone of Spring Security, ensuring every request is authenticated, authorized, and protected before reaching your application.



Spring Security Filter Chain

A series of filters that process every HTTP request before it reaches your application



What is it?

Spring Security uses a chain of filters to secure web requests and responses.




Key Points

- ✓ Request passes through each filter in order
- ✓ Each filter has a specific security responsibility
- ✓ If a filter denies access, processing stops
- ✓ If all filters allow, the request reaches the application



Filter Chain Flow



Default Filter Order (High Level)

- 1 SecurityContextPersistenceFilter
- 2 UsernamePasswordAuthenticationFilter
- 3 BasicAuthenticationFilter
- 4 RequestCacheAwareFilter
- 5 SecurityContextHolderAwareRequestFilter
- 6 AnonymousAuthenticationFilter
- 7 SessionManagementFilter
- 8 ExceptionTranslationFilter
- 9 FilterSecurityInterceptor



Note

The actual list may vary based on your configuration and dependencies.



Key Benefits



Modular

Each filter has a single responsibility



Extensible

Add, remove, or customize filters easily



Secure by Default

Built-in protections against common attacks



Centralized Security

Consistent security for all requests

Legend

- Request Flow
- > Response Flow



The Filter Chain ensures every request is authenticated, authorized, and protected before it reaches your application.

SECURITY FILTER CHAIN (2 OF 2)

Common filters in the chain, their purpose, and how the chain processes a request end to end.

COMMON FILTERS IN THE CHAIN

Filter	Purpose
SecurityContextPersistenceFilter	Loads and stores the security context.
UsernamePasswordAuthenticationFilter	Authenticates username and password logins.
BasicAuthenticationFilter	Handles HTTP Basic Authentication.
CsrfFilter	Protects against Cross-Site Request Forgery.
ExceptionTranslationFilter	Converts security exceptions to HTTP responses.
FilterSecurityInterceptor	Enforces authorization rules for protected resources.

HOW IT WORKS

- 1. Request enters the application.
- 2. It passes through each filter in the chain, in order.
- 3. Each filter performs its task (authenticate, authorize, validate).
- 4. If a filter rejects the request, an error/redirect response is returned.
- 5. If all filters approve, the request reaches the target resource (controller/service).

KEY TAKEAWAY The Security Filter Chain is the backbone of Spring Security, ensuring every request is authenticated, authorized, and protected before reaching your application.

TRY IT YOURSELF -- EXERCISE 2: SECURITYFILTERCHAIN SKETCH

Reinforces: sketching Lab 28's four security components and route rules -- design only, no implementation yet.

STEP	WHAT TO DO
Goal	Sketch Lab 28's security components in notes/filter-chain.md without implementing them.
Components	List all four: SecurityFilterChain, JwtService, JwtAuthenticationFilter, CrmUserDetailsService.
Session policy	Write: session creation policy is STATELESS for JWT APIs -- no HttpSession is used.
Route rules	/api/auth/login permitAll(); /api/customers/** AGENT or ADMIN; /api/admin/** ADMIN only.
CSRF note	For stateless Bearer APIs, CSRF is typically disabled -- confirm the reasoning in the lab guide.
Reference	exercises/exercise-02-filter-chain-sketch.md

Four Components (fill notes/filter-chain.md)


```
SecurityFilterChain    -- authorizes HTTP requests
JwtService            -- issues and parses tokens
JwtAuthenticationFilter -- reads the Bearer header
CrmUserDetailsService -- loads lab users/roles
```

KEY TAKEAWAY TRY IT NOW Complete Exercise 2 before continuing -- list the four components, note STATELESS, and write the three route rules -- see exercises/exercise-02-filter-chain-sketch.md.

REQUEST PROCESSING FLOW (1 OF 2)

Spring Security intercepts every HTTP request through the Security Filter Chain and ensures only authenticated and authorized requests reach your application.

Spring Security sits in front of your application. It authenticates the user, authorizes the request, and protects your resources.




KEY TAKEAWAY The request processing flow ensures that every request is authenticated, authorized, and validated before reaching your application -- keeping your data and users secure.



Spring Security Request Processing Flow

How an HTTP request is secured and processed in a Spring application



Flow Explanation



- | 1 HTTP Request | 2 SecurityContext PersistenceFilter | 3 Authentication Filter | 4 Authorization Filter | 5 Exception Translation Filter | 6 FilterSecurity Interceptor | 7 Application | 8 Response |
|--|--|--|---|--|--|--|---|
| Client sends an HTTP request to the application. | Loads the security context from session or creates a new one for this request. | Validates the user's credentials (if needed) and stores the Authentication in SecurityContext. | Verifies if the user has sufficient roles/permissions to access the requested resource. | Converts security exceptions into proper HTTP responses (401 / 403). | Performs the final access decision before the request is allowed to reach the application. | If authorized, the request is processed by controllers / services. | On success, a normal response is returned. On failure, an error response is sent. |



Key Benefits



Centralized security for all requests



Consistent authentication and authorization



Robust exception handling



Extensible and highly customizable



Protects resources before they reach your application

REQUEST PROCESSING FLOW (2 OF 2)

What happens when authentication or authorization fails, and the filters most commonly involved.

WHEN THINGS GO WRONG

Failure	Result
Authentication Failed	User is not authenticated. Return 401 Unauthorized (or redirect to login for browser apps).
Access Denied	User is authenticated but not authorized. Return 403 Forbidden.

EXAMPLE FILTERS IN THE CHAIN

- SecurityContextPersistenceFilter** — loads security context.
- UsernamePasswordAuthenticationFilter** — authenticates user credentials.
- AuthorizationFilter** — checks access permissions.
- ExceptionHandler** — handles exceptions and errors.
- FilterSecurityInterceptor** — final authorization decision.

WHAT HAPPENS AT EACH STEP

- 1. Request enters the Security Filter Chain.
- 2. User identity is verified (username/password or token validation).
- 3. User roles/permissions are checked against the requested resource.
- 4. Additional security checks are performed (CSRF, session, headers, etc.).
- 5. If everything is valid, the request reaches your application; the response is sent back to the client.

KEY TAKEAWAY The request processing flow ensures that every request is authenticated, authorized, and validated before reaching your application -- keeping your data and users secure.

USER AUTHENTICATION WORKFLOW (1 OF 2)

Spring Security provides a secure and flexible authentication process to verify the identity of users before granting access.

Authentication answers the question "Who are you?" Only authenticated users can access protected resources.



KEY COMPONENTS

AuthenticationFilter — processes login requests and creates authentication tokens.

AuthenticationManager — coordinates authentication providers to validate the token.


UserDetailsService — loads user-specific data (username, password hash, roles).

PasswordEncoder — encodes and verifies passwords securely.


KEY TAKEAWAY On success, an authenticated Authentication object is created and stored in the SecurityContext -- the user is logged in and can access protected resources.

Spring Security Authentication Flow

How a user is authenticated in a Spring Security based application



DETAILED FLOW DIAGRAM



✓ AUTHENTICATION SUCCESS

- Authentication object is stored in SecurityContextHolder.
- SecurityContext is persisted in HttpSession (or returned as JWT).
- User is now authenticated and can access protected resources.

✗ AUTHENTICATION FAILURE

- Provider throws AuthenticationException (subclass).
- Exception is caught by the filter.
- AuthenticationFailureHandler is invoked.
- User is redirected back to login page with error message.

COMMON AUTHENTICATION PROVIDERS

- DaoAuthenticationProvider – Uses UserDetailsService and PasswordEncoder.
- LdapAuthenticationProvider – Authenticates against LDAP directory.
- JwtAuthenticationProvider – Validates JWT tokens.
- CustomAuthenticationProvider – Custom logic.

FILTER CHAIN (Simplified Order)



KEY BENEFITS

- Centralized security
- Pluggable authentication providers
- Support for multiple auth mechanisms
- Secure by default
- Extensible and customizable

EXAMPLE CONFIGURATION

```




@Bean
public SecurityFilterChain filterChain(HttpSecurity http) throws Exception {
    http
        .authorizeHttpRequests(auth -> auth
            .requestMatchers("/login", "/public/**").permitAll()
            .anyRequest().authenticated())
        .formLogin(form -> form
            .loginPage("/login").permitAll())
        .logout(logout -> logout.permitAll());
    return http.build();
}
    
```

💡 BEST PRACTICES

- Use strong password encoding (BCrypt/Argon2)
- Always use HTTPS
- Protect against brute force attacks
- Invalidate session on logout
- Follow the principle of least privilege
- Keep dependencies up to date



How a user is authenticated in a Spring application



Spring Security ensures a robust, flexible, and extensible authentication process for enterprise applications.

USER AUTHENTICATION WORKFLOW (2 OF 2)

Authentication outcomes, and the security best practices that keep the workflow safe.

SEQUENCE (WHO TALKS TO WHOM)

#	Step
1	User submits login -> Filter Chain.
2-3	Filter Chain -> AuthenticationFilter -> AuthenticationManager: authenticate.
4-6	AuthenticationManager -> UserDetailsService -> Database: load user.
7	AuthenticationManager validates the password.
8-9	Success: SecurityContext is set; response returned to user.

AUTHENTICATION OUTCOMES

Success — SecurityContext updated, user authenticated, access granted to protected resources.

Failure — invalid credentials, authentication fails, 401 Unauthorized, user remains unauthenticated.

BEST PRACTICE

Strong Password Policies

Use PasswordEncoder (BCrypt)

Never Store Plain Text

Account Lockout on Failures


Enable HTTPS

KEY TAKEAWAY Best practice: always use strong password policies, PasswordEncoder (e.g. BCrypt), never store plain text passwords, implement account lockout on failures, and enable HTTPS.

LOGIN PROCESS

Spring Security handles the login process to authenticate users and establish a secure session (or issue a token) for accessing the application.

Purpose: verify user credentials and create an authenticated session (or JWT) so the user can access protected resources.



OUTCOMES

Success — user is authenticated; SecurityContext (or JWT) is created; user is granted access.

Failure — invalid username or password; authentication fails; error is shown; user remains unauthenticated.

BEST PRACTICES



- Use strong password policies; use PasswordEncoder (e.g. BCrypt).
- Do not reveal whether the username exists (generic error messages).
- Implement account lockout on repeated failures.
- Always use HTTPS for login.

KEY TAKEAWAY Verify credentials, encode passwords, and never leak which field was wrong -- a secure login process is the front door to your entire application.



Spring Security Login Process

How a user logs in to a Spring application




Spring Security provides a secure and configurable login mechanism to protect your applications and user data.

PASSWORD ENCODING (1 OF 2)

Spring Security never stores plain text passwords. It encodes passwords using a secure hashing algorithm with a salt to protect user credentials.

Purpose: protect user passwords even if the database is compromised; store passwords in a one-way, irreversible format; salt and hash make each password unique and secure.



HOW PASSWORD ENCODING WORKS


- Input password -> a random salt is generated for each password.
- Hashing algorithm (BCrypt, Argon2, PBKDF2, ...) combines password + salt.
- Same password + different salt = different encoded password.

KEY TAKEAWAY Password encoding is the first line of defense for protecting user credentials. Always encode, never store plain text.



Spring Security Password Encoding

Never store plaintext passwords – always encode (hash) them



Why Password Encoding?

- Protects users if the database is compromised
- Prevents rainbow table attacks
- Adds salt and multiple iterations to increase security
- One-way – cannot be reversed to get the original password

How a Secure Hash is Created



Recommended Algorithms

- bcrypt:** Adaptive, widely used, built-in in Spring Security
- Argon2:** Memory-hard, modern, highly secure
- PBKDF2:** Standard based, supported in all environments

Spring Security Configuration

```
@Bean
public PasswordEncoder passwordEncoder() {
    return new BCryptPasswordEncoder(10);
}
```

// 10 = strength (log rounds)
// Higher value = more secure
// but slower



Always encode passwords before storing



Use strong algorithms like bcrypt or Argon2



Use unique salt (handled automatically)



Use an appropriate strength (e.g., bcrypt 10 or higher)



Never store or log raw passwords or encoded passwords in plaintext logs



Password Encoding is your first line of defense. Spring Security makes it easy to implement strong, robust, and secure password storage.

PASSWORD ENCODING (2 OF 2)

Choosing a PasswordEncoder, best practices, and a working BCryptPasswordEncoder example.

PASSWORD ENCODERS IN SPRING SECURITY

Encoder	Strength	Use Case
BCryptPasswordEncoder	Strong	Recommended (default choice).
Pbkdf2PasswordEncoder	Strong	Good for compliance requirements.
Argon2PasswordEncoder	Very Strong	Best for new applications.
NoOpPasswordEncoder	Very Weak	Testing only -- never production.

SecurityConfig.java

```
@Bean
public PasswordEncoder passwordEncoder() {
    return new BCryptPasswordEncoder(10);
    // 10 = strength (log rounds)
}
```

BEST PRACTICES

- Always use a strong PasswordEncoder like BCrypt (the default choice).
- Never store or log plain text passwords, in code, notes, or screenshots.
- Use the same PasswordEncoder for encoding and matching.
- Ensure an adequate work factor (strength) for better security; a unique salt per password is handled automatically by Spring Security.

KEY TAKEAWAY Never use MD5, SHA-1, or NoOpPasswordEncoder for passwords in production -- always use a modern, adaptive hashing algorithm like BCrypt or Argon2.

ROLE-BASED ACCESS CONTROL (RBAC) (1 OF 2)

RBAC restricts system access based on the roles assigned to users. Users inherit permissions through roles, simplifying access management and enforcing least privilege.

RBAC is an authorization model that grants permissions to users based on their roles. Roles are assigned permissions, and users are assigned roles.



BENEFITS OF RBAC



Improved Security

Users have only the access they need.



Simplified Management

Manage access by roles, not individual permissions.



Scalability

Easily add new users and roles as the system grows.



Auditability

Clear visibility of who has access to what and why.

KEY TAKEAWAY RBAC centralizes permission management through roles, improving security, simplifying administration, and ensuring users get the right access to the right resources.



Spring Security Role-Based Access Control (RBAC)

Control access to resources based on user roles and permissions



What is RBAC?

RBAC restricts system access based on the roles assigned to a user. Roles are granted permissions to access specific resources or perform actions.



Key Benefits

- ✓ Simplifies permission management
- ✓ Enforces least privilege access
- ✓ Scales easily as application grows
- ✓ Improves security and compliance
- ✓ Centralized role administration




Common Use Cases


- Admin dashboards
- Multi-tenant applications
- Enterprise systems
- API access control



How It Works



RBAC Model



Example Configuration

```
@PreAuthorize("hasRole('ADMIN')")
@GetMapping("/admin/**")
public String adminEndpoint() { ... }

@PreAuthorize("hasAnyRole('ADMIN', 'MANAGER')")
@GetMapping("/reports/**")
public String reports() { ... }

@PreAuthorize("hasRole('VIEWER')")
@GetMapping("/dashboard/**")
public String dashboard() { ... }
```


Access Matrix (Example)

Resource / Action	ADMIN	MANAGER	VIEWER
User Management	✓	✗	✗
Reports (Read)	✓	✓	✓
Reports (Export)	✓	✓	✗
Dashboard (View)	✓	✓	✓
Settings	✓	✗	✗

Best Practices

- ✓ Use meaningful and consistent role names
- ✓ Grant minimum permissions (least privilege)
- ✓ Avoid hardcoding roles in code
- ✓ Use role hierarchy if roles inherit permissions
- ✓ Regularly review roles and permissions

Role Hierarchy (Example)



RBAC in Spring Security helps you build secure, maintainable, and scalable applications by managing access through roles and permissions.

ROLE-BASED ACCESS CONTROL (RBAC) (2 OF 2)

A worked example of user -> role -> permission mapping, how the access decision works, and best practices.

EXAMPLE: USER -> ROLE -> PERMISSION

User	Role	Permission
agent1	AGENT	Read/write CUS-1001, CUS-1002 via /api/customers/**
admin1	ADMIN	All AGENT permissions + /api/admin/** access

HOW THE ACCESS DECISION WORKS

- 1. User attempts to access a protected resource.
- 2. Is the user authenticated? No -> Access Denied (401).
- 3. Does the user's role satisfy the required permission? No -> Access Denied (403).
- 4. Yes to both -> Access Granted; resource is returned.

RBAC BEST PRACTICES

- **Design Roles Around Business Functions** — not technical permissions.
- **Follow the Principle of Least Privilege** — grant the minimum permissions required.
- **Use Role Hierarchies (if needed)** — avoid duplication of permissions.
- **Review Roles and Permissions Regularly** — remove unused roles and outdated permissions.

KEY TAKEAWAY RBAC centralizes permission management through roles, improving security, simplifying administration, and ensuring users get the right access to the right resources.

USER ROLES AND PERMISSIONS

Roles group users with similar responsibilities. Permissions define what actions can be performed on specific resources.

COMMON USER ROLES

Role	Description
ADMIN	Full system access; can manage users, roles, and all resources.
MANAGER	Can manage data and processes within their domain.
USER / AGENT	Can access and manage assigned resources.
AUDITOR	Read-only access for monitoring and reporting.
GUEST	Limited access to public or non-sensitive resources.

EXAMPLE PERMISSIONS

Permission	Allows
VIEW / READ	Viewing dashboards, reports, or records.
CREATE	Creating new data (e.g. a new customer).
UPDATE	Modifying existing data or settings.
DELETE	Removing records.
MANAGE	Managing users, roles, and permissions.

BEST PRACTICES

Define Roles by Business Function

Grant Minimum Permissions (Least Privilege)

Review Regularly

Avoid Hardcoding Roles

Use Meaningful Names

KEY TAKEAWAY Proper use of roles and permissions ensures secure, scalable, and maintainable access control. Assign the right roles, grant the right permissions, and review regularly.



Roles and Permissions in Spring Security

Roles group permissions. Permissions grant access to specific resources and actions.

Key Concepts



Role

A role is a collection of permissions that defines what a user can do.




Permission

A permission represents a specific operation allowed on a resource.

Why Use Roles?

- ✓ Simplifies permission management
- ✓ Enforces separation of duties
- ✓ Improves maintainability
- ✓ Enhances security and compliance
- ✓ Easier to scale as application grows

How Roles and Permissions Work Together



Example Roles and Their Permissions



ROLE_ADMIN

- user:create, user:read, user:update, user:delete
- report:read, report:export
- dashboard:view, settings:manage



ROLE_MANAGER

- user:read, user:update
- report:read, report:export
- dashboard:view




ROLE_VIEWER

- report:read
- dashboard:view

Access Matrix (Example)

Resource / Action	ADMIN	MANAGER	VIEWER
User Management (Create)	✓	✗	✗
User Management (Read)	✓	✓	✓
User Management (Update)	✓	✓	✗
User Management (Delete)	✓	✗	✗
Reports (Read)	✓	✓	✓
Reports (Export)	✓	✓	✗
Dashboard (View)	✓	✓	✓
Settings (Manage)	✓	✗	✗

How It Works (Example Flow)



Role vs Permission

Role (What)	Permission (How)
High-level grouping	Fine-grained access
Assigned to users	Applied to resources/actions
Changes infrequent	Changes more frequent
Example: ROLE_ADMIN	Example: user:read



Use Roles to organize permissions. Use Permissions to secure resources.



Least Privilege Access



Stronger Security Posture



Better Governance & Compliance



Scalable & Maintainable Access Control

SECURING ENDPOINTS (1 OF 2)

Spring Security lets you protect application endpoints (URLs/APIs) so that only authenticated and authorized users can access them.

Purpose: protect sensitive endpoints from unauthorized access, enforce authentication and authorization rules, and apply the principle of least privilege.



SecurityConfig.java (matcher-based endpoint protection -- Lab 28 pattern)

```
@Bean
SecurityFilterChain filterChain(HttpSecurity http) throws Exception {
    http.csrf(csrf -> csrf.disable())
        .sessionManagement(sm -> sm.sessionCreationPolicy(SessionCreationPolicy.STATELESS))
        .authorizeHttpRequests(auth -> auth
            .requestMatchers("/api/auth/login", "/actuator/health").permitAll()
            .requestMatchers("/api/admin/**").hasRole("ADMIN")
            .requestMatchers("/api/customers/**").hasAnyRole("AGENT", "ADMIN")
            .anyRequest().authenticated())
        .addFilterBefore(jwtFilter, UsernamePasswordAuthenticationFilter.class);
    return http.build();
}
```

KEY TAKEAWAY Default deny: allow only what is necessary. Authenticate first, then authorize.



Securing Endpoints in Spring Security

Control who can access your endpoints and what actions they can perform

Ways to Secure Endpoints



1. URL/Request Matchers
Secure endpoints based on HTTP method and URL path patterns.



2. Role-Based Access
Restrict access using user roles (RBAC).




3. Authority-Based Access
Use fine-grained authorities (permissions) for access control.



4. Method-Level Security
Secure individual controller methods with annotations.

How a Secured Endpoint Request is Processed



Common Endpoint Security Examples



Public Endpoints (No Auth Required)

- GET /api/public/**
- POST /api/auth/login
- POST /api/auth/register



Authenticated Users

- GET /api/profile
- PUT /api/profile



Role-Based Access

- GET /api/admin/** (ROLE_ADMIN)
- GET /api/manager/** (ROLE_MANAGER)



Authority-Based Access

- DELETE /api/users/** (user:delete)
- POST /api/reports/export (report:export)

Example: URL-Based Security Configuration

```
1 @Bean
2 SecurityFilterChain securityFilterChain(HttpSecurity http) throws Exception {
3     http
4         .authorizeHttpRequests(auth -> auth
5             .requestMatchers("/api/public/**", "/api/auth/**").permitAll()
6             .requestMatchers(HttpMethod.GET, "/api/profile").authenticated()
7             .requestMatchers("/api/admin/**").hasRole("ADMIN")
8             .anyRequest().denyAll()
9         )
10        .formLogin(Customizer.withDefaults())
11        .csrf(csrf -> csrf.disable());
12    return http.build();
13 }
```

Public endpoints accessible to all

Authenticated users only

Only users with ROLE_ADMIN

All other requests are denied

Example: Method-Level Security



```
@PreAuthorize("hasRole('ADMIN')")
@GetMapping("/admin/users")
public List<User> getAllUsers() { ... }
```

Only ADMIN role can access



```
@PreAuthorize("hasAuthority('user:delete')")
@DeleteMapping("/users/{id}")
public void deleteUser(@PathVariable Long id) { ... }
```

User must have specific authority



```
@PreAuthorize("isAuthenticated()")
@GetMapping("/profile")
public Profile getProfile() { ... }
```

Any authenticated user can access

Best Practices



Follow the Principle of Least Privilege
Grant only the permissions required.



Secure by Default
Deny all requests by default and explicitly allow needed ones.



Use Roles for Broad Access, Authorities for Fine-Grained Access
Roles for modules, authorities for operations.



Centralize Security Configuration
Keep rules in one place for consistency and maintainability.



Regularly Review Access Rules
Remove unused permissions and review role assignments.



Secure your endpoints by combining authentication, authorization, and best practices to protect your application and data.

SECURING ENDPOINTS (2 OF 2)

Endpoint protection example, method-level security annotations, and techniques to secure endpoints.

EXAMPLE: ENDPOINT PROTECTION (LAB 28)

Endpoint	Method	Access Rule	Role
/api/auth/login	POST	permitAll()	None (public)
/api/customers/**	GET/POST	hasAnyRole(...)	AGENT or ADMIN
/api/admin/**	GET	hasRole('ADMIN')	ADMIN
anyRequest()	*	authenticated()	Any logged-in user

Method-Level Security (Alternative)

```
@RestController
@RequestMapping("/api/admin")
public class AdminController {
    @GetMapping("/customers")
    @PreAuthorize("hasRole('ADMIN')")
    public List<CustomerResponse> adminList() {
        // ...
    }
}
```

TECHNIQUES TO SECURE ENDPOINTS



KEY TAKEAWAY Securing endpoints ensures users can access only the resources they are allowed to. Authenticate first, then authorize.

WHAT IS JWT? (1 OF 2)

JWT (JSON Web Token) is a compact, URL-safe token format used to securely transmit information between parties as a JSON object.

Commonly used for authentication and authorization in stateless applications (e.g. Spring Security with REST APIs).

WHY USE JWT?

Stateless — no server-side session storage required.

Scalable — works across distributed systems and microservices.

Secure — digitally signed to prevent tampering.

Compact — small in size and easy to transmit (e.g. in HTTP headers).

HOW JWT WORKS



HTTP Header Example

```
Authorization: Bearer <JWT_TOKEN>
```

KEY TAKEAWAY JWT is a secure and efficient way to transmit authentication and authorization information between client and server -- stateless, scalable, and widely used in modern REST APIs.



JWT Structure

A JWT is made of three parts separated by dots (.)

HEADER

```
{
  "alg": "HS256",
  "typ": "JWT"
}
```

•

PAYLOAD (CLAIMS)

```
{
  "sub": "1234567890",
  "name": "Alice",
  "role": "ADMIN",
  "exp": 1715133600
}
```

•

SIGNATURE

```
HMACSHA256(
  base64UrlEncode(header)
  + "." +
  base64UrlEncode(payload),
  secret)
```

eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.
eyJzdWIiOiIxMjMONTY3ODkwIiwibmFtZSI6IkpSaWNIiwicm9sZSI6IkpETUUNJiwiZXhwIjoxNzE1MTMzMjAwfQ.
Sf1KxwRJSMeKKF2QT4fwpMeJf36P0k6yJV_adQssw5c

1 Header – Metadata about the token

2 Payload – Contains the claims

3 Signature – Verifies integrity & authenticity

Common JWT Claims			
	Registered Claims		Custom Claims (Example)
iss	Issuer of the token	name	Alice
sub	Subject (user id)	role	ADMIN
aud	Audience	email	alice@example.com
exp	Expiration time	permissions	["read:users", "write:users"]
nbf	Not before (valid from)	tenantId	tenant_123
iat	Issued at		
jti	JWT ID (unique identifier)		

How JWT Works

```
graph LR; subgraph "Authentication Phase"; C1[Client] -- "User logs in with username/password" --> AS[Authentication Server]; AS -- "Server validates credentials" --> T[JWT Token]; T -- "If valid, server generates and signs a JWT" --> C2[Client]; C2 -- "JWT is stored on the client (e.g., localStorage, cookie)" --> C2; end; subgraph "Resource Access Phase"; C2 -- "Client sends JWT in Authorization header" --> RS[Resource Server]; RS -- "Server verifies the JWT signature and validates claims" --> V[Valid Token]; RS -- "Server verifies the JWT signature and validates claims" --> I[Invalid Token]; V -- "Access is granted to the requested resource" --> End(( )); I -- "Access is denied (401 Unauthorized)" --> End; end;
```

The diagram illustrates the JWT (JSON Web Token) workflow, divided into two main phases: Authentication and Resource Access.

Authentication Phase:

- Client:** User logs in with username/password.
- Authentication Server:** Server validates credentials.
- JWT (Token):** If valid, server generates and signs a JWT.
- Client:** JWT is stored on the client (e.g., localStorage, cookie).

Resource Access Phase:

- Client:** Client sends JWT in Authorization header (`Authorization: Bearer <token>`).
- Resource Server:** Server verifies the JWT signature and validates claims.
- Outcomes:**
 - Valid Token:** Access is granted to the requested resource (indicated by a green checkmark).
 - Invalid Token:** Access is denied (401 Unauthorized) (indicated by a red X).

Key Characteristics

 Stateless No server-side session required	 Secure Signed (and optionally encrypted)	 Compact Small size, ideal for HTTP transmission	 Interoperable Works across different platforms and languages
--	---	--	---

The diagram illustrates five common use cases for OAuth 2.0, each represented by an icon and a description:

- Authentication**: User login and identity verification (Icon: Shield with a checkmark).
- Authorization**: Role/permission based access (Icon: Briefcase with a person silhouette).
- API Security**: Secure APIs between client and server (Icon: Cloud with a keyhole).
- Single Sign-On (SSO)**: Share authentication across applications (Icon: Smartphone).
- Microservices**: Trust tokens between services (Icon: Network of four nodes).



Benefits of JWT

- ✓ Reduces server load (no session storage)
- ✓ Scalable for distributed systems
- ✓ Can be used across domains
- ✓ Tamper-proof and verifiable



Note:
Store tokens securely and use HTTPS. Keep tokens short-lived and validate expiration.

WHAT IS JWT? (2 OF 2)

Common claims, where JWT is used, and its advantages and limitations.

COMMON JWT CLAIMS (PAYLOAD)

Claim	Meaning
sub	Subject (user ID / username, e.g. "agent1").
role	User role(s), e.g. AGENT or ADMIN.
iat	Issued at (timestamp).
exp	Expiration time.
iss / aud	Issuer / audience.

ADVANTAGES

- Stateless -- no server-side session storage.
- Self-contained and cross-language compatible.
- Digitally signed -- cannot be tampered with silently.

WHERE JWT IS USED

- Authentication for REST APIs
- Microservices communication
- Single Sign-On (SSO)
- Mobile and SPA applications

LIMITATIONS

- Cannot be revoked easily (until expiration).
- Sensitive data should never be stored in the payload.
- Must use HTTPS to prevent token interception.

KEY TAKEAWAY JWT enables stateless security and scalability -- but never store secrets in the payload, and always use HTTPS.

JWT STRUCTURE

A JSON Web Token consists of three parts separated by dots (.), each Base64Url encoded.

1. HEADER

```
{
  "alg": "HS256",
  "typ": "JWT"
}
```

2. PAYLOAD (CLAIMS)

```
{
  "sub": "agent1",
  "role": "AGENT",
  "iat": 1717152345,
  "exp": 1717155945
}
```

3. SIGNATURE

```
HMACSHA256(
  base64UrlEncode(header) + "." +
  base64UrlEncode(payload),
  secretKey
)
```

ALGORITHM TYPES

Type	Description	Example
HMAC (Symmetric)	Uses a shared secret key -- both issuer and verifier hold the same key.	HS256 (Lab 28's choice)
RSA / ECDSA (Asymmetric)	Uses a private/public key pair -- issuer signs with private, others verify with public.	RS256, ES256

KEY TAKEAWAY If any part of the token is changed, signature verification fails and the token is rejected -- keep the secret key private and secure.



HEADER


PAYLOAD (CLAIMS)

SIGNATURE

eyJzdWIiOiIxMjM0NTY3ODkwIiwibmFtZSI6IkFsaWNl:
Iiwi cm9sZSI6IkFETUIvbiAwf0Ijo xNzE1MTMzNiAwLCJleHAiOiE3MTUxMzM5MDB9

MEUCIQDE1xZrYk4QvXKZ...
MZ7OQ4Zb5Q8nV6rQ7QlgX8...


1) HEADER



```
{
  "alg": "HS256",
  "typ": "JWT"
}
```

- 1 alg Algorithm used to sign the token (e.g., HS256, RS256)
- 1 typ Type of token (always JWT)


2) PAYLOAD (CLAIMS)



```
{
  "sub": "1234567890",
  "name": "Alice",
  "role": "ADMIN",
  "iat": 1715133600,
  "exp": 1715133900
}
```

- ✓ **sub** Subject (unique identifier of the user)
- ✓ **name** Name of the user
- ✓ **role** Role of the user
- ✓ **iat** Issued At (timestamp when token was issued)
- ✓ **exp** Expiration Time (timestamp when token expires)
- Custom claims can be added as needed

3) SIGNATURE



```
HMACSHA256(  
    base64UrlEncode(header) + "." +  
    base64UrlEncode(payload),  
    secret_key  
)
```

- 1 Created by the server using a secret (or private key)
- ✓ Ensures authenticity and integrity
- ✓ Any change in header or payload will make the signature invalid

How the Parts Form a JWT

Base64Url (Header)


Base64Url
(Payload)

Base64Url
(Signature)

JWT Token (Compact & URL-safe)

Key Points

- ✓ Compact and URL-safe
- ✓ Stateless (no server-side session required)
- ✓ Can be used for Authentication and Authorization
- ✓ Keep tokens secure and use HTTPS
- ✓ Short-lived tokens with expiration are recommended



JWT AUTHENTICATION WORKFLOW (1 OF 2)

JWT enables stateless authentication. Once the user is authenticated, the server issues a token which is used for all subsequent requests.

CLIENT

- 1. Login Request -- user submits credentials.
- 5. Store Token -- client stores the JWT securely.

SERVER

2. Validate	3. Generate	4. Return	6-9. Verify
Server validates username and password.	If valid, generates a signed JWT.	Returns the JWT to the client.	Validates JWT + role on each request.

Authenticated Request

```
GET /api/customers/CUS-1001
Authorization: Bearer <JWT_TOKEN>
X-Correlation-Id: lab-request-001
```



KEY TAKEAWAY JWT allows secure, stateless authentication by issuing a signed token that the client uses for all subsequent requests until it expires.



JWT Authentication Architecture

Stateless, Secure and Scalable Authentication using JSON Web Tokens

→ Request Flow → Response Flow - - - - - Validation / Internal Flow





JWT (JSON Web Token) Workflow

JWT enables stateless authentication and secure authorization between client and server.

1. AUTHENTICATION FLOW – Getting the JWT

1 User Login Request



The client sends the username and password to the authentication endpoint.

2 Validate Credentials




The server validates the credentials against the user store (DB).

3 Generate JWT



If valid, the server creates a JWT with claims (user info, roles, permissions, expiry, etc.) and signs it using a secret key (HMAC) or private key (RSA).

4 Return JWT to Client



The server returns the JWT to the client (usually in the response body).

5 Store JWT



The client stores the JWT securely (e.g., localStorage, sessionStorage, or HttpOnly cookie).

2. AUTHORIZATION FLOW – Using the JWT for Access

6 Client Sends Request



Authorization: Bearer <JWT>

For each request to a protected resource, the client sends the JWT in the Authorization header.

7 Verify JWT



The server verifies the token signature using the secret key or public key.

8 Validate Claims



The server validates the claims (expiry, issuer, audience, etc.) and checks if the token is valid.

9 Authorization Decision

Valid

Invalid / Expired



Access Granted
The user is allowed to access the requested resource.



Access Denied
The request is rejected (e.g., 401 Unauthorized or 403 Forbidden).

Where is JWT Used?



APIs & Microservices



Mobile Applications



Single Page Applications



Serverless Applications

Typical JWT Claims

sub	→	Subject (User ID)
name	→	Name
role	→	Role(s)
iat	→	Issued At (timestamp)
exp	→	Expiration Time
iss	→	Issuer
aud	→	Audience
...	→	Custom Claims

Key Points

- ✓ JWT is stateless – no server-side session required.
- ✓ The server does not store the token.
- ✓ Token is self-contained and tamper-proof (when signed).
- ✓ Short-lived access tokens + refresh tokens are recommended.
- ✓ Always use HTTPS to transmit tokens.

Benefits of JWT

- ✓ Stateless & scalable
- ✓ Works across domains
- ✓ Reduces server load
- ✓ Ideal for distributed systems
- ✓ Secure when implemented properly



Note: Keep your secret/private keys secure. Do not expose them in the client.

TRY IT YOURSELF -- EXERCISE 3: JWT LOGIN TODOs (STARTER)

Reinforces: completing a JWT login/filter sketch -- a fill-in-the-blank TODO starter, not a from-scratch build.

STEP	WHAT TO DO
Starter	Create notes/JwtSecuritySketch.java -- a TODO / fill-in-the-blank skeleton is provided; blanks do not compile as-is.
Fill: login()	Replace ____ so jwtService.issue/createToken(username) returns a token, and the response Map returns it as "accessToken".
Fill: filter	Replace ____ so the filter checks authorizationHeader.startsWith("Bearer ") before parsing the token.
Secret hygiene	In .env.example-style notes, write JWT_SECRET=____ as a placeholder only -- never a real production secret.
Reflect	SOAP UsernameToken (Lab 24) is a separate mechanism from REST JWT -- do not conflate the two.
Reference	exercises/exercise-03-jwt-login-todos.md

JwtSecuritySketch.java (fill every ____) -- STARTER, not a solution

```
class AuthController {
  String login(String u, String p) {
    String token = jwtService.____(u); // issue/create
    return Map.of("accessToken", ____);
  }
}
// Filter: require header.startsWith(____) == "Bearer "
// then token = authHeader.substring(7); parse + set context
```

KEY TAKEAWAY TRY IT NOW Complete Exercise 3 (STARTER) -- fill in every ____ and // TODO, then re-read your sketch -- see exercises/exercise-03-jwt-login-todos.md.

JWT AUTHENTICATION WORKFLOW (2 OF 2)

Validating and authorizing an incoming request, the token lifecycle, and important notes.

VALIDATE -> AUTHORIZE -> RESPOND



TOKEN LIFECYCLE



IMPORTANT NOTES

Keep Secret Private

Short Expiration + Refresh

Always Use HTTPS

No Sensitive Data in Token

KEY TAKEAWAY JWT allows secure, stateless authentication by issuing a signed token that the client uses for all subsequent requests until it expires.

TOKEN VALIDATION (JWT)

Token validation is the process of verifying a JWT to ensure it is authentic, not expired, and safe to use.

Goal: ensure the token is issued by a trusted server, is valid, not expired, and contains the expected claims.

TOKEN VALIDATION STEPS

- 1. **Extract Token** — extract the JWT from the Authorization header (Bearer token).
- 2. **Parse Token** — decode into Header, Payload, and Signature.
- 3. **Verify Signature** — verify using the server's secret key.
- 4. **Validate Claims** — check standard claims like exp, iat, sub.
- 5. **Custom Validation** — validate roles/permissions as per business rules.
- 6. **Result** — if all validations pass, access is granted; otherwise, reject the request.

IF VALIDATION FAILS

Failure	Result
Invalid Signature	Token is tampered or not issued by trusted server -- 401.
Expired Token	Token has expired -- user must log in again -- 401.
Invalid Claims	One or more claims invalid (wrong issuer/audience) -- 401.
Insufficient Role	Token is valid but role does not satisfy the rule -- 403.

KEY TAKEAWAY Token validation ensures that only genuine and valid tokens are accepted. Always validate signature, expiration, and important claims before trusting the token.



JWT Token Validation – How It Works

The server validates a JWT to ensure it is authentic, valid, and safe to use.

1 Receive Token



Client sends the JWT in the Authorization header:

Authorization: Bearer <token>

2 Extract Token



Server extracts the token from the Authorization header.

3 Verify Signature



Server verifies the token signature using the secret key (HMAC) or public key (RSA/ECDSA).

4 Validate Claims



Server validates the claims (exp, iss, aud, nbf, etc.) to ensure the token is valid and trusted.

5 Authorization Check



Server checks if the user has permission to access the requested resource.

6 Allow or Deny Access



Access Granted
Token is valid and user is authorized.



Access Denied
Token is invalid or user is not authorized.

What is Validated?

	Signature	Ensures the token is not tampered.	Algorithm + Secret/Public Key
	Expiration (exp)	Token must not be expired.	Current time < exp
	Not Before (nbf)	Token must be used after the valid time.	Current time ≥ nbf
	Issuer (iss)	Token must be issued by a trusted server.	iss matches expected value
	Audience (aud)	Token must be intended for this application/API.	aud matches expected value
	Subject (sub)	Identifies the user (usually user ID).	Must not be empty
	Custom Claims	Any business-specific claims validation.	Validate as required

Key Points

- Always validate the signature first.
- Never trust the payload before validation.
- Use short-lived tokens (e.g., 15–60 minutes).
- Use HTTPS to transmit tokens.
- Store secrets/private keys securely.
- Do not store sensitive data in JWT payload.

Example

JWT Token (Compact)

```
eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiIxMjM0NTY3ODkiLCJybW11IjoiaWpWxpY2UiLCJyb21eIjoiaURNSU4iLCJpc3MiOiJteWpCisImF1Ij0jE3MTU1NzI0MD89.Sf1KxwRJSMekKF2QT4fwpMeJf36P0k6yJV_adQssw5c
```

Header Payload (Claims) Signature

Decoded Payload (Claims)

```
{  "sub": "1234567890",
  "name": "Alice",
  "role": "ADMIN",
  "iss": "myApp",
  "aud": "myApi",
  "iat": 1715572400,
  "nbf": 1715572400,
  "exp": 1715576000
}
```

→ User ID
→ User Name
→ User Role
→ Issuer
→ Audience (Intended API)
→ Issued At
→ Not Valid Before
→ Expiration Time

Common Validation Failures

Invalid Signature	Token is altered or signed with a different key.
Expired Token	The exp claim time has passed.
Token Not Yet Valid	Current time is before the nbf claim.
Invalid Issuer	The iss claim does not match the trusted issuer.
Invalid Audience	The aud claim does not match this API.
Missing / Invalid Claims	Required claims are missing or invalid.



Note

JWT is stateless. The server does not store the token. All information needed to validate the token is contained within the token or available on the server (keys, config).

TRY IT YOURSELF -- EXERCISE 4: MOCKMVC EVIDENCE MATRIX

Reinforces: drafting the 401/403/200 status matrix Lab 28's automated MockMvc tests must prove -- design only, no test code yet.

STEP	WHAT TO DO
Goal	Draft the status matrix Lab 28's MockMvc tests must cover, in notes/mockmvc-matrix.md.
Scenarios	Five rows: anonymous GET customers; bad token; agent GET customer; agent GET admin; admin GET admin.
Expected statuses	Fill the expected 401/403/200 result for each of the five scenarios.
Fixture	The successful customer-read scenario uses CUS-1001 (Amina Khan).
Boundary	Do not write full MockMvc test code in this pre-lab exercise -- plan the matrix only.
Reference	exercises/exercise-04-mockmvc-matrix.md

Status Matrix Skeleton (notes/mockmvc-matrix.md)

```
Scenario      Expected
anonymous GET /api/customers/** 401
invalid/bad Bearer token        401
agent1 GET CUS-1001             200
agent1 GET /api/admin/**        403
admin1 GET /api/admin/**        200
```

KEY TAKEAWAY TRY IT NOW Complete Exercise 4 before continuing -- fill in all five expected statuses using CUS-1001 as the fixture -- see exercises/exercise-04-mockmvc-matrix.md.

SECURITY BEST PRACTICES (1 OF 2)

Following security best practices helps protect your application, users, and data from common threats and vulnerabilities.

Category	Practices
1. Authentication	Use strong password policies; enforce MFA; avoid user enumeration; use secure login endpoints (HTTPS only).
2. Authorization	Implement RBAC; follow least privilege; validate permissions on the server for every request; never rely on client-side checks.
3. Protect Data in Transit	Enforce HTTPS for all endpoints; use TLS 1.2+; redirect HTTP to HTTPS; use HSTS.
4. Protect Data at Rest	Encrypt sensitive data in the database; store passwords with strong hashing (BCrypt, Argon2); manage encryption keys securely; never store secrets in code or configuration.
5. JWT and Token Best Practices	Use short-lived access tokens; store tokens securely (HttpOnly, Secure cookies preferred); validate signature, expiration, and claims; implement refresh token rotation.
6. Input Validation and Sanitization	Validate and sanitize all inputs; use server-side validation; prevent injection attacks; use parameterized queries and prepared statements.

KEY TAKEAWAY Security is not a one-time task. It is an ongoing process that involves people, processes, and technology. Secure by design. Verify always. Trust never.

SECURITY BEST PRACTICES (2 OF 2)

Practices 7-12: session management through secure development.

Category	Practices
7. Session Management	Use secure, HttpOnly, SameSite cookies where sessions are used; set appropriate timeouts; invalidate on logout; regenerate session ID after login.
8. Error Handling	Do not expose stack traces or internal details; return meaningful but safe error messages; log errors securely for monitoring.
9. Dependency and Patch Management	Keep all dependencies and libraries up to date; regularly scan for known vulnerabilities; apply security patches promptly.
10. Rate Limiting and Brute-Force Protection	Limit login attempts and API requests; use lockout policies for repeated failures; monitor and alert on anomalies.
11. Logging and Monitoring	Log security events (login, access denied, token failures); avoid logging sensitive data (passwords, tokens); use centralized logging tools.
12. Secure Development Practices	Follow secure coding standards; conduct threat modeling; perform regular security testing (SAST, DAST, penetration testing).

KEY TAKEAWAY Security is not a one-time task. It is an ongoing process that involves people, processes, and technology. Secure by design. Verify always. Trust never.

COMMON SECURITY MISTAKES (1 OF 2)

Avoid these common mistakes to build secure and resilient applications.

Mistake	Avoid It By
1. Weak or Default Passwords	Enforce strong password policies; use MFA for better protection.
2. Missing Authorization	Only authenticating users but not checking permissions -- always enforce authorization on every endpoint (least privilege).
3. Exposing Sensitive Information	Returning stack traces, SQL errors, or internal details -- log securely on the server side instead.
4. Insecure Data Transmission	Using HTTP instead of HTTPS -- always use HTTPS and HSTS; redirect all HTTP traffic to HTTPS.
5. Improper Token Management	Storing tokens in localStorage or exposing them in URLs -- prefer HttpOnly/Secure cookies; set proper expiration and refresh rotation.
6. No Input Validation or Sanitization	Trusting user input leads to SQL Injection, XSS, Command Injection -- validate, sanitize, and use parameterized queries.

KEY TAKEAWAY Most security breaches happen due to simple mistakes that could have been avoided. Follow best practices, review your code, and stay vigilant.

COMMON SECURITY MISTAKES (2 OF 2)

Mistakes 7-12: hardcoded secrets through outdated dependencies.

Mistake	Avoid It By
7. Hardcoding Secrets in Code	Storing passwords, API keys, secrets in code or config files -- use environment variables, Vault, or a secret manager.
8. Overly Permissive CORS Settings	Allowing all origins, methods, and headers -- restrict CORS to trusted origins only; avoid wildcards in production.
9. Not Protecting Against CSRF	Missing CSRF protection on state-changing requests -- use CSRF tokens or SameSite cookies where sessions are used; for stateless Bearer APIs, document why CSRF is disabled.
10. Insufficient Session Management	Long session timeouts and not invalidating sessions -- set proper timeouts; invalidate on logout and password change.
11. Excessive Privileges to Application	Running apps with admin or root privileges -- use dedicated service accounts with minimal permissions.
12. Outdated Dependencies and Libraries	Using libraries with known vulnerabilities -- regularly update dependencies; scan for vulnerabilities continuously.

KEY TAKEAWAY Security is not a feature, it is a mindset. Design securely, validate always, and monitor continuously.

PRODUCTION SECURITY CONSIDERATIONS (1 OF 2)

Security in production requires more than secure code. It involves people, processes, infrastructure, and continuous monitoring.

Consideration	What It Involves
1. Secure Configuration	Harden server/OS configuration; disable unnecessary services and default accounts; apply least privilege; use security headers (HSTS, CSP).
2. Strong Authentication and Authorization	Enforce MFA for users and admins; use strong password policies; implement RBAC and least privilege; review roles and permissions regularly.
3. Secure Communication	Enforce HTTPS (TLS 1.2+); redirect all HTTP traffic to HTTPS; use HSTS to prevent protocol downgrade; validate SSL/TLS certificates.
4. Protect Secrets and Sensitive Data	Store secrets in a dedicated secrets manager (Vault, AWS Secrets Manager); never store secrets in code, images, or environment files; rotate keys and secrets regularly.
5. Input Validation and Output Encoding	Validate and sanitize all user input; prevent SQL Injection, XSS, CSRF, Command Injection; use parameterized queries; encode output to prevent XSS.

KEY TAKEAWAY A secure application builds trust, protects data, and ensures business continuity -- security is an ongoing process, not a one-time task.

PRODUCTION SECURITY CONSIDERATIONS (2 OF 2)

Considerations 6-10, plus additional production safeguards.

Consideration	What It Involves
6. Secure Token and Session Management	Use short-lived access tokens and refresh tokens; store tokens in HttpOnly, Secure, SameSite cookies where applicable; invalidate tokens on logout/password change; implement token revocation.
7. Logging, Monitoring, and Alerting	Log security events (login, access denied, config changes); avoid logging sensitive data; monitor logs in real time; alert on suspicious activity and anomalies.
8. Patch Management and Vulnerability Management	Keep OS, dependencies, and frameworks up to date; scan for known vulnerabilities regularly; apply security patches promptly.
9. Backups and Disaster Recovery	Maintain encrypted, tested backups in a separate secure location; test restore procedures regularly; have a documented incident response and DR plan.
10. Access Control and Auditing	Limit access to production systems and data; use bastion hosts/VPN for access; enable audit trails for critical actions; review access regularly.

ADDITIONAL CONSIDERATIONS

- Web Application Firewall (WAF)
- API Rate Limiting
- Network Security
- Regular Security Testing (SAST/DAST/Pen Test)

KEY TAKEAWAY Defense in depth protects your systems from multiple layers. Monitor continuously, adapt, and improve.

TRY IT YOURSELF -- EXERCISE 5: PRODUCTION IDP CHECKLIST

Reinforces: drafting the production IdP and key-rotation checklist that separates Lab 28's teaching setup from a real deployment.

STEP	WHAT TO DO
Goal	Draft docs/security-notes.md outline items for a production IdP and key rotation.
Outline	In notes/security-notes-outline.md: replace lab users with a real IdP; rotate signing keys; use short token TTL; enforce HTTPS only.
Lab vs. prod	State explicitly that in-memory agent1/admin1 users are lab-only, never production accounts.
Transfers	Note that Lab 27's money-transfer routes must stay behind auth in production narratives too.
Boundary	Do not implement a full OAuth2 Authorization Server here -- outline only.
Reference	exercises/exercise-05-production-checklist.md

security-notes-outline.md (four checklist items)

```
1. Replace in-memory agent1/admin1 with a real IdP
2. Rotate JWT signing keys on a schedule
3. Use a short access-token TTL (+ refresh flow)
4. Enforce HTTPS everywhere -- no plain HTTP
```

KEY TAKEAWAY TRY IT NOW Complete Exercise 5 before continuing -- draft all four checklist items and mark agent1/admin1 as lab-only -- see exercises/exercise-05-production-checklist.md.

TRY IT YOURSELF -- EXERCISE 6: LAB 28 READINESS CHECKLIST

Capstone: confirm your Labs 25-27 CRM baseline is ready before Lab 28 layers Spring Security on top.

STEP	WHAT TO DO
Goal	Ready lab28-crm by confirming the Labs 25-27 concepts it depends on, in notes/lab28-readiness.md.
Depends on	A runnable Customer REST API from Labs 25-27 -- confirm it starts and responds before adding security.
Path	Write the working folder path: examples/lab28-crm.
Evidence plan	Plan where login + Bearer GET CUS-1001 screenshots will be saved as evidence.
Defer	Global Bean Validation / ErrorResponse unification waits for Lab 29 -- do not build it now.
Reference	exercises/exercise-06-lab28-readiness.md

Readiness Checklist (notes/lab28-readiness.md)

```
[ ] Customer REST API from Labs 25-27 runs cleanly
[ ] examples/lab28-crm path created
[ ] Evidence folder planned for login + Bearer GET screenshots
[ ] ErrorResponse unification deferred to Lab 29
```

KEY TAKEAWAY TRY IT NOW Complete Exercise 6 before Lab 28 -- confirm your CRM baseline is ready and note what's deferred to Lab 29 -- see exercises/exercise-06-lab28-readiness.md.

LAB OVERVIEW -- SPRING SECURITY FUNDAMENTALS

Lab 28: Spring Security Basics -- Northstar CRM JWT and Roles

BUSINESS SCENARIO

- Leadership will not expose customer APIs on the open network -- unauthenticated callers must be rejected.
- Agents (AGENT) work Amina/Ravi records within policy; admins (ADMIN) get elevated operations.
- Authn/authz must be automated so new routes do not silently ship open.

LEARNING OBJECTIVES

- Add Spring Security to a Spring Boot 3 CRM API; issue a JWT on login.
- Validate JWTs on every request with a filter; deny by default.
- Protect `/api/customers/**` for AGENT/ADMIN and `/api/admin/**` for ADMIN only.
- Prove the 401/403/200 matrix with MockMvc, keeping secrets out of Git.
- Explain the trust boundary between login, token issuance, and authorization.

WHAT YOU BUILD

- Copy prior CRM to lab28-crm; add Security + JWT deps; build a stateless SecurityFilterChain, JwtService, JwtAuthenticationFilter, and `/api/auth/login`; enforce AGENT/ADMIN matchers; write MockMvc 401/403/200 tests; document production IdP/secret-rotation notes.

KEY TAKEAWAY Fixtures CUS-1001 (Amina Khan, ACTIVE) and CUS-1002 (Ravi Singh, PROSPECT) anchor every example; lab users agent1 (AGENT) and admin1 (ADMIN) prove role separation.

LAB TASKS AND DELIVERABLES

Northstar CRM JWT and Roles -- implementation steps, deliverables, and the evaluation rubric.

#	Implementation Step
1	Branch prior CRM to lab28-crm; pin Security + JWT dependencies; no secrets committed.
2	Configure the stateless SecurityFilterChain -- deny by default.
3	Implement UserDetails and BCrypt password encoding (agent1, admin1).
4	Implement JwtService -- issue and parse tokens (HS256, sub/roles/iat/exp).
5	Build AuthController.login() -- verify credentials, return a JWT.
6	JWT filter validates Bearer tokens; authenticated customer access works.
7	Role separation -- AGENT vs ADMIN, proving 403 vs 200.
8-10	Automated MockMvc 401/403/200 matrix; runbook + production IdP notes; failure experiments + evidence pack.

EXPECTED DELIVERABLES

- lab28-crm with SecurityFilterChain, JWT login, AGENT/ADMIN roles.
- MockMvc evidence for 401/403/200.
- Successful-path evidence (login + CUS-1001 with AGENT).
- Controlled-failure evidence (401/403).
- Auth-flow notes (docs/security-notes.md) + production IdP/secret-rotation checklist; no secrets or target/ committed.

RUBRIC (100 MARKS)

- Environment 10 · Core Impl 30 · Integration/Config 15 · Failure Handling 15 · Verification 10 · Security/Production 10 · Docs 10

KEY TAKEAWAY Shipping an open `/api/customers/**` is an honor violation. Logging raw JWTs or committing secrets loses security marks. Cannot distinguish 401 from 403 -> incomplete.

MODULE 28 SUMMARY

In this module, we explored how Spring Security provides authentication, authorization, and protection for enterprise Java applications.

KEY CONCEPTS COVERED



Security Basics

Spring Security's comprehensive framework for authn, authz, and protection.



Authentication

Verifying identity via credentials, password encoding, and JWT.



Authorization

Role-based access control -- only authorized users reach protected resources.



Secured Endpoints

Public endpoints stay open; protected endpoints require authentication and roles.



Configuration

SecurityFilterChain, in-memory/JWT users, and password encoding.



Best Practices

Least privilege, strong passwords, secure tokens, and validated input.

MODULE FLOW RECAP

1

Authn (who)

2

Authz (what)

3

Filter Chain

4

JWT

5

Lab: Northstar CRM

KEY TAKEAWAY You can now build secure, role-based Spring Boot applications that protect resources, authenticate users, and enforce proper access control.

KNOWLEDGE CHECK (1 OF 3)

Test your understanding of Spring Security's purpose, authentication, and configuration.

1. What is the primary purpose of Spring Security?

- A. To connect to a database
- B. To add security to Spring applications**
- C. To build REST APIs
- D. To manage application logs

3. What type of authentication does Lab 28's Northstar CRM implement?

- A. HTTP Basic Authentication
- B. Form-based session authentication
- C. OAuth2 Authentication
- D. JWT (stateless Bearer token) Authentication**

2. Which component is responsible for authenticating users?

- A. AuthorizationManager
- B. AuthenticationManager**
- C. PasswordEncoder
- D. SecurityContextHolder

4. Where do we configure security settings in a Spring Boot application?

- A. application.properties
- B. web.xml
- C. SecurityConfig.java (a SecurityFilterChain @Bean)**
- D. logback.xml

KEY TAKEAWAY Spring Security exists to add authentication and authorization to Spring applications -- the AuthenticationManager verifies identity, and SecurityConfig wires it all together.

KNOWLEDGE CHECK (2 OF 3)

Four more questions on roles, password encoding, unauthenticated access, and logout.

5. Which annotation is commonly used to secure endpoints based on roles?

- A. @Secured
- B. @RolesAllowed
- C. @PreAuthorize**
- D. @EnableSecurity

7. Which component is used to encode passwords in Spring Security?

- A. UserDetails
- B. PasswordEncoder**
- C. AuthenticationProvider
- D. UserDetailsService

6. What does an AGENT role allow access to in Lab 28's Northstar CRM?

- A. Only /api/admin/** endpoints
- B. Public endpoints and /api/customers/****
- C. Only database operations
- D. All endpoints without a token

8. What happens when a user calls a protected endpoint with no JWT at all?

- A. Access is granted
- B. 401 Unauthorized is returned**
- C. 403 Forbidden is returned
- D. 500 Internal Server Error is returned

KEY TAKEAWAY PasswordEncoder secures credentials; @PreAuthorize enforces roles; a missing token means 401, not 403.

KNOWLEDGE CHECK (3 OF 3)

Two final questions, plus what these ten questions prove together.

9. Which endpoint is typically used to handle a JWT logout / client-side token discard?

- A. /logout**
- B. /exit**
- C. /signout**
- D. /logoutUser**

10. Which interface is used to load user-specific data for authentication?

- A. UserDetailsService**
- B. AuthenticationService**
- C. UserService**
- D. SecurityService**

WHAT THESE TEN QUESTIONS PROVE TOGETHER

Vocabulary — authentication versus authorization, and the components that implement each (AuthenticationManager, PasswordEncoder, UserDetailsService).

Configuration — security is wired declaratively in a SecurityFilterChain bean, not scattered through Controller code.

Failure Modes — a missing token is 401; an insufficient role is 403 -- and the difference is instructor-verified in Lab 28.

Real-World Grounding — the AGENT/ADMIN roles and JWT design in this quiz are exactly what Lab 28 requires you to build.

KEY TAKEAWAY Score 7 or more out of 10 to demonstrate a good understanding of Spring Security basics before starting Lab 28.

"Authenticate first, then authorize -- every request, every time."

MODULE 28 COMPLETE

Spring Security Fundamentals

You can now build secure, role-based Spring Boot applications -- authenticating users, encoding passwords, issuing and validating JWTs, and enforcing access control at every endpoint.