Incident Lifecycle Automation in ServiceNow

Model Performance, Functional & User Acceptance Testing

Project Development Phase Documentation

Project Name	Incident Lifecycle Automation in ServiceNow
Document	Project Development Phase — Testing & Evaluation Documentation
Phase	5. Project Development Phase
Date	08 September 2026
Team ID	
Maximum Marks	Per section (see evaluation summary below)

Evaluation Summary

No.	Section	Maximum Marks	Marks Awarded
1	Salesforce — Model Performance Test	10 Marks	
2	Artificial Intelligence — Model Performance Test	10 Marks	
3	Machine Learning — Model Performance Test	10 Marks	
4	Power BI — Model Performance Test	10 Marks	
5	Tableau — Performance Test	10 Marks	
6	GenAI Functional & Performance Testing	10 Marks	
7	User Acceptance Testing (UAT)	4 Marks	

Document Conventions and Evidence Status

This document consolidates the testing and evaluation work for the **Incident Lifecycle Automation in ServiceNow** project. It contains seven sections, one for each assessed testing area. Each section follows the same layout: a metadata table, an explanation of the component, the original reported parameters and results (preserved unchanged), an interpretation of those results, and an evidence area.

Evidence Status Labels

Every result in this document is tagged with one of the following labels so that actual evidence, reported figures and planned items are never confused.

Label	Meaning
REPORTED — NO EVIDENCE ATTACHED	A value or outcome recorded in the original project documentation. It has not been independently re-verified in this document and no supporting screenshot or log is attached yet.
EVIDENCE PLACEHOLDER	A clearly labelled space where a genuine screenshot, log or record must be inserted. Nothing has been fabricated to fill it.
PLANNED / PROPOSED	Testing or documentation that is suggested but has not been executed or recorded.
N/A	Not applicable, or evidence genuinely unavailable (retained from the original documentation where it was marked N/A).

> **Important:** All accuracy, confidence, timing and pass/fail values in this document are the figures reported in the original Project Development Phase documentation. They have not been changed, re-calculated or independently verified here. Explanations of what the metrics mean are educational context only and do not add new results. Items that need confirmation are listed in Appendix A.

Contents

1. Salesforce — Model Performance Test
2. Artificial Intelligence — Model Performance Test
3. Machine Learning — Model Performance Test
4. Power BI — Model Performance Test
5. Tableau — Performance Test
6. GenAI Functional & Performance Testing
7. User Acceptance Testing (UAT)

Appendix A — Items Flagged for Verification

1. Salesforce — Model Performance Test

Project Name	Incident Lifecycle Automation in ServiceNow
Document	Salesforce — Model Performance Test
Phase	5. Project Development Phase
Date	08 September 2026
Team ID	
Maximum Marks	10 Marks

1.1 Purpose of Salesforce Integration

Service Desk Agents resolve incidents faster when they know who the affected customer is and which account they belong to. In this project, Salesforce is integrated with ServiceNow to synchronize **Account** and **Contact** records into ServiceNow. Once synchronized, this information gives agents additional customer and account context on incidents that are linked to the affected Service, so they do not need to look up customer details in a separate system while handling an incident.

> **Scope note:** This section evaluates an integration and record-matching process. Salesforce is the source system for Account and Contact data; it is not described here as an AI model.

1.2 Integration Workflow

1. **Retrieve records.** Account and Contact records are retrieved from Salesforce during each synchronization run.
2. **Match records.** Each retrieved record is compared with the corresponding existing ServiceNow CI / Contact record using the matching logic.
3. **Update matched records.** Where a match is found, the existing ServiceNow record is updated with the Salesforce information.
4. **Flag unmatched records.** Records that cannot be matched are not applied automatically; they are flagged for review.
5. **Make context available.** The synchronized Account and Contact information is available to Service Desk Agents in the incident-management process, on incidents linked to the affected Service.

1.3 Model Performance Testing (Original Reported Parameters)

S.No.	Parameter	Values
1	Model Summary	Salesforce integration used to sync Account and Contact records into ServiceNow, giving Service Desk agents customer/account context on incidents linked to the affected Service. On sync, matching Account/Contact records are updated; unmatched records are flagged for review.
2	Accuracy	Sync Match Accuracy – 98% (Account/Contact records correctly matched to existing ServiceNow CI/Contact records)
3	Confidence Score	Reflects how confident the matching logic is when linking a Salesforce record to an existing ServiceNow record. Average confidence – 92%.

1.4 Performance Metrics and Interpretation

Metric	Reported Value	What it measures	Evidence Status
Sync Match Accuracy	98%	The proportion of synchronized Account/Contact records that were correctly matched to the right existing ServiceNow CI/Contact record. It describes **outcomes** — whether the matches were right.	Reported — no evidence attached
Average Confidence	92%	The average certainty the matching logic assigned to its own matches. It describes the logic's **self-assessed certainty** when linking a record — not whether the match was actually correct.	Reported — no evidence attached

How to read these two values

- **Accuracy is checked against the correct answer; confidence is not.** A match can be made with high confidence and still be wrong, or with low confidence and still be right. The two numbers should be read side by side but never treated as the same measurement.
- A 98% match accuracy alongside a 92% average confidence indicates that the matching logic was, on average, slightly more cautious about its matches than the observed correctness rate. This is an observation about the two reported figures only.
- Unmatched records are flagged for human review rather than being forced into a match, which keeps the update step conservative.
- The number of records evaluated, the method used to determine whether a match was "correct", and the confidence calculation are not stated in the original documentation. These are flagged in Appendix A.

> **Evidence status:** Both values are REPORTED figures from the original documentation. They are not presented as independently verified because no test logs or screenshots are attached.

1.5 Evidence

[Insert actual Salesforce Account / Contact screenshot here]

Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 1.1 — Salesforce Account/Contact records used for synchronization

[Insert actual ServiceNow matched-record screenshot here]

Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 1.2 — ServiceNow record updated by the sync (matched record)

[Insert actual flagged-for-review screenshot or sync log here]

Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 1.3 — Unmatched records flagged for review

2. Artificial Intelligence — Model Performance Test

Project Name	Incident Lifecycle Automation in ServiceNow
Document	Artificial Intelligence — Model Performance Test
Phase	5. Project Development Phase
Date	08 September 2026
Team ID	
Maximum Marks	10 Marks

2.1 AI Model Overview

The project uses **ServiceNow Predictive Intelligence** to support Service Desk Agents during triage. The model learns from historical incidents — the text typed in the short description and the Category, Subcategory and knowledge articles that were eventually used — and then uses that learning to suggest values for new incidents. The suggestions are:

- **Category**
- **Subcategory**
- **Relevant Knowledge Articles**

The aim, as stated in the original summary, is to reduce manual triage time for Service Desk Agents.

2.2 Working Process

1. **Training.** Historical incident data is used to train the model.
2. **Input.** When an incident is raised, its short description is provided to the model as input.
3. **Prediction.** The model generates suggestions for Category, Subcategory and relevant Knowledge Articles.
4. **Agent review.** The Service Desk Agent reviews the suggestions and accepts or changes them.
5. **Evaluation.** The agent's final selection can be compared with the model's suggestion; the share of suggestions that match is used to evaluate model performance.

2.3 Model Performance Testing (Original Reported Parameters)

S.No.	Parameter	Values	Screenshot
1	Model Summary	ServiceNow Predictive Intelligence model trained on historical incidents to auto-suggest Category, Subcategory, and relevant Knowledge Articles from the incident's short description, reducing manual triage time for Service Desk agents.	N/A (original). Insert model configuration screenshot if available — see Figure 2.1.
2	Accuracy	Training Accuracy – 91% / Validation Accuracy – 88% (suggested Category/Article matched agent's final selection)	N/A (original). See Figures 2.2 – 2.3.
3	Fine Tuning Result (if Done)	Validation Accuracy – 93% after retraining the solution on 3 months of additional resolved incidents	N/A (original). See Figure 2.4.

2.4 Performance Metrics and Interpretation

Metric	Reported Value	Meaning	Evidence Status
Training Accuracy	91%	How often the model's suggestions are right on the incidents it learned from.	Reported — no evidence attached
Validation Accuracy	88%	How often suggested Category/Article matched the agent's final selection.	Reported — no evidence attached
Validation Accuracy after retraining	93%	Validation accuracy after retraining on 3 months of additional resolved incidents.	Reported — no evidence attached

Training accuracy vs. validation accuracy

Training accuracy is measured on the data the model learned from, so it shows how well the model has absorbed that history. **Validation accuracy** is measured on incidents the model did not learn from (as reflected by comparison with the agent's final selection), so it is the better indicator of how the model is likely to behave on new incidents. Validation accuracy is normally equal to or lower than training accuracy; here the reported gap is 3 percentage points (91% vs. 88%), which the original documentation does not analyse further.

Why retraining may improve performance

Service Desk issues, wording and knowledge articles change over time. Retraining on newer resolved incidents lets the model learn recent vocabulary, new issue types and updated agent choices, which can improve its match with agents' final selections. The original documentation reports validation accuracy rising from 88% to 93% after retraining on 3 months of additional resolved incidents.

> **Evidence status:** All three accuracy values are REPORTED figures with no attached evidence. The dataset size, number of training records, train/validation split and retraining procedure are not documented and are flagged in Appendix A — they have deliberately not been estimated.

2.5 Evidence

[Insert actual model configuration screenshot here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 2.1 — Predictive Intelligence model configuration

[Insert actual prediction screenshot here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 2.2 — Category / Subcategory / Knowledge Article predictions on an incident

[Insert actual validation result screenshot here]

Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 2.3 — Validation results (88%)

[Insert actual retraining result screenshot here]

Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 2.4 — Retraining and post-retraining validation results (93%)

3. Machine Learning — Model Performance Test

Project Name	Incident Lifecycle Automation in ServiceNow
Document	Machine Learning — Model Performance Test
Phase	5. Project Development Phase
Date	08 September 2026
Team ID	
Maximum Marks	10 Marks

3.1 Machine Learning Model Overview

The Machine Learning section covers the **classification component underlying the Predictive Intelligence model** — the part that automatically assigns Category, Subcategory and Urgency. Where Section 2 describes what the AI feature does for agents and its accuracy as experienced in use, this section describes how that underlying classifier is evaluated using standard machine-learning metrics.

> **Relationship to Section 2:** Both sections relate to the same Predictive Intelligence functionality. The figures reported here (92% test-set accuracy; precision 0.91; recall 0.90; F1 0.90) are reported separately in the original documentation from the AI figures (91% / 88% / 93%). The original does not state whether they come from the same or different datasets or runs, so they are not presented here as independent experiments. This is flagged in Appendix A.

3.2 Model Performance Testing (Original Reported Parameters)

S.No.	Parameter	Values	Screenshot
1	Metrics	Underlying classification solution for the Predictive Intelligence model (Category / Subcategory / Urgency auto-assignment). Classification Model: Confusion Matrix – 92/100 correctly classified on test set, Accuracy Score – 92%, Classification Report – Precision 0.91, Recall 0.90, F1-score 0.90	N/A (original). See Figures 3.1 – 3.2.
2	Tune the Model	Hyperparameter Tuning – adjusted cluster similarity threshold and minimum cluster size in the Solution Definition / Validation Method – 5-fold Cross-Validation on historical incident data	N/A (original). See Figure 3.3.

3.3 Evaluation Metrics

In simple terms, the metrics below describe how well a classifier sorted incidents into the correct classes.

Metric	Plain-language meaning	Standard formula
Confusion Matrix	A table that compares the model's predicted class with the true class. Correct predictions fall on the diagonal; mistakes fall elsewhere. TP = true positive, TN = true negative, FP = false positive, FN = false negative.	Counts of TP, TN, FP, FN per class
Accuracy	Out of all test incidents, the share classified correctly.	(TP + TN) / (TP + TN + FP + FN)
Precision	Of the incidents the model assigned to a class, how many truly belong to it. High precision means few wrong suggestions.	TP / (TP + FP)
Recall	Of the incidents that truly belong to a class, how many the model found. High recall means few missed cases.	TP / (TP + FN)
F1-score	A single balanced score combining precision and recall.	2 × (Precision × Recall) / (Precision + Recall)

Reported Result	Value	Reading	Evidence Status
Correctly classified (test set)	92 / 100	92 of 100 test incidents classified correctly, consistent with the reported accuracy.	Reported — no evidence attached
Accuracy Score	92%	92 ÷ 100.	Reported — no evidence attached
Precision	0.91	Of predicted classifications, about 91% were right.	Reported — no evidence attached
Recall	0.90	Of true cases, about 90% were found.	Reported — no evidence attached
F1-score	0.90	Balance of precision and recall.	Reported — no evidence attached

Evidence status: The averaging method used for precision, recall and F1 (for example macro or weighted across classes) and class-wise values are not stated in the original and are not invented here. No confusion matrix is provided in the original.

3.4 Model Tuning

Tuning adjusts a model's settings (hyperparameters) to find a configuration that performs reliably rather than relying on default values. The original documentation records the following tuning information:

- Adjusted the **cluster similarity threshold** in the Solution Definition.
- Adjusted the **minimum cluster size** in the Solution Definition.
- Validation method: **5-fold Cross-Validation** on historical incident data.

How cross-validation helps. In 5-fold cross-validation, the historical data is divided into five parts. The model is trained on four parts and tested on the remaining one, and this is repeated so every part is used for testing once. Results that stay similar across the five rounds suggest the model performs consistently and is not dependent on one lucky split of the data.

> **Evidence status:** The tuned values, tried ranges and the per-fold results are not stated in the original documentation and are not provided here.

3.5 Evidence

[Insert actual confusion matrix here — do not estimate]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 3.1 — Confusion matrix on the test set (92/100 correctly classified)

[Insert actual classification report here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 3.2 — Classification report (precision, recall, F1-score)

[Insert actual validation evidence here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 3.3 — Hyperparameter tuning and 5-fold cross-validation results

4. Power BI — Model Performance Test

Project Name	Incident Lifecycle Automation in ServiceNow
Document	Power BI — Model Performance Test
Phase	5. Project Development Phase
Date	08 September 2026
Team ID	
Maximum Marks	10 Marks

4.1 Original Reported Parameters

S.No.	Parameter	Screenshot / Values
1	Data Rendered	Incident, Service, SLA, and related-record data pulled from ServiceNow via the built-in OData/Table API connector for reporting
2	Data Preprocessing	Filtering and structuring incident records by Category, Status, Priority, and Assignment Group
3	Utilization of Data Filters	Filters applied for Service, Urgency, Assignment Group, and SLA status
4	DAX Queries Used	SLA Compliance % = DIVIDE(COUNTROWS(FILTER(Incidents,Incidents[SLA_Met]=TRUE())),COUNTROWS(Incidents))
5	Dashboard design	Incident volume, SLA compliance, and escalation-tracking views. No. of Visualizations / Graphs – 6
6	Report Design	Summary reporting on incident resolution and knowledge-article reuse. No. of Visualizations / Graphs – 4

4.2 Data Integration

Power BI retrieves **Incident, Service, SLA and related-record** data directly from ServiceNow using the built-in **OData / Table API connector**. This gives the reports a live link to the platform's tables, so the dashboards reflect incident-management data held in ServiceNow without manual exports.

4.3 Data Preprocessing

Before visualization, incident records are filtered and structured so they can be analysed consistently. They are organized by:

- **Category** — type of issue reported.
- **Status** — where the incident is in its lifecycle.
- **Priority** — business importance of the incident.
- **Assignment Group** — the team responsible for the incident.

4.4 Filters

Filter	Purpose in interactive reporting
Service	Narrows the report to incidents affecting a selected business service.
Urgency	Lets viewers focus on high-urgency incidents or compare urgency levels.
Assignment Group	Shows workload and performance for a specific support team.
SLA Status	Separates incidents that met their SLA from those that did not, for compliance analysis.

4.5 DAX Formula

```
SLA Compliance % =
DIVIDE(
    COUNTROWS(
        FILTER(Incidents, Incidents[SLA_Met] = TRUE())
    ),
    COUNTROWS(Incidents)
)
```

What it calculates. The formula counts the incidents where the SLA_Met field is TRUE and divides that count by the total number of incidents, giving the percentage of incidents resolved within their SLA. DIVIDE is used instead of the "/" operator so that an empty selection (zero incidents) returns a blank rather than an error.

Formula status. The formula is preserved exactly as in the original; only its layout has changed. No error was identified and no correction is proposed.

4.6 Dashboard and Report

Component	Visualizations	Purpose
Dashboard — Incident volume	Part of 6 in dashboard	Shows how many incidents are being raised, to reveal demand and trends.
Dashboard — SLA compliance	Part of 6 in dashboard	Shows the SLA Compliance % measure so service-level performance can be monitored.
Dashboard — Escalation tracking	Part of 6 in dashboard	Tracks incidents escalated between support levels.
Report — Incident resolution	Part of 4 in report	Summarizes how incidents are resolved.
Report — Knowledge-article reuse	Part of 4 in report	Summarizes how often existing knowledge articles are reused in incident handling.

Totals preserved from the original: **Dashboard – 6 visualizations; Report – 4 visualizations.** The chart type and the split of the visualizations across the views are not stated in the original.

Evidence status: The visualization counts are REPORTED. The dashboard and report cannot be confirmed from this document until screenshots are inserted.

4.7 Evidence

[Insert actual Power BI dashboard screenshot here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 4.1 — Power BI dashboard (6 visualizations)

[Insert actual Power BI report screenshot here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 4.2 — Power BI report (4 visualizations)

5. Tableau — Performance Test

Project Name	Incident Lifecycle Automation in ServiceNow
Document	Tableau — Performance Test
Phase	5. Project Development Phase
Date	08 September 2026
Team ID	
Maximum Marks	10 Marks

5.1 Original Reported Parameters

S.No.	Parameter	Screenshot / Values
1	Data Rendered	Incident, change, and child-incident records exported from ServiceNow via scheduled Table API extract
2	Data Preprocessing	Grouping incidents by service, technician, and resolution status
3	Utilization of Filters	Filters for Service, Level 2 Assignment, and Resolution status
4	Calculation fields Used	Days Open = DATEDIFF([Opened Date],[Resolved Date],'day') (as written in the original; see 5.5)
5	Dashboard design	Incident-lifecycle tracking dashboard. No. of Visualizations / Graphs – 5
6	Story Design	Story walking through incident creation → escalation → resolution. No. of Visualizations / Graphs – 4

5.2 Data Integration

Tableau uses **incident, change and child-incident** records exported from ServiceNow by a **scheduled Table API extract**. A scheduled extract refreshes the data at set intervals, so the dashboard reflects recent ServiceNow data without a manual export.

5.3 Data Preprocessing

Incident records are grouped by:

- **Service** — to compare incidents across business services.
- **Technician** — to review workload and activity by assignee.
- **Resolution Status** — to separate open, in-progress and resolved incidents.

5.4 Filters

Filter	Purpose
Service	Focuses the view on one or more services.
Level 2 Assignment	Isolates incidents escalated to the Level 2 group.
Resolution Status	Shows incidents by their current resolution state.

5.5 Calculated Field

```
Days Open =
DATEDIFF('day', [Opened Date], [Resolved Date])
```

What it calculates. The number of days between the date an incident was opened and the date it was resolved.

> **Formula note:** The original document wrote this as DATEDIFF([Opened Date],[Resolved Date],'day'). Tableau's DATEDIFF function takes the date part first — DATEDIFF(date_part, start_date, end_date) — so the version above uses that argument order. The calculation itself (days from Opened Date to Resolved Date) is unchanged; only the argument order is written in Tableau's syntax. Please confirm against the workbook's actual calculated field (see Appendix A).

5.6 Dashboard and Story

Dashboard (5 visualizations). The incident-lifecycle tracking dashboard presents incident, change and child-incident activity grouped by service, technician and resolution status, so lifecycle progress and time open (Days Open) can be tracked in one place.

Story (4 visualizations). The story walks through the incident lifecycle in sequence — **creation → escalation → resolution** — to demonstrate how an incident moves through the process.

> **Evidence status:** Visualization counts (5 and 4) are REPORTED. The individual chart types are not documented in the original and are not described here.

5.7 Evidence

[Insert actual Tableau dashboard screenshot here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 5.1 — Tableau incident-lifecycle dashboard (5 visualizations)

[Insert actual Tableau story screenshot here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 5.2 — Tableau story: creation → escalation → resolution (4 visualizations)

6. GenAI Functional & Performance Testing

Project Name	Incident Lifecycle Automation in ServiceNow
Document	GenAI Functional & Performance Testing
Phase	5. Project Development Phase
Date	08 September 2026
Team ID	
Maximum Marks	10 Marks

6.1 Test Scenarios & Results

The table lists all seven original test cases. Scenarios, steps, expected results, actual results and Pass/Fail outcomes are as recorded in the original documentation. Preconditions were not recorded and are left blank.

Test Case ID	Test Scenario	Pre-conditions	Test Steps	Expected Result	Actual Result	Status	Evidence
FT-01	Validate incident classification fields		Enter valid/invalid Category, Subcategory, Urgency, CI	Valid inputs accepted; errors shown for invalid ones	Invalid entries correctly blocked with inline error messages	Pass	No evidence attached. [Insert screenshot / log]
FT-02	Knowledge / Agent Assist suggestions		Search a known issue	Relevant knowledge articles returned	Top 3 matching articles displayed within the incident form	Pass	No evidence attached. [Insert screenshot / log]
FT-03	GenAI incident summary generation (Now Assist)		Trigger "Generate Summary" on a resolved incident	Concise, accurate summary of incident and resolution generated	Summary generated in ~4s, accurately reflected cause and resolution	Pass	No evidence attached. [Insert screenshot / log]
FT-04	Escalation / reassignment		Reassign incident to Level 2	Incident routed to correct group	Incident appeared in Level 2 queue immediately after reassignment	Pass	No evidence attached. [Insert screenshot / log]
PT-01	Incident save time		Time saving a new incident	Completes within acceptable response time	Average save time 1.4s across 10 runs	Pass	No evidence attached. [Insert screenshot / log]
PT-02	Concurrent incident load		Create several incidents at once	System does not slow down or fail	20 simultaneous incident creations completed with no errors	Pass	No evidence attached. [Insert screenshot / log]

Test Case ID	Test Scenario	Pre-conditions	Test Steps	Expected Result	Actual Result	Status	Evidence
PT-03	Related-record load (attachments / child incidents)		Attach files / create child incidents	Processes smoothly, no crashes	5 attachments and 3 child incidents processed without issue	Pass	No evidence attached. [Insert screenshot / log]

Status values are the Pass outcomes reported in the original documentation; they are not independently re-verified here.

6.2 Functional Testing

The four functional test cases check that the incident form and GenAI features behave correctly:

- **FT-01 — Incident classification:** confirms the form accepts valid Category, Subcategory, Urgency and CI values and blocks invalid entries with inline error messages.
- **FT-02 — Knowledge / Agent Assist:** confirms that searching a known issue returns relevant knowledge articles inside the incident form (reported: top 3 matching articles).
- **FT-03 — Summary generation (Now Assist):** confirms that a concise summary reflecting the cause and resolution can be generated for a resolved incident.
- **FT-04 — Escalation / reassignment:** confirms that reassigning an incident to Level 2 routes it to the correct group and queue.

6.3 Performance Testing

The three performance test cases evaluate responsiveness and stability:

- **PT-01 — Incident save response time:** measures how long saving a new incident takes.
- **PT-02 — Concurrent incident creation:** checks the system stays stable when several incidents are created at the same time.
- **PT-03 — Related-record and attachment processing:** checks that attachments and child incidents are handled smoothly.

6.4 Reported Results and How to Read Them

Reported Measurement	Value	Interpretation	Evidence Status
Incident summary generation time	Approximately 4 seconds	Time taken by Now Assist to produce a summary in FT-03.	Reported — no evidence attached
Average incident save time	1.4 seconds (10 runs)	Mean time to save a new incident over 10 test runs.	Reported — no evidence attached
Concurrent incident creation	20 simultaneous, no errors	20 incidents created at once completed without errors.	Reported — no evidence attached
Related records processed	5 attachments and 3 child incidents, no issue	Related-record handling worked for these quantities.	Reported — no evidence attached

> **Limitation:** These measurements come from the project's test run as reported. They do not represent independently verified production performance. The acceptable response-time threshold for PT-01 was not specified in the original; the Pass result relies on the original's assessment.

6.5 Test Evidence

[Insert actual test execution screenshots here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 6.1 — Functional test evidence (FT-01 to FT-04)

[Insert actual execution log / timing record here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 6.2 — Performance test evidence — save time and concurrent load (PT-01, PT-02)

[Insert actual result record here]
Status: EVIDENCE PLACEHOLDER — no screenshot attached

Figure 6.3 — Related-record evidence — attachments and child incidents (PT-03)

7. User Acceptance Testing (UAT)

Project Name	Incident Lifecycle Automation in ServiceNow
Document	User Acceptance Testing (UAT)
Phase	5. Project Development Phase
Date	08 September 2026
Team ID	
Maximum Marks	4 Marks

7.1 Project Overview

User Acceptance Testing confirms that the solution supports the real incident-handling activities it was built for. UAT was performed on the **Incident Lifecycle Automation solution in ServiceNow**, covering service setup, incident creation and classification, knowledge-assisted investigation, Level 2 escalation, emergency changes, child incidents, resolution, and knowledge-article creation.

Project Version	v1.0
Testing Period	02 September 2026 to 08 September 2026

7.2 Testing Scope

- Service setup
- Incident creation & classification
- Knowledge / Agent Assist
- Escalation to Level 2
- Emergency Change
- Child Incident
- Resolution & documentation
- Knowledge Article creation
- SLA tracking
- Final validation

7.3 Test Cases

Test Case ID	Scenario	Steps	Expected Result	Actual Result	Pass/Fail
TC-001	Create & classify incident	Set Category/Urgency/CI; save	Correctly classified	Saved correctly	Pass
TC-002	Knowledge / Agent Assist	Search knowledge base	Relevant articles shown	3 articles surfaced	Pass
TC-003	Escalate to L2	Reassign to L2 group	Routed to L2	Visible in L2 queue	Pass
TC-004	Emergency Change	Create linked Change	Linked correctly	Change created & linked	Pass
TC-005	Child Incident	Create linked child	Linked correctly	Linked; context retained	Pass
TC-006	Resolve incident	Enter cause; close	Resolved & documented	Captured; closed	Pass
TC-007	Knowledge Article	Convert incident	Article created	Published & linked	Pass

Outcomes are as recorded in the original UAT. No screenshots were attached to the original UAT.

7.4 Bug Tracking

Bug ID	Description	Severity	Status	Resolution Details
BG-001	Knowledge Article link showed only after page refresh	Low	Closed	Not documented
BG-002	Emergency Change field was editable after the incident was closed	Medium	Closed	Not documented

BG-001 was a display issue: the link to the Knowledge Article appeared only after the page was refreshed. **BG-002** was a data-control issue: the Emergency Change field could still be edited after the incident was closed. Both are recorded as **Closed**. The original documentation does not describe the technical fix applied for either bug, so none is stated here.

7.5 UAT Conclusion

Final Notes (original): All test cases passed; two low/medium-severity issues found and resolved. Recommended for deployment.

- All seven test cases (TC-001 to TC-007) are reported as Pass.
- Two issues (BG-001 Low, BG-002 Medium) were identified and are recorded as Closed.
- The solution was recommended for deployment.

> **Please note:** Successful UAT with a recommendation for deployment is not the same as formal production deployment approval. No deployment approval, sign-off or release authorisation is recorded in this document. Production deployment approval status: not recorded.

Appendix A — Items Flagged for Verification

The following points are unclear or missing in the original documentation. Nothing has been assumed or filled in; please confirm or supply the information before final submission.

No.	Section	Item to verify
1	All sections	Team ID is blank in the original and is left blank.
2	All sections	The original contained no screenshots and no hyperlinks/URLs. All evidence areas are placeholders; insert genuine screenshots and any demo links.
3	1 — Salesforce	Number of records evaluated, how a "correct match" was determined, and how the 92% average confidence was calculated.
4	2 — AI	Dataset size, number of training records, train/validation split and retraining procedure (only "3 months of additional resolved incidents" is stated).
5	2 & 3	Whether the AI figures (91% / 88% / 93%) and the ML figures (92%, 0.91, 0.90, 0.90) come from the same data and run or from separate evaluations.
6	3 — ML	Confusion matrix, class-wise metrics, averaging method for precision/recall/F1, tuned values, and per-fold cross-validation results.
7	4 & 5	Types of the individual visualizations; split of the counts (6, 4, 5, 4) is as reported.
8	5 — Tableau	Original wrote DATEDIFF([Opened Date],[Resolved Date],'day'); shown here in Tableau argument order. Confirm against the workbook.
9	6 — GenAI	Preconditions for each test case; the acceptable response-time threshold for PT-01.
10	7 — UAT	Technical resolution of BG-001 and BG-002; formal deployment approval (not recorded).