SIM900_EVB kit_
User Guide_V1.03



Document Title:	SIM900 EVB kit User Guide
Version:	1.03
Date:	2010-12-22
Status:	Release
Document Control ID:	SIM900_EVB kit_User Guide_V1.03

General Notes

SIMCom offers this information as a service to its customers, to support application and engineering efforts that use the products designed by SIMCom. The information provided is based upon requirements specifically provided to SIMCom by the customers. SIMCom has not undertaken any independent search for additional relevant information, including any information that may be in the customer's possession. Furthermore, system validation of this product designed by SIMCom within a larger electronic system remains the responsibility of the customer or the customer's system integrator. All specifications supplied herein are subject to change.

Copyright

Contents

Contents 3
Version History 4
1. SIM900 EVB 5
2. EVB Accessory 7
3. Accessory Interface 8
3.1 Power Interface 8
3.2 Audio Interface 9
3.3 SIM card interface 10
3.4 Antenna Interface 11
3.5 Serial port Interface 11
3.6 LED Indicator 12
4. Test Interface 14
4.1 J103 14
4.2 J201 15
4.3 J104 16
5. EVB and Accessory 17
6. Illustration: 18
6.1 Power on module: 18
6.2 Registering Network and making a call 18
6.3 Downloading 22
6.4 Turn off 22

Figure Index

FIGURE 1: EVB TOP VIEW 5
FIGURE 2: EVB BOTTOM VIEW 6
FIGURE 3: EVB ACCESSORY 7
FIGURE 4: POWER INTERFACE 8
FIGURE 5: AUDIO INTERFACE 9
FIGURE 6: SIM CARD INTERFACE 10
FIGURE 7: ANTENNA INTERFACE 11
FIGURE 8: SERIAL PORTS 11
FIGURE 9: LED INDICATOR 12
FIGURE 10: TEST INTERFACE OVERVIEW 14
FIGURE 11: J103 INTERFACE 14
FIGURE 12: J201 INTERFACE 15
FIGURE 13: J104 INTERFACE 16
FIGURE 14: EVB AND ACCESSORY 17

Version History

Data	Version	Description of change	Author
2009-12-08	1.01	Origin	Lee
2010-07-01	1.02	§6.1 Add notice：You should equip four sets of screws for better grounding to achieve a better performance.	Jerry
2010-12-22	1.03	§6.2 Add the Hyper Terminal setting. Update the figures: 1,2,6,7,10,11,12,13	Jerry

SCOPE

This document describes how to use SIM900 EVB to do test; user can get useful info about the SIM900 EVB quickly through this document.

This document is subject to change without notice at any time.

1. SIM900 EVB



Figure 1: EVB TOP view



Figure 2: EVB BOTTOM view

A: DC jack
B: MAIN serial port
C: DEBUG serial port
D: SIM card holder
E: Test point
F: Antenna fix hole
G: SIM900-TE with SIM900 module interface
H: Module fix hole
I: Reset key
J: Power key
K: Charge switch
L: Download switch
M: Power switch
N: Headphones jack
O: Headset jack
P: Line in jack
Q: LED indicator

2. EVB Accessory



Figure 3: EVB Accessory

A: Antenna
B: Antenna cable
C: 5V DC adapter
D: Serial Port cable

3. Accessory Interface

3.1 Power Interface



Figure 4: Power Interface

Pin	Signal	I/O	Description
1	Adapter input	I	5V/2.0A DC source input

3.2 Audio Interface



Figure 5: Audio Interface

Headset interface:

Pin	Signal	I/O	Description
1	MIC1P	I	Positive microphone input
2	SPK1P	O	Positive receiver output
3	MIC1N	I	Negative microphone input
4	SPK1N	O	Negative receiver output

Earphone interface:

Pin	Signal	Input/Output	Description
5	MIC2P&SPK2P	I/O	Auxiliary audio input/output

Line in interface:

Pin	Signal	Input/Output	Description
6	Line in R/L	I	Line in inputl

3.3 SIM card interface



Figure 6: SIM card interface

3.4 Antenna Interface



Figure 7: Antenna Interface

3.5 Serial port Interface



Figure 8: Serial Ports

Serial Port 1——MAIN Interface
Serial Port 2——DEBUG Interface

Main Interface:

Pin	Signal	I/O	Description
1	DCD	O	Data carrier detection
2	TXD	O	Transmit data
3	RXD	I	Receive data
4	DTR	I	Data Terminal Ready
5	GND		GND
7	RTS	I	Request to Send
8	CTS	O	Clear to Send
9	RI	O	Ring Indicator

Debug Interface:

Pin	Signal	I/O	Description
2	DEBUG_TX	O	Transmit data
3	DEBUG_RX	I	Receive data
5	GND		GND

3.6 LED Indicator



Figure 9: LED Indicator

Working state of LED as list:

Name	Description	STATUS
Q1	Power ON/OFF indicator	Bright：EVB Power ON; Extinct: EVB Power OFF
Q2	Module status indicator	Bright: Module runs normally Extinct: System is powered down
Q3	GSM_NET status indicator	Blinking at a certain frequency according various GSM net status

4. Test Interface



Figure 10: Test interface overview

4.1 J103



Figure 11: J103 Interface

J103 Interface Pin List:

Pin	Signal	I/O	Description
1	DISP_D/C	O	Display data or address select
2	DISP_CS	O	Display select output
3	DISP_CLK	O	Display clock output
4	DISP_DATA	O	Display data
5	GPIO12	I/O	GPIO
6	ADC	I	ADC input
7	GPIO11	I/O	GPIO
8	TEMP_BAT	I	ADC input
9	SIMPRESENCE	I	SIM detect input
10	PWM1	O	PWM output 1
11	SDA	I/O	I2C BUS DATA
12	SCL	O	I2C BUS CLOCK

13	GND	/	GND
14	PWM2	O	PWM output 2

4.2 J201



Figure 12: J201 Interface

J201 Interface Pin List:

Pin	Signal	I/O	Description
1	TXD	O	Transmit data
2	RXD	I	Receive data
3	DCD	O	Data carrier detection
4	RI	O	Ring Indicator
5	CTS	O	Clear to Send
6	GND	/	GND
7	DTR	I	Data Terminal Ready
8	DEBUG_RX	I	Receive data
9	RTS	I	Request to Send
10	DEBUG_TX	O	Transmit data

4.3 J104



Figure 13: J104 Interface

J104 Interface Pin List:

Pin	Signal	I/O	Description
1	GPIO10	**I/O**	General purpose input and output
2	GPIO5	**I/O**	
3	GPIO9	**I/O**	
4	GPIO4	**I/O**	
5	GPIO8	**I/O**	
6	GPIO3	**I/O**	
7	GPIO7	**I/O**	
8	GPIO2	**I/O**	
9	GPIO6	**I/O**	
10	GPIO1	**I/O**	
11	PWRKEY_OUT	O	POWER KEY OUT
12	PWRKEY	I	POWER KEY IN
13	VDD_EXT	POWER	VEXT
14	VBAT	POWER	POWER

5. EVB and Accessory

The EVB and its accessory are equipped as the Figure 14

Figure 14: EVB and Accessory

6. Illustration:

6.1 Power on module:

(1) Connect the SIM900-TE to the 60pins connector on SIM900 EVB, plug in 5V DC adapter, switch S105 to "**ON"** state; keep S101 and S102 at "**OFF"** state,

(2) Press the PWRKEY for more than 1 second and then release, SIM900 module power on.

After the module is powered on, the light Q3 will flash at a certain frequency. Through the state of LED, you can judge registering status of the module. For detailed description, please refer to SIM900 HD spec.

Note: You should equip four sets of screws for better grounding to achieve a better performance.

6.2 Registering Network and making a call

(1) Connect the antenna to the SIM900-TE, insert SIM card and earphone.

(2) Connect the serial port cable to the MAIN serial port; Open the Hyper Terminal (AT command windows) on your computer.

First, check the serial port number:

My computer (right click) →Manage → Device Manager → Ports (COM&LPT)



Second, use the Hyper Terminal to call the module as following:

a. Open the HyperTerminal

START→ All Programs → Accessory →Communication → HyperTerminal.


Ben GU
Internet
Internet Explorer
E-mail
Microsoft Office Outl
Microsoft Office
Communicator 20
UltraEdit-32 Text Edi
SpyTracerV2-v2.7.2
TINA-VPN II
Source Insight 3.5
Microsoft Office Exce
bfloader_TD_7.4.5.e
All Programs
start
7-Zip
Accessories
Catalyst Control Center
Games
Intel® Matrix Storage Manager
LANDesk Management
Microsoft Office
Microsoft Office Live Meeting 2007
PDFCreator
PDFCreator Toolbar
SoundMAX
ST Wireless LAN
Startup
TINA-VPN II
TINA Remote access
Adobe Reader 9
Microsoft Office Communicator 2007
Microsoft Office Outlook
Outlook Express
Remote Assistance
Windows Media Player
Windows Movie Maker
Windows Search
UltraEdit
Accessibility
Entertainment
System Tools
Address Book
Calculator
Command Prompt
Notepad
Paint
Program Compatibility Wizard
Synchronize
Tour Windows XP
Windows Explorer
WordPad
Communications
HyperTerminal
Network Connections
Network Setup Wizard
New Connection Wizard
Remote Desktop Connection
Wireless Network Setup Wizard
HyperTerminal


New Connection - HyperTerminal
File Edit View Call Transfer Help
Connection Description
New Connection
Enter a name and choose an icon for the connection:
Name:
Icon:
OK
Cancel
Disconnected
Auto detect
Auto detect
SCROLL
CAPS
NUM
Capture
Print echo

b. Configure the serial port number



c. Set the baud rate and flow control



User can set the baud rate from 1200bps to 115200bps, and the flow control set to “None”

(3) Act on the step of running which mentioned above, power on the module, typing the AT command in the HyperTerminal, and then the SIM900 module will execute its corresponding function.

a. Connect the module.



Click the "**call**" icon.

b. Typing the AT command. When module is powered on with autobauding enabled, user must firstly send "AT" to synchronize the baud rate. The default setting of the module is autobauding.

c. Use AT command to make a call.



6.3 Downloading

Connect the serial port cable to the **DEBUG** serial port, plug 5V DC adapter, open the download tool and click the START key, switch the S105 and S102 to "**ON"** state.



6.4 Turn off

Turn off SIM900 module: press the PWRKEY for about 2 seconds, SIM900 module will be turned off.

Contact us:

Shanghai SIMCom Wireless Solutions Ltd.
Add: SIM Technology Building，No.633，Jinzhong Road，Changning District，Shanghai P.R. China 200335
Tel: +86 21 3235 3300
Fax: +86 21 3235 3301
URL: www.sim.com/wm