
INDEX

12-bit FAT entries 10-3 to 10-6
16-bit applications 5-1
16-bit FAT entries 10-3 to 10-6
32-bit applications 5-2
32-bit protected mode 1-2
8253 timer/counter chip 6-6
\$386.SYS 2-3, 2-4
\$NETBIOS.SYS 6-18
\$PIPE.SYS 6-18, 12-105
\$\$MASTER.SYS 2-2
\$\$MOS.SYS 2-1, 2-2

A

ADDDEV 12-23
ADDTASK
 API function (22) 13-2
 command 13-2
allocation of disk storage 10-3 to 10-6
ANSI escape sequences 7-6 to 7-8
applications interface
 16-bit 5-1
 32-bit 5-2
ASCII mode reads/writes 7-4

B

- BIOS parameter block (BPB) 12-16
- binary mode read/writes 7-3
- block device
 - block (BDB) 9-11
 - drivers 12-2
- boot record 10-9, 10-10
- boot sector 2-1, 10-2
- bootstrap procedure 2-1 to 2-3

C

- character device drivers 12-2
- clusters 10-3 to 10-6
- COM files 11-1
- COMMAND.COM 3-3
- communications
 - COM1 interrupt (IRQ4) 2-8
 - COM2 interrupt (IRQ3) 2-8
- compatibility considerations 3-8
- console
 - device driver 7-5 to 7-9
 - input, efficient 6-8
- context save area 3-1
- control-break handler interrupt 2-10
- current directory block (CDB) 9-7

D

data structure access 9-1, 13-1

design considerations, product 6-19

device driver

- creating 12-3

- design considerations 12-23

- device header fields 12-4 to 12-9

- establishing raw mode 13-8

- request header 12-10

- task-specific 12-23

- task switching 12-24

- task table 12-26

- types 12-2

device driver functions

- 0 - init function 12-14

- 1 - media check function 12-15

- 2 - build BPB function 12-16

- 3,4,8,9,12 - I/O functions 12-19

- 5 - read without dequeue function 12-19

- 6,10 - status functions 12-20

- 7,11 - flush functions 12-20

- 13,14 - open/close functions 12-20

- 15 - removable media function 12-21

- 19 - generic IOCTL function 12-21

- 23,24 - get/set logical device functions 12-22

directory entry fields 10-7, 10-8

DIS mode 6-12

disk

- data structures 10-1 to 10-10

- directory structure 10-7, 10-8

- I/O interrupt 2-9

divide by zero interrupt 2-6

E

error codes

- extended 8-98
- standard 8-99, 8-100

escape sequences 7-6 to 7-8

EXE files 11-2 to 11-4

executable files

- COM files 11-1
- EXE files 11-2 to 11-4

expanded memory driver 3-7

extended

- error codes 8-98
- memory 3-1
- services interrupt [INT38h & D4h] 2-12
(also see "system calls, extended services")

F

features

- of PC-MOS 1-1
- of Intel 80386 microprocessor 1-2

file

- allocation table (FAT) 10-3 to 10-6
- and record locking 6-2, 6-3
- control block (FCB) 6-2, 9-12
- handles 7-2 to 7-4
- I/O 7-1 to 7-9
- names 7-1
- sharing 6-2, 6-3

floppy disk drive interrupt (IRQ6) 2-8

FREEMEM 2-3, 3-7

G

global file block (GFB) 9-8
graphics attributes 7-8, 7-9

H

hard disk drive interrupt (IRQ5) 2-8

I

I/O

programming 6-5
trapping 6-5

IRQ handlers, placement 6-20

Intel 80386 microprocessor 1-1, 1-2, 4-1, 4-2

interfacing applications

16-bit 5-1

32-bit 5-2

interrupt

15H, function 4FH 6-17

17H, function 3 8-148

21H 8-4 to 8-109

(see "system calls, basic - INT 21H")

25H 8-3

26H 8-3

27H 8-3

38H 9-1

MOS entry point 8-33, 8-110

6 handler 12-106

8 2-7, 2-12, 6-14

9 2-7, 2-12, 6-16

D4H 2-12, 9-1

interrupts

- AT-class machines 2-6, 2-12

- handling 2-4

- trapped by more than one application/task 2-12

- trapped by MOS 2-5 to 2-12

intertask communication 6-18

K

kernel

- functions 2-1

- interrupt trapping 2-4 to 2-6

keyboard

- hardware interrupt (IRQ1) 2-7

- I/O interrupt 2-10

- polling 6-9

L

logical

- disk structure 10-2

- sectors 10-1

M

machine sharing 6-4

master boot record 10-9, 10-10

MEMDEV driver 2-2, 2-3, 3-1

memory

- context save area 3-1

- extended 3-1

- management 3-1, 3-5, 4-1

- map, w/o memory management 3-4

- map, with memory management 3-6

- organization 3-1 to 3-8

- task 3-1

- video areas 3-2

memory management device driver functions

- 1 - Allocate extended memory 12-97

- 2 - release extended memory 12-98

- 3 - logical memory remap 12-99

- 4 - unmap logical memory 12-100

- 5 - physical memory remap 12-101

- 6 - protect memory (80386 only) 12-102

- 7 - unprotect memory (80386 only) 12-103

- 8 - set I/O protection (80386 only) 12-104

- 9 - clear I/O protection (80386 only) 12-105

memory management interface 12-95, 12-96

MOSADM TMFACTOR 6-15

multi-purpose interrupt (IRQ2) 2-8

multi-tasking 6-1 to 6-19

N

native

- context area (NCA) 9-14
- mode 1-2, 3-8, 4-1, 5-2

NETBIOS

- driver, calls supported 12-91 to 12-94
- error recovery 12-90
- functions 12-88 to 12-90
- interface 12-80, 12-81

network control block (NCB) 12-81 to 12-87

O

operating system services interrupt

- basic 2-10
- extended 2-11

P

paging 1-2

partition table 10-9, 10-10

path names 7-1

PC-MOS

- features 1-1
- kernel 2-1 to 2-4

print screen interrupt 2-6

printer

- interrupt (IRQ7) 2-9
- I/O interrupt 2-10

product design considerations 6-19

program

- control-break exit address interrupt 2-11
 - critical error exit address interrupt 2-11
 - file structures 11-1 to 11-4
 - segment prefix (PSP) 9-13
 - terminate address interrupt 2-10
- protected mode 1-2
- PUSHF/FAR CALL calling method 13-3

R

- RAM data structures 9-1 to 9-14
- raw mode 13-8
- read disk sector(s) interrupt 2-11, 8-3
- record lock block (RLB) 6-3, 9-10

S

- scan code intercepts 6-17
- sectors 10-3 to 10-6
- serial device driver functions
- 0 (80h) - initialize port 12-54
 - 1 (81h) - write a character 12-55
 - 2 (82h) - read a character 12-56
 - 3 (83h) - return port status 12-57
 - 4 (84h) - extended port init 12-58
 - 5 (85h) - change port protocol 12-59
 - 6 (86h) - driver ID 12-61
 - 7 (87h) - send RS232C "break" 12-62
 - 8 (88h) - input status check 12-63
 - 9 (89h) - reset I/O buffer pointers 12-64
 - 10 (8Ah) - input queue check 12-65

- 11 (8Bh) - disable port 12-66
- 12 (8Ch) - return current port parameters 12-68
- 13 (8Dh) - register port with terminal 12-69
- 14 (8Eh) - string output 12-70
- 15 (8Fh) - string input 12-71
- 16 (90h) - link to another serial driver 12-72
- 17 (91h) - write modem control registers 12-73
- 18 (92h) - return driver description 12-74
- 19 (93h) - selective buffer flush 12-75
- 20 (94h) - output queue check 12-76
- 21 (95h) - output the character in AL 12-77
- 22 (96h) - receive a character into AL 12-78
- 23 (97h) - declare port ownership 12-79

serial device interface 12-49 to 12-53

serial I/O interrupt 2-9

standard

- devices 7-1 to 7-9
- error codes 8-99, 8-100

system

- calls 8-1 to 8-148
- control block (SCB) 9-3, 13-2
- differences 4-1
- files 2-1, 2-2
- memory pool (SMP) 9-1
- services interrupt 2-9
- timer interrupt (IRQ0) 2-7, 6-14

system calls, basic - INT 21H

- 00H - terminate program 8-5
- 01H - keyboard read 8-6
- 02H - display character 8-7
- 03H - auxiliary device read 8-8
- 04H - auxiliary device write 8-9
- 05H - printer write 8-10
- 06H - raw console I/O 8-11
- 07H - raw console input - no echo 8-12
- 08H - read keyboard - no echo 8-13
- 09H - string write 8-14
- 0AH - buffered keyboard read 8-15
- 0BH - standard input status check 8-16
- 0CH - KB buffer clear - call KB function 8-17
- 0DH - disk buffer flush 8-18
- 0EH - set default disk 8-19
- 19H - get current drive 8-20
- 1AH - set disk transfer area (DTA) address 8-21
- 1CH - get disk allocation information 8-22
- 25H - set interrupt vector 8-23
- 2AH - get current date 8-24
- 2BH - set current date 8-25
- 2CH - get time of day 8-26
- 2DH - set time of day 8-27
- 2EH - verify on/off 8-28
- 2FH - get disk transfer address (DTA) 8-29
- 30H - get version number 8-30
- 31H - terminate and stay resident (TSR) 8-31
- 33H - get/set break switch 8-32
- 34H - get "INMOS" flag pointer 8-33

35H - get interrupt vector 8-34
36H - get disk space information 8-35
38H - get/set country information 8-36
39H - make directory 8-40
3AH - remove directory 8-42
3BH - set default directory 8-43
3CH - create file 8-44
3DH - open file 8-46
3EH - close file 8-50
3FH - read 8-51
40H - write 8-53
41H - delete file 8-55
42H - seek file position 8-56
43H - get/set file attributes 8-57
44H - device I/O control 8-59 to 8-74
45H - file handle duplicate 8-75
46H - force duplicate handle 8-76
47H - get default directory 8-77
48H - memory allocation (8086 mode only) 8-78
49H - free memory (8086 mode only) 8-79
4AH - alter allocated memory blocks (8086) 8-80
4BH - program load/execute (8086 only) 8-81
4CH - terminate program 8-86
4DH - request return code 8-87
4EH - find first directory entry 8-88
4FH - find next directory entry 8-90
54H - interrogate verify switch 8-92
56H - rename file 8-93
57H - get or change file date/time 8-95
59H - get extended error code 8-97

- 5AH - create temporary file 8-101
- 5BH - create new file 8-103
- 5CH - lock or unlock records 8-105
- 62H - get program segment prefix (PSP) address 8-107
- 67H - set handle count 8-108
- 68H - commit file to disk 8-109
- system calls, extended services (INT 38H & INT D4H)
 - 02H - get system control block (SCB) address 8-111
 - 03H - get or change extended directory info 8-112
 - 04H - get task control block (TCB) address 8-114
 - 07H - wait for event 8-115
 - 10H - mode change 8-119
 - 11H - allocate extended memory (Native mode) 8-121
 - 12H - deallocate extended memory (Native mode) 8-123
 - 13H - get alias (Native mode only) 8-124
 - 16H - set/reset IRQ reservation 8-125
 - 19H - return task ID 8-126
 - 1AH - set/read/exchange priority 8-127
 - 1BH - set/read/exchange time slice 8-128
 - 1CH - clear/set/read keyboard mode 6-14, 8-129
 - 1DH - return current program name 8-130
 - 1EH - return user name and class 8-131
 - 1FH - return task partition info 8-132
 - 20H - return port & baud rate info 8-133
 - 21H - remove a task 8-134
 - 22H - add a task 8-135
 - 23H - change terminal driver 8-139
 - 25H - identify device driver location 8-140
 - 26H - get SCB address segment/selector 8-141
 - 27H - get TCB address segment/selector 8-142

28H - read control block data 8-143
29H - write control block data 8-144
2AH - swap control block data 8-145
2CH - get/set spooler parameters 8-146
2DH - return maximum task size 8-147
interrupt 17H, function 3 8-148

T

task

control block (TCB) 7-5, 9-3 to 9-6, 13-2
file block (TFB) 9-9
linked list 13-3
unregistration 6-21
waiting 6-4

terminal device driver functions

0 - register a port 12-31
1 - input keyboard scan code 12-32
2 - clear current scan code 12-33
3 - set terminal mode 12-34
4 - set cursor type 12-35
5 - position cursor 12-36
6 - screen scroll up 12-37
7 - screen scroll down 12-38
8 - write character/attribute 12-39
9 - set color palette 12-40
10 - write TTY 12-41
11 - write string of characters 12-42
12 - re-display window 12-43

13 - write character 12-44
14 - read character/attribute 12-45
15 - get screen 12-46
16 - send character to terminal's printer 12-47
17 - send string to terminal's printer 12-48
terminal interface 12-27 to 12-30
terminate
 and stay resident interrupt 2-11, 8-3
 and stay resident programs 6-19
 application interrupt 2-10
time
 delay 13-10
 measurement 6-15, 6-16
timer/counter chip 6-6
timer interrupt (IRQ0) 6-14
timer-tick handler interrupt 2-10

V

video
 I/O interrupt 2-9
 memory 3-2
virtual-8086 mode 1-2

W

wait for event 13-10
write disk sector(s) interrupt 2-11, 8-3

This page intentionally left blank.