# More System calls and Page faults

ECE 469, Feb 13


**Aravind Machiry** 




# Recap: Syscalls

- An API of an OS
- User-level Application calls functions in kernel
  - Open
  - Read
  - Write
  - Exec
  - Send
  - Recv
  - Socket
  - Etc...


















printf("ECE469")

A library call in ring 3
















printf("ECE469")

A library call in ring 3

sys\_write(1, "ECE469", 6);
A system call, From ring 3















printf("ECE469")


A library call in ring 3

sys\_write(1, "ECE469", 6);

A system call, From ring 3

Interrupt!, switch from ring3 to ring0















printf("ECE469")


A library call in ring 3


sys\_write(1, "ECE469", 6);

A system call, From ring 3

Interrupt!, switch from ring3 to ring0

A kernel function do\_sys\_write(1, "ECE469", 6)







printf("ECE469")


A library call in ring 3

sys\_write(1, "ECE469", 6);

A system call, From ring 3

Interrupt!, switch from ring3 to ring0

A kernel function do\_sys\_write(1, "ECE469", 6)



```
int main() {
   printf("ECE469");
}
```



printf("ECE469")


A library call in ring 3

sys\_write(1, "ECE469", 6);

A system call, From ring 3

Interrupt!, switch from ring3 to ring0

A kernel function do\_sys\_write(1, "ECE469", 6)




int main() {
 printf("ECE469");
}

# System calls via Interrupt Handler



- Call gate
  - System call can be invoked only with trap handler
    - int \$0x30 in JOS
    - int \$0x80 in Linux (32-bit)
    - int \$0x2e in Windows (32-bit)
    - sysenter/sysexit (32-bit)
    - syscall/sysret (64-bit)
- OS performs checks if userspace is doing a right thing
  - Before performing important ring 0 operations
  - E.g., accessing hardware..




# System calls via Interrupt Handler



- Call gate
  - System call can be invoked only with trap handler
    - int \$0x30 in JOS
    - int \$0x80 in Linux (32-bit)
    - int \$0x2e in Windows (32-bit)
    - sysenter/sysexit (32-bit)
    - syscall/sysret (64-bit)

int \$0x30
CHECK!!



- OS performs checks if userspace is doing a right thing
  - Before performing important ring 0 operations
  - E.g., accessing hardware..

## Implementing Syscalls in JOS



- See kern/syscall.c
- void sys\_cputs (const char \*s, size\_t len)
  - Print a string in s to the console
- int sys\_cgetc(void)
  - Get a character from the keyboard
- envid\_t sys\_getenvid(void)
  - Get the current environment ID (process ID)
- int sys env destroy(envid t)
  - Kill the current environment (process)

## Implementing Syscalls in JOS



- See kern/syscall.c
- void sys\_cputs(const char \*s, size\_t len)
  - Print a string in s to the console
- int sys\_cgetc(void)—
  - Get a character from the keyboard
- envid\_t sys\_getenvid(void)
  - Get the current environment ID (process ID)
- int sys\_env\_destroy(envid\_t)
  - Kill the current environment (process)

Required for Implementing scanf, printf, etc...

- How can we pass arguments to syscalls?
  - Remember syscalls are implemented as interrupts!

- How can we pass arguments to syscalls?
  - Remember syscalls are implemented as interrupts!

**General Purpose Registers!!!** 



- In JOS
  - eax = system call number
  - $\circ$  edx = 1<sup>st</sup> argument
  - $\circ$  ecx =  $2^{nd}$  argument
  - ebx = 3<sup>rd</sup> argument
  - edi = 4<sup>th</sup> argument
  - esi = 5<sup>th</sup> argument
- E.g., calling sys\_cputs("asdf", 4);
  - $\circ$  eax = 0
  - edx = address of "asdf"
  - $\circ$  ecx = 4
  - ebx, edi, esi = not used
- And then
  - o Run int \$0x30

```
/* system call numbers */
enum {
    SYS_cputs = 0,
    SYS_cgetc,
    SYS_getenvid,
    SYS_env_destroy,
    NSYSCALLS
};
```



- In JOS
  - eax = system call number
  - $\circ$  edx = 1<sup>st</sup> argument
  - $\circ$  ecx =  $2^{nd}$  argument
  - ebx = 3<sup>rd</sup> argument
  - edi = 4<sup>th</sup> argument
  - esi = 5<sup>th</sup> argument
- E.g., calling sys\_cputs("asdf", 4);
  - $\circ$  eax = 0
  - edx = address of "asdf"
  - ecx = 4
  - ebx, edi, esi = not used
- And then
  - $\circ$  Run int \$0x30

```
/* system call numbers */
enum {
    SYS_cputs = 0,
    SYS_cgetc,
    SYS_getenvid,
    SYS_env_destroy,
    NSYSCALLS
};
```

Will add more as our lab implementation progresses



- In Linux x86 (32-bit)
  - eax = system call number
  - ebx = 1<sup>st</sup> argument
  - ecx = 2<sup>nd</sup> argument
  - edx = 3<sup>rd</sup> argument
  - esi = 4<sup>th</sup> argument
  - edi = 5<sup>th</sup> argument
- See table
  - <a href="https://syscalls.kernelgrok.com/">https://syscalls.kernelgrok.com/</a> : lists 337 system calls...

0	sys_restart_syscall	0x00
1	sys_exit	0x01
2	sys_fork	0x02
3	sys_read	0x03
4	sys_write	0x04
5	sys_open	0x05
6	sys_close	0x06
7	sys_waitpid	0x07
8	sys_creat	0x08
9	sys_link	0x09
10	sys_unlink	0x0a
11	sys_execve	0x0b

## Handling arguments to Syscalls



```
E.g., calling sys_cputs("asdf", 4);
eax = 0
edx = address of "asdf"
ecx = 4
ebx, edi, esi = not used
```

- And then
  - Run int \$0x30
- At interrupt handler
  - · Read syscall number from the eax of tf
    - syscall number is 0 -> calling SYS\_cputs
  - Read 1<sup>st</sup> argument from the edx of tf
    - Address of "adsf"
  - Read 2<sup>nd</sup> argument from ecx of tf
    - 4
  - call sys\_cputs("asdf", 4) // in kernel

```
/* system call numbers */
enum {
    SYS_cputs = 0,
    SYS_cgetc,
    SYS_getenvid,
    SYS_env_destroy,
    NSYSCALLS
};
```

## **Invoking Syscalls**

- Set all arguments in the registers
  - Order: edx ecx ebx edi esi
- int \$0x30 (in JOS)
  - Software interrupt 48
- int \$0x80 (in 32bit Linux)
  - Software interrupt 128

User calls a function



- User calls a function
  - cprintf -> calls sys\_cputs()

- User calls a function
  - cprintf -> calls sys\_cputs()
- sys\_cputs() at user code will call syscall() (lib/syscall.c)
  - This syscall() is at lib/syscall.c

- User calls a function
  - cprintf -> calls sys\_cputs()
- sys\_cputs() at user code will call syscall() (lib/syscall.c)
  - This syscall() is at lib/syscall.c
  - Set args in the register and then

- User calls a function
  - cprintf -> calls sys\_cputs()
- sys\_cputs() at user code will call syscall() (lib/syscall.c)
  - This syscall() is at lib/syscall.c
  - Set args in the register and then
- int \$0x30

- User calls a function
  - cprintf -> calls sys\_cputs()
- sys\_cputs() at user code will call syscall() (lib/syscall.c)
  - This syscall() is at lib/syscall.c
  - Set args in the register and then
- int \$0x30

Now kernel execution starts...

- User calls a function
  - cprintf -> calls sys\_cputs()
- sys\_cputs() at user code will call syscall() (lib/syscall.c)
  - This syscall() is at lib/syscall.c
  - Set args in the register and then
- int \$0x30

Now kernel execution starts...

```
struct Trapframe {
    struct PushRegs tf_regs;
    uint16_t tf_es;
    uint16_t tf_padding1;
    uint16_t tf_ds;
    uint16_t tf_padding2;
    uint32_t tf_trapno;
    /* below here defined by
    uint32_t tf_err;
    uintptr_t tf_eip;
    uint16_t tf_cs:
    uint16_t tf_padding3;
    uint32_t tf_eflags;
    /* below here only when
    uintptr_t tf_esp;
    uint16_t tf_ss;
    uint16_t tf_padding4;
    _attribute__((packed));
```

CPU gets software interrupt



```
struct Trapframe {
    struct PushReas tf_reas;
    uint16_t tf_es;
    uint16_t tf_padding1;
    uint16_t tf_ds;
    uint16_t tf_padding2;
    uint32_t tf_trapno;
    /* below here defined by
    uint32_t tf_err;
    uintptr_t tf_eip;
    uint16_t tf_cs;
    uint16_t tf_padding3;
    uint32_t tf_eflags;
    /* below here only when
    uintptr_t tf_esp;
    uint16_t tf_ss;
    uint16_t tf_padding4;
   _attribute__((packed));
```

- CPU gets software interrupt
- TRAPHANDLER\_NOEC(T\_SYSCALL...)



```
struct Trapframe {
    struct PushReas tf_reas;
    uint16_t tf_es;
    uint16_t tf_padding1;
    uint16_t tf_ds;
    uint16_t tf_padding2;
    uint32_t tf_trapno;
    /* below here defined by
    uint32_t tf_err;
    uintptr_t tf_eip;
    uint16_t tf_cs;
    uint16_t tf_padding3;
    uint32_t tf_eflags;
    /* below here only when
    uintptr_t tf_esp;
    uint16_t tf_ss;
    uint16_t tf_padding4;
   _attribute__((packed));
```

- CPU gets software interrupt
- TRAPHANDLER\_NOEC(T\_SYSCALL...)
- \_alltraps()



```
struct Trapframe {
    struct PushReas tf_reas;
    uint16_t tf_es;
    uint16_t tf_padding1;
    uint16_t tf_ds;
    uint16_t tf_padding2;
    uint32_t tf_trapno;
    /* below here defined by
    uint32_t tf_err;
    uintptr_t tf_eip;
    uint16_t tf_cs;
    uint16_t tf_padding3;
    uint32_t tf_eflags;
    /* below here only when
    uintptr_t tf_esp;
    uint16_t tf_ss;
    uint16_t tf_padding4;
   _attribute__((packed));
```

- CPU gets software interrupt
- TRAPHANDLER\_NOEC(T\_SYSCALL...)
- \_alltraps()
- trap()



```
struct Trapframe {
    struct PushReas tf_reas;
    uint16_t tf_es;
    uint16_t tf_padding1;
    uint16_t tf_ds;
    uint16_t tf_padding2;
    uint32_t tf_trapno;
    /* below here defined by
    uint32_t tf_err;
    uintptr_t tf_eip;
    uint16_t tf_cs;
    uint16_t tf_padding3;
    uint32_t tf_eflags;
    /* below here only when
    uintptr_t tf_esp;
    uint16_t tf_ss;
    uint16_t tf_padding4;
   _attribute__((packed));
```

- CPU gets software interrupt
- TRAPHANDLER\_NOEC(T\_SYSCALL...)
- \_alltraps()
- trap()
- trap\_dispatch()



```
struct Trapframe {
    struct PushReas tf_reas;
    uint16_t tf_es;
    uint16_t tf_padding1;
    uint16_t tf_ds;
    uint16_t tf_padding2;
    uint32_t tf_trapno;
    /* below here defined by
    uint32_t tf_err;
    uintptr_t tf_eip;
    uint16_t tf_cs;
    uint16_t tf_padding3;
    uint32_t tf_eflags;
    /* below here only when
    uintptr_t tf_esp;
    uint16_t tf_ss;
    uint16_t tf_padding4;
   _attribute__((packed));
```

- CPU gets software interrupt
- TRAPHANDLER\_NOEC(T\_SYSCALL...)
- \_alltraps()
- trap()
- trap\_dispatch()
  - Get registers that store arguments from struct Trapframe \*tf



```
struct Trapframe {
    struct PushReas tf_reas;
    uint16_t tf_es;
    uint16_t tf_padding1;
    uint16_t tf_ds;
    uint16_t tf_padding2;
    uint32_t tf_trapno;
    /* below here defined by
    uint32_t tf_err;
    uintptr_t tf_eip;
    uint16_t tf_cs;
    uint16_t tf_padding3;
    uint32_t tf_eflags;
    /* below here only when
    uintptr_t tf_esp;
    uint16_t tf_ss;
    uint16_t tf_padding4;
    _attribute__((packed));
```

- CPU gets software interrupt
- TRAPHANDLER\_NOEC(T\_SYSCALL...)
- \_alltraps()
- trap()
- trap\_dispatch()
  - Get registers that store arguments from struct Trapframe \*tf
  - Call syscall() using those registers
    - This syscall() is at kern/syscall.c



```
struct Trapframe {
    struct PushReas tf_reas;
    uint16_t tf_es;
    uint16_t tf_padding1;
    uint16_t tf_ds;
    uint16_t tf_padding2;
    uint32_t tf_trapno;
    /* below here defined by
    uint32_t tf_err;
    uintptr_t tf_eip;
    uint16_t tf_cs;
    uint16_t tf_padding3;
    uint32_t tf_eflags;
    /* below here only when
    uintptr_t tf_esp;
    uint16_t tf_ss;
    uint16_t tf_padding4;
    _attribute__((packed));
```

# **Syscall Return from Kernel**

Finishing handling of syscall (return of syscall())

# **Syscall Return from Kernel**



Finishing handling of syscall (return of syscall())

- trap() calls env\_pop\_tf()
  - Get back to the user environment!



Finishing handling of syscall (return of syscall())

- trap() calls env\_pop\_tf()
  - Get back to the user environment!

•env\_pop\_tf()

```
void
env_pop_tf(struct Trapframe *tf)
{
    asm volatile(
        "\tmovl %0,%%esp\n"
        "\tpopal\n"
        "\tpopl %%es\n"
        "\tpopl %%ds\n"
        "\taddl $0x8,%%esp\n" /* skip tf_trapno and tf_errcode */
        "\tiret\n"
        : "g" (tf) : "memory");
    panic("iret failed"); /* mostly to placate the compiler */
}
```



- trap() calls env\_pop\_tf()
  - Get back to the user environment!

- •env\_pop\_tf()
  - Runs iret

```
void
env pop tf(struct Trapframe *tf)
{
    asm volatile(
        "\tmovl %0,%%esp\n"
        "\tpopal\n"
        "\tpopl %%es\n"
        "\tpopl %%ds\n"
        "\taddl $0x8,%%esp\n" /* skip tf_trapno and tf_errcode */
        "\tiret\n"
        : "g" (tf) : "memory");
    panic("iret failed"); /* mostly to placate the compiler */
}
```

- trap() calls env\_pop\_tf()
  - Get back to the user environment!

- •env\_pop\_tf()
  - Runs iret

- trap() calls env\_pop\_tf()
  - Get back to the user environment!

- •env\_pop\_tf()
  - Runs iret

- trap() calls env\_pop\_tf()
  - Get back to the user environment!

- •env\_pop\_tf()
  - Runs iret
- Back to Ring 3!

- Execution...
- int \$0x30
- Call trap gate
- Handle trap!
- Pop context
- iret
- Execution resumes...

- Execution...
- int \$0x30
- Call trap gate
- Handle trap!
- Pop context
- iret
- Execution resumes...

Ring 3

- Execution...
- int \$0x30
- Call trap gate
- Handle trap!
- Pop context
- iret
- Execution resumes...

Ring 3

Ring 0



	_						
•	Ŀχ	Δ	$\sim$ 1	111	$\cap$	n	
	ᆫᄼ		ι	a u			

• int \$0x30 Ring 3

- Call trap gate
- Handle trap!
- Pop context
- iret
- Execution resumes...

Ring 0

Ring 3

#### Page faults



- Occurs when paging (address translation) fails
  - !(pde&PTE\_P) or !(pte&PTE\_P): Present bit not set
    - Automated extension of runtime stack
  - Write access but !(pte&PTE\_W): access violation
  - Access from user but !(pte&PTE\_U): protection violation

## Page faults Handling (2): Copy-On-Write (CoW)



- Copy-on-Write (CoW)
  - Technique to reduce memory footprint
  - Share pages read-only
  - Create a private copy when the first write access happens
- Memory Swapping
  - Use disk as extra space for physical memory
  - Limited RAM Size: 16GB?
  - We have a bigger storage: 1T SSD, Hard Disk, online storage, etc.
  - Can we store some 'currently unused but will be used later' part into the disk?
    - Then we can store only the active part of data in memory

#### **Program in Memory**

- .text
  - Code area. Read-only and executable
- .rodata
  - Data area, Read-only and not executable
- .data
  - Data area, Read/Writable (not executable)
  - Initialized by some values
- .bss (uninitialized data)
  - Data area, Read/Writable (not executable)
  - Initialized as 0



.bss (RW-)

.data (RW-)

.rodata (R--)



.bss (RW-)

.data (RW-)

.rodata (R--)



.bss (RW-)

.data (RW-)

.rodata (R--)

.text (R-X)

#### Process 1

.bss (RW-)

.data (RW-)

.rodata (R--)



.bss (RW-)

.data (RW-)

.rodata (R--)

.text (R-X)

#### Process 1

.bss (RW-)

.data (RW-)

.rodata (R--)

.text (R-X)

#### Process 2

.bss (RW-)

.data (RW-)

.rodata (R--)



Do we need to copy the same data for each process creation?

Process 2

.bss (RW-)

.data (RW-)

.rodata (R--)

.text (R-X)

.bss (RW-)

Process 1

.data (RW-)

.rodata (R--)

.text (R-X)

.bss (RW-)

.data (RW-)

.rodata (R--)

#### **Sharing pages by marking read-only**




Set page table to map the same physical address to share contents

.bss (RW-) .data (RW-) .rodata (R--) .text (R-X)

#### **Sharing pages by marking read-only**




• Set page table to map the same physical address to share contents




#### **Sharing pages by marking read-only**



Set page table to map the same physical address to share contents




#### What about writes?




#### What about writes?





#### What about writes?









- Read CR2
  - A fault from one of the shared location!
- Read Error code
  - Write on read-only memory
    - Hmm... the process requires a private copy! (we actually mark if COW is required in PTE)
- ToDo: create a writable, private copy for that process!
  - Map a new physical page (page\_alloc, page\_insert)
  - Copy the contents
  - Mark it read/write
  - Resume...






How can Process 1 write on .bss??




.bss (RW-)

Write

Page fault!





#### **Benefits**



- Can reduce time for copying contents that is already in some physical memory (page cache)
- Can reduce actual use of physical memory by sharing code/read-only data among multiple processes
  - 1,000,000 processes, requiring only 1 copy of .text/.rodata
- At the same time
  - Can support sharing of writable pages (if nothing has written at all)
  - Can create private pages seamlessly on write

#### **Benefits**

By exploiting page fault and its handler, we can implement copy-on-write, a mechanism that can reduce physical memory usage by sharing pages of same contents among multiple processes.

- Can reduce time for copying contents that is already in some physical memory (page cache)
- Can reduce actual use of physical memory by sharing code/read-only data among multiple processes
  - 1,000,000 processes, requiring only 1 copy of .text/.rodata
- At the same time
  - Can support sharing of writable pages (if not has written at all)
  - Can create private pages seamlessly on write


#### Handling low memory

Suppose you have 8GB of main memory

- Can you run a program that its program size is 16GB?
  - Yes, you can load them part by part
  - This is because we do not use all of data at the same time
- Can your OS do this execution seamlessly to your application?

# **Memory Hierarchy**







#### **Memory Swapping**

• Use disk as backing store under memory pressure


## **Memory Swapping**




#### Memory Swapping - Removing a page




## Memory Swapping - Removing a page



## Memory Swapping - Removing a page



# Memory Swapping - Removing a page





Page fault handler



- Page fault handler
  - Read CR2 (get address, 0xf0200000)



- Page fault handler
  - Read CR2 (get address, 0xf020000)
  - Read error code



- Page fault handler
  - Read CR2 (get address, 0xf0200000)
  - Read error code
- If error code says that the fault is caused by non-present page and



- Page fault handler
  - Read CR2 (get address, 0xf0200000)
  - Read error code
- If error code says that the fault is caused by non-present page and
- The faulting page of the current process is stored in the disk



- Page fault handler
  - Read CR2 (get address, 0xf0200000)
  - Read error code
- If error code says that the fault is caused by non-present page and
- The faulting page of the current process is stored in the disk
  - Lookup disk if it swapped put 0xf0200000 of this environment (process)




- Page fault handler
  - Read CR2 (get address, 0xf0200000)
  - Read error code
- If error code says that the fault is caused by non-present page and
- The faulting page of the current process is stored in the disk
  - Lookup disk if it swapped put 0xf0200000 of this environment (process)
    - This must be per process because virtual address is per-process resource





- Page fault handler
  - Read CR2 (get address, 0xf0200000)
  - Read error code
- If error code says that the fault is caused by non-present page and
- The faulting page of the current process is stored in the disk
  - Lookup disk if it swapped put 0xf0200000 of this environment (process)
    - This must be per process because virtual address is per-process resource
- Load that page into physical memory





- Page fault handler
  - Read CR2 (get address, 0xf0200000)
  - Read error code
- If error code says that the fault is caused by non-present page and
- The faulting page of the current process is stored in the disk
  - Lookup disk if it swapped put 0xf0200000 of this environment (process)
    - This must be per process because virtual address is per-process resource
- Load that page into physical memory
- Map it and then continue!











## **Page Fault**



- Is generated when there is a memory error (regarding paging)
- Is an exception that can be recovered
  - And user program may resume the execution

- Is useful for implementing
  - Automatic stack allocation
  - Copy-on-write (will do in Lab4)
  - Swapping