


Seok-Oh Jeong, In Heok Lee, and Jay W. Rojewski  
University of Georgia

# The R Workshop


Applying the Integrated Suite of Software  
Facilities for Statistical Computing and Graphics

University of Georgia  
Department of Workforce Education, Leadership, and Social Foundations  
College of Education Research Office




January 23-January 24, 2012

January 23-January 24, 2012



## 5. Advanced Programming

University of Georgia  
Department of Workforce Education, Leadership, and Social Foundations  
College of Education Research Office



## Conditional Execution

- A conditional statement by 'if-else'

```
> if (x<3) print("x<3") else print("x>4")
```

- Commands can be grouped by braces

```
> x <- 4
> if ( x < 3 ) {print("x<3"); z <- "M"} else
{print("x>3"); z <- "F"}
```

Advanced Programming



## Iteration, loop

- Loop: A repeatedly executed instruction cycle
- for-loop: loop over all elements in a vector

```
x <- 1:10
n <- length(x)
y <- rep(0, n)
for ( i in 1:n ) {
  y[i] <- x[i]^2
}
z <- x^2
print(cbind(y, z))
```

Advanced Programming



## Iteration, loop

- while-loop: for which we don't know in advance how many iterations there will be

```
n <- 0
sum.so.far <- 0
while ( sum.so.far <= 1000 ) {
  n <- n+1
  sum.so.far <- sum.so.far + n
}
print(c(n, sum.so.far))
sum(1:45)
```

✓ **Whenever possible, try to avoid loops!**

Advanced Programming



## Applying a function to every row/column

- To apply a function to every row[or column], use `apply()`.

```
> A <- matrix(1:20, 4, 5)
> apply(A, 1, sum)      # to every row
> apply(A, 2, sum)      # to every column
```

Advanced Programming



# Writing New Functions

```
my.stat <- function(x)
{
  m <- mean(x); s <- sd(x)
  res <- list(x=x, m=m, s=s)

  par(mfrow=c(1,2))
  boxplot(x, main="Boxplot")
  hist(x, prob=T, col="lightgray", main="Histogram",
       xlab="data")
  z <- seq(from=min(x), to=max(x), by=0.01)
  lines(z, dnorm(z, mean=3, sd=1), col=2, lwd=3, lty=2)
  return(res)
}

X <- rnorm(1000, mean=3, sd=1)
my.stat(x=X)
```

Advanced Programming

