Expt-4

# **Create UDF (User Defined Functions) in Apache Pig and execute** it in MapReduce / HDFS mode

#### AIM:

To create UDF in Apache Pig and execute it in MapReduce/HDFS mode.

#### **Procedure:**

# Step 1: Install and Configure Apache Pig

1. Download Apache Pig:

# Download the latest version of Pig from the official website:

wget https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz

2. Extract Pig:

tar xvzf pig-0.16.0.tar.gz

3. Move Pig Directory:

## Move the extracted Pig files to a dedicated folder:

sudo mv pig-0.16.0 /usr/local/pig

4. Set Environment Variables:

## Edit the .bashrc file to set up Pig environment variables:

nano ~/.bashrc

# **Append the following lines:**

```
export PIG_HOME=/usr/local/pig
export PATH=$PATH:$PIG_HOME/bin
export PIG_CLASSPATH=$HADOOP_HOME/conf
```

## Apply the changes:

source ~/.bashrc

5. Verify Pig Installation:

#### Run the following command to verify if Pig has been installed correctly:

pig -version

#### **Step 2: Create Sample Data for the Pig Job**

1. **Create a Sample Data File**: Create a sample text file (sample.txt) with some dummy data:

nano sample.txt

## Add the following content:

- 1,John
- 2,Jane
- 3,Joe
- 4,Emma
- 2. **Upload the Data File to HDFS**: Upload the sample file to Hadoop's distributed file system (HDFS):

hdfs dfs -mkdir /piginput

hdfs dfs -put sample.txt /piginput

## **Step 3: Write Pig Script for the UDF**

1. Create the Pig Script:

Create a new Pig script (demo pig.pig):

nano demo pig.pig

Write the following code in the script to load and display the data:

pig

-- Load data from HDFS

data = LOAD '/piginput/sample.txt' USING PigStorage(',') AS (id:int, name:chararray);

-- Display the loaded data

DUMP data;

## **Step 4: Write the UDF in Python**

1. Create the Python UDF:

Create a Python file (uppercase udf.py) to convert text to uppercase:

nano uppercase udf.py

```
def uppercase(text):
    return text.upper()

if __name__ == "__main__":
    import sys
    for line in sys.stdin:
        line = line.strip()
        print(uppercase(line))
```

## 2. Upload the Python UDF to HDFS:

# **Upload the UDF to HDFS:**

hdfs dfs -mkdir /udfs hdfs dfs -put uppercase\_udf.py /udfs

## **Step 5: Update Pig Script to Use UDF**

1. Modify the Pig Script to Include UDF:

Edit the demo\_pig.pig script to register the UDF and process the data:

nano demo\_pig.pig

Modify the script as follows:

pig

## -- Register the Python UDF script

REGISTER '/udfs/uppercase udf.py' USING jython AS myudf;

-- Load data from HDFS

data = LOAD '/piginput/sample.txt' USING PigStorage(',') AS (id:int, name:chararray)

-- Apply UDF to convert names to uppercase

uppercased\_data = FOREACH data GENERATE
myudf.uppercase(name);

-- Display the transformed data

DUMP uppercased\_data;

## **Step 6: Run the Pig Script**

1. Run the Pig Script:


# Run the Pig script using the following command:

pig -x mapreduce demo pig.pig

## 2. View Output

hdfs dfs -cat /pigoutput/part-m-00000

#### **OUTPUT:**



#### **RESULT:**

Thus, UDF in Apache Pig has been created and executed in MapReduce/HDFS mode successfully.