

## Styles and CSS

- Styles are set of attributes defined for HTML elements to make the presentation more interactive and responsive.
- HTML elements have attributes but limited in functionality, style attributes make HTML more effective. They extend HTML element.
- Styles can be defined in 3 ways
  - Inline Styles
  - Embedded Styles
  - External Style Sheet

### Inline Styles:

- The styles are defined for elements by using “style” attribute.
- Every element has its own individual styles.
- The styles defined for one element can't be re-used for other elements.
- These styles are faster in rendering as they are local to element.

Ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>Styles</title>
```

```
  </head>
```

```
<body>
    <h2 style="background-color: green; color:white; text-align: center;">HTML</h2>
    <h2>CSS</h2>
    <h2>JavaScript</h2>
</body>
</html>
```

### **Embedded Styles:**

- Styles are defined in page by using <style> element.
- You configure in head or body section.
- You can keep all your styles at one location and use across various elements.
- It is good for reusing styles.
- Slower than inline.

Ex:

```
<!DOCTYPE html>
<html>
    <head>
        <title>Styles</title>
        <style>
            h2 {
                background-color: green;
```

```
        color: white;
        text-align: center;
    }
</style>
</head>
<body>
    <h2>HTML</h2>
    <h2>CSS</h2>
    <h2>JavaScript</h2>
</body>
</html>
```

### **FAQ: Where to embed the styles, in head or in body?**

**A.** If you want to configure a set of style, which are loaded into browser memory, and used later by the elements according to the requirement then keep in <head> section.

If you want to configure a set of styles, which are applied directly on body load then better define them in <body>.

### **Ex:**

```
<!DOCTYPE html>
<html>
    <head>
```

```
<title>Styles</title>
<style>
  .heading {
    background-color: green;
    color: white;
    text-align: center;
  }
</style>
</head>
<body>
  <style>
    body {
      background-color: lightgreen;
    }
  </style>
  <h2 class="heading">HTML</h2>
  <h2>CSS</h2>
  <h2>JavaScript</h2>
</body>
</html>
```

**FAQ: What is MIME type for Styles?**

- MIME type defines the type content present in element.
- The MIME type is used by browser to understand the type of content.
- Styles MIME type is "text/css"

Syntax:

```
<style type="text/css"> </style>
```

Ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<title>Styles</title>
```

```
<style type="text/css">
```

```
  .heading {
```

```
    background-color: green;
```

```
    color: white;
```

```
    text-align: center;
```

```
  }
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<style type="text/css">
```

```
  body {
```

```
    background-color: lightgreen;
```

```
    }  
</style>  
<h2 class="heading">HTML</h2>  
<h2>CSS</h2>  
<h2>JavaScript</h2>  
</body>  
</html>
```

### **Styles from External File:**

- The styles are maintained in a separate style sheet that have the extension “.css”
- You can link the style sheet to any HTML page.
- Styles are accessible across several pages.
- If you use external style sheet then number of requests for page will increase and also the page load time.

Ex:

- Add a new folder “Styles”
- Add a new style sheet into folder “effects.css”
- Add effects into style sheet

```
h2 {  
    background-color:blue;  
    color:white;  
    text-align: center;  
}
```
- Link the stylesheet to your web page.

```
<!DOCTYPE html>
<html>
  <head>
    <title>Styles</title>
    <link type="text/css" rel="stylesheet"
href="../Styles/effects.css">
  </head>
  <body>
    <h2>HTML</h2>
    <h2>CSS</h2>
    <h2>JavaScript</h2>
  </body>
</html>
```

### **FAQ: What is CDN?**

- CDN is Content Distribution Network
- We can maintain all style sheets in a repository server [SandBox]
- We can directly connect and access the style sheet from repository server instead of download into project.

Ex:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Styles</title>
```

```
<link type="text/css" rel="stylesheet"
href="http://127.0.0.1/cdn/styles/effects.css">
</head>
<body>
  <h2>HTML</h2>
  <h2>CSS</h2>
  <h2>JavaScript</h2>
</body>
</html>
```

## Minification of CSS

- Minification is the process of compressing CSS.
- It is always recommended to Minify and use the CSS for production. [Live]
- CSS original file will occupy more space, we have to use them for development but not for production.

## FAQ: What is “media” type for styles?

- Media specifies the styles target, which can be for Print, Screen, Speech.
- “media” is an attribute used to configure styles targeting different sources like printer, screen, audio out etc.
- You can configure “media” attribute for <style> or <link> element.
- Media values can be
  - All



- Print
- Screen
- Speech
- You can configure effects which will work for specific media.

Ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<style type="text/css" media="screen">
```

```
body {
```

```
    border:2px solid darkcyan;
```

```
    padding:20px;
```

```
}
```

```
h1{
```

```
    border:1px solid red;
```

```
    box-shadow: 2px 3px 4px red;
```

```
    text-align: center;
```

```
    padding: 10px;
```

```
}
```

```
</style>
```

```
<style type="text/css" media="print">
```

```
h1{
```

```

        border:1px solid red;
        text-align: center;
        padding: 10px;
    }
</style>
</head>
<body>
    <h1>Amazon Shopping</h1>
</body>
</html>

```

## Writing Styles for Elements

- If you are writing inline style for any element  

```
<div style="stylePropertyName:value; stylePropertyName:value"> </div>
```
- If you are writing styles embedded or in external file  

```
<style>
    selector
    {
        stylePropertyName: value;
        stylePropertyName: value;
    }
</style>
```
- Selector is used to define the target where the given styles need to apply.

- CSS can use various types of selectors
- The primary selectors used in styles are:
  - Type Selector
  - ID Selector
  - Class Selector

### **Type Selector**

- Type selector refers to HTML element tag name [Image <img>, Bold <b>].
- The given styles will be applied to specified tag where ever it is used in page.
- It will apply effects to every occurrence of the tag in page. You can't disable for any specific.

Ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <style>
```

```
      h2
```

```
      {
```

```
        background-color:red;
```

```
        color:white;
```

```
        text-align:center;
```

```
      }
```

```
</style>
</head>
<body>
  <h2>HTML</h2>
  <p>It is a markup language.</p>
  <h2>CSS</h2>
  <p>Defines styles of HTML.</p>
  <h2>JavaScript</h2>
  <p>Handles client side interactions.</p>
</body>
</html>
```

## **ID Selector**

- Every element can be defined with ID.
- You can use ID to access the element and apply effects.
- You can choose to which element you want the effects.
- Element is defined with ID

```
<div id="effects"> </div>
```
- You can access the ID in styles by using “#” reference

```
<style>
#effects
{
}
</style>
```
- Every tag can use only one ID reference.

- If you have configured multiple categories of styles with ID selector and want to use for specific tag, then it is not possible to define all effects to one element.

Ex:

```
<!DOCTYPE html>

<html>

  <head>

    <style>

      #textEffects {

        text-align: center;

        color:yellow;

      }

      #bgEffects {

        background-color: red;

      }

    </style>

  </head>

  <body>

    <h2 id="textEffects">HTML</h2>

    <p>It is a markup language.</p>

    <h2 id="bgEffects">CSS</h2>

    <p>Defines styles of HTML.</p>
```

```
<h2>JavaScript</h2>
<p>Handles client side interactions.</p>
</body>
</html>
```

## Class Selector

- A class selector is defined by using “.”
- Class is accessed and applied to element by using “class” attribute.
- Every tag can implement multiple classes.
- Multiple classes are specified with space.

```
<style>
```

```
.cssClassName
```

```
{
```

```
}
```

```
</style>
```

```
<div class="cssClassName1 cssClassName2"> </div>
```

- The CSS selectors are further classified into various groups based on behaviour
  - **Combinators / Rational Selectors**
  - **Attribute Selectors**
  - **Pseudo Selectors**
  - **Structural Pseudo Selectors**

## Rational or Combinators

- These selector default with parent and child elements as well as with elements that have relation.
- Relation like adjacent, below, above, before, after, first, last etc..

Selector	Description
Descendent Selector	<p>Targets all tags under specified parent. It includes any level hierarchy. It defines the parent element and the child element by using space.</p> <p>Syntax:</p> <pre>parentElement childElement {</pre> <pre>}</pre> <p>Ex:</p> <pre>&lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;style&gt;       ol li {         color: red;       }       div p {         color:green;       }     &lt;/style&gt;   &lt;/head&gt;   &lt;body&gt;     &lt;h2&gt;Web Technologies&lt;/h2&gt;     &lt;ol&gt;       &lt;li&gt;HTML       &lt;ol&gt;</pre>

	<pre>         &lt;li&gt;Void Elements&lt;/li&gt;         &lt;li&gt;Normal Elements&lt;/li&gt;       &lt;/ol&gt;     &lt;/li&gt;     &lt;li&gt;CSS&lt;/li&gt;     &lt;li&gt;JavaScript&lt;/li&gt;   &lt;/ol&gt;   &lt;div&gt;     &lt;blockquote&gt;Blockquote...&lt;/blockquote&gt;     &lt;p&gt;Para-1&lt;/p&gt;     &lt;div&gt;       &lt;p&gt;Para-2&lt;/p&gt;     &lt;/div&gt;   &lt;/div&gt;   &lt;p&gt;Para-3&lt;/p&gt; &lt;/body&gt; &lt;/html&gt; </pre>
Child Selector	<p>It applies effects only to the direct child of parent element.</p> <p>Syntax:</p> <p>Parent &gt; child {</p> <p>}</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;style&gt;       div&gt;p {         color:red;       }     &lt;/style&gt;   &lt;/head&gt;   &lt;body&gt;     &lt;div&gt;       &lt;p&gt; </pre>



	<pre>         &lt;/style&gt;     &lt;/head&gt;     &lt;body&gt;         &lt;div&gt;             &lt;p&gt;Para-1&lt;/p&gt;         &lt;/div&gt;         &lt;div&gt;             &lt;span&gt;                 &lt;p&gt;Para-2&lt;/p&gt;             &lt;/span&gt;         &lt;/div&gt;     &lt;/body&gt; &lt;/html&gt; </pre>
Adjacent Sibling	<p>It defines effects to an element which is specified immediately after current element.</p> <p>It is not parent and child, it is one below another.</p> <p>It will apply only to the first adjacent element.</p> <p>Syntax:</p> <pre> FirstElement + adjacentElement { } </pre> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;     &lt;head&gt;         &lt;style&gt;             h2+p { </pre>

	<pre>         color:red;     } &lt;/style&gt; &lt;/head&gt; &lt;body&gt;     &lt;h2&gt;HTML Elements&lt;/h2&gt;     &lt;p&gt;Para-1&lt;/p&gt;     &lt;p&gt;Para-2&lt;/p&gt;     &lt;p&gt;Para-3&lt;/p&gt;     &lt;p&gt;Para-4&lt;/p&gt; &lt;/body&gt; &lt;/html&gt; </pre>
General Sibling	<p>It defines effects to all elements which are specified after the current element.</p> <p>Syntax:</p> <pre> FirstElement ~ AdjacentElements { } </pre> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;     &lt;head&gt;         &lt;style&gt;             h2~p {                 color:red;             }         &lt;/style&gt;     &lt;/head&gt;     &lt;body&gt; </pre>

	<pre>&lt;h2&gt;HTML Elements&lt;/h2&gt; &lt;p&gt;Para-1&lt;/p&gt; &lt;p&gt;Para-2&lt;/p&gt; &lt;p&gt;Para-3&lt;/p&gt; &lt;p&gt;Para-4&lt;/p&gt; &lt;/body&gt; &lt;/html&gt;</pre>
--	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Attribute Selectors

- Several elements in HTML are presented by using attribute of tag.

```
<input type="button">
```

```
<input type="radio">
```

- "type" is attribute.
- We have to apply effects based on attribute and value.

Syntax:

```
tagName["attribute"] { }
```

```
tagName["attribute=value"] { }
```

## Ex: Attribute and Value

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<style>
```

```
    input[type="button"] {
        background-color: lightgreen;
    }
    input[type="password"] {
        background-color: lightpink;
    }
</style>
</head>
<body>
    <form>
        <dl>
            <dt>Name</dt>
            <dd><input type="text"></dd>
            <dt>Password</dt>
            <dd><input type="password"></dd>
        </dl>
        <input type="button" value="Register">
    </form>
</body>
</html>
```

## Ex: Only Attribute

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <style>
```

```
      p[id] {
```

```
        color: red;
```

```
      }
```

```
    </style>
```

```
  </head>
```

```
  <body>
```

```
    <p>Para-1</p>
```

```
    <p id="p2">Para-2</p>
```

```
    <p>Para-3</p>
```

```
    <p id="p4">Para-4</p>
```

```
  </body>
```

```
</html>
```

- Attribute selectors can be defined with conditions.
- Effects are applied only to attribute that match the given condition.

Condition	Purpose
[attribute="val"]	<p>Equal specifies that it should be exact match.</p> <p>Ex:</p> <pre>&lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;style&gt;       p[class="Effect"] {         color:red;       }     &lt;/style&gt;   &lt;/head&gt;   &lt;body&gt;     &lt;p class="paraEffect"&gt;Para-1&lt;/p&gt;     &lt;p class="para"&gt;Para- 2&lt;/p&gt;     &lt;p class="Effectpara"&gt;Para-3&lt;/p&gt;     &lt;p class="Effect"&gt;Para- 4&lt;/p&gt;   &lt;/body&gt; &lt;/html&gt;</pre>
[attribute^="val"]	<p>It refers the value starting with specified term.</p> <p>Ex:</p>

	<pre> &lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;style&gt;       p[class^="Effect"] {         color:red;       }     &lt;/style&gt;   &lt;/head&gt;   &lt;body&gt;     &lt;p class="paraEffect"&gt;Para-1&lt;/p&gt;     &lt;p class="para"&gt;Para- 2&lt;/p&gt;     &lt;p class="Effectpara"&gt;Para-3&lt;/p&gt;     &lt;p class="Effect"&gt;Para- 4&lt;/p&gt;   &lt;/body&gt; &lt;/html&gt; </pre>
[attribute\$="val"]	<p>It specifies that the value ending with given term. Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;style&gt;       p[class\$="Effect"] { </pre>

	<pre>         color:red;     }     &lt;/style&gt; &lt;/head&gt; &lt;body&gt;     &lt;p class="paraEffect"&gt;Para-1&lt;/p&gt;     &lt;p class="para"&gt;Para- 2&lt;/p&gt;     &lt;p class="Effectpara"&gt;Para-3&lt;/p&gt;     &lt;p class="Effect"&gt;Para- 4&lt;/p&gt;     &lt;/body&gt; &lt;/html&gt; </pre>
[attribute*="val"]	<p>It matches the term at any location.</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;     &lt;head&gt;         &lt;style&gt;             p[class*="Effect"] {                 color:red;             }         &lt;/style&gt;     &lt;/head&gt;     &lt;body&gt; </pre>



	<pre>         &lt;p class="paraEffect"&gt;Para-1&lt;/p&gt;         &lt;p class="para"&gt;Para- 2&lt;/p&gt;         &lt;p class="Effectpara"&gt;Para-3&lt;/p&gt;         &lt;p class="Effect"&gt;Para- 4&lt;/p&gt;         &lt;/body&gt; &lt;/html&gt; </pre>
[attribute   ="val"]	<p>Name starts with specified term and separated with “-”.</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;style&gt;       p[class   ="Effect"] {         color:red;       }     &lt;/style&gt;   &lt;/head&gt;   &lt;body&gt;     &lt;p class="para- Effect"&gt;Para-1&lt;/p&gt;     &lt;p class="para"&gt;Para- 2&lt;/p&gt;     &lt;p class="Effect- </pre>

	<pre> para"&gt;Para-3&lt;/p&gt;     &lt;p class="Effect"&gt;Para- 4&lt;/p&gt;     &lt;/body&gt; &lt;/html&gt; </pre>
[attribute~="val"]	<p>Name start with specified term and contain blank space.</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;     &lt;head&gt;         &lt;style&gt;             p[class~="Effect"] {                 color:red;             }         &lt;/style&gt;     &lt;/head&gt;     &lt;body&gt;         &lt;p class="para- Effect"&gt;Para-1&lt;/p&gt;         &lt;p class="Effect para"&gt;Para-2&lt;/p&gt;         &lt;p class="Effect- para"&gt;Para-3&lt;/p&gt;         &lt;p class="Effect"&gt;Para- 4&lt;/p&gt;     &lt;/body&gt; &lt;/html&gt; </pre>

## Dynamic Pseudo-Classes

- Dynamic indicates that the effect can change according to state and situation.
- Pseudo indicates that it is not referring to exactly the element which is having the same name as selector name.
- The selector name and the element if effects may differ.

Syntax:

link - not <link> element, it refers to <a>

```
class/Id/type: pseudoClass {  
}
```

Selector	Description
:link	Specifies effect for Hyperlink.
:visited	It defines effects for visited links.
:hover	It defines effects when mouse pointer is over element.
:active	It defines effects when link is in active state.
:focus	It defines effects when element get focus. Ex: <!DOCTYPE html> <html> <head>

	<pre> &lt;style&gt;   .txtName+span {     display: none;   }   .txtName:focus+span {     display: inline;   } &lt;/style&gt; &lt;/head&gt; &lt;body&gt;   &lt;div&gt;     &lt;label&gt;Name&lt;/label&gt;     &lt;div&gt;       &lt;input class="txtName" type="text"&gt;         &lt;span&gt;Name 4 Chars&lt;/span&gt;     &lt;/div&gt;   &lt;/div&gt; &lt;/body&gt; &lt;/html&gt; </pre>
--	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Syntax:

Element:Link { }

#heading:hover { }

.txtName:focus { }

Ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <style>
```

```
      .txtName+span {
```

```
        display: none;
```

```
      }
```

```
      .txtName:focus+span {
```

```
        display: inline;
```

```
      }
```

```
      input:focus {
```

```
        border:2px solid darkcyan;
```

```
        box-shadow: 2px 2px 3px darkcyan;
```

```
      }
```

```
      a{
```

```
        text-decoration: none;
```

```
      }
```

```
      a:hover {
```

```
        text-decoration: underline;
```

```
      }
```

```
      a:active {
```

```
        color:red;
    }
    a:visited {
        color:green
    }
    a:link {
        color: gray;
    }
</style>
</head>
<body>
    <div>
        <label>Name</label>
        <div>
            <input class="txtName" type="text">
            <span>Name 4 Chars</span>
        </div>
    </div>
    <div>
        <a href="home.html">Home</a>
        <span>|</span>
        <a href="http://www.flipkart.com">Flipkart</a>
```

```
        </div>
    </body>
</html>
```

## Target pseudo class

Selector	Description
:target	<ul style="list-style-type: none"><li>- It defines effects to any element when it becomes target of a link.</li><li>- You can implement in intra document navigation.</li></ul>

Ex:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Target</title>
    <style>
      ul {
        list-style: none;
        display: flex;
      }
      li {
        margin-left: 50px;
        border:2px solid darkblue;
```

```
padding: 10px;
width: 200px;
text-align: center;
border-radius: 10px;
}
.group {
border: 2px solid darkgreen;
background-color: lightgreen;
color: black;
margin-top: 20px;
padding: 10px;
}
.group:target {
background-color: black;
color: white;
}
</style>
</head>
<body>
<header>
<nav>
<ul>
```



```
<li><a href="#html">HTML</a></li>
<li><a href="#css">CSS</a></li>
<li><a href="#js">JavaScript</a></li>
</ul>
</nav>
</header>
<section>
  <div id="html" class="group">
    <h3>HTML</h3>
    <p>It is a markup language.</p>
  </div>
  <div id="css" class="group">
    <h3>CSS</h3>
    <p>It is to define styles</p>
  </div>
  <div id="js" class="group">
    <h3>JavaScript</h3>
    <p>It is a language.</p>
  </div>
</section>
</body>
</html>
```

## The UI element state pseudo-classes

- Element state indicates the state of element like enabled, disabled, readonly, checked.

Selector	Description
:enabled	It defines effects when element is enabled.
:disabled	<p>It defines effects when element is disabled.</p> <p>Ex:</p> <pre>&lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;title&gt;State&lt;/title&gt;     &lt;style&gt;       input:read-only {         background-color: gainsboro;         color: gray;       }       button:disabled {         cursor: not-allowed;       }       button:enabled {         cursor: grab;       }     &lt;/style&gt;   &lt;/head&gt;   &lt;body&gt;     &lt;fieldset&gt;       &lt;legend&gt;User Name&lt;/legend&gt;</pre>





	<pre>         &lt;input type="checkbox"&gt;       &lt;span&gt;I Accept&lt;/span&gt;       &lt;/div&gt;     &lt;/fieldset&gt;   &lt;/body&gt; &lt;/html&gt; </pre>
--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------

### The UI element validation state pseudo classes:

- HTML 5 provides pre-defined form validations like require, email, url, pattern etc.
- CSS can use HTML 5 validations to verify the state valid or not and can apply effects.

Selector	Description
:valid	<p>It defines effects for element if its value is valid against the validation defined.</p> <p>Validation can be verified by using:</p> <ul style="list-style-type: none"> <li>- Minlength</li> <li>- Maxlength</li> <li>- Required</li> <li>- Pattern</li> <li>- Email</li> <li>- URL etc.</li> </ul>
:invalid	<p>It defines effect for element when it is invalid.</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt; </pre>

	<pre> &lt;head&gt;   &lt;title&gt;State&lt;/title&gt;   &lt;style&gt;     #txtName:valid+span {       display: none;     }     #txtName:invalid+span {       display: inline;     }     #txtName:valid {       border:2px solid green;       box-shadow: 2px 2px 3px green;     }     #txtName:invalid {       border:2px solid red;       box-shadow: 2px 2px 3px red;     }   &lt;/style&gt; &lt;/head&gt; &lt;body&gt;   &lt;div class="form-group"&gt;     &lt;label&gt;User Name&lt;/label&gt;     &lt;div&gt;       &lt;input id="txtName" type="text" minlength="4"&gt;       &lt;span&gt;Name too short&lt;/span&gt;     &lt;/div&gt;   &lt;/div&gt; &lt;/body&gt; &lt;/html&gt; </pre>
:in-range	It defines effects for element when input



	</body> </html>
:required	It defines effects to element when it verified with required error. It is not validating required, It is just verifying whether the required defined or not.
:optional	If it is not defined with required validation then it is treated as optional.

Ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>State</title>
```

```
    <style>
```

```
      input:in-range {
        border: 2px solid green;
        box-shadow: 2px 3px 4px green;
      }
```

```
      input:out-of-range {
        border: 2px solid red;
        box-shadow: 2px 3px 4px red;
      }
```

```
      .form-group {
```



```
        margin-top: 20px;
    }
    #txtName:optional+div {
        display: none;
    }
    #txtName:required+div {
        display: block;
        color:red;
    }
    #txtName:valid+div {
        display: none;
    }
</style>
</head>
<body>
    <div class="form-group">
        <label>Age</label>
        <div>
            <input type="number" min="16" max="35">
        </div>
    </div>
    <div class="form-group">
```

```

<label>Name</label>

<div>

    <input required id="txtName" type="text">

    <div>Name required</div>

</div>

</div>

</body>

</html>

```

### Structural Pseudo Selector:

- You can target your effects based on the position of element in parent and child hierarchy.

Selector	Description
:first-child	It defines effects only for first child element.
:last-child	It defines effects only for last child element.
:nth-child(LevelNumber)	<p>It defines effects only to specific child element that occurs at given level.</p> <p>Level number starts with 1.</p> <p>Index number starts with 0.</p> <p>You can also define the pre-set values like 'even &amp; odd' to apply effects based on even and odd occurrences.</p> <p>Ex:</p>

```
<!DOCTYPE html>
<html>
  <head>
    <title>Structure</title>
    <style>
      ol > li:first-child {
        color:red;
      }
      ol > li:last-child {
        color:blue;
      }
      ol > li:nth-child(3){
        color: green;
        font-size: 30px;
      }
    </style>
  </head>
  <body>
    <ol>
      <li>Item-1</li>
      <li>Item-2</li>
      <li>Item-3</li>
      <li>Item-4</li>
      <li>Item-5</li>
    </ol>
  </body>
</html>
```

Ex: Even and Odd occurrence

```
<!DOCTYPE html>
<html>
```

```
<head>
  <title>Odd Even</title>
  <style>
    thead > tr {
      background-color:
darkcyan;
      color:white;
    }
    tbody > tr:nth-child(even)
{
      background-color:
lightcyan;
    }
    tbody > tr:nth-child(odd){
      background-color:
lightgreen;
    }
  </style>
</head>
<body>
  <table border="1"
width="400">
    <thead>
      <tr>
        <th>Name</th>
        <th>Price</th>
      </tr>
    </thead>
    <tbody>
      <tr>
        <td>TV</td>
```

	<pre>         &lt;td&gt;45000.55&lt;/td&gt;       &lt;/tr&gt;       &lt;tr&gt;         &lt;td&gt;Mobile&lt;/td&gt;         &lt;td&gt;41000.22&lt;/td&gt;       &lt;/tr&gt;       &lt;tr&gt;         &lt;td&gt;Nike&lt;/td&gt;         &lt;td&gt;5200.33&lt;/td&gt;       &lt;/tr&gt;       &lt;tr&gt;         &lt;td&gt;Shirt&lt;/td&gt;         &lt;td&gt;4100.33&lt;/td&gt;       &lt;/tr&gt;     &lt;/tbody&gt;   &lt;/table&gt; &lt;/body&gt; &lt;/html&gt; </pre>
<p>:nth-of-type(LevelNumber[n])</p> <p>:nth-of-type(2n)</p> <p>:nth-of-type(2n+startNumber)</p>	<p>It will repeat the effect for every nth occurrence.</p> <p>It will repeat the effect for every 2<sup>nd</sup> occurrence.</p> <p>It will start with specific level.</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;title&gt;Structure&lt;/title&gt;     &lt;style&gt; </pre>

	<pre>         ol &gt; li:nth-of-type(2n+1){             color:red;         }     &lt;/style&gt; &lt;/head&gt; &lt;body&gt;     &lt;ol&gt;         &lt;li&gt;Item-1&lt;/li&gt;         &lt;li&gt;Item-2&lt;/li&gt;         &lt;li&gt;Item-3&lt;/li&gt;         &lt;li&gt;Item-4&lt;/li&gt;         &lt;li&gt;Item-5&lt;/li&gt;     &lt;/ol&gt; &lt;/body&gt; &lt;/html&gt; </pre>
:nth-last-of-type(n)	<p>It will apply effect for every nth occurrence from bottom.</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;     &lt;head&gt;         &lt;title&gt;Structure&lt;/title&gt;         &lt;style&gt;             ol &gt; li:nth-last-of- type(2n+1){                 color:red;             }         &lt;/style&gt;     &lt;/head&gt;     &lt;body&gt;         &lt;ol&gt; </pre>

	<pre>         &lt;li&gt;Item-1&lt;/li&gt;         &lt;li&gt;Item-2&lt;/li&gt;         &lt;li&gt;Item-3&lt;/li&gt;         &lt;li&gt;Item-4&lt;/li&gt;         &lt;li&gt;Item-5&lt;/li&gt;         &lt;li&gt;Item-6&lt;/li&gt;         &lt;li&gt;Item-7&lt;/li&gt;         &lt;li&gt;Item-8&lt;/li&gt;       &lt;/ol&gt;     &lt;/body&gt;   &lt;/html&gt; </pre>
:nth-last-child(n)	<p>It will apply from bottom without repeating.</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;title&gt;Structure&lt;/title&gt;     &lt;style&gt;       ol &gt; li:nth-last-child(2){         color:red;       }     &lt;/style&gt;   &lt;/head&gt;   &lt;body&gt;     &lt;ol&gt;       &lt;li&gt;Item-1&lt;/li&gt;       &lt;li&gt;Item-2&lt;/li&gt;       &lt;li&gt;Item-3&lt;/li&gt;       &lt;li&gt;Item-4&lt;/li&gt;     &lt;/ol&gt;   &lt;/body&gt; &lt;/html&gt; </pre>

	<pre>         &lt;li&gt;Item-5&lt;/li&gt;         &lt;li&gt;Item-6&lt;/li&gt;         &lt;li&gt;Item-7&lt;/li&gt;         &lt;li&gt;Item-8&lt;/li&gt;       &lt;/ol&gt;     &lt;/body&gt;   &lt;/html&gt; </pre>
:root	<p>It refers to root of document, which is 'body'</p> <p>Ex:</p> <pre> :root {   font-family:Arial; } </pre>
:empty	<p>If any element is empty, without any content then its will define the given effects.</p> <p>You can configure for containers like &lt;div&gt;, &lt;span&gt;, &lt;td&gt;, &lt;dd&gt;, &lt;p&gt; etc.</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;title&gt;Odd Even&lt;/title&gt;     &lt;style&gt;       thead &gt; tr {         background-color: darkcyan;         color:white;       } </pre>



```

        tbody > tr:nth-child(even)
    {
        background-color:
lightcyan;
    }
        tbody > tr:nth-child(odd){
        background-color:
lightgreen;
    }
        tbody > tr > td:empty {
        background-color: red;
    }
    </style>
</head>
<body>
        <table border="1"
width="400">
    <thead>
        <tr>
            <th>Name</th>
            <th>Price</th>
        </tr>
    </thead>
    <tbody>
        <tr>
            <td>TV</td>
            <td>45000.55</td>
        </tr>
        <tr>
            <td>Mobile</td>
            <td>41000.22</td>

```

	<pre>         &lt;/tr&gt;         &lt;tr&gt;             &lt;td&gt;Nike&lt;/td&gt;             &lt;td&gt;&lt;/td&gt;         &lt;/tr&gt;         &lt;tr&gt;             &lt;td&gt;Shirt&lt;/td&gt;             &lt;td&gt;4100.33&lt;/td&gt;         &lt;/tr&gt;     &lt;/tbody&gt; &lt;/table&gt; &lt;/body&gt; &lt;/html&gt; </pre>
--	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Pseudo-Element Selectors:

Selector	Description
::first-line	Effects for first line in paragraph.
::first-letter	<p>Effects for first character.</p> <p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;title&gt;Element Selectors&lt;/title&gt;     &lt;style&gt;       p::first-letter {         font-family: Arial;         font-size: 30px;         color:red;       }       p::first-line { </pre>

	<pre>         color:red;     }     &lt;/style&gt; &lt;/head&gt; &lt;body&gt;     &lt;p&gt;Depending on how you obtained the Windows software, this is a license agreement between (i) you and the device manufacturer or software installer that distributes the software with your device; or (ii) you and Microsoft Corporation (or, based on where you live or, if a business, where your principal place of business is located, one of its affiliates) if you acquired the software from a retailer. Microsoft is the device manufacturer for devices produced by Microsoft or one of its affiliates, and Microsoft is the retailer if you acquired the software directly from Microsoft. Note that if you are a volume license customer, use of this software is subject to your volume license agreement rather than this agreement.     &lt;/p&gt; &lt;/body&gt; &lt;/html&gt; </pre>
::before	Effect or <b>content</b> to add before the current element.
::after	Effect or <b>content</b> to add after the current element.

	<p>Ex:</p> <pre> &lt;!DOCTYPE html&gt; &lt;html&gt;   &lt;head&gt;     &lt;title&gt;Before After&lt;/title&gt;     &lt;style&gt;       ul {         display: flex;         list-style: none;       }       li::before {         content: "--&gt;";       }       li:first-child::before {         content: "";       }     &lt;/style&gt;   &lt;/head&gt;   &lt;body&gt;     Site Map     &lt;nav&gt;       &lt;ul&gt;         &lt;li&gt;Home&lt;/li&gt;         &lt;li&gt;About&lt;/li&gt;         &lt;li&gt;Contact&lt;/li&gt;         &lt;li&gt;Login&lt;/li&gt;       &lt;/ul&gt;     &lt;/nav&gt;   &lt;/body&gt; &lt;/html&gt; </pre>
::placeholder	It will apply effects for placeholder.

::selection

It will apply effects for selection.

Ex:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Languages</title>
    <style>
      * {
        font-style: italic;
      }
      input::placeholder {
        color:lightgreen;
      }
      p::selection {
        background-color: yellow;
      }
    </style>
  </head>
  <body>
    <p>Some content.. select and see..</p>
    <dl>
      <dt>Name</dt>
      <dd><input placeholder="Name 4
chars" type="text"></dd>
      <dt>Password</dt>
      <dd><input disabled
type="password"></dd>
      <dt>Mobile</dt>
      <dd><input required
type="text"></dd>
    </dl>
```

	<code>&lt;/body&gt;</code> <code>&lt;/html&gt;</code>
--	----------------------------------------------------------

## Language Selector:

- It defines effects based on lang configured for element.
- If you page is multi lingual then you can define effects to content based on specific language.

“:lang()”

Ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>Languages</title>
```

```
    <style>
```

```
      p:lang(en){
```

```
        font-style: italic;
```

```
      }
```

```
    </style>
```

```
  </head>
```

```
  <body>
```

```
    <h2>Language Selector</h2>
```

```
    <p>Some Text</p>
```

```
    <p lang="en">English US</p>
```

```
  </body>
```

</html>

## Negation Selector

- It is used to define effects for the elements which are not matching with specified criteria.
- The negation selector is defined using “:not()”
- It will ignore effects for specific element and apply for other.

Ex:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <title>Languages</title>
```

```
    <style>
```

```
      p:not(#effects){
```

```
        color:red;
```

```
      }
```

```
    </style>
```

```
  </head>
```

```
  <body>
```

```
    <p>Para-1</p>
```

```
    <p id="effects">Para-2</p>
```

```
<p>Para-3</p>
<p id="styles">Para-4</p>
<p id="effects">Para-5</p>
</body>
</html>
```

- You can also configure for properties.

Ex:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Languages</title>
    <style>
      input:not([disabled]) {
        background-color: lightgreen;
      }
    </style>
  </head>
  <body>
    <dl>
      <dt>Name</dt>
      <dd><input type="text"></dd>
```



```
<dt>Password</dt>
<dd><input disabled type="password"></dd>
<dt>Mobile</dt>
<dd><input required type="text"></dd>
</dl>
</body>
</html>
```

### **Universal Selector:**

- It is defined by using “\*” that represents all.
- It apply effects to all elements.

Ex:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Languages</title>
    <style>
      * {
        font-style: italic;
      }
    </style>
  </head>
```

```
<body>
  <dl>
    <dt>Name</dt>
    <dd><input type="text"></dd>
    <dt>Password</dt>
    <dd><input disabled type="password"></dd>
    <dt>Mobile</dt>
    <dd><input required type="text"></dd>
  </dl>
</body>
</html>
```