

QuikTrack API

A Simple, Plain-English Guide to Using & Testing It

For anyone — no coding experience needed to follow along

1. What is this, in plain words?

Normally you use QuikTrack by opening the website and clicking around. An **API** is a second door into the exact same system — but built for *programs* instead of people. It lets another app (or a simple command on your computer) read and change your QuikTrack data automatically: create tasks, list projects, log time, and so on.

Think of it like this: the website is the *front counter* of a shop where you talk to a person. The API is the *staff entrance* with a checklist — other computers walk in, follow the checklist, and get things done without needing the counter.

You do the same things you'd do on the website (make a task, comment, etc.), just by sending short text messages called **requests** instead of clicking buttons.

2. What you need before you start

- A **QuikTrack account** — the same **email and password** you use to log in.
- The **web address** of QuikTrack (we call it the "host"), for example `https://track.quikit.ai`.
- A way to send requests. Two easy options:
 - **The interactive page** (easiest): open `/api/v1/docs` in your browser and click buttons. No typing commands.
 - **A terminal** using a tool called `curl` (examples below).

3. The big idea in 3 steps

The wristband analogy: At a concert you show your ticket *once* at the gate and get a **wristband**. After that, the wristband alone gets you into every area — you don't show your ticket again. Our **token** is that wristband.

1. **Show your ticket:** send your email & password once → you receive a **token**.
2. **Wear the wristband:** attach that token to every request.
3. **Go anywhere you're allowed:** now you can list projects, create tasks, etc. — but only the things your account is allowed to do.

The token expires after **1 hour** (the wristband is only good for tonight). When it stops working, just do step 1 again to get a new one.

4. Step 1 — Get your token

Send your email and password to the login address. Here it is as a `curl` command:

```
curl -X POST "https://track.quikit.ai/api/v1/token" \
-H "Content-Type: application/json" \
-d '{ "email": "you@company.com", "password": "your-password" }'
```

What each part means:

- `POST` — "I'm sending you some information."
- `/api/v1/token` — the login door.
- `-H "Content-Type: application/json"` — "the info I'm sending is in JSON format" (a simple text format).
- `-d '{ ... }'` — the actual info: your email and password.

You get back something like this:

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIs... ", <-- this long string is your token
  "token_type": "Bearer",
  "expires_in": 3600 <-- valid for 3600 seconds = 1 hour
}
```

Tip: Copy the long `access_token` value. That's your wristband for the next hour.

5. Step 2 — Use your token

From now on, every request carries the token in a line called the **Authorization header**. It looks like this:

```
Authorization: Bearer YOUR_TOKEN_HERE
```

If you're using the interactive page at `/api/v1/docs`, you don't type this — just click the **Authorize** button, paste the token once, and every "Try it" button includes it for you automatically.

6. Step 3 — Try things (common tasks)

Below, `$TOKEN` means "your token from step 1". Each example shows the command and, in plain words, what it does.

See your projects

```
curl "https://track.quikit.ai/api/projects" \
-H "Authorization: Bearer $TOKEN"
```

Returns the list of projects (called "spaces") you can see.

Create a new project

```
curl -X POST "https://track.quikit.ai/api/projects" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{ "name": "My New Project", "projectKey": "MYPROJ" }'
```

Makes a new project. `projectKey` is a short code (UPPERCASE letters/numbers, 2–10 characters, e.g. `MYPROJ`) used as a prefix for its tasks.

See the tasks in a project

```
curl "https://track.quikit.ai/api/issues?projectId=PROJECT_ID" \
-H "Authorization: Bearer $TOKEN"
```

Lists the work items ("issues") in one project. Replace `PROJECT_ID` with the `id` you got when creating or listing projects.

Create a task

```
curl -X POST "https://track.quikit.ai/api/issues" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "projectId": "PROJECT_ID",
  "title": "Fix the login button",
  "type": "BUG",
  "priority": "HIGH"
}'
```

Creates a task. `type` can be TASK, BUG, STORY, EPIC or SUBTASK. `priority` can be LOWEST, LOW, MEDIUM, HIGH or HIGHEST.

Add a comment to a task

```
curl -X POST "https://track.quikit.ai/api/issues/ISSUE_ID/comments" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{ "body": "I have started working on this." }'
```

Log time spent on a task

```
curl -X POST "https://track.quikit.ai/api/timesheets" \
-H "Authorization: Bearer $TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "issueId": "ISSUE_ID",
  "entryDate": "2026-07-07T00:00:00.000Z",
  "hours": 2.5
}'
```

Records 2.5 hours against a task. Dates use the format `YYYY-MM-DDT00:00:00.000Z`.

Easiest way to test all of these: open </api/v1/docs>, click **Authorize**, paste your token, then use the **Try it** button on any endpoint. It fills in an example for you and shows the result instantly.

7. Understanding the replies

Most replies come back in this shape:

```
{ "success": true, "data": { ... } }    <-- it worked; your info is in "data"
{ "success": false, "error": "message" } <-- something went wrong; read "error"
```

Every reply also has a **status number**. Here's what they mean in plain words:

Number	Plain meaning
200 / 201	Success — it worked.
400	Your message was written wrong (a field is missing or malformed).
401	Not logged in — your token is missing, wrong, or expired. Get a new one.
403	You're logged in, but you're not allowed to do this / see this.
404	The thing you asked for doesn't exist (or you can't access it).
429	Too many login tries too fast — wait a bit and try again.
500	Something broke on our side, not yours.

8. Common problems & quick fixes

"Unauthorized" (401): Your token expired (they last 1 hour) or wasn't included. Fix: get a fresh token (Step 1) and try again.

"Invalid email or password" (401 at login): Double-check the email and password — the same ones you use on the website.

"email and password are required" (400): One of them is missing or the JSON is mistyped (check the quotes and commas).

"Too many attempts" (429): The login is protected against guessing. Wait for the time shown in the `Retry-After` reply, then try once.

9. A note on safety

- Your token is like a temporary password — **don't share it** or paste it into untrusted places.
- Everything you do through the API happens **as you**, limited to **your organization** and the **permissions** you already have.
- Always use `https://` (secure) addresses.

10. Where to explore everything

The full, always-up-to-date list of everything you can do is the interactive reference:

```
https://track.quikit.ai/api/v1/docs
```

Open it, click **Authorize**, paste your token, and browse every feature grouped by area (Issues, Projects, Sprints, Timesheets, Reports, and more) with ready-made examples and a **Try it** button for each.