

Scan Report

September 2, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “Metasploitable2-VulnScan”. The scan started at Mon Aug 31 14:26:50 2026 UTC and ended at Mon Aug 31 15:30:58 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
1.1	Host Authentications	2
2	Results per Host	2
2.1	192.168.56.102	2
2.1.1	Critical 3632/tcp	3
2.1.2	Critical 5900/tcp	3
2.1.3	Critical 8009/tcp	4
2.1.4	Critical 80/tcp	8
2.1.5	Critical 3306/tcp	9
2.1.6	Critical 1524/tcp	10
2.1.7	Critical 5432/tcp	10
2.1.8	Critical 21/tcp	11
2.1.9	Critical 513/tcp	12
2.1.10	Critical general/tcp	12
2.1.11	Critical 6200/tcp	13
2.1.12	Critical 8787/tcp	14
2.1.13	Critical 512/tcp	15
2.1.14	High 1099/tcp	15
2.1.15	High 80/tcp	16
2.1.16	High 2121/tcp	19
2.1.17	High 5432/tcp	20
2.1.18	High 514/tcp	21
2.1.19	High 21/tcp	22
2.1.20	High 513/tcp	23
2.1.21	Medium 445/tcp	24
2.1.22	Medium 5900/tcp	24
2.1.23	Medium 80/tcp	25
2.1.24	Medium 2121/tcp	34
2.1.25	Medium 5432/tcp	35

2.1.26	Medium 21/tcp	46
2.1.27	Medium 23/tcp	47
2.1.28	Medium 25/tcp	47
2.1.29	Medium 22/tcp	60
2.1.30	Low 5432/tcp	63
2.1.31	Low general/icmp	64
2.1.32	Low 25/tcp	65
2.1.33	Low 22/tcp	69
2.1.34	Low general/tcp	70

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.56.102	13	9	40	6	0	0
Total: 1	13	9	40	6	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 68 results selected by the filtering described above. Before filtering there were 632 results.

1.1 Host Authentications

Host	Protocol	Result	Port/User
192.168.56.102	SMB	Success	Protocol SMB, Port 445, User

2 Results per Host

2.1 192.168.56.102

Host scan start Mon Aug 31 14:31:24 2026 UTC
Host scan end Mon Aug 31 15:30:52 2026 UTC

Service (Port)	Threat Level
3632/tcp	Critical
5900/tcp	Critical
8009/tcp	Critical
80/tcp	Critical
3306/tcp	Critical
1524/tcp	Critical
5432/tcp	Critical
21/tcp	Critical
513/tcp	Critical
general/tcp	Critical
6200/tcp	Critical
8787/tcp	Critical
512/tcp	Critical
1099/tcp	High
80/tcp	High
2121/tcp	High
5432/tcp	High
514/tcp	High
21/tcp	High
513/tcp	High
445/tcp	Medium
5900/tcp	Medium
80/tcp	Medium
2121/tcp	Medium
5432/tcp	Medium
21/tcp	Medium

... (continues) ...

... (continued) ...

Service (Port)	Threat Level
23/tcp	Medium
25/tcp	Medium
22/tcp	Medium
5432/tcp	Low
general/icmp	Low
25/tcp	Low
22/tcp	Low
general/tcp	Low

2.1.1 Critical 3632/tcp

Critical (CVSS: 9.3)
NVT: DistCC RCE Vulnerability (CVE-2004-2687)
Summary DistCC is prone to a remote code execution (RCE) vulnerability.
Quality of Detection (QoD): 99%
Vulnerability Detection Result It was possible to execute the "id" command. Result: uid=1(daemon) gid=1(daemon)
Impact DistCC by default trusts its clients completely that in turn could allow a malicious client to execute arbitrary commands on the server.
Solution: Solution type: VendorFix Vendor updates are available. Please see the references for more information. For more information about DistCC's security see the references.
Vulnerability Insight DistCC 2.x, as used in XCode 1.5 and others, when not configured to restrict access to the server port, allows remote attackers to execute arbitrary commands via compilation jobs, which are executed by the server without authorization checks.
Vulnerability Detection Method Details: DistCC RCE Vulnerability (CVE-2004-2687) OID:1.3.6.1.4.1.25623.1.0.103553 Version used: 2022-07-07T10:16:06Z
References cve: CVE-2004-2687 url: https://distcc.github.io/security.html url: https://web.archive.org/web/20150511045306/http://archives.neohapsis.com:80/archives/bugtraq/2005-03/0183.html dfn-cert: DFN-CERT-2019-0381

[[return to 192.168.56.102](#)]

2.1.2 Critical 5900/tcp

Critical (CVSS: 9.0)
NVT: VNC Brute Force Login
Summary The VNC service is prone to default credentials.
... continues on next page ...

...continued from previous page ...
Quality of Detection (QoD): 70%
Vulnerability Detection Result It was possible to connect to the VNC server with the password: password
Solution: Solution type: Mitigation Change the password to something hard to guess or enable password protection at all.
Affected Software/OS Various products (e.g. HIPASE-250) and misconfigurations.
Vulnerability Insight This script tries to authenticate to a VNC server with the passwords set in the password preference. It will also test and report if no authentication / password is required at all. Note: Some VNC servers have a blacklisting scheme that blocks IP addresses after five unsuccessful connection attempts for a period of time. The script will abort the brute force attack if it encounters that it gets blocked. Note as well that passwords can be max. 8 characters long.
Vulnerability Detection Method Tries to log in with given passwords via VNC protocol. Details: VNC Brute Force Login OID:1.3.6.1.4.1.25623.1.0.106056 Version used: 2026-08-18T05:48:51Z
References cve: CVE-2026-65313

[[return to 192.168.56.102](#)]

2.1.3 Critical 8009/tcp

Critical (CVSS: 9.8) NVT: Apache Tomcat AJP RCE Vulnerability (Ghostcat) - Active Check
Summary Apache Tomcat is prone to a remote code execution (RCE) vulnerability in the AJP connector dubbed 'Ghostcat'.
Quality of Detection (QoD): 99%
Vulnerability Detection Result It was possible to read the file "/WEB-INF/web.xml" through the AJP connector. Result: AB 8\x0004 Ã\x0088 \x00020K \x0001 \x000CContent-Type \x001Ctext/html;charset= ↳ISO-8859-1 AB\x001FÃ¼\x0003\x001FÃ, <!-- Licensed to the Apache Software Foundation (ASF) under one or more contributor license agreements. See the NOTICE file distributed with this work for additional information regarding copyright ownership. The ASF licenses this file to You under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at http://www.apache.org/licenses/LICENSE-2.0 Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License. --> <?xml version="1.0" encoding="ISO-8859-1"?> <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd"> <html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en"> <head> <title>Apache Tomcat/5.5</title>
...continues on next page ...

...continued from previous page ...

```

<style type="text/css">
/**]
  body {
    color: #000000;
    background-color: #FFFFFF;
font-family: Arial, "Times New Roman", Times, serif;
    margin: 10px 0px;
  }
  img {
    border: none;
  }

  a:link, a:visited {
    color: blue
  }
  th {
    font-family: Verdana, "Times New Roman", Times, serif;
    font-size: 110%;
    font-weight: normal;
    font-style: italic;
    background: #D2A41C;
    text-align: left;
  }
  td {
    color: #000000;
font-family: Arial, Helvetica, sans-serif;
  }

  td.menu {
    background: #FFDC75;
  }
  .center {
    text-align: center;
  }
  .code {
    color: #000000;
    font-family: "Courier New", Courier, monospace;
    font-size: 110%;
    margin-left: 2.5em;
  }

  #banner {
    margin-bottom: 12px;
  }
  p#congrats {
    margin-top: 0;
    font-weight: bold;
    text-align: center;
  }
  p#footer {
    text-align: right;
    font-size: 80%;
  }
/*]]]&gt;*/
&lt;/style&gt;
&lt;/head&gt;
&lt;body&gt;
&lt;!-- Header --&gt;
&lt;table id="banner" width="100%"&gt;
  &lt;tr&gt;
    &lt;td align="left" style="width:130px"&gt;
      &lt;a href="http://tomcat.apache.org/"&gt;
        &lt;img src="tomcat.gif" height="92" width="130" alt="The Mighty Tomcat - MEOW!"
        ↵&gt;
      &lt;/a&gt;
    &lt;/td&gt;
    &lt;td align="left" valign="top"&gt;&lt;b&gt;Apache Tomcat/5.5&lt;/b&gt;&lt;/td&gt;
    &lt;td align="right"&gt;
      &lt;a href="http://www.apache.org/"&gt;
        &lt;img src="asf-logo-wide.gif" height="51" width="537" alt="The Apache Software
        ↵ Foundation"/&gt;
      &lt;/a&gt;
    &lt;/td&gt;
  &lt;/tr&gt;
&lt;/table&gt;
</pre>
</div>
<div data-bbox="155 810 333 822" data-label="Text">...continues on next page ...</div>
```

...continued from previous page ...

```

        </td>
      </tr>
    </table>
    <table>
      <tr>
        <!-- Table of Contents -->
        <td valign="top">
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
            <tr>
              <th>Administration</th>
            </tr>
            <tr>
              <td class="menu">
                <a href="manager/status">Status</a><br/>
                <a href="admin">Tomcat&nbsp;Administration</a><br/>
                <a href="manager/html">Tomcat&nbsp;Manager</a><br/>
                &nbsp;
              </td>
            </tr>
          </table>
          <br />
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
            <tr>
              <th>Documentation</th>
            </tr>
            <tr>
              <td class="menu">
                <a href="RELEASE-NOTES.txt">Release&nbsp;Notes</a><br/>
                <a href="tomcat-docs/changelog.html">Change&nbsp;Log</a><br/>
                <a href="tomcat-docs">Tomcat&nbsp;Documentation</a><br/>
                &nbsp;
              </td>
            </tr>
          </table>
          <br/>
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
            <tr>
              <th>Tomcat Online</th>
            </tr>
            <tr>
              <td class="menu">
                <a href="http://tomcat.apache.org/">Home&nbsp;Page</a><br/>
                <a href="http://tomcat.apache.org/faq/">FAQ</a><br/>
                <a href="http://tomcat.apache.org/bugreport.html">Bug&nbsp;Database</a><br/>
                <a href="http://issues.apache.org/bugzilla/buglist.cgi?bug_status=UNCONFIRMED&bug_status=NEW&bug_status=ASSIGNED&bug_status=RESOLVED&bug_status=CLOSED&bug_status=OPENED&bug_status=RESOLVED&resolution=LATER&resolution=REMOVED&resolution=---&bugidtype=include&product=Tomcat+5&cmdtype=doit&order=Importance">Open Bugs</a><br/>
                <a href="http://mail-archives.apache.org/mod_mbox/tomcat-users/">Users&nbsp;Mailing List</a><br/>
                <a href="http://mail-archives.apache.org/mod_mbox/tomcat-dev">Developers&nbsp;Mailing List</a><br/>
                <a href="irc://irc.freenode.net/#tomcat">IRC</a><br/>
                &nbsp;
              </td>
            </tr>
          </table>
          <br/>
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
            <tr>
              <th>Examples</th>
            </tr>
            <tr>
              <td class="menu">
                <a href="jsp-examples/">JSP&nbsp;Examples</a><br/>
                <a href="servlets-examples/">Servlet&nbsp;Examples</a><br/>

```

...continues on next page ...

...continued from previous page ...
<pre> WebDAV&nbsp;capabilities
 &nbsp; </td> </tr> </table>
 <table width="100%" border="1" cellspacing="0" cellpadding="3"> <tr> <th>Miscellaneous</th> </tr> <tr> <td class="menu"> Sun's&nbsp;Java& ↳bsp;Server&nbsp;Pages&nbsp;Site
 Sun's&nbsp;Se ↳rvlet&nbsp;Site
 &nbsp; </td> </tr> </table> </td> <td style="width:20px">&nbsp;</td> <!-- Body --> <td align="left" valign="top"> <p id="congrats">If you're seeing this page via a web browser, it mean ↳s you've setup Tomcat successfully. Congratulations!</p> <p>As you may have guessed by now, this is the default Tomcat home pag ↳e. It can be found on the local filesystem at:</p> <p class="code">\${CATALINA_HOME}/webapps/ROOT/index.jsp</p> <p>where "\${CATALINA_HOME}" is the root of the Tomcat installation direc ↳tory. If you're seeing this page, and you don't think you should be, then eith ↳er you're either a user who has arrived at new installation of Tomcat, or you' ↳re an administrator who hasn't got his/her setup quite right. Providing the la ↳tter is the case, please refer to the Tomcat Documentati ↳on for more detailed setup and administration information than is found in ↳ the INSTALL file.</p> <p>NOTE: This page is precompiled. If you change it, this pag ↳e will not change since it was compiled into a servlet at build time. (See <tt>\${CATALINA_HOME}/webapps/ROOT/WEB-INF/web.xml</tt> as t ↳o how it was mapped.) </p> <p>NOTE: For security reasons, using the administration webapp is restricted to users with role "admin". The manager webapp is restricted to users with role "manager". Users are defined in <code>\${CATALINA_HOME}/conf/tomcat-users.xml</cod ↳e>.</p> <p>Included with this release are a host of sample Servlets and JSPs ↳ (with associated source code), extensive documentation (including the Servlet ↳ 2.4 and JSP 2.0 API JavaDoc), and an introductory guide to developing web app ↳ lications.</p> <p>Tomcat mailing lists are available at the Tomcat project web site ↳:</p> users@tomc </pre>
Solution: Solution type: VendorFix - Update Apache Tomcat to version 7.0.100, 8.5.51, 9.0.31 or later - For other products using Tomcat please contact the vendor for more information on fixed versions
Affected Software/OS Apache Tomcat versions prior 7.0.100, 8.5.51 or 9.0.31 when the AJP connector is enabled. Other products like JBoss or Wildfly which are using Tomcat might be affected as well.
Vulnerability Insight ...continues on next page ...

...continued from previous page ...
Apache Tomcat server has a file containing vulnerability, which can be used by an attacker to read or include any files in all webapp directories on Tomcat, such as webapp configuration files or source code.
Vulnerability Detection Method Sends a crafted AJP request and checks the response. Details: Apache Tomcat AJP RCE Vulnerability (Ghostcat) - Active Check OID:1.3.6.1.4.1.25623.1.0.143545 Version used: 2026-03-18T05:59:10Z
References cve: CVE-2020-1938 url: https://lists.apache.org/thread/bnys5lvg1875dsslkx2vmwxv833135x url: https://tomcat.apache.org/security-9.html#Fixed_in_Apache_Tomcat_9.0.31 url: https://tomcat.apache.org/security-8.html#Fixed_in_Apache_Tomcat_8.5.51 url: https://tomcat.apache.org/security-7.html#Fixed_in_Apache_Tomcat_7.0.100 url: https://web.archive.org/web/20250114042903/https://www.chaitin.cn/en/ghostcat url: https://www.cnvd.org.cn/flaw/show/CNVD-2020-10487 url: https://github.com/YDHCUI/CNVD-2020-10487-Tomcat-Ajp-lfi url: https://securityboulevard.com/2020/02/patch-your-tomcat-and-jboss-instances-to-protect-from-ghostcat-vulnerability-cve-2020-1938-1938/ url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog cisa: Known Exploited Vulnerability (KEV) catalog cert-bund: WID-SEC-2024-0528 cert-bund: WID-SEC-2023-2480 cert-bund: CB-K20/0711 cert-bund: CB-K20/0705 cert-bund: CB-K20/0693 cert-bund: CB-K20/0555 cert-bund: CB-K20/0543 cert-bund: CB-K20/0154 dfn-cert: DFN-CERT-2021-1736 dfn-cert: DFN-CERT-2020-1508 dfn-cert: DFN-CERT-2020-1413 dfn-cert: DFN-CERT-2020-1276 dfn-cert: DFN-CERT-2020-1134 dfn-cert: DFN-CERT-2020-0850 dfn-cert: DFN-CERT-2020-0835 dfn-cert: DFN-CERT-2020-0821 dfn-cert: DFN-CERT-2020-0569 dfn-cert: DFN-CERT-2020-0557 dfn-cert: DFN-CERT-2020-0501 dfn-cert: DFN-CERT-2020-0381

[[return to 192.168.56.102](#)]

2.1.4 Critical 80/tcp

Critical (CVSS: 10.0)
NVT: TWiki < 4.2.4 Multiple XSS / Command Execution Vulnerabilities
Summary TWiki is prone to multiple cross-site scripting (XSS) and command execution vulnerabilities.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 4.2.4
Impact Successful exploitation could allow execution of arbitrary script code or commands. This could let attackers steal cookie-based authentication credentials or compromise the affected application.
Solution: Solution type: VendorFix Update to version 4.2.4 or later.
...continues on next page ...

...continued from previous page ...
Affected Software/OS TWiki versions prior to 4.2.4.
Vulnerability Insight The flaws are due to: - %URLPARAM}% variable is not properly sanitized which lets attackers conduct cross-site scripting attack. - %SEARCH}% variable is not properly sanitised before being used in an eval() call which lets the attackers execute perl code through eval injection attack.
Vulnerability Detection Method Details: TWiki < 4.2.4 Multiple XSS / Command Execution Vulnerabilities OID:1.3.6.1.4.1.25623.1.0.800320 Version used: 2025-12-11T05:46:19Z
References cve: CVE-2008-5304 cve: CVE-2008-5305 url: http://twiki.org/cgi-bin/view/Codev/SecurityAlert-CVE-2008-5304 url: http://www.securityfocus.com/bid/32668 url: http://www.securityfocus.com/bid/32669 url: http://twiki.org/cgi-bin/view/Codev/SecurityAlert-CVE-2008-5305

[[return to 192.168.56.102](#)]

2.1.5 Critical 3306/tcp

Critical (CVSS: 9.8) NVT: MySQL / MariaDB Default Credentials (MySQL Protocol)
Product detection result cpe:/a:mysql:mysql:5.0.51a Detected by MariaDB / Oracle MySQL Detection (MySQL Protocol) (OID: 1.3.6.1.4.1.25623.1.0.100152)
Summary It was possible to login into the remote MySQL using default credentials.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to login as user "root" with an empty password.
Solution: Solution type: Mitigation - Change the password as soon as possible - Contact the vendor for other possible fixes / updates
Affected Software/OS The following products are know to use such weak credentials: - CVE-2001-0645: Symantec/AXENT NetProwler 3.5.x - CVE-2002-1809: Windows binary release of MySQL 3.23.2 through 3.23.52 - CVE-2004-1532: AppServ 2.5.x and earlier - CVE-2004-2357: Proofpoint Protection Server - CVE-2006-1451: MySQL Manager in Apple Mac OS X 10.3.9 and 10.4.6 - CVE-2007-2554: Associated Press (AP) Newspower 4.0.1 and earlier - CVE-2007-6081: AdventNet EventLog Analyzer build 4030 - CVE-2009-0919: XAMPP - CVE-2014-3419: Infoblox NetMRI before 6.8.5 - CVE-2015-4669: Xsuite 2.x - CVE-2016-6531, CVE-2018-15719: Open Dental before version 18.4 - CVE-2024-22901: Vinchin Backup & Recovery 7.2 and prior ...continues on next page ...

...continued from previous page ...
- CVE-2026-47847: Bitnami MariaDB Galera container images and Helm chart - No CVE / GHSA-g38h-mr9p-fjmf: Vvveb CMS 1.0.8 and prior Other products might be affected as well.
Vulnerability Detection Method Details: MySQL / MariaDB Default Credentials (MySQL Protocol) OID:1.3.6.1.4.1.25623.1.0.103551 Version used: 2026-07-22T06:26:54Z
Product Detection Result Product: cpe:/a:mysql:mysql:5.0.51a Method: MariaDB / Oracle MySQL Detection (MySQL Protocol) OID: 1.3.6.1.4.1.25623.1.0.100152
References cve: CVE-2001-0645 cve: CVE-2002-1809 cve: CVE-2004-1532 cve: CVE-2004-2357 cve: CVE-2006-1451 cve: CVE-2007-2554 cve: CVE-2007-6081 cve: CVE-2009-0919 cve: CVE-2014-3419 cve: CVE-2015-4669 cve: CVE-2016-6531 cve: CVE-2018-15719 cve: CVE-2024-22901 cve: CVE-2026-47847

[\[return to 192.168.56.102 \]](#)

2.1.6 Critical 1524/tcp

Critical (CVSS: 10.0) NVT: Possible Backdoor: Ingreslock
Summary A backdoor is installed on the remote host.
Quality of Detection (QoD): 99%
Vulnerability Detection Result The service is answering to an 'id;' command with the following response: uid=0(↪root) gid=0(root)
Impact Attackers can exploit this issue to execute arbitrary commands in the context of the application. Successful attacks will compromise the affected system.
Solution: Solution type: Workaround A whole cleanup of the infected system is recommended.
Vulnerability Detection Method Details: Possible Backdoor: Ingreslock OID:1.3.6.1.4.1.25623.1.0.103549 Version used: 2023-07-25T05:05:58Z

[\[return to 192.168.56.102 \]](#)

2.1.7 Critical 5432/tcp

Critical (CVSS: 9.0)
NVT: PostgreSQL Default Credentials (PostgreSQL Protocol)
Product detection result cpe:/a:postgresql:postgresql:8.3.1 Detected by PostgreSQL Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.12802 ↔5)
Summary It was possible to login into the remote PostgreSQL as user postgres using weak credentials.
Quality of Detection (QoD): 99%
Vulnerability Detection Result It was possible to login as user postgres with password "postgres".
Solution: Solution type: Mitigation Change the password as soon as possible.
Vulnerability Detection Method Details: PostgreSQL Default Credentials (PostgreSQL Protocol) OID:1.3.6.1.4.1.25623.1.0.103552 Version used: 2024-07-19T15:39:06Z
Product Detection Result Product: cpe:/a:postgresql:postgresql:8.3.1 Method: PostgreSQL Detection Consolidation OID: 1.3.6.1.4.1.25623.1.0.128025

[[return to 192.168.56.102](#)]

2.1.8 Critical 21/tcp

Critical (CVSS: 9.8)
NVT: vsftpd Compromised Source Packages Backdoor Vulnerability - Active Check
Summary vsftpd is prone to a backdoor vulnerability.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact Attackers can exploit this issue to execute arbitrary commands in the context of the application. Successful attacks will compromise the affected application.
Solution: Solution type: VendorFix The repaired package can be downloaded from the referenced vendor homepage. Please validate the package with its signature.
Affected Software/OS vsftpd 2.3.4 source packages downloaded between 20110630 and 20110703 are affected.
Vulnerability Insight The tainted source package contains a backdoor which opens a shell on port 6200/tcp.
Vulnerability Detection Method Details: vsftpd Compromised Source Packages Backdoor Vulnerability - Active Check ...continues on next page ...

OID:1.3.6.1.4.1.25623.1.0.103185 Version used: 2026-02-18T05:57:21Z	...continued from previous page ...
References cve: CVE-2011-2523 url: https://scarybeastsecurity.blogspot.com/2011/07/alert-vsftpd-download-backdoored.html url: https://web.archive.org/web/20210127090551/https://www.securityfocus.com/bid/48539/	

[[return to 192.168.56.102](#)]

2.1.9 Critical 513/tcp

Critical (CVSS: 10.0)	
NVT: rlogin Passwordless Login	
Summary The rlogin service allows root access without a password.	
Quality of Detection (QoD): 80%	
Vulnerability Detection Result It was possible to gain root access without a password.	
Impact This vulnerability allows an attacker to gain complete control over the target system.	
Solution: Solution type: Mitigation Disable the rlogin service and use alternatives like SSH instead.	
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: rlogin Passwordless Login OID:1.3.6.1.4.1.25623.1.0.113766 Version used: 2020-09-30T09:30:12Z	

[[return to 192.168.56.102](#)]

2.1.10 Critical general/tcp

Critical (CVSS: 10.0)	
NVT: Operating System (OS) End of Life (EOL) Detection	
Product detection result cpe:/o:canonical:ubuntu_linux:8.04 Detected by OS Detection Consolidation and Reporting (OID: 1.3.6.1.4.1.25623.1.0 ↪.105937)	
Summary The Operating System (OS) on the remote host has reached the end of life (EOL) and should not be used anymore.	
Quality of Detection (QoD): 80%	
Vulnerability Detection Result The "Ubuntu" Operating System on the remote host has reached the end of life. CPE: cpe:/o:canonical:ubuntu_linux:8.04 Installed version, ...continues on next page ...	

...continued from previous page ...	
build or SP:	8.04
EOL date:	2013-05-09
EOL info:	https://documentation.ubuntu.com/project/release-team/list-of-releases/
Impact An EOL version of an OS is not receiving any security updates from the vendor. Unfixed security vulnerabilities might be leveraged by an attacker to compromise the security of this host.	
Solution: Solution type: Mitigation Update the OS on the remote host to a version which is still supported and receiving security updates by the vendor. Note / Important: Please create an override for this result if the target host is a: - Windows system with Extended Security Updates (ESU) - System with additional 3rd-party / non-vendor security updates like e.g. from 'TuxCare', 'Freexian Extended LTS' or similar	
Vulnerability Detection Method Checks if an EOL version of an OS is present on the target host. Details: Operating System (OS) End of Life (EOL) Detection OID:1.3.6.1.4.1.25623.1.0.103674 Version used: 2025-05-21T05:40:19Z	
Product Detection Result Product: cpe:/o:canonical:ubuntu_linux:8.04 Method: OS Detection Consolidation and Reporting OID: 1.3.6.1.4.1.25623.1.0.105937	

[\[return to 192.168.56.102 \]](#)

2.1.11 Critical 6200/tcp

Critical (CVSS: 9.8)	
NVT: vsftpd Compromised Source Packages Backdoor Vulnerability - Active Check	
Summary vsftpd is prone to a backdoor vulnerability.	
Quality of Detection (QoD): 99%	
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.	
Impact Attackers can exploit this issue to execute arbitrary commands in the context of the application. Successful attacks will compromise the affected application.	
Solution: Solution type: VendorFix The repaired package can be downloaded from the referenced vendor homepage. Please validate the package with its signature.	
Affected Software/OS vsftpd 2.3.4 source packages downloaded between 20110630 and 20110703 are affected.	
Vulnerability Insight The tainted source package contains a backdoor which opens a shell on port 6200/tcp.	
Vulnerability Detection Method Details: vsftpd Compromised Source Packages Backdoor Vulnerability - Active Check OID:1.3.6.1.4.1.25623.1.0.103185 Version used: 2026-02-18T05:57:21Z	
...continues on next page ...	

...continued from previous page ...

References

cve: CVE-2011-2523

url: <https://scarybeastsecurity.blogspot.com/2011/07/alert-vsftpd-download-backdoored.html>url: <https://web.archive.org/web/20210127090551/https://www.securityfocus.com/bid/48539/>[\[return to 192.168.56.102 \]](#)**2.1.12 Critical 8787/tcp**

Critical (CVSS: 10.0)

NVT: Distributed Ruby (dRuby/DRb) Multiple RCE Vulnerabilities

Summary

Systems using Distributed Ruby (dRuby/DRb), which is available in Ruby versions 1.6 and later, may permit unauthorized systems to execute distributed commands.

Quality of Detection (QoD): 99%

Vulnerability Detection Result

The service is running in \$SAFE >= 1 mode. However it is still possible to run a
 ↳ arbitrary syscall commands on the remote host. Sending an invalid syscall the s
 ↳ ervice returned the following response:

```
Flo:Errno:ENOSYS:bt["3/usr/lib/ruby/1.8/drb/drb.rb:1555:in 'syscall'"0/usr/lib/
↳ ruby/1.8/drb/drb.rb:1555:in 'send'"4/usr/lib/ruby/1.8/drb/drb.rb:1555:in 'se
↳ nd_"A/usr/lib/ruby/1.8/drb/drb.rb:1555:in 'perform_without_block'"3/usr/lib/
↳ ruby/1.8/drb/drb.rb:1515:in 'perform'"5/usr/lib/ruby/1.8/drb/drb.rb:1589:in 'm
↳ ain_loop'"0/usr/lib/ruby/1.8/drb/drb.rb:1585:in 'loop'"5/usr/lib/ruby/1.8/drb/
↳ drb.rb:1585:in 'main_loop'"1/usr/lib/ruby/1.8/drb/drb.rb:1581:in 'start'"5/usr
↳ /lib/ruby/1.8/drb/drb.rb:1581:in 'main_loop'"/usr/lib/ruby/1.8/drb/drb.rb:143
↳ 0:in 'run'"1/usr/lib/ruby/1.8/drb/drb.rb:1427:in 'start'"/usr/lib/ruby/1.8/dr
↳ b/drb.rb:1427:in 'run'"6/usr/lib/ruby/1.8/drb/drb.rb:1347:in 'initialize'"/us
↳ r/lib/ruby/1.8/drb/drb.rb:1627:in 'new'"9/usr/lib/ruby/1.8/drb/drb.rb:1627:in
↳ 'start_service'"/usr/sbin/druby-timeserver.rb:12:errno:mesg"Function not im
↳ plemented
```

Impact

By default, Distributed Ruby does not impose restrictions on allowed hosts or set the \$SAFE environment variable to prevent privileged activities. If other controls are not in place, especially if the Distributed Ruby process runs with elevated privileges, an attacker could execute arbitrary system commands or Ruby scripts on the Distributed Ruby server. An attacker may need to know only the URI of the listening Distributed Ruby server to submit Ruby commands.

Solution:**Solution type:** Mitigation

Administrators of environments that rely on Distributed Ruby should ensure that appropriate controls are in place. Code-level controls may include:

- Implementing taint on untrusted input
- Setting \$SAFE levels appropriately (>=2 is recommended if untrusted hosts are allowed to submit Ruby commands, and >=3 may be appropriate)
- Including drb/acl.rb to set ACLEntry to restrict access to trusted hosts

Vulnerability Detection Method

Send a crafted command to the service and check for a remote command execution via the instance_eval or syscall requests.

Details: Distributed Ruby (dRuby/DRb) Multiple RCE Vulnerabilities

OID:1.3.6.1.4.1.25623.1.0.108010

Version used: 2024-06-28T05:05:33Z

Referencesurl: <https://tools.cisco.com/security/center/viewAlert.x?alertId=22750>url: <http://www.securityfocus.com/bid/47071>url: http://blog.recurity-labs.com/archives/2011/05/12/druby_for_penetration_testers/url: <http://www.ruby-doc.org/stdlib-1.9.3/libdoc/drb/rdoc/DRb.html>[\[return to 192.168.56.102 \]](#)

2.1.13 Critical 512/tcp

Critical (CVSS: 10.0) NVT: The rexec service is running
Summary This remote host is running a rexec service.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The rexec service was detected on the target system.
Solution: Solution type: Mitigation Disable the rexec service and use alternatives like SSH instead.
Vulnerability Insight rexec (remote execution client for an exec server) has the same kind of functionality that rsh has: you can execute shell commands on a remote computer. The main difference is that rexec authenticates by reading the username and password *unencrypted* from the socket.
Vulnerability Detection Method Checks whether an rexec service is exposed on the target host. Details: The rexec service is running OID: 1.3.6.1.4.1.25623.1.0.100111 Version used: 2023-09-12T05:05:19Z
References cve: CVE-1999-0618

[[return to 192.168.56.102](#)]

2.1.14 High 1099/tcp

High (CVSS: 7.5) NVT: Java RMI Server Insecure Default Configuration RCE Vulnerability - Active Check
Summary Multiple Java products that implement the RMI Server contain a vulnerability that could allow an unauthenticated, remote attacker to execute arbitrary code (remote code execution/RCE) on a targeted system with elevated privileges.
Quality of Detection (QoD): 95%
Vulnerability Detection Result By doing an RMI request it was possible to trigger the vulnerability and make the → remote host send a request back to the scanner host (Details on the received ↔ packet follows). Destination IP: 192.168.56.103 (receiving IP on scanner host side) Destination port: 16670/tcp (receiving port on scanner host side) Originating IP: 192.168.56.102 (originating IP from target host side)
Impact An unauthenticated, remote attacker could exploit the vulnerability by transmitting crafted packets to the affected software. When the packets are processed, the attacker could execute arbitrary code on the system with elevated privileges.
Solution: Solution type: Workaround Disable class-loading. Please contact the vendor of the affected system for additional guidance.
... continues on next page ...

...continued from previous page ...
Vulnerability Insight The vulnerability exists because of an incorrect default configuration of the Remote Method Invocation (RMI) Server in the affected software.
Vulnerability Detection Method Sends a crafted JRMI request and checks if the target is connecting back to the scanner host. Note: For a successful detection of this flaw the target host needs to be able to reach the scanner host on a TCP port randomly generated during the runtime of the VT (currently in the range of 10000-32000). Details: Java RMI Server Insecure Default Configuration RCE Vulnerability - Active Check OID:1.3.6.1.4.1.25623.1.0.140051 Version used: 2026-04-17T15:51:27Z
References cve: CVE-2011-3556 url: https://web.archive.org/web/20211208040855/http://www.securitytracker.com/id?1026215 url: https://web.archive.org/web/20110824060234/http://download.oracle.com/javase/1.3/docs/guide/rmi/spec/rmi-protocol.html url: https://tools.cisco.com/security/center/viewAlert.x?alertId=23665 dfn-cert: DFN-CERT-2012-1829 dfn-cert: DFN-CERT-2012-1380 dfn-cert: DFN-CERT-2012-1377 dfn-cert: DFN-CERT-2012-1156 dfn-cert: DFN-CERT-2012-1155 dfn-cert: DFN-CERT-2012-0956 dfn-cert: DFN-CERT-2012-0828 dfn-cert: DFN-CERT-2012-0815 dfn-cert: DFN-CERT-2012-0638 dfn-cert: DFN-CERT-2012-0451 dfn-cert: DFN-CERT-2012-0418 dfn-cert: DFN-CERT-2012-0354 dfn-cert: DFN-CERT-2012-0146 dfn-cert: DFN-CERT-2012-0142 dfn-cert: DFN-CERT-2012-0126 dfn-cert: DFN-CERT-2012-0095 dfn-cert: DFN-CERT-2012-0047 dfn-cert: DFN-CERT-2011-1844 dfn-cert: DFN-CERT-2011-1826 dfn-cert: DFN-CERT-2011-1804 dfn-cert: DFN-CERT-2011-1743 dfn-cert: DFN-CERT-2011-1738 dfn-cert: DFN-CERT-2011-1706 dfn-cert: DFN-CERT-2011-1628 dfn-cert: DFN-CERT-2011-1627 dfn-cert: DFN-CERT-2011-1619

[[return to 192.168.56.102](#)]

2.1.15 High 80/tcp

High (CVSS: 7.5)
NVT: PHP < 5.3.13, 5.4.x < 5.4.3 Multiple Vulnerabilities - Active Check
Summary PHP is prone to multiple vulnerabilities.
Quality of Detection (QoD): 95%
Vulnerability Detection Result By doing the following HTTP POST request: "HTTP POST" body : <?php phpinfo();> URL : http://192.168.56.102/cgi-bin/php?%2D%64+%61%6C%6C%6F%77%5F%7 ↳5%72%6C%5F%69%6E%63%6C%75%64%65%3D%6F%6E+%2D%64+%73%61%66%65%5F%6D%6F%64%65%3D ↳%6F%66%66+%2D%64+%73%75%68%6F%73%69%6E%2E%73%69%6D%75%6C%61%74%69%6F%6E%3D%6F% ↳6E+%2D%64+%64%69%73%61%62%6C%65%5F%66%75%6E%63%74%69%6F%6E%73%3D%22%22+%2D%64+ ↳%6F%70%65%6E%5F%62%61%73%65%64%69%72%3D%6E%6F%6E%65+%2D%64+%61%75%74%6F%5F%70%
...continues on next page ...

...continued from previous page ...	
<pre> ↪72%65%70%65%6E%64%5F%66%69%6C%65%3D%70%68%70%3A%2F%2F%69%6E%70%75%74+%2D%64+%6 ↪3%67%69%2E%66%6F%72%63%65%5F%72%65%64%69%72%65%63%74%3D%30+%2D%64+%63%67%69%2E ↪%72%65%64%69%72%65%63%74%5F%73%74%61%74%75%73%5F%65%6E%76%3D%30+%2D%6E it was possible to execute the "<?php phpinfo();?>" command. Result: <title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV ↪E" /></head> <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph ↪p5/cgi </td></tr> <h2>PHP Core</h2> <h2>PHP Variables</h2> </pre>	
Impact	Exploiting this issue allows remote attackers to view the source code of files in the context of the server process. This may allow the attacker to obtain sensitive information and to run arbitrary PHP code on the affected computer. Other attacks are also possible.
Solution:	
Solution type:	VendorFix
	PHP: Update to version 5.3.13, 5.4.3 or later
	- Other products / applications: Please contact the vendor for a solution
Affected Software/OS	
	PHP versions prior to 5.3.13 and 5.4.x prior to 5.4.3.
	Other products / applications might be affected by the tested CVE-2012-1823 as well.
Vulnerability Insight	When PHP is used in a CGI-based setup (such as Apache's mod_cgid), the php-cgi receives a processed query string parameter as command line arguments which allows command-line switches, such as -s, -d or -c to be passed to the php-cgi binary, which can be exploited to disclose source code and obtain arbitrary code execution. An example of the -s command, allowing an attacker to view the source code of index.php is below: http://example.com/index.php?-s
Vulnerability Detection Method	Send multiple a crafted HTTP POST requests and checks the responses.
Notes:	
	- This script checks for the presence of CVE-2012-1823 which indicates that the system is also affected by the other included CVEs.
	- It is currently expected that a result of this VT is reported if the system is generally exposing a phpinfo() output on the relevant URL / endpoint (independent from the running product). Exposing such sensitive information is generally seen as a security misconfiguration and should be avoided.
	Details: PHP < 5.3.13, 5.4.x < 5.4.3 Multiple Vulnerabilities - Active Check
	OID:1.3.6.1.4.1.25623.1.0.103482
	Version used: 2026-04-23T06:21:05Z
References	
	cve: CVE-2012-1823
	cve: CVE-2012-2311
	cve: CVE-2012-2336
	cve: CVE-2012-2335
	url: https://web.archive.org/web/20190212080415/http://eindbazen.net/2012/05/php-cgi-advisory-cve-2012-1823/
	url: https://www.kb.cert.org/vuls/id/520827
	url: https://bugs.php.net/bug.php?id=61910
	url: https://www.php.net/manual/en/security.cgi-bin.php
	url: https://web.archive.org/web/20210121223743/http://www.securityfocus.com/bid/53388
	url: https://web.archive.org/web/20120709064615/http://www.h-online.com/open/news/item/Critical-open-hole-in-PHP-creates-risks-Update-2-1567532.html
	url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog
	cisa: Known Exploited Vulnerability (KEV) catalog
	dfn-cert: DFN-CERT-2013-1494
	dfn-cert: DFN-CERT-2012-1316
	dfn-cert: DFN-CERT-2012-1276
	dfn-cert: DFN-CERT-2012-1268
	dfn-cert: DFN-CERT-2012-1267
	dfn-cert: DFN-CERT-2012-1266
	dfn-cert: DFN-CERT-2012-1173
	dfn-cert: DFN-CERT-2012-1101
	dfn-cert: DFN-CERT-2012-0994
	dfn-cert: DFN-CERT-2012-0993
	dfn-cert: DFN-CERT-2012-0992
...continues on next page ...	

dfn-cert: DFN-CERT-2012-0920	...continued from previous page ...
dfn-cert: DFN-CERT-2012-0915	
dfn-cert: DFN-CERT-2012-0914	
dfn-cert: DFN-CERT-2012-0913	
dfn-cert: DFN-CERT-2012-0907	
dfn-cert: DFN-CERT-2012-0906	
dfn-cert: DFN-CERT-2012-0900	
dfn-cert: DFN-CERT-2012-0880	
dfn-cert: DFN-CERT-2012-0878	

High (CVSS: 7.5)
NVT: Test HTTP dangerous methods
Summary Misconfigured web servers allows remote clients to perform dangerous HTTP methods such as PUT and DELETE.
Quality of Detection (QoD): 99%
Vulnerability Detection Result We could upload the following files via the PUT method at this web server: http://192.168.56.102/dav/puttest1434520156.html We could delete the following files via the DELETE method at this web server: http://192.168.56.102/dav/puttest1434520156.html
Impact - Enabled PUT method: This might allow an attacker to upload and run arbitrary code on this web server. - Enabled DELETE method: This might allow an attacker to delete additional files on this web server.
Solution: Solution type: Mitigation Use access restrictions to these dangerous HTTP methods or disable them completely.
Affected Software/OS Web servers with enabled PUT and/or DELETE methods.
Vulnerability Detection Method Checks if dangerous HTTP methods such as PUT and DELETE are enabled and can be misused to upload or delete files. Details: Test HTTP dangerous methods OID:1.3.6.1.4.1.25623.1.0.10498 Version used: 2023-08-01T13:29:10Z
References url: http://www.securityfocus.com/bid/12141 owasp: OWASP-CM-001

High (CVSS: 7.5)
NVT: EasyPHP Webserver <= 12.1 Multiple Vulnerabilities - Active Check
Summary EasyPHP Webserver is prone to multiple vulnerabilities.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerable URL: http://192.168.56.102/phpinfo.php Concluded from: <pre><title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV ↵E" /></head> <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph ↵p5/cgi </td></tr> <h2>PHP Core</h2> <h2>PHP Variables</h2></pre>
...continues on next page ...

...continued from previous page ...
Impact Successful exploitation will allow attackers to gain administrative access, disclose the information, inject PHP code/shell and execute a remote PHP Code.
Solution: Solution type: WillNotFix No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
Affected Software/OS EasyPHP version 12.1 and prior.
Vulnerability Insight The bug in EasyPHP WebServer Manager, its skipping authentication for certain requests. Which allows to bypass the authentication, disclose the information or execute a remote PHP code.
Vulnerability Detection Method Sends a crafted HTTP GET request and checks the response. Note: It is currently expected that a result of this VT is reported if the system is generally exposing a phpinfo() output on the relevant URL / endpoint (independent from the running product). Exposing such sensitive information is generally seen as a security misconfiguration and should be avoided. Details: EasyPHP Webserver <= 12.1 Multiple Vulnerabilities - Active Check OID:1.3.6.1.4.1.25623.1.0.803189 Version used: 2025-11-11T05:40:18Z
References url: https://cxsecurity.com/issue/WLB-2013040069

[[return to 192.168.56.102](#)]

2.1.16 High 2121/tcp

High (CVSS: 7.5) NVT: FTP Brute Force Logins With Default Credentials Reporting
Summary It was possible to login into the remote FTP server using weak/known credentials.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to login with the following credentials <User>:<Password> msfadmin:msfadmin postgres:postgres service:service user:user
Impact This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.
Solution: Solution type: Mitigation Change the password as soon as possible.
Vulnerability Insight The following devices are / software is known to be affected: - CVE-2001-1594: Codonics printer FTP service as used in GE Healthcare eNTEGRA P&R - CVE-2013-7404: GE Healthcare Discovery NM 750b - CVE-2014-9198: Schneider Electric ETG3000 FactoryCast HMI gateways - CVE-2015-7261: QNAP iArtist Lite distributed with QNAP Signage Station ...continues on next page ...

...continued from previous page ...
- CVE-2016-8731: Foscam C1 devices - CVE-2017-8218: vsftpd on TP-Link C2 and C20i devices - CVE-2018-9068: IMM2 for IBM and Lenovo System x - CVE-2018-17771: Ingenico Telium 2 PoS terminals - CVE-2018-19063, CVE-2018-19064: Foscam C2 and Opticam i5 devices - CVE-2018-25147: Microhard Systems IPn4G - CVE-2020-36915: Adtec Digital SignEdge Digital Signage Player Note: As the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.
Vulnerability Detection Method Reports weak/known credentials detected by the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717). Details: FTP Brute Force Logins With Default Credentials Reporting OID:1.3.6.1.4.1.25623.1.0.108718 Version used: 2026-01-16T15:42:49Z
References cve: CVE-1999-0501 cve: CVE-1999-0502 cve: CVE-1999-0507 cve: CVE-1999-0508 cve: CVE-2001-1594 cve: CVE-2013-7404 cve: CVE-2014-9198 cve: CVE-2015-7261 cve: CVE-2016-8731 cve: CVE-2017-8218 cve: CVE-2018-9068 cve: CVE-2018-17771 cve: CVE-2018-19063 cve: CVE-2018-19064 cve: CVE-2018-25147 cve: CVE-2020-36915

[\[return to 192.168.56.102 \]](#)

2.1.17 High 5432/tcp

High (CVSS: 7.4)
NVT: SSL/TLS: OpenSSL CCS Man in the Middle Security Bypass Vulnerability
Summary OpenSSL is prone to a security bypass vulnerability.
Quality of Detection (QoD): 70%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact Successfully exploiting this issue may allow attackers to obtain sensitive information by conducting a man-in-the-middle attack. This may lead to other attacks.
Solution: Solution type: VendorFix Updates are available. Please see the references for more information.
Affected Software/OS OpenSSL before 0.9.8za, 1.0.0 before 1.0.0m and 1.0.1 before 1.0.1h.
Vulnerability Insight ...continues on next page ...

...continued from previous page ...
OpenSSL does not properly restrict processing of ChangeCipherSpec messages, which allows man-in-the-middle attackers to trigger use of a zero-length master key in certain OpenSSL-to-OpenSSL communications, and consequently hijack sessions or obtain sensitive information, via a crafted TLS handshake, aka the 'CCS Injection' vulnerability.
Vulnerability Detection Method Send two SSL ChangeCipherSpec request and check the response. Details: SSL/TLS: OpenSSL CCS Man in the Middle Security Bypass Vulnerability OID:1.3.6.1.4.1.25623.1.0.105042 Version used: 2025-01-17T15:39:18Z
References cve: CVE-2014-0224 url: https://www.openssl.org/news/secadv/20140605.txt url: http://www.securityfocus.com/bid/67899 cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2023-0500 cert-bund: CB-K15/0567 cert-bund: CB-K15/0415 cert-bund: CB-K15/0384 cert-bund: CB-K15/0080 cert-bund: CB-K15/0079 cert-bund: CB-K15/0074 cert-bund: CB-K14/1617 cert-bund: CB-K14/1537 cert-bund: CB-K14/1299 cert-bund: CB-K14/1297 cert-bund: CB-K14/1294 cert-bund: CB-K14/1202 cert-bund: CB-K14/1174 cert-bund: CB-K14/1153 cert-bund: CB-K14/0876 cert-bund: CB-K14/0756 cert-bund: CB-K14/0746 cert-bund: CB-K14/0736 cert-bund: CB-K14/0722 cert-bund: CB-K14/0716 cert-bund: CB-K14/0708 cert-bund: CB-K14/0684 cert-bund: CB-K14/0683 cert-bund: CB-K14/0680 dfn-cert: DFN-CERT-2016-0388 dfn-cert: DFN-CERT-2015-0593 dfn-cert: DFN-CERT-2015-0427 dfn-cert: DFN-CERT-2015-0396 dfn-cert: DFN-CERT-2015-0082 dfn-cert: DFN-CERT-2015-0079 dfn-cert: DFN-CERT-2015-0078 dfn-cert: DFN-CERT-2014-1717 dfn-cert: DFN-CERT-2014-1632 dfn-cert: DFN-CERT-2014-1364 dfn-cert: DFN-CERT-2014-1357 dfn-cert: DFN-CERT-2014-1350 dfn-cert: DFN-CERT-2014-1265 dfn-cert: DFN-CERT-2014-1209 dfn-cert: DFN-CERT-2014-0917 dfn-cert: DFN-CERT-2014-0789 dfn-cert: DFN-CERT-2014-0778 dfn-cert: DFN-CERT-2014-0768 dfn-cert: DFN-CERT-2014-0752 dfn-cert: DFN-CERT-2014-0747 dfn-cert: DFN-CERT-2014-0738 dfn-cert: DFN-CERT-2014-0715 dfn-cert: DFN-CERT-2014-0714 dfn-cert: DFN-CERT-2014-0709

[[return to 192.168.56.102](#)]

2.1.18 High 514/tcp

High (CVSS: 7.5)
NVT: rsh Unencrypted Cleartext Login
Summary This remote host is running a rsh service.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The rsh service currently has issues with name resolution and is not allowing connections from this host.
Solution: Solution type: Mitigation Disable the rsh service and use alternatives like SSH instead.
Vulnerability Insight rsh (remote shell) is a command line computer program which can execute shell commands as another user, and on another computer across a computer network. Remark: NIST don't see 'configuration issues' as software flaws so the referenced CVE has a severity of 0.0. The severity of this VT has been raised by Greenbone to still report a configuration issue on the target.
Vulnerability Detection Method Details: rsh Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.100080 Version used: 2021-10-20T09:03:29Z
References cve: CVE-1999-0651

[[return to 192.168.56.102](#)]

2.1.19 High 21/tcp

High (CVSS: 7.5)
NVT: FTP Brute Force Logins With Default Credentials Reporting
Summary It was possible to login into the remote FTP server using weak/known credentials.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to login with the following credentials <User>:<Password> msfadmin:msfadmin postgres:postgres service:service user:user
Impact This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.
Solution: Solution type: Mitigation Change the password as soon as possible.
Vulnerability Insight The following devices are / software is known to be affected: - CVE-2001-1594: Codonics printer FTP service as used in GE Healthcare eNTEGRA P&R - CVE-2013-7404: GE Healthcare Discovery NM 750b - CVE-2014-9198: Schneider Electric ETG3000 FactoryCast HMI gateways - CVE-2015-7261: QNAP iArtist Lite distributed with QNAP Signage Station ...continues on next page ...

...continued from previous page ...
- CVE-2016-8731: Foscam C1 devices - CVE-2017-8218: vsftpd on TP-Link C2 and C20i devices - CVE-2018-9068: IMM2 for IBM and Lenovo System x - CVE-2018-17771: Ingenico Telium 2 PoS terminals - CVE-2018-19063, CVE-2018-19064: Foscam C2 and Opticam i5 devices - CVE-2018-25147: Microhard Systems IPn4G - CVE-2020-36915: Adtec Digital SignEdge Digital Signage Player Note: As the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.
Vulnerability Detection Method Reports weak/known credentials detected by the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717). Details: FTP Brute Force Logins With Default Credentials Reporting OID:1.3.6.1.4.1.25623.1.0.108718 Version used: 2026-01-16T15:42:49Z
References cve: CVE-1999-0501 cve: CVE-1999-0502 cve: CVE-1999-0507 cve: CVE-1999-0508 cve: CVE-2001-1594 cve: CVE-2013-7404 cve: CVE-2014-9198 cve: CVE-2015-7261 cve: CVE-2016-8731 cve: CVE-2017-8218 cve: CVE-2018-9068 cve: CVE-2018-17771 cve: CVE-2018-19063 cve: CVE-2018-19064 cve: CVE-2018-25147 cve: CVE-2020-36915

[\[return to 192.168.56.102 \]](#)

2.1.20 High 513/tcp

High (CVSS: 7.5)
NVT: The rlogin service is running
Summary This remote host is running a rlogin service.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The rlogin service is running on the target system.
Solution: Solution type: Mitigation Disable the rlogin service and use alternatives like SSH instead.
Vulnerability Insight rlogin has several serious security problems, - all information, including passwords, is transmitted unencrypted. - .rlogin (or .rhosts) file is easy to misuse (potentially allowing anyone to login without a password)
Vulnerability Detection Method Details: The rlogin service is running OID:1.3.6.1.4.1.25623.1.0.901202 Version used: 2025-03-05T05:38:53Z
References ...continues on next page ...

cve: CVE-1999-0651	...continued from previous page ...
--------------------	-------------------------------------

[\[return to 192.168.56.102 \]](#)

2.1.21 Medium 445/tcp

Medium (CVSS: 6.0) NVT: Samba 3.0.0 <= 3.0.25rc3 MS-RPC Remote Shell Command Execution Vulnerability - Active Check
Product detection result cpe:/a:samba:samba:3.0.20 Detected by SMB NativeLanMan (OID: 1.3.6.1.4.1.25623.1.0.102011)
Summary Samba is prone to a vulnerability that allows attackers to execute arbitrary shell commands because the software fails to sanitize user-supplied input.
Quality of Detection (QoD): 99%
Vulnerability Detection Result By sending a special crafted SMB request it was possible to execute ‘ping -p 5f ↪4f70656e564153565435353830345f -c50 192.168.56.103‘ on the remote host. Received answer (ICMP "Data" field): 0x00: 57 9A 95 6A 54 08 08 00 56 54 35 35 38 30 34 5F W..jT...VT55804_ 0x10: 5F 4F 70 65 6E 56 41 53 56 54 35 35 38 30 34 5F _OpenVASVT55804_ 0x20: 5F 4F 70 65 6E 56 41 53 56 54 35 35 38 30 34 5F _OpenVASVT55804_ 0x30: 5F 4F 70 65 6E 56 41 53 _OpenVAS
Impact An attacker may leverage this issue to execute arbitrary shell commands on an affected system with the privileges of the application.
Solution: Solution type: VendorFix Updates are available. Please see the referenced vendor advisory.
Affected Software/OS Samba versions 3.0.0 through 3.0.25rc3.
Vulnerability Detection Method Sends a crafted SMB request and checks if the target is sending an ICMP Echo Request back to the scanner host. Note: For a successful detection of this flaw the scanner host needs to be able to directly receive ICMP Echo Requests (Type 8) from the target. Details: Samba 3.0.0 <= 3.0.25rc3 MS-RPC Remote Shell Command Execution Vulnerability - . ↪.. OID:1.3.6.1.4.1.25623.1.0.108011 Version used: 2026-03-12T05:56:11Z
Product Detection Result Product: cpe:/a:samba:samba:3.0.20 Method: SMB NativeLanMan OID: 1.3.6.1.4.1.25623.1.0.102011
References cve: CVE-2007-2447 url: https://www.samba.org/samba/security/CVE-2007-2447.html url: https://web.archive.org/web/20210121173708/http://www.securityfocus.com/bid/23972

[\[return to 192.168.56.102 \]](#)

2.1.22 Medium 5900/tcp

Medium (CVSS: 4.8)
NVT: VNC Server Unencrypted Data Transmission
Summary The remote host is running a VNC server providing one or more insecure or cryptographically weak Security Type(s) not intended for use on untrusted networks.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The VNC server provides the following insecure or cryptographically weak Security Type(s): 2 (VNC authentication)
Impact An attacker can uncover sensitive data by sniffing traffic to the VNC server.
Solution: Solution type: Mitigation Run the session over an encrypted channel provided by IPsec [RFC4301] or SSH [RFC4254]. Some VNC server vendors are also providing more secure Security Types within their products.
Vulnerability Detection Method Details: VNC Server Unencrypted Data Transmission OID:1.3.6.1.4.1.25623.1.0.108529 Version used: 2023-07-12T05:05:04Z
References url: https://tools.ietf.org/html/rfc6143#page-10

[[return to 192.168.56.102](#)]

2.1.23 Medium 80/tcp

Medium (CVSS: 6.8)
NVT: TWiki Cross-Site Request Forgery Vulnerability (Sep 2010)
Summary TWiki is prone to a cross-site request forgery (CSRF) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 4.3.2
Impact Successful exploitation will allow attacker to gain administrative privileges on the target application and can cause CSRF attack.
Solution: Solution type: VendorFix Upgrade to TWiki version 4.3.2 or later.
Affected Software/OS TWiki version prior to 4.3.2
Vulnerability Insight Attack can be done by tricking an authenticated TWiki user into visiting a static HTML page on another side, where a Javascript enabled browser will send an HTTP POST request to TWiki, which in turn will process the request as the TWiki user.
Vulnerability Detection Method ...continues on next page ...

...continued from previous page ...
Details: TWiki Cross-Site Request Forgery Vulnerability (Sep 2010) OID:1.3.6.1.4.1.25623.1.0.801281 Version used: 2024-03-01T14:37:10Z
References cve: CVE-2009-4898 url: http://www.openwall.com/lists/oss-security/2010/08/03/8 url: http://www.openwall.com/lists/oss-security/2010/08/02/17 url: http://twiki.org/cgi-bin/view/Codev/SecurityAuditTokenBasedCsrfFix url: http://twiki.org/cgi-bin/view/Codev/DownloadTWiki

Medium (CVSS: 6.1) NVT: TWiki < 6.1.0 XSS Vulnerability
Summary bin/statistics in TWiki 6.0.2 allows XSS via the webs parameter.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 6.1.0
Solution: Solution type: VendorFix Update to version 6.1.0 or later.
Affected Software/OS TWiki version 6.0.2 and probably prior.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: TWiki < 6.1.0 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141830 Version used: 2023-07-14T16:09:27Z
References cve: CVE-2018-20212 url: https://seclists.org/fulldisclosure/2019/Jan/7 url: http://twiki.org/cgi-bin/view/Codev/DownloadTWiki

Medium (CVSS: 6.1) NVT: jQuery < 1.9.0 XSS Vulnerability
Summary jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 1.3.2 Fixed version: 1.9.0 Installation path / port: /mutillidae/javascript/ddsmoothmenu/jquery.min.js Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info): - Identified file: http://192.168.56.102/mutillidae/javascript/ddsmoothmenu/jquery.min.js - Referenced at: http://192.168.56.102/mutillidae/
Solution: Solution type: VendorFix Update to version 1.9.0 or later.
...continues on next page ...

...continued from previous page ...
Affected Software/OS jQuery prior to version 1.9.0.
Vulnerability Insight The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: jQuery < 1.9.0 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141636 Version used: 2023-07-14T05:06:08Z
References cve: CVE-2012-6708 url: https://bugs.jquery.com/ticket/11290 cert-bund: WID-SEC-2026-1752 cert-bund: WID-SEC-2022-0673 cert-bund: CB-K22/0045 cert-bund: CB-K18/1131 dfn-cert: DFN-CERT-2025-1803 dfn-cert: DFN-CERT-2023-1197 dfn-cert: DFN-CERT-2020-0590

Medium (CVSS: 6.0)
NVT: TWiki CSRF Vulnerability
Summary TWiki is prone to a cross-site request forgery (CSRF) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 4.3.1
Impact Successful exploitation will allow attacker to gain administrative privileges on the target application and can cause CSRF attack.
Solution: Solution type: VendorFix Upgrade to version 4.3.1 or later.
Affected Software/OS TWiki version prior to 4.3.1
Vulnerability Insight Remote authenticated user can create a specially crafted image tag that, when viewed by the target user, will update pages on the target system with the privileges of the target user via HTTP requests.
Vulnerability Detection Method Details: TWiki CSRF Vulnerability OID:1.3.6.1.4.1.25623.1.0.800400 Version used: 2024-06-28T05:05:33Z
References cve: CVE-2009-1339 url: http://secunia.com/advisories/34880 url: http://bugs.debian.org/cgi-bin/bugreport.cgi?bug=526258 url: http://twiki.org/pub/Coder/SecurityAlert-CVE-2009-1339/TWiki-4.3.0-c-diff-cve-2009-1339.txt

Medium (CVSS: 5.8)
NVT: HTTP Debugging Methods (TRACE/TRACK) Enabled
Summary The remote web server supports the TRACE and/or TRACK methods. TRACE and TRACK are HTTP methods which are used to debug web server connections.
Quality of Detection (QoD): 99%
Vulnerability Detection Result The web server has the following HTTP methods enabled: TRACE
Impact An attacker may use this flaw to trick your legitimate web users to give him their credentials.
Solution: Solution type: Mitigation Disable the TRACE and TRACK methods in your web server configuration. Please see the manual of your web server or the references for more information.
Affected Software/OS Web servers with enabled TRACE and/or TRACK methods.
Vulnerability Insight It has been shown that web servers supporting this methods are subject to cross-site-scripting attacks, dubbed XST for Cross-Site-Tracing, when used in conjunction with various weaknesses in browsers.
Vulnerability Detection Method Checks if HTTP methods such as TRACE and TRACK are enabled and can be used. Details: HTTP Debugging Methods (TRACE/TRACK) Enabled OID:1.3.6.1.4.1.25623.1.0.11213 Version used: 2023-08-01T13:29:10Z
References cve: CVE-2003-1567 cve: CVE-2004-2320 cve: CVE-2004-2763 cve: CVE-2005-3398 cve: CVE-2006-4683 cve: CVE-2007-3008 cve: CVE-2008-7253 cve: CVE-2009-2823 cve: CVE-2010-0386 cve: CVE-2012-2223 cve: CVE-2014-7883 url: http://www.kb.cert.org/vuls/id/288308 url: http://www.securityfocus.com/bid/11604 url: http://www.securityfocus.com/bid/15222 url: http://www.securityfocus.com/bid/19915 url: http://www.securityfocus.com/bid/24456 url: http://www.securityfocus.com/bid/33374 url: http://www.securityfocus.com/bid/36956 url: http://www.securityfocus.com/bid/36990 url: http://www.securityfocus.com/bid/37995 url: http://www.securityfocus.com/bid/9506 url: http://www.securityfocus.com/bid/9561 url: http://www.kb.cert.org/vuls/id/867593 url: https://httpd.apache.org/docs/current/en/mod/core.html#traceenable url: https://techcommunity.microsoft.com/t5/iis-support-blog/http-track-and-trace-verbs/ba-p/784482 url: https://owasp.org/www-community/attacks/Cross_Site_Tracing cert-bund: CB-K14/0981 dfn-cert: DFN-CERT-2021-1825 dfn-cert: DFN-CERT-2014-1018 dfn-cert: DFN-CERT-2010-0020

Medium (CVSS: 5.3)
NVT: phpinfo() Output Reporting (HTTP)
Summary Reporting of files containing the output of the phpinfo() PHP function previously detected via HTTP.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following files are calling the function phpinfo() which disclose potentiall ↳ y sensitive information: http://192.168.56.102/mutillidae/phpinfo.php Concluded from: <title>phpinfo(</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV ↳ E" /></head> <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph ↳ p5/cgi </td></tr> PHP Core PHP Variables http://192.168.56.102/phpinfo.php Concluded from: <title>phpinfo(</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV ↳ E" /></head> <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph ↳ p5/cgi </td></tr> PHP Core PHP Variables
Impact Some of the information that can be gathered from this file includes: The username of the user running the PHP process, if it is a sudo user, the IP address of the host, the web server version, the system version (Unix, Linux, Windows, ...), and the root directory of the web server.
Solution: Solution type: Workaround Delete the listed files or restrict access to them.
Affected Software/OS All systems exposing a file containing the output of the phpinfo() PHP function. This VT is also reporting if an affected endpoint for the following products have been identified: - CVE-2008-0149: TUTOS - CVE-2023-49282, CVE-2023-49283: Microsoft Graph PHP SDK - CVE-2024-10486: Google for WooCommerce plugin for WordPress
Vulnerability Insight Many PHP installation tutorials instruct the user to create a file called phpinfo.php or similar containing the phpinfo() statement. Such a file is often left back in the webserver directory.
Vulnerability Detection Method This script reports files identified by the following separate VT: 'phpinfo() Output Detection (HTTP)' (OID: 1.3.6.1.4.1.25623.1.0.108474). Details: phpinfo() Output Reporting (HTTP) OID:1.3.6.1.4.1.25623.1.0.11229 Version used: 2025-07-09T05:43:50Z
References cve: CVE-2008-0149 cve: CVE-2023-49282 cve: CVE-2023-49283 cve: CVE-2024-10486 url: https://www.php.net/manual/en/function.phpinfo.php url: https://beaglesecurity.com/blog/vulnerability/revealing-phpinfo.html

Medium (CVSS: 5.0)
NVT: /doc directory browsable
... continues on next page ...

...continued from previous page ...
Summary The /doc directory is browsable. /doc shows the content of the /usr/doc directory and therefore it shows which programs and - important! - the version of the installed programs.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Vulnerable URL: http://192.168.56.102/doc/
Solution: Solution type: Mitigation Use access restrictions for the /doc directory. If you use Apache you might use this in your access.conf: <Directory /usr/doc> AllowOverride None order deny, allow deny from all allow from localhost </Directory>
Vulnerability Detection Method Details: /doc directory browsable OID:1.3.6.1.4.1.25623.1.0.10056 Version used: 2023-08-01T13:29:10Z
References cve: CVE-1999-0678 url: http://www.securityfocus.com/bid/318

Medium (CVSS: 5.0)
NVT: awiki <= 20100125 Multiple LFI Vulnerabilities - Active Check
Summary awiki is prone to multiple local file include (LFI) vulnerabilities because it fails to properly sanitize user-supplied input.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerable URL: http://192.168.56.102/mutillidae/index.php?page=/etc/passwd
Impact An attacker can exploit this vulnerability to obtain potentially sensitive information and execute arbitrary local scripts in the context of the webserver process. This may allow the attacker to compromise the application and the host.
Solution: Solution type: WillNotFix No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
Affected Software/OS awiki version 20100125 and prior.
Vulnerability Detection Method Sends a crafted HTTP GET request and checks the response. Details: awiki <= 20100125 Multiple LFI Vulnerabilities - Active Check OID:1.3.6.1.4.1.25623.1.0.103210 Version used: 2025-04-15T05:54:49Z
References url: https://www.exploit-db.com/exploits/36047/ url: http://www.securityfocus.com/bid/49187

Medium (CVSS: 5.0)
NVT: QWikiwiki directory traversal vulnerability
Summary The remote host is running QWikiwiki, a Wiki application written in PHP.
...continues on next page ...

...continued from previous page ...
The remote version of this software contains a validation input flaw which may allow an attacker to use it to read arbitrary files on the remote host with the privileges of the web server.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerable URL: http://192.168.56.102/mutillidae/index.php?page=../../../../../../etc/passwd%00 ↪../../../../../../etc/passwd%00
Solution: Solution type: WillNotFix No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
Vulnerability Detection Method Details: QWikiwiki directory traversal vulnerability OID:1.3.6.1.4.1.25623.1.0.16100 Version used: 2025-04-15T05:54:49Z
References cve: CVE-2005-0283 url: http://www.securityfocus.com/bid/12163

Medium (CVSS: 4.8)
NVT: Cleartext Transmission of Sensitive Information via HTTP
Summary The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following input fields were identified (URL:input name): http://192.168.56.102/dvwa/login.php :password http://192.168.56.102/phpMyAdmin/ :pma_password http://192.168.56.102/phpMyAdmin/?D=A :pma_password http://192.168.56.102/tikiwiki/tiki-install.php :pass http://192.168.56.102/twiki/bin/view/TWiki/TWikiUserAuthentication :oldpassword
Impact An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.
Solution: Solution type: Workaround Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.
Affected Software/OS Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.
Vulnerability Detection Method Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection. The script is currently checking the following: - HTTP Basic Authentication (Basic Auth) - HTTP Forms (e.g. Login) with input field of type 'password' Details: Cleartext Transmission of Sensitive Information via HTTP OID:1.3.6.1.4.1.25623.1.0.108440 Version used: 2023-09-07T05:05:21Z
References url: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management url: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure
...continues on next page ...

url: https://cwe.mitre.org/data/definitions/319.html	...continued from previous page ...
--	-------------------------------------

Medium (CVSS: 4.3) NVT: phpMyAdmin 'error.php' Cross Site Scripting Vulnerability
Summary phpMyAdmin is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact Successful exploitation will allow attackers to inject arbitrary HTML code within the error page and conduct phishing attacks.
Solution: Solution type: WillNotFix No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
Affected Software/OS phpMyAdmin version 3.3.8.1 and prior.
Vulnerability Insight The flaw is caused by input validation errors in the 'error.php' script when processing crafted BBcode tags containing '@' characters, which could allow attackers to inject arbitrary HTML code within the error page and conduct phishing attacks.
Vulnerability Detection Method Details: phpMyAdmin 'error.php' Cross Site Scripting Vulnerability OID:1.3.6.1.4.1.25623.1.0.801660 Version used: 2023-10-17T05:05:34Z
References cve: CVE-2010-4480 url: http://www.exploit-db.com/exploits/15699/ url: http://www.vupen.com/english/advisories/2010/3133 dfn-cert: DFN-CERT-2011-0467 dfn-cert: DFN-CERT-2011-0451 dfn-cert: DFN-CERT-2011-0016 dfn-cert: DFN-CERT-2011-0002

Medium (CVSS: 4.3) NVT: Apache HTTP Server 'httpOnly' Cookie Information Disclosure Vulnerability
Product detection result cpe:/a:apache:http_server:2.2.8 Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1 ↔.0.117232)
Summary Apache HTTP Server is prone to a cookie information disclosure vulnerability.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact ...continues on next page ...

...continued from previous page ...
Successful exploitation will allow attackers to obtain sensitive information that may aid in further attacks.
Solution: Solution type: VendorFix Update to Apache HTTP Server version 2.2.22 or later.
Affected Software/OS Apache HTTP Server versions 2.2.0 through 2.2.21.
Vulnerability Insight The flaw is due to an error within the default error response for status code 400 when no custom ErrorDocument is configured, which can be exploited to expose 'httpOnly' cookies.
Vulnerability Detection Method Details: Apache HTTP Server 'httpOnly' Cookie Information Disclosure Vulnerability OID:1.3.6.1.4.1.25623.1.0.902830 Version used: 2026-02-24T05:57:09Z
Product Detection Result Product: cpe:/a:apache:http_server:2.2.8 Method: Apache HTTP Server Detection Consolidation OID: 1.3.6.1.4.1.25623.1.0.117232
References cve: CVE-2012-0053 url: http://secunia.com/advisories/47779 url: http://www.securityfocus.com/bid/51706 url: http://www.exploit-db.com/exploits/18442 url: http://rhn.redhat.com/errata/RHSA-2012-0128.html url: http://httpd.apache.org/security/vulnerabilities_22.html url: http://svn.apache.org/viewvc?view=revision&revision=1235454 url: http://lists.opensuse.org/opensuse-security-announce/2012-02/msg00026.html cert-bund: CB-K15/0080 cert-bund: CB-K14/1505 cert-bund: CB-K14/0608 dfn-cert: DFN-CERT-2015-0082 dfn-cert: DFN-CERT-2014-1592 dfn-cert: DFN-CERT-2014-0635 dfn-cert: DFN-CERT-2013-1307 dfn-cert: DFN-CERT-2012-1276 dfn-cert: DFN-CERT-2012-1112 dfn-cert: DFN-CERT-2012-0928 dfn-cert: DFN-CERT-2012-0758 dfn-cert: DFN-CERT-2012-0744 dfn-cert: DFN-CERT-2012-0568 dfn-cert: DFN-CERT-2012-0425 dfn-cert: DFN-CERT-2012-0424 dfn-cert: DFN-CERT-2012-0387 dfn-cert: DFN-CERT-2012-0343 dfn-cert: DFN-CERT-2012-0332 dfn-cert: DFN-CERT-2012-0306 dfn-cert: DFN-CERT-2012-0264 dfn-cert: DFN-CERT-2012-0203 dfn-cert: DFN-CERT-2012-0188

Medium (CVSS: 4.3)
NVT: jQuery < 1.6.3 XSS Vulnerability
Summary jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 1.3.2 Fixed version: 1.6.3 Installation
...continues on next page ...

...continued from previous page ...	
path / port:	/mutillidae/javascript/ddsmoothmenu/jquery.min.js
Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):	
- Identified file: http://192.168.56.102/mutillidae/javascript/ddsmoothmenu/jque	
↔ry.min.js	
- Referenced at: http://192.168.56.102/mutillidae/	
Solution:	
Solution type: VendorFix	
Update to version 1.6.3 or later.	
Affected Software/OS	
jQuery prior to version 1.6.3.	
Vulnerability Insight	
Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.	
Vulnerability Detection Method	
Checks if a vulnerable version is present on the target host.	
Details: jQuery < 1.6.3 XSS Vulnerability	
OID:1.3.6.1.4.1.25623.1.0.141637	
Version used: 2023-07-14T05:06:08Z	
References	
cve: CVE-2011-4969	
url: https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/	
cert-bund: WID-SEC-2026-1752	
cert-bund: CB-K17/0195	
dfn-cert: DFN-CERT-2017-0199	
dfn-cert: DFN-CERT-2016-0890	

[[return to 192.168.56.102](#)]

2.1.24 Medium 2121/tcp

Medium (CVSS: 4.8)
NVT: FTP Unencrypted Cleartext Login
Summary
The remote host is running a FTP service that allows cleartext logins over unencrypted connections.
Quality of Detection (QoD): 70%
Vulnerability Detection Result
The remote FTP service accepts logins without a previous sent 'AUTH TLS' command
↔. Response(s):
Non-anonymous sessions: 331 Password required for openvasvt
Anonymous sessions: 331 Password required for anonymous
Impact
An attacker can uncover login names and passwords by sniffing traffic to the FTP service.
Solution:
Solution type: Mitigation
Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.
Vulnerability Detection Method
Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command.
Details: FTP Unencrypted Cleartext Login
OID:1.3.6.1.4.1.25623.1.0.108528
Version used: 2023-12-20T05:05:58Z

[[return to 192.168.56.102](#)]

2.1.25 Medium 5432/tcp

Medium (CVSS: 5.9)
NVT: SSL/TLS: Deprecated SSLv2 and SSLv3 Protocol Detection
Product detection result cpe:/a:ietf:transport_layer_security:1.0 Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)
Summary It was possible to detect the usage of the deprecated SSLv2 and/or SSLv3 protocol on this system.
Quality of Detection (QoD): 98%
Vulnerability Detection Result In addition to TLSv1.0+ the service is also providing the deprecated SSLv3 proto col and supports one or more ciphers. Those supported ciphers can be found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1.25623.1.0.8020 67) VT.
Impact An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection. Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.
Solution: Solution type: Mitigation It is recommended to disable the deprecated SSLv2 and/or SSLv3 protocols in favor of the TLSv1.2+ protocols. Please see the references for more resources supporting you with this task.
Affected Software/OS All services providing an encrypted communication using the SSLv2 and/or SSLv3 protocols.
Vulnerability Insight The SSLv2 and SSLv3 protocols contain known cryptographic flaws like: - CVE-2014-3566: Padding Oracle On Downgraded Legacy Encryption (POODLE) - CVE-2016-0800: Decrypting RSA with Obsolete and Weakened eNcryption (DROWN)
Vulnerability Detection Method Checks the used SSL protocols of the services provided by this system. Details: SSL/TLS: Deprecated SSLv2 and SSLv3 Protocol Detection OID:1.3.6.1.4.1.25623.1.0.111012 Version used: 2026-06-03T07:18:10Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security:1.0 Method: SSL/TLS: Version Detection OID: 1.3.6.1.4.1.25623.1.0.105782
References cve: CVE-2016-0800 cve: CVE-2014-3566 url: https://configurator.tlsref.org/ url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TRO3116/BSI-TR-03116-4.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014 url: https://drownattack.com url: https://www.imperialviolet.org/2014/10/14/poodle.html cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2025-1658 cert-bund: WID-SEC-2023-0431
... continues on next page ...

	...continued from previous page ...
cert-bund: WID-SEC-2023-0427	
cert-bund: CB-K18/0094	
cert-bund: CB-K17/1198	
cert-bund: CB-K17/1196	
cert-bund: CB-K16/1828	
cert-bund: CB-K16/1438	
cert-bund: CB-K16/1384	
cert-bund: CB-K16/1141	
cert-bund: CB-K16/1107	
cert-bund: CB-K16/1102	
cert-bund: CB-K16/0792	
cert-bund: CB-K16/0599	
cert-bund: CB-K16/0597	
cert-bund: CB-K16/0459	
cert-bund: CB-K16/0456	
cert-bund: CB-K16/0433	
cert-bund: CB-K16/0424	
cert-bund: CB-K16/0415	
cert-bund: CB-K16/0413	
cert-bund: CB-K16/0374	
cert-bund: CB-K16/0367	
cert-bund: CB-K16/0331	
cert-bund: CB-K16/0329	
cert-bund: CB-K16/0328	
cert-bund: CB-K16/0156	
cert-bund: CB-K15/1514	
cert-bund: CB-K15/1358	
cert-bund: CB-K15/1021	
cert-bund: CB-K15/0972	
cert-bund: CB-K15/0637	
cert-bund: CB-K15/0590	
cert-bund: CB-K15/0525	
cert-bund: CB-K15/0393	
cert-bund: CB-K15/0384	
cert-bund: CB-K15/0287	
cert-bund: CB-K15/0252	
cert-bund: CB-K15/0246	
cert-bund: CB-K15/0237	
cert-bund: CB-K15/0118	
cert-bund: CB-K15/0110	
cert-bund: CB-K15/0108	
cert-bund: CB-K15/0080	
cert-bund: CB-K15/0078	
cert-bund: CB-K15/0077	
cert-bund: CB-K15/0075	
cert-bund: CB-K14/1617	
cert-bund: CB-K14/1581	
cert-bund: CB-K14/1537	
cert-bund: CB-K14/1479	
cert-bund: CB-K14/1458	
cert-bund: CB-K14/1342	
cert-bund: CB-K14/1314	
cert-bund: CB-K14/1313	
cert-bund: CB-K14/1311	
cert-bund: CB-K14/1304	
cert-bund: CB-K14/1296	
dfn-cert: DFN-CERT-2018-0096	
dfn-cert: DFN-CERT-2017-1238	
dfn-cert: DFN-CERT-2017-1236	
dfn-cert: DFN-CERT-2016-1929	
dfn-cert: DFN-CERT-2016-1527	
dfn-cert: DFN-CERT-2016-1468	
dfn-cert: DFN-CERT-2016-1216	
dfn-cert: DFN-CERT-2016-1174	
dfn-cert: DFN-CERT-2016-1168	
dfn-cert: DFN-CERT-2016-0884	
dfn-cert: DFN-CERT-2016-0841	
dfn-cert: DFN-CERT-2016-0644	
dfn-cert: DFN-CERT-2016-0642	
dfn-cert: DFN-CERT-2016-0496	
dfn-cert: DFN-CERT-2016-0495	
dfn-cert: DFN-CERT-2016-0465	
...continues on next page ...	

...continued from previous page ...	
dfn-cert:	DFN-CERT-2016-0459
dfn-cert:	DFN-CERT-2016-0453
dfn-cert:	DFN-CERT-2016-0451
dfn-cert:	DFN-CERT-2016-0415
dfn-cert:	DFN-CERT-2016-0403
dfn-cert:	DFN-CERT-2016-0388
dfn-cert:	DFN-CERT-2016-0360
dfn-cert:	DFN-CERT-2016-0359
dfn-cert:	DFN-CERT-2016-0357
dfn-cert:	DFN-CERT-2016-0171
dfn-cert:	DFN-CERT-2015-1431
dfn-cert:	DFN-CERT-2015-1075
dfn-cert:	DFN-CERT-2015-1026
dfn-cert:	DFN-CERT-2015-0664
dfn-cert:	DFN-CERT-2015-0548
dfn-cert:	DFN-CERT-2015-0404
dfn-cert:	DFN-CERT-2015-0396
dfn-cert:	DFN-CERT-2015-0259
dfn-cert:	DFN-CERT-2015-0254
dfn-cert:	DFN-CERT-2015-0245
dfn-cert:	DFN-CERT-2015-0118
dfn-cert:	DFN-CERT-2015-0114
dfn-cert:	DFN-CERT-2015-0083
dfn-cert:	DFN-CERT-2015-0082
dfn-cert:	DFN-CERT-2015-0081
dfn-cert:	DFN-CERT-2015-0076
dfn-cert:	DFN-CERT-2014-1717
dfn-cert:	DFN-CERT-2014-1680
dfn-cert:	DFN-CERT-2014-1632
dfn-cert:	DFN-CERT-2014-1564
dfn-cert:	DFN-CERT-2014-1542
dfn-cert:	DFN-CERT-2014-1414
dfn-cert:	DFN-CERT-2014-1366
dfn-cert:	DFN-CERT-2014-1354

Medium (CVSS: 5.9)
NVT: SSL/TLS: Report Weak Cipher Suites
Product detection result cpe:/a:ietf:transport_layer_security Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0. ↪802067)
Summary This routine reports all weak SSL/TLS cipher suites accepted by a service.
Quality of Detection (QoD): 98%
Vulnerability Detection Result 'Weak' cipher suites accepted by this service via the SSLv3 protocol: TLS_RSA_WITH_RC4_128_SHA 'Weak' cipher suites accepted by this service via the TLSv1.0 protocol: TLS_RSA_WITH_RC4_128_SHA
Impact This could allow remote attackers to obtain sensitive information or have other, unspecified impacts.
Solution: Solution type: Mitigation The configuration of this services should be changed so that it does not accept the listed weak cipher suites anymore. Please see the references for more resources supporting you with this task.
Affected Software/OS All services providing an encrypted communication using weak SSL/TLS cipher suites.
Vulnerability Insight ...continues on next page ...

...continued from previous page ...
These rules are applied for the evaluation of the cryptographic strength: - RC4 is considered to be weak (CVE-2013-2566, CVE-2015-2808) - Ciphers using 64 bit or less are considered to be vulnerable to brute force methods and therefore considered as weak (CVE-2015-4000) - 1024 bit RSA authentication is considered to be insecure and therefore as weak - Any cipher considered to be secure for only the next 10 years is considered as medium - Any other cipher is considered as strong
Vulnerability Detection Method Checks previous collected cipher suites. NOTE: No severity for SMTP services with 'Opportunistic TLS' and weak cipher suites on port 25/tcp is reported. If too strong cipher suites are configured for this service the alternative would be to fall back to an even more insecure cleartext communication. Details: SSL/TLS: Report Weak Cipher Suites OID:1.3.6.1.4.1.25623.1.0.103440 Version used: 2026-06-03T07:18:10Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security Method: SSL/TLS: Report Supported Cipher Suites OID: 1.3.6.1.4.1.25623.1.0.802067
References cve: CVE-2013-2566 cve: CVE-2015-2808 cve: CVE-2015-4000 url: https://configurator.tlsref.org/ url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014 cert-bund: WID-SEC-2026-0180 cert-bund: CB-K21/0067 cert-bund: CB-K19/0812 cert-bund: CB-K17/1750 cert-bund: CB-K16/1593 cert-bund: CB-K16/1552 cert-bund: CB-K16/1102 cert-bund: CB-K16/0617 cert-bund: CB-K16/0599 cert-bund: CB-K16/0168 cert-bund: CB-K16/0121 cert-bund: CB-K16/0090 cert-bund: CB-K16/0030 cert-bund: CB-K15/1751 cert-bund: CB-K15/1591 cert-bund: CB-K15/1550 cert-bund: CB-K15/1517 cert-bund: CB-K15/1514 cert-bund: CB-K15/1464 cert-bund: CB-K15/1442 cert-bund: CB-K15/1334 cert-bund: CB-K15/1269 cert-bund: CB-K15/1136 cert-bund: CB-K15/1090 cert-bund: CB-K15/1059 cert-bund: CB-K15/1022 cert-bund: CB-K15/1015 cert-bund: CB-K15/0986 cert-bund: CB-K15/0964 cert-bund: CB-K15/0962 cert-bund: CB-K15/0932 cert-bund: CB-K15/0927 cert-bund: CB-K15/0926 cert-bund: CB-K15/0907 cert-bund: CB-K15/0901 cert-bund: CB-K15/0896
...continues on next page ...

...continued from previous page ...	
cert-bund:	CB-K15/0889
cert-bund:	CB-K15/0877
cert-bund:	CB-K15/0850
cert-bund:	CB-K15/0849
cert-bund:	CB-K15/0834
cert-bund:	CB-K15/0827
cert-bund:	CB-K15/0802
cert-bund:	CB-K15/0764
cert-bund:	CB-K15/0733
cert-bund:	CB-K15/0667
cert-bund:	CB-K14/0935
cert-bund:	CB-K13/0942
dfn-cert:	DFN-CERT-2023-2939
dfn-cert:	DFN-CERT-2021-0775
dfn-cert:	DFN-CERT-2020-1561
dfn-cert:	DFN-CERT-2020-1276
dfn-cert:	DFN-CERT-2017-1821
dfn-cert:	DFN-CERT-2016-1692
dfn-cert:	DFN-CERT-2016-1648
dfn-cert:	DFN-CERT-2016-1168
dfn-cert:	DFN-CERT-2016-0665
dfn-cert:	DFN-CERT-2016-0642
dfn-cert:	DFN-CERT-2016-0184
dfn-cert:	DFN-CERT-2016-0135
dfn-cert:	DFN-CERT-2016-0101
dfn-cert:	DFN-CERT-2016-0035
dfn-cert:	DFN-CERT-2015-1853
dfn-cert:	DFN-CERT-2015-1679
dfn-cert:	DFN-CERT-2015-1632
dfn-cert:	DFN-CERT-2015-1608
dfn-cert:	DFN-CERT-2015-1542
dfn-cert:	DFN-CERT-2015-1518
dfn-cert:	DFN-CERT-2015-1406
dfn-cert:	DFN-CERT-2015-1341
dfn-cert:	DFN-CERT-2015-1194
dfn-cert:	DFN-CERT-2015-1144
dfn-cert:	DFN-CERT-2015-1113
dfn-cert:	DFN-CERT-2015-1078
dfn-cert:	DFN-CERT-2015-1067
dfn-cert:	DFN-CERT-2015-1038
dfn-cert:	DFN-CERT-2015-1016
dfn-cert:	DFN-CERT-2015-1012
dfn-cert:	DFN-CERT-2015-0980
dfn-cert:	DFN-CERT-2015-0977
dfn-cert:	DFN-CERT-2015-0976
dfn-cert:	DFN-CERT-2015-0960
dfn-cert:	DFN-CERT-2015-0956
dfn-cert:	DFN-CERT-2015-0944
dfn-cert:	DFN-CERT-2015-0937
dfn-cert:	DFN-CERT-2015-0925
dfn-cert:	DFN-CERT-2015-0884
dfn-cert:	DFN-CERT-2015-0881
dfn-cert:	DFN-CERT-2015-0879
dfn-cert:	DFN-CERT-2015-0866
dfn-cert:	DFN-CERT-2015-0844
dfn-cert:	DFN-CERT-2015-0800
dfn-cert:	DFN-CERT-2015-0737
dfn-cert:	DFN-CERT-2015-0696
dfn-cert:	DFN-CERT-2014-0977

Medium (CVSS: 5.3)

NVT: SSL/TLS: Server Certificate / Certificate in Chain with RSA keys less than 2048 bits

Summary

The remote SSL/TLS server certificate and/or any of the certificates in the certificate chain is using a RSA key with less than 2048 bits.

Quality of Detection (QoD): 80%

...continues on next page ...

...continued from previous page ...
Vulnerability Detection Result The remote SSL/TLS server is using the following certificate(s) with a RSA key w ↳ with less than 2048 bits (public-key-size:public-key-algorithm:serial:issuer): 1024:RSA:00FAF93A4C7FB6B9CC:1.2.840.113549.1.9.1=#726F6F74407562756E74753830342D ↳ 626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office for C ↳ omplication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is no su ↳ ch thing outside US,C=XX (Server certificate)
Impact Using certificates with weak RSA key size can lead to unauthorized exposure of sensitive information.
Solution: Solution type: Mitigation Replace the certificate with a stronger key and reissue the certificates it signed.
Vulnerability Insight SSL/TLS certificates using RSA keys with less than 2048 bits are considered unsafe.
Vulnerability Detection Method Checks the RSA keys size of the server certificate and all certificates in chain for a size < 2048 bit. Details: SSL/TLS: Server Certificate / Certificate in Chain with RSA keys less than 2048. ↳ .. OID:1.3.6.1.4.1.25623.1.0.150710 Version used: 2021-12-10T12:48:00Z
References url: https://www.cabforum.org/wp-content/uploads/Baseline_Requirements_V1.pdf

Medium (CVSS: 5.0)
NVT: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)
Summary The remote SSL/TLS service is prone to a denial of service (DoS) vulnerability.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The following indicates that the remote SSL/TLS service is affected: Protocol Version Successful re-done SSL/TLS handshakes (Renegotiation) over an ↳ existing / already established SSL/TLS connection ----- ↳ ----- TLSv1.0 10
Impact The flaw might make it easier for remote attackers to cause a DoS (CPU consumption) by performing many renegotiations within a single connection.
Solution: Solution type: VendorFix Users should contact their vendors for specific patch information. A general solution is to remove/disable renegotiation capabilities altogether from/in the affected SSL/TLS service.
Affected Software/OS Every SSL/TLS service which does not properly restrict client-initiated renegotiation.
Vulnerability Insight The flaw exists because the remote SSL/TLS service does not properly restrict client-initiated renegotiation within the SSL and TLS protocols. Note: The referenced CVEs are affecting OpenSSL and Mozilla Network Security Services (NSS) but both are in a DISPUTED state with the following rationale: > It can also be argued that it is the responsibility of server deployments, not a security library, to prevent or limit renegotiation when it is inappropriate within a specific environment. Both CVEs are still kept in this VT as a reference to the origin of this flaw.
...continues on next page ...

...continued from previous page ...

Vulnerability Detection Method

Checks if the remote service allows to re-do the same SSL/TLS handshake (Renegotiation) over an existing / already established SSL/TLS connection.

Details: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)

OID:1.3.6.1.4.1.25623.1.0.117761

Version used: 2026-03-13T05:54:58Z

References

cve: CVE-2011-1473

cve: CVE-2011-5094

url: <https://web.archive.org/web/20211201133213/https://orchilles.com/ssl-renegotiation-dos/>

url: https://mailarchive.ietf.org/arch/msg/tls/wdg46VE_jkYBbgJ5yE4P9nQ-8IU/

url: <https://vincent.bernat.ch/en/blog/2011-ssl-dos-mitigation>

url: <https://www.openwall.com/lists/oss-security/2011/07/08/2>

cert-bund: WID-SEC-2026-2904

cert-bund: WID-SEC-2026-0180

cert-bund: WID-SEC-2024-1591

cert-bund: WID-SEC-2024-0796

cert-bund: WID-SEC-2023-1435

cert-bund: CB-K17/0980

cert-bund: CB-K17/0979

cert-bund: CB-K14/0772

cert-bund: CB-K13/0915

cert-bund: CB-K13/0462

dfn-cert: DFN-CERT-2025-0933

dfn-cert: DFN-CERT-2017-1013

dfn-cert: DFN-CERT-2017-1012

dfn-cert: DFN-CERT-2014-0809

dfn-cert: DFN-CERT-2013-1928

dfn-cert: DFN-CERT-2012-1112

Medium (CVSS: 5.0)

NVT: SSL/TLS: Certificate Expired

Product detection result

cpe:/a:ietf:transport_layer_security

Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25

↪623.1.0.103692)

Summary

The remote server's SSL/TLS certificate has already expired.

Quality of Detection (QoD): 99%

Vulnerability Detection Result

The certificate of the remote service expired on 2010-04-16 14:07:45.

Certificate details:

fingerprint (SHA-1) | ED093088706603BFD5DC237399B498DA2D4D31C6

fingerprint (SHA-256) | E7A7FA0D63E457C7C4A59B38B70849C6A70BDA6F830C7A

↪F1E32DEE436DE813CC

issued by | 1.2.840.113549.1.9.1=#726F6F74407562756E747538

↪30342D626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office

↪ for Complication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is

↪ no such thing outside US,C=XX

public key algorithm | RSA

public key size (bits) | 1024

serial | 00FAF93A4C7FB6B9CC

signature algorithm | sha1WithRSAEncryption

subject | 1.2.840.113549.1.9.1=#726F6F74407562756E747538

↪30342D626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office

↪ for Complication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is

↪ no such thing outside US,C=XX

subject alternative names (SAN) | None

valid from | 2010-03-17 14:07:45 UTC

valid until | 2010-04-16 14:07:45 UTC

...continues on next page ...

...continued from previous page ...
Solution: Solution type: Mitigation Replace the SSL/TLS certificate by a new one.
Vulnerability Insight This script checks expiry dates of certificates associated with SSL/TLS-enabled services on the target and reports whether any have already expired.
Vulnerability Detection Method Details: SSL/TLS: Certificate Expired OID: 1.3.6.1.4.1.25623.1.0.103955 Version used: 2026-03-13T05:54:58Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security Method: SSL/TLS: Collect and Report Certificate Details OID: 1.3.6.1.4.1.25623.1.0.103692

Medium (CVSS: 4.3)
NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection
Product detection result cpe:/a:ietf:transport_layer_security:1.0 Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)
Summary It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.
Quality of Detection (QoD): 98%
Vulnerability Detection Result The service is only providing the deprecated TLSv1.0 protocol and supports one o ↪r more ciphers. Those supported ciphers can be found in the 'SSL/TLS: Report S ↪upported Cipher Suites' (OID: 1.3.6.1.4.1.25623.1.0.802067) VT.
Impact An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection. Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.
Solution: Solution type: Mitigation It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols. Please see the references for more resources supporting you with this task.
Affected Software/OS - All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols - CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder - CVE-2024-41270: Gorush v1.18.4 - CVE-2025-3200: Multiple products from Wiesemann & Theis
Vulnerability Insight The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like: - CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST) - CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)
Vulnerability Detection Method Checks the used TLS protocols of the services provided by this system. Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection OID: 1.3.6.1.4.1.25623.1.0.117274 Version used: 2026-06-03T07:18:10Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security:1.0 ...continues on next page ...

...continued from previous page ...	
Method: SSL/TLS: Version Detection	
OID: 1.3.6.1.4.1.25623.1.0.105782	
References	
cve: CVE-2011-3389	
cve: CVE-2015-0204	
cve: CVE-2023-41928	
cve: CVE-2024-41270	
cve: CVE-2025-3200	
url: https://configurator.tlsref.org/	
url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html	
url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html	
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html	
url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html	
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org	
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014	
url: https://datatracker.ietf.org/doc/rfc8996/	
url: https://vnhacker.blogspot.com/2011/09/beast.html	
url: https://web.archive.org/web/20201108095603/https://censys.io/blog/freak	
url: https://certvde.com/en/advisories/VDE-2025-031/	
url: https://gist.github.com/nyxfq/cfae38fada582a0f576d154belaeb1fc	
url: https://advisories.ncsc.nl/advisory?id=NCSC-2024-0273	
cert-bund: WID-SEC-2026-0180	
cert-bund: WID-SEC-2023-1435	
cert-bund: CB-K18/0799	
cert-bund: CB-K16/1289	
cert-bund: CB-K16/1096	
cert-bund: CB-K15/1751	
cert-bund: CB-K15/1266	
cert-bund: CB-K15/0850	
cert-bund: CB-K15/0764	
cert-bund: CB-K15/0720	
cert-bund: CB-K15/0548	
cert-bund: CB-K15/0526	
cert-bund: CB-K15/0509	
cert-bund: CB-K15/0493	
cert-bund: CB-K15/0384	
cert-bund: CB-K15/0365	
cert-bund: CB-K15/0364	
cert-bund: CB-K15/0302	
cert-bund: CB-K15/0192	
cert-bund: CB-K15/0079	
cert-bund: CB-K15/0016	
cert-bund: CB-K14/1342	
cert-bund: CB-K14/0231	
cert-bund: CB-K13/0845	
cert-bund: CB-K13/0796	
cert-bund: CB-K13/0790	
dfn-cert: DFN-CERT-2020-0177	
dfn-cert: DFN-CERT-2020-0111	
dfn-cert: DFN-CERT-2019-0068	
dfn-cert: DFN-CERT-2018-1441	
dfn-cert: DFN-CERT-2018-1408	
dfn-cert: DFN-CERT-2016-1372	
dfn-cert: DFN-CERT-2016-1164	
dfn-cert: DFN-CERT-2016-0388	
dfn-cert: DFN-CERT-2015-1853	
dfn-cert: DFN-CERT-2015-1332	
dfn-cert: DFN-CERT-2015-0884	
dfn-cert: DFN-CERT-2015-0800	
dfn-cert: DFN-CERT-2015-0758	
dfn-cert: DFN-CERT-2015-0567	
dfn-cert: DFN-CERT-2015-0544	
dfn-cert: DFN-CERT-2015-0530	
dfn-cert: DFN-CERT-2015-0396	
dfn-cert: DFN-CERT-2015-0375	
dfn-cert: DFN-CERT-2015-0374	
dfn-cert: DFN-CERT-2015-0305	
dfn-cert: DFN-CERT-2015-0199	
...continues on next page ...	

...continued from previous page ...	
dfn-cert:	DFN-CERT-2015-0079
dfn-cert:	DFN-CERT-2015-0021
dfn-cert:	DFN-CERT-2014-1414
dfn-cert:	DFN-CERT-2013-1847
dfn-cert:	DFN-CERT-2013-1792
dfn-cert:	DFN-CERT-2012-1979
dfn-cert:	DFN-CERT-2012-1829
dfn-cert:	DFN-CERT-2012-1530
dfn-cert:	DFN-CERT-2012-1380
dfn-cert:	DFN-CERT-2012-1377
dfn-cert:	DFN-CERT-2012-1292
dfn-cert:	DFN-CERT-2012-1214
dfn-cert:	DFN-CERT-2012-1213
dfn-cert:	DFN-CERT-2012-1180
dfn-cert:	DFN-CERT-2012-1156
dfn-cert:	DFN-CERT-2012-1155
dfn-cert:	DFN-CERT-2012-1039
dfn-cert:	DFN-CERT-2012-0956
dfn-cert:	DFN-CERT-2012-0908
dfn-cert:	DFN-CERT-2012-0868
dfn-cert:	DFN-CERT-2012-0867
dfn-cert:	DFN-CERT-2012-0848
dfn-cert:	DFN-CERT-2012-0838
dfn-cert:	DFN-CERT-2012-0776
dfn-cert:	DFN-CERT-2012-0722
dfn-cert:	DFN-CERT-2012-0638
dfn-cert:	DFN-CERT-2012-0627
dfn-cert:	DFN-CERT-2012-0451
dfn-cert:	DFN-CERT-2012-0418
dfn-cert:	DFN-CERT-2012-0354
dfn-cert:	DFN-CERT-2012-0234
dfn-cert:	DFN-CERT-2012-0221
dfn-cert:	DFN-CERT-2012-0177
dfn-cert:	DFN-CERT-2012-0170
dfn-cert:	DFN-CERT-2012-0146
dfn-cert:	DFN-CERT-2012-0142
dfn-cert:	DFN-CERT-2012-0126
dfn-cert:	DFN-CERT-2012-0123
dfn-cert:	DFN-CERT-2012-0095
dfn-cert:	DFN-CERT-2012-0051
dfn-cert:	DFN-CERT-2012-0047
dfn-cert:	DFN-CERT-2012-0021
dfn-cert:	DFN-CERT-2011-1953
dfn-cert:	DFN-CERT-2011-1946
dfn-cert:	DFN-CERT-2011-1844
dfn-cert:	DFN-CERT-2011-1826
dfn-cert:	DFN-CERT-2011-1774
dfn-cert:	DFN-CERT-2011-1743
dfn-cert:	DFN-CERT-2011-1738
dfn-cert:	DFN-CERT-2011-1706
dfn-cert:	DFN-CERT-2011-1628
dfn-cert:	DFN-CERT-2011-1627
dfn-cert:	DFN-CERT-2011-1619
dfn-cert:	DFN-CERT-2011-1482

Medium (CVSS: 4.0)
NVT: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm
Summary The remote service is using a SSL/TLS certificate in the certificate chain that has been signed using a cryptographically weak hashing algorithm.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following certificates are part of the certificate chain but using insecure ↪signature algorithms: Subject: 1.2.840.113549.1.9.1=#726F6F74407562756E74753830342D626173
...continues on next page ...

...continued from previous page ...
<pre> ↪652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office for Complic ↪ation of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is no such thi ↪ng outside US,C=XX Signature Algorithm: sha1WithRSAEncryption </pre>
Solution: Solution type: Mitigation Servers that use SSL/TLS certificates signed with a weak SHA-1, MD5, MD4 or MD2 hashing algorithm will need to obtain new SHA-2 signed SSL/TLS certificates to avoid web browser SSL/TLS certificate warnings.
Vulnerability Insight The following hashing algorithms used for signing SSL/TLS certificates are considered cryptographically weak and not secure enough for ongoing use: - Secure Hash Algorithm 1 (SHA-1) - Message Digest 5 (MD5) - Message Digest 4 (MD4) - Message Digest 2 (MD2) Beginning as late as January 2017 and as early as June 2016, browser developers such as Microsoft and Google will begin warning users when visiting web sites that use SHA-1 signed Secure Socket Layer (SSL) certificates. NOTE: The script preference allows to set one or more custom SHA-1 fingerprints of CA certificates which are trusted by this routine. The fingerprints needs to be passed comma-separated and case-insensitive: Fingerprint1 or fingerprint1, Fingerprint2
Vulnerability Detection Method Check which hashing algorithm was used to sign the remote SSL/TLS certificate. Details: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm OID:1.3.6.1.4.1.25623.1.0.105880 Version used: 2021-10-15T11:13:32Z
References url: https://blog.mozilla.org/security/2014/09/23/phasing-out-certificates-with-sha-1-based-signature-algorithms/

Medium (CVSS: 4.0)
NVT: SSL/TLS: Diffie-Hellman Key Exchange Insufficient DH Group Strength Vulnerability
Summary The SSL/TLS service uses Diffie-Hellman groups with insufficient strength (key size < 2048).
Quality of Detection (QoD): 80%
Vulnerability Detection Result Server Temporary Key Size: 1024 bits
Impact An attacker might be able to decrypt the SSL/TLS communication offline.
Solution: Solution type: Workaround - Deploy (Ephemeral) Elliptic-Curve Diffie-Hellman (ECDHE) or use a 2048-bit or stronger Diffie-Hellman group. Please see the references for more resources supporting you with this task. - For Apache Web Servers: Beginning with version 2.4.7, mod_ssl will use DH parameters which include primes with lengths of more than 1024 bits.
Affected Software/OS All services providing an encrypted communication using Diffie-Hellman groups with insufficient strength.
Vulnerability Insight The Diffie-Hellman group are some big numbers that are used as base for the DH computations. They can be, and often are, fixed. The security of the final secret depends on the size of these parameters. It was found that 512 and 768 bits to be weak, 1024 bits to be breakable by really powerful attackers like governments.
Vulnerability Detection Method Checks the DHE temporary public key size. Details: SSL/TLS: Diffie-Hellman Key Exchange Insufficient DH Group Strength Vulnerability.
...continues on next page ...

↔...	...continued from previous page ...
OID:1.3.6.1.4.1.25623.1.0.106223 Version used: 2026-06-03T07:18:10Z	
References url: https://weakdh.org url: https://weakdh.org/sysadmin.html url: https://configurator.tlsref.org/ url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014 url: https://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslcertificatefile	

[[return to 192.168.56.102](#)]

2.1.26 Medium 21/tcp

Medium (CVSS: 6.4)
NVT: Anonymous FTP Login Reporting
Summary Reports if the remote FTP Server allows anonymous logins.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was possible to login to the remote FTP service with the following anonymous ↔account(s): anonymous:anonymous@example.com ftp:anonymous@example.com
Impact Based on the files accessible via this anonymous FTP login and the permissions of this account an attacker might be able to: - gain access to sensitive files - upload or delete files.
Solution: Solution type: Mitigation If you do not want to share files, you should disable anonymous logins.
Vulnerability Insight A host that provides an FTP service may additionally provide Anonymous FTP access as well. Under this arrangement, users do not strictly need an account on the host. Instead the user typically enters 'anonymous' or 'ftp' when prompted for username. Although users are commonly asked to send their email address as their password, little to no verification is actually performed on the supplied data. Remark: NIST don't see 'configuration issues' as software flaws so the referenced CVE has a severity of 0.0. The severity of this VT has been raised by Greenbone to still report a configuration issue on the target.
Vulnerability Detection Method Details: Anonymous FTP Login Reporting OID:1.3.6.1.4.1.25623.1.0.900600 Version used: 2021-10-20T09:03:29Z
References cve: CVE-1999-0497

Medium (CVSS: 4.8)
NVT: FTP Unencrypted Cleartext Login
Summary The remote host is running a FTP service that allows cleartext logins over unencrypted connections.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The remote FTP service accepts logins without a previous sent 'AUTH TLS' command ↔. Response(s): Non-anonymous sessions: 331 Please specify the password. Anonymous sessions: 331 Please specify the password.
Impact An attacker can uncover login names and passwords by sniffing traffic to the FTP service.
Solution: Solution type: Mitigation Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.
Vulnerability Detection Method Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command. Details: FTP Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.108528 Version used: 2023-12-20T05:05:58Z

[\[return to 192.168.56.102 \]](#)

2.1.27 Medium 23/tcp

Medium (CVSS: 4.8)
NVT: Telnet Unencrypted Cleartext Login
Summary The remote host is running a Telnet service that allows cleartext logins over unencrypted connections.
Quality of Detection (QoD): 70%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact An attacker can uncover login names and passwords by sniffing traffic to the Telnet service.
Solution: Solution type: Mitigation Replace Telnet with a protocol like SSH which supports encrypted connections.
Vulnerability Detection Method Details: Telnet Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.108522 Version used: 2023-10-13T05:06:09Z

[\[return to 192.168.56.102 \]](#)

2.1.28 Medium 25/tcp

Medium (CVSS: 6.8)
NVT: Multiple Vendors STARTTLS Implementation Plaintext Arbitrary Command Injection Vulnerability
Summary Multiple vendors' implementations of 'STARTTLS' are prone to a vulnerability that lets attackers inject arbitrary commands.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact An attacker can exploit this issue to execute arbitrary commands in the context of the user running the application. Successful exploits can allow attackers to obtain email usernames and passwords.
Solution: Solution type: VendorFix Updates are available. Please see the references for more information.
Affected Software/OS The following vendors are known to be affected: Ipswitch Kerio Postfix Qmail-TLS Oracle SCO Group spamdyke ISC
Vulnerability Detection Method Send a special crafted 'STARTTLS' request and check the response. Details: Multiple Vendors STARTTLS Implementation Plaintext Arbitrary Command Injection . ↪.. OID:1.3.6.1.4.1.25623.1.0.103935 Version used: 2023-10-31T05:06:37Z
References cve: CVE-2011-0411 cve: CVE-2011-1430 cve: CVE-2011-1431 cve: CVE-2011-1432 cve: CVE-2011-1506 cve: CVE-2011-1575 cve: CVE-2011-1926 cve: CVE-2011-2165 url: http://www.securityfocus.com/bid/46767 url: http://kolab.org/pipermail/kolab-announce/2011/000101.html url: http://bugzilla.cyrusimap.org/show_bug.cgi?id=3424 url: http://cyrusimap.org/mediawiki/index.php/Bugs_Resolved_in_2.4.7 url: http://www.kb.cert.org/vuls/id/MAPG-8D9M4P url: http://files.kolab.org/server/release/kolab-server-2.3.2/sources/release-notes.txt url: http://www.postfix.org/CVE-2011-0411.html url: http://www.pureftpd.org/project/pure-ftpd/news url: http://www.watchguard.com/support/release-notes/xcs/9/en-US/EN_ReleaseNotes_XCS_9_1_1/EN_ReleaseNotes_WG_XCS_9_1_TLS_Hotfix.pdf url: http://www.spamdyke.org/documentation/Changelog.txt url: http://datatracker.ietf.org/doc/draft-josefsson-kerberos5-starttls/?include_text=1 url: http://www.securityfocus.com/archive/1/516901 url: http://support.avaya.com/css/P8/documents/100134676 url: http://support.avaya.com/css/P8/documents/100141041 url: http://www.oracle.com/technetwork/topics/security/cpuapr2011-301950.html url: http://inoa.net/qmail-tls/vu555316.patch url: http://www.kb.cert.org/vuls/id/555316 cert-bund: CB-K15/1514 dfn-cert: DFN-CERT-2011-0917 dfn-cert: DFN-CERT-2011-0912 dfn-cert: DFN-CERT-2011-0897 dfn-cert: DFN-CERT-2011-0844 ... continues on next page ...

...continued from previous page ...	
dfn-cert: DFN-CERT-2011-0818	
dfn-cert: DFN-CERT-2011-0808	
dfn-cert: DFN-CERT-2011-0771	
dfn-cert: DFN-CERT-2011-0741	
dfn-cert: DFN-CERT-2011-0712	
dfn-cert: DFN-CERT-2011-0673	
dfn-cert: DFN-CERT-2011-0597	
dfn-cert: DFN-CERT-2011-0596	
dfn-cert: DFN-CERT-2011-0519	
dfn-cert: DFN-CERT-2011-0516	
dfn-cert: DFN-CERT-2011-0483	
dfn-cert: DFN-CERT-2011-0434	
dfn-cert: DFN-CERT-2011-0393	
dfn-cert: DFN-CERT-2011-0381	
Medium (CVSS: 5.9)	
NVT: SSL/TLS: Deprecated SSLv2 and SSLv3 Protocol Detection	
Product detection result cpe:/a:ietf:transport_layer_security:1.0 Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)	
Summary It was possible to detect the usage of the deprecated SSLv2 and/or SSLv3 protocol on this system.	
Quality of Detection (QoD): 98%	
Vulnerability Detection Result In addition to TLSv1.0+ the service is also providing the deprecated SSLv2 and S ↪SSLv3 protocols and supports one or more ciphers. Those supported ciphers can b ↪e found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1.256 ↪23.1.0.802067) VT.	
Impact An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection. Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.	
Solution: Solution type: Mitigation It is recommended to disable the deprecated SSLv2 and/or SSLv3 protocols in favor of the TLSv1.2+ protocols. Please see the references for more resources supporting you with this task.	
Affected Software/OS All services providing an encrypted communication using the SSLv2 and/or SSLv3 protocols.	
Vulnerability Insight The SSLv2 and SSLv3 protocols contain known cryptographic flaws like: - CVE-2014-3566: Padding Oracle On Downgraded Legacy Encryption (POODLE) - CVE-2016-0800: Decrypting RSA with Obsolete and Weakened eNcryption (DROWN)	
Vulnerability Detection Method Checks the used SSL protocols of the services provided by this system. Details: SSL/TLS: Deprecated SSLv2 and SSLv3 Protocol Detection OID:1.3.6.1.4.1.25623.1.0.111012 Version used: 2026-06-03T07:18:10Z	
Product Detection Result Product: cpe:/a:ietf:transport_layer_security:1.0 Method: SSL/TLS: Version Detection OID: 1.3.6.1.4.1.25623.1.0.105782	
References cve: CVE-2016-0800 cve: CVE-2014-3566 url: https://configurator.tlsref.org/	
...continues on next page ...	

...continued from previous page ...	
url:	https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html
url:	https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
url:	https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
url:	https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
url:	https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url:	https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014
url:	https://drownattack.com
url:	https://www.imperialviolet.org/2014/10/14/poodle.html
cert-bund:	WID-SEC-2026-0180
cert-bund:	WID-SEC-2025-1658
cert-bund:	WID-SEC-2023-0431
cert-bund:	WID-SEC-2023-0427
cert-bund:	CB-K18/0094
cert-bund:	CB-K17/1198
cert-bund:	CB-K17/1196
cert-bund:	CB-K16/1828
cert-bund:	CB-K16/1438
cert-bund:	CB-K16/1384
cert-bund:	CB-K16/1141
cert-bund:	CB-K16/1107
cert-bund:	CB-K16/1102
cert-bund:	CB-K16/0792
cert-bund:	CB-K16/0599
cert-bund:	CB-K16/0597
cert-bund:	CB-K16/0459
cert-bund:	CB-K16/0456
cert-bund:	CB-K16/0433
cert-bund:	CB-K16/0424
cert-bund:	CB-K16/0415
cert-bund:	CB-K16/0413
cert-bund:	CB-K16/0374
cert-bund:	CB-K16/0367
cert-bund:	CB-K16/0331
cert-bund:	CB-K16/0329
cert-bund:	CB-K16/0328
cert-bund:	CB-K16/0156
cert-bund:	CB-K15/1514
cert-bund:	CB-K15/1358
cert-bund:	CB-K15/1021
cert-bund:	CB-K15/0972
cert-bund:	CB-K15/0637
cert-bund:	CB-K15/0590
cert-bund:	CB-K15/0525
cert-bund:	CB-K15/0393
cert-bund:	CB-K15/0384
cert-bund:	CB-K15/0287
cert-bund:	CB-K15/0252
cert-bund:	CB-K15/0246
cert-bund:	CB-K15/0237
cert-bund:	CB-K15/0118
cert-bund:	CB-K15/0110
cert-bund:	CB-K15/0108
cert-bund:	CB-K15/0080
cert-bund:	CB-K15/0078
cert-bund:	CB-K15/0077
cert-bund:	CB-K15/0075
cert-bund:	CB-K14/1617
cert-bund:	CB-K14/1581
cert-bund:	CB-K14/1537
cert-bund:	CB-K14/1479
cert-bund:	CB-K14/1458
cert-bund:	CB-K14/1342
cert-bund:	CB-K14/1314
cert-bund:	CB-K14/1313
cert-bund:	CB-K14/1311
cert-bund:	CB-K14/1304
cert-bund:	CB-K14/1296
dfn-cert:	DFN-CERT-2018-0096
dfn-cert:	DFN-CERT-2017-1238
...continues on next page ...	

...continued from previous page ...	
dfn-cert:	DFN-CERT-2017-1236
dfn-cert:	DFN-CERT-2016-1929
dfn-cert:	DFN-CERT-2016-1527
dfn-cert:	DFN-CERT-2016-1468
dfn-cert:	DFN-CERT-2016-1216
dfn-cert:	DFN-CERT-2016-1174
dfn-cert:	DFN-CERT-2016-1168
dfn-cert:	DFN-CERT-2016-0884
dfn-cert:	DFN-CERT-2016-0841
dfn-cert:	DFN-CERT-2016-0644
dfn-cert:	DFN-CERT-2016-0642
dfn-cert:	DFN-CERT-2016-0496
dfn-cert:	DFN-CERT-2016-0495
dfn-cert:	DFN-CERT-2016-0465
dfn-cert:	DFN-CERT-2016-0459
dfn-cert:	DFN-CERT-2016-0453
dfn-cert:	DFN-CERT-2016-0451
dfn-cert:	DFN-CERT-2016-0415
dfn-cert:	DFN-CERT-2016-0403
dfn-cert:	DFN-CERT-2016-0388
dfn-cert:	DFN-CERT-2016-0360
dfn-cert:	DFN-CERT-2016-0359
dfn-cert:	DFN-CERT-2016-0357
dfn-cert:	DFN-CERT-2016-0171
dfn-cert:	DFN-CERT-2015-1431
dfn-cert:	DFN-CERT-2015-1075
dfn-cert:	DFN-CERT-2015-1026
dfn-cert:	DFN-CERT-2015-0664
dfn-cert:	DFN-CERT-2015-0548
dfn-cert:	DFN-CERT-2015-0404
dfn-cert:	DFN-CERT-2015-0396
dfn-cert:	DFN-CERT-2015-0259
dfn-cert:	DFN-CERT-2015-0254
dfn-cert:	DFN-CERT-2015-0245
dfn-cert:	DFN-CERT-2015-0118
dfn-cert:	DFN-CERT-2015-0114
dfn-cert:	DFN-CERT-2015-0083
dfn-cert:	DFN-CERT-2015-0082
dfn-cert:	DFN-CERT-2015-0081
dfn-cert:	DFN-CERT-2015-0076
dfn-cert:	DFN-CERT-2014-1717
dfn-cert:	DFN-CERT-2014-1680
dfn-cert:	DFN-CERT-2014-1632
dfn-cert:	DFN-CERT-2014-1564
dfn-cert:	DFN-CERT-2014-1542
dfn-cert:	DFN-CERT-2014-1414
dfn-cert:	DFN-CERT-2014-1366
dfn-cert:	DFN-CERT-2014-1354

Medium (CVSS: 5.3)

NVT: SSL/TLS: Server Certificate / Certificate in Chain with RSA keys less than 2048 bits

Summary

The remote SSL/TLS server certificate and/or any of the certificates in the certificate chain is using a RSA key with less than 2048 bits.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

The remote SSL/TLS server is using the following certificate(s) with a RSA key with less than 2048 bits (public-key-size:public-key-algorithm:serial:issuer):
 1024:RSA:00FAF93A4C7FB6B9CC:1.2.840.113549.1.9.1=#726F6F74407562756E74753830342D
 626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office for C
 omplication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is no su
 ch thing outside US,C=XX (Server certificate)

Impact

Using certificates with weak RSA key size can lead to unauthorized exposure of sensitive information.

...continues on next page ...

...continued from previous page ...
Solution: Solution type: Mitigation Replace the certificate with a stronger key and reissue the certificates it signed.
Vulnerability Insight SSL/TLS certificates using RSA keys with less than 2048 bits are considered unsafe.
Vulnerability Detection Method Checks the RSA keys size of the server certificate and all certificates in chain for a size < 2048 bit. Details: SSL/TLS: Server Certificate / Certificate in Chain with RSA keys less than 2048. ↪... OID:1.3.6.1.4.1.25623.1.0.150710 Version used: 2021-12-10T12:48:00Z
References url: https://www.cabforum.org/wp-content/uploads/Baseline_Requirements_V1.pdf

Medium (CVSS: 5.0)
NVT: SSL/TLS: Certificate Expired
Product detection result cpe:/a:ietf:transport_layer_security Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25 ↪623.1.0.103692)
Summary The remote server's SSL/TLS certificate has already expired.
Quality of Detection (QoD): 99%
Vulnerability Detection Result The certificate of the remote service expired on 2010-04-16 14:07:45. Certificate details: fingerprint (SHA-1) ED093088706603BFD5DC237399B498DA2D4D31C6 fingerprint (SHA-256) E7A7FA0D63E457C7C4A59B38B70849C6A70BDA6F830C7A ↪F1E32DEE436DE813CC issued by 1.2.840.113549.1.9.1=#726F6F74407562756E747538 ↪30342D626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office ↪ for Complication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is ↪ no such thing outside US,C=XX public key algorithm RSA public key size (bits) 1024 serial 00FAF93A4C7FB6B9CC signature algorithm sha1WithRSAEncryption subject 1.2.840.113549.1.9.1=#726F6F74407562756E747538 ↪30342D626173652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office ↪ for Complication of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is ↪ no such thing outside US,C=XX subject alternative names (SAN) None valid from 2010-03-17 14:07:45 UTC valid until 2010-04-16 14:07:45 UTC
Solution: Solution type: Mitigation Replace the SSL/TLS certificate by a new one.
Vulnerability Insight This script checks expiry dates of certificates associated with SSL/TLS-enabled services on the target and reports whether any have already expired.
Vulnerability Detection Method Details: SSL/TLS: Certificate Expired OID:1.3.6.1.4.1.25623.1.0.103955 ...continues on next page ...

...continued from previous page ...	
Version used: 2026-03-13T05:54:58Z	
Product Detection Result Product: cpe:/a:ietf:transport_layer_security Method: SSL/TLS: Collect and Report Certificate Details OID: 1.3.6.1.4.1.25623.1.0.103692	
Medium (CVSS: 5.0)	
NVT: Check if Mailserver answer to VRFY and EXPN requests	
Summary The Mailserver on this host answers to VRFY and/or EXPN requests.	
Quality of Detection (QoD): 99%	
Vulnerability Detection Result 'VRFY root' produces the following answer: 252 2.0.0 root	
Solution: Solution type: Workaround Disable VRFY and/or EXPN on your Mailserver. For postfix add 'disable_vrfy_command=yes' in 'main.cf'. For Sendmail add the option 'O PrivacyOptions=goaway'. It is suggested that, if you really want to publish this type of information, you use a mechanism that legitimate users actually know about, such as Finger or HTTP.	
Vulnerability Insight VRFY and EXPN ask the server for information about an address. They are inherently unusable through firewalls, gateways, mail exchangers for part-time hosts, etc.	
Vulnerability Detection Method Details: Check if Mailserver answer to VRFY and EXPN requests OID: 1.3.6.1.4.1.25623.1.0.100072 Version used: 2023-10-31T05:06:37Z	
References url: http://cr.yp.to/smtp/vrfy.html	
Medium (CVSS: 5.0)	
NVT: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)	
Summary The remote SSL/TLS service is prone to a denial of service (DoS) vulnerability.	
Quality of Detection (QoD): 70%	
Vulnerability Detection Result The following indicates that the remote SSL/TLS service is affected: Protocol Version Successful re-done SSL/TLS handshakes (Renegotiation) over an ⇔ existing / already established SSL/TLS connection ----- ⇔ ----- TLSv1.0 10	
Impact The flaw might make it easier for remote attackers to cause a DoS (CPU consumption) by performing many renegotiations within a single connection.	
Solution: Solution type: VendorFix Users should contact their vendors for specific patch information. A general solution is to remove/disable renegotiation capabilities altogether from/in the affected SSL/TLS service.	
...continues on next page ...	

...continued from previous page ...
Affected Software/OS Every SSL/TLS service which does not properly restrict client-initiated renegotiation.
Vulnerability Insight The flaw exists because the remote SSL/TLS service does not properly restrict client-initiated renegotiation within the SSL and TLS protocols. Note: The referenced CVEs are affecting OpenSSL and Mozilla Network Security Services (NSS) but both are in a DISPUTED state with the following rationale: > It can also be argued that it is the responsibility of server deployments, not a security library, to prevent or limit renegotiation when it is inappropriate within a specific environment. Both CVEs are still kept in this VT as a reference to the origin of this flaw.
Vulnerability Detection Method Checks if the remote service allows to re-do the same SSL/TLS handshake (Renegotiation) over an existing / already established SSL/TLS connection. Details: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094) OID:1.3.6.1.4.1.25623.1.0.117761 Version used: 2026-03-13T05:54:58Z
References cve: CVE-2011-1473 cve: CVE-2011-5094 url: https://web.archive.org/web/20211201133213/https://orchilles.com/ssl-renegotiation-dos/ url: https://mailarchive.ietf.org/arch/msg/tls/wdg46VE_jkYBbgJ5yE4P9nQ-8IU/ url: https://vincent.bernat.ch/en/blog/2011-ssl-dos-mitigation url: https://www.openwall.com/lists/oss-security/2011/07/08/2 cert-bund: WID-SEC-2026-2904 cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2024-1591 cert-bund: WID-SEC-2024-0796 cert-bund: WID-SEC-2023-1435 cert-bund: CB-K17/0980 cert-bund: CB-K17/0979 cert-bund: CB-K14/0772 cert-bund: CB-K13/0915 cert-bund: CB-K13/0462 dfn-cert: DFN-CERT-2025-0933 dfn-cert: DFN-CERT-2017-1013 dfn-cert: DFN-CERT-2017-1012 dfn-cert: DFN-CERT-2014-0809 dfn-cert: DFN-CERT-2013-1928 dfn-cert: DFN-CERT-2012-1112

Medium (CVSS: 4.3)
NVT: SSL/TLS: RSA Temporary Key Handling 'RSA_EXPORT' Downgrade Issue (FREAK)
Product detection result cpe:/a:ietf:transport_layer_security Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0. ↪802067)
Summary This host is accepting 'RSA_EXPORT' cipher suites and is prone to a man-in-the-middle (MITM) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result 'RSA_EXPORT' cipher suites accepted by this service via the SSLv3 protocol: TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA TLS_RSA_EXPORT_WITH_DES40_CBC_SHA TLS_RSA_EXPORT_WITH_RC2_CBC_40_MD5 TLS_RSA_EXPORT_WITH_RC4_40_MD5 'RSA_EXPORT' cipher suites accepted by this service via the TLSv1.0 protocol: TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA TLS_RSA_EXPORT_WITH_DES40_CBC_SHA TLS_RSA_EXPORT_WITH_RC2_CBC_40_MD5
...continues on next page ...

...continued from previous page ...	
TLS_RSA_EXPORT_WITH_RC4_40_MD5	
Impact Successful exploitation will allow remote attacker to downgrade the security of a session to use 'RSA_EXPORT' cipher suites, which are significantly weaker than non-export cipher suites. This may allow a man-in-the-middle attacker to more easily break the encryption and monitor or tamper with the encrypted stream.	
Solution: Solution type: VendorFix - Remove support for 'RSA_EXPORT' cipher suites from the service. Please see the references for more resources supporting you with this task. - If the service is using OpenSSL: Update to version 0.9.8zd, 1.0.0p, 1.0.1k or later.	
Affected Software/OS - Hosts accepting 'RSA_EXPORT' cipher suites. - OpenSSL versions prior to 0.9.8zd, 1.0.0 prior to 1.0.0p and 1.0.1 prior to 1.0.1k.	
Vulnerability Insight Flaw is due to improper handling RSA temporary keys in a non-export RSA key exchange cipher suite.	
Vulnerability Detection Method Checks previous collected cipher suites. Details: SSL/TLS: RSA Temporary Key Handling 'RSA_EXPORT' Downgrade Issue (FREAK) OID:1.3.6.1.4.1.25623.1.0.805142 Version used: 2026-06-03T07:18:10Z	
Product Detection Result Product: cpe:/a:ietf:transport_layer_security Method: SSL/TLS: Report Supported Cipher Suites OID: 1.3.6.1.4.1.25623.1.0.802067	
References cve: CVE-2015-0204 url: https://freakattack.com url: https://openssl-library.org/news/secadv/20150108.txt url: https://web.archive.org/web/20210122095002/http://www.securityfocus.com/bid/71936 url: https://www.secpod.com/blog/freak-attack url: https://blog.cryptographyengineering.com/2015/03/03/attack-of-week-freak-or-factoring-nsa url: https://configurator.tlsref.org/ url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014 cert-bund: WID-SEC-2026-0180 cert-bund: CB-K18/0799 cert-bund: CB-K16/1289 cert-bund: CB-K16/1096 cert-bund: CB-K15/1751 cert-bund: CB-K15/1266 cert-bund: CB-K15/0850 cert-bund: CB-K15/0764 cert-bund: CB-K15/0720 cert-bund: CB-K15/0548 cert-bund: CB-K15/0526 cert-bund: CB-K15/0509 cert-bund: CB-K15/0493 cert-bund: CB-K15/0384 cert-bund: CB-K15/0365 cert-bund: CB-K15/0364 cert-bund: CB-K15/0302 cert-bund: CB-K15/0192 cert-bund: CB-K15/0016 dfn-cert: DFN-CERT-2018-1408 dfn-cert: DFN-CERT-2016-1372 dfn-cert: DFN-CERT-2016-1164	
...continues on next page ...	

dfn-cert: DFN-CERT-2016-0388	...continued from previous page ...
dfn-cert: DFN-CERT-2015-1853	
dfn-cert: DFN-CERT-2015-1332	
dfn-cert: DFN-CERT-2015-0884	
dfn-cert: DFN-CERT-2015-0800	
dfn-cert: DFN-CERT-2015-0758	
dfn-cert: DFN-CERT-2015-0567	
dfn-cert: DFN-CERT-2015-0544	
dfn-cert: DFN-CERT-2015-0530	
dfn-cert: DFN-CERT-2015-0396	
dfn-cert: DFN-CERT-2015-0375	
dfn-cert: DFN-CERT-2015-0374	
dfn-cert: DFN-CERT-2015-0305	
dfn-cert: DFN-CERT-2015-0199	
dfn-cert: DFN-CERT-2015-0021	

Medium (CVSS: 4.3)
NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection
Product detection result cpe:/a:ietf:transport_layer_security:1.0 Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)
Summary It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.
Quality of Detection (QoD): 98%
Vulnerability Detection Result The service is only providing the deprecated TLSv1.0 protocol and supports one o ↪r more ciphers. Those supported ciphers can be found in the 'SSL/TLS: Report S ↪upported Cipher Suites' (OID: 1.3.6.1.4.1.25623.1.0.802067) VT.
Impact An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection. Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.
Solution: Solution type: Mitigation It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols. Please see the references for more resources supporting you with this task.
Affected Software/OS - All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols - CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder - CVE-2024-41270: Gorush v1.18.4 - CVE-2025-3200: Multiple products from Wiesemann & Theis
Vulnerability Insight The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like: - CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST) - CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)
Vulnerability Detection Method Checks the used TLS protocols of the services provided by this system. Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection OID:1.3.6.1.4.1.25623.1.0.117274 Version used: 2026-06-03T07:18:10Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security:1.0 Method: SSL/TLS: Version Detection OID: 1.3.6.1.4.1.25623.1.0.105782
...continues on next page ...

...continued from previous page ...

References

cve: CVE-2011-3389
 cve: CVE-2015-0204
 cve: CVE-2023-41928
 cve: CVE-2024-41270
 cve: CVE-2025-3200
 url: <https://configurator.tlsref.org/>
 url: <https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html>
 url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html
 url: <https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html>
 url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html
 url: <https://web.archive.org/web/20240113175943/https://www.bettercrypto.org>
 url: <https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014>
 url: <https://datatracker.ietf.org/doc/rfc8996/>
 url: <https://vnhacker.blogspot.com/2011/09/beast.html>
 url: <https://web.archive.org/web/20201108095603/https://censys.io/blog/freak>
 url: <https://certvde.com/en/advisories/VDE-2025-031/>
 url: <https://gist.github.com/nyxfq/cfae38fada582a0f576d154belaeb1fc>
 url: <https://advisories.ncsc.nl/advisory?id=WCSC-2024-0273>
 cert-bund: WID-SEC-2026-0180
 cert-bund: WID-SEC-2023-1435
 cert-bund: CB-K18/0799
 cert-bund: CB-K16/1289
 cert-bund: CB-K16/1096
 cert-bund: CB-K15/1751
 cert-bund: CB-K15/1266
 cert-bund: CB-K15/0850
 cert-bund: CB-K15/0764
 cert-bund: CB-K15/0720
 cert-bund: CB-K15/0548
 cert-bund: CB-K15/0526
 cert-bund: CB-K15/0509
 cert-bund: CB-K15/0493
 cert-bund: CB-K15/0384
 cert-bund: CB-K15/0365
 cert-bund: CB-K15/0364
 cert-bund: CB-K15/0302
 cert-bund: CB-K15/0192
 cert-bund: CB-K15/0079
 cert-bund: CB-K15/0016
 cert-bund: CB-K14/1342
 cert-bund: CB-K14/0231
 cert-bund: CB-K13/0845
 cert-bund: CB-K13/0796
 cert-bund: CB-K13/0790
 dfn-cert: DFN-CERT-2020-0177
 dfn-cert: DFN-CERT-2020-0111
 dfn-cert: DFN-CERT-2019-0068
 dfn-cert: DFN-CERT-2018-1441
 dfn-cert: DFN-CERT-2018-1408
 dfn-cert: DFN-CERT-2016-1372
 dfn-cert: DFN-CERT-2016-1164
 dfn-cert: DFN-CERT-2016-0388
 dfn-cert: DFN-CERT-2015-1853
 dfn-cert: DFN-CERT-2015-1332
 dfn-cert: DFN-CERT-2015-0884
 dfn-cert: DFN-CERT-2015-0800
 dfn-cert: DFN-CERT-2015-0758
 dfn-cert: DFN-CERT-2015-0567
 dfn-cert: DFN-CERT-2015-0544
 dfn-cert: DFN-CERT-2015-0530
 dfn-cert: DFN-CERT-2015-0396
 dfn-cert: DFN-CERT-2015-0375
 dfn-cert: DFN-CERT-2015-0374
 dfn-cert: DFN-CERT-2015-0305
 dfn-cert: DFN-CERT-2015-0199
 dfn-cert: DFN-CERT-2015-0079
 dfn-cert: DFN-CERT-2015-0021
 dfn-cert: DFN-CERT-2014-1414

...continues on next page ...

...continued from previous page ...	
dfn-cert:	DFN-CERT-2013-1847
dfn-cert:	DFN-CERT-2013-1792
dfn-cert:	DFN-CERT-2012-1979
dfn-cert:	DFN-CERT-2012-1829
dfn-cert:	DFN-CERT-2012-1530
dfn-cert:	DFN-CERT-2012-1380
dfn-cert:	DFN-CERT-2012-1377
dfn-cert:	DFN-CERT-2012-1292
dfn-cert:	DFN-CERT-2012-1214
dfn-cert:	DFN-CERT-2012-1213
dfn-cert:	DFN-CERT-2012-1180
dfn-cert:	DFN-CERT-2012-1156
dfn-cert:	DFN-CERT-2012-1155
dfn-cert:	DFN-CERT-2012-1039
dfn-cert:	DFN-CERT-2012-0956
dfn-cert:	DFN-CERT-2012-0908
dfn-cert:	DFN-CERT-2012-0868
dfn-cert:	DFN-CERT-2012-0867
dfn-cert:	DFN-CERT-2012-0848
dfn-cert:	DFN-CERT-2012-0838
dfn-cert:	DFN-CERT-2012-0776
dfn-cert:	DFN-CERT-2012-0722
dfn-cert:	DFN-CERT-2012-0638
dfn-cert:	DFN-CERT-2012-0627
dfn-cert:	DFN-CERT-2012-0451
dfn-cert:	DFN-CERT-2012-0418
dfn-cert:	DFN-CERT-2012-0354
dfn-cert:	DFN-CERT-2012-0234
dfn-cert:	DFN-CERT-2012-0221
dfn-cert:	DFN-CERT-2012-0177
dfn-cert:	DFN-CERT-2012-0170
dfn-cert:	DFN-CERT-2012-0146
dfn-cert:	DFN-CERT-2012-0142
dfn-cert:	DFN-CERT-2012-0126
dfn-cert:	DFN-CERT-2012-0123
dfn-cert:	DFN-CERT-2012-0095
dfn-cert:	DFN-CERT-2012-0051
dfn-cert:	DFN-CERT-2012-0047
dfn-cert:	DFN-CERT-2012-0021
dfn-cert:	DFN-CERT-2011-1953
dfn-cert:	DFN-CERT-2011-1946
dfn-cert:	DFN-CERT-2011-1844
dfn-cert:	DFN-CERT-2011-1826
dfn-cert:	DFN-CERT-2011-1774
dfn-cert:	DFN-CERT-2011-1743
dfn-cert:	DFN-CERT-2011-1738
dfn-cert:	DFN-CERT-2011-1706
dfn-cert:	DFN-CERT-2011-1628
dfn-cert:	DFN-CERT-2011-1627
dfn-cert:	DFN-CERT-2011-1619
dfn-cert:	DFN-CERT-2011-1482

Medium (CVSS: 4.0)
NVT: SSL/TLS: Diffie-Hellman Key Exchange Insufficient DH Group Strength Vulnerability
Summary The SSL/TLS service uses Diffie-Hellman groups with insufficient strength (key size < 2048).
Quality of Detection (QoD): 80%
Vulnerability Detection Result Server Temporary Key Size: 1024 bits
Impact An attacker might be able to decrypt the SSL/TLS communication offline.
Solution: Solution type: Workaround
...continues on next page ...

...continued from previous page ...
- Deploy (Ephemeral) Elliptic-Curve Diffie-Hellman (ECDHE) or use a 2048-bit or stronger Diffie-Hellman group. Please see the references for more resources supporting you with this task. - For Apache Web Servers: Beginning with version 2.4.7, mod_ssl will use DH parameters which include primes with lengths of more than 1024 bits.
Affected Software/OS All services providing an encrypted communication using Diffie-Hellman groups with insufficient strength.
Vulnerability Insight The Diffie-Hellman group are some big numbers that are used as base for the DH computations. They can be, and often are, fixed. The security of the final secret depends on the size of these parameters. It was found that 512 and 768 bits to be weak, 1024 bits to be breakable by really powerful attackers like governments.
Vulnerability Detection Method Checks the DHE temporary public key size. Details: SSL/TLS: Diffie-Hellman Key Exchange Insufficient DH Group Strength Vulnerability. ↔... OID:1.3.6.1.4.1.25623.1.0.106223 Version used: 2026-06-03T07:18:10Z
References url: https://weakdh.org url: https://weakdh.org/sysadmin.html url: https://configurator.tlsref.org/ url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014 url: https://httpd.apache.org/docs/2.4/mod/mod_ssl.html#sslcertificatefile

Medium (CVSS: 4.0)
NVT: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm
Summary The remote service is using a SSL/TLS certificate in the certificate chain that has been signed using a cryptographically weak hashing algorithm.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following certificates are part of the certificate chain but using insecure ↔signature algorithms: Subject: 1.2.840.113549.1.9.1=#726F6F74407562756E74753830342D626173 ↔652E6C6F63616C646F6D61696E,CN=ubuntu804-base.localdomain,OU=Office for Complic ↔ation of Otherwise Simple Affairs,O=OCOSA,L=Everywhere,ST=There is no such thi ↔ng outside US,C=XX Signature Algorithm: sha1WithRSAEncryption
Solution: Solution type: Mitigation Servers that use SSL/TLS certificates signed with a weak SHA-1, MD5, MD4 or MD2 hashing algorithm will need to obtain new SHA-2 signed SSL/TLS certificates to avoid web browser SSL/TLS certificate warnings.
Vulnerability Insight The following hashing algorithms used for signing SSL/TLS certificates are considered cryptographically weak and not secure enough for ongoing use: - Secure Hash Algorithm 1 (SHA-1) - Message Digest 5 (MD5) - Message Digest 4 (MD4) - Message Digest 2 (MD2)
...continues on next page ...

...continued from previous page ...
Beginning as late as January 2017 and as early as June 2016, browser developers such as Microsoft and Google will begin warning users when visiting web sites that use SHA-1 signed Secure Socket Layer (SSL) certificates. NOTE: The script preference allows to set one or more custom SHA-1 fingerprints of CA certificates which are trusted by this routine. The fingerprints needs to be passed comma-separated and case-insensitive: Fingerprint1 or fingerprint1, Fingerprint2
Vulnerability Detection Method Check which hashing algorithm was used to sign the remote SSL/TLS certificate. Details: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm OID:1.3.6.1.4.1.25623.1.0.105880 Version used: 2021-10-15T11:13:32Z
References url: https://blog.mozilla.org/security/2014/09/23/phasing-out-certificates-with-sha-1-based-signature-algorithms/

[[return to 192.168.56.102](#)]

2.1.29 Medium 22/tcp

Medium (CVSS: 5.3) NVT: Weak Host Key Algorithm(s) (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↔)
Summary The remote SSH server is configured to allow / support weak host key algorithm(s).
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak host key algorithm(s): host key algorithm Description ----- ↔----- ssh-dss Digital Signature Algorithm (DSA) / Digital Signature Stand ↔ard (DSS)
Solution: Solution type: Mitigation Disable the reported weak host key algorithm(s).
Vulnerability Detection Method Checks the supported host key algorithms of the remote SSH server. Currently weak host key algorithms are defined as the following: - ssh-dss: Digital Signature Algorithm (DSA) / Digital Signature Standard (DSS) Details: Weak Host Key Algorithm(s) (SSH) OID:1.3.6.1.4.1.25623.1.0.117687 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565
References url: https://www.rfc-editor.org/rfc/rfc8332 url: https://www.rfc-editor.org/rfc/rfc8709 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.6

Medium (CVSS: 5.3)
NVT: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↔)
Summary The remote SSH server is configured to allow / support weak key exchange (KEX) algorithm(s).
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak KEX algorithm(s): KEX algorithm Reason ----- ↔----- diffie-hellman-group-exchange-sha1 Using SHA-1 diffie-hellman-group1-sha1 Using Oakley Group 2 (a 1024-bit MODP group ↔) and SHA-1
Impact An attacker can quickly break individual connections.
Solution: Solution type: Mitigation Disable the reported weak KEX algorithm(s) - 1024-bit MODP group / prime KEX algorithms: Alternatively use elliptic-curve Diffie-Hellmann in general, e.g. Curve 25519.
Vulnerability Insight - 1024-bit MODP group / prime KEX algorithms: Millions of HTTPS, SSH, and VPN servers all use the same prime numbers for Diffie-Hellman key exchange. Practitioners believed this was safe as long as new key exchange messages were generated for every connection. However, the first step in the number field sieve-the most efficient algorithm for breaking a Diffie-Hellman connection-is dependent only on this prime. A nation-state can break a 1024-bit prime.
Vulnerability Detection Method Checks the supported KEX algorithms of the remote SSH server. Currently weak KEX algorithms are defined as the following: - non-elliptic-curve Diffie-Hellmann (DH) KEX algorithms with 1024-bit MODP group / prime - ephemeral generated key exchange groups uses SHA-1 - using RSA 1024-bit modulus key Details: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH) OID:1.3.6.1.4.1.25623.1.0.150713 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565
References url: https://weakdh.org/sysadmin.html url: https://www.rfc-editor.org/rfc/rfc9142 url: https://www.rfc-editor.org/rfc/rfc9142#name-summary-guidance-for-implementations url: https://www.rfc-editor.org/rfc/rfc6194 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.5

Medium (CVSS: 4.3)
NVT: Weak Encryption Algorithm(s) Supported (SSH)
Product detection result ... continues on next page ...

...continued from previous page ...	
cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↔)	
Summary The remote SSH server is configured to allow / support weak encryption algorithm(s).	
Quality of Detection (QoD): 80%	
Vulnerability Detection Result The remote SSH server supports the following weak client-to-server encryption al gorithm(s): 3des-cbc aes128-cbc aes192-cbc aes256-cbc arcfour arcfour128 arcfour256 blowfish-cbc cast128-cbc rijndael-cbc@lysator.liu.se The remote SSH server supports the following weak server-to-client encryption al gorithm(s): 3des-cbc aes128-cbc aes192-cbc aes256-cbc arcfour arcfour128 arcfour256 blowfish-cbc cast128-cbc rijndael-cbc@lysator.liu.se	
Solution: Solution type: Mitigation Disable the reported weak encryption algorithm(s).	
Vulnerability Insight - The 'arcfour' cipher is the Arcfour stream cipher with 128-bit keys. The Arcfour cipher is believed to be compatible with the RC4 cipher [SCHNEIER]. Arcfour (and RC4) has problems with weak keys, and should not be used anymore. - The 'none' algorithm specifies that no encryption is to be done. Note that this method provides no confidentiality protection, and it is NOT RECOMMENDED to use it. - A vulnerability exists in SSH messages that employ CBC mode that may allow an attacker to recover plaintext from a block of ciphertext.	
Vulnerability Detection Method Checks the supported encryption algorithms (client-to-server and server-to-client) of the remote SSH server. Currently weak encryption algorithms are defined as the following: - Arcfour (RC4) cipher based algorithms - 'none' algorithm - CBC mode cipher based algorithms Details: Weak Encryption Algorithm(s) Supported (SSH) OID:1.3.6.1.4.1.25623.1.0.105611 Version used: 2024-06-14T05:05:48Z	
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565	
References url: https://www.rfc-editor.org/rfc/rfc8758 url: https://www.kb.cert.org/vuls/id/958563 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.3	

[return to 192.168.56.102]

2.1.30 Low 5432/tcp

Low (CVSS: 3.4)
NVT: SSL/TLS: SSLv3 Protocol CBC Cipher Suites Information Disclosure Vulnerability (POODLE)
Product detection result cpe:/a:ietf:transport_layer_security Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0. ↔802067)
Summary This host is prone to an information disclosure vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact Successful exploitation will allow a man-in-the-middle attackers gain access to the plain text data stream.
Solution: Solution type: Mitigation Possible Mitigations are: - Disable SSLv3 - Disable cipher suites supporting CBC cipher modes - Enable TLS_FALLBACK_SCSV if the service is providing TLSv1.0+
Vulnerability Insight The flaw is due to the block cipher padding not being deterministic and not covered by the Message Authentication Code
Vulnerability Detection Method Evaluate previous collected information about this service. Details: SSL/TLS: SSLv3 Protocol CBC Cipher Suites Information Disclosure Vulnerability . ↔. OID:1.3.6.1.4.1.25623.1.0.802087 Version used: 2026-03-13T05:54:58Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security Method: SSL/TLS: Report Supported Cipher Suites OID: 1.3.6.1.4.1.25623.1.0.802067
References cve: CVE-2014-3566 url: https://www.openssl.org/~bodo/ssl-poodle.pdf url: http://www.securityfocus.com/bid/70574 url: https://www.imperialviolet.org/2014/10/14/poodle.html url: https://www.dfranke.us/posts/2014-10-14-how-poodle-happened.html url: http://googleonlinesecurity.blogspot.in/2014/10/this-poodle-bites-exploiting-ssl-30.html cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2025-1658 cert-bund: WID-SEC-2023-0431 cert-bund: CB-K17/1198 cert-bund: CB-K17/1196 cert-bund: CB-K16/1828 cert-bund: CB-K16/1438 cert-bund: CB-K16/1384 cert-bund: CB-K16/1102 cert-bund: CB-K16/0599 cert-bund: CB-K16/0156 cert-bund: CB-K15/1514 cert-bund: CB-K15/1358 cert-bund: CB-K15/1021 cert-bund: CB-K15/0972 cert-bund: CB-K15/0637 cert-bund: CB-K15/0590
...continues on next page ...

...continued from previous page ...

```

cert-bund: CB-K15/0525
cert-bund: CB-K15/0393
cert-bund: CB-K15/0384
cert-bund: CB-K15/0287
cert-bund: CB-K15/0252
cert-bund: CB-K15/0246
cert-bund: CB-K15/0237
cert-bund: CB-K15/0118
cert-bund: CB-K15/0110
cert-bund: CB-K15/0108
cert-bund: CB-K15/0080
cert-bund: CB-K15/0078
cert-bund: CB-K15/0077
cert-bund: CB-K15/0075
cert-bund: CB-K14/1617
cert-bund: CB-K14/1581
cert-bund: CB-K14/1537
cert-bund: CB-K14/1479
cert-bund: CB-K14/1458
cert-bund: CB-K14/1342
cert-bund: CB-K14/1314
cert-bund: CB-K14/1313
cert-bund: CB-K14/1311
cert-bund: CB-K14/1304
cert-bund: CB-K14/1296
dfn-cert: DFN-CERT-2017-1238
dfn-cert: DFN-CERT-2017-1236
dfn-cert: DFN-CERT-2016-1929
dfn-cert: DFN-CERT-2016-1527
dfn-cert: DFN-CERT-2016-1468
dfn-cert: DFN-CERT-2016-1168
dfn-cert: DFN-CERT-2016-0884
dfn-cert: DFN-CERT-2016-0642
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2016-0171
dfn-cert: DFN-CERT-2015-1431
dfn-cert: DFN-CERT-2015-1075
dfn-cert: DFN-CERT-2015-1026
dfn-cert: DFN-CERT-2015-0664
dfn-cert: DFN-CERT-2015-0548
dfn-cert: DFN-CERT-2015-0404
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0259
dfn-cert: DFN-CERT-2015-0254
dfn-cert: DFN-CERT-2015-0245
dfn-cert: DFN-CERT-2015-0118
dfn-cert: DFN-CERT-2015-0114
dfn-cert: DFN-CERT-2015-0083
dfn-cert: DFN-CERT-2015-0082
dfn-cert: DFN-CERT-2015-0081
dfn-cert: DFN-CERT-2015-0076
dfn-cert: DFN-CERT-2014-1717
dfn-cert: DFN-CERT-2014-1680
dfn-cert: DFN-CERT-2014-1632
dfn-cert: DFN-CERT-2014-1564
dfn-cert: DFN-CERT-2014-1542
dfn-cert: DFN-CERT-2014-1414
dfn-cert: DFN-CERT-2014-1366
dfn-cert: DFN-CERT-2014-1354

```

[\[return to 192.168.56.102 \]](#)

2.1.31 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure
Summary The remote host responded to an ICMP timestamp request.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following response / ICMP packet has been received: - ICMP Type: 14 - ICMP Code: 0
Impact This information could theoretically be used to exploit weak time-based random number generators in other services.
Solution: Solution type: Mitigation Various mitigations are possible: - Disable the support for ICMP timestamp on the remote host completely - Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)
Vulnerability Insight The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.
Vulnerability Detection Method Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received. Details: ICMP Timestamp Reply Information Disclosure OID:1.3.6.1.4.1.25623.1.0.103190 Version used: 2025-01-21T05:37:33Z
References cve: CVE-1999-0524 url: https://datatracker.ietf.org/doc/html/rfc792 url: https://datatracker.ietf.org/doc/html/rfc2780 cert-bund: CB-K15/1514 cert-bund: CB-K14/0632 dfn-cert: DFN-CERT-2014-0658

[[return to 192.168.56.102](#)]

2.1.32 Low 25/tcp

Low (CVSS: 3.7)
NVT: SSL/TLS: 'DHE_EXPORT' MITM Security Bypass Vulnerability (LogJam)
Product detection result cpe:/a:ietf:transport_layer_security Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.↵802067)
Summary This host is accepting 'DHE_EXPORT' cipher suites and is prone to a man-in-the-middle (MITM) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result 'DHE_EXPORT' cipher suites accepted by this service via the SSLv3 protocol: TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA TLS_DH_anon_EXPORT_WITH_DES40_CBC_SHA TLS_DH_anon_EXPORT_WITH_RC4_40_MD5 ... continues on next page ...

...continued from previous page ...
'DHE_EXPORT' cipher suites accepted by this service via the TLSv1.0 protocol: TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA TLS_DH_anon_EXPORT_WITH_DES40_CBC_SHA TLS_DH_anon_EXPORT_WITH_RC4_40_MD5
Impact Successful exploitation will allow a man-in-the-middle attacker to downgrade the security of a TLS session to 512-bit export-grade cryptography, which is significantly weaker, allowing the attacker to more easily break the encryption and monitor or tamper with the encrypted stream.
Solution: Solution type: VendorFix - Remove support for 'DHE_EXPORT' cipher suites from the service. Please see the references for more resources supporting you with this task. - If the service is using OpenSSL: Update to version 1.0.1n, 1.0.2b or later.
Affected Software/OS - Hosts accepting 'DHE_EXPORT' cipher suites. - OpenSSL versions prior to 1.0.1n and 1.0.2 prior to 1.0.2b.
Vulnerability Insight Flaw is triggered when handling Diffie-Hellman key exchanges defined in the 'DHE_EXPORT' cipher suites.
Vulnerability Detection Method Checks previous collected cipher suites. Details: SSL/TLS: 'DHE_EXPORT' MITM Security Bypass Vulnerability (LogJam) OID:1.3.6.1.4.1.25623.1.0.805188 Version used: 2026-06-03T07:18:10Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security Method: SSL/TLS: Report Supported Cipher Suites OID: 1.3.6.1.4.1.25623.1.0.802067
References cve: CVE-2015-4000 url: https://weakdh.org url: https://weakdh.org/sysadmin.html url: https://web.archive.org/web/20210122160144/http://www.securityfocus.com/bid/74733 url: https://weakdh.org/imperfect-forward-secrecy.pdf url: https://openwall.com/lists/oss-security/2015/05/20/8 url: https://blog.cloudflare.com/logjam-the-latest-tls-vulnerability-explained url: https://openssl-library.org/post/2015-05-20-logjam-freak-upcoming-changes/index.html url: https://configurator.tlsref.org/ url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.html url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014 cert-bund: WID-SEC-2026-0180 cert-bund: CB-K21/0067 cert-bund: CB-K19/0812 cert-bund: CB-K16/1593 cert-bund: CB-K16/1552 cert-bund: CB-K16/0617 cert-bund: CB-K16/0599 cert-bund: CB-K16/0168 cert-bund: CB-K16/0121 cert-bund: CB-K16/0090 cert-bund: CB-K16/0030 cert-bund: CB-K15/1591 cert-bund: CB-K15/1550 cert-bund: CB-K15/1517 cert-bund: CB-K15/1464 cert-bund: CB-K15/1442 cert-bund: CB-K15/1334
...continues on next page ...

...continued from previous page ...	
cert-bund:	CB-K15/1269
cert-bund:	CB-K15/1136
cert-bund:	CB-K15/1090
cert-bund:	CB-K15/1059
cert-bund:	CB-K15/1022
cert-bund:	CB-K15/1015
cert-bund:	CB-K15/0964
cert-bund:	CB-K15/0932
cert-bund:	CB-K15/0927
cert-bund:	CB-K15/0926
cert-bund:	CB-K15/0907
cert-bund:	CB-K15/0901
cert-bund:	CB-K15/0896
cert-bund:	CB-K15/0877
cert-bund:	CB-K15/0834
cert-bund:	CB-K15/0802
cert-bund:	CB-K15/0733
dfn-cert:	DFN-CERT-2023-2939
dfn-cert:	DFN-CERT-2021-0775
dfn-cert:	DFN-CERT-2020-1561
dfn-cert:	DFN-CERT-2020-1276
dfn-cert:	DFN-CERT-2016-1692
dfn-cert:	DFN-CERT-2016-1648
dfn-cert:	DFN-CERT-2016-0665
dfn-cert:	DFN-CERT-2016-0642
dfn-cert:	DFN-CERT-2016-0184
dfn-cert:	DFN-CERT-2016-0135
dfn-cert:	DFN-CERT-2016-0101
dfn-cert:	DFN-CERT-2016-0035
dfn-cert:	DFN-CERT-2015-1679
dfn-cert:	DFN-CERT-2015-1632
dfn-cert:	DFN-CERT-2015-1608
dfn-cert:	DFN-CERT-2015-1542
dfn-cert:	DFN-CERT-2015-1518
dfn-cert:	DFN-CERT-2015-1406
dfn-cert:	DFN-CERT-2015-1341
dfn-cert:	DFN-CERT-2015-1194
dfn-cert:	DFN-CERT-2015-1144
dfn-cert:	DFN-CERT-2015-1113
dfn-cert:	DFN-CERT-2015-1078
dfn-cert:	DFN-CERT-2015-1067
dfn-cert:	DFN-CERT-2015-1016
dfn-cert:	DFN-CERT-2015-0980
dfn-cert:	DFN-CERT-2015-0977
dfn-cert:	DFN-CERT-2015-0976
dfn-cert:	DFN-CERT-2015-0960
dfn-cert:	DFN-CERT-2015-0956
dfn-cert:	DFN-CERT-2015-0944
dfn-cert:	DFN-CERT-2015-0925
dfn-cert:	DFN-CERT-2015-0879
dfn-cert:	DFN-CERT-2015-0844
dfn-cert:	DFN-CERT-2015-0737

Low (CVSS: 3.4)

NVT: SSL/TLS: SSLv3 Protocol CBC Cipher Suites Information Disclosure Vulnerability (POODLE)

Product detection result

cpe:/a:ietf:transport_layer_security

Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↔802067)

Summary

This host is prone to an information disclosure vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

...continues on next page ...

...continued from previous page ...
Vulnerability was detected according to the Vulnerability Detection Method.
Impact Successful exploitation will allow a man-in-the-middle attackers gain access to the plain text data stream.
Solution: Solution type: Mitigation Possible Mitigations are: - Disable SSLv3 - Disable cipher suites supporting CBC cipher modes - Enable TLS_FALLBACK_SCSV if the service is providing TLSv1.0+
Vulnerability Insight The flaw is due to the block cipher padding not being deterministic and not covered by the Message Authentication Code
Vulnerability Detection Method Evaluate previous collected information about this service. Details: SSL/TLS: SSLv3 Protocol CBC Cipher Suites Information Disclosure Vulnerability . ↩→.. OID:1.3.6.1.4.1.25623.1.0.802087 Version used: 2026-03-13T05:54:58Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security Method: SSL/TLS: Report Supported Cipher Suites OID: 1.3.6.1.4.1.25623.1.0.802067
References cve: CVE-2014-3566 url: https://www.openssl.org/~bodo/ssl-poodle.pdf url: http://www.securityfocus.com/bid/70574 url: https://www.imperialviolet.org/2014/10/14/poodle.html url: https://www.dfranke.us/posts/2014-10-14-how-poodle-happened.html url: http://googleonlinesecurity.blogspot.in/2014/10/this-poodle-bites-exploiting-ssl-30.html cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2025-1658 cert-bund: WID-SEC-2023-0431 cert-bund: CB-K17/1198 cert-bund: CB-K17/1196 cert-bund: CB-K16/1828 cert-bund: CB-K16/1438 cert-bund: CB-K16/1384 cert-bund: CB-K16/1102 cert-bund: CB-K16/0599 cert-bund: CB-K16/0156 cert-bund: CB-K15/1514 cert-bund: CB-K15/1358 cert-bund: CB-K15/1021 cert-bund: CB-K15/0972 cert-bund: CB-K15/0637 cert-bund: CB-K15/0590 cert-bund: CB-K15/0525 cert-bund: CB-K15/0393 cert-bund: CB-K15/0384 cert-bund: CB-K15/0287 cert-bund: CB-K15/0252 cert-bund: CB-K15/0246 cert-bund: CB-K15/0237 cert-bund: CB-K15/0118 cert-bund: CB-K15/0110 cert-bund: CB-K15/0108 cert-bund: CB-K15/0080 cert-bund: CB-K15/0078 cert-bund: CB-K15/0077 cert-bund: CB-K15/0075 cert-bund: CB-K14/1617 cert-bund: CB-K14/1581 cert-bund: CB-K14/1537 cert-bund: CB-K14/1479 cert-bund: CB-K14/1458
...continues on next page ...

...continued from previous page ...	
cert-bund:	CB-K14/1342
cert-bund:	CB-K14/1314
cert-bund:	CB-K14/1313
cert-bund:	CB-K14/1311
cert-bund:	CB-K14/1304
cert-bund:	CB-K14/1296
dfn-cert:	DFN-CERT-2017-1238
dfn-cert:	DFN-CERT-2017-1236
dfn-cert:	DFN-CERT-2016-1929
dfn-cert:	DFN-CERT-2016-1527
dfn-cert:	DFN-CERT-2016-1468
dfn-cert:	DFN-CERT-2016-1168
dfn-cert:	DFN-CERT-2016-0884
dfn-cert:	DFN-CERT-2016-0642
dfn-cert:	DFN-CERT-2016-0388
dfn-cert:	DFN-CERT-2016-0171
dfn-cert:	DFN-CERT-2015-1431
dfn-cert:	DFN-CERT-2015-1075
dfn-cert:	DFN-CERT-2015-1026
dfn-cert:	DFN-CERT-2015-0664
dfn-cert:	DFN-CERT-2015-0548
dfn-cert:	DFN-CERT-2015-0404
dfn-cert:	DFN-CERT-2015-0396
dfn-cert:	DFN-CERT-2015-0259
dfn-cert:	DFN-CERT-2015-0254
dfn-cert:	DFN-CERT-2015-0245
dfn-cert:	DFN-CERT-2015-0118
dfn-cert:	DFN-CERT-2015-0114
dfn-cert:	DFN-CERT-2015-0083
dfn-cert:	DFN-CERT-2015-0082
dfn-cert:	DFN-CERT-2015-0081
dfn-cert:	DFN-CERT-2015-0076
dfn-cert:	DFN-CERT-2014-1717
dfn-cert:	DFN-CERT-2014-1680
dfn-cert:	DFN-CERT-2014-1632
dfn-cert:	DFN-CERT-2014-1564
dfn-cert:	DFN-CERT-2014-1542
dfn-cert:	DFN-CERT-2014-1414
dfn-cert:	DFN-CERT-2014-1366
dfn-cert:	DFN-CERT-2014-1354

[[return to 192.168.56.102](#)]

2.1.33 Low 22/tcp

Low (CVSS: 2.6)	
NVT: Weak MAC Algorithm(s) Supported (SSH)	
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↔)	
Summary The remote SSH server is configured to allow / support weak MAC algorithm(s).	
Quality of Detection (QoD): 80%	
Vulnerability Detection Result The remote SSH server supports the following weak client-to-server MAC algorithm ↔(s): hmac-md5 hmac-md5-96 hmac-sha1-96 umac-64@openssh.com	
...continues on next page ...	

...continued from previous page ...
The remote SSH server supports the following weak server-to-client MAC algorithm <pre>↔(s): hmac-md5 hmac-md5-96 hmac-sha1-96 umac-64@openssh.com</pre>
Solution: Solution type: Mitigation Disable the reported weak MAC algorithm(s).
Vulnerability Detection Method Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server. Currently weak MAC algorithms are defined as the following: - MD5 based algorithms - 96-bit based algorithms - 64-bit based algorithms - 'none' algorithm Details: Weak MAC Algorithm(s) Supported (SSH) OID:1.3.6.1.4.1.25623.1.0.105610 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565
References url: https://www.rfc-editor.org/rfc/rfc6668 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.4

[[return to 192.168.56.102](#)]

2.1.34 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 337716 Packet 2: 337820
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS ...continues on next page ...

...continued from previous page ...	
TCP implementations that implement RFC1323/RFC7323.	
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.	
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z	
References url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152 url: https://www.fortiguard.com/psirt/FG-IR-16-090	

[[return to 192.168.56.102](#)]