

7. Stored Procedures or Function with Cursors

Create and execute stored procedures / function using cursors.

```
mysql> CREATE TABLE Emp1 (emp_id int,emp_name VARCHAR(50),salary int);
```

Query OK, 0 rows affected (0.02 sec)

```
mysql> INSERT INTO Emp1 VALUES (1, 'Ram', 50000);
```

Query OK, 1 row affected (0.01 sec)

```
mysql> INSERT INTO Emp1 VALUES (2, 'Sham', 60000);
```

Query OK, 1 row affected (0.01 sec)

```
mysql> INSERT INTO Emp1 VALUES (3, 'Tom', 55000);
```

Query OK, 1 row affected (0.01 sec)

```
mysql> DELIMITER //
```

```
mysql> DROP PROCEDURE IF EXISTS show_employee_details //
```

Query OK, 0 rows affected, 1 warning (0.01 sec)

```
mysql> CREATE PROCEDURE show_employee_details()
```

```
-> BEGIN
```

```
-> DECLARE done INT DEFAULT 0;
```

```
-> DECLARE v_id INT;
```

```
-> DECLARE v_name VARCHAR(20);
```

```
-> DECLARE v_salary INT;
```

```
-> DECLARE emp_cursor CURSOR FOR
```

```
-> SELECT emp_id,emp_name,salary from Emp1;
```

```
-> DECLARE CONTINUE HANDLER FOR NOT FOUND SET done = 1;
```

```
-> OPEN emp_cursor;
```

```
-> read_loop: LOOP
```

```
-> FETCH emp_cursor INTO v_id, v_name, v_salary;
```

```
-> IF done = 1 THEN
```

```
-> LEAVE read_loop;
```

```
->     END IF;
->     SELECT v_id,v_name, v_salary;
->     END LOOP;
->     CLOSE emp_cursor;
-> END //
```

Query OK, 0 rows affected (0.02 sec)

```
mysql> DELIMITER ;
```

```
mysql> call show_employee_details();
```

```
+-----+-----+-----+
| v_id | v_name | v_salary |
+-----+-----+-----+
|  1  | Ram   |  50000  |
+-----+-----+-----+
```

1 row in set (0.01 sec)

```
+-----+-----+-----+
| v_id | v_name | v_salary |
+-----+-----+-----+
|  2  | Sham  |  60000  |
+-----+-----+-----+
```

1 row in set (0.03 sec)

```
+-----+-----+-----+
| v_id | v_name | v_salary |
+-----+-----+-----+
|  3  | Tom   |  55000  |
+-----+-----+-----+
```

1 row in set (0.07 sec)

Query OK, 0 rows affected (0.12 sec)