

## EQUIPMENT

## CATEGORIES

[Autoclaves](#)

**[Balances](#)**

[Bio Safety](#)

[Block Trimmer](#)

[Cell Washers](#)

[Centrifuges](#)

[CO<sub>2</sub> Incubators](#)

[Cooling & Stretching](#)

[Cryostats](#)

[Embedding Centres](#)

[Freezers](#)

[Freezers -20 to -40](#)

[Freezers -85](#)

[Fridge/Freezer Combo](#)

[Fume Hoods](#)

[Heated Forceps](#)

[Hotplates](#)

[Incubators](#)

[Microscopes](#)

[Microtomes](#)

[Ovens](#)

[Paraffin Dispensers](#)

[Printers Cassette/Slide](#)

[Refrigerators](#)

[Shakers](#)

[Slide Drying](#)

[Slide Incubation](#)

[Slide Stainers](#)

[SpeedVac](#)

[Sterilizers](#)

[Storage](#)

[Thermometers](#)

[Tissue Baths](#)

[Tissue Processors](#)

[Transfusion Equipment](#)

[Washers](#)

[Water Baths](#)

[Water Purification](#)

### A&D FX-120I - 122g x 0.001g Precision Balance



The A&D FX-120I is the best value, precision scale on the market. Featuring a patented Compact Super Hybrid Sensor at its heart, providing fast, one-second weighing response time. Fx-120i also contains a specially designed internal shock absorber that offers protection from the adverse effects of vertical or transverse overloading. Durable and reliable, the FX-120i is an entry level, full-featured 0.01g to 1mg resolution balance at a very affordable price.

A&D offers a patented Compact Super Hybrid Sensor - the heart of the balance. It allows the balance to provide fast, one-second response time with precise readouts. It also contains a specially designed shock absorber, that offers internal protection to the sensors which protects it from accidental overloading.

#### Features:

- External Calibration - 50g or 100g weight required to calibrate. (Not Included.)
- Capacity: 122g
- Readability: 0.001g
- 5 Year Warranty

Capacity	122g
Readability	122g
Repeatability	0.001g
Linearity	±0.002g
Calibration	External (100g / 50g)
Stablization Time	~1s
Weighing Pan Dimensions	130mm / 5.1in
Product Dimensions	193 x 262.5 x 84.5mm / 7.6 x 10.3 x 3.3in
Applications	Counting with Automatic Counting Accuracy Improvement (ACAI), Percent, Animal weighing with display hold, Statistical calculation function, Comparator function with buzzer
Weighing Units	g, oz, lb, lb-oz, ozt, ct, mom, dwt, grain
Connectivity	RS-232C interface, Quick USB interface (optional), LAN – Ethernet interface with WinCT-Plus software (optional)
Warranty	5 Years

## CONTACT US

Your Name\*

Your Email\*

Your Message



Contact

REQUEST  
A QUOTE