


EQUIPMENT

CATEGORIES



- Autoclaves
- Balances
- Bio Safety
- Block Trimmer
- Cell Washers
- Centrifuges
- CO₂ Incubators
- Cooling & Stretching
- Cryostats
- Embedding Centres
- Freezers
- Freezers -20 to -40
- Freezers -85
- Fridge/Freezer Combo
- Fume Hoods
- Heated Forceps
- Hotplates
- Incubators
- Microscopes
- Microtomes
- Ovens
- Paraffin Dispensers
- Printers Cassette/Slide
- Refrigerators
- Shakers
- Slide Drying
- Slide Incubation
- Slide Stainers
- SpeedVac
- Sterilizers
- Storage
- Thermometers
- Tissue Baths
- Tissue Processors
- Transfusion Equipment
- Washers
- Water Baths
- Water Purification

A&D FX-120I - 122g x 0.001g Precision Balance



The A&D FX-120I is the best value, precision scale on the market. Featuring a patented Compact Super Hybrid Sensor at its heart, providing fast, one-second weighing response time. Fx-120i also contains a specially designed internal shock absorber that offers protection from the adverse effects of vertical or transverse overloading. Durable and reliable, the FX-120i is an entry level, full-featured 0.01g to 1mg resolution balance at a very affordable price.

A&D offers a patented Compact Super Hybrid Sensor - the heart of the balance. It allows the balance to provide fast, one-second response time with precise readouts. It also contains a specially designed shock absorber, that offers internal protection to the sensors which protects it from accidental overloading.

Features:

- External Calibration - 50g or 100g weight required to calibrate. (Not Included.)
- Capacity: 122g
- Readability: 0.001g
- 5 Year Warranty

Capacity	122g
Readability	122g
Repeatability	0.001g
Linearity	±0.002g
Calibration	External (100g / 50g)
Stablization Time	~1s
Weighing Pan Dimensions	130mm / 5.1in
Product Dimensions	193 x 262.5 x 84.5mm / 7.6 x 10.3 x 3.3in
Applications	Counting with Automatic Counting Accuracy Improvement (ACAI), Percent, Animal weighing with display hold, Statistical calculation function, Comparator function with buzzer
Weighing Units	g, oz, lb, lb-oz, ozt, ct, mom, dwt, grain
Connectivity	RS-232C interface, Quick USB interface (optional), LAN – Ethernet interface with WinCT-Plus software (optional)
Warranty	5 Years

CONTACT US

Your Name*


Your Email*

Your Message

☐ I'm not a robot

Contact

REQUEST A QUOTE



Stay up to date!



Home

Service

Equipment

Consumables

Contact