2. Messages from TigerTMS to PMS

The PMS interface should make available via a soap URL the following method call which takes a string parameter, and returns a string parameter – “SUCCESS” or “FAILED” .
If “FAILED” is returned please extend the response with a failure reason for logging purposes. Eg. “FAILED – Invalid room number.”

String **SendMessageToExternalInterface (**string **Msg)** **-** General single input method.

A simple C# Example of the required WebMethod is as follows:

```
namespace InterfaceMessageOut
{
    /// <summary>
    /// Summary description for Service1
    /// </summary>
    [WebService(Namespace = "http://CONNECTED GUESTSgenericinterface.org/")]
    [WebServiceBinding(ConformsTo = WsiProfiles.BasicProfile1_1)]
    [System.ComponentModel.ToolboxItem(false)]
    // To allow this Web Service to be called from script, using ASP.NET AJAX, uncomment the
following line.
    // [System.Web.Script.Services.ScriptService]
    public class InterfaceMessageOut : System.Web.Services.WebService
    {
        public string SendMessageToExternalInterface(string Msg)
        {
            string Response = "SUCCESS";
return Response;
        }

}

}
```

Due to the fact that the WEB API is constantly evolving, please successfully acknowledge any messages which you do not implement in order for the communication to continue without any timeouts/retransmission attempts.

The following types of messages will be sent to the PMS system

Charge Records: Different Types – CallRecord, Internet , Minibar and Video
Room Status
Wakeup Answer Status
Request Bill
Request Checkout
Request Refresh
Voicemail

1. CALL RECORD: *chargerecord Type - callrecord*

```
<?xml version="1.0" encoding="utf-8"?>
<!--Reservation Number-->
<chargerecord resno="" type="callrecord">  resno sent but always blank, for future use
    <!--Site -->
    <site>HotelX</site>
    <!--Room number -->
    <room>100</room>
    <!--Date time of call -->
    <datetime>06/04/2010 09:00:03</datetime>
    <!--Dialled -->
    <dialled>01202387678</dialled>
    <!--Duration-->
    <duration>00:23:12</duration>
    <!--Call Type O = OUTGOING I = incoming String-->
    <calltype>O</calltype>
    <!--Call Charge major . minor currency String-->
    <charge>9.12</charge>
    <!--Call Category    F= Free, L = Local, N = National, I = International, M = Mobile>
    <callcategory>N</callcategory>

    <!--Additional User Defined Fields as required 0-19❼
<userdefine0>1234</userdefine0>

    <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE IN/OUT)-->
    <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</chargerecord>
```

If xml nodes are not used by the interfacing system eg. userdefine0 then TigerTMS will still pass the values but as a blank string eg. <userdefine0></userdefine0> or will not supply the nodes, the external interface should cater for either scenario.

The wsuserkey is a unique key used to identify the system, this should be configurable at the interfacing system

2. INTERNET CHARGE: *chargerecord Type - internet*

```
<?xml version="1.0" encoding="utf-8"?>
<!--Reservation Number-->
<chargerecord resno="" type="internet"> resno sent but always blank, for future use      <!--
Site -->
    <site>HotelX</site>
    <!--Room number -->
    <room>100</room>
    <!--Date time of charge -->
    <datetime>06/04/2010 09:30:03</datetime>
    <!--Charge major . minor currency String-->
    <charge>10.50</charge>
```

```
        <!--Additional User Defined Fields as required 0-19❼
<userdefine0>1234</userdefine0>

        <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE IN/OUT)-->
        <wsuserkey>Abc249PPP6pppk14</wsuserkey>
    </chargerecord>
```


3. MINIBAR CHARGE: *chargerecord Type - minibar*


```
    <?xml version="1.0" encoding="utf-8"?>
    <!--Reservation Number-->
    <chargerecord resno="" type="minibar"> resno sent but always blank, for future use
        <!--Site -->
         <site>HotelX</site>
        <!--Room number -->
         <room>100</room>
        <!--Date time of charge -->
         <datetime>06/04/2010 09:45:03</datetime>
        <!—Charge major . minor currency String-->
         <charge>3.25</charge>
        <!--Item ID-->
         <itemid>12</itemid>
        <!--Item description-->
         <itemdescription>Orange Juice</itemdescription>
        <!--Item quantity-->
         <itemquantity>1</itemquantity>

        <!--Additional User Defined Fields as required 0-19❼
<userdefine0>1234</userdefine0>

        <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE IN/OUT)-->
        <wsuserkey>Abc249PPP6pppk14</wsuserkey>
    </chargerecord>
```


4. VIDEO CHARGE: *chargerecord Type - video*


```
    <?xml version="1.0" encoding="utf-8"?>
    <!--Reservation Number-->
    <chargerecord resno="" type="video"> resno sent but always blank, for future use
        <!--Site -->
         <site>HotelX</site>
        <!--Room number -->
         <room>100</room>
        <!--Date time of charge -->
```

```
 <datetime>06/04/2010 09:45:03</datetime>
<!--Charge major . minor currency String-->
 <charge>10.00</charge>
<!—item description-->
 <itemdescription>Video Package 10</itemdescription>

<!--Additional User Defined Fields as required 0-19❼
<userdefine0>1234</userdefine0>

<!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE IN/OUT)-->
<wsuserkey>Abc249PPP6pppk14</wsuserkey>
</chargerecord>
```

5. DIRECT CHARGE: *chargerecord Type - direct*

Used to post sundry items – this could include credits i.e. negative charges.

```
<?xml version="1.0" encoding="utf-8"?>
<!--Reservation Number-->
<chargerecord resno="" type="direct"> resno sent but always blank, for future use      <!--
Site -->
     <site>HotelX</site>
    <!--Room number -->
     <room>100</room>
    <!--Date time of charge -->
     <datetime>06/04/2010 09:45:03</datetime>
    <!--Charge major . minor currency String-->
     <charge>15.00</charge>
    <!—item description-->
     <itemdescription>Laundry</itemdescription>
    <!—Posting Account>
     <postingaccount>023</postingaccount>

    <!--Additional User Defined Fields as required 0-19❼
<userdefine0>1234</userdefine0>

    <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE IN/OUT)-->
    <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</chargerecord>
```

6. ROOM STATUS: *Message - roomstatusresults*

```
<?xml version="1.0" encoding="utf-8"?>
<!--reservation number-->
<roomstatusresults resno=""> resno sent but always blank, for future use
     <!--Site -->
     <site>HotelX</site>
     <!--Room Number -->
     <room>101</room>
     <!--Status -->
     <status>1</status>
     <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE
     IN/OUT)-->
     <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</roomstatusresults>
```

Note : Status values are as follows:

1 – Dirty/Vacant
2 – Dirty/Occupied
3 – Clean/Vacant
4 – Clean/Occupied
5 – Inspected/Vacant
6 – Inspected/Occupied
7 – MakeMyRoom

7. WAKEUP STATUS *Message - wakeupstatusresults*

```
<?xml version="1.0" encoding="utf-8"?>
<!--reservation number-->
<wakeupstatusresults resno=""> resno sent but always blank, for future use
    <!--Site -->
    <site>HotelX</site>
    <!--Room Number -->
    <room>101</room>
    <wakeupdate>07/04/2010</wakeupdate>
    <!--Wakeup Time -->
    <wakeuptime>07:30:00</wakeuptime>
    <!--Status -->
    <status>BY</status>
    <!--Info -->
    <info>Extension Busy</info>
    <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE
    IN/OUT)-->
    <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</rwakeupstatusresults>
```

Note : Status values are as follows:

OK – Wakeup was answered.
BY – Wakeup was Busy
NR – Wakeup was unanswered (No Response)

8. BILL REQUEST : *Message - requestbill*

```
<?xml version="1.0" encoding="utf-8"?>
<!--reservation number-->
< requestbill resno="1000TD">
    <!--Site -->
    <site>HotelX</site>
    <!--Room Number -->
    <room>101</room>
    <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE
    IN/OUT)-->
```

```
        <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</requestbill >
```

9. EXPRESS CHECKOUT: *Message - requestcheckout*

```
<?xml version="1.0" encoding="utf-8"?>
<!--reservation number-->
< requestcheckout resno="1000TD">
      <!--Site -->
      <site>HotelX</site>
      <!--Room Number -->
      <room>101</room>
      <!--Balance Amount  major . minor currency string -->
      <balance>138.50</balance>
      <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE
      IN/OUT)-->
      <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</ requestcheckout >
```

10. REQUEST REFRESH: *Message - requestrefresh*

Either a single room or a full refresh can be requested. Individual messages to be returned.

```
<?xml version="1.0" encoding="utf-8"?>
<requestrefresh>
      <!--Site -->
      <site>HotelX</site>
      <!--Room Number -->
      <room>101</room>
      <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE
      IN/OUT)-->
      <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</requestrefresh>
```

```
<?xml version="1.0" encoding="utf-8"?>
<requestrefresh>
      <!--Site -->
      <site>HotelX</site>
      <!--Room Number -->
      <room>ALL</room>
```

```
        <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE
        IN/OUT)-->
        <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</requestrefresh>
```


11. VOICEMAIL: *Message - voicemailresults*


```
<?xml version="1.0" encoding="utf-8"?>
<!--reservation number-->
< voicemailresults  resno=""> resno sent but always blank, for future use
      <!--Site -->
       <site>HotelX</site>
      <!--Room Number -->
      <room>101</room>
      <!—Voicemail Messages -->
      < voicemsgs >True</ voicemsgs >
      <!—message count -->
      <messagecount>1</messagecount>
      <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE IN/OUT)-
      ->
      <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</ voicemailresults >
```


Note :

voicemsgs will be set true if there are any voicemail messages indicated by the external voicemail system. Message count may or may not be available depending upon the external voicemail system used. If message count it is not available the field will be empty.

12. TEXT REQUEST *Message - requestmessagetext*

```
<?xml version="1.0" encoding="utf-8"?>
<!--reservation number-->
< requestmessagetext resno="1000TD">
    <!--Site -->
    <site>HotelX</site>
    <!—Room Number -->
    <room>101</room>
    <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE
    IN/OUT)-->
    <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</requestmessagetext >
```

13. TEXT DELETE *Message - deletemessagetext*

```
<?xml version="1.0" encoding="utf-8"?>
<!--reservation number-->
< deletemessagetext resno="1000TD">
    <!--Site -->
    <site>HotelX</site>
    <!—Room Number -->
    <room>101</room>
    <!—Message ID -->
    <msgid>903</msgid>
    <!--Valid Message Key String (SUPPLIED BY TIGERTMS TO VALIDATE THE MESSAGE
    IN/OUT)-->
    <wsuserkey>Abc249PPP6pppk14</wsuserkey>
</deletemessagetext >
```